FCC RF Exposure Evaluation

FOR

ASIS TECHNOLOGIES PTE LTD

R502 Reader

Test Model: R502

Additional Model No.: R501, R503, R504

Prepared for	:	ASIS TECHNOLOGIES PTE LTD
Address	:	71 Ubi Crescent #08-05 Excalibur Centre Singapore 408571
Prepared by	:	Shenzhen LCS Compliance Testing Laboratory Ltd.
Address	:	101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China
Tel	:	(+86)755-82591330
Fax	:	(+86)755-82591332
Web	:	www.LCS-cert.com
Mail	:	webmaster@LCS-cert.com

Date of receipt of test sample	:	February 12, 2025
Number of tested samples	:	2
Sample No.	:	A250116073-1, A250116073-2
Serial number	:	Prototype
Date of Test	:	February 12, 2025 ~ February 24, 2025
Date of Report	:	February 25, 2025

RF Exposure Evaluation

Report Reference No. ..... :	**LCSA02115044EB**
Date of Issue ..... :	February 25, 2025
Testing Laboratory Name..... :	**Shenzhen LCS Compliance Testing Laboratory Ltd.**
Address ..... :	101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China
Testing Location/ Procedure ..... :	Full application of Harmonised standards ■ Partial application of Harmonised standards □ Other standard testing method □
Applicant's Name ..... :	**ASIS TECHNOLOGIES PTE LTD**
Address ..... :	71 Ubi Crescent #08-05 Excalibur Centre Singapore 408571
Test Specification	
Standard..... :	CFR 47§1.1310 CFR 47§2.1091 KDB447498 D01 General RF Exposure Guidance v06
Test Report Form No. ..... :	TRF-4-E-148 A/0
TRF Originator ..... :	Shenzhen LCS Compliance Testing Laboratory Ltd.
Master TRF ..... :	Dated 2011-03

Shenzhen LCS Compliance Testing Laboratory Ltd. All rights reserved.
This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen LCS Compliance Testing Laboratory Ltd. is acknowledged as copyright owner and source of the material. Shenzhen LCS Compliance Testing Laboratory Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

Test Item Description. ..... :	**R502 Reader**
Trade Mark..... :	WebENTRA
Test Model ..... :	R502
Ratings ..... :	DC 12V
Result ..... :	Positive

Compiled by:	**Supervised by:**	**Approved by:**
Nadia Zhou	Jack Liu	Gavin Liang
Nadia Zhou/ Administrator	Jack Liu/ Technique principal	Gavin Liang/ Manager

FCC -- TEST REPORT

Test Report No. : **LCSA02115044EB**	February 25, 2025 Date of issue

Test Model.....	: R502
EUT.....	: R502 Reader
Applicant.....	**: ASIS TECHNOLOGIES PTE LTD**
Address.....	: 71 Ubi Crescent #08-05 Excalibur Centre Singapore 408571
Telephone.....	: /
Fax.....	: /
Manufacturer.....	**: ASIS TECHNOLOGIES PTE LTD**
Address.....	: 71 Ubi Crescent #08-05 Excalibur Centre Singapore 408571
Telephone.....	: /
Fax.....	: /
Factory.....	: **ASIS TECHNOLOGIES PTE LTD**
Address.....	: 71 Ubi Crescent #08-05 Excalibur Centre Singapore 408571
Telephone.....	: /
Fax.....	: /

Test Result	**Positive**

The test report merely corresponds to the test sample.
It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

Revision History

Report Version	Issue Date	Revision Content	Revised By
000	February 25, 2025	Initial Issue	---

TABLE OF CONTENTS

Description **Page**

1. Product Information 6
2. Evaluation method and Limit..... 6
3. Limit..... 6
4. MPE Calculation Method 7
5.Measurement Uncertainty..... 7
6. Conducted Power 8
7. Conclusion..... 8
8. Description of Test Facility..... 8

1. Product Information

Product name	R502 Reader
Test Model	R502
Additional Model No.	R501, R503, R504
Model Declaration	Only the appearance is different (form), the structure, circuit scheme (principle, PCB) are the same, So no additional models were tested.
Ratings	DC 12V
Hardware Version	/
Software Version	/
NFC	
Operating Frequency	13.56MHz
Modulation Type	ASK
Antenna Description	Loop antenna, 0dBi(Max.)
Exposure category	General population/uncontrolled environment
EUT Type	Production Unit
Device Type	Mobile Devices

2. Evaluation method and Limit

Systems operating under the provisions of FCC 47 CFR section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.
In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as mobile device whereby a distance of 0.2m normally can be maintained between the user and the device, and below RF Permissible Exposure limit shall comply with.
In accordance with KDB447498D01 for Simultaneous transmission MPE test exclusion applies when the sum of the MPE ratios for all simultaneous transmitting antennas incorporated in a host device, based on the calculated/estimated, numerically modelled or measured field strengths or power density, is ≤ 1.0. The MPE ratio of each antenna is determined at the minimum test separation distance required by the operating configurations and exposure conditions of the host device, according to the ratio of field strengths or power density to MPE limit, at the test frequency. Either the maximum peak or spatially averaged results from measurements or numerical simulations may be used to determine the MPE ratios. Spatial averaging does not apply when MPE is estimated using simple calculations based on far-field plane-wave equivalent conditions. The antenna installation and operating requirements for the host device must meet the minimum test separation distances required by all antennas, in both standalone and simultaneous transmission operations, to satisfy compliance.

3. Limit

3. 1 Refer Evaluation Method

ANSI C95.1–2019: IEEE Standard for Safety Levels with Respect to Human Exposure to Electric, Magnetic, and Electromagnetic Fields, 0 Hz to 300 GHz
FCC KDB publication 447498 D01 General 1 RF Exposure Guidance v06: Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies.

FCC CFR 47 part1 1.1310: Radiofrequency radiation exposure limits.
FCC CFR 47 part2 2.1091: Radiofrequency radiation exposure evaluation: mobile devices.

3. 2 Limit

Limits for Maximum Permissible Exposure (MPE)/Controlled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm²)	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	(100) *	6
3.0 – 30	1842/f	4.89/f	$(900/f^2)$*	6
30 – 300	61.4	0.163	1.0	6
300 – 1500	/	/	f/300	6
1500 – 100,000	/	/	5	6

Limits for Maximum Permissible Exposure (MPE)/Uncontrolled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm²)	Averaging Time (minute)
Limits for Occupational/Uncontrolled Exposure				
0.3 – 3.0	614	1.63	(100) *	30
3.0 – 30	824/f	2.19/f	$(180/f^2)$*	30
30 – 300	27.5	0.073	0.2	30
300 – 1500	/	/	f/1500	30
1500 – 100,000	/	/	1.0	30

F=frequency in MHz
*=Plane-wave equivalent power density

4. MPE Calculation Method

Predication of MPE limit at a given distance
Equation from page 18 of OET Bulletin 65, Edition 97-01

$S=PG/4\pi R^2$

Where: S=power density
P=power input to antenna
G=power gain of the antenna in the direction of interest relative to an isotropic radiator
R=distance to the center of radiation of the antenna

5.Measurement Uncertainty

Test Item		Frequency Range	Uncertainty	Note
Radiation Uncertainty	:	9KHz~30MHz	±3.10dB	(1)
		30MHz~200MHz	±2.96dB	(1)
		200MHz~1000MHz	±3.10dB	(1)
		1GHz~26.5GHz	±3.80dB	(1)
		26.5GHz~40GHz	±3.90dB	(1)

(1) This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

6. Conducted Power

Test Procedure

TX frequency range: 13.56MHz, Limit: 824/13.56=60.77V/m
Device category: Mobile device (Distance: 20cm)
Max. Field Strength: 29.96dBuV/m @3m
@20cm=@3m+40*log(3/0.2)=77.00dBuV/m
For 13.56MHz: 77.00dBuV/m=10^(77.00/20)/10^6=0.0071V/m< 60.77V/m

Note: In the report, evaluation/test results are only relevant to the sample being tested.

7. Conclusion

The measurement results comply with the FCC Limit per 47 CFR 2.1091 for the uncontrolled RF Exposure of mobile device.

8. Description of Test Facility

NVLAP Accreditation Code is 600167-0.
FCC Designation Number is CN5024.
CAB identifier is CN0071.
CNAS Registration Number is L4595.
Test Firm Registration Number: 254912.

.....THE END OF REPORT.....