

APPROVAL SHEET

(RoHS)

CUSTOMER : Laird

**CUSTOMER'S
PART NO.** :

DESCRIPTION : RF ANTENNA ASSEMBLY

PART NO. : EDA-8709-2G4C1-B27-CY

DATE :

AUTHORIZED BY : *Marco Hsu*

	FULLY APPROVED	PARTIALLY APPROVED	REJECTED
SIGN			
SUGGESTION			

美磊科技股份有限公司

MAG. LAYERS SCIENTIFIC-TECHNICS CO., LTD
HEAD OFFICE / HSINCHU PLANT

No 18, Tz-Chiang Road, Hsin-Chu Industrial Park, Hsin-Chu, Taiwan

TEL: +886-3-5972488 FAX: +886-3-5972477

<http://www.maglayers.com.tw>

E-mail : info@maglayers.com.tw



MAG.LAYERS

EDA-8709-2G4C1-B27_V01 Dec. 2012

Contents

Item	Description	Page
1.	Antenna Specification	3
2.	Mechanical Specification	4
3.	Test Report	5~9

RF Antenna Assembly Specification

ELECTRICAL PROPERTIES

- 1.1 Frequency Range..... 2.4GHz ~2.5GHz**
- 1.2 Impedance..... 50 Ohm Nominal**
- 1.3 VSWR..... 2 (Max)**
- 1.4 Return Loss..... -10dB (Max)**
- 1.5 Radiation..... Omni-directional (Only Antenna)**
- 1.6 Gain(peak)..... 2.32dBi (Only Antenna)**
- 1.7 Cable Loss..... 0.7dB**
- 1.8 Polarization..... Linear Vertical**
- 1.9 Admitted Power..... 1W**

PHYSICAL PROPERTIES

- 2.1 Cable..... § 1.13 Black**
- 2.2 Antenna Cover..... TPEE**
- 2.3 Antenna Base..... PC/PBT**
- 2.4 Operating Temp.....-25℃ ~ +75℃**
- 2.5 Storage Temp.....-30℃ ~ +75℃**
- 2.6 Color..... Black**
- 2.7 Connector..... IPEX Compatible(MHF4)**



Mechanical Specification

LTR	DESCRIPTION	DATE	REQ. BY
△	NEW Release	12/05/12	HWCHAN


RoHS COMPLIANT

MECHANICAL

Antenna Cover : TPEE
Antenna Base : PC/PBT
Color: Black

ELECTRICAL

Frequency : 2.4GHz
Cable : Coaxial Cable 1.13(Black)
Connector : IPEX Compatible(MHF4)



※凡標記△記號者,為品管檢驗之尺寸

設計 DR. HWCHAN 2012/12/05	核准 APP. Marco 2012/12/05	容許公差 TOLERANCE .XXX ±0.20 .XX ±0.35 .X ±0.50 X ±1.00 ANG ±5	品名 ARTICLE EDA-8709-2G4C1-B27
版本說明	REVISION NOTE		
MAGLAYERS			單位 UNIT mm
			比例 SCALE ****
			張數 SHEET 1
			版本 REV. A



MAG.LAYERS

Test Report

ELECTRICAL CHARACTERISTICS

P/NO: EDA-8709-2G4C1-B27

Spec: 2.4 GHz ~2.5GHz

S11




VSWR



MAG.LAYERS


Frequency(MHz) : 2400~2500. Pattern Field : X-Z plane



Layer	Max value	Min value	Average
2400(MHz)	2.05 dB	-24.34 dB	-2.61 dB
2450(MHz)	2.25 dB	-23.80 dB	-2.07 dB
2500(MHz)	2.16 dB	-24.13 dB	-2.29 dB




Frequency(MHz) : 2400~2500. Pattern Field : Y-Z plane



Layer	Max value	Min value	Average
2400(MHz)	0.89 dB	-24.94 dB	-2.45 dB
2450(MHz)	1.59 dB	-23.09 dB	-1.85 dB
2500(MHz)	1.30 dB	-23.44 dB	-2.16 dB


Frequency(MHz) : 2400~2500. Pattern Field : X-Y plane



Layer	Max value	Min value	Average
2400(MHz)	2.12 dB	-0.06 dB	1.02 dB
2450(MHz)	2.32 dB	0.34 dB	1.40 dB
2500(MHz)	1.91 dB	0.16 dB	1.15 dB



Antenna Efficiency



Maximum Efficiency At 2.4~2.5GHz: 85.35%



MAG.LAYERS