



International Certification Corp.

No. 3-1, Lane 6, Wen San 3rd St., Kwei Shan Hsiang, Tao Yuan Hsien 333, Taiwan, R.O.C.

Tel: 886-3-271-8666


Fax: 886-3-318-0155

FCC Test Report

FCC ID : SQG-WB45NBT
Equipment : 45 Series WB module with Bluetooth
Model No. : WB45NBT
Brand Name : Laird Technologies
Applicant : Laird Technologies
Address : 11160 Thompson Ave. / Lenexa, Kansas /
66219 / USA
Standard : 47 CFR FCC Part 15.407
Received Date : May 03, 2013
Tested Date : May 17 ~ Jun. 03, 2013

We, International Certification Corp., would like to declare that the tested sample has been evaluated and in compliance with the requirement of the above standards. The test results contained in this report refer exclusively to the product. It may be duplicated completely for legal use with the approval of the applicant. It shall not be reproduced except in full without the written approval of our laboratory.

Approved & Reviewed by:



Gary Chang / Manager





Table of Contents

1	GENERAL DESCRIPTION	5
1.1	Information.....	5
1.2	Test Setup Chart	7
1.3	The Equipment List	8
1.4	Testing Applied Standards	10
1.5	Measurement Uncertainty	11
2	TEST CONFIGURATION	12
2.1	Testing Condition	12
2.2	The Worst Test Modes and Channel Details	12
3	TRANSMITTER TEST RESULTS.....	13
3.1	Conducted Emissions.....	13
3.2	Emission Bandwidth	16
3.3	RF Output Power.....	18
3.4	Peak Power Spectral Density.....	20
3.5	Peak Excursion.....	22
3.6	Transmitter Radiated and Band Edge Emissions	25
3.7	Frequency Stability.....	141



International Certification Corp.

No. 3-1, Lane 6, Wen San 3rd St., Kwei Shan Hsiang, Tao Yuan Hsien 333, Taiwan, R.O.C.

Tel: 886-3-271-8666

Fax: 886-3-318-0155

Release Record

Report No.	Version	Description	Issued Date
FR350301AN	Rev. 01	Initial issue	Aug. 20, 2013



Summary of Test Results

FCC Rules	Test Items	Measured	Result
15.207	Conducted Emissions	[dBuV]: 0.153MHz 51.43 (Margin -14.39dB) - QP	Pass
15.407(b) 15.209	Radiated Emissions	[dBuV/m at 3m]: 5725MHz 67.29 (Margin -1.01dB) - PK	Pass
15.407(a)	Emission Bandwidth	Meet the requirement of limit	Pass
15.407(a)	RF Output Power	Power [dBm]: 5150~5250 MHz : 16.91 5250~5350 MHz : 16.73 5470~5725 MHz : 17.83	Pass
15.407(a)	Peak Power Spectral Density	Meet the requirement of limit	Pass
15.407(a)	Peak Excursion	Meet the requirement of limit	Pass
15.407(g)	Frequency Stability	Meet the requirement of limit	Pass
15.203	Antenna Requirement	Meet the requirement of limit	Pass



1 General Description

1.1 Information

1.1.1 Specification of the Equipment under Test (EUT)

RF General Information					
Frequency Range (MHz)	IEEE Std. 802.11	Ch. Freq. (MHz)	Channel Number	Transmit Chains (N _{TX})	Data Rate / MCS
5150-5250 5250-5350 5470-5725	a	5180-5240 5260-5320 5500-5700	36-48 [4] 52-64 [4] 100-140 [8]	1	6-54 Mbps
5150-5250 5250-5350 5470-5725	n (HT20)	5180-5240 5260-5320 5500-5700	36-48 [4] 52-64 [4] 100-140 [8]	1	MCS 0-7

Note 1: RF output power specifies that Maximum Conducted Output Power.
Note 2: 802.11a/n uses a combination of OFDM-BPSK, QPSK, 16QAM, 64QAM modulation.

1.1.2 Antenna Details

Ant. No.	Model	Type	Connector	Operating Frequencies (MHz) / Antenna Gain (dBi)				
				2400~2483.5	5150~5250	5250~5350	5470~5725	5725~5850
1	MAG.LAYERS EDA-1513-25GR 2-B2-CY	Dipole	SMA Jack Reverse	2	2	2	2	2
2	MAG.LAYERS PCA-4606-2G4C 1-A13-CY	PCB Dipole	UFL	2.21	2.21	2.21	2.21	2.21
3	Larid NanoBlade-IP04	PCB Dipole	UFL	2	3.9	3.9	4	4
4	Larid MAF95310 Mini NanoBlade Flex	PCB Dipole	UFL	2.79	3.38	3.38	3.38	3.38
5	Laird NanoBlue-IP04	PCB Dipole	UFL	2	---	---	---	-
6	Ethertronics WLAN_1000146	PIFA	UFL	2.5	3.5	3.5	3.5	3.5

1.1.3 EUT Operational Condition

Supply Voltage	☐ AC mains	☒ DC (3.3 / 1.8Vdc)	
Type of DC Source	☐ Internal DC supply	☐ External DC adapter	☒ From Host



1.1.4 Accessories

N/A

1.1.5 Channel List

Frequency band (MHz)	
802.11 a / n HT20	
Channel	Frequency(MHz)
36	5180
40	5200
44	5220
48	5240
52	5260
56	5280
60	5300
64	5320
100	5500
104	5520
108	5540
112	5560
116	5580
132	5660
136	5680
140	5700

1.1.6 Test Tool and Duty Cycle


Test Tool	VC_Example_windows_forms, ver 1.3
Duty Cycle Of Test Signal (%)	99.59% - IEEE 802.11a 99.56% - IEEE 802.11n (HT20)
Duty Factor	0.02 - IEEE 802.11a 0.02 - IEEE 802.11n (HT20)

1.1.7 Power Setting

Modulation Mode	Test Frequency (MHz)								
	a / n HT20								
	5180	5200	5240	5260	5300	5320	5500	5580	5700
a	15	15	16	17	16.5	17	19	19	18.5
n (HT20)	15	15	16.5	17	17	17.5	19	19	18.5



1.2 Test Setup Chart





1.3 The Equipment List

Test Item	Conducted Emission				
Test Site	Conduction room 1 / (CO01-WS)				
Instrument	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Until
EMC Receiver	R&S	ESCS 30	100169	Dec. 12, 2012	Dec. 11, 2013
LISN	SCHWARZBECK MESS-ELEKTRONIK	Schwarzbeck 8127	8127-667	Dec. 04, 2012	Dec. 03, 2013
LISN (Support Unit)	SCHWARZBECK MESS-ELEKTRONIK	Schwarzbeck 8127	8127-666	Dec. 04, 2012	Dec. 03, 2013
ISN	TESEQ	ISN T800	34406	Apr. 08, 2013	Apr. 07, 2014
ISN	TESEQ	ISN T200A	30494	Apr. 09, 2013	Apr. 08, 2014
ISN	TESEQ	ISN T8-Cat6	27262	Sep. 17, 2012	Sep. 16, 2013
ISN	TESEQ	ISN ST08	22589	Jan. 24, 2013	Jan. 23, 2014
RF Current Probe	FCC	F-33-4	121630	Dec. 04, 2012	Dec. 03, 2013
RF Cable-CON	Woken	CFD200-NL	CFD200-NL-001	Dec. 25, 2012	Dec. 24, 2013
ESH3-Z6 V-Network(+)	R&S	ESH3-Z6	100920	Nov. 21, 2012	Nov. 20, 2013
ESH3-Z6 V-Network(-)	R&S	ESH3-Z6	100951	Jan. 03, 2013	Jan. 02, 2014
Two-Line V-Network	R&S	ENV216	101579	Jan. 07, 2013	Jan. 06, 2014
50 ohm terminal	NA	50	01	Apr. 22, 2013	Apr. 21, 2014
50 ohm terminal	NA	50	02	Apr. 22, 2013	Apr. 21, 2014
50 ohm terminal	NA	50	03	Apr. 22, 2013	Apr. 21, 2014
50 ohm terminal (Support Unit)	NA	50	04	Apr. 22, 2013	Apr. 21, 2014
Note: Calibration Interval of instruments listed above is one year.					



International Certification Corp.

No. 3-1, Lane 6, Wen San 3rd St., Kwei Shan Hsiang, Tao Yuan Hsien 333, Taiwan, R.O.C.

Tel: 886-3-271-8666

Fax: 886-3-318-0155

Test Item	Radiated Emission above 1GHz				
Test Site	966 chamber1 / (03CH01-WS)				
Instrument	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Until
3m semi-anechoic chamber	CHAMPRO	SAC-03	03CH01-WS	Jan. 04, 2013	Jan. 03, 2014
Spectrum Analyzer	R&S	FSV40	101498	Jan. 24, 2013	Jan. 23, 2014
Receiver	ROHDE&SCHWARZ	ESR3	101658	Jan. 28, 2013	Jan. 27, 2014
Bilog Antenna	SCHWARZBECK	VULB9168	VULB9168-522	Jan. 11, 2013	Jan. 10, 2014
Horn Antenna 1G-18G	SCHWARZBECK	BBHA 9120 D	BBHA 9120 D 1096	Feb. 18, 2013	Feb. 17, 2014
Horn Antenna 18G-40G	SCHWARZBECK	BBHA 9170	BBHA 9170517	Jan. 14, 2013	Jan. 13, 2014
Amplifier	Burgeon	BPA-530	100219	Nov. 28, 2012	Nov. 27, 2013
Amplifier	Agilent	83017A	MY39501308	Dec. 18, 2012	Dec. 17, 2013
RF Cable	HUBER+SUHNER	SUCOFLEX104	MY16014/4	Dec. 25, 2012	Dec. 24, 2013
RF Cable	HUBER+SUHNER	SUCOFLEX104	MY16019/4	Dec. 25, 2012	Dec. 24, 2013
RF Cable	HUBER+SUHNER	SUCOFLEX104	MY16139/4	Dec. 25, 2012	Dec. 24, 2013
RF Cable-R03m	Woken	CFD400NL-LW	CFD400NL-001	Dec. 25, 2012	Dec. 24, 2013
RF Cable-R10m	Woken	CFD400NL-LW	CFD400NL-002	Dec. 25, 2012	Dec. 24, 2013
control	EM Electronics	EM1000	60612	N/A	N/A
Note: Calibration Interval of instruments listed above is one year.					

Loop Antenna	R&S	HFH2-Z2	100330	Nov. 15, 2012	Nov. 14, 2013
Amplifier	MITEQ	AMF-6F-260400	9121372	Apr. 19, 2013	Apr. 18, 2014
Note: Calibration Interval of instruments listed above is two year.					



Test Item	RF Conducted				
Test Site	(TH01-WS)				
Instrument	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Until
Spectrum Analyzer	R&S	FSV 40	101063	Feb. 18, 2013	Feb. 17, 2014
TEMP&HUMIDITY CHAMBER	GIANT FORCE	GCT-225-40-SP-SD	MAF1212-002	Nov. 29, 2012	Nov. 28, 2013
Power Meter	Anritsu	ML2495A	1241002	Oct. 15, 2012	Oct. 14, 2013
Power Sensor	Anritsu	MA2411B	1027366	Oct. 24, 2012	Oct. 23, 2013
Signal Generator	R&S	SMB100A	175727	Jan. 14, 2013	Jan. 13, 2014
Radio Communication Analyzer	Anritsu	MT8820C	6201240341	Mar. 13, 2013	Mar. 12, 2014
Wideband Radio Communication Tester	R&S	CMW500	106070	Jan. 29, 2013	Jan. 28, 2014
Bluetooth Tester	R&S	CBT	100959	Jan. 09, 2013	Jan. 08, 2014
MXG-B RF Vector Signal Generator	Agilent	N5182B	MY53050081	Apr. 19, 2013	Apr. 18, 2014
Note: Calibration Interval of instruments listed above is one year.					

1.4 Testing Applied Standards

According to the specification of EUT, the EUT must comply with following standards and KDB documents.

47 CFR FCC Part 15.407

ANSI C63.10-2009

FCC KDB 412172

FCC KDB 789033 D01 General UNII Test procedures v01r03

Note: The EUT has been tested and complied with FCC part 15B requirement. FCC Part 15B test results are issued to another report.



1.5 Measurement Uncertainty

ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor (k=2))

Measurement Uncertainty	
Parameters	Uncertainty
Bandwidth	± 74.147 Hz
Conducted power	± 0.717 dB
Power density	± 2.687 dB
Frequency error	± 74.147 Hz
Temperature	± 0.3 °C
AC conducted emission	± 2.43 dB
Radiated emission	± 2.49 dB



2 Test Configuration

2.1 Testing Condition

Test Item	Test Site	Ambient Condition	Tested By
AC Conduction	CO01-WS	23°C / 55%	Skys Huang
Radiated Emissions	03CH01-WS	24°C / 63%	Aska Huang Haru Yang
RF Conducted	TH01-WS	21°C / 60%	Brad Wu

➤ FCC site registration No.: 657002

➤ IC site registration No.: 10807A-1

2.2 The Worst Test Modes and Channel Details

Test item	Mode	Test Frequency (MHz)	Data rate (Mbps)	Test Configuration
Conducted Emissions	HT20	5240	MCS 0	1
Radiated Emissions <1GHz	HT20	5240	MCS 0	1, 2, 3
Radiated Emissions >1GHz	11a	5180 / 5200 / 5240	6	1, 2, 3
	11a	5260 / 5300 / 5320	6	
	11a	5500 / 5580 / 5700	6	
	HT20	5180 / 5200 / 5240	MCS 0	
	HT20	5260 / 5300 / 5320	MCS 0	
	HT20	5500 / 5580 / 5700	MCS 0	
RF Output Power Emission Bandwidth Peak Power Spectral Density	11a	5180 / 5200 / 5240	6	1
	11a	5260 / 5300 / 5320	6	
	11a	5500 / 5580 / 5700	6	
	HT20	5180 / 5200 / 5240	MCS 0	
	HT20	5260 / 5300 / 5320	MCS 0	
	HT20	5500 / 5580 / 5700	MCS 0	
Peak Excursion	11a	5240 / 5260 / 5500	6	1
	HT20	5240 / 5260 / 5500	MCS 0	
Frequency Stability	Un-modulation	5320	-	1

NOTE:

1. The EUT was pretested with 3 orientations placed on the table for the radiated emission measurement – X, Y, and Z-plane. The **Y-plane** results were found as the worst case and were shown in this report.
2. 3 types antenna are used for this device, highest gain antenna of each type is selected to perform radiated emission test as below test configuration
 - 1) Configuration 1 : Dipole antenna (Antenna No.1) , Y-plane
 - 2) Configuration 2 : PCB Dipole antenna (Antenna No.3) , Y-plane
 - 3) Configuration 3 : PIFA antenna (Antenna No.6), Y-plane
3. The EUT supports two DC voltage options, 3.3Vdc and 1.8Vdc. Both options were assessed and 3.3Vdc was found to be the worst case and was selected for the final test.



3 Transmitter Test Results

3.1 Conducted Emissions

3.1.1 Limit of Conducted Emissions


Conducted Emissions Limit		
Frequency Emission (MHz)	Quasi-Peak	Average
0.15-0.5	66 - 56 *	56 - 46 *
0.5-5	56	46
5-30	60	50

Note 1: * Decreases with the logarithm of the frequency.

3.1.2 Test Procedures

1. The device is placed on a test table, raised 80 cm above the reference ground plane. The vertical conducting plane is located 40 cm to the rear of the device.
2. The device is connected to line impedance stabilization network (LISN) and other accessories are connected to other LISN. Measured levels of AC power line conducted emission are across the 50 Ω LISN port.
3. AC conducted emission measurements is made over frequency range from 150 kHz to 30 MHz.

3.1.3 Test Setup



Note: 1. Support units were connected to second LISN.

2. Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes



3.1.4 Test Result of Conducted Emissions

Modulation Mode	HT20	Test Freq. (MHz)	5240
Power Phase	Line	Test Configuration	1

Level (dBuV) Date: 2013-06-03

Frequency (MHz)

	Freq MHz	Level dBuV	Limit Line dBuV	Over Limit dB	Read Level dBuV	LISN factor dB	cable loss dB	Remark
1	0.153	30.81	55.82	-25.01	30.71	0.03	0.07	Average
2	0.153	51.43	65.82	-14.39	51.33	0.03	0.07	QP
3	0.167	24.12	55.12	-31.00	23.99	0.03	0.10	Average
4	0.167	47.78	65.12	-17.34	47.65	0.03	0.10	QP
5	0.195	23.78	53.80	-30.02	23.58	0.03	0.17	Average
6	0.195	46.38	63.80	-17.42	46.18	0.03	0.17	QP
7	0.258	24.47	51.51	-27.04	24.31	0.03	0.13	Average
8	0.258	42.83	61.51	-18.68	42.67	0.03	0.13	QP
9	0.361	14.50	48.69	-34.19	14.40	0.03	0.07	Average
10	0.361	35.42	58.69	-23.27	35.32	0.03	0.07	QP
11	1.027	6.89	46.00	-39.11	6.81	0.04	0.04	Average
12	1.027	26.78	56.00	-29.22	26.70	0.04	0.04	QP
13	5.929	16.17	50.00	-33.83	15.92	0.07	0.18	Average
14	5.929	29.27	60.00	-30.73	29.02	0.07	0.18	QP


Note 1: Level (dBuV) = Read Level (dBuV) + LISN Factor (dB) + Cable Loss (dB).
2: Over Limit (dBuV) = Limit Line (dBuV) – Level (dBuV).



International Certification Corp.

No. 3-1, Lane 6, Wen San 3rd St., Kwei Shan Hsiang, Tao Yuan Hsien 333, Taiwan, R.O.C.
Tel: 886-3-271-8666 Fax: 886-3-318-0155

Modulation Mode	HT20	Test Freq. (MHz)	5240
Power Phase	Neutral	Test Configuration	1



	Freq	Level	Limit	Over	Read	LISN	cable	
	MHz	dBuV	Line	Limit	Level	factor	loss	Remark
			dBuV	dB	dBuV	dB	dB	
1	0.158	34.50	55.56	-21.06	34.40	0.02	0.08	Average
2	0.158	50.18	65.56	-15.38	50.08	0.02	0.08	QP
3	0.183	20.43	54.33	-33.90	20.27	0.02	0.14	Average
4	0.183	45.86	64.33	-18.47	45.70	0.02	0.14	QP
5	0.207	33.20	53.32	-20.12	33.01	0.02	0.17	Average
6	0.207	46.17	63.32	-17.15	45.98	0.02	0.17	QP
7	0.320	18.09	49.71	-31.62	17.98	0.02	0.09	Average
8	0.320	37.44	59.71	-22.27	37.33	0.02	0.09	QP
9	1.088	14.36	46.00	-31.64	14.29	0.02	0.05	Average
10	1.088	26.50	56.00	-29.50	26.43	0.02	0.05	QP
11	4.407	16.97	46.00	-29.03	16.69	0.05	0.23	Average
12	4.407	29.02	56.00	-26.98	28.74	0.05	0.23	QP
13	6.805	12.15	50.00	-37.85	11.92	0.07	0.16	Average
14	6.805	28.80	60.00	-31.20	28.57	0.07	0.16	QP

Note 1: Level (dBuV) = Read Level (dBuV) + LISN Factor (dB) + Cable Loss (dB).
2: Over Limit (dBuV) = Limit Line (dBuV) – Level (dBuV).




3.2 Emission Bandwidth

3.2.1 Test Procedures

1. Set RBW = approximately 1% of the emission bandwidth.
2. Set the VBW > RBW, Detector = Peak.
3. Trace mode = max hold.
4. Measure the maximum width of the emission that is 26 dB down from the peak of the emission.

3.2.2 Test Setup






3.2.3 Test Result of Emission Bandwidth

Modulation Mode	N _{TX}	Freq. (MHz)	26dB Bandwidth (MHz)				99% Bandwidth (MHz)				Limit (dBm)	
			Chain 0	Chain 1	Chain 2	Chain 3	Chain 0	Chain 1	Chain 2	Chain 3	26dB BW	99% BW
11a	1	5180	25.10	---	---	---	16.79	---	---	---	17.00	16.25
11a	1	5200	22.20	---	---	---	16.73	---	---	---	17.00	16.23
11a	1	5240	25.57	---	---	---	16.85	---	---	---	17.00	16.27
HT20	1	5180	24.35	---	---	---	17.89	---	---	---	17.00	16.53
HT20	1	5200	23.25	---	---	---	17.83	---	---	---	17.00	16.51
HT20	1	5240	25.22	---	---	---	18.00	---	---	---	17.00	16.55
11a	1	5260	25.57	---	---	---	16.90	---	---	---	24.00	23.28
11a	1	5300	23.42	---	---	---	16.73	---	---	---	24.00	23.23
11a	1	5320	23.88	---	---	---	16.79	---	---	---	24.00	23.25
HT20	1	5260	25.22	---	---	---	18.00	---	---	---	24.00	23.55
HT20	1	5300	24.46	---	---	---	17.89	---	---	---	24.00	23.53
HT20	1	5320	24.52	---	---	---	17.89	---	---	---	24.00	23.53
11a	1	5500	27.19	---	---	---	16.96	---	---	---	24.00	23.29
11a	1	5580	26.43	---	---	---	17.02	---	---	---	24.00	23.31
11a	1	5700	25.51	---	---	---	16.85	---	---	---	24.00	23.27
HT20	1	5500	28.81	---	---	---	18.06	---	---	---	24.00	23.57
HT20	1	5580	30.38	---	---	---	18.12	---	---	---	24.00	23.58
HT20	1	5700	24.75	---	---	---	18.00	---	---	---	24.00	23.55

Worst Plots





3.3 RF Output Power

3.3.1 Limit of RF Output Power


	Frequency Band (GHz)	Limit
☒	5.15~5.25	50mW or 4dBm+10 log B
☒	5.25~5.35	250mW or 11dBm+10 log B
☒	5.47~5.725	250mW or 11dBm+10 log B

Note: "B" is the 26dB emission bandwidth in MHz.

3.3.2 Test Procedures

- ☒ **Method PM-G (Measurement using a gated RF average power meter)**
 - ☒ Measurements may is performed using a wideband gated RF power meter provided that the gate parameters are adjusted such that the power is measured only when the EUT is transmitting at its maximum power control level. Since the measurement is made only during the ON time of the transmitter, no duty cycle correction factor is required.

3.3.3 Test Setup





3.3.4 Test Result of Maximum Conducted Output Power

Modulation Mode	N _{TX}	Freq. (MHz)	Average Power (dBm)				Total Power (mW)	Total Power (dBm)	Limit (dBm)
			Chain 0	Chain 1	Chain 2	Chain 3			
11a	1	5180	15.76	---	---	---	37.67	15.76	17.00
11a	1	5200	15.12	---	---	---	32.51	15.12	17.00
11a	1	5240	16.50	---	---	---	44.67	16.50	17.00
HT20	1	5180	15.69	---	---	---	37.07	15.69	17.00
HT20	1	5200	15.05	---	---	---	31.99	15.05	17.00
HT20	1	5240	16.91	---	---	---	49.09	16.91	17.00
11a	1	5260	16.73	---	---	---	47.10	16.73	24.00
11a	1	5300	15.91	---	---	---	38.99	15.91	24.00
11a	1	5320	15.71	---	---	---	37.24	15.71	24.00
HT20	1	5260	16.68	---	---	---	46.56	16.68	24.00
HT20	1	5300	16.23	---	---	---	41.98	16.23	24.00
HT20	1	5320	15.91	---	---	---	38.99	15.91	24.00
11a	1	5500	17.83	---	---	---	60.67	17.83	24.00
11a	1	5580	17.79	---	---	---	60.12	17.79	24.00
11a	1	5700	17.03	---	---	---	50.47	17.03	24.00
HT20	1	5500	17.82	---	---	---	60.53	17.82	24.00
HT20	1	5580	17.81	---	---	---	60.39	17.81	24.00
HT20	1	5700	16.99	---	---	---	50.00	16.99	24.00



3.4 Peak Power Spectral Density

3.4.1 Limit of Peak Power Spectral Density

	Frequency Band (GHz)	Limit (dBm)
☒	5.15~5.25	4
☒	5.25~5.35	11
☒	5.47~5.725	11

3.4.2 Test Procedures

☒ Method SA-1

1. Set RBW = 1 MHz, VBW = 3 MHz, Sweep time = auto, Detector = RMS.
2. Trace average 100 traces.
3. Use the peak marker function to determine the maximum amplitude level.

☐ Method SA-2


1. Set RBW = 1 MHz, VBW = 3 MHz, Sweep time = auto, Detector = RMS.
2. Trace average at 100 traces
3. Use the peak marker function to determine the maximum amplitude level.
4. Add $10 \log(1/x)$, where x is the duty cycle

☐ Method SA-2 Alternative

1. Set RBW = 1 MHz, VBW = 3 MHz, Detector = RMS.
2. Set sweep time $\geq 10 * (\text{number of points in sweep}) * (\text{total on/off period of the transmitted signal})$.
3. Perform a single sweep.
4. Use the peak marker function to determine the maximum amplitude level.
5. Add $10 \log(1/x)$, where x is the duty cycle.

Note: 11a and HT20 uses Method SA-1, HT40 uses Method SA-2 Alternative.

3.4.3 Test Setup






3.4.4 Test Result of Peak Power Spectral Density

Modulation Mode	N _{TX}	Freq. (MHz)	PSD (dBm)	Duty Factor	Total PSD (dBm)	Limit (dBm)
11a	1	5180	2.54	0	2.54	4
11a	1	5200	2.55	0	2.55	4
11a	1	5240	3.56	0	3.56	4
HT20	1	5180	2.17	0	2.17	4
HT20	1	5200	1.93	0	1.93	4
HT20	1	5240	3.79	0	3.79	4
11a	1	5260	3.92	0	3.92	11
11a	1	5300	2.74	0	2.74	11
11a	1	5320	2.94	0	2.94	11
HT20	1	5260	3.76	0	3.76	11
HT20	1	5300	2.98	0	2.98	11
HT20	1	5320	2.83	0	2.83	11
11a	1	5500	5.00	0	5.00	11
11a	1	5580	4.95	0	4.95	11
11a	1	5700	3.90	0	3.90	11
HT20	1	5500	4.84	0	4.84	11
HT20	1	5580	4.81	0	4.81	11
HT20	1	5700	3.93	0	3.93	11

Worst Plots





3.5 Peak Excursion


3.5.1 Peak Excursion Limit

Peak excursion of the modulation envelope shall not exceed 13 dB across any 1 MHz bandwidth.

3.5.2 Test Procedures

1. Set RBW = 1 MHz, VBW = 3 MHz, Detector = peak.
2. Trace mode = max-hold. Allow the sweeps to continue until the trace stabilizes.
3. Use the peak search function to find the peak of the spectrum.
4. Use the procedure of section 3.4.2 to measure the PPSD.
5. Compute the ratio of the maximum of the peak-max-hold spectrum to the PPSD

3.5.3 Test Setup





3.5.4 Test Result of Peak Excursion


Mode	Modulation Mode	N _{TX}	Freq. (MHz)	Measured value(dB)	Duty factor (dB)	Peak Excursion (dB)	Limit
11a	BPSK	1	5240	6.99	0.00	6.99	13
11a	QPSK	1	5240	8.99	0.00	8.99	13
11a	16QAM	1	5240	7.67	0.16	7.51	13
11a	64QAM	1	5240	8.99	0.37	8.62	13
HT20	BPSK	1	5240	7.14	0.00	7.14	13
HT20	QPSK	1	5240	8.36	0.00	8.36	13
HT20	16QAM	1	5240	8.26	0.17	8.09	13
HT20	64QAM	1	5240	9.14	0.35	8.79	13
11a	BPSK	1	5260	7.02	0.00	7.02	13
11a	QPSK	1	5260	9.02	0.00	9.02	13
11a	16QAM	1	5260	7.79	0.16	7.63	13
11a	64QAM	1	5260	8.82	0.37	8.45	13
HT20	BPSK	1	5260	6.72	0.00	6.72	13
HT20	QPSK	1	5260	7.97	0.00	7.97	13
HT20	16QAM	1	5260	8.14	0.17	7.97	13
HT20	64QAM	1	5260	9.42	0.35	9.07	13
11a	BPSK	1	5500	6.81	0.00	6.81	13
11a	QPSK	1	5500	8.84	0.00	8.84	13
11a	16QAM	1	5500	7.8	0.16	7.64	13
11a	64QAM	1	5500	8.84	0.37	8.47	13
HT20	BPSK	1	5500	7.15	0.00	7.15	13
HT20	QPSK	1	5500	8.07	0.00	8.07	13
HT20	16QAM	1	5500	8.31	0.17	8.14	13
HT20	64QAM	1	5500	8.96	0.35	8.61	13

Note: Measured value = Peak-max-hold spectrum to the maximum of the average spectrum for continuous transmission. Since the duty cycle is < 98 %, duty factor is required to average spectrum

Peak excursion = Measured value – duty factor



Worst Plots



Note1: Peak exclusion = Peak value –PPSD

Note2: If duty cycle of test signal is < 98%, duty factor is required to PPSSD

Peak exclusion = Peak value – (PPSD + duty factor)



3.6 Transmitter Radiated and Band Edge Emissions

3.6.1 Limit of Transmitter Radiated and Band Edge Emissions

Restricted Band Emissions Limit			
Frequency Range (MHz)	Field Strength (uV/m)	Field Strength (dBuV/m)	Measure Distance (m)
0.009~0.490	2400/F(kHz)	48.5 - 13.8	300
0.490~1.705	24000/F(kHz)	33.8 - 23	30
1.705~30.0	30	29	30
30~88	100	40	3
88~216	150	43.5	3
216~960	200	46	3
Above 960	500	54	3

Note 1:
Qusai-Peak value is measured for frequency below 1GHz except for 9–90 kHz, 110–490 kHz frequency band. Peak and average value are measured for frequency above 1GHz. The limit on average radio frequency emission is as above table. The limit on peak radio frequency emissions is 20 dB above the maximum permitted average emission limit

Note 2:
Measurements may be performed at a distance other than what is specified provided. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor as below, Frequency at or above 30 MHz: 20 dB/decade Frequency below 30 MHz: 40 dB/decade.

Un-restricted band emissions above 1GHz Limit	
Operating Band	Limit
5.15 - 5.25 GHz	e.i.r.p. -27 dBm [68.2 dBuV/m@3m]
5.25 - 5.35 GHz	e.i.r.p. -27 dBm [68.2 dBuV/m@3m]
5.47 - 5.725 GHz	e.i.r.p. -27 dBm [68.2 dBuV/m@3m]
5.725 - 5.825 GHz	5.715 5.725 GHz: e.i.r.p. -17 dBm [78.2 dBuV/m@3m] 5.825 5.835 GHz: e.i.r.p. -17 dBm [78.2 dBuV/m@3m] Other un-restricted band: e.i.r.p. -27 dBm [68.2 dBuV/m@3m]

Note 1: Measurements may be performed at a distance other than the limit distance provided they are not performed in the near field and the emissions to be measured can be detected by the measurement equipment. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade (inverse of linear distance for field-strength measurements, inverse of linear distance-squared for power-density measurements).




3.6.2 Test Procedures

1. Measurement is made at a semi-anechoic chamber that incorporates a turntable allowing a EUT rotation of 360° . A continuously-rotating, remotely-controlled turntable is installed at the test site to support the EUT and facilitate determination of the direction of maximum radiation for each EUT emission frequency. The EUT is placed at a height of 0.8 m test table above the ground plane.
2. Measurement is made with the antenna positioned in both the horizontal and vertical planes of polarization. The measurement antenna is varied in height (1m ~ 4m) above the reference ground plane to obtain the maximum signal strength. Distance between EUT and antenna is 3 m.
3. This investigation is performed with the EUT rotated 360° , the antenna height scanned between 1 m and 4 m, and the antenna rotated to repeat the measurements for both the horizontal and vertical antenna polarizations.

Note:


1. 120kHz measurement bandwidth of test receiver and Quasi-peak detector is for radiated emission below 1GHz.
2. RBW=1MHz, VBW=3MHz and Peak detector is for peak measured value of radiated emission above 1GHz.
3. RBW=1MHz, VBW=1/T and Peak detector is for average measured value of radiated emission above 1GHz.

3.6.3 Test Setup





3.6.4 Transmitter Radiated Unwanted Emissions (Below 1GHz)

Modulation Mode	HT20	Test Freq. (MHz)	5240																																																																						
Polarization	Horizontal	Test Configuration	1																																																																						
Level (dBuV/m)  <table><tr><th></th><th>Freq. MHz</th><th>Emission level dBuV/m</th><th>Limit dBuV/m</th><th>Margin dB</th><th>SA reading dBuV</th><th>Factor dB</th><th>Remark</th><th>ANT High cm</th><th>Turn Table deg</th></tr><tr><td>1</td><td>62.75</td><td>37.69</td><td>40.00</td><td>-2.31</td><td>55.52</td><td>-17.83</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>2</td><td>140.28</td><td>37.36</td><td>43.50</td><td>-6.14</td><td>54.54</td><td>-17.18</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>3</td><td>172.84</td><td>41.28</td><td>43.50</td><td>-2.22</td><td>58.78</td><td>-17.50</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>4</td><td>217.93</td><td>40.55</td><td>46.00</td><td>-5.45</td><td>59.94</td><td>-19.39</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>5</td><td>247.96</td><td>34.79</td><td>46.00</td><td>-11.21</td><td>52.72</td><td>-17.93</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>6</td><td>533.87</td><td>30.16</td><td>46.00</td><td>-15.84</td><td>41.15</td><td>-10.99</td><td>Peak</td><td>---</td><td>---</td></tr></table>					Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg	1	62.75	37.69	40.00	-2.31	55.52	-17.83	Peak	---	---	2	140.28	37.36	43.50	-6.14	54.54	-17.18	Peak	---	---	3	172.84	41.28	43.50	-2.22	58.78	-17.50	Peak	---	---	4	217.93	40.55	46.00	-5.45	59.94	-19.39	Peak	---	---	5	247.96	34.79	46.00	-11.21	52.72	-17.93	Peak	---	---	6	533.87	30.16	46.00	-15.84	41.15	-10.99	Peak	---	---
	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg																																																																
1	62.75	37.69	40.00	-2.31	55.52	-17.83	Peak	---	---																																																																
2	140.28	37.36	43.50	-6.14	54.54	-17.18	Peak	---	---																																																																
3	172.84	41.28	43.50	-2.22	58.78	-17.50	Peak	---	---																																																																
4	217.93	40.55	46.00	-5.45	59.94	-19.39	Peak	---	---																																																																
5	247.96	34.79	46.00	-11.21	52.72	-17.93	Peak	---	---																																																																
6	533.87	30.16	46.00	-15.84	41.15	-10.99	Peak	---	---																																																																
Note 1: Level (dBuV/m) = Read Level (dBuV/m) + Antenna Factor (dB) + Cable Loss (dB) - Preamp Factor (dB). 2: Over Limit (dBuV/m) = Limit Line (dBuV/m) – Level (dBuV/m).																																																																									



International Certification Corp.

No. 3-1, Lane 6, Wen San 3rd St., Kwei Shan Hsiang, Tao Yuan Hsien 333, Taiwan, R.O.C.
Tel: 886-3-271-8666 Fax: 886-3-318-0155

Modulation Mode	HT20	Test Freq. (MHz)	5240
Polarization	Vertical	Test Configuration	1

Level (dBuV/m)

Frequency (MHz)

	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	62.45	38.65	40.00	-1.35	56.42	-17.77	QP	---	---
2	126.39	32.47	43.50	-11.03	50.96	-18.49	Peak	---	---
3	213.52	31.68	43.50	-11.82	51.08	-19.40	Peak	---	---
4	399.64	33.54	46.00	-12.46	47.21	-13.67	Peak	---	---
5	667.34	30.57	46.00	-15.43	39.32	-8.75	Peak	---	---
6	960.56	32.97	54.00	-21.03	37.73	-4.76	Peak	---	---


Note 1: Level (dBuV/m) = Read Level (dBuV/m) + Antenna Factor (dB) + Cable Loss (dB) - Preamp Factor (dB).
2: Over Limit (dBuV/m) = Limit Line (dBuV/m) – Level (dBuV/m).



International Certification Corp.

No. 3-1, Lane 6, Wen San 3rd St., Kwei Shan Hsiang, Tao Yuan Hsien 333, Taiwan, R.O.C.
Tel: 886-3-271-8666 Fax: 886-3-318-0155

Modulation Mode	HT20	Test Freq. (MHz)	5240
Polarization	Horizontal	Test Configuration	2



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	60.45	37.57	40.00	-2.43	54.96	-17.39	Peak	---	---
2	171.28	40.15	43.50	-3.35	57.48	-17.33	Peak	---	---
3	218.94	39.41	46.00	-6.59	58.79	-19.38	Peak	---	---
4	399.16	25.93	46.00	-20.07	39.61	-13.68	Peak	---	---
5	533.75	29.22	46.00	-16.78	40.21	-10.99	Peak	---	---
6	667.36	30.48	46.00	-15.52	39.23	-8.75	Peak	---	---


Note 1: Level (dBuV/m) = Read Level (dBuV/m) + Antenna Factor (dB) + Cable Loss (dB) - Preamp Factor (dB).
2: Over Limit (dBuV/m) = Limit Line (dBuV/m) – Level (dBuV/m).



International Certification Corp.

No. 3-1, Lane 6, Wen San 3rd St., Kwei Shan Hsiang, Tao Yuan Hsien 333, Taiwan, R.O.C.
Tel: 886-3-271-8666 Fax: 886-3-318-0155

Modulation Mode	HT20	Test Freq. (MHz)	5240
Polarization	Vertical	Test Configuration	2



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	61.03	38.83	40.00	-1.17	56.33	-17.50	QP	---	---
2	76.55	37.69	40.00	-2.31	58.61	-20.92	Peak	---	---
3	130.58	31.24	43.50	-12.26	49.31	-18.07	Peak	---	---
4	212.86	32.47	43.50	-11.03	51.87	-19.40	Peak	---	---
5	533.65	30.96	46.00	-15.04	41.95	-10.99	Peak	---	---
6	667.82	33.91	46.00	-12.09	42.66	-8.75	Peak	---	---

Note 1: Level (dBuV/m) = Read Level (dBuV/m) + Antenna Factor (dB) + Cable Loss (dB) - Preamp Factor (dB).
2: Over Limit (dBuV/m) = Limit Line (dBuV/m) – Level (dBuV/m).




Modulation Mode	HT20		Test Freq. (MHz)	5240																																																																															
Polarization	Horizontal		Test Configuration	3																																																																															
Level (dBUV/m) Frequency (MHz) <table><tr><th>Freq.</th><th>Emission level</th><th>Limit</th><th>Margin</th><th>SA reading</th><th>Factor</th><th>Remark</th><th>ANT High</th><th>Turn Table</th></tr><tr><th>MHz</th><th>dBUV/m</th><th>dBUV/m</th><th>dB</th><th>dBUV</th><th>dB</th><th></th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>60.39</td><td>37.52</td><td>40.00</td><td>-2.48</td><td>54.90</td><td>-17.38</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>2</td><td>172.73</td><td>40.32</td><td>43.50</td><td>-3.18</td><td>57.81</td><td>-17.49</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>3</td><td>219.24</td><td>39.31</td><td>46.00</td><td>-6.69</td><td>58.69</td><td>-19.38</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>4</td><td>533.61</td><td>27.83</td><td>46.00</td><td>-18.17</td><td>38.81</td><td>-10.98</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>5</td><td>667.34</td><td>32.56</td><td>46.00</td><td>-13.44</td><td>41.31</td><td>-8.75</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>6</td><td>800.43</td><td>35.85</td><td>46.00</td><td>-10.15</td><td>42.60</td><td>-6.75</td><td>Peak</td><td>---</td><td>---</td></tr></table>						Freq.	Emission level	Limit	Margin	SA reading	Factor	Remark	ANT High	Turn Table	MHz	dBUV/m	dBUV/m	dB	dBUV	dB		cm	deg	1	60.39	37.52	40.00	-2.48	54.90	-17.38	Peak	---	---	2	172.73	40.32	43.50	-3.18	57.81	-17.49	Peak	---	---	3	219.24	39.31	46.00	-6.69	58.69	-19.38	Peak	---	---	4	533.61	27.83	46.00	-18.17	38.81	-10.98	Peak	---	---	5	667.34	32.56	46.00	-13.44	41.31	-8.75	Peak	---	---	6	800.43	35.85	46.00	-10.15	42.60	-6.75	Peak	---	---
Freq.	Emission level	Limit	Margin	SA reading	Factor	Remark	ANT High	Turn Table																																																																											
MHz	dBUV/m	dBUV/m	dB	dBUV	dB		cm	deg																																																																											
1	60.39	37.52	40.00	-2.48	54.90	-17.38	Peak	---	---																																																																										
2	172.73	40.32	43.50	-3.18	57.81	-17.49	Peak	---	---																																																																										
3	219.24	39.31	46.00	-6.69	58.69	-19.38	Peak	---	---																																																																										
4	533.61	27.83	46.00	-18.17	38.81	-10.98	Peak	---	---																																																																										
5	667.34	32.56	46.00	-13.44	41.31	-8.75	Peak	---	---																																																																										
6	800.43	35.85	46.00	-10.15	42.60	-6.75	Peak	---	---																																																																										
Note 1: Level (dBUV/m) = Read Level (dBUV/m) + Antenna Factor (dB) + Cable Loss (dB) - Preamp Factor (dB). 2: Over Limit (dBUV/m) = Limit Line (dBUV/m) – Level (dBUV/m).																																																																																			



International Certification Corp.

No. 3-1, Lane 6, Wen San 3rd St., Kwei Shan Hsiang, Tao Yuan Hsien 333, Taiwan, R.O.C.
Tel: 886-3-271-8666 Fax: 886-3-318-0155

Modulation Mode	HT20	Test Freq. (MHz)	5240
Polarization	Vertical	Test Configuration	3



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	60.31	38.46	40.00	-1.54	55.82	-17.36	QP	---	---
2	126.27	32.39	43.50	-11.11	50.89	-18.50	Peak	---	---
3	218.67	32.16	46.00	-13.84	51.54	-19.38	Peak	---	---
4	399.43	31.85	46.00	-14.15	45.52	-13.67	Peak	---	---
5	533.74	32.68	46.00	-13.32	43.67	-10.99	Peak	---	---
6	667.37	32.51	46.00	-13.49	41.26	-8.75	Peak	---	---

Note 1: Level (dBuV/m) = Read Level (dBuV/m) + Antenna Factor (dB) + Cable Loss (dB) - Preamp Factor (dB).
2: Over Limit (dBuV/m) = Limit Line (dBuV/m) – Level (dBuV/m).



3.6.5 Transmitter Radiated Unwanted Emissions (Above 1GHz) for 11a

Polarization	Horizontal		Test Freq. (MHz)		5180																																																																																				
Test Configuration	1																																																																																								
 <table><tr><th></th><th>Freq.</th><th>Emission</th><th>Limit</th><th>Margin</th><th>SA</th><th>Factor</th><th>Remark</th><th>ANT</th><th>Turn</th></tr><tr><th></th><th>MHz</th><th>level</th><th>dBuV/m</th><th>dB</th><th>reading</th><th>dB</th><th></th><th>High</th><th>Table</th></tr><tr><th></th><th></th><th></th><th></th><th></th><th></th><th></th><th></th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>1050.00</td><td>35.44</td><td>54.00</td><td>-18.56</td><td>44.65</td><td>-9.21</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>2</td><td>1050.00</td><td>46.38</td><td>74.00</td><td>-27.62</td><td>55.59</td><td>-9.21</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>3</td><td>5150.00</td><td>44.25</td><td>54.00</td><td>-9.75</td><td>39.31</td><td>4.94</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>4</td><td>5150.00</td><td>56.11</td><td>74.00</td><td>-17.89</td><td>51.17</td><td>4.94</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>5</td><td>10360.00</td><td>60.15</td><td>68.30</td><td>-8.15</td><td>45.44</td><td>14.71</td><td>Peak</td><td>---</td><td>---</td></tr></table>											Freq.	Emission	Limit	Margin	SA	Factor	Remark	ANT	Turn		MHz	level	dBuV/m	dB	reading	dB		High	Table									cm	deg	1	1050.00	35.44	54.00	-18.56	44.65	-9.21	Average	---	---	2	1050.00	46.38	74.00	-27.62	55.59	-9.21	Peak	---	---	3	5150.00	44.25	54.00	-9.75	39.31	4.94	Average	---	---	4	5150.00	56.11	74.00	-17.89	51.17	4.94	Peak	---	---	5	10360.00	60.15	68.30	-8.15	45.44	14.71	Peak	---	---
	Freq.	Emission	Limit	Margin	SA	Factor	Remark	ANT	Turn																																																																																
	MHz	level	dBuV/m	dB	reading	dB		High	Table																																																																																
								cm	deg																																																																																
1	1050.00	35.44	54.00	-18.56	44.65	-9.21	Average	---	---																																																																																
2	1050.00	46.38	74.00	-27.62	55.59	-9.21	Peak	---	---																																																																																
3	5150.00	44.25	54.00	-9.75	39.31	4.94	Average	---	---																																																																																
4	5150.00	56.11	74.00	-17.89	51.17	4.94	Peak	---	---																																																																																
5	10360.00	60.15	68.30	-8.15	45.44	14.71	Peak	---	---																																																																																
Note 1: “>20dB” means spurious emission levels that exceed the level of 20 dB below the applicable limit. Note 2: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.																																																																																									




International Certification Corp.

No. 3-1, Lane 6, Wen San 3rd St., Kwei Shan Hsiang, Tao Yuan Hsien 333, Taiwan, R.O.C.

Tel: 886-3-271-8666

Fax: 886-3-318-0155

Polarization	Vertical	Test Freq. (MHz)	5180																																																												
Test Configuration	1																																																														
 <table><tr><th></th><th>Freq. MHz</th><th>Emission level dBuV/m</th><th>Limit dBuV/m</th><th>Margin dB</th><th>SA reading dBuV</th><th>Factor dB</th><th>Remark</th><th>ANT High cm</th><th>Turn Table deg</th></tr><tr><td>1</td><td>1050.00</td><td>35.57</td><td>54.00</td><td>-18.43</td><td>44.78</td><td>-9.21</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>2</td><td>1050.00</td><td>46.28</td><td>74.00</td><td>-27.72</td><td>55.49</td><td>-9.21</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>3</td><td>5150.00</td><td>47.82</td><td>54.00</td><td>-6.18</td><td>42.88</td><td>4.94</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>4</td><td>5150.00</td><td>63.06</td><td>74.00</td><td>-10.94</td><td>58.12</td><td>4.94</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>5</td><td>10360.00</td><td>64.97</td><td>68.30</td><td>-3.33</td><td>50.26</td><td>14.71</td><td>Peak</td><td>---</td><td>---</td></tr></table>					Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg	1	1050.00	35.57	54.00	-18.43	44.78	-9.21	Average	---	---	2	1050.00	46.28	74.00	-27.72	55.49	-9.21	Peak	---	---	3	5150.00	47.82	54.00	-6.18	42.88	4.94	Average	---	---	4	5150.00	63.06	74.00	-10.94	58.12	4.94	Peak	---	---	5	10360.00	64.97	68.30	-3.33	50.26	14.71	Peak	---	---
	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg																																																						
1	1050.00	35.57	54.00	-18.43	44.78	-9.21	Average	---	---																																																						
2	1050.00	46.28	74.00	-27.72	55.49	-9.21	Peak	---	---																																																						
3	5150.00	47.82	54.00	-6.18	42.88	4.94	Average	---	---																																																						
4	5150.00	63.06	74.00	-10.94	58.12	4.94	Peak	---	---																																																						
5	10360.00	64.97	68.30	-3.33	50.26	14.71	Peak	---	---																																																						
Note 1: “>20dB” means spurious emission levels that exceed the level of 20 dB below the applicable limit. Note 2: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.																																																															



International Certification Corp.

No. 3-1, Lane 6, Wen San 3rd St., Kwei Shan Hsiang, Tao Yuan Hsien 333, Taiwan, R.O.C.

Tel: 886-3-271-8666

Fax: 886-3-318-0155

Polarization	Horizontal		Test Freq. (MHz)		5200																																																																
Test Configuration	1																																																																				
The graph displays the emission level in dBuV/m on the y-axis (ranging from 0 to 117) against frequency in MHz on the x-axis (ranging from 1000 to 40000). A red line represents the FCC PART15E limit, which is 70 dBuV/m for frequencies below 30 MHz and 60 dBuV/m for frequencies above 30 MHz. A blue line represents the test results, showing a peak at 1050 MHz and a higher peak at 5150 MHz. The test results are summarized in the table below. <table><tr><th></th><th>Freq. MHz</th><th>Emission level dBuV/m</th><th>Limit dBuV/m</th><th>Margin dB</th><th>SA reading dBuV</th><th>Factor dB</th><th>Remark</th><th>ANT High cm</th><th>Turn Table deg</th></tr><tr><td>1</td><td>1050.00</td><td>35.46</td><td>54.00</td><td>-18.54</td><td>44.67</td><td>-9.21</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>2</td><td>1050.00</td><td>46.37</td><td>74.00</td><td>-27.63</td><td>55.58</td><td>-9.21</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>3</td><td>5150.00</td><td>43.83</td><td>54.00</td><td>-10.17</td><td>38.89</td><td>4.94</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>4</td><td>5150.00</td><td>56.58</td><td>74.00</td><td>-17.42</td><td>51.64</td><td>4.94</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>5</td><td>10400.00</td><td>60.22</td><td>68.30</td><td>-8.08</td><td>45.47</td><td>14.75</td><td>Peak</td><td>---</td><td>---</td></tr></table>											Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg	1	1050.00	35.46	54.00	-18.54	44.67	-9.21	Average	---	---	2	1050.00	46.37	74.00	-27.63	55.58	-9.21	Peak	---	---	3	5150.00	43.83	54.00	-10.17	38.89	4.94	Average	---	---	4	5150.00	56.58	74.00	-17.42	51.64	4.94	Peak	---	---	5	10400.00	60.22	68.30	-8.08	45.47	14.75	Peak	---	---
	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg																																																												
1	1050.00	35.46	54.00	-18.54	44.67	-9.21	Average	---	---																																																												
2	1050.00	46.37	74.00	-27.63	55.58	-9.21	Peak	---	---																																																												
3	5150.00	43.83	54.00	-10.17	38.89	4.94	Average	---	---																																																												
4	5150.00	56.58	74.00	-17.42	51.64	4.94	Peak	---	---																																																												
5	10400.00	60.22	68.30	-8.08	45.47	14.75	Peak	---	---																																																												
Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit. Note 2: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.																																																																					



International Certification Corp.

No. 3-1, Lane 6, Wen San 3rd St., Kwei Shan Hsiang, Tao Yuan Hsien 333, Taiwan, R.O.C.

Tel: 886-3-271-8666

Fax: 886-3-318-0155

Polarization	Vertical	Test Freq. (MHz)	5200																																																																		
Test Configuration	1																																																																				
The graph displays the emission level in dBuV/m on the y-axis (ranging from 0 to 117) against frequency in MHz on the x-axis (ranging from 1000 to 40000). A red stepped line represents the FCC PART15E limit, and a lower red line represents the average limit (FCC PART15E (AVG)). Blue vertical lines indicate specific test points: Point 1 at 1050 MHz, Point 2 at 1050 MHz, Point 3 at 5150 MHz, Point 4 at 5150 MHz, and Point 5 at 10400 MHz. The test results are summarized in the table below. <table><tr><th></th><th>Freq. MHz</th><th>Emission level dBuV/m</th><th>Limit dBuV/m</th><th>Margin dB</th><th>SA reading dBuV</th><th>Factor dB</th><th>Remark</th><th>ANT High cm</th><th>Turn Table deg</th></tr><tr><td>1</td><td>1050.00</td><td>35.42</td><td>54.00</td><td>-18.58</td><td>44.63</td><td>-9.21</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>2</td><td>1050.00</td><td>46.39</td><td>74.00</td><td>-27.61</td><td>55.60</td><td>-9.21</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>3</td><td>5150.00</td><td>44.85</td><td>54.00</td><td>-9.15</td><td>39.91</td><td>4.94</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>4</td><td>5150.00</td><td>57.43</td><td>74.00</td><td>-16.57</td><td>52.49</td><td>4.94</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>5</td><td>10400.00</td><td>63.76</td><td>68.30</td><td>-4.54</td><td>49.01</td><td>14.75</td><td>Peak</td><td>---</td><td>---</td></tr></table>											Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg	1	1050.00	35.42	54.00	-18.58	44.63	-9.21	Average	---	---	2	1050.00	46.39	74.00	-27.61	55.60	-9.21	Peak	---	---	3	5150.00	44.85	54.00	-9.15	39.91	4.94	Average	---	---	4	5150.00	57.43	74.00	-16.57	52.49	4.94	Peak	---	---	5	10400.00	63.76	68.30	-4.54	49.01	14.75	Peak	---	---
	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg																																																												
1	1050.00	35.42	54.00	-18.58	44.63	-9.21	Average	---	---																																																												
2	1050.00	46.39	74.00	-27.61	55.60	-9.21	Peak	---	---																																																												
3	5150.00	44.85	54.00	-9.15	39.91	4.94	Average	---	---																																																												
4	5150.00	57.43	74.00	-16.57	52.49	4.94	Peak	---	---																																																												
5	10400.00	63.76	68.30	-4.54	49.01	14.75	Peak	---	---																																																												
Note 1: “>20dB” means spurious emission levels that exceed the level of 20 dB below the applicable limit. Note 2: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.																																																																					



International Certification Corp.

No. 3-1, Lane 6, Wen San 3rd St., Kwei Shan Hsiang, Tao Yuan Hsien 333, Taiwan, R.O.C.
Tel: 886-3-271-8666 Fax: 886-3-318-0155

Polarization	Horizontal		Test Freq. (MHz)		5240				
Test Configuration	1								
Level (dBuV/m) <									



International Certification Corp.

No. 3-1, Lane 6, Wen San 3rd St., Kwei Shan Hsiang, Tao Yuan Hsien 333, Taiwan, R.O.C.

Tel: 886-3-271-8666

Fax: 886-3-318-0155

Polarization	Vertical		Test Freq. (MHz)		5240				
Test Configuration	1								
The graph displays the emission level in dBuV/m on the y-axis (ranging from 0 to 117) against frequency in MHz on the x-axis (ranging from 1000 to 40000). A red line represents the FCC PART15E limit, and a lower red line represents the FCC PART15E (AVG) limit. Blue vertical lines indicate specific measurement points labeled 1 through 5. Point 1 is at 1050.00 MHz, point 2 at 1050.00 MHz, point 3 at 5150.00 MHz, point 4 at 5150.00 MHz, and point 5 at 10480.00 MHz. The emission levels at these points are shown in the table below.									
	Freq.	Emission	Limit	Margin	SA	Factor	Remark	ANT	Turn
	MHz	level			reading			High	Table
		dBuV/m	dBuV/m	dB	dBuV	dB		cm	deg
1	1050.00	35.44	54.00	-18.56	44.65	-9.21	Average	---	---
2	1050.00	46.81	74.00	-27.19	56.02	-9.21	Peak	---	---
3	5150.00	44.18	54.00	-9.82	39.24	4.94	Average	---	---
4	5150.00	57.39	74.00	-16.61	52.45	4.94	Peak	---	---
5	10480.00	65.07	68.30	-3.23	50.23	14.84	Peak	---	---

Note 1: “>20dB” means spurious emission levels that exceed the level of 20 dB below the applicable limit.

Note 2: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.




International Certification Corp.

No. 3-1, Lane 6, Wen San 3rd St., Kwei Shan Hsiang, Tao Yuan Hsien 333, Taiwan, R.O.C.

Tel: 886-3-271-8666

Fax: 886-3-318-0155

Polarization	Vertical			Test Freq. (MHz)		5260																																																																																			
Test Configuration	1																																																																																								
Level (dBuV/m)  <table><tr><th></th><th>Freq.</th><th>Emission</th><th>Limit</th><th>Margin</th><th>SA</th><th>Factor</th><th>Remark</th><th>ANT</th><th>Turn</th></tr><tr><th></th><th>MHz</th><th>level</th><th></th><th></th><th>reading</th><th></th><th></th><th>High</th><th>Table</th></tr><tr><th></th><th></th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB</th><th></th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>1050.00</td><td>35.42</td><td>54.00</td><td>-18.58</td><td>44.63</td><td>-9.21</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>2</td><td>1050.00</td><td>46.68</td><td>74.00</td><td>-27.32</td><td>55.89</td><td>-9.21</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>3</td><td>5350.00</td><td>40.69</td><td>54.00</td><td>-13.31</td><td>35.60</td><td>5.09</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>4</td><td>5350.00</td><td>53.37</td><td>74.00</td><td>-20.63</td><td>48.28</td><td>5.09</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>5</td><td>10520.00</td><td>67.10</td><td>68.30</td><td>-1.20</td><td>52.23</td><td>14.87</td><td>Peak</td><td>---</td><td>---</td></tr></table>											Freq.	Emission	Limit	Margin	SA	Factor	Remark	ANT	Turn		MHz	level			reading			High	Table			dBuV/m	dBuV/m	dB	dBuV	dB		cm	deg	1	1050.00	35.42	54.00	-18.58	44.63	-9.21	Average	---	---	2	1050.00	46.68	74.00	-27.32	55.89	-9.21	Peak	---	---	3	5350.00	40.69	54.00	-13.31	35.60	5.09	Average	---	---	4	5350.00	53.37	74.00	-20.63	48.28	5.09	Peak	---	---	5	10520.00	67.10	68.30	-1.20	52.23	14.87	Peak	---	---
	Freq.	Emission	Limit	Margin	SA	Factor	Remark	ANT	Turn																																																																																
	MHz	level			reading			High	Table																																																																																
		dBuV/m	dBuV/m	dB	dBuV	dB		cm	deg																																																																																
1	1050.00	35.42	54.00	-18.58	44.63	-9.21	Average	---	---																																																																																
2	1050.00	46.68	74.00	-27.32	55.89	-9.21	Peak	---	---																																																																																
3	5350.00	40.69	54.00	-13.31	35.60	5.09	Average	---	---																																																																																
4	5350.00	53.37	74.00	-20.63	48.28	5.09	Peak	---	---																																																																																
5	10520.00	67.10	68.30	-1.20	52.23	14.87	Peak	---	---																																																																																
Note 1: “>20dB” means spurious emission levels that exceed the level of 20 dB below the applicable limit. Note 2: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.																																																																																									



International Certification Corp.

No. 3-1, Lane 6, Wen San 3rd St., Kwei Shan Hsiang, Tao Yuan Hsien 333, Taiwan, R.O.C.

Tel: 886-3-271-8666


Fax: 886-3-318-0155

Polarization	Horizontal		Test Freq. (MHz)		5300																																																																							
Test Configuration	1																																																																											
The graph displays the emission level in dBuV/m on the y-axis (0 to 117) against frequency in MHz on the x-axis (1000 to 40000). A red stepped line represents the FCC PART15E limit, and a lower red line represents the average limit (FCC PART15E (AVG)). Blue vertical lines with markers indicate specific test points: 2 at 1050 MHz, 3 at 5350 MHz, 4 at 5350 MHz, 5 at 10600 MHz, and 6 at 10600 MHz. The test results are summarized in the table below. <table><tr><th></th><th>Freq. MHz</th><th>Emission level dBuV/m</th><th>Limit dBuV/m</th><th>Margin dB</th><th>SA reading dBuV</th><th>Factor dB</th><th>Remark</th><th>ANT High cm</th><th>Turn Table deg</th></tr><tr><td>1</td><td>1050.00</td><td>35.44</td><td>54.00</td><td>-18.56</td><td>44.65</td><td>-9.21</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>2</td><td>1050.00</td><td>46.98</td><td>74.00</td><td>-27.02</td><td>56.19</td><td>-9.21</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>3</td><td>5350.00</td><td>35.82</td><td>54.00</td><td>-18.18</td><td>30.73</td><td>5.09</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>4</td><td>5350.00</td><td>48.69</td><td>74.00</td><td>-25.31</td><td>43.60</td><td>5.09</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>5</td><td>10600.00</td><td>49.20</td><td>54.00</td><td>-4.80</td><td>34.26</td><td>14.94</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>6</td><td>10600.00</td><td>63.47</td><td>74.00</td><td>-10.53</td><td>48.53</td><td>14.94</td><td>Peak</td><td>---</td><td>---</td></tr></table>								Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg	1	1050.00	35.44	54.00	-18.56	44.65	-9.21	Average	---	---	2	1050.00	46.98	74.00	-27.02	56.19	-9.21	Peak	---	---	3	5350.00	35.82	54.00	-18.18	30.73	5.09	Average	---	---	4	5350.00	48.69	74.00	-25.31	43.60	5.09	Peak	---	---	5	10600.00	49.20	54.00	-4.80	34.26	14.94	Average	---	---	6	10600.00	63.47	74.00	-10.53	48.53	14.94	Peak	---	---
	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg																																																																			
1	1050.00	35.44	54.00	-18.56	44.65	-9.21	Average	---	---																																																																			
2	1050.00	46.98	74.00	-27.02	56.19	-9.21	Peak	---	---																																																																			
3	5350.00	35.82	54.00	-18.18	30.73	5.09	Average	---	---																																																																			
4	5350.00	48.69	74.00	-25.31	43.60	5.09	Peak	---	---																																																																			
5	10600.00	49.20	54.00	-4.80	34.26	14.94	Average	---	---																																																																			
6	10600.00	63.47	74.00	-10.53	48.53	14.94	Peak	---	---																																																																			
Note 1: “>20dB” means spurious emission levels that exceed the level of 20 dB below the applicable limit. Note 2: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.																																																																												



International Certification Corp.

No. 3-1, Lane 6, Wen San 3rd St., Kwei Shan Hsiang, Tao Yuan Hsien 333, Taiwan, R.O.C.
Tel: 886-3-271-8666 Fax: 886-3-318-0155

Polarization	Vertical				Test Freq. (MHz)		5300																																																																								
Test Configuration	1																																																																														
 <table><tr><th></th><th>Freq. MHz</th><th>Emission level dBuV/m</th><th>Limit dBuV/m</th><th>Margin dB</th><th>SA reading dBuV</th><th>Factor dB</th><th>Remark</th><th>ANT High cm</th><th>Turn Table deg</th></tr><tr><td>1</td><td>1050.00</td><td>35.41</td><td>54.00</td><td>-18.59</td><td>44.62</td><td>-9.21</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>2</td><td>1050.00</td><td>46.68</td><td>74.00</td><td>-27.32</td><td>55.89</td><td>-9.21</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>3</td><td>5350.00</td><td>41.70</td><td>54.00</td><td>-12.30</td><td>36.61</td><td>5.09</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>4</td><td>5350.00</td><td>54.50</td><td>74.00</td><td>-19.50</td><td>49.41</td><td>5.09</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>5</td><td>10600.00</td><td>52.50</td><td>54.00</td><td>-1.50</td><td>37.56</td><td>14.94</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>6</td><td>10600.00</td><td>66.10</td><td>74.00</td><td>-7.90</td><td>51.16</td><td>14.94</td><td>Peak</td><td>---</td><td>---</td></tr></table>											Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg	1	1050.00	35.41	54.00	-18.59	44.62	-9.21	Average	---	---	2	1050.00	46.68	74.00	-27.32	55.89	-9.21	Peak	---	---	3	5350.00	41.70	54.00	-12.30	36.61	5.09	Average	---	---	4	5350.00	54.50	74.00	-19.50	49.41	5.09	Peak	---	---	5	10600.00	52.50	54.00	-1.50	37.56	14.94	Average	---	---	6	10600.00	66.10	74.00	-7.90	51.16	14.94	Peak	---	---
	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg																																																																						
1	1050.00	35.41	54.00	-18.59	44.62	-9.21	Average	---	---																																																																						
2	1050.00	46.68	74.00	-27.32	55.89	-9.21	Peak	---	---																																																																						
3	5350.00	41.70	54.00	-12.30	36.61	5.09	Average	---	---																																																																						
4	5350.00	54.50	74.00	-19.50	49.41	5.09	Peak	---	---																																																																						
5	10600.00	52.50	54.00	-1.50	37.56	14.94	Average	---	---																																																																						
6	10600.00	66.10	74.00	-7.90	51.16	14.94	Peak	---	---																																																																						
Note 1: “>20dB” means spurious emission levels that exceed the level of 20 dB below the applicable limit. Note 2: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.																																																																															



International Certification Corp.

No. 3-1, Lane 6, Wen San 3rd St., Kwei Shan Hsiang, Tao Yuan Hsien 333, Taiwan, R.O.C.

Tel: 886-3-271-8666

Fax: 886-3-318-0155

Polarization	Horizontal		Test Freq. (MHz)		5320																																																																										
Test Configuration	1																																																																														
Level (dBuV/m) Frequency (MHz) <table><thead><tr><th></th><th>Freq. MHz</th><th>Emission level dBuV/m</th><th>Limit dBuV/m</th><th>Margin dB</th><th>SA reading dBuV</th><th>Factor dB</th><th>Remark</th><th>ANT High cm</th><th>Turn Table deg</th></tr></thead><tbody><tr><td>1</td><td>1050.00</td><td>35.24</td><td>54.00</td><td>-18.76</td><td>44.45</td><td>-9.21</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>2</td><td>1050.00</td><td>46.27</td><td>74.00</td><td>-27.73</td><td>55.48</td><td>-9.21</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>3</td><td>5350.00</td><td>43.80</td><td>54.00</td><td>-10.20</td><td>38.71</td><td>5.09</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>4</td><td>5350.00</td><td>57.29</td><td>74.00</td><td>-16.71</td><td>52.20</td><td>5.09</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>5</td><td>10640.00</td><td>49.94</td><td>54.00</td><td>-4.06</td><td>34.96</td><td>14.98</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>6</td><td>10640.00</td><td>62.95</td><td>74.00</td><td>-11.05</td><td>47.97</td><td>14.98</td><td>Peak</td><td>---</td><td>---</td></tr></tbody></table>											Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg	1	1050.00	35.24	54.00	-18.76	44.45	-9.21	Average	---	---	2	1050.00	46.27	74.00	-27.73	55.48	-9.21	Peak	---	---	3	5350.00	43.80	54.00	-10.20	38.71	5.09	Average	---	---	4	5350.00	57.29	74.00	-16.71	52.20	5.09	Peak	---	---	5	10640.00	49.94	54.00	-4.06	34.96	14.98	Average	---	---	6	10640.00	62.95	74.00	-11.05	47.97	14.98	Peak	---	---
	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg																																																																						
1	1050.00	35.24	54.00	-18.76	44.45	-9.21	Average	---	---																																																																						
2	1050.00	46.27	74.00	-27.73	55.48	-9.21	Peak	---	---																																																																						
3	5350.00	43.80	54.00	-10.20	38.71	5.09	Average	---	---																																																																						
4	5350.00	57.29	74.00	-16.71	52.20	5.09	Peak	---	---																																																																						
5	10640.00	49.94	54.00	-4.06	34.96	14.98	Average	---	---																																																																						
6	10640.00	62.95	74.00	-11.05	47.97	14.98	Peak	---	---																																																																						
Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit. Note 2: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.																																																																															




International Certification Corp.

No. 3-1, Lane 6, Wen San 3rd St., Kwei Shan Hsiang, Tao Yuan Hsien 333, Taiwan, R.O.C.

Tel: 886-3-271-8666

Fax: 886-3-318-0155

Polarization	Vertical		Test Freq. (MHz)		5320																																																																										
Test Configuration	1																																																																														
 <table><tr><th></th><th>Freq. MHz</th><th>Emission level dBuV/m</th><th>Limit dBuV/m</th><th>Margin dB</th><th>SA reading dBuV</th><th>Factor dB</th><th>Remark</th><th>ANT High cm</th><th>Turn Table deg</th></tr><tr><td>1</td><td>1050.00</td><td>35.56</td><td>54.00</td><td>-18.44</td><td>44.77</td><td>-9.21</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>2</td><td>1050.00</td><td>46.77</td><td>74.00</td><td>-27.23</td><td>55.98</td><td>-9.21</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>3</td><td>5350.00</td><td>49.43</td><td>54.00</td><td>-4.57</td><td>44.34</td><td>5.09</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>4</td><td>5350.00</td><td>64.82</td><td>74.00</td><td>-9.18</td><td>59.73</td><td>5.09</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>5</td><td>10640.00</td><td>52.90</td><td>54.00</td><td>-1.10</td><td>37.92</td><td>14.98</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>6</td><td>10640.00</td><td>66.64</td><td>74.00</td><td>-7.36</td><td>51.66</td><td>14.98</td><td>Peak</td><td>---</td><td>---</td></tr></table>											Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg	1	1050.00	35.56	54.00	-18.44	44.77	-9.21	Average	---	---	2	1050.00	46.77	74.00	-27.23	55.98	-9.21	Peak	---	---	3	5350.00	49.43	54.00	-4.57	44.34	5.09	Average	---	---	4	5350.00	64.82	74.00	-9.18	59.73	5.09	Peak	---	---	5	10640.00	52.90	54.00	-1.10	37.92	14.98	Average	---	---	6	10640.00	66.64	74.00	-7.36	51.66	14.98	Peak	---	---
	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg																																																																						
1	1050.00	35.56	54.00	-18.44	44.77	-9.21	Average	---	---																																																																						
2	1050.00	46.77	74.00	-27.23	55.98	-9.21	Peak	---	---																																																																						
3	5350.00	49.43	54.00	-4.57	44.34	5.09	Average	---	---																																																																						
4	5350.00	64.82	74.00	-9.18	59.73	5.09	Peak	---	---																																																																						
5	10640.00	52.90	54.00	-1.10	37.92	14.98	Average	---	---																																																																						
6	10640.00	66.64	74.00	-7.36	51.66	14.98	Peak	---	---																																																																						
Note 1: “>20dB” means spurious emission levels that exceed the level of 20 dB below the applicable limit. Note 2: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.																																																																															



Polarization	Horizontal		Test Freq. (MHz)		5500																																																																																					
Test Configuration	1																																																																																									
The graph displays the emission level in dBuV/m on the y-axis (0 to 117) against frequency in MHz on the x-axis (1000 to 40000). A red line represents the FCC PART15E (74) limit, and a lower red line represents the FCC PART15E (AVG) limit. Blue vertical lines indicate test results at specific frequencies, with points labeled 3 through 8. The test results show varying levels of compliance with the limits. <table><tr><th>Freq. MHz</th><th>Emission level dBuV/m</th><th>Limit dBuV/m</th><th>Margin dB</th><th>SA reading dBuV</th><th>Factor dB</th><th>Remark</th><th>ANT High cm</th><th>Turn Table deg</th></tr><tr><td>1050.00</td><td>35.44</td><td>54.00</td><td>-18.56</td><td>44.65</td><td>-9.21</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>1050.00</td><td>46.57</td><td>74.00</td><td>-27.43</td><td>55.78</td><td>-9.21</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>5460.00</td><td>42.82</td><td>54.00</td><td>-11.18</td><td>37.64</td><td>5.18</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>5460.00</td><td>56.22</td><td>74.00</td><td>-17.78</td><td>51.04</td><td>5.18</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>5470.00</td><td>47.13</td><td>54.00</td><td>-6.87</td><td>41.94</td><td>5.19</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>5470.00</td><td>63.15</td><td>74.00</td><td>-10.85</td><td>57.96</td><td>5.19</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>11000.00</td><td>49.90</td><td>54.00</td><td>-4.10</td><td>34.62</td><td>15.28</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>11000.00</td><td>63.29</td><td>74.00</td><td>-10.71</td><td>48.01</td><td>15.28</td><td>Peak</td><td>---</td><td>---</td></tr></table>										Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg	1050.00	35.44	54.00	-18.56	44.65	-9.21	Average	---	---	1050.00	46.57	74.00	-27.43	55.78	-9.21	Peak	---	---	5460.00	42.82	54.00	-11.18	37.64	5.18	Average	---	---	5460.00	56.22	74.00	-17.78	51.04	5.18	Peak	---	---	5470.00	47.13	54.00	-6.87	41.94	5.19	Average	---	---	5470.00	63.15	74.00	-10.85	57.96	5.19	Peak	---	---	11000.00	49.90	54.00	-4.10	34.62	15.28	Average	---	---	11000.00	63.29	74.00	-10.71	48.01	15.28	Peak	---	---
Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg																																																																																		
1050.00	35.44	54.00	-18.56	44.65	-9.21	Average	---	---																																																																																		
1050.00	46.57	74.00	-27.43	55.78	-9.21	Peak	---	---																																																																																		
5460.00	42.82	54.00	-11.18	37.64	5.18	Average	---	---																																																																																		
5460.00	56.22	74.00	-17.78	51.04	5.18	Peak	---	---																																																																																		
5470.00	47.13	54.00	-6.87	41.94	5.19	Average	---	---																																																																																		
5470.00	63.15	74.00	-10.85	57.96	5.19	Peak	---	---																																																																																		
11000.00	49.90	54.00	-4.10	34.62	15.28	Average	---	---																																																																																		
11000.00	63.29	74.00	-10.71	48.01	15.28	Peak	---	---																																																																																		
Note 1: “>20dB” means spurious emission levels that exceed the level of 20 dB below the applicable limit. Note 2: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.																																																																																										



International Certification Corp.

No. 3-1, Lane 6, Wen San 3rd St., Kwei Shan Hsiang, Tao Yuan Hsien 333, Taiwan, R.O.C.
Tel: 886-3-271-8666 Fax: 886-3-318-0155

Polarization	Vertical		Test Freq. (MHz)		5500																																																																																														
Test Configuration	1																																																																																																		
The graph displays the emission level in dBuV/m on the y-axis (0 to 117) against frequency in MHz on the x-axis (1000 to 40000). A red line represents the FCC Part 15E (74) limit, and a blue line represents the FCC Part 15E (AVG) limit. Test results are plotted as blue vertical lines with markers 1 through 8. The table below provides the numerical data for these points. <table><tr><th></th><th>Freq. MHz</th><th>Emission level dBuV/m</th><th>Limit dBuV/m</th><th>Margin dB</th><th>SA reading dBuV</th><th>Factor dB</th><th>Remark</th><th>ANT High cm</th><th>Turn Table deg</th></tr><tr><td>1</td><td>1050.00</td><td>35.48</td><td>54.00</td><td>-18.52</td><td>44.69</td><td>-9.21</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>2</td><td>1050.00</td><td>46.52</td><td>74.00</td><td>-27.48</td><td>55.73</td><td>-9.21</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>3</td><td>5460.00</td><td>45.32</td><td>54.00</td><td>-8.68</td><td>40.14</td><td>5.18</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>4</td><td>5460.00</td><td>60.78</td><td>74.00</td><td>-13.22</td><td>55.60</td><td>5.18</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>5</td><td>5470.00</td><td>52.51</td><td>54.00</td><td>-1.49</td><td>47.32</td><td>5.19</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>6</td><td>5470.00</td><td>68.57</td><td>74.00</td><td>-5.43</td><td>63.38</td><td>5.19</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>7</td><td>11000.00</td><td>51.58</td><td>54.00</td><td>-2.42</td><td>36.30</td><td>15.28</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>8</td><td>11000.00</td><td>65.05</td><td>74.00</td><td>-8.95</td><td>49.77</td><td>15.28</td><td>Peak</td><td>---</td><td>---</td></tr></table>											Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg	1	1050.00	35.48	54.00	-18.52	44.69	-9.21	Average	---	---	2	1050.00	46.52	74.00	-27.48	55.73	-9.21	Peak	---	---	3	5460.00	45.32	54.00	-8.68	40.14	5.18	Average	---	---	4	5460.00	60.78	74.00	-13.22	55.60	5.18	Peak	---	---	5	5470.00	52.51	54.00	-1.49	47.32	5.19	Average	---	---	6	5470.00	68.57	74.00	-5.43	63.38	5.19	Peak	---	---	7	11000.00	51.58	54.00	-2.42	36.30	15.28	Average	---	---	8	11000.00	65.05	74.00	-8.95	49.77	15.28	Peak	---	---
	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg																																																																																										
1	1050.00	35.48	54.00	-18.52	44.69	-9.21	Average	---	---																																																																																										
2	1050.00	46.52	74.00	-27.48	55.73	-9.21	Peak	---	---																																																																																										
3	5460.00	45.32	54.00	-8.68	40.14	5.18	Average	---	---																																																																																										
4	5460.00	60.78	74.00	-13.22	55.60	5.18	Peak	---	---																																																																																										
5	5470.00	52.51	54.00	-1.49	47.32	5.19	Average	---	---																																																																																										
6	5470.00	68.57	74.00	-5.43	63.38	5.19	Peak	---	---																																																																																										
7	11000.00	51.58	54.00	-2.42	36.30	15.28	Average	---	---																																																																																										
8	11000.00	65.05	74.00	-8.95	49.77	15.28	Peak	---	---																																																																																										
Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit. Note 2: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.																																																																																																			




International Certification Corp.

No. 3-1, Lane 6, Wen San 3rd St., Kwei Shan Hsiang, Tao Yuan Hsien 333, Taiwan, R.O.C.

Tel: 886-3-271-8666

Fax: 886-3-318-0155

Polarization	Horizontal		Test Freq. (MHz)		5580																																																																										
Test Configuration	1																																																																														
 <table><tr><th></th><th>Freq. MHz</th><th>Emission level dBuV/m</th><th>Limit dBuV/m</th><th>Margin dB</th><th>SA reading dBuV</th><th>Factor dB</th><th>Remark</th><th>ANT High cm</th><th>Turn Table deg</th></tr><tr><td>1</td><td>1050.00</td><td>35.44</td><td>54.00</td><td>-18.56</td><td>44.65</td><td>-9.21</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>2</td><td>1050.00</td><td>46.68</td><td>74.00</td><td>-27.32</td><td>55.89</td><td>-9.21</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>3</td><td>5418.50</td><td>39.95</td><td>54.00</td><td>-14.05</td><td>34.83</td><td>5.12</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>4</td><td>5418.50</td><td>52.49</td><td>74.00</td><td>-21.51</td><td>47.37</td><td>5.12</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>5</td><td>11160.00</td><td>48.27</td><td>54.00</td><td>-5.73</td><td>33.09</td><td>15.18</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>6</td><td>11160.00</td><td>62.35</td><td>74.00</td><td>-11.65</td><td>47.17</td><td>15.18</td><td>Peak</td><td>---</td><td>---</td></tr></table>											Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg	1	1050.00	35.44	54.00	-18.56	44.65	-9.21	Average	---	---	2	1050.00	46.68	74.00	-27.32	55.89	-9.21	Peak	---	---	3	5418.50	39.95	54.00	-14.05	34.83	5.12	Average	---	---	4	5418.50	52.49	74.00	-21.51	47.37	5.12	Peak	---	---	5	11160.00	48.27	54.00	-5.73	33.09	15.18	Average	---	---	6	11160.00	62.35	74.00	-11.65	47.17	15.18	Peak	---	---
	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg																																																																						
1	1050.00	35.44	54.00	-18.56	44.65	-9.21	Average	---	---																																																																						
2	1050.00	46.68	74.00	-27.32	55.89	-9.21	Peak	---	---																																																																						
3	5418.50	39.95	54.00	-14.05	34.83	5.12	Average	---	---																																																																						
4	5418.50	52.49	74.00	-21.51	47.37	5.12	Peak	---	---																																																																						
5	11160.00	48.27	54.00	-5.73	33.09	15.18	Average	---	---																																																																						
6	11160.00	62.35	74.00	-11.65	47.17	15.18	Peak	---	---																																																																						
Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit. Note 2: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.																																																																															



International Certification Corp.

No. 3-1, Lane 6, Wen San 3rd St., Kwei Shan Hsiang, Tao Yuan Hsien 333, Taiwan, R.O.C.

Tel: 886-3-271-8666


Fax: 886-3-318-0155

Polarization	Horizontal		Test Freq. (MHz)		5700																																																																										
Test Configuration	1																																																																														
<table><tr><th></th><th>Freq. MHz</th><th>Emission level dBuV/m</th><th>Limit dBuV/m</th><th>Margin dB</th><th>SA reading dBuV</th><th>Factor dB</th><th>Remark</th><th>ANT High cm</th><th>Turn Table deg</th></tr><tr><td>1</td><td>1050.00</td><td>35.52</td><td>54.00</td><td>-18.48</td><td>44.73</td><td>-9.21</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>2</td><td>1050.00</td><td>46.37</td><td>74.00</td><td>-27.63</td><td>55.58</td><td>-9.21</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>3</td><td>5725.00</td><td>46.38</td><td>54.00</td><td>-7.62</td><td>40.82</td><td>5.56</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>4</td><td>5725.00</td><td>62.47</td><td>74.00</td><td>-11.53</td><td>56.91</td><td>5.56</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>5</td><td>11400.00</td><td>46.38</td><td>54.00</td><td>-7.62</td><td>31.35</td><td>15.03</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>6</td><td>11400.00</td><td>59.58</td><td>74.00</td><td>-14.42</td><td>44.55</td><td>15.03</td><td>Peak</td><td>---</td><td>---</td></tr></table>											Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg	1	1050.00	35.52	54.00	-18.48	44.73	-9.21	Average	---	---	2	1050.00	46.37	74.00	-27.63	55.58	-9.21	Peak	---	---	3	5725.00	46.38	54.00	-7.62	40.82	5.56	Average	---	---	4	5725.00	62.47	74.00	-11.53	56.91	5.56	Peak	---	---	5	11400.00	46.38	54.00	-7.62	31.35	15.03	Average	---	---	6	11400.00	59.58	74.00	-14.42	44.55	15.03	Peak	---	---
	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg																																																																						
1	1050.00	35.52	54.00	-18.48	44.73	-9.21	Average	---	---																																																																						
2	1050.00	46.37	74.00	-27.63	55.58	-9.21	Peak	---	---																																																																						
3	5725.00	46.38	54.00	-7.62	40.82	5.56	Average	---	---																																																																						
4	5725.00	62.47	74.00	-11.53	56.91	5.56	Peak	---	---																																																																						
5	11400.00	46.38	54.00	-7.62	31.35	15.03	Average	---	---																																																																						
6	11400.00	59.58	74.00	-14.42	44.55	15.03	Peak	---	---																																																																						
Note 1: “>20dB” means spurious emission levels that exceed the level of 20 dB below the applicable limit. Note 2: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.																																																																															



International Certification Corp.

No. 3-1, Lane 6, Wen San 3rd St., Kwei Shan Hsiang, Tao Yuan Hsien 333, Taiwan, R.O.C.
Tel: 886-3-271-8666 Fax: 886-3-318-0155

Polarization	Vertical			Test Freq. (MHz)		5700																																																																									
Test Configuration	1																																																																														
 <table><tr><th></th><th>Freq. MHz</th><th>Emission level dBuV/m</th><th>Limit dBuV/m</th><th>Margin dB</th><th>SA reading dBuV</th><th>Factor dB</th><th>Remark</th><th>ANT High cm</th><th>Turn Table deg</th></tr><tr><td>1</td><td>1050.00</td><td>35.43</td><td>54.00</td><td>-18.57</td><td>44.64</td><td>-9.21</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>2</td><td>1050.00</td><td>46.78</td><td>74.00</td><td>-27.22</td><td>55.99</td><td>-9.21</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>3</td><td>5725.00</td><td>52.75</td><td>54.00</td><td>-1.25</td><td>47.19</td><td>5.56</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>4</td><td>5725.00</td><td>68.91</td><td>74.00</td><td>-5.09</td><td>63.35</td><td>5.56</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>5</td><td>11400.00</td><td>48.55</td><td>54.00</td><td>-5.45</td><td>33.52</td><td>15.03</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>6</td><td>11400.00</td><td>61.71</td><td>74.00</td><td>-12.29</td><td>46.68</td><td>15.03</td><td>Peak</td><td>---</td><td>---</td></tr></table>											Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg	1	1050.00	35.43	54.00	-18.57	44.64	-9.21	Average	---	---	2	1050.00	46.78	74.00	-27.22	55.99	-9.21	Peak	---	---	3	5725.00	52.75	54.00	-1.25	47.19	5.56	Average	---	---	4	5725.00	68.91	74.00	-5.09	63.35	5.56	Peak	---	---	5	11400.00	48.55	54.00	-5.45	33.52	15.03	Average	---	---	6	11400.00	61.71	74.00	-12.29	46.68	15.03	Peak	---	---
	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg																																																																						
1	1050.00	35.43	54.00	-18.57	44.64	-9.21	Average	---	---																																																																						
2	1050.00	46.78	74.00	-27.22	55.99	-9.21	Peak	---	---																																																																						
3	5725.00	52.75	54.00	-1.25	47.19	5.56	Average	---	---																																																																						
4	5725.00	68.91	74.00	-5.09	63.35	5.56	Peak	---	---																																																																						
5	11400.00	48.55	54.00	-5.45	33.52	15.03	Average	---	---																																																																						
6	11400.00	61.71	74.00	-12.29	46.68	15.03	Peak	---	---																																																																						
Note 1: “>20dB” means spurious emission levels that exceed the level of 20 dB below the applicable limit. Note 2: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.																																																																															




International Certification Corp.

No. 3-1, Lane 6, Wen San 3rd St., Kwei Shan Hsiang, Tao Yuan Hsien 333, Taiwan, R.O.C.

Tel: 886-3-271-8666

Fax: 886-3-318-0155

Polarization	Vertical		Test Freq. (MHz)		5180																																																																
Test Configuration	2																																																																				
 <table><tr><th></th><th>Freq. MHz</th><th>Emission level dBuV/m</th><th>Limit dBuV/m</th><th>Margin dB</th><th>SA reading dBuV</th><th>Factor dB</th><th>Remark</th><th>ANT High cm</th><th>Turn Table deg</th></tr><tr><td>1</td><td>1050.00</td><td>36.00</td><td>54.00</td><td>-18.00</td><td>45.21</td><td>-9.21</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>2</td><td>1050.00</td><td>46.17</td><td>74.00</td><td>-27.83</td><td>55.38</td><td>-9.21</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>3</td><td>5150.00</td><td>47.78</td><td>54.00</td><td>-6.22</td><td>42.84</td><td>4.94</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>4</td><td>5150.00</td><td>64.55</td><td>74.00</td><td>-9.45</td><td>59.61</td><td>4.94</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>5</td><td>10360.00</td><td>65.88</td><td>68.30</td><td>-2.42</td><td>51.17</td><td>14.71</td><td>Peak</td><td>---</td><td>---</td></tr></table>											Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg	1	1050.00	36.00	54.00	-18.00	45.21	-9.21	Average	---	---	2	1050.00	46.17	74.00	-27.83	55.38	-9.21	Peak	---	---	3	5150.00	47.78	54.00	-6.22	42.84	4.94	Average	---	---	4	5150.00	64.55	74.00	-9.45	59.61	4.94	Peak	---	---	5	10360.00	65.88	68.30	-2.42	51.17	14.71	Peak	---	---
	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg																																																												
1	1050.00	36.00	54.00	-18.00	45.21	-9.21	Average	---	---																																																												
2	1050.00	46.17	74.00	-27.83	55.38	-9.21	Peak	---	---																																																												
3	5150.00	47.78	54.00	-6.22	42.84	4.94	Average	---	---																																																												
4	5150.00	64.55	74.00	-9.45	59.61	4.94	Peak	---	---																																																												
5	10360.00	65.88	68.30	-2.42	51.17	14.71	Peak	---	---																																																												
Note 1: “>20dB” means spurious emission levels that exceed the level of 20 dB below the applicable limit. Note 2: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.																																																																					



International Certification Corp.

No. 3-1, Lane 6, Wen San 3rd St., Kwei Shan Hsiang, Tao Yuan Hsien 333, Taiwan, R.O.C.
Tel: 886-3-271-8666 Fax: 886-3-318-0155

Polarization	Horizontal	Test Freq. (MHz)	5200
Test Configuration	2		
Level (dBuV/m) 117 110 90 70 50 30 10 0 1000 6000 10000 14000 18000 22000 26000 30000 34000 40000 Frequency (MHz) 117 110 90 70 50 30 10 0 1000 6000 10000 14000 18000 22000 26000 30000 34000 40000 Frequency (MHz) 117 110 90 70 50 30 10 0 1000 6000 10000 14000 18000 22000 26000 30000 34000 40000 Frequency (MHz) 117 110 90 70 50 30 10 0 1000 6000 10000 14000 18000 22000 26000 30000 34000 40000 Frequency (MHz) 117 110 90 70 50 30 10 0 1000 6000 10000 14000 18000 22000 26000 30000 34000 40000 Frequency (MHz) 117 110 90 70 50 30 10 0 1000 6000 10000 14000 18000 22000 26000 30000 34000 40000 Frequency (MHz) 117 110 90 70 50 30 10 0 1000 6000 10000 14000 18000 22000 26000 30000 34000 40000 Frequency (MHz) 117 110 90 70 50 30 10 0 1000 6000 10000 14000 18000 22000 26000 30000 34000 40000 Frequency (MHz) 117 110 90 70 50 30 10 0 1000 6000 10000 14000 18000 22000 26000 30000 34000 40000 Frequency (MHz) 117 110 90 70 50 30 10 0 1000 6000 10000 14000 18000 22000 26000 30000 34000 40000 Frequency (MHz) 117 110 90 70 50 30 10 0 1000 6000 10000 14000 18000 22000 26000 30000 34000 40000 Frequency (MHz) 117 110 90 70 50 30 10 0 1000 6000 10000 14000 18000 22000 26000 30000 34000 40000 Frequency (MHz) 117 110 90 70 50 30 10 0 1000 6000 10000 14000 18000 22000 26000 30000 34000 40000 Frequency (MHz) 117 110 90 70 50 30 10 0 1000 6000 10000 14000 18000 22000 26000 30000 34000 40000 Frequency (MHz) 117 110 90 70 50 30 10 0 1000 6000 10000 14000 18000 22000 26000 30000 34000 40000 Frequency (MHz) 117 110 90 70 50 30 10 0 1000 6000 10000 14000 18000 22000 26000 30000 34000 40000 Frequency (MHz) 117 110 90 70 50 30 10 0 1000 6000 10000 14000 18000 22000 26000 30000 34000 40000 Frequency (MHz) 117 110 90 70 50 30 10 0 1000 6000 10000 14000 18000 22000 26000 30000 34000 40000 Frequency (MHz) 117 110 90 70 50 30 10 0 1000 6000 10000 14000 18000 22000 26000 30000 34000 40000 Frequency (MHz) 117 110 90 70 50 30 10 0 1000 6000 10000 14000 18000 22000 26000 30000 34000 40000 Frequency (MHz) 117 110 90 70 50 30 10 0 1000 6000 10000 14000 18000 22000 26000 30000 34000 40000 Frequency (MHz) 117 110 90 70 50 30 10 0 1000 6000 10000 14000 18000 22000 26000 30000 34000 40000 Frequency (MHz) 117 110 90 70 50 30 10 0 1000 6000 10000 14000 18000 22000 26000 30000 34000 40000 Frequency (MHz) 117 110 90 70 50 30 10 0 1000 6000 10000 14000 18000 22000 26000 30000 34000 40000 Frequency (MHz) 117 110 90 70 50 30 10 0 1000 6000 10000 14000 18000 22000 26000 30000 34000 40000 Frequency (MHz) 117 110 90 70 50 30 10 0 1000 6000 10000 14000 18000 22000 26000 30000 34000 40000 Frequency (MHz) 117 110 90 70 50 30 10 0 1000 6000 10000 14000 18000 22000 26000 30000 34000 40000 Frequency (MHz) 117 110 90 70 50 30 10 0 1000 6000 10000 14000 18000 22000 26000 30000 34000 40000 Frequency (MHz) 117 110 90 70 50 30 10 0 1000 6000 10000 14000 18000 22000 26000 30000 34000 40000 Frequency (MHz) 117 110 90 70 50 30 10 0 1000 6000 10000 14000 18000 22000 26000 30000 34000 40000 Frequency (MHz) 117 110 90 70 50 30 10 0 1000 6000 10000 14000 18000 22000 26000 30000 34000 40000 Frequency (MHz) 117 110 90 70 50 30 10 0 1000 6000 10000 14000 18000 22000 26000 30000 34000 40000 Frequency (MHz) 117 110 90 70 50 30 10 0 1000 6000 10000 14000 18000 22000 26000 30000 34000 40000 Frequency (MHz) 117 110 90 70 50 30 10 0 1000 6000 10000 14000 18000 22000 26000 30000 34000 40000 Frequency (MHz) 117 110 90 70 50 30 10 0 1000 6000 10000 14000 18000 22000 26000 30000 34000 40000 Frequency (MHz) 117 110 90 70 50 30 10 0 1000 6000 10000 14000 18000 22000 26000 30000 34000 40000 Frequency (MHz) 117 110 90 70 50 30 10 0 1000 6000 10000 14000 18000 22000 26000 30000 34000 40000 Frequency (MHz) 117 110 90 70 50 30 10 0 1000 6000 10000 14000 18000 22000 26000 30000 34000 40000 Frequency (MHz) 117 110 90 70 50 30 10 0 1000 6000 10000 14000 18000 22000 26000 30000 34000 40000 Frequency (MHz) 117 110 90 70 50 30 10 0 1000 6000 10000 14000 18000 22000 26000 30000 34000 40000 Frequency (MHz) 117 110 90 70 50 30 10 0 1000 6000 10000 14000 18000 22000 26000 30000 34000 40000 Frequency (MHz) 117 110 90 70 50 30 10 0 1000 6000 10000 14000 18000 22000 26000 30000 34000 40000 Frequency (MHz) 117 110 90 70 50 30 10 0 1000 6000 10000 14000 18000 22000 26000 30000 34000 40000 Frequency (MHz) 117 110 90 70 50 30 10 0 1000 6000 10000 14000 18000 22000 26000 30000 34000 40000 Frequency (MHz) 117 110 90 70 50 30 10 0 1000 6000 10000 14000 18000 22000 26000 30000 34000 40000 Frequency (MHz) 117 110 90 70 50 30 10 0 1000 6000 10000 14000 18000 22000 26000 30000 34000 40000 Frequency (MHz) 117 110 90 70 50 30 10 0 1000 6000 10000 14000 18000 22000 26000 30000 34000 40000 Frequency (MHz) 117 110 90 70 50 30 10 0 1000 6000 10000 14000 18000 22000 26000 30000 34000 40000 Frequency (MHz) 117 110 90 70 50 30 10 0 1000 6000 10000 14000 18000 22000 26000 30000 34000 40000 Frequency (MHz) 117 110 90 70 50 30 10 0 1000 6000 10000 14000 18000 22000 26000 30000 34000 40000 Frequency (MHz) 117 110 90 70 50 30 10 0 1000 6000 10000 14000 18000 22000 26000 30000 34000 40000 Frequency (MHz) 117 110 90 70 50 30 10 0 1000 6000 10000 14000 18000 22000 26000 30000 34000 40000 Frequency (MHz) 117 110 90 70 50 30 10 0 1000 6000 10000 14000 18000 22000 26000 30000 34000 40000 Frequency (MHz) 117 110 90 70 50 30 10 0 1000 6000 10000 14000 18000 22000 26000 30000 34000 40000 Frequency (MHz) 117 110 90 70 50 30 10 0 1000 6000 10000 14000 18000 22000 26000 30000 34000 40000 Frequency (MHz) 117 110 90 70 50 30 10 0 1000 6000 10000 14000 18000 22000 26000 30000 34000 40000 Frequency (MHz) 117 110 90 70 50 30 10 0 1000 6000 10000 14000 18000 22000 26000 30000 34000 40000 Frequency (MHz) 117 110 90 70 50 30 10 0 1000 6000 10000 14000 18000 22000 26000 30000 34000 40000 Frequency (MHz) 117 110 90 70 50 30 10 0 1000 6000 10000 14000 18000 22000 26000 30000 34000 40000 Frequency (MHz) 117 110 90 70 50 30 10 0 1000 6000 10000 14000 18000 22000 26000 30000 34000 40000 Frequency (MHz) 117 110 90 70 50 30 10 0 1000 6000 10000 14000 18000 22000 26000 30000 34000 40000 Frequency (MHz) 117 110 90 70 50 30 10 0 1000 6000 10000 14000 18000 22000 26000 30000 34000 40000 Frequency (MHz) 117 110 90 70 50 30 10 0 1000			



International Certification Corp.

No. 3-1, Lane 6, Wen San 3rd St., Kwei Shan Hsiang, Tao Yuan Hsien 333, Taiwan, R.O.C.
Tel: 886-3-271-8666 Fax: 886-3-318-0155

Polarization	Vertical	Test Freq. (MHz)	5200
Test Configuration	2		

The graph displays the emission level in dBuV/m on the y-axis (0 to 117) against frequency in MHz on the x-axis (1000 to 40000). A red stepped line represents the FCC PART15E limit. A solid red line shows the average emission level, and a blue line shows the peak emission level. Five specific points are marked with blue vertical lines and labeled 1 through 5.

Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1050.00	35.86	54.00	-18.14	45.07	-9.21	Average	---	---
1050.00	46.41	74.00	-27.59	55.62	-9.21	Peak	---	---
5150.00	37.29	54.00	-16.71	32.35	4.94	Average	---	---
5150.00	51.67	74.00	-22.33	46.73	4.94	Peak	---	---
10400.00	65.41	68.30	-2.89	50.66	14.75	Peak	---	---

Note 1: “>20dB” means spurious emission levels that exceed the level of 20 dB below the applicable limit.

Note 2: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.



Polarization	Horizontal			Test Freq. (MHz)		5240																																																															
Test Configuration	2																																																																				
Level (dBuV/m) Frequency (MHz) <table><tr><th></th><th>Freq. MHz</th><th>Emission level dBuV/m</th><th>Limit dBuV/m</th><th>Margin dB</th><th>SA reading dBuV</th><th>Factor dB</th><th>Remark</th><th>ANT High cm</th><th>Turn Table deg</th></tr><tr><td>1</td><td>1050.00</td><td>35.44</td><td>54.00</td><td>-18.56</td><td>44.65</td><td>-9.21</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>2</td><td>1050.00</td><td>45.75</td><td>74.00</td><td>-28.25</td><td>54.96</td><td>-9.21</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>3</td><td>5150.00</td><td>35.23</td><td>54.00</td><td>-18.77</td><td>30.29</td><td>4.94</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>4</td><td>5150.00</td><td>48.36</td><td>74.00</td><td>-25.64</td><td>43.42</td><td>4.94</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>5</td><td>10480.00</td><td>61.15</td><td>68.30</td><td>-7.15</td><td>46.31</td><td>14.84</td><td>Peak</td><td>---</td><td>---</td></tr></table>											Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg	1	1050.00	35.44	54.00	-18.56	44.65	-9.21	Average	---	---	2	1050.00	45.75	74.00	-28.25	54.96	-9.21	Peak	---	---	3	5150.00	35.23	54.00	-18.77	30.29	4.94	Average	---	---	4	5150.00	48.36	74.00	-25.64	43.42	4.94	Peak	---	---	5	10480.00	61.15	68.30	-7.15	46.31	14.84	Peak	---	---
	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg																																																												
1	1050.00	35.44	54.00	-18.56	44.65	-9.21	Average	---	---																																																												
2	1050.00	45.75	74.00	-28.25	54.96	-9.21	Peak	---	---																																																												
3	5150.00	35.23	54.00	-18.77	30.29	4.94	Average	---	---																																																												
4	5150.00	48.36	74.00	-25.64	43.42	4.94	Peak	---	---																																																												
5	10480.00	61.15	68.30	-7.15	46.31	14.84	Peak	---	---																																																												
Note 1: “>20dB” means spurious emission levels that exceed the level of 20 dB below the applicable limit. Note 2: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.																																																																					



International Certification Corp.

No. 3-1, Lane 6, Wen San 3rd St., Kwei Shan Hsiang, Tao Yuan Hsien 333, Taiwan, R.O.C.

Tel: 886-3-271-8666

Fax: 886-3-318-0155

Polarization	Vertical			Test Freq. (MHz)			5240																																																														
Test Configuration	2																																																																				
Level (dBuV/m) Frequency (MHz) <table><thead><tr><th></th><th>Freq. MHz</th><th>Emission level dBuV/m</th><th>Limit dBuV/m</th><th>Margin dB</th><th>SA reading dBuV</th><th>Factor dB</th><th>Remark</th><th>ANT High cm</th><th>Turn Table deg</th></tr></thead><tbody><tr><td>1</td><td>1050.00</td><td>36.32</td><td>54.00</td><td>-17.68</td><td>45.53</td><td>-9.21</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>2</td><td>1050.00</td><td>47.10</td><td>74.00</td><td>-26.90</td><td>56.31</td><td>-9.21</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>3</td><td>5150.00</td><td>36.33</td><td>54.00</td><td>-17.67</td><td>31.39</td><td>4.94</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>4</td><td>5150.00</td><td>50.72</td><td>74.00</td><td>-23.28</td><td>45.78</td><td>4.94</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>5</td><td>10480.00</td><td>66.63</td><td>68.30</td><td>-1.67</td><td>51.79</td><td>14.84</td><td>Peak</td><td>---</td><td>---</td></tr></tbody></table>											Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg	1	1050.00	36.32	54.00	-17.68	45.53	-9.21	Average	---	---	2	1050.00	47.10	74.00	-26.90	56.31	-9.21	Peak	---	---	3	5150.00	36.33	54.00	-17.67	31.39	4.94	Average	---	---	4	5150.00	50.72	74.00	-23.28	45.78	4.94	Peak	---	---	5	10480.00	66.63	68.30	-1.67	51.79	14.84	Peak	---	---
	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg																																																												
1	1050.00	36.32	54.00	-17.68	45.53	-9.21	Average	---	---																																																												
2	1050.00	47.10	74.00	-26.90	56.31	-9.21	Peak	---	---																																																												
3	5150.00	36.33	54.00	-17.67	31.39	4.94	Average	---	---																																																												
4	5150.00	50.72	74.00	-23.28	45.78	4.94	Peak	---	---																																																												
5	10480.00	66.63	68.30	-1.67	51.79	14.84	Peak	---	---																																																												
Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit. Note 2: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.																																																																					



International Certification Corp.

No. 3-1, Lane 6, Wen San 3rd St., Kwei Shan Hsiang, Tao Yuan Hsien 333, Taiwan, R.O.C.

Tel: 886-3-271-8666

Fax: 886-3-318-0155

Polarization	Horizontal		Test Freq. (MHz)		5260																																																																								
Test Configuration	2																																																																												
Level (dBuV/m) Frequency (MHz) <table><thead><tr><th>Freq.</th><th>Emission level</th><th>Limit</th><th>Margin</th><th>SA reading</th><th>Factor</th><th>Remark</th><th>ANT High</th><th>Turn Table</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB</th><th></th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>1050.00</td><td>35.42</td><td>54.00</td><td>-18.58</td><td>44.63</td><td>-9.21</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>2</td><td>1050.00</td><td>45.08</td><td>74.00</td><td>-28.92</td><td>54.29</td><td>-9.21</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>3</td><td>5350.00</td><td>36.59</td><td>54.00</td><td>-17.41</td><td>31.50</td><td>5.09</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>4</td><td>5350.00</td><td>51.07</td><td>74.00</td><td>-22.93</td><td>45.98</td><td>5.09</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>5</td><td>10520.00</td><td>61.06</td><td>68.30</td><td>-7.24</td><td>46.19</td><td>14.87</td><td>Peak</td><td>---</td><td>---</td></tr></tbody></table>										Freq.	Emission level	Limit	Margin	SA reading	Factor	Remark	ANT High	Turn Table	MHz	dBuV/m	dBuV/m	dB	dBuV	dB		cm	deg	1	1050.00	35.42	54.00	-18.58	44.63	-9.21	Average	---	---	2	1050.00	45.08	74.00	-28.92	54.29	-9.21	Peak	---	---	3	5350.00	36.59	54.00	-17.41	31.50	5.09	Average	---	---	4	5350.00	51.07	74.00	-22.93	45.98	5.09	Peak	---	---	5	10520.00	61.06	68.30	-7.24	46.19	14.87	Peak	---	---
Freq.	Emission level	Limit	Margin	SA reading	Factor	Remark	ANT High	Turn Table																																																																					
MHz	dBuV/m	dBuV/m	dB	dBuV	dB		cm	deg																																																																					
1	1050.00	35.42	54.00	-18.58	44.63	-9.21	Average	---	---																																																																				
2	1050.00	45.08	74.00	-28.92	54.29	-9.21	Peak	---	---																																																																				
3	5350.00	36.59	54.00	-17.41	31.50	5.09	Average	---	---																																																																				
4	5350.00	51.07	74.00	-22.93	45.98	5.09	Peak	---	---																																																																				
5	10520.00	61.06	68.30	-7.24	46.19	14.87	Peak	---	---																																																																				
Note 1: “>20dB” means spurious emission levels that exceed the level of 20 dB below the applicable limit. Note 2: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.																																																																													



International Certification Corp.

No. 3-1, Lane 6, Wen San 3rd St., Kwei Shan Hsiang, Tao Yuan Hsien 333, Taiwan, R.O.C.

Tel: 886-3-271-8666

Fax: 886-3-318-0155

Polarization	Vertical			Test Freq. (MHz)		5260			
Test Configuration	2								
The graph displays the emission level in dBUV/m on the y-axis (0 to 117) against frequency in MHz on the x-axis (1000 to 40000). A red line represents the FCC PART15E limit, and a red line represents the FCC PART15E (AVG) limit. A blue line shows the measured emission level, which is generally below the limits. A vertical blue line is drawn at 10520.00 MHz, indicating a peak measurement point.									
	Freq.	Emission	Limit	Margin	SA	Factor	Remark	ANT	Turn
	MHz	level			reading			High	Table
		dBUV/m	dBUV/m	dB	dBUV	dB		cm	deg
1	1050.00	35.96	54.00	-18.04	45.17	-9.21	Average	---	---
2	1050.00	46.71	74.00	-27.29	55.92	-9.21	Peak	---	---
3	5350.00	40.79	54.00	-13.21	35.70	5.09	Average	---	---
4	5350.00	54.20	74.00	-19.80	49.11	5.09	Peak	---	---
5	10520.00	67.03	68.30	-1.27	52.16	14.87	Peak	---	---

Note 1: “>20dB” means spurious emission levels that exceed the level of 20 dB below the applicable limit.

Note 2: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.



International Certification Corp.

No. 3-1, Lane 6, Wen San 3rd St., Kwei Shan Hsiang, Tao Yuan Hsien 333, Taiwan, R.O.C.
Tel: 886-3-271-8666 Fax: 886-3-318-0155

Polarization	Horizontal	Test Freq. (MHz)	5300
Test Configuration	2		

Level (dBUV/m)

Frequency (MHz)

	Freq. MHz	Emission level dBUV/m	Limit dBUV/m	Margin dB	SA reading dBUV	Factor dB	Remark	ANT High cm	Turn Table deg
1	1050.00	35.11	54.00	-18.89	44.32	-9.21	Average	---	---
2	1050.00	45.70	74.00	-28.30	54.91	-9.21	Peak	---	---
3	5350.00	36.55	54.00	-17.45	31.46	5.09	Average	---	---
4	5350.00	50.07	74.00	-23.93	44.98	5.09	Peak	---	---
5	10600.00	47.52	54.00	-6.48	32.58	14.94	Average	---	---
6	10600.00	61.33	74.00	-12.67	46.39	14.94	Peak	---	---

Note 1: “>20dB” means spurious emission levels that exceed the level of 20 dB below the applicable limit.

Note 2: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.



International Certification Corp.

No. 3-1, Lane 6, Wen San 3rd St., Kwei Shan Hsiang, Tao Yuan Hsien 333, Taiwan, R.O.C.

Tel: 886-3-271-8666

Fax: 886-3-318-0155

Polarization	Vertical	Test Freq. (MHz)	5300																																																																						
Test Configuration	2																																																																								
The graph displays the emission level in dBuV/m on the y-axis (0 to 117) against frequency in MHz on the x-axis (1000 to 40000). A red line represents the FCC PART15E limit, which is 70 dBuV/m from 1000 to 10000 MHz and 50 dBuV/m from 10000 to 40000 MHz. A blue line represents the test results, showing a peak of 66.64 dBuV/m at 10600 MHz. The graph also includes a table of test results below it. <table><tr><th></th><th>Freq. MHz</th><th>Emission level dBuV/m</th><th>Limit dBuV/m</th><th>Margin dB</th><th>SA reading dBuV</th><th>Factor dB</th><th>Remark</th><th>ANT High cm</th><th>Turn Table deg</th></tr><tr><td>1</td><td>1050.00</td><td>36.27</td><td>54.00</td><td>-17.73</td><td>45.48</td><td>-9.21</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>2</td><td>1050.00</td><td>46.46</td><td>74.00</td><td>-27.54</td><td>55.67</td><td>-9.21</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>3</td><td>5350.00</td><td>41.36</td><td>54.00</td><td>-12.64</td><td>36.27</td><td>5.09</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>4</td><td>5350.00</td><td>54.78</td><td>74.00</td><td>-19.22</td><td>49.69</td><td>5.09</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>5</td><td>10600.00</td><td>52.89</td><td>54.00</td><td>-1.11</td><td>37.95</td><td>14.94</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>6</td><td>10600.00</td><td>66.64</td><td>74.00</td><td>-7.36</td><td>51.70</td><td>14.94</td><td>Peak</td><td>---</td><td>---</td></tr></table>					Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg	1	1050.00	36.27	54.00	-17.73	45.48	-9.21	Average	---	---	2	1050.00	46.46	74.00	-27.54	55.67	-9.21	Peak	---	---	3	5350.00	41.36	54.00	-12.64	36.27	5.09	Average	---	---	4	5350.00	54.78	74.00	-19.22	49.69	5.09	Peak	---	---	5	10600.00	52.89	54.00	-1.11	37.95	14.94	Average	---	---	6	10600.00	66.64	74.00	-7.36	51.70	14.94	Peak	---	---
	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg																																																																
1	1050.00	36.27	54.00	-17.73	45.48	-9.21	Average	---	---																																																																
2	1050.00	46.46	74.00	-27.54	55.67	-9.21	Peak	---	---																																																																
3	5350.00	41.36	54.00	-12.64	36.27	5.09	Average	---	---																																																																
4	5350.00	54.78	74.00	-19.22	49.69	5.09	Peak	---	---																																																																
5	10600.00	52.89	54.00	-1.11	37.95	14.94	Average	---	---																																																																
6	10600.00	66.64	74.00	-7.36	51.70	14.94	Peak	---	---																																																																
Note 1: “>20dB” means spurious emission levels that exceed the level of 20 dB below the applicable limit. Note 2: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.																																																																									



International Certification Corp.

No. 3-1, Lane 6, Wen San 3rd St., Kwei Shan Hsiang, Tao Yuan Hsien 333, Taiwan, R.O.C.
Tel: 886-3-271-8666 Fax: 886-3-318-0155

Polarization	Horizontal		Test Freq. (MHz)		5320																																																																																											
Test Configuration	2																																																																																															
Level (dBuV/m) 117 110 90 70 50 30 10 0 1000 6000 10000 14000 18000 22000 26000 30000 34000 40000 Frequency (MHz) FCC PART15E FCC PART15E (AVG) <table><thead><tr><th></th><th>Freq.</th><th>Emission</th><th>Limit</th><th>Margin</th><th>SA</th><th>Factor</th><th>Remark</th><th>ANT</th><th>Turn</th></tr><tr><th></th><th>MHz</th><th>level</th><th>dBuV/m</th><th>dB</th><th>reading</th><th>dB</th><th></th><th>High</th><th>Table</th></tr><tr><th></th><th></th><th>dBuV/m</th><th></th><th></th><th>dBuV</th><th></th><th></th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>1050.00</td><td>35.36</td><td>54.00</td><td>-18.64</td><td>44.57</td><td>-9.21</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>2</td><td>1050.00</td><td>45.75</td><td>74.00</td><td>-28.25</td><td>54.96</td><td>-9.21</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>3</td><td>5350.00</td><td>40.71</td><td>54.00</td><td>-13.29</td><td>35.62</td><td>5.09</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>4</td><td>5350.00</td><td>55.63</td><td>74.00</td><td>-18.37</td><td>50.54</td><td>5.09</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>5</td><td>10640.00</td><td>47.36</td><td>54.00</td><td>-6.64</td><td>32.38</td><td>14.98</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>6</td><td>10640.00</td><td>61.83</td><td>74.00</td><td>-12.17</td><td>46.85</td><td>14.98</td><td>Peak</td><td>---</td><td>---</td></tr></tbody></table>								Freq.	Emission	Limit	Margin	SA	Factor	Remark	ANT	Turn		MHz	level	dBuV/m	dB	reading	dB		High	Table			dBuV/m			dBuV			cm	deg	1	1050.00	35.36	54.00	-18.64	44.57	-9.21	Average	---	---	2	1050.00	45.75	74.00	-28.25	54.96	-9.21	Peak	---	---	3	5350.00	40.71	54.00	-13.29	35.62	5.09	Average	---	---	4	5350.00	55.63	74.00	-18.37	50.54	5.09	Peak	---	---	5	10640.00	47.36	54.00	-6.64	32.38	14.98	Average	---	---	6	10640.00	61.83	74.00	-12.17	46.85	14.98	Peak	---	---
	Freq.	Emission	Limit	Margin	SA	Factor	Remark	ANT	Turn																																																																																							
	MHz	level	dBuV/m	dB	reading	dB		High	Table																																																																																							
		dBuV/m			dBuV			cm	deg																																																																																							
1	1050.00	35.36	54.00	-18.64	44.57	-9.21	Average	---	---																																																																																							
2	1050.00	45.75	74.00	-28.25	54.96	-9.21	Peak	---	---																																																																																							
3	5350.00	40.71	54.00	-13.29	35.62	5.09	Average	---	---																																																																																							
4	5350.00	55.63	74.00	-18.37	50.54	5.09	Peak	---	---																																																																																							
5	10640.00	47.36	54.00	-6.64	32.38	14.98	Average	---	---																																																																																							
6	10640.00	61.83	74.00	-12.17	46.85	14.98	Peak	---	---																																																																																							
Note 1: “>20dB” means spurious emission levels that exceed the level of 20 dB below the applicable limit. Note 2: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.																																																																																																

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.
Note 2: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.




International Certification Corp.

No. 3-1, Lane 6, Wen San 3rd St., Kwei Shan Hsiang, Tao Yuan Hsien 333, Taiwan, R.O.C.

Tel: 886-3-271-8666

Fax: 886-3-318-0155

Polarization	Vertical	Test Freq. (MHz)	5320																																																																						
Test Configuration	2																																																																								
 <table><tr><th></th><th>Freq. MHz</th><th>Emission level dBuV/m</th><th>Limit dBuV/m</th><th>Margin dB</th><th>SA reading dBuV</th><th>Factor dB</th><th>Remark</th><th>ANT High cm</th><th>Turn Table deg</th></tr><tr><td>1</td><td>1050.00</td><td>35.90</td><td>54.00</td><td>-18.10</td><td>45.11</td><td>-9.21</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>2</td><td>1050.00</td><td>46.08</td><td>74.00</td><td>-27.92</td><td>55.29</td><td>-9.21</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>3</td><td>5350.00</td><td>47.79</td><td>54.00</td><td>-6.21</td><td>42.70</td><td>5.09</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>4</td><td>5350.00</td><td>64.04</td><td>74.00</td><td>-9.96</td><td>58.95</td><td>5.09</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>5</td><td>10640.00</td><td>52.93</td><td>54.00</td><td>-1.07</td><td>37.95</td><td>14.98</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>6</td><td>10640.00</td><td>67.66</td><td>74.00</td><td>-6.34</td><td>52.68</td><td>14.98</td><td>Peak</td><td>---</td><td>---</td></tr></table>					Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg	1	1050.00	35.90	54.00	-18.10	45.11	-9.21	Average	---	---	2	1050.00	46.08	74.00	-27.92	55.29	-9.21	Peak	---	---	3	5350.00	47.79	54.00	-6.21	42.70	5.09	Average	---	---	4	5350.00	64.04	74.00	-9.96	58.95	5.09	Peak	---	---	5	10640.00	52.93	54.00	-1.07	37.95	14.98	Average	---	---	6	10640.00	67.66	74.00	-6.34	52.68	14.98	Peak	---	---
	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg																																																																
1	1050.00	35.90	54.00	-18.10	45.11	-9.21	Average	---	---																																																																
2	1050.00	46.08	74.00	-27.92	55.29	-9.21	Peak	---	---																																																																
3	5350.00	47.79	54.00	-6.21	42.70	5.09	Average	---	---																																																																
4	5350.00	64.04	74.00	-9.96	58.95	5.09	Peak	---	---																																																																
5	10640.00	52.93	54.00	-1.07	37.95	14.98	Average	---	---																																																																
6	10640.00	67.66	74.00	-6.34	52.68	14.98	Peak	---	---																																																																
Note 1: “>20dB” means spurious emission levels that exceed the level of 20 dB below the applicable limit. Note 2: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.																																																																									



Polarization	Horizontal			Test Freq. (MHz)		5500																																																																																																																	
Test Configuration	2																																																																																																																						
Level (dBuV/m) <table><tr><th></th><th>Freq.</th><th>Emission</th><th>Limit</th><th>Margin</th><th>SA</th><th>Factor</th><th>Remark</th><th>ANT</th><th>Turn</th></tr><tr><th></th><th>MHz</th><th>level</th><th></th><th></th><th>reading</th><th></th><th></th><th>High</th><th>Table</th></tr><tr><th></th><th></th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB</th><th></th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>1050.00</td><td>35.18</td><td>54.00</td><td>-18.82</td><td>44.39</td><td>-9.21</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>2</td><td>1050.00</td><td>45.07</td><td>74.00</td><td>-28.93</td><td>54.28</td><td>-9.21</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>3</td><td>5460.00</td><td>38.13</td><td>54.00</td><td>-15.87</td><td>32.95</td><td>5.18</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>4</td><td>5460.00</td><td>54.18</td><td>74.00</td><td>-19.82</td><td>49.00</td><td>5.18</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>5</td><td>5470.00</td><td>44.28</td><td>54.00</td><td>-9.72</td><td>39.09</td><td>5.19</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>6</td><td>5470.00</td><td>60.99</td><td>74.00</td><td>-13.01</td><td>55.80</td><td>5.19</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>7</td><td>11000.00</td><td>49.23</td><td>54.00</td><td>-4.77</td><td>33.95</td><td>15.28</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>8</td><td>11000.00</td><td>62.53</td><td>74.00</td><td>-11.47</td><td>47.25</td><td>15.28</td><td>Peak</td><td>---</td><td>---</td></tr></table>											Freq.	Emission	Limit	Margin	SA	Factor	Remark	ANT	Turn		MHz	level			reading			High	Table			dBuV/m	dBuV/m	dB	dBuV	dB		cm	deg	1	1050.00	35.18	54.00	-18.82	44.39	-9.21	Average	---	---	2	1050.00	45.07	74.00	-28.93	54.28	-9.21	Peak	---	---	3	5460.00	38.13	54.00	-15.87	32.95	5.18	Average	---	---	4	5460.00	54.18	74.00	-19.82	49.00	5.18	Peak	---	---	5	5470.00	44.28	54.00	-9.72	39.09	5.19	Average	---	---	6	5470.00	60.99	74.00	-13.01	55.80	5.19	Peak	---	---	7	11000.00	49.23	54.00	-4.77	33.95	15.28	Average	---	---	8	11000.00	62.53	74.00	-11.47	47.25	15.28	Peak	---	---
	Freq.	Emission	Limit	Margin	SA	Factor	Remark	ANT	Turn																																																																																																														
	MHz	level			reading			High	Table																																																																																																														
		dBuV/m	dBuV/m	dB	dBuV	dB		cm	deg																																																																																																														
1	1050.00	35.18	54.00	-18.82	44.39	-9.21	Average	---	---																																																																																																														
2	1050.00	45.07	74.00	-28.93	54.28	-9.21	Peak	---	---																																																																																																														
3	5460.00	38.13	54.00	-15.87	32.95	5.18	Average	---	---																																																																																																														
4	5460.00	54.18	74.00	-19.82	49.00	5.18	Peak	---	---																																																																																																														
5	5470.00	44.28	54.00	-9.72	39.09	5.19	Average	---	---																																																																																																														
6	5470.00	60.99	74.00	-13.01	55.80	5.19	Peak	---	---																																																																																																														
7	11000.00	49.23	54.00	-4.77	33.95	15.28	Average	---	---																																																																																																														
8	11000.00	62.53	74.00	-11.47	47.25	15.28	Peak	---	---																																																																																																														
Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit. Note 2: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.																																																																																																																							



International Certification Corp.


No. 3-1, Lane 6, Wen San 3rd St., Kwei Shan Hsiang, Tao Yuan Hsien 333, Taiwan, R.O.C.
Tel: 886-3-271-8666 Fax: 886-3-318-0155

Polarization	Vertical	Test Freq. (MHz)	5500
Test Configuration	2		
Level (dBuV/m)			



International Certification Corp.

No. 3-1, Lane 6, Wen San 3rd St., Kwei Shan Hsiang, Tao Yuan Hsien 333, Taiwan, R.O.C.
Tel: 886-3-271-8666 Fax: 886-3-318-0155

Polarization	Horizontal			Test Freq. (MHz)		5580																																																																																													
Test Configuration	2																																																																																																		
 <table><tr><th></th><th>Freq.</th><th>Emission</th><th>Limit</th><th>Margin</th><th>SA</th><th>Factor</th><th>Remark</th><th>ANT</th><th>Turn</th></tr><tr><th></th><th>MHz</th><th>level</th><th>dBuV/m</th><th>dB</th><th>reading</th><th>dB</th><th></th><th>High</th><th>Table</th></tr><tr><th></th><th></th><th></th><th></th><th></th><th></th><th></th><th></th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>1050.00</td><td>35.64</td><td>54.00</td><td>-18.36</td><td>44.85</td><td>-9.21</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>2</td><td>1050.00</td><td>45.11</td><td>74.00</td><td>-28.89</td><td>54.32</td><td>-9.21</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>3</td><td>5418.50</td><td>36.25</td><td>54.00</td><td>-17.75</td><td>31.13</td><td>5.12</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>4</td><td>5418.50</td><td>49.80</td><td>74.00</td><td>-24.20</td><td>44.68</td><td>5.12</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>5</td><td>11160.00</td><td>49.20</td><td>54.00</td><td>-4.80</td><td>34.02</td><td>15.18</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>6</td><td>11160.00</td><td>62.52</td><td>74.00</td><td>-11.48</td><td>47.34</td><td>15.18</td><td>Peak</td><td>---</td><td>---</td></tr></table>											Freq.	Emission	Limit	Margin	SA	Factor	Remark	ANT	Turn		MHz	level	dBuV/m	dB	reading	dB		High	Table									cm	deg	1	1050.00	35.64	54.00	-18.36	44.85	-9.21	Average	---	---	2	1050.00	45.11	74.00	-28.89	54.32	-9.21	Peak	---	---	3	5418.50	36.25	54.00	-17.75	31.13	5.12	Average	---	---	4	5418.50	49.80	74.00	-24.20	44.68	5.12	Peak	---	---	5	11160.00	49.20	54.00	-4.80	34.02	15.18	Average	---	---	6	11160.00	62.52	74.00	-11.48	47.34	15.18	Peak	---	---
	Freq.	Emission	Limit	Margin	SA	Factor	Remark	ANT	Turn																																																																																										
	MHz	level	dBuV/m	dB	reading	dB		High	Table																																																																																										
								cm	deg																																																																																										
1	1050.00	35.64	54.00	-18.36	44.85	-9.21	Average	---	---																																																																																										
2	1050.00	45.11	74.00	-28.89	54.32	-9.21	Peak	---	---																																																																																										
3	5418.50	36.25	54.00	-17.75	31.13	5.12	Average	---	---																																																																																										
4	5418.50	49.80	74.00	-24.20	44.68	5.12	Peak	---	---																																																																																										
5	11160.00	49.20	54.00	-4.80	34.02	15.18	Average	---	---																																																																																										
6	11160.00	62.52	74.00	-11.48	47.34	15.18	Peak	---	---																																																																																										
Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit. Note 2: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.																																																																																																			



International Certification Corp.

No. 3-1, Lane 6, Wen San 3rd St., Kwei Shan Hsiang, Tao Yuan Hsien 333, Taiwan, R.O.C.
Tel: 886-3-271-8666 Fax: 886-3-318-0155

Polarization	Vertical	Test Freq. (MHz)	5580
Test Configuration	2		

Level (dBuV/m)

The graph displays the emission level in dBuV/m on the y-axis (0 to 117) against frequency in MHz on the x-axis (1000 to 40000). A red line represents the FCC PART15E limit, and a blue line represents the test results. The test results show a peak at 11160 MHz and an average at 11160 MHz. The graph also includes a table of test results.

	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	1050.00	36.17	54.00	-17.83	45.38	-9.21	Average	---	---
2	1050.00	46.40	74.00	-27.60	55.61	-9.21	Peak	---	---
3	5418.50	40.68	54.00	-13.32	35.56	5.12	Average	---	---
4	5418.50	52.82	74.00	-21.18	47.70	5.12	Peak	---	---
5	11160.00	51.81	54.00	-2.19	36.63	15.18	Average	---	---
6	11160.00	64.82	74.00	-9.18	49.64	15.18	Peak	---	---

Note 1: “>20dB” means spurious emission levels that exceed the level of 20 dB below the applicable limit.

Note 2: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.



International Certification Corp.

No. 3-1, Lane 6, Wen San 3rd St., Kwei Shan Hsiang, Tao Yuan Hsien 333, Taiwan, R.O.C.

Tel: 886-3-271-8666

Fax: 886-3-318-0155

Polarization	Horizontal		Test Freq. (MHz)		5700																																																																																				
Test Configuration	2																																																																																								
Level (dBUV/m) Frequency (MHz) <table><tr><th></th><th>Freq.</th><th>Emission level</th><th>Limit</th><th>Margin</th><th>SA reading</th><th>Factor</th><th>Remark</th><th>ANT High</th><th>Turn Table</th></tr><tr><th></th><th>MHz</th><th>dBUV/m</th><th>dBUV/m</th><th>dB</th><th>dBUV</th><th>dB</th><th></th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>1050.00</td><td>35.82</td><td>54.00</td><td>-18.18</td><td>45.03</td><td>-9.21</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>2</td><td>1050.00</td><td>45.91</td><td>74.00</td><td>-28.09</td><td>55.12</td><td>-9.21</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>3</td><td>5725.00</td><td>42.36</td><td>54.00</td><td>-11.64</td><td>36.80</td><td>5.56</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>4</td><td>5725.00</td><td>58.10</td><td>74.00</td><td>-15.90</td><td>52.54</td><td>5.56</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>5</td><td>11400.00</td><td>48.04</td><td>54.00</td><td>-5.96</td><td>33.01</td><td>15.03</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>6</td><td>11400.00</td><td>61.58</td><td>74.00</td><td>-12.42</td><td>46.55</td><td>15.03</td><td>Peak</td><td>---</td><td>---</td></tr></table>											Freq.	Emission level	Limit	Margin	SA reading	Factor	Remark	ANT High	Turn Table		MHz	dBUV/m	dBUV/m	dB	dBUV	dB		cm	deg	1	1050.00	35.82	54.00	-18.18	45.03	-9.21	Average	---	---	2	1050.00	45.91	74.00	-28.09	55.12	-9.21	Peak	---	---	3	5725.00	42.36	54.00	-11.64	36.80	5.56	Average	---	---	4	5725.00	58.10	74.00	-15.90	52.54	5.56	Peak	---	---	5	11400.00	48.04	54.00	-5.96	33.01	15.03	Average	---	---	6	11400.00	61.58	74.00	-12.42	46.55	15.03	Peak	---	---
	Freq.	Emission level	Limit	Margin	SA reading	Factor	Remark	ANT High	Turn Table																																																																																
	MHz	dBUV/m	dBUV/m	dB	dBUV	dB		cm	deg																																																																																
1	1050.00	35.82	54.00	-18.18	45.03	-9.21	Average	---	---																																																																																
2	1050.00	45.91	74.00	-28.09	55.12	-9.21	Peak	---	---																																																																																
3	5725.00	42.36	54.00	-11.64	36.80	5.56	Average	---	---																																																																																
4	5725.00	58.10	74.00	-15.90	52.54	5.56	Peak	---	---																																																																																
5	11400.00	48.04	54.00	-5.96	33.01	15.03	Average	---	---																																																																																
6	11400.00	61.58	74.00	-12.42	46.55	15.03	Peak	---	---																																																																																
Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit. Note 2: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.																																																																																									



International Certification Corp.

No. 3-1, Lane 6, Wen San 3rd St., Kwei Shan Hsiang, Tao Yuan Hsien 333, Taiwan, R.O.C.
Tel: 886-3-271-8666 Fax: 886-3-318-0155

Polarization	Vertical	Test Freq. (MHz)	5700																																																																																										
Test Configuration	2																																																																																												
Level (dBuV/m) 117 110 90 70 50 30 10 0 1000 6000 10000 14000 18000 22000 26000 30000 34000 40000 Frequency (MHz) 4 6 3 5 FCC PART15E (74) FCC PART15E (AVG) <table><tr><th></th><th>Freq.</th><th>Emission</th><th>Limit</th><th>Margin</th><th>SA</th><th>Factor</th><th>Remark</th><th>ANT</th><th>Turn</th></tr><tr><th></th><th>MHz</th><th>level</th><th></th><th></th><th>reading</th><th></th><th></th><th>High</th><th>Table</th></tr><tr><th></th><th></th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB</th><th></th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>1050.00</td><td>36.28</td><td>54.00</td><td>-17.72</td><td>45.49</td><td>-9.21</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>2</td><td>1050.00</td><td>46.63</td><td>74.00</td><td>-27.37</td><td>55.84</td><td>-9.21</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>3</td><td>5725.00</td><td>52.74</td><td>54.00</td><td>-1.26</td><td>47.18</td><td>5.56</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>4</td><td>5725.00</td><td>67.87</td><td>74.00</td><td>-6.13</td><td>62.31</td><td>5.56</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>5</td><td>11400.00</td><td>48.04</td><td>54.00</td><td>-5.96</td><td>33.01</td><td>15.03</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>6</td><td>11400.00</td><td>61.58</td><td>74.00</td><td>-12.42</td><td>46.55</td><td>15.03</td><td>Peak</td><td>---</td><td>---</td></tr></table>					Freq.	Emission	Limit	Margin	SA	Factor	Remark	ANT	Turn		MHz	level			reading			High	Table			dBuV/m	dBuV/m	dB	dBuV	dB		cm	deg	1	1050.00	36.28	54.00	-17.72	45.49	-9.21	Average	---	---	2	1050.00	46.63	74.00	-27.37	55.84	-9.21	Peak	---	---	3	5725.00	52.74	54.00	-1.26	47.18	5.56	Average	---	---	4	5725.00	67.87	74.00	-6.13	62.31	5.56	Peak	---	---	5	11400.00	48.04	54.00	-5.96	33.01	15.03	Average	---	---	6	11400.00	61.58	74.00	-12.42	46.55	15.03	Peak	---	---
	Freq.	Emission	Limit	Margin	SA	Factor	Remark	ANT	Turn																																																																																				
	MHz	level			reading			High	Table																																																																																				
		dBuV/m	dBuV/m	dB	dBuV	dB		cm	deg																																																																																				
1	1050.00	36.28	54.00	-17.72	45.49	-9.21	Average	---	---																																																																																				
2	1050.00	46.63	74.00	-27.37	55.84	-9.21	Peak	---	---																																																																																				
3	5725.00	52.74	54.00	-1.26	47.18	5.56	Average	---	---																																																																																				
4	5725.00	67.87	74.00	-6.13	62.31	5.56	Peak	---	---																																																																																				
5	11400.00	48.04	54.00	-5.96	33.01	15.03	Average	---	---																																																																																				
6	11400.00	61.58	74.00	-12.42	46.55	15.03	Peak	---	---																																																																																				
Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit. Note 2: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.																																																																																													



Polarization	Horizontal		Test Freq. (MHz)		5180																																																																
Test Configuration	3																																																																				
Level (dBuV/m) Frequency (MHz) <table><thead><tr><th></th><th>Freq. MHz</th><th>Emission level dBuV/m</th><th>Limit dBuV/m</th><th>Margin dB</th><th>SA reading dBuV</th><th>Factor dB</th><th>Remark</th><th>ANT High cm</th><th>Turn Table deg</th></tr></thead><tbody><tr><td>1</td><td>1050.00</td><td>35.62</td><td>54.00</td><td>-18.38</td><td>44.83</td><td>-9.21</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>2</td><td>1050.00</td><td>46.06</td><td>74.00</td><td>-27.94</td><td>55.27</td><td>-9.21</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>3</td><td>5150.00</td><td>47.05</td><td>54.00</td><td>-6.95</td><td>42.11</td><td>4.94</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>4</td><td>5150.00</td><td>63.87</td><td>74.00</td><td>-10.13</td><td>58.93</td><td>4.94</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>5</td><td>10360.00</td><td>61.18</td><td>68.30</td><td>-7.12</td><td>46.47</td><td>14.71</td><td>Peak</td><td>---</td><td>---</td></tr></tbody></table>											Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg	1	1050.00	35.62	54.00	-18.38	44.83	-9.21	Average	---	---	2	1050.00	46.06	74.00	-27.94	55.27	-9.21	Peak	---	---	3	5150.00	47.05	54.00	-6.95	42.11	4.94	Average	---	---	4	5150.00	63.87	74.00	-10.13	58.93	4.94	Peak	---	---	5	10360.00	61.18	68.30	-7.12	46.47	14.71	Peak	---	---
	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg																																																												
1	1050.00	35.62	54.00	-18.38	44.83	-9.21	Average	---	---																																																												
2	1050.00	46.06	74.00	-27.94	55.27	-9.21	Peak	---	---																																																												
3	5150.00	47.05	54.00	-6.95	42.11	4.94	Average	---	---																																																												
4	5150.00	63.87	74.00	-10.13	58.93	4.94	Peak	---	---																																																												
5	10360.00	61.18	68.30	-7.12	46.47	14.71	Peak	---	---																																																												
Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit. Note 2: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.																																																																					



International Certification Corp.

No. 3-1, Lane 6, Wen San 3rd St., Kwei Shan Hsiang, Tao Yuan Hsien 333, Taiwan, R.O.C.

Tel: 886-3-271-8666

Fax: 886-3-318-0155

Polarization	Vertical	Test Freq. (MHz)	5180																																																												
Test Configuration	3																																																														
Level (dBuV/m) Frequency (MHz) <table><tr><th></th><th>Freq. MHz</th><th>Emission level dBuV/m</th><th>Limit dBuV/m</th><th>Margin dB</th><th>SA reading dBuV</th><th>Factor dB</th><th>Remark</th><th>ANT High cm</th><th>Turn Table deg</th></tr><tr><td>1</td><td>1050.00</td><td>35.46</td><td>54.00</td><td>-18.54</td><td>44.67</td><td>-9.21</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>2</td><td>1050.00</td><td>46.17</td><td>74.00</td><td>-27.83</td><td>55.38</td><td>-9.21</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>3</td><td>5150.00</td><td>46.75</td><td>54.00</td><td>-7.25</td><td>41.81</td><td>4.94</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>4</td><td>5150.00</td><td>62.31</td><td>74.00</td><td>-11.69</td><td>57.37</td><td>4.94</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>5</td><td>10360.00</td><td>65.77</td><td>68.30</td><td>-2.53</td><td>51.06</td><td>14.71</td><td>Peak</td><td>---</td><td>---</td></tr></table>					Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg	1	1050.00	35.46	54.00	-18.54	44.67	-9.21	Average	---	---	2	1050.00	46.17	74.00	-27.83	55.38	-9.21	Peak	---	---	3	5150.00	46.75	54.00	-7.25	41.81	4.94	Average	---	---	4	5150.00	62.31	74.00	-11.69	57.37	4.94	Peak	---	---	5	10360.00	65.77	68.30	-2.53	51.06	14.71	Peak	---	---
	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg																																																						
1	1050.00	35.46	54.00	-18.54	44.67	-9.21	Average	---	---																																																						
2	1050.00	46.17	74.00	-27.83	55.38	-9.21	Peak	---	---																																																						
3	5150.00	46.75	54.00	-7.25	41.81	4.94	Average	---	---																																																						
4	5150.00	62.31	74.00	-11.69	57.37	4.94	Peak	---	---																																																						
5	10360.00	65.77	68.30	-2.53	51.06	14.71	Peak	---	---																																																						
Note 1: “>20dB” means spurious emission levels that exceed the level of 20 dB below the applicable limit. Note 2: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.																																																															



International Certification Corp.

No. 3-1, Lane 6, Wen San 3rd St., Kwei Shan Hsiang, Tao Yuan Hsien 333, Taiwan, R.O.C.

Tel: 886-3-271-8666

Fax: 886-3-318-0155

Polarization	Horizontal		Test Freq. (MHz)		5200																																																																
Test Configuration	3																																																																				
The graph displays the emission level in dBuV/m on the y-axis (0 to 117) against frequency in MHz on the x-axis (1000 to 40000). A red line represents the FCC PART15E limit, which is 70 dBuV/m for frequencies below 10 MHz and 54 dBuV/m for frequencies above 10 MHz. A red line labeled 'FCC PART15E (AVG)' is also shown at 54 dBuV/m. Blue vertical lines indicate test results at 1050 MHz (labeled 1), 1050 MHz (labeled 2), 5150 MHz (labeled 3), 5150 MHz (labeled 4), and 10400 MHz (labeled 5). The test results are summarized in the table below. <table><tr><th></th><th>Freq. MHz</th><th>Emission level dBuV/m</th><th>Limit dBuV/m</th><th>Margin dB</th><th>SA reading dBuV</th><th>Factor dB</th><th>Remark</th><th>ANT High cm</th><th>Turn Table deg</th></tr><tr><td>1</td><td>1050.00</td><td>35.48</td><td>54.00</td><td>-18.52</td><td>44.69</td><td>-9.21</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>2</td><td>1050.00</td><td>46.61</td><td>74.00</td><td>-27.39</td><td>55.82</td><td>-9.21</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>3</td><td>5150.00</td><td>37.99</td><td>54.00</td><td>-16.01</td><td>33.05</td><td>4.94</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>4</td><td>5150.00</td><td>53.73</td><td>74.00</td><td>-20.27</td><td>48.79</td><td>4.94</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>5</td><td>10400.00</td><td>60.51</td><td>68.30</td><td>-7.79</td><td>45.76</td><td>14.75</td><td>Peak</td><td>---</td><td>---</td></tr></table>											Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg	1	1050.00	35.48	54.00	-18.52	44.69	-9.21	Average	---	---	2	1050.00	46.61	74.00	-27.39	55.82	-9.21	Peak	---	---	3	5150.00	37.99	54.00	-16.01	33.05	4.94	Average	---	---	4	5150.00	53.73	74.00	-20.27	48.79	4.94	Peak	---	---	5	10400.00	60.51	68.30	-7.79	45.76	14.75	Peak	---	---
	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg																																																												
1	1050.00	35.48	54.00	-18.52	44.69	-9.21	Average	---	---																																																												
2	1050.00	46.61	74.00	-27.39	55.82	-9.21	Peak	---	---																																																												
3	5150.00	37.99	54.00	-16.01	33.05	4.94	Average	---	---																																																												
4	5150.00	53.73	74.00	-20.27	48.79	4.94	Peak	---	---																																																												
5	10400.00	60.51	68.30	-7.79	45.76	14.75	Peak	---	---																																																												
Note 1: “>20dB” means spurious emission levels that exceed the level of 20 dB below the applicable limit. Note 2: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.																																																																					



International Certification Corp.

No. 3-1, Lane 6, Wen San 3rd St., Kwei Shan Hsiang, Tao Yuan Hsien 333, Taiwan, R.O.C.

Tel: 886-3-271-8666

Fax: 886-3-318-0155

Polarization	Vertical	Test Freq. (MHz)	5200						
Test Configuration	3								
The graph displays the emission level in dBuV/m on the y-axis (ranging from 0 to 117) against frequency in MHz on the x-axis (ranging from 1000 to 40000). A red stepped line represents the FCC PART15E limit. A solid red line indicates the average level (FCC PART15E (AVG)) at approximately 55 dBuV/m. Blue vertical lines with markers at the top indicate specific test points: Point 1 at 1050 MHz (level ~35 dBuV/m), Point 2 at 1050 MHz (level ~46 dBuV/m), Point 3 at 5150 MHz (level ~36 dBuV/m), Point 4 at 5150 MHz (level ~50 dBuV/m), and Point 5 at 10400 MHz (level ~65 dBuV/m).									
	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	1050.00	35.30	54.00	-18.70	44.51	-9.21	Average	---	---
2	1050.00	46.15	74.00	-27.85	55.36	-9.21	Peak	---	---
3	5150.00	35.84	54.00	-18.16	30.90	4.94	Average	---	---
4	5150.00	50.17	74.00	-23.83	45.23	4.94	Peak	---	---
5	10400.00	65.44	68.30	-2.86	50.69	14.75	Peak	---	---

Note 1: “>20dB” means spurious emission levels that exceed the level of 20 dB below the applicable limit.

Note 2: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.




International Certification Corp.

No. 3-1, Lane 6, Wen San 3rd St., Kwei Shan Hsiang, Tao Yuan Hsien 333, Taiwan, R.O.C.

Tel: 886-3-271-8666

Fax: 886-3-318-0155

Polarization	Horizontal		Test Freq. (MHz)		5240																																																																																				
Test Configuration	3																																																																																								
 <table><tr><th></th><th>Freq.</th><th>Emission</th><th>Limit</th><th>Margin</th><th>SA</th><th>Factor</th><th>Remark</th><th>ANT</th><th>Turn</th></tr><tr><th></th><th>MHz</th><th>level</th><th>dBuV/m</th><th>dB</th><th>reading</th><th>dB</th><th></th><th>High</th><th>Table</th></tr><tr><th></th><th></th><th></th><th></th><th></th><th></th><th></th><th></th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>1050.00</td><td>35.72</td><td>54.00</td><td>-18.28</td><td>44.93</td><td>-9.21</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>2</td><td>1050.00</td><td>46.44</td><td>74.00</td><td>-27.56</td><td>55.65</td><td>-9.21</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>3</td><td>5150.00</td><td>36.44</td><td>54.00</td><td>-17.56</td><td>31.50</td><td>4.94</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>4</td><td>5150.00</td><td>49.64</td><td>74.00</td><td>-24.36</td><td>44.70</td><td>4.94</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>5</td><td>10480.00</td><td>61.09</td><td>68.30</td><td>-7.21</td><td>46.25</td><td>14.84</td><td>Peak</td><td>---</td><td>---</td></tr></table>											Freq.	Emission	Limit	Margin	SA	Factor	Remark	ANT	Turn		MHz	level	dBuV/m	dB	reading	dB		High	Table									cm	deg	1	1050.00	35.72	54.00	-18.28	44.93	-9.21	Average	---	---	2	1050.00	46.44	74.00	-27.56	55.65	-9.21	Peak	---	---	3	5150.00	36.44	54.00	-17.56	31.50	4.94	Average	---	---	4	5150.00	49.64	74.00	-24.36	44.70	4.94	Peak	---	---	5	10480.00	61.09	68.30	-7.21	46.25	14.84	Peak	---	---
	Freq.	Emission	Limit	Margin	SA	Factor	Remark	ANT	Turn																																																																																
	MHz	level	dBuV/m	dB	reading	dB		High	Table																																																																																
								cm	deg																																																																																
1	1050.00	35.72	54.00	-18.28	44.93	-9.21	Average	---	---																																																																																
2	1050.00	46.44	74.00	-27.56	55.65	-9.21	Peak	---	---																																																																																
3	5150.00	36.44	54.00	-17.56	31.50	4.94	Average	---	---																																																																																
4	5150.00	49.64	74.00	-24.36	44.70	4.94	Peak	---	---																																																																																
5	10480.00	61.09	68.30	-7.21	46.25	14.84	Peak	---	---																																																																																
Note 1: “>20dB” means spurious emission levels that exceed the level of 20 dB below the applicable limit. Note 2: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.																																																																																									



International Certification Corp.

No. 3-1, Lane 6, Wen San 3rd St., Kwei Shan Hsiang, Tao Yuan Hsien 333, Taiwan, R.O.C.

Tel: 886-3-271-8666

Fax: 886-3-318-0155

Polarization	Vertical	Test Freq. (MHz)	5240																																																												
Test Configuration	3																																																														
Level (dBuV/m) Frequency (MHz) <table><tr><th></th><th>Freq. MHz</th><th>Emission level dBuV/m</th><th>Limit dBuV/m</th><th>Margin dB</th><th>SA reading dBuV</th><th>Factor dB</th><th>Remark</th><th>ANT High cm</th><th>Turn Table deg</th></tr><tr><td>1</td><td>1050.00</td><td>35.38</td><td>54.00</td><td>-18.62</td><td>44.59</td><td>-9.21</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>2</td><td>1050.00</td><td>46.66</td><td>74.00</td><td>-27.34</td><td>55.87</td><td>-9.21</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>3</td><td>5150.00</td><td>34.08</td><td>54.00</td><td>-19.92</td><td>29.14</td><td>4.94</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>4</td><td>5150.00</td><td>48.97</td><td>74.00</td><td>-25.03</td><td>44.03</td><td>4.94</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>5</td><td>10480.00</td><td>65.51</td><td>68.30</td><td>-2.79</td><td>50.67</td><td>14.84</td><td>Peak</td><td>---</td><td>---</td></tr></table>					Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg	1	1050.00	35.38	54.00	-18.62	44.59	-9.21	Average	---	---	2	1050.00	46.66	74.00	-27.34	55.87	-9.21	Peak	---	---	3	5150.00	34.08	54.00	-19.92	29.14	4.94	Average	---	---	4	5150.00	48.97	74.00	-25.03	44.03	4.94	Peak	---	---	5	10480.00	65.51	68.30	-2.79	50.67	14.84	Peak	---	---
	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg																																																						
1	1050.00	35.38	54.00	-18.62	44.59	-9.21	Average	---	---																																																						
2	1050.00	46.66	74.00	-27.34	55.87	-9.21	Peak	---	---																																																						
3	5150.00	34.08	54.00	-19.92	29.14	4.94	Average	---	---																																																						
4	5150.00	48.97	74.00	-25.03	44.03	4.94	Peak	---	---																																																						
5	10480.00	65.51	68.30	-2.79	50.67	14.84	Peak	---	---																																																						
Note 1: “>20dB” means spurious emission levels that exceed the level of 20 dB below the applicable limit. Note 2: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.																																																															



International Certification Corp.

No. 3-1, Lane 6, Wen San 3rd St., Kwei Shan Hsiang, Tao Yuan Hsien 333, Taiwan, R.O.C.

Tel: 886-3-271-8666

Fax: 886-3-318-0155

Polarization	Vertical			Test Freq. (MHz)		5260																																																															
Test Configuration	3																																																																				
The graph displays the emission level in dBuV/m on the y-axis (0 to 117) against frequency in MHz on the x-axis (1000 to 40000). A red line represents the FCC PART15E limit, which is 70 dBuV/m for frequencies below 10 MHz and 50 dBuV/m for frequencies above 10 MHz. A blue line represents the test results, showing a peak at 10520 MHz. The test results are summarized in the table below: <table><tr><th></th><th>Freq. MHz</th><th>Emission level dBuV/m</th><th>Limit dBuV/m</th><th>Margin dB</th><th>SA reading dBuV</th><th>Factor dB</th><th>Remark</th><th>ANT High cm</th><th>Turn Table deg</th></tr><tr><td>1</td><td>1050.00</td><td>35.28</td><td>54.00</td><td>-18.72</td><td>44.49</td><td>-9.21</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>2</td><td>1050.00</td><td>46.05</td><td>74.00</td><td>-27.95</td><td>55.26</td><td>-9.21</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>3</td><td>5350.00</td><td>36.74</td><td>54.00</td><td>-17.26</td><td>31.65</td><td>5.09</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>4</td><td>5350.00</td><td>49.53</td><td>74.00</td><td>-24.47</td><td>44.44</td><td>5.09</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>5</td><td>10520.00</td><td>66.84</td><td>68.30</td><td>-1.46</td><td>51.97</td><td>14.87</td><td>Peak</td><td>---</td><td>---</td></tr></table>											Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg	1	1050.00	35.28	54.00	-18.72	44.49	-9.21	Average	---	---	2	1050.00	46.05	74.00	-27.95	55.26	-9.21	Peak	---	---	3	5350.00	36.74	54.00	-17.26	31.65	5.09	Average	---	---	4	5350.00	49.53	74.00	-24.47	44.44	5.09	Peak	---	---	5	10520.00	66.84	68.30	-1.46	51.97	14.87	Peak	---	---
	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg																																																												
1	1050.00	35.28	54.00	-18.72	44.49	-9.21	Average	---	---																																																												
2	1050.00	46.05	74.00	-27.95	55.26	-9.21	Peak	---	---																																																												
3	5350.00	36.74	54.00	-17.26	31.65	5.09	Average	---	---																																																												
4	5350.00	49.53	74.00	-24.47	44.44	5.09	Peak	---	---																																																												
5	10520.00	66.84	68.30	-1.46	51.97	14.87	Peak	---	---																																																												
Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit. Note 2: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.																																																																					



International Certification Corp.

No. 3-1, Lane 6, Wen San 3rd St., Kwei Shan Hsiang, Tao Yuan Hsien 333, Taiwan, R.O.C.

Tel: 886-3-271-8666

Fax: 886-3-318-0155

Polarization	Horizontal		Test Freq. (MHz)		5300				
Test Configuration	3								
The graph displays the emission level in dBuV/m on the y-axis (0 to 117) against frequency in MHz on the x-axis (1000 to 40000). A red line represents the FCC PART15E limit, and a red line represents the FCC PART15E (AVG) limit. Blue vertical lines indicate specific frequency points: 1050.00 MHz (point 1), 10600.00 MHz (point 2), 5350.00 MHz (point 3), 5350.00 MHz (point 4), 10600.00 MHz (point 5), and 10600.00 MHz (point 6). The emission level is generally below the limit, with some peaks near 10600 MHz.									
	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	1050.00	35.11	54.00	-18.89	44.32	-9.21	Average	---	---
2	1050.00	46.37	74.00	-27.63	55.58	-9.21	Peak	---	---
3	5350.00	40.24	54.00	-13.76	35.15	5.09	Average	---	---
4	5350.00	58.04	74.00	-15.96	52.95	5.09	Peak	---	---
5	10600.00	46.58	54.00	-7.42	31.64	14.94	Average	---	---
6	10600.00	60.23	74.00	-13.77	45.29	14.94	Peak	---	---

Note 1: “>20dB” means spurious emission levels that exceed the level of 20 dB below the applicable limit.

Note 2: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.




International Certification Corp.

No. 3-1, Lane 6, Wen San 3rd St., Kwei Shan Hsiang, Tao Yuan Hsien 333, Taiwan, R.O.C.

Tel: 886-3-271-8666

Fax: 886-3-318-0155

Polarization	Vertical	Test Freq. (MHz)	5300																																																																						
Test Configuration	3																																																																								
 <table><tr><th></th><th>Freq. MHz</th><th>Emission level dBuV/m</th><th>Limit dBuV/m</th><th>Margin dB</th><th>SA reading dBuV</th><th>Factor dB</th><th>Remark</th><th>ANT High cm</th><th>Turn Table deg</th></tr><tr><td>1</td><td>1050.00</td><td>35.64</td><td>54.00</td><td>-18.36</td><td>44.85</td><td>-9.21</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>2</td><td>1050.00</td><td>46.55</td><td>74.00</td><td>-27.45</td><td>55.76</td><td>-9.21</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>3</td><td>5350.00</td><td>37.03</td><td>54.00</td><td>-16.97</td><td>31.94</td><td>5.09</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>4</td><td>5350.00</td><td>50.18</td><td>74.00</td><td>-23.82</td><td>45.09</td><td>5.09</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>5</td><td>10600.00</td><td>52.84</td><td>54.00</td><td>-1.16</td><td>37.90</td><td>14.94</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>6</td><td>10600.00</td><td>67.02</td><td>74.00</td><td>-6.98</td><td>52.08</td><td>14.94</td><td>Peak</td><td>---</td><td>---</td></tr></table>					Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg	1	1050.00	35.64	54.00	-18.36	44.85	-9.21	Average	---	---	2	1050.00	46.55	74.00	-27.45	55.76	-9.21	Peak	---	---	3	5350.00	37.03	54.00	-16.97	31.94	5.09	Average	---	---	4	5350.00	50.18	74.00	-23.82	45.09	5.09	Peak	---	---	5	10600.00	52.84	54.00	-1.16	37.90	14.94	Average	---	---	6	10600.00	67.02	74.00	-6.98	52.08	14.94	Peak	---	---
	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg																																																																
1	1050.00	35.64	54.00	-18.36	44.85	-9.21	Average	---	---																																																																
2	1050.00	46.55	74.00	-27.45	55.76	-9.21	Peak	---	---																																																																
3	5350.00	37.03	54.00	-16.97	31.94	5.09	Average	---	---																																																																
4	5350.00	50.18	74.00	-23.82	45.09	5.09	Peak	---	---																																																																
5	10600.00	52.84	54.00	-1.16	37.90	14.94	Average	---	---																																																																
6	10600.00	67.02	74.00	-6.98	52.08	14.94	Peak	---	---																																																																
Note 1: “>20dB” means spurious emission levels that exceed the level of 20 dB below the applicable limit. Note 2: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.																																																																									




International Certification Corp.

No. 3-1, Lane 6, Wen San 3rd St., Kwei Shan Hsiang, Tao Yuan Hsien 333, Taiwan, R.O.C.

Tel: 886-3-271-8666

Fax: 886-3-318-0155

Polarization	Horizontal		Test Freq. (MHz)		5320																																																																																				
Test Configuration	3																																																																																								
Level (dBuV/m)  Frequency (MHz) <table><tr><th></th><th>Freq.</th><th>Emission level</th><th>Limit</th><th>Margin</th><th>SA reading</th><th>Factor</th><th>Remark</th><th>ANT High</th><th>Turn Table</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB</th><th></th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>1050.00</td><td>35.61</td><td>54.00</td><td>-18.39</td><td>44.82</td><td>-9.21</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>2</td><td>1050.00</td><td>46.42</td><td>74.00</td><td>-27.58</td><td>55.63</td><td>-9.21</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>3</td><td>5350.00</td><td>46.67</td><td>54.00</td><td>-7.33</td><td>41.58</td><td>5.09</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>4</td><td>5350.00</td><td>63.50</td><td>74.00</td><td>-10.50</td><td>58.41</td><td>5.09</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>5</td><td>10640.00</td><td>45.97</td><td>54.00</td><td>-8.03</td><td>30.99</td><td>14.98</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>6</td><td>10640.00</td><td>59.65</td><td>74.00</td><td>-14.35</td><td>44.67</td><td>14.98</td><td>Peak</td><td>---</td><td>---</td></tr></table>											Freq.	Emission level	Limit	Margin	SA reading	Factor	Remark	ANT High	Turn Table		MHz	dBuV/m	dBuV/m	dB	dBuV	dB		cm	deg	1	1050.00	35.61	54.00	-18.39	44.82	-9.21	Average	---	---	2	1050.00	46.42	74.00	-27.58	55.63	-9.21	Peak	---	---	3	5350.00	46.67	54.00	-7.33	41.58	5.09	Average	---	---	4	5350.00	63.50	74.00	-10.50	58.41	5.09	Peak	---	---	5	10640.00	45.97	54.00	-8.03	30.99	14.98	Average	---	---	6	10640.00	59.65	74.00	-14.35	44.67	14.98	Peak	---	---
	Freq.	Emission level	Limit	Margin	SA reading	Factor	Remark	ANT High	Turn Table																																																																																
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB		cm	deg																																																																																
1	1050.00	35.61	54.00	-18.39	44.82	-9.21	Average	---	---																																																																																
2	1050.00	46.42	74.00	-27.58	55.63	-9.21	Peak	---	---																																																																																
3	5350.00	46.67	54.00	-7.33	41.58	5.09	Average	---	---																																																																																
4	5350.00	63.50	74.00	-10.50	58.41	5.09	Peak	---	---																																																																																
5	10640.00	45.97	54.00	-8.03	30.99	14.98	Average	---	---																																																																																
6	10640.00	59.65	74.00	-14.35	44.67	14.98	Peak	---	---																																																																																
Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit. Note 2: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.																																																																																									



International Certification Corp.

No. 3-1, Lane 6, Wen San 3rd St., Kwei Shan Hsiang, Tao Yuan Hsien 333, Taiwan, R.O.C.
Tel: 886-3-271-8666 Fax: 886-3-318-0155

Polarization	Vertical		Test Freq. (MHz)		5320																																																																																														
Test Configuration	3																																																																																																		
Level (dBuV/m)  <table><tr><th></th><th>Freq.</th><th>Emission</th><th>Limit</th><th>Margin</th><th>SA</th><th>Factor</th><th>Remark</th><th>ANT</th><th>Turn</th></tr><tr><th></th><th>MHz</th><th>level</th><th>dBuV/m</th><th>dB</th><th>reading</th><th>dB</th><th></th><th>High</th><th>Table</th></tr><tr><th></th><th></th><th></th><th></th><th></th><th>dBuV</th><th></th><th></th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>1050.00</td><td>35.75</td><td>54.00</td><td>-18.25</td><td>44.96</td><td>-9.21</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>2</td><td>1050.00</td><td>46.81</td><td>74.00</td><td>-27.19</td><td>56.02</td><td>-9.21</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>3</td><td>5350.00</td><td>45.10</td><td>54.00</td><td>-8.90</td><td>40.01</td><td>5.09</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>4</td><td>5350.00</td><td>61.27</td><td>74.00</td><td>-12.73</td><td>56.18</td><td>5.09</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>5</td><td>10640.00</td><td>52.77</td><td>54.00</td><td>-1.23</td><td>37.79</td><td>14.98</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>6</td><td>10640.00</td><td>66.72</td><td>74.00</td><td>-7.28</td><td>51.74</td><td>14.98</td><td>Peak</td><td>---</td><td>---</td></tr></table>											Freq.	Emission	Limit	Margin	SA	Factor	Remark	ANT	Turn		MHz	level	dBuV/m	dB	reading	dB		High	Table						dBuV			cm	deg	1	1050.00	35.75	54.00	-18.25	44.96	-9.21	Average	---	---	2	1050.00	46.81	74.00	-27.19	56.02	-9.21	Peak	---	---	3	5350.00	45.10	54.00	-8.90	40.01	5.09	Average	---	---	4	5350.00	61.27	74.00	-12.73	56.18	5.09	Peak	---	---	5	10640.00	52.77	54.00	-1.23	37.79	14.98	Average	---	---	6	10640.00	66.72	74.00	-7.28	51.74	14.98	Peak	---	---
	Freq.	Emission	Limit	Margin	SA	Factor	Remark	ANT	Turn																																																																																										
	MHz	level	dBuV/m	dB	reading	dB		High	Table																																																																																										
					dBuV			cm	deg																																																																																										
1	1050.00	35.75	54.00	-18.25	44.96	-9.21	Average	---	---																																																																																										
2	1050.00	46.81	74.00	-27.19	56.02	-9.21	Peak	---	---																																																																																										
3	5350.00	45.10	54.00	-8.90	40.01	5.09	Average	---	---																																																																																										
4	5350.00	61.27	74.00	-12.73	56.18	5.09	Peak	---	---																																																																																										
5	10640.00	52.77	54.00	-1.23	37.79	14.98	Average	---	---																																																																																										
6	10640.00	66.72	74.00	-7.28	51.74	14.98	Peak	---	---																																																																																										
Note 1: “>20dB” means spurious emission levels that exceed the level of 20 dB below the applicable limit. Note 2: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.																																																																																																			



Polarization	Horizontal			Test Freq. (MHz)		5500																																																																																													
Test Configuration	3																																																																																																		
Level (dBuV/m) Frequency (MHz) <table><thead><tr><th></th><th>Freq. MHz</th><th>Emission level dBuV/m</th><th>Limit dBuV/m</th><th>Margin dB</th><th>SA reading dBuV</th><th>Factor dB</th><th>Remark</th><th>ANT High cm</th><th>Turn Table deg</th></tr></thead><tbody><tr><td>1</td><td>1050.00</td><td>35.91</td><td>54.00</td><td>-18.09</td><td>45.12</td><td>-9.21</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>2</td><td>1050.00</td><td>46.82</td><td>74.00</td><td>-27.18</td><td>56.03</td><td>-9.21</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>3</td><td>5460.00</td><td>43.82</td><td>54.00</td><td>-10.18</td><td>38.64</td><td>5.18</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>4</td><td>5460.00</td><td>59.76</td><td>74.00</td><td>-14.24</td><td>54.58</td><td>5.18</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>5</td><td>5470.00</td><td>50.14</td><td>54.00</td><td>-3.86</td><td>44.95</td><td>5.19</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>6</td><td>5470.00</td><td>66.43</td><td>74.00</td><td>-7.57</td><td>61.24</td><td>5.19</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>7</td><td>11000.00</td><td>49.02</td><td>54.00</td><td>-4.98</td><td>33.74</td><td>15.28</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>8</td><td>11000.00</td><td>61.44</td><td>74.00</td><td>-12.56</td><td>46.16</td><td>15.28</td><td>Peak</td><td>---</td><td>---</td></tr></tbody></table> Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit. Note 2: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.											Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg	1	1050.00	35.91	54.00	-18.09	45.12	-9.21	Average	---	---	2	1050.00	46.82	74.00	-27.18	56.03	-9.21	Peak	---	---	3	5460.00	43.82	54.00	-10.18	38.64	5.18	Average	---	---	4	5460.00	59.76	74.00	-14.24	54.58	5.18	Peak	---	---	5	5470.00	50.14	54.00	-3.86	44.95	5.19	Average	---	---	6	5470.00	66.43	74.00	-7.57	61.24	5.19	Peak	---	---	7	11000.00	49.02	54.00	-4.98	33.74	15.28	Average	---	---	8	11000.00	61.44	74.00	-12.56	46.16	15.28	Peak	---	---
	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg																																																																																										
1	1050.00	35.91	54.00	-18.09	45.12	-9.21	Average	---	---																																																																																										
2	1050.00	46.82	74.00	-27.18	56.03	-9.21	Peak	---	---																																																																																										
3	5460.00	43.82	54.00	-10.18	38.64	5.18	Average	---	---																																																																																										
4	5460.00	59.76	74.00	-14.24	54.58	5.18	Peak	---	---																																																																																										
5	5470.00	50.14	54.00	-3.86	44.95	5.19	Average	---	---																																																																																										
6	5470.00	66.43	74.00	-7.57	61.24	5.19	Peak	---	---																																																																																										
7	11000.00	49.02	54.00	-4.98	33.74	15.28	Average	---	---																																																																																										
8	11000.00	61.44	74.00	-12.56	46.16	15.28	Peak	---	---																																																																																										



International Certification Corp.

No. 3-1, Lane 6, Wen San 3rd St., Kwei Shan Hsiang, Tao Yuan Hsien 333, Taiwan, R.O.C.

Tel: 886-3-271-8666

Fax: 886-3-318-0155

Polarization	Vertical				Test Freq. (MHz)		5500																																																																																																																
Test Configuration	3																																																																																																																						
Level (dBuV/m) Frequency (MHz) <table><tr><th></th><th>Freq.</th><th>Emission</th><th>Limit</th><th>Margin</th><th>SA</th><th>Factor</th><th>Remark</th><th>ANT</th><th>Turn</th></tr><tr><th></th><th>MHz</th><th>level</th><th></th><th></th><th>reading</th><th></th><th></th><th>High</th><th>Table</th></tr><tr><th></th><th></th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB</th><th></th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>1050.00</td><td>35.68</td><td>54.00</td><td>-18.32</td><td>44.89</td><td>-9.21</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>2</td><td>1050.00</td><td>46.26</td><td>74.00</td><td>-27.74</td><td>55.47</td><td>-9.21</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>3</td><td>5460.00</td><td>43.95</td><td>54.00</td><td>-10.05</td><td>38.77</td><td>5.18</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>4</td><td>5460.00</td><td>57.64</td><td>74.00</td><td>-16.36</td><td>52.46</td><td>5.18</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>5</td><td>5470.00</td><td>49.88</td><td>54.00</td><td>-4.12</td><td>44.69</td><td>5.19</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>6</td><td>5470.00</td><td>65.84</td><td>74.00</td><td>-8.16</td><td>60.65</td><td>5.19</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>7</td><td>11000.00</td><td>52.22</td><td>54.00</td><td>-1.78</td><td>36.94</td><td>15.28</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>8</td><td>11000.00</td><td>63.76</td><td>74.00</td><td>-10.24</td><td>48.48</td><td>15.28</td><td>Peak</td><td>---</td><td>---</td></tr></table>											Freq.	Emission	Limit	Margin	SA	Factor	Remark	ANT	Turn		MHz	level			reading			High	Table			dBuV/m	dBuV/m	dB	dBuV	dB		cm	deg	1	1050.00	35.68	54.00	-18.32	44.89	-9.21	Average	---	---	2	1050.00	46.26	74.00	-27.74	55.47	-9.21	Peak	---	---	3	5460.00	43.95	54.00	-10.05	38.77	5.18	Average	---	---	4	5460.00	57.64	74.00	-16.36	52.46	5.18	Peak	---	---	5	5470.00	49.88	54.00	-4.12	44.69	5.19	Average	---	---	6	5470.00	65.84	74.00	-8.16	60.65	5.19	Peak	---	---	7	11000.00	52.22	54.00	-1.78	36.94	15.28	Average	---	---	8	11000.00	63.76	74.00	-10.24	48.48	15.28	Peak	---	---
	Freq.	Emission	Limit	Margin	SA	Factor	Remark	ANT	Turn																																																																																																														
	MHz	level			reading			High	Table																																																																																																														
		dBuV/m	dBuV/m	dB	dBuV	dB		cm	deg																																																																																																														
1	1050.00	35.68	54.00	-18.32	44.89	-9.21	Average	---	---																																																																																																														
2	1050.00	46.26	74.00	-27.74	55.47	-9.21	Peak	---	---																																																																																																														
3	5460.00	43.95	54.00	-10.05	38.77	5.18	Average	---	---																																																																																																														
4	5460.00	57.64	74.00	-16.36	52.46	5.18	Peak	---	---																																																																																																														
5	5470.00	49.88	54.00	-4.12	44.69	5.19	Average	---	---																																																																																																														
6	5470.00	65.84	74.00	-8.16	60.65	5.19	Peak	---	---																																																																																																														
7	11000.00	52.22	54.00	-1.78	36.94	15.28	Average	---	---																																																																																																														
8	11000.00	63.76	74.00	-10.24	48.48	15.28	Peak	---	---																																																																																																														
Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit. Note 2: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.																																																																																																																							



International Certification Corp.

No. 3-1, Lane 6, Wen San 3rd St., Kwei Shan Hsiang, Tao Yuan Hsien 333, Taiwan, R.O.C.

Tel: 886-3-271-8666

Fax: 886-3-318-0155

Polarization	Horizontal		Test Freq. (MHz)		5580																																																																							
Test Configuration	3																																																																											
The graph displays the emission level in dBuV/m on the y-axis (0 to 117) against frequency in MHz on the x-axis (1000 to 40000). A red line represents the FCC PART15E limit, which is 70 dBuV/m for frequencies below 30 MHz and 54 dBuV/m for frequencies above 30 MHz. A blue line represents the test results, showing a peak at 11160 MHz. The graph also includes a table of test results. <table><tr><th></th><th>Freq. MHz</th><th>Emission level dBuV/m</th><th>Limit dBuV/m</th><th>Margin dB</th><th>SA reading dBuV</th><th>Factor dB</th><th>Remark</th><th>ANT High cm</th><th>Turn Table deg</th></tr><tr><td>1</td><td>1050.00</td><td>35.51</td><td>54.00</td><td>-18.49</td><td>44.72</td><td>-9.21</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>2</td><td>1050.00</td><td>46.70</td><td>74.00</td><td>-27.30</td><td>55.91</td><td>-9.21</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>3</td><td>5418.50</td><td>38.24</td><td>54.00</td><td>-15.76</td><td>33.12</td><td>5.12</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>4</td><td>5418.50</td><td>51.50</td><td>74.00</td><td>-22.50</td><td>46.38</td><td>5.12</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>5</td><td>11160.00</td><td>45.83</td><td>54.00</td><td>-8.17</td><td>30.65</td><td>15.18</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>6</td><td>11160.00</td><td>59.94</td><td>74.00</td><td>-14.06</td><td>44.76</td><td>15.18</td><td>Peak</td><td>---</td><td>---</td></tr></table>								Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg	1	1050.00	35.51	54.00	-18.49	44.72	-9.21	Average	---	---	2	1050.00	46.70	74.00	-27.30	55.91	-9.21	Peak	---	---	3	5418.50	38.24	54.00	-15.76	33.12	5.12	Average	---	---	4	5418.50	51.50	74.00	-22.50	46.38	5.12	Peak	---	---	5	11160.00	45.83	54.00	-8.17	30.65	15.18	Average	---	---	6	11160.00	59.94	74.00	-14.06	44.76	15.18	Peak	---	---
	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg																																																																			
1	1050.00	35.51	54.00	-18.49	44.72	-9.21	Average	---	---																																																																			
2	1050.00	46.70	74.00	-27.30	55.91	-9.21	Peak	---	---																																																																			
3	5418.50	38.24	54.00	-15.76	33.12	5.12	Average	---	---																																																																			
4	5418.50	51.50	74.00	-22.50	46.38	5.12	Peak	---	---																																																																			
5	11160.00	45.83	54.00	-8.17	30.65	15.18	Average	---	---																																																																			
6	11160.00	59.94	74.00	-14.06	44.76	15.18	Peak	---	---																																																																			
Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit. Note 2: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.																																																																												



International Certification Corp.

No. 3-1, Lane 6, Wen San 3rd St., Kwei Shan Hsiang, Tao Yuan Hsien 333, Taiwan, R.O.C.
Tel: 886-3-271-8666 Fax: 886-3-318-0155

Polarization	Vertical			Test Freq. (MHz)		5580			
Test Configuration	3								
The graph displays the emission level in dBuV/m on the y-axis (0 to 117) against frequency in MHz on the x-axis (1000 to 40000). A red line represents the FCC PART15E limit, and a red line represents the FCC PART15E (AVG) limit. Blue vertical lines indicate specific measurement points labeled 3, 4, 5, and 6. The emission level is generally below the limit, with a peak at 11160.00 MHz.									
	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	1050.00	35.47	54.00	-18.53	44.68	-9.21	Average	---	---
2	1050.00	46.32	74.00	-27.68	55.53	-9.21	Peak	---	---
3	5418.50	32.16	54.00	-21.84	27.04	5.12	Average	---	---
4	5418.50	48.09	74.00	-25.91	42.97	5.12	Peak	---	---
5	11160.00	50.81	54.00	-3.19	35.63	15.18	Average	---	---
6	11160.00	63.47	74.00	-10.53	48.29	15.18	Peak	---	---

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.

Note 2: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.




International Certification Corp.


No. 3-1, Lane 6, Wen San 3rd St., Kwei Shan Hsiang, Tao Yuan Hsien 333, Taiwan, R.O.C.

Tel: 886-3-271-8666

Fax: 886-3-318-0155


Polarization	Horizontal		Test Freq. (MHz)		5700																																																																
Test Configuration	3																																																																				
 <table><tr><th></th><th>Freq. MHz</th><th>Emission level dBuV/m</th><th>Limit dBuV/m</th><th>Margin dB</th><th>SA reading dBuV</th><th>Factor dB</th><th>Remark</th><th>ANT High cm</th><th>Turn Table deg</th></tr><tr><td>1</td><td>1050.00</td><td>36.07</td><td>54.00</td><td>-17.93</td><td>45.28</td><td>-9.21</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>2</td><td>1050.00</td><td>46.72</td><td>74.00</td><td>-27.28</td><td>55.93</td><td>-9.21</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>3</td><td>5725.00</td><td>66.14</td><td>68.30</td><td>-2.16</td><td>60.58</td><td>5.56</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>4</td><td>11400.00</td><td>44.02</td><td>54.00</td><td>-9.98</td><td>28.99</td><td>15.03</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>5</td><td>11400.00</td><td>57.54</td><td>74.00</td><td>-16.46</td><td>42.51</td><td>15.03</td><td>Peak</td><td>---</td><td>---</td></tr></table>											Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg	1	1050.00	36.07	54.00	-17.93	45.28	-9.21	Average	---	---	2	1050.00	46.72	74.00	-27.28	55.93	-9.21	Peak	---	---	3	5725.00	66.14	68.30	-2.16	60.58	5.56	Peak	---	---	4	11400.00	44.02	54.00	-9.98	28.99	15.03	Average	---	---	5	11400.00	57.54	74.00	-16.46	42.51	15.03	Peak	---	---
	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg																																																												
1	1050.00	36.07	54.00	-17.93	45.28	-9.21	Average	---	---																																																												
2	1050.00	46.72	74.00	-27.28	55.93	-9.21	Peak	---	---																																																												
3	5725.00	66.14	68.30	-2.16	60.58	5.56	Peak	---	---																																																												
4	11400.00	44.02	54.00	-9.98	28.99	15.03	Average	---	---																																																												
5	11400.00	57.54	74.00	-16.46	42.51	15.03	Peak	---	---																																																												
Note 1: “>20dB” means spurious emission levels that exceed the level of 20 dB below the applicable limit. Note 2: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.																																																																					



Polarization	Vertical		Test Freq. (MHz)		5700																																																																																				
Test Configuration	3																																																																																								
Level (dBuV/m)  Frequency (MHz) <table><tr><th></th><th>Freq.</th><th>Emission</th><th>Limit</th><th>Margin</th><th>SA</th><th>Factor</th><th>Remark</th><th>ANT</th><th>Turn</th></tr><tr><th></th><th>MHz</th><th>level</th><th></th><th></th><th>reading</th><th></th><th></th><th>High</th><th>Table</th></tr><tr><th></th><th></th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB</th><th></th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>1050.00</td><td>35.03</td><td>54.00</td><td>-18.97</td><td>44.24</td><td>-9.21</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>2</td><td>1050.00</td><td>46.44</td><td>74.00</td><td>-27.56</td><td>55.65</td><td>-9.21</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>3</td><td>5725.00</td><td>64.08</td><td>68.30</td><td>-4.22</td><td>58.52</td><td>5.56</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>4</td><td>11400.00</td><td>50.44</td><td>54.00</td><td>-3.56</td><td>35.41</td><td>15.03</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>5</td><td>11400.00</td><td>63.32</td><td>74.00</td><td>-10.68</td><td>48.29</td><td>15.03</td><td>Peak</td><td>---</td><td>---</td></tr></table>											Freq.	Emission	Limit	Margin	SA	Factor	Remark	ANT	Turn		MHz	level			reading			High	Table			dBuV/m	dBuV/m	dB	dBuV	dB		cm	deg	1	1050.00	35.03	54.00	-18.97	44.24	-9.21	Average	---	---	2	1050.00	46.44	74.00	-27.56	55.65	-9.21	Peak	---	---	3	5725.00	64.08	68.30	-4.22	58.52	5.56	Peak	---	---	4	11400.00	50.44	54.00	-3.56	35.41	15.03	Average	---	---	5	11400.00	63.32	74.00	-10.68	48.29	15.03	Peak	---	---
	Freq.	Emission	Limit	Margin	SA	Factor	Remark	ANT	Turn																																																																																
	MHz	level			reading			High	Table																																																																																
		dBuV/m	dBuV/m	dB	dBuV	dB		cm	deg																																																																																
1	1050.00	35.03	54.00	-18.97	44.24	-9.21	Average	---	---																																																																																
2	1050.00	46.44	74.00	-27.56	55.65	-9.21	Peak	---	---																																																																																
3	5725.00	64.08	68.30	-4.22	58.52	5.56	Peak	---	---																																																																																
4	11400.00	50.44	54.00	-3.56	35.41	15.03	Average	---	---																																																																																
5	11400.00	63.32	74.00	-10.68	48.29	15.03	Peak	---	---																																																																																
Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit. Note 2: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.																																																																																									



3.6.6 Transmitter Radiated Unwanted Emissions (Above 1GHz) for HT20

Polarization	Horizontal		Test Freq. (MHz)		5180																																																													
Test Configuration	1																																																																	
 <table><tr><th></th><th>Freq. MHz</th><th>Emission level dBUV/m</th><th>Limit dBUV/m</th><th>Margin dB</th><th>SA reading dBUV</th><th>Factor dB</th><th>Remark</th><th>ANT High cm</th><th>Turn Table deg</th></tr><tr><td>1</td><td>1050.00</td><td>35.48</td><td>54.00</td><td>-18.52</td><td>44.69</td><td>-9.21</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>2</td><td>1050.00</td><td>46.39</td><td>74.00</td><td>-27.61</td><td>55.60</td><td>-9.21</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>3</td><td>5150.00</td><td>44.35</td><td>54.00</td><td>-9.65</td><td>39.41</td><td>4.94</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>4</td><td>5150.00</td><td>63.45</td><td>74.00</td><td>-10.55</td><td>58.51</td><td>4.94</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>5</td><td>10360.00</td><td>60.15</td><td>68.30</td><td>-8.15</td><td>45.44</td><td>14.71</td><td>Peak</td><td>---</td><td>---</td></tr></table>								Freq. MHz	Emission level dBUV/m	Limit dBUV/m	Margin dB	SA reading dBUV	Factor dB	Remark	ANT High cm	Turn Table deg	1	1050.00	35.48	54.00	-18.52	44.69	-9.21	Average	---	---	2	1050.00	46.39	74.00	-27.61	55.60	-9.21	Peak	---	---	3	5150.00	44.35	54.00	-9.65	39.41	4.94	Average	---	---	4	5150.00	63.45	74.00	-10.55	58.51	4.94	Peak	---	---	5	10360.00	60.15	68.30	-8.15	45.44	14.71	Peak	---	---
	Freq. MHz	Emission level dBUV/m	Limit dBUV/m	Margin dB	SA reading dBUV	Factor dB	Remark	ANT High cm	Turn Table deg																																																									
1	1050.00	35.48	54.00	-18.52	44.69	-9.21	Average	---	---																																																									
2	1050.00	46.39	74.00	-27.61	55.60	-9.21	Peak	---	---																																																									
3	5150.00	44.35	54.00	-9.65	39.41	4.94	Average	---	---																																																									
4	5150.00	63.45	74.00	-10.55	58.51	4.94	Peak	---	---																																																									
5	10360.00	60.15	68.30	-8.15	45.44	14.71	Peak	---	---																																																									
Note 1: “>20dB” means spurious emission levels that exceed the level of 20 dB below the applicable limit. Note 2: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.																																																																		



International Certification Corp.

No. 3-1, Lane 6, Wen San 3rd St., Kwei Shan Hsiang, Tao Yuan Hsien 333, Taiwan, R.O.C.

Tel: 886-3-271-8666

Fax: 886-3-318-0155

Polarization	Horizontal		Test Freq. (MHz)		5200																																																																
Test Configuration	1																																																																				
Level (dBuV/m) Frequency (MHz) <table><thead><tr><th></th><th>Freq. MHz</th><th>Emission level dBuV/m</th><th>Limit dBuV/m</th><th>Margin dB</th><th>SA reading dBuV</th><th>Factor dB</th><th>Remark</th><th>ANT High cm</th><th>Turn Table deg</th></tr></thead><tbody><tr><td>1</td><td>1050.00</td><td>35.31</td><td>54.00</td><td>-18.69</td><td>44.52</td><td>-9.21</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>2</td><td>1050.00</td><td>46.27</td><td>74.00</td><td>-27.73</td><td>55.48</td><td>-9.21</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>3</td><td>5150.00</td><td>44.26</td><td>54.00</td><td>-9.74</td><td>39.32</td><td>4.94</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>4</td><td>5150.00</td><td>54.39</td><td>74.00</td><td>-19.61</td><td>49.45</td><td>4.94</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>5</td><td>10400.00</td><td>60.47</td><td>68.30</td><td>-7.83</td><td>45.72</td><td>14.75</td><td>Peak</td><td>---</td><td>---</td></tr></tbody></table>											Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg	1	1050.00	35.31	54.00	-18.69	44.52	-9.21	Average	---	---	2	1050.00	46.27	74.00	-27.73	55.48	-9.21	Peak	---	---	3	5150.00	44.26	54.00	-9.74	39.32	4.94	Average	---	---	4	5150.00	54.39	74.00	-19.61	49.45	4.94	Peak	---	---	5	10400.00	60.47	68.30	-7.83	45.72	14.75	Peak	---	---
	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg																																																												
1	1050.00	35.31	54.00	-18.69	44.52	-9.21	Average	---	---																																																												
2	1050.00	46.27	74.00	-27.73	55.48	-9.21	Peak	---	---																																																												
3	5150.00	44.26	54.00	-9.74	39.32	4.94	Average	---	---																																																												
4	5150.00	54.39	74.00	-19.61	49.45	4.94	Peak	---	---																																																												
5	10400.00	60.47	68.30	-7.83	45.72	14.75	Peak	---	---																																																												
Note 1: “>20dB” means spurious emission levels that exceed the level of 20 dB below the applicable limit. Note 2: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.																																																																					



International Certification Corp.

No. 3-1, Lane 6, Wen San 3rd St., Kwei Shan Hsiang, Tao Yuan Hsien 333, Taiwan, R.O.C.

Tel: 886-3-271-8666


Fax: 886-3-318-0155

Polarization	Vertical		Test Freq. (MHz)		5200																																																													
Test Configuration	1																																																																	
Level (dBuV/m) Frequency (MHz) <table><tr><th></th><th>Freq. MHz</th><th>Emission level dBuV/m</th><th>Limit dBuV/m</th><th>Margin dB</th><th>SA reading dBuV</th><th>Factor dB</th><th>Remark</th><th>ANT High cm</th><th>Turn Table deg</th></tr><tr><td>1</td><td>1050.00</td><td>35.44</td><td>54.00</td><td>-18.56</td><td>44.65</td><td>-9.21</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>2</td><td>1050.00</td><td>46.57</td><td>74.00</td><td>-27.43</td><td>55.78</td><td>-9.21</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>3</td><td>5150.00</td><td>44.35</td><td>54.00</td><td>-9.65</td><td>39.41</td><td>4.94</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>4</td><td>5150.00</td><td>54.35</td><td>74.00</td><td>-19.65</td><td>49.41</td><td>4.94</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>5</td><td>10400.00</td><td>66.33</td><td>68.30</td><td>-1.97</td><td>51.58</td><td>14.75</td><td>Peak</td><td>---</td><td>---</td></tr></table>								Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg	1	1050.00	35.44	54.00	-18.56	44.65	-9.21	Average	---	---	2	1050.00	46.57	74.00	-27.43	55.78	-9.21	Peak	---	---	3	5150.00	44.35	54.00	-9.65	39.41	4.94	Average	---	---	4	5150.00	54.35	74.00	-19.65	49.41	4.94	Peak	---	---	5	10400.00	66.33	68.30	-1.97	51.58	14.75	Peak	---	---
	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg																																																									
1	1050.00	35.44	54.00	-18.56	44.65	-9.21	Average	---	---																																																									
2	1050.00	46.57	74.00	-27.43	55.78	-9.21	Peak	---	---																																																									
3	5150.00	44.35	54.00	-9.65	39.41	4.94	Average	---	---																																																									
4	5150.00	54.35	74.00	-19.65	49.41	4.94	Peak	---	---																																																									
5	10400.00	66.33	68.30	-1.97	51.58	14.75	Peak	---	---																																																									
Note 1: “>20dB” means spurious emission levels that exceed the level of 20 dB below the applicable limit. Note 2: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.																																																																		



International Certification Corp.

No. 3-1, Lane 6, Wen San 3rd St., Kwei Shan Hsiang, Tao Yuan Hsien 333, Taiwan, R.O.C.
Tel: 886-3-271-8666 Fax: 886-3-318-0155

Polarization	Horizontal			Test Freq. (MHz)		5240																																																															
Test Configuration	1																																																																				
 <table><tr><th></th><th>Freq. MHz</th><th>Emission level dBuV/m</th><th>Limit dBuV/m</th><th>Margin dB</th><th>SA reading dBuV</th><th>Factor dB</th><th>Remark</th><th>ANT High cm</th><th>Turn Table deg</th></tr><tr><td>1</td><td>1050.00</td><td>36.11</td><td>54.00</td><td>-17.89</td><td>45.32</td><td>-9.21</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>2</td><td>1050.00</td><td>46.76</td><td>74.00</td><td>-27.24</td><td>55.97</td><td>-9.21</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>3</td><td>5150.00</td><td>44.16</td><td>54.00</td><td>-9.84</td><td>39.22</td><td>4.94</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>4</td><td>5150.00</td><td>54.31</td><td>74.00</td><td>-19.69</td><td>49.37</td><td>4.94</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>5</td><td>10480.00</td><td>60.35</td><td>68.30</td><td>-7.95</td><td>45.51</td><td>14.84</td><td>Peak</td><td>---</td><td>---</td></tr></table>											Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg	1	1050.00	36.11	54.00	-17.89	45.32	-9.21	Average	---	---	2	1050.00	46.76	74.00	-27.24	55.97	-9.21	Peak	---	---	3	5150.00	44.16	54.00	-9.84	39.22	4.94	Average	---	---	4	5150.00	54.31	74.00	-19.69	49.37	4.94	Peak	---	---	5	10480.00	60.35	68.30	-7.95	45.51	14.84	Peak	---	---
	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg																																																												
1	1050.00	36.11	54.00	-17.89	45.32	-9.21	Average	---	---																																																												
2	1050.00	46.76	74.00	-27.24	55.97	-9.21	Peak	---	---																																																												
3	5150.00	44.16	54.00	-9.84	39.22	4.94	Average	---	---																																																												
4	5150.00	54.31	74.00	-19.69	49.37	4.94	Peak	---	---																																																												
5	10480.00	60.35	68.30	-7.95	45.51	14.84	Peak	---	---																																																												
Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit. Note 2: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.																																																																					



International Certification Corp.

No. 3-1, Lane 6, Wen San 3rd St., Kwei Shan Hsiang, Tao Yuan Hsien 333, Taiwan, R.O.C.
Tel: 886-3-271-8666 Fax: 886-3-318-0155

Polarization	Vertical			Test Freq. (MHz)		5240																																																																																			
Test Configuration	1																																																																																								
Level (dBuV/m) 117 110 90 70 50 30 10 0 1000 6000 10000 14000 18000 22000 26000 30000 34000 40000 Frequency (MHz) 4 3 5 FCC PART15E FCC PART15E (AVG) <table><thead><tr><th></th><th>Freq.</th><th>Emission</th><th>Limit</th><th>Margin</th><th>SA</th><th>Factor</th><th>Remark</th><th>ANT</th><th>Turn</th></tr><tr><th></th><th>MHz</th><th>level</th><th></th><th></th><th>reading</th><th></th><th></th><th>High</th><th>Table</th></tr><tr><th></th><th></th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB</th><th></th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>1050.00</td><td>35.68</td><td>54.00</td><td>-18.32</td><td>44.89</td><td>-9.21</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>2</td><td>1050.00</td><td>46.38</td><td>74.00</td><td>-27.62</td><td>55.59</td><td>-9.21</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>3</td><td>5150.00</td><td>44.25</td><td>54.00</td><td>-9.75</td><td>39.31</td><td>4.94</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>4</td><td>5150.00</td><td>54.35</td><td>74.00</td><td>-19.65</td><td>49.41</td><td>4.94</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>5</td><td>10480.00</td><td>66.58</td><td>68.30</td><td>-1.72</td><td>51.74</td><td>14.84</td><td>Peak</td><td>---</td><td>---</td></tr></tbody></table>											Freq.	Emission	Limit	Margin	SA	Factor	Remark	ANT	Turn		MHz	level			reading			High	Table			dBuV/m	dBuV/m	dB	dBuV	dB		cm	deg	1	1050.00	35.68	54.00	-18.32	44.89	-9.21	Average	---	---	2	1050.00	46.38	74.00	-27.62	55.59	-9.21	Peak	---	---	3	5150.00	44.25	54.00	-9.75	39.31	4.94	Average	---	---	4	5150.00	54.35	74.00	-19.65	49.41	4.94	Peak	---	---	5	10480.00	66.58	68.30	-1.72	51.74	14.84	Peak	---	---
	Freq.	Emission	Limit	Margin	SA	Factor	Remark	ANT	Turn																																																																																
	MHz	level			reading			High	Table																																																																																
		dBuV/m	dBuV/m	dB	dBuV	dB		cm	deg																																																																																
1	1050.00	35.68	54.00	-18.32	44.89	-9.21	Average	---	---																																																																																
2	1050.00	46.38	74.00	-27.62	55.59	-9.21	Peak	---	---																																																																																
3	5150.00	44.25	54.00	-9.75	39.31	4.94	Average	---	---																																																																																
4	5150.00	54.35	74.00	-19.65	49.41	4.94	Peak	---	---																																																																																
5	10480.00	66.58	68.30	-1.72	51.74	14.84	Peak	---	---																																																																																
Note 1: “>20dB” means spurious emission levels that exceed the level of 20 dB below the applicable limit. Note 2: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.																																																																																									



International Certification Corp.

No. 3-1, Lane 6, Wen San 3rd St., Kwei Shan Hsiang, Tao Yuan Hsien 333, Taiwan, R.O.C.

Tel: 886-3-271-8666

Fax: 886-3-318-0155

Polarization	Horizontal		Test Freq. (MHz)		5260																																																																
Test Configuration	1																																																																				
Level (dBuV/m) Frequency (MHz) <table><thead><tr><th></th><th>Freq. MHz</th><th>Emission level dBuV/m</th><th>Limit dBuV/m</th><th>Margin dB</th><th>SA reading dBuV</th><th>Factor dB</th><th>Remark</th><th>ANT High cm</th><th>Turn Table deg</th></tr></thead><tbody><tr><td>1</td><td>1050.00</td><td>35.36</td><td>54.00</td><td>-18.64</td><td>44.57</td><td>-9.21</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>2</td><td>1050.00</td><td>46.57</td><td>74.00</td><td>-27.43</td><td>55.78</td><td>-9.21</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>3</td><td>5350.00</td><td>44.36</td><td>54.00</td><td>-9.64</td><td>39.27</td><td>5.09</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>4</td><td>5350.00</td><td>55.26</td><td>74.00</td><td>-18.74</td><td>50.17</td><td>5.09</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>5</td><td>10520.00</td><td>60.41</td><td>68.30</td><td>-7.89</td><td>45.54</td><td>14.87</td><td>Peak</td><td>---</td><td>---</td></tr></tbody></table>											Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg	1	1050.00	35.36	54.00	-18.64	44.57	-9.21	Average	---	---	2	1050.00	46.57	74.00	-27.43	55.78	-9.21	Peak	---	---	3	5350.00	44.36	54.00	-9.64	39.27	5.09	Average	---	---	4	5350.00	55.26	74.00	-18.74	50.17	5.09	Peak	---	---	5	10520.00	60.41	68.30	-7.89	45.54	14.87	Peak	---	---
	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg																																																												
1	1050.00	35.36	54.00	-18.64	44.57	-9.21	Average	---	---																																																												
2	1050.00	46.57	74.00	-27.43	55.78	-9.21	Peak	---	---																																																												
3	5350.00	44.36	54.00	-9.64	39.27	5.09	Average	---	---																																																												
4	5350.00	55.26	74.00	-18.74	50.17	5.09	Peak	---	---																																																												
5	10520.00	60.41	68.30	-7.89	45.54	14.87	Peak	---	---																																																												
Note 1: “>20dB” means spurious emission levels that exceed the level of 20 dB below the applicable limit. Note 2: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.																																																																					



Polarization	Vertical		Test Freq. (MHz)		5260																																																																
Test Configuration	1																																																																				
Level (dBuV/m) Frequency (MHz) <table><tr><th></th><th>Freq. MHz</th><th>Emission level dBuV/m</th><th>Limit dBuV/m</th><th>Margin dB</th><th>SA reading dBuV</th><th>Factor dB</th><th>Remark</th><th>ANT High cm</th><th>Turn Table deg</th></tr><tr><td>1</td><td>1050.00</td><td>35.66</td><td>54.00</td><td>-18.34</td><td>44.87</td><td>-9.21</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>2</td><td>1050.00</td><td>46.51</td><td>74.00</td><td>-27.49</td><td>55.72</td><td>-9.21</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>3</td><td>5350.00</td><td>41.54</td><td>54.00</td><td>-12.46</td><td>36.45</td><td>5.09</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>4</td><td>5350.00</td><td>54.66</td><td>74.00</td><td>-19.34</td><td>49.57</td><td>5.09</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>5</td><td>10520.00</td><td>66.91</td><td>68.30</td><td>-1.39</td><td>52.04</td><td>14.87</td><td>Peak</td><td>---</td><td>---</td></tr></table>											Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg	1	1050.00	35.66	54.00	-18.34	44.87	-9.21	Average	---	---	2	1050.00	46.51	74.00	-27.49	55.72	-9.21	Peak	---	---	3	5350.00	41.54	54.00	-12.46	36.45	5.09	Average	---	---	4	5350.00	54.66	74.00	-19.34	49.57	5.09	Peak	---	---	5	10520.00	66.91	68.30	-1.39	52.04	14.87	Peak	---	---
	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg																																																												
1	1050.00	35.66	54.00	-18.34	44.87	-9.21	Average	---	---																																																												
2	1050.00	46.51	74.00	-27.49	55.72	-9.21	Peak	---	---																																																												
3	5350.00	41.54	54.00	-12.46	36.45	5.09	Average	---	---																																																												
4	5350.00	54.66	74.00	-19.34	49.57	5.09	Peak	---	---																																																												
5	10520.00	66.91	68.30	-1.39	52.04	14.87	Peak	---	---																																																												
Note 1: “>20dB” means spurious emission levels that exceed the level of 20 dB below the applicable limit. Note 2: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.																																																																					




International Certification Corp.

No. 3-1, Lane 6, Wen San 3rd St., Kwei Shan Hsiang, Tao Yuan Hsien 333, Taiwan, R.O.C.

Tel: 886-3-271-8666

Fax: 886-3-318-0155

Polarization	Horizontal		Test Freq. (MHz)		5300																																																																							
Test Configuration	1																																																																											
 <table><tr><th></th><th>Freq. MHz</th><th>Emission level dBuV/m</th><th>Limit dBuV/m</th><th>Margin dB</th><th>SA reading dBuV</th><th>Factor dB</th><th>Remark</th><th>ANT High cm</th><th>Turn Table deg</th></tr><tr><td>1</td><td>1050.00</td><td>35.62</td><td>54.00</td><td>-18.38</td><td>44.83</td><td>-9.21</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>2</td><td>1050.00</td><td>46.69</td><td>74.00</td><td>-27.31</td><td>55.90</td><td>-9.21</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>3</td><td>5350.00</td><td>40.35</td><td>54.00</td><td>-13.65</td><td>35.26</td><td>5.09</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>4</td><td>5350.00</td><td>57.62</td><td>74.00</td><td>-16.38</td><td>52.53</td><td>5.09</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>5</td><td>10600.00</td><td>48.35</td><td>54.00</td><td>-5.65</td><td>33.41</td><td>14.94</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>6</td><td>10600.00</td><td>64.26</td><td>74.00</td><td>-9.74</td><td>49.32</td><td>14.94</td><td>Peak</td><td>---</td><td>---</td></tr></table>								Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg	1	1050.00	35.62	54.00	-18.38	44.83	-9.21	Average	---	---	2	1050.00	46.69	74.00	-27.31	55.90	-9.21	Peak	---	---	3	5350.00	40.35	54.00	-13.65	35.26	5.09	Average	---	---	4	5350.00	57.62	74.00	-16.38	52.53	5.09	Peak	---	---	5	10600.00	48.35	54.00	-5.65	33.41	14.94	Average	---	---	6	10600.00	64.26	74.00	-9.74	49.32	14.94	Peak	---	---
	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg																																																																			
1	1050.00	35.62	54.00	-18.38	44.83	-9.21	Average	---	---																																																																			
2	1050.00	46.69	74.00	-27.31	55.90	-9.21	Peak	---	---																																																																			
3	5350.00	40.35	54.00	-13.65	35.26	5.09	Average	---	---																																																																			
4	5350.00	57.62	74.00	-16.38	52.53	5.09	Peak	---	---																																																																			
5	10600.00	48.35	54.00	-5.65	33.41	14.94	Average	---	---																																																																			
6	10600.00	64.26	74.00	-9.74	49.32	14.94	Peak	---	---																																																																			
Note 1: “>20dB” means spurious emission levels that exceed the level of 20 dB below the applicable limit. Note 2: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.																																																																												




International Certification Corp.

No. 3-1, Lane 6, Wen San 3rd St., Kwei Shan Hsiang, Tao Yuan Hsien 333, Taiwan, R.O.C.

Tel: 886-3-271-8666

Fax: 886-3-318-0155

Polarization	Vertical			Test Freq. (MHz)		5300																																																																																													
Test Configuration	1																																																																																																		
Level (dBuV/m)  Frequency (MHz) <table><tr><th></th><th>Freq.</th><th>Emission</th><th>Limit</th><th>Margin</th><th>SA</th><th>Factor</th><th>Remark</th><th>ANT</th><th>Turn</th></tr><tr><th></th><th>MHz</th><th>level</th><th></th><th></th><th>reading</th><th></th><th></th><th>High</th><th>Table</th></tr><tr><th></th><th></th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB</th><th></th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>1050.00</td><td>35.47</td><td>54.00</td><td>-18.53</td><td>44.68</td><td>-9.21</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>2</td><td>1050.00</td><td>46.37</td><td>74.00</td><td>-27.63</td><td>55.58</td><td>-9.21</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>3</td><td>5350.00</td><td>42.28</td><td>54.00</td><td>-11.72</td><td>37.19</td><td>5.09</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>4</td><td>5350.00</td><td>59.40</td><td>74.00</td><td>-14.60</td><td>54.31</td><td>5.09</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>5</td><td>10600.00</td><td>52.51</td><td>54.00</td><td>-1.49</td><td>37.57</td><td>14.94</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>6</td><td>10600.00</td><td>68.43</td><td>74.00</td><td>-5.57</td><td>53.49</td><td>14.94</td><td>Peak</td><td>---</td><td>---</td></tr></table>											Freq.	Emission	Limit	Margin	SA	Factor	Remark	ANT	Turn		MHz	level			reading			High	Table			dBuV/m	dBuV/m	dB	dBuV	dB		cm	deg	1	1050.00	35.47	54.00	-18.53	44.68	-9.21	Average	---	---	2	1050.00	46.37	74.00	-27.63	55.58	-9.21	Peak	---	---	3	5350.00	42.28	54.00	-11.72	37.19	5.09	Average	---	---	4	5350.00	59.40	74.00	-14.60	54.31	5.09	Peak	---	---	5	10600.00	52.51	54.00	-1.49	37.57	14.94	Average	---	---	6	10600.00	68.43	74.00	-5.57	53.49	14.94	Peak	---	---
	Freq.	Emission	Limit	Margin	SA	Factor	Remark	ANT	Turn																																																																																										
	MHz	level			reading			High	Table																																																																																										
		dBuV/m	dBuV/m	dB	dBuV	dB		cm	deg																																																																																										
1	1050.00	35.47	54.00	-18.53	44.68	-9.21	Average	---	---																																																																																										
2	1050.00	46.37	74.00	-27.63	55.58	-9.21	Peak	---	---																																																																																										
3	5350.00	42.28	54.00	-11.72	37.19	5.09	Average	---	---																																																																																										
4	5350.00	59.40	74.00	-14.60	54.31	5.09	Peak	---	---																																																																																										
5	10600.00	52.51	54.00	-1.49	37.57	14.94	Average	---	---																																																																																										
6	10600.00	68.43	74.00	-5.57	53.49	14.94	Peak	---	---																																																																																										
Note 1: “>20dB” means spurious emission levels that exceed the level of 20 dB below the applicable limit. Note 2: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.																																																																																																			




International Certification Corp.

No. 3-1, Lane 6, Wen San 3rd St., Kwei Shan Hsiang, Tao Yuan Hsien 333, Taiwan, R.O.C.

Tel: 886-3-271-8666

Fax: 886-3-318-0155

Polarization	Horizontal		Test Freq. (MHz)		5320																																																																																											
Test Configuration	1																																																																																															
 <table><tr><th></th><th>Freq.</th><th>Emission level</th><th>Limit</th><th>Margin</th><th>SA reading</th><th>Factor</th><th>Remark</th><th>ANT</th><th>Turn</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB</th><th></th><th>High</th><th>Table</th></tr><tr><th></th><th></th><th></th><th></th><th></th><th></th><th></th><th></th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>1050.00</td><td>35.62</td><td>54.00</td><td>-18.38</td><td>44.83</td><td>-9.21</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>2</td><td>1050.00</td><td>46.35</td><td>74.00</td><td>-27.65</td><td>55.56</td><td>-9.21</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>3</td><td>5350.00</td><td>44.36</td><td>54.00</td><td>-9.64</td><td>39.27</td><td>5.09</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>4</td><td>5350.00</td><td>56.51</td><td>74.00</td><td>-17.49</td><td>51.42</td><td>5.09</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>5</td><td>10640.00</td><td>47.25</td><td>54.00</td><td>-6.75</td><td>32.27</td><td>14.98</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>6</td><td>10640.00</td><td>62.93</td><td>74.00</td><td>-11.07</td><td>47.95</td><td>14.98</td><td>Peak</td><td>---</td><td>---</td></tr></table>								Freq.	Emission level	Limit	Margin	SA reading	Factor	Remark	ANT	Turn		MHz	dBuV/m	dBuV/m	dB	dBuV	dB		High	Table									cm	deg	1	1050.00	35.62	54.00	-18.38	44.83	-9.21	Average	---	---	2	1050.00	46.35	74.00	-27.65	55.56	-9.21	Peak	---	---	3	5350.00	44.36	54.00	-9.64	39.27	5.09	Average	---	---	4	5350.00	56.51	74.00	-17.49	51.42	5.09	Peak	---	---	5	10640.00	47.25	54.00	-6.75	32.27	14.98	Average	---	---	6	10640.00	62.93	74.00	-11.07	47.95	14.98	Peak	---	---
	Freq.	Emission level	Limit	Margin	SA reading	Factor	Remark	ANT	Turn																																																																																							
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB		High	Table																																																																																							
								cm	deg																																																																																							
1	1050.00	35.62	54.00	-18.38	44.83	-9.21	Average	---	---																																																																																							
2	1050.00	46.35	74.00	-27.65	55.56	-9.21	Peak	---	---																																																																																							
3	5350.00	44.36	54.00	-9.64	39.27	5.09	Average	---	---																																																																																							
4	5350.00	56.51	74.00	-17.49	51.42	5.09	Peak	---	---																																																																																							
5	10640.00	47.25	54.00	-6.75	32.27	14.98	Average	---	---																																																																																							
6	10640.00	62.93	74.00	-11.07	47.95	14.98	Peak	---	---																																																																																							
Note 1: “>20dB” means spurious emission levels that exceed the level of 20 dB below the applicable limit. Note 2: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.																																																																																																




International Certification Corp.

No. 3-1, Lane 6, Wen San 3rd St., Kwei Shan Hsiang, Tao Yuan Hsien 333, Taiwan, R.O.C.

Tel: 886-3-271-8666

Fax: 886-3-318-0155

Polarization	Horizontal		Test Freq. (MHz)		5500																																																																																														
Test Configuration	1																																																																																																		
 <table><tr><th></th><th>Freq. MHz</th><th>Emission level dBuV/m</th><th>Limit dBuV/m</th><th>Margin dB</th><th>SA reading dBuV</th><th>Factor dB</th><th>Remark</th><th>ANT High cm</th><th>Turn Table deg</th></tr><tr><td>1</td><td>1050.00</td><td>35.26</td><td>54.00</td><td>-18.74</td><td>44.47</td><td>-9.21</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>2</td><td>1050.00</td><td>46.34</td><td>74.00</td><td>-27.66</td><td>55.55</td><td>-9.21</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>3</td><td>5460.00</td><td>41.36</td><td>54.00</td><td>-12.64</td><td>36.18</td><td>5.18</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>4</td><td>5460.00</td><td>58.41</td><td>74.00</td><td>-15.59</td><td>53.23</td><td>5.18</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>5</td><td>5470.00</td><td>44.38</td><td>54.00</td><td>-9.62</td><td>39.19</td><td>5.19</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>6</td><td>5470.00</td><td>61.63</td><td>74.00</td><td>-12.37</td><td>56.44</td><td>5.19</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>7</td><td>11000.00</td><td>48.26</td><td>54.00</td><td>-5.74</td><td>32.98</td><td>15.28</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>8</td><td>11000.00</td><td>63.11</td><td>74.00</td><td>-10.89</td><td>47.83</td><td>15.28</td><td>Peak</td><td>---</td><td>---</td></tr></table>											Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg	1	1050.00	35.26	54.00	-18.74	44.47	-9.21	Average	---	---	2	1050.00	46.34	74.00	-27.66	55.55	-9.21	Peak	---	---	3	5460.00	41.36	54.00	-12.64	36.18	5.18	Average	---	---	4	5460.00	58.41	74.00	-15.59	53.23	5.18	Peak	---	---	5	5470.00	44.38	54.00	-9.62	39.19	5.19	Average	---	---	6	5470.00	61.63	74.00	-12.37	56.44	5.19	Peak	---	---	7	11000.00	48.26	54.00	-5.74	32.98	15.28	Average	---	---	8	11000.00	63.11	74.00	-10.89	47.83	15.28	Peak	---	---
	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg																																																																																										
1	1050.00	35.26	54.00	-18.74	44.47	-9.21	Average	---	---																																																																																										
2	1050.00	46.34	74.00	-27.66	55.55	-9.21	Peak	---	---																																																																																										
3	5460.00	41.36	54.00	-12.64	36.18	5.18	Average	---	---																																																																																										
4	5460.00	58.41	74.00	-15.59	53.23	5.18	Peak	---	---																																																																																										
5	5470.00	44.38	54.00	-9.62	39.19	5.19	Average	---	---																																																																																										
6	5470.00	61.63	74.00	-12.37	56.44	5.19	Peak	---	---																																																																																										
7	11000.00	48.26	54.00	-5.74	32.98	15.28	Average	---	---																																																																																										
8	11000.00	63.11	74.00	-10.89	47.83	15.28	Peak	---	---																																																																																										
Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit. Note 2: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.																																																																																																			



International Certification Corp.

No. 3-1, Lane 6, Wen San 3rd St., Kwei Shan Hsiang, Tao Yuan Hsien 333, Taiwan, R.O.C.
Tel: 886-3-271-8666 Fax: 886-3-318-0155

Polarization	Vertical			Test Freq. (MHz)		5500			
Test Configuration	1								
The graph displays the emission level in dBUV/m on the y-axis (0 to 117) against frequency in MHz on the x-axis (1000 to 40000). A red line represents the FCC PART 15E (74) limit, and a blue line represents the FCC PART 15E (AVG) limit. Test results are shown as blue vertical lines with labels 1 through 8. The test results show that the emission levels are generally below the limits, with some peaks near 1050 MHz and 11000 MHz.									
	Freq. MHz	Emission level dBUV/m	Limit dBUV/m	Margin dB	SA reading dBUV	Factor dB	Remark	ANT High cm	Turn Table deg
1	1050.00	35.45	54.00	-18.55	44.66	-9.21	Average	---	---
2	1050.00	46.41	74.00	-27.59	55.62	-9.21	Peak	---	---
3	5460.00	43.35	54.00	-10.65	38.17	5.18	Average	---	---
4	5460.00	60.52	74.00	-13.48	55.34	5.18	Peak	---	---
5	5470.00	52.86	54.00	-1.14	47.67	5.19	Average	---	---
6	5470.00	69.93	74.00	-4.07	64.74	5.19	Peak	---	---
7	11000.00	50.96	54.00	-3.04	35.68	15.28	Average	---	---
8	11000.00	65.59	74.00	-8.41	50.31	15.28	Peak	---	---

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.

Note 2: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.



International Certification Corp.

No. 3-1, Lane 6, Wen San 3rd St., Kwei Shan Hsiang, Tao Yuan Hsien 333, Taiwan, R.O.C.
Tel: 886-3-271-8666 Fax: 886-3-318-0155

Polarization	Horizontal		Test Freq. (MHz)		5580																																																																							
Test Configuration	1																																																																											
Level (dBuV/m) Frequency (MHz) <table><tr><th></th><th>Freq. MHz</th><th>Emission level dBuV/m</th><th>Limit dBuV/m</th><th>Margin dB</th><th>SA reading dBuV</th><th>Factor dB</th><th>Remark</th><th>ANT High cm</th><th>Turn Table deg</th></tr><tr><td>1</td><td>1050.00</td><td>35.28</td><td>54.00</td><td>-18.72</td><td>44.49</td><td>-9.21</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>2</td><td>1050.00</td><td>46.33</td><td>74.00</td><td>-27.67</td><td>55.54</td><td>-9.21</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>3</td><td>5418.50</td><td>38.47</td><td>54.00</td><td>-15.53</td><td>33.35</td><td>5.12</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>4</td><td>5418.50</td><td>50.51</td><td>74.00</td><td>-23.49</td><td>45.39</td><td>5.12</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>5</td><td>11160.00</td><td>48.16</td><td>54.00</td><td>-5.84</td><td>32.98</td><td>15.18</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>6</td><td>11160.00</td><td>62.02</td><td>74.00</td><td>-11.98</td><td>46.84</td><td>15.18</td><td>Peak</td><td>---</td><td>---</td></tr></table>								Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg	1	1050.00	35.28	54.00	-18.72	44.49	-9.21	Average	---	---	2	1050.00	46.33	74.00	-27.67	55.54	-9.21	Peak	---	---	3	5418.50	38.47	54.00	-15.53	33.35	5.12	Average	---	---	4	5418.50	50.51	74.00	-23.49	45.39	5.12	Peak	---	---	5	11160.00	48.16	54.00	-5.84	32.98	15.18	Average	---	---	6	11160.00	62.02	74.00	-11.98	46.84	15.18	Peak	---	---
	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg																																																																			
1	1050.00	35.28	54.00	-18.72	44.49	-9.21	Average	---	---																																																																			
2	1050.00	46.33	74.00	-27.67	55.54	-9.21	Peak	---	---																																																																			
3	5418.50	38.47	54.00	-15.53	33.35	5.12	Average	---	---																																																																			
4	5418.50	50.51	74.00	-23.49	45.39	5.12	Peak	---	---																																																																			
5	11160.00	48.16	54.00	-5.84	32.98	15.18	Average	---	---																																																																			
6	11160.00	62.02	74.00	-11.98	46.84	15.18	Peak	---	---																																																																			
Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit. Note 2: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.																																																																												



International Certification Corp.

No. 3-1, Lane 6, Wen San 3rd St., Kwei Shan Hsiang, Tao Yuan Hsien 333, Taiwan, R.O.C.

Tel: 886-3-271-8666

Fax: 886-3-318-0155

Polarization	Vertical		Test Freq. (MHz)		5580																																																																							
Test Configuration	1																																																																											
The graph displays the emission level in dBuV/m on the y-axis (0 to 117) against frequency in MHz on the x-axis (1000 to 40000). A red line represents the FCC PART15E limit, which is 70 dBuV/m from 1000 to 14000 MHz and 50 dBuV/m from 14000 to 40000 MHz. A blue line represents the test results, showing a peak of 67.11 dBuV/m at 11160 MHz. The graph also includes a table of test results below it. <table><tr><th></th><th>Freq. MHz</th><th>Emission level dBuV/m</th><th>Limit dBuV/m</th><th>Margin dB</th><th>SA reading dBuV</th><th>Factor dB</th><th>Remark</th><th>ANT High cm</th><th>Turn Table deg</th></tr><tr><td>1</td><td>1050.00</td><td>35.22</td><td>54.00</td><td>-18.78</td><td>44.43</td><td>-9.21</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>2</td><td>1050.00</td><td>45.98</td><td>74.00</td><td>-28.02</td><td>55.19</td><td>-9.21</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>3</td><td>5418.50</td><td>40.56</td><td>54.00</td><td>-13.44</td><td>35.44</td><td>5.12</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>4</td><td>5418.50</td><td>52.64</td><td>74.00</td><td>-21.36</td><td>47.52</td><td>5.12</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>5</td><td>11160.00</td><td>52.75</td><td>54.00</td><td>-1.25</td><td>37.57</td><td>15.18</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>6</td><td>11160.00</td><td>67.11</td><td>74.00</td><td>-6.89</td><td>51.93</td><td>15.18</td><td>Peak</td><td>---</td><td>---</td></tr></table>								Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg	1	1050.00	35.22	54.00	-18.78	44.43	-9.21	Average	---	---	2	1050.00	45.98	74.00	-28.02	55.19	-9.21	Peak	---	---	3	5418.50	40.56	54.00	-13.44	35.44	5.12	Average	---	---	4	5418.50	52.64	74.00	-21.36	47.52	5.12	Peak	---	---	5	11160.00	52.75	54.00	-1.25	37.57	15.18	Average	---	---	6	11160.00	67.11	74.00	-6.89	51.93	15.18	Peak	---	---
	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg																																																																			
1	1050.00	35.22	54.00	-18.78	44.43	-9.21	Average	---	---																																																																			
2	1050.00	45.98	74.00	-28.02	55.19	-9.21	Peak	---	---																																																																			
3	5418.50	40.56	54.00	-13.44	35.44	5.12	Average	---	---																																																																			
4	5418.50	52.64	74.00	-21.36	47.52	5.12	Peak	---	---																																																																			
5	11160.00	52.75	54.00	-1.25	37.57	15.18	Average	---	---																																																																			
6	11160.00	67.11	74.00	-6.89	51.93	15.18	Peak	---	---																																																																			
Note 1: “>20dB” means spurious emission levels that exceed the level of 20 dB below the applicable limit. Note 2: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.																																																																												




International Certification Corp.

No. 3-1, Lane 6, Wen San 3rd St., Kwei Shan Hsiang, Tao Yuan Hsien 333, Taiwan, R.O.C.

Tel: 886-3-271-8666

Fax: 886-3-318-0155

Polarization	Horizontal			Test Freq. (MHz)		5700																																																																									
Test Configuration	1																																																																														
 <table><tr><th></th><th>Freq. MHz</th><th>Emission level dBuV/m</th><th>Limit dBuV/m</th><th>Margin dB</th><th>SA reading dBuV</th><th>Factor dB</th><th>Remark</th><th>ANT High cm</th><th>Turn Table deg</th></tr><tr><td>1</td><td>1050.00</td><td>35.25</td><td>54.00</td><td>-18.75</td><td>44.46</td><td>-9.21</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>2</td><td>1050.00</td><td>46.38</td><td>74.00</td><td>-27.62</td><td>55.59</td><td>-9.21</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>3</td><td>5725.00</td><td>46.34</td><td>54.00</td><td>-7.66</td><td>40.78</td><td>5.56</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>4</td><td>5725.00</td><td>62.96</td><td>74.00</td><td>-11.04</td><td>57.40</td><td>5.56</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>5</td><td>11400.00</td><td>46.26</td><td>54.00</td><td>-7.74</td><td>31.23</td><td>15.03</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>6</td><td>11400.00</td><td>60.44</td><td>74.00</td><td>-13.56</td><td>45.41</td><td>15.03</td><td>Peak</td><td>---</td><td>---</td></tr></table>											Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg	1	1050.00	35.25	54.00	-18.75	44.46	-9.21	Average	---	---	2	1050.00	46.38	74.00	-27.62	55.59	-9.21	Peak	---	---	3	5725.00	46.34	54.00	-7.66	40.78	5.56	Average	---	---	4	5725.00	62.96	74.00	-11.04	57.40	5.56	Peak	---	---	5	11400.00	46.26	54.00	-7.74	31.23	15.03	Average	---	---	6	11400.00	60.44	74.00	-13.56	45.41	15.03	Peak	---	---
	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg																																																																						
1	1050.00	35.25	54.00	-18.75	44.46	-9.21	Average	---	---																																																																						
2	1050.00	46.38	74.00	-27.62	55.59	-9.21	Peak	---	---																																																																						
3	5725.00	46.34	54.00	-7.66	40.78	5.56	Average	---	---																																																																						
4	5725.00	62.96	74.00	-11.04	57.40	5.56	Peak	---	---																																																																						
5	11400.00	46.26	54.00	-7.74	31.23	15.03	Average	---	---																																																																						
6	11400.00	60.44	74.00	-13.56	45.41	15.03	Peak	---	---																																																																						
Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit. Note 2: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.																																																																															




International Certification Corp.

No. 3-1, Lane 6, Wen San 3rd St., Kwei Shan Hsiang, Tao Yuan Hsien 333, Taiwan, R.O.C.

Tel: 886-3-271-8666

Fax: 886-3-318-0155

Polarization	Vertical				Test Freq. (MHz)		5700																																																																																												
Test Configuration	1																																																																																																		
Level (dBuV/m)  <table><tr><th></th><th>Freq.</th><th>Emission</th><th>Limit</th><th>Margin</th><th>SA</th><th>Factor</th><th>Remark</th><th>ANT</th><th>Turn</th></tr><tr><th></th><th>MHz</th><th>level</th><th></th><th></th><th>reading</th><th></th><th></th><th>High</th><th>Table</th></tr><tr><th></th><th></th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB</th><th></th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>1050.00</td><td>35.68</td><td>54.00</td><td>-18.32</td><td>44.89</td><td>-9.21</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>2</td><td>1050.00</td><td>46.84</td><td>74.00</td><td>-27.16</td><td>56.05</td><td>-9.21</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>3</td><td>5725.00</td><td>52.73</td><td>54.00</td><td>-1.27</td><td>47.17</td><td>5.56</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>4</td><td>5725.00</td><td>68.30</td><td>74.00</td><td>-5.70</td><td>62.74</td><td>5.56</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>5</td><td>11400.00</td><td>50.36</td><td>54.00</td><td>-3.64</td><td>35.33</td><td>15.03</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>6</td><td>11400.00</td><td>64.48</td><td>74.00</td><td>-9.52</td><td>49.45</td><td>15.03</td><td>Peak</td><td>---</td><td>---</td></tr></table>											Freq.	Emission	Limit	Margin	SA	Factor	Remark	ANT	Turn		MHz	level			reading			High	Table			dBuV/m	dBuV/m	dB	dBuV	dB		cm	deg	1	1050.00	35.68	54.00	-18.32	44.89	-9.21	Average	---	---	2	1050.00	46.84	74.00	-27.16	56.05	-9.21	Peak	---	---	3	5725.00	52.73	54.00	-1.27	47.17	5.56	Average	---	---	4	5725.00	68.30	74.00	-5.70	62.74	5.56	Peak	---	---	5	11400.00	50.36	54.00	-3.64	35.33	15.03	Average	---	---	6	11400.00	64.48	74.00	-9.52	49.45	15.03	Peak	---	---
	Freq.	Emission	Limit	Margin	SA	Factor	Remark	ANT	Turn																																																																																										
	MHz	level			reading			High	Table																																																																																										
		dBuV/m	dBuV/m	dB	dBuV	dB		cm	deg																																																																																										
1	1050.00	35.68	54.00	-18.32	44.89	-9.21	Average	---	---																																																																																										
2	1050.00	46.84	74.00	-27.16	56.05	-9.21	Peak	---	---																																																																																										
3	5725.00	52.73	54.00	-1.27	47.17	5.56	Average	---	---																																																																																										
4	5725.00	68.30	74.00	-5.70	62.74	5.56	Peak	---	---																																																																																										
5	11400.00	50.36	54.00	-3.64	35.33	15.03	Average	---	---																																																																																										
6	11400.00	64.48	74.00	-9.52	49.45	15.03	Peak	---	---																																																																																										
Note 1: “>20dB” means spurious emission levels that exceed the level of 20 dB below the applicable limit. Note 2: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.																																																																																																			




International Certification Corp.

No. 3-1, Lane 6, Wen San 3rd St., Kwei Shan Hsiang, Tao Yuan Hsien 333, Taiwan, R.O.C.

Tel: 886-3-271-8666

Fax: 886-3-318-0155

Polarization	Horizontal			Test Freq. (MHz)			5180																																																																																		
Test Configuration	2																																																																																								
Level (dBuV/m)  <table><tr><th></th><th>Freq.</th><th>Emission</th><th>Limit</th><th>Margin</th><th>SA</th><th>Factor</th><th>Remark</th><th>ANT</th><th>Turn</th></tr><tr><th></th><th>MHz</th><th>level</th><th>dBuV/m</th><th>dB</th><th>reading</th><th>dB</th><th></th><th>High</th><th>Table</th></tr><tr><th></th><th></th><th>dBuV/m</th><th></th><th></th><th>dBuV</th><th></th><th></th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>1050.00</td><td>34.96</td><td>54.00</td><td>-19.04</td><td>44.17</td><td>-9.21</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>2</td><td>1050.00</td><td>45.31</td><td>74.00</td><td>-28.69</td><td>54.52</td><td>-9.21</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>3</td><td>5150.00</td><td>40.81</td><td>54.00</td><td>-13.19</td><td>35.87</td><td>4.94</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>4</td><td>5150.00</td><td>55.07</td><td>74.00</td><td>-18.93</td><td>50.13</td><td>4.94</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>5</td><td>10360.00</td><td>59.27</td><td>68.30</td><td>-9.03</td><td>44.56</td><td>14.71</td><td>Peak</td><td>---</td><td>---</td></tr></table>											Freq.	Emission	Limit	Margin	SA	Factor	Remark	ANT	Turn		MHz	level	dBuV/m	dB	reading	dB		High	Table			dBuV/m			dBuV			cm	deg	1	1050.00	34.96	54.00	-19.04	44.17	-9.21	Average	---	---	2	1050.00	45.31	74.00	-28.69	54.52	-9.21	Peak	---	---	3	5150.00	40.81	54.00	-13.19	35.87	4.94	Average	---	---	4	5150.00	55.07	74.00	-18.93	50.13	4.94	Peak	---	---	5	10360.00	59.27	68.30	-9.03	44.56	14.71	Peak	---	---
	Freq.	Emission	Limit	Margin	SA	Factor	Remark	ANT	Turn																																																																																
	MHz	level	dBuV/m	dB	reading	dB		High	Table																																																																																
		dBuV/m			dBuV			cm	deg																																																																																
1	1050.00	34.96	54.00	-19.04	44.17	-9.21	Average	---	---																																																																																
2	1050.00	45.31	74.00	-28.69	54.52	-9.21	Peak	---	---																																																																																
3	5150.00	40.81	54.00	-13.19	35.87	4.94	Average	---	---																																																																																
4	5150.00	55.07	74.00	-18.93	50.13	4.94	Peak	---	---																																																																																
5	10360.00	59.27	68.30	-9.03	44.56	14.71	Peak	---	---																																																																																
Note 1: “>20dB” means spurious emission levels that exceed the level of 20 dB below the applicable limit. Note 2: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.																																																																																									



International Certification Corp.

No. 3-1, Lane 6, Wen San 3rd St., Kwei Shan Hsiang, Tao Yuan Hsien 333, Taiwan, R.O.C.
Tel: 886-3-271-8666 Fax: 886-3-318-0155

Polarization	Vertical	Test Freq. (MHz)	5180																																																																		
Test Configuration	2																																																																				
Level (dBuV/m) 117 110 90 70 50 30 10 0 1000 6000 10000 14000 18000 22000 26000 30000 34000 40000 Frequency (MHz) 1 2 3 4 5 1050.00 1050.00 5150.00 5150.00 10360.00 Emission level dBuV/m 36.17 45.98 47.74 64.21 66.15 Limit dBuV/m 54.00 74.00 54.00 74.00 68.30 Margin dB -17.83 -28.02 -6.26 -9.79 -2.15 SA reading dBuV 45.38 55.19 42.80 59.27 51.44 Factor dB -9.21 -9.21 4.94 4.94 14.71 Remark Average Peak Average Peak ANT High cm Turn Table deg --- --- --- --- --- <table><tr><th></th><th>Freq. MHz</th><th>Emission level dBuV/m</th><th>Limit dBuV/m</th><th>Margin dB</th><th>SA reading dBuV</th><th>Factor dB</th><th>Remark</th><th>ANT High cm</th><th>Turn Table deg</th></tr><tr><td>1</td><td>1050.00</td><td>36.17</td><td>54.00</td><td>-17.83</td><td>45.38</td><td>-9.21</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>2</td><td>1050.00</td><td>45.98</td><td>74.00</td><td>-28.02</td><td>55.19</td><td>-9.21</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>3</td><td>5150.00</td><td>47.74</td><td>54.00</td><td>-6.26</td><td>42.80</td><td>4.94</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>4</td><td>5150.00</td><td>64.21</td><td>74.00</td><td>-9.79</td><td>59.27</td><td>4.94</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>5</td><td>10360.00</td><td>66.15</td><td>68.30</td><td>-2.15</td><td>51.44</td><td>14.71</td><td>Peak</td><td>---</td><td>---</td></tr></table>											Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg	1	1050.00	36.17	54.00	-17.83	45.38	-9.21	Average	---	---	2	1050.00	45.98	74.00	-28.02	55.19	-9.21	Peak	---	---	3	5150.00	47.74	54.00	-6.26	42.80	4.94	Average	---	---	4	5150.00	64.21	74.00	-9.79	59.27	4.94	Peak	---	---	5	10360.00	66.15	68.30	-2.15	51.44	14.71	Peak	---	---
	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg																																																												
1	1050.00	36.17	54.00	-17.83	45.38	-9.21	Average	---	---																																																												
2	1050.00	45.98	74.00	-28.02	55.19	-9.21	Peak	---	---																																																												
3	5150.00	47.74	54.00	-6.26	42.80	4.94	Average	---	---																																																												
4	5150.00	64.21	74.00	-9.79	59.27	4.94	Peak	---	---																																																												
5	10360.00	66.15	68.30	-2.15	51.44	14.71	Peak	---	---																																																												
Note 1: “>20dB” means spurious emission levels that exceed the level of 20 dB below the applicable limit. Note 2: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.																																																																					

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.
Note 2: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.



International Certification Corp.

No. 3-1, Lane 6, Wen San 3rd St., Kwei Shan Hsiang, Tao Yuan Hsien 333, Taiwan, R.O.C.
Tel: 886-3-271-8666 Fax: 886-3-318-0155

Polarization	Horizontal	Test Freq. (MHz)	5200
Test Configuration	2		

Level (dBuV/m)

Frequency (MHz)

	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	1050.00	35.32	54.00	-18.68	44.53	-9.21	Average	---	---
2	1050.00	45.27	74.00	-28.73	54.48	-9.21	Peak	---	---
3	5150.00	35.80	54.00	-18.20	30.86	4.94	Average	---	---
4	5150.00	49.51	74.00	-24.49	44.57	4.94	Peak	---	---
5	10400.00	60.35	68.30	-7.95	45.60	14.75	Peak	---	---

Note 1: “>20dB” means spurious emission levels that exceed the level of 20 dB below the applicable limit.

Note 2: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.




International Certification Corp.

No. 3-1, Lane 6, Wen San 3rd St., Kwei Shan Hsiang, Tao Yuan Hsien 333, Taiwan, R.O.C.

Tel: 886-3-271-8666

Fax: 886-3-318-0155

Polarization	Vertical	Test Freq. (MHz)	5200																																																																																
Test Configuration	2																																																																																		
 <table><tr><th></th><th>Freq.</th><th>Emission</th><th>Limit</th><th>Margin</th><th>SA</th><th>Factor</th><th>Remark</th><th>ANT</th><th>Turn</th></tr><tr><th></th><th>MHz</th><th>level</th><th>dBuV/m</th><th>dB</th><th>reading</th><th>dB</th><th></th><th>High</th><th>Table</th></tr><tr><th></th><th></th><th>dBuV/m</th><th></th><th></th><th>dBuV</th><th></th><th></th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>1050.00</td><td>35.98</td><td>54.00</td><td>-18.02</td><td>45.19</td><td>-9.21</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>2</td><td>1050.00</td><td>46.64</td><td>74.00</td><td>-27.36</td><td>55.85</td><td>-9.21</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>3</td><td>5150.00</td><td>37.87</td><td>54.00</td><td>-16.13</td><td>32.93</td><td>4.94</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>4</td><td>5150.00</td><td>52.08</td><td>74.00</td><td>-21.92</td><td>47.14</td><td>4.94</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>5</td><td>10400.00</td><td>67.21</td><td>68.30</td><td>-1.09</td><td>52.46</td><td>14.75</td><td>Peak</td><td>---</td><td>---</td></tr></table>					Freq.	Emission	Limit	Margin	SA	Factor	Remark	ANT	Turn		MHz	level	dBuV/m	dB	reading	dB		High	Table			dBuV/m			dBuV			cm	deg	1	1050.00	35.98	54.00	-18.02	45.19	-9.21	Average	---	---	2	1050.00	46.64	74.00	-27.36	55.85	-9.21	Peak	---	---	3	5150.00	37.87	54.00	-16.13	32.93	4.94	Average	---	---	4	5150.00	52.08	74.00	-21.92	47.14	4.94	Peak	---	---	5	10400.00	67.21	68.30	-1.09	52.46	14.75	Peak	---	---
	Freq.	Emission	Limit	Margin	SA	Factor	Remark	ANT	Turn																																																																										
	MHz	level	dBuV/m	dB	reading	dB		High	Table																																																																										
		dBuV/m			dBuV			cm	deg																																																																										
1	1050.00	35.98	54.00	-18.02	45.19	-9.21	Average	---	---																																																																										
2	1050.00	46.64	74.00	-27.36	55.85	-9.21	Peak	---	---																																																																										
3	5150.00	37.87	54.00	-16.13	32.93	4.94	Average	---	---																																																																										
4	5150.00	52.08	74.00	-21.92	47.14	4.94	Peak	---	---																																																																										
5	10400.00	67.21	68.30	-1.09	52.46	14.75	Peak	---	---																																																																										
Note 1: “>20dB” means spurious emission levels that exceed the level of 20 dB below the applicable limit. Note 2: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.																																																																																			



International Certification Corp.

No. 3-1, Lane 6, Wen San 3rd St., Kwei Shan Hsiang, Tao Yuan Hsien 333, Taiwan, R.O.C.

Tel: 886-3-271-8666

Fax: 886-3-318-0155

Polarization	Horizontal	Test Freq. (MHz)	5240						
Test Configuration	2								
The graph displays the emission level in dBuV/m on the y-axis (0 to 117) against frequency in MHz on the x-axis (1000 to 40000). A red stepped line represents the FCC Part 15E (74) limit, and a lower red line represents the FCC Part 15E (AVG) limit. Blue vertical lines with markers indicate specific test results at 1050 MHz, 5150 MHz, and 10480 MHz. The markers are labeled 1 through 6, corresponding to the data in the table below.									
	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	1050.00	35.62	54.00	-18.38	44.83	-9.21	Average	---	---
2	1050.00	46.13	74.00	-27.87	55.34	-9.21	Peak	---	---
3	5150.00	35.80	54.00	-18.20	30.86	4.94	Average	---	---
4	5150.00	48.85	74.00	-25.15	43.91	4.94	Peak	---	---
5	10480.00	46.08	54.00	-7.92	31.24	14.84	Average	---	---
6	10480.00	61.82	74.00	-12.18	46.98	14.84	Peak	---	---

Note 1: “>20dB” means spurious emission levels that exceed the level of 20 dB below the applicable limit.

Note 2: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.



International Certification Corp.


No. 3-1, Lane 6, Wen San 3rd St., Kwei Shan Hsiang, Tao Yuan Hsien 333, Taiwan, R.O.C.
Tel: 886-3-271-8666 Fax: 886-3-318-0155

Polarization	Vertical	Test Freq. (MHz)	5240																																																																																										
Test Configuration	2																																																																																												
Level (dBuV/m) 117 110 90 70 50 30 10 0 1000 6000 10000 14000 18000 22000 26000 30000 34000 40000 Frequency (MHz) 6 5 4 3 FCC PART15E (74) FCC PART15E (AVG) <table><thead><tr><th></th><th>Freq.</th><th>Emission</th><th>Limit</th><th>Margin</th><th>SA</th><th>Factor</th><th>Remark</th><th>ANT</th><th>Turn</th></tr><tr><th></th><th>MHz</th><th>level</th><th>dBuV/m</th><th>dB</th><th>reading</th><th>dB</th><th></th><th>High</th><th>Table</th></tr><tr><th></th><th></th><th>dBuV/m</th><th></th><th></th><th>dBuV</th><th></th><th></th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>1050.00</td><td>36.70</td><td>54.00</td><td>-17.30</td><td>45.91</td><td>-9.21</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>2</td><td>1050.00</td><td>47.36</td><td>74.00</td><td>-26.64</td><td>56.57</td><td>-9.21</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>3</td><td>5150.00</td><td>36.46</td><td>54.00</td><td>-17.54</td><td>31.52</td><td>4.94</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>4</td><td>5150.00</td><td>51.11</td><td>74.00</td><td>-22.89</td><td>46.17</td><td>4.94</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>5</td><td>10480.00</td><td>52.75</td><td>54.00</td><td>-1.25</td><td>37.91</td><td>14.84</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>6</td><td>10480.00</td><td>68.68</td><td>74.00</td><td>-5.32</td><td>53.84</td><td>14.84</td><td>Peak</td><td>---</td><td>---</td></tr></tbody></table>					Freq.	Emission	Limit	Margin	SA	Factor	Remark	ANT	Turn		MHz	level	dBuV/m	dB	reading	dB		High	Table			dBuV/m			dBuV			cm	deg	1	1050.00	36.70	54.00	-17.30	45.91	-9.21	Average	---	---	2	1050.00	47.36	74.00	-26.64	56.57	-9.21	Peak	---	---	3	5150.00	36.46	54.00	-17.54	31.52	4.94	Average	---	---	4	5150.00	51.11	74.00	-22.89	46.17	4.94	Peak	---	---	5	10480.00	52.75	54.00	-1.25	37.91	14.84	Average	---	---	6	10480.00	68.68	74.00	-5.32	53.84	14.84	Peak	---	---
	Freq.	Emission	Limit	Margin	SA	Factor	Remark	ANT	Turn																																																																																				
	MHz	level	dBuV/m	dB	reading	dB		High	Table																																																																																				
		dBuV/m			dBuV			cm	deg																																																																																				
1	1050.00	36.70	54.00	-17.30	45.91	-9.21	Average	---	---																																																																																				
2	1050.00	47.36	74.00	-26.64	56.57	-9.21	Peak	---	---																																																																																				
3	5150.00	36.46	54.00	-17.54	31.52	4.94	Average	---	---																																																																																				
4	5150.00	51.11	74.00	-22.89	46.17	4.94	Peak	---	---																																																																																				
5	10480.00	52.75	54.00	-1.25	37.91	14.84	Average	---	---																																																																																				
6	10480.00	68.68	74.00	-5.32	53.84	14.84	Peak	---	---																																																																																				
Note 1: “>20dB” means spurious emission levels that exceed the level of 20 dB below the applicable limit. Note 2: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.																																																																																													



International Certification Corp.

No. 3-1, Lane 6, Wen San 3rd St., Kwei Shan Hsiang, Tao Yuan Hsien 333, Taiwan, R.O.C.
Tel: 886-3-271-8666 Fax: 886-3-318-0155

Polarization	Horizontal	Test Freq. (MHz)	5260																																																																						
Test Configuration	2																																																																								
Level (dBuV/m)  Frequency (MHz) <table><tr><th></th><th>Freq. MHz</th><th>Emission level dBuV/m</th><th>Limit dBuV/m</th><th>Margin dB</th><th>SA reading dBuV</th><th>Factor dB</th><th>Remark</th><th>ANT High cm</th><th>Turn Table deg</th></tr><tr><td>1</td><td>1050.00</td><td>35.07</td><td>54.00</td><td>-18.93</td><td>44.28</td><td>-9.21</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>2</td><td>1050.00</td><td>45.42</td><td>74.00</td><td>-28.58</td><td>54.63</td><td>-9.21</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>3</td><td>5350.00</td><td>36.36</td><td>54.00</td><td>-17.64</td><td>31.27</td><td>5.09</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>4</td><td>5350.00</td><td>51.43</td><td>74.00</td><td>-22.57</td><td>46.34</td><td>5.09</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>5</td><td>10520.00</td><td>46.53</td><td>54.00</td><td>-7.47</td><td>31.66</td><td>14.87</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>6</td><td>10520.00</td><td>61.71</td><td>74.00</td><td>-12.29</td><td>46.84</td><td>14.87</td><td>Peak</td><td>---</td><td>---</td></tr></table>					Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg	1	1050.00	35.07	54.00	-18.93	44.28	-9.21	Average	---	---	2	1050.00	45.42	74.00	-28.58	54.63	-9.21	Peak	---	---	3	5350.00	36.36	54.00	-17.64	31.27	5.09	Average	---	---	4	5350.00	51.43	74.00	-22.57	46.34	5.09	Peak	---	---	5	10520.00	46.53	54.00	-7.47	31.66	14.87	Average	---	---	6	10520.00	61.71	74.00	-12.29	46.84	14.87	Peak	---	---
	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg																																																																
1	1050.00	35.07	54.00	-18.93	44.28	-9.21	Average	---	---																																																																
2	1050.00	45.42	74.00	-28.58	54.63	-9.21	Peak	---	---																																																																
3	5350.00	36.36	54.00	-17.64	31.27	5.09	Average	---	---																																																																
4	5350.00	51.43	74.00	-22.57	46.34	5.09	Peak	---	---																																																																
5	10520.00	46.53	54.00	-7.47	31.66	14.87	Average	---	---																																																																
6	10520.00	61.71	74.00	-12.29	46.84	14.87	Peak	---	---																																																																
Note 1: “>20dB” means spurious emission levels that exceed the level of 20 dB below the applicable limit. Note 2: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.																																																																									




International Certification Corp.

No. 3-1, Lane 6, Wen San 3rd St., Kwei Shan Hsiang, Tao Yuan Hsien 333, Taiwan, R.O.C.

Tel: 886-3-271-8666

Fax: 886-3-318-0155

Polarization	Vertical	Test Freq. (MHz)	5260																																																																												
Test Configuration	2																																																																														
 <table><tr><th></th><th>Freq. MHz</th><th>Emission level dBuV/m</th><th>Limit dBuV/m</th><th>Margin dB</th><th>SA reading dBuV</th><th>Factor dB</th><th>Remark</th><th>ANT High cm</th><th>Turn Table deg</th></tr><tr><td>1</td><td>1050.00</td><td>36.47</td><td>54.00</td><td>-17.53</td><td>45.68</td><td>-9.21</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>2</td><td>1050.00</td><td>46.66</td><td>74.00</td><td>-27.34</td><td>55.87</td><td>-9.21</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>3</td><td>5350.00</td><td>40.55</td><td>54.00</td><td>-13.45</td><td>35.46</td><td>5.09</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>4</td><td>5350.00</td><td>53.76</td><td>74.00</td><td>-20.24</td><td>48.67</td><td>5.09</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>5</td><td>10520.00</td><td>52.83</td><td>54.00</td><td>-1.17</td><td>37.96</td><td>14.87</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>6</td><td>10520.00</td><td>68.73</td><td>74.00</td><td>-5.27</td><td>53.86</td><td>14.87</td><td>Peak</td><td>---</td><td>---</td></tr></table>											Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg	1	1050.00	36.47	54.00	-17.53	45.68	-9.21	Average	---	---	2	1050.00	46.66	74.00	-27.34	55.87	-9.21	Peak	---	---	3	5350.00	40.55	54.00	-13.45	35.46	5.09	Average	---	---	4	5350.00	53.76	74.00	-20.24	48.67	5.09	Peak	---	---	5	10520.00	52.83	54.00	-1.17	37.96	14.87	Average	---	---	6	10520.00	68.73	74.00	-5.27	53.86	14.87	Peak	---	---
	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg																																																																						
1	1050.00	36.47	54.00	-17.53	45.68	-9.21	Average	---	---																																																																						
2	1050.00	46.66	74.00	-27.34	55.87	-9.21	Peak	---	---																																																																						
3	5350.00	40.55	54.00	-13.45	35.46	5.09	Average	---	---																																																																						
4	5350.00	53.76	74.00	-20.24	48.67	5.09	Peak	---	---																																																																						
5	10520.00	52.83	54.00	-1.17	37.96	14.87	Average	---	---																																																																						
6	10520.00	68.73	74.00	-5.27	53.86	14.87	Peak	---	---																																																																						
Note 1: “>20dB” means spurious emission levels that exceed the level of 20 dB below the applicable limit. Note 2: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.																																																																															



International Certification Corp.

No. 3-1, Lane 6, Wen San 3rd St., Kwei Shan Hsiang, Tao Yuan Hsien 333, Taiwan, R.O.C.
Tel: 886-3-271-8666 Fax: 886-3-318-0155

Polarization	Horizontal	Test Freq. (MHz)	5300																																																																														
Test Configuration	2																																																																																
<table><tr><th>Freq.</th><th>Emission level</th><th>Limit</th><th>Margin</th><th>SA reading</th><th>Factor</th><th>Remark</th><th>ANT High</th><th>Turn Table</th></tr><tr><th>MHz</th><th>dBUV/m</th><th>dBUV/m</th><th>dB</th><th>dBUV</th><th>dB</th><th></th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>1050.00</td><td>35.38</td><td>54.00</td><td>-18.62</td><td>44.59</td><td>-9.21</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>2</td><td>1050.00</td><td>46.10</td><td>74.00</td><td>-27.90</td><td>55.31</td><td>-9.21</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>3</td><td>5350.00</td><td>37.01</td><td>54.00</td><td>-16.99</td><td>31.92</td><td>5.09</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>4</td><td>5350.00</td><td>50.32</td><td>74.00</td><td>-23.68</td><td>45.23</td><td>5.09</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>5</td><td>10600.00</td><td>47.41</td><td>54.00</td><td>-6.59</td><td>32.47</td><td>14.94</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>6</td><td>10600.00</td><td>61.77</td><td>74.00</td><td>-12.23</td><td>46.83</td><td>14.94</td><td>Peak</td><td>---</td><td>---</td></tr></table>				Freq.	Emission level	Limit	Margin	SA reading	Factor	Remark	ANT High	Turn Table	MHz	dBUV/m	dBUV/m	dB	dBUV	dB		cm	deg	1	1050.00	35.38	54.00	-18.62	44.59	-9.21	Average	---	---	2	1050.00	46.10	74.00	-27.90	55.31	-9.21	Peak	---	---	3	5350.00	37.01	54.00	-16.99	31.92	5.09	Average	---	---	4	5350.00	50.32	74.00	-23.68	45.23	5.09	Peak	---	---	5	10600.00	47.41	54.00	-6.59	32.47	14.94	Average	---	---	6	10600.00	61.77	74.00	-12.23	46.83	14.94	Peak	---	---
Freq.	Emission level	Limit	Margin	SA reading	Factor	Remark	ANT High	Turn Table																																																																									
MHz	dBUV/m	dBUV/m	dB	dBUV	dB		cm	deg																																																																									
1	1050.00	35.38	54.00	-18.62	44.59	-9.21	Average	---	---																																																																								
2	1050.00	46.10	74.00	-27.90	55.31	-9.21	Peak	---	---																																																																								
3	5350.00	37.01	54.00	-16.99	31.92	5.09	Average	---	---																																																																								
4	5350.00	50.32	74.00	-23.68	45.23	5.09	Peak	---	---																																																																								
5	10600.00	47.41	54.00	-6.59	32.47	14.94	Average	---	---																																																																								
6	10600.00	61.77	74.00	-12.23	46.83	14.94	Peak	---	---																																																																								
Note 1: “>20dB” means spurious emission levels that exceed the level of 20 dB below the applicable limit. Note 2: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.																																																																																	



International Certification Corp.

No. 3-1, Lane 6, Wen San 3rd St., Kwei Shan Hsiang, Tao Yuan Hsien 333, Taiwan, R.O.C.
Tel: 886-3-271-8666 Fax: 886-3-318-0155

Polarization	Horizontal		Test Freq. (MHz)		5320				
Test Configuration	2								
The graph displays the emission level in dBUV/m on the y-axis (ranging from 0 to 117) against frequency in MHz on the x-axis (ranging from 1000 to 40000). A red line represents the FCC PART15E limit, and a lower red line represents the FCC PART15E (AVG) limit. Blue vertical lines indicate specific measurement points labeled 1 through 6. The emission levels are generally below the limits, with some peaks near 1050 MHz and 10640 MHz.									
	Freq.	Emission	Limit	Margin	SA	Factor	Remark	ANT	Turn
	MHz	level			reading			High	Table
		dBuV/m	dBuV/m	dB	dBuV	dB		cm	deg
1	1050.00	36.00	54.00	-18.00	45.21	-9.21	Average	---	---
2	1050.00	46.05	74.00	-27.95	55.26	-9.21	Peak	---	---
3	5350.00	41.37	54.00	-12.63	36.28	5.09	Average	---	---
4	5350.00	56.05	74.00	-17.95	50.96	5.09	Peak	---	---
5	10640.00	47.62	54.00	-6.38	32.64	14.98	Average	---	---
6	10640.00	61.39	74.00	-12.61	46.41	14.98	Peak	---	---

Note 1: “>20dB” means spurious emission levels that exceed the level of 20 dB below the applicable limit.

Note 2: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.




International Certification Corp.

No. 3-1, Lane 6, Wen San 3rd St., Kwei Shan Hsiang, Tao Yuan Hsien 333, Taiwan, R.O.C.

Tel: 886-3-271-8666

Fax: 886-3-318-0155

Polarization	Vertical			Test Freq. (MHz)		5320																																																																																													
Test Configuration	2																																																																																																		
 <table><tr><th></th><th>Freq.</th><th>Emission</th><th>Limit</th><th>Margin</th><th>SA</th><th>Factor</th><th>Remark</th><th>ANT</th><th>Turn</th></tr><tr><th></th><th>MHz</th><th>level</th><th>dBuV/m</th><th>dB</th><th>reading</th><th>dB</th><th></th><th>High</th><th>Table</th></tr><tr><th></th><th></th><th>dBuV/m</th><th></th><th></th><th>dBuV</th><th></th><th></th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>1050.00</td><td>36.16</td><td>54.00</td><td>-17.84</td><td>45.37</td><td>-9.21</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>2</td><td>1050.00</td><td>46.20</td><td>74.00</td><td>-27.80</td><td>55.41</td><td>-9.21</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>3</td><td>5350.00</td><td>48.06</td><td>54.00</td><td>-5.94</td><td>42.97</td><td>5.09</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>4</td><td>5350.00</td><td>64.33</td><td>74.00</td><td>-9.67</td><td>59.24</td><td>5.09</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>5</td><td>10640.00</td><td>52.97</td><td>54.00</td><td>-1.03</td><td>37.99</td><td>14.98</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>6</td><td>10640.00</td><td>68.50</td><td>74.00</td><td>-5.50</td><td>53.52</td><td>14.98</td><td>Peak</td><td>---</td><td>---</td></tr></table>											Freq.	Emission	Limit	Margin	SA	Factor	Remark	ANT	Turn		MHz	level	dBuV/m	dB	reading	dB		High	Table			dBuV/m			dBuV			cm	deg	1	1050.00	36.16	54.00	-17.84	45.37	-9.21	Average	---	---	2	1050.00	46.20	74.00	-27.80	55.41	-9.21	Peak	---	---	3	5350.00	48.06	54.00	-5.94	42.97	5.09	Average	---	---	4	5350.00	64.33	74.00	-9.67	59.24	5.09	Peak	---	---	5	10640.00	52.97	54.00	-1.03	37.99	14.98	Average	---	---	6	10640.00	68.50	74.00	-5.50	53.52	14.98	Peak	---	---
	Freq.	Emission	Limit	Margin	SA	Factor	Remark	ANT	Turn																																																																																										
	MHz	level	dBuV/m	dB	reading	dB		High	Table																																																																																										
		dBuV/m			dBuV			cm	deg																																																																																										
1	1050.00	36.16	54.00	-17.84	45.37	-9.21	Average	---	---																																																																																										
2	1050.00	46.20	74.00	-27.80	55.41	-9.21	Peak	---	---																																																																																										
3	5350.00	48.06	54.00	-5.94	42.97	5.09	Average	---	---																																																																																										
4	5350.00	64.33	74.00	-9.67	59.24	5.09	Peak	---	---																																																																																										
5	10640.00	52.97	54.00	-1.03	37.99	14.98	Average	---	---																																																																																										
6	10640.00	68.50	74.00	-5.50	53.52	14.98	Peak	---	---																																																																																										
Note 1: “>20dB” means spurious emission levels that exceed the level of 20 dB below the applicable limit. Note 2: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.																																																																																																			



International Certification Corp.


No. 3-1, Lane 6, Wen San 3rd St., Kwei Shan Hsiang, Tao Yuan Hsien 333, Taiwan, R.O.C.
Tel: 886-3-271-8666 Fax: 886-3-318-0155

Polarization	Horizontal	Test Freq. (MHz)	5500																																																																																										
Test Configuration	2																																																																																												
The graph displays the emission level in dBuV/m on the y-axis (0 to 117) against frequency in MHz on the x-axis (1000 to 40000). A red stepped line represents the FCC Part 15E (74) limit, and a lower red line represents the FCC Part 15E (AVG) limit. Blue vertical lines with markers indicate specific test points. The data points are summarized in the table below: <table><tr><th></th><th>Freq. MHz</th><th>Emission level dBuV/m</th><th>Limit dBuV/m</th><th>Margin dB</th><th>SA reading dBuV</th><th>Factor dB</th><th>Remark</th><th>ANT High cm</th><th>Turn Table deg</th></tr><tr><td>1</td><td>1050.00</td><td>35.06</td><td>54.00</td><td>-18.94</td><td>44.27</td><td>-9.21</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>2</td><td>1050.00</td><td>45.15</td><td>74.00</td><td>-28.85</td><td>54.36</td><td>-9.21</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>3</td><td>5460.00</td><td>38.32</td><td>54.00</td><td>-15.68</td><td>33.14</td><td>5.18</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>4</td><td>5460.00</td><td>53.83</td><td>74.00</td><td>-20.17</td><td>48.65</td><td>5.18</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>5</td><td>5470.00</td><td>44.52</td><td>54.00</td><td>-9.48</td><td>39.33</td><td>5.19</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>6</td><td>5470.00</td><td>61.43</td><td>74.00</td><td>-12.57</td><td>56.24</td><td>5.19</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>7</td><td>11000.00</td><td>48.80</td><td>54.00</td><td>-5.20</td><td>33.52</td><td>15.28</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>8</td><td>11000.00</td><td>62.12</td><td>74.00</td><td>-11.88</td><td>46.84</td><td>15.28</td><td>Peak</td><td>---</td><td>---</td></tr></table>					Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg	1	1050.00	35.06	54.00	-18.94	44.27	-9.21	Average	---	---	2	1050.00	45.15	74.00	-28.85	54.36	-9.21	Peak	---	---	3	5460.00	38.32	54.00	-15.68	33.14	5.18	Average	---	---	4	5460.00	53.83	74.00	-20.17	48.65	5.18	Peak	---	---	5	5470.00	44.52	54.00	-9.48	39.33	5.19	Average	---	---	6	5470.00	61.43	74.00	-12.57	56.24	5.19	Peak	---	---	7	11000.00	48.80	54.00	-5.20	33.52	15.28	Average	---	---	8	11000.00	62.12	74.00	-11.88	46.84	15.28	Peak	---	---
	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg																																																																																				
1	1050.00	35.06	54.00	-18.94	44.27	-9.21	Average	---	---																																																																																				
2	1050.00	45.15	74.00	-28.85	54.36	-9.21	Peak	---	---																																																																																				
3	5460.00	38.32	54.00	-15.68	33.14	5.18	Average	---	---																																																																																				
4	5460.00	53.83	74.00	-20.17	48.65	5.18	Peak	---	---																																																																																				
5	5470.00	44.52	54.00	-9.48	39.33	5.19	Average	---	---																																																																																				
6	5470.00	61.43	74.00	-12.57	56.24	5.19	Peak	---	---																																																																																				
7	11000.00	48.80	54.00	-5.20	33.52	15.28	Average	---	---																																																																																				
8	11000.00	62.12	74.00	-11.88	46.84	15.28	Peak	---	---																																																																																				
Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit. Note 2: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.																																																																																													



International Certification Corp.

No. 3-1, Lane 6, Wen San 3rd St., Kwei Shan Hsiang, Tao Yuan Hsien 333, Taiwan, R.O.C.
Tel: 886-3-271-8666 Fax: 886-3-318-0155

Polarization	Vertical		Test Freq. (MHz)		5500																																																																																																																		
Test Configuration	2																																																																																																																						
 <table><tr><th></th><th>Freq.</th><th>Emission</th><th>Limit</th><th>Margin</th><th>SA</th><th>Factor</th><th>Remark</th><th>ANT</th><th>Turn</th></tr><tr><th></th><th>MHz</th><th>level</th><th>dBuV/m</th><th>dB</th><th>reading</th><th>dB</th><th></th><th>High</th><th>Table</th></tr><tr><th></th><th></th><th>dBuV/m</th><th></th><th></th><th>dBuV</th><th></th><th></th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>1050.00</td><td>36.18</td><td>54.00</td><td>-17.82</td><td>45.39</td><td>-9.21</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>2</td><td>1050.00</td><td>47.14</td><td>74.00</td><td>-26.86</td><td>56.35</td><td>-9.21</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>3</td><td>5460.00</td><td>45.39</td><td>54.00</td><td>-8.61</td><td>40.21</td><td>5.18</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>4</td><td>5460.00</td><td>61.13</td><td>74.00</td><td>-12.87</td><td>55.95</td><td>5.18</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>5</td><td>5470.00</td><td>52.22</td><td>54.00</td><td>-1.78</td><td>47.03</td><td>5.19</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>6</td><td>5470.00</td><td>68.30</td><td>74.00</td><td>-5.70</td><td>63.11</td><td>5.19</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>7</td><td>11000.00</td><td>51.83</td><td>54.00</td><td>-2.17</td><td>36.55</td><td>15.28</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>8</td><td>11000.00</td><td>66.41</td><td>74.00</td><td>-7.59</td><td>51.13</td><td>15.28</td><td>Peak</td><td>---</td><td>---</td></tr></table>											Freq.	Emission	Limit	Margin	SA	Factor	Remark	ANT	Turn		MHz	level	dBuV/m	dB	reading	dB		High	Table			dBuV/m			dBuV			cm	deg	1	1050.00	36.18	54.00	-17.82	45.39	-9.21	Average	---	---	2	1050.00	47.14	74.00	-26.86	56.35	-9.21	Peak	---	---	3	5460.00	45.39	54.00	-8.61	40.21	5.18	Average	---	---	4	5460.00	61.13	74.00	-12.87	55.95	5.18	Peak	---	---	5	5470.00	52.22	54.00	-1.78	47.03	5.19	Average	---	---	6	5470.00	68.30	74.00	-5.70	63.11	5.19	Peak	---	---	7	11000.00	51.83	54.00	-2.17	36.55	15.28	Average	---	---	8	11000.00	66.41	74.00	-7.59	51.13	15.28	Peak	---	---
	Freq.	Emission	Limit	Margin	SA	Factor	Remark	ANT	Turn																																																																																																														
	MHz	level	dBuV/m	dB	reading	dB		High	Table																																																																																																														
		dBuV/m			dBuV			cm	deg																																																																																																														
1	1050.00	36.18	54.00	-17.82	45.39	-9.21	Average	---	---																																																																																																														
2	1050.00	47.14	74.00	-26.86	56.35	-9.21	Peak	---	---																																																																																																														
3	5460.00	45.39	54.00	-8.61	40.21	5.18	Average	---	---																																																																																																														
4	5460.00	61.13	74.00	-12.87	55.95	5.18	Peak	---	---																																																																																																														
5	5470.00	52.22	54.00	-1.78	47.03	5.19	Average	---	---																																																																																																														
6	5470.00	68.30	74.00	-5.70	63.11	5.19	Peak	---	---																																																																																																														
7	11000.00	51.83	54.00	-2.17	36.55	15.28	Average	---	---																																																																																																														
8	11000.00	66.41	74.00	-7.59	51.13	15.28	Peak	---	---																																																																																																														
Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit. Note 2: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.																																																																																																																							




International Certification Corp.

No. 3-1, Lane 6, Wen San 3rd St., Kwei Shan Hsiang, Tao Yuan Hsien 333, Taiwan, R.O.C.

Tel: 886-3-271-8666


Fax: 886-3-318-0155

Polarization	Horizontal		Test Freq. (MHz)		5580																																																																																											
Test Configuration	2																																																																																															
 <table><tr><th></th><th>Freq.</th><th>Emission</th><th>Limit</th><th>Margin</th><th>SA</th><th>Factor</th><th>Remark</th><th>ANT</th><th>Turn</th></tr><tr><th></th><th>MHz</th><th>level</th><th></th><th></th><th>reading</th><th></th><th></th><th>High</th><th>Table</th></tr><tr><th></th><th></th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB</th><th></th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>1050.00</td><td>35.46</td><td>54.00</td><td>-18.54</td><td>44.67</td><td>-9.21</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>2</td><td>1050.00</td><td>45.00</td><td>74.00</td><td>-29.00</td><td>54.21</td><td>-9.21</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>3</td><td>5418.50</td><td>36.37</td><td>54.00</td><td>-17.63</td><td>31.25</td><td>5.12</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>4</td><td>5418.50</td><td>50.05</td><td>74.00</td><td>-23.95</td><td>44.93</td><td>5.12</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>5</td><td>11160.00</td><td>48.86</td><td>54.00</td><td>-5.14</td><td>33.68</td><td>15.18</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>6</td><td>11160.00</td><td>62.21</td><td>74.00</td><td>-11.79</td><td>47.03</td><td>15.18</td><td>Peak</td><td>---</td><td>---</td></tr></table>								Freq.	Emission	Limit	Margin	SA	Factor	Remark	ANT	Turn		MHz	level			reading			High	Table			dBuV/m	dBuV/m	dB	dBuV	dB		cm	deg	1	1050.00	35.46	54.00	-18.54	44.67	-9.21	Average	---	---	2	1050.00	45.00	74.00	-29.00	54.21	-9.21	Peak	---	---	3	5418.50	36.37	54.00	-17.63	31.25	5.12	Average	---	---	4	5418.50	50.05	74.00	-23.95	44.93	5.12	Peak	---	---	5	11160.00	48.86	54.00	-5.14	33.68	15.18	Average	---	---	6	11160.00	62.21	74.00	-11.79	47.03	15.18	Peak	---	---
	Freq.	Emission	Limit	Margin	SA	Factor	Remark	ANT	Turn																																																																																							
	MHz	level			reading			High	Table																																																																																							
		dBuV/m	dBuV/m	dB	dBuV	dB		cm	deg																																																																																							
1	1050.00	35.46	54.00	-18.54	44.67	-9.21	Average	---	---																																																																																							
2	1050.00	45.00	74.00	-29.00	54.21	-9.21	Peak	---	---																																																																																							
3	5418.50	36.37	54.00	-17.63	31.25	5.12	Average	---	---																																																																																							
4	5418.50	50.05	74.00	-23.95	44.93	5.12	Peak	---	---																																																																																							
5	11160.00	48.86	54.00	-5.14	33.68	15.18	Average	---	---																																																																																							
6	11160.00	62.21	74.00	-11.79	47.03	15.18	Peak	---	---																																																																																							
Note 1: “>20dB” means spurious emission levels that exceed the level of 20 dB below the applicable limit. Note 2: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.																																																																																																



International Certification Corp.

No. 3-1, Lane 6, Wen San 3rd St., Kwei Shan Hsiang, Tao Yuan Hsien 333, Taiwan, R.O.C.
Tel: 886-3-271-8666 Fax: 886-3-318-0155

Polarization	Vertical			Test Freq. (MHz)		5580																																																																																													
Test Configuration	2																																																																																																		
Level (dBuV/m)  <table><tr><th></th><th>Freq.</th><th>Emission</th><th>Limit</th><th>Margin</th><th>SA</th><th>Factor</th><th>Remark</th><th>ANT</th><th>Turn</th></tr><tr><th></th><th>MHz</th><th>level</th><th>dBuV/m</th><th>dB</th><th>reading</th><th>dB</th><th></th><th>High</th><th>Table</th></tr><tr><th></th><th></th><th>dBuV/m</th><th></th><th></th><th>dBuV</th><th></th><th></th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>1050.00</td><td>36.41</td><td>54.00</td><td>-17.59</td><td>45.62</td><td>-9.21</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>2</td><td>1050.00</td><td>46.63</td><td>74.00</td><td>-27.37</td><td>55.84</td><td>-9.21</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>3</td><td>5418.50</td><td>40.83</td><td>54.00</td><td>-13.17</td><td>35.71</td><td>5.12</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>4</td><td>5418.50</td><td>53.25</td><td>74.00</td><td>-20.75</td><td>48.13</td><td>5.12</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>5</td><td>11160.00</td><td>51.34</td><td>54.00</td><td>-2.66</td><td>36.16</td><td>15.18</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>6</td><td>11160.00</td><td>65.98</td><td>74.00</td><td>-8.02</td><td>50.80</td><td>15.18</td><td>Peak</td><td>---</td><td>---</td></tr></table>											Freq.	Emission	Limit	Margin	SA	Factor	Remark	ANT	Turn		MHz	level	dBuV/m	dB	reading	dB		High	Table			dBuV/m			dBuV			cm	deg	1	1050.00	36.41	54.00	-17.59	45.62	-9.21	Average	---	---	2	1050.00	46.63	74.00	-27.37	55.84	-9.21	Peak	---	---	3	5418.50	40.83	54.00	-13.17	35.71	5.12	Average	---	---	4	5418.50	53.25	74.00	-20.75	48.13	5.12	Peak	---	---	5	11160.00	51.34	54.00	-2.66	36.16	15.18	Average	---	---	6	11160.00	65.98	74.00	-8.02	50.80	15.18	Peak	---	---
	Freq.	Emission	Limit	Margin	SA	Factor	Remark	ANT	Turn																																																																																										
	MHz	level	dBuV/m	dB	reading	dB		High	Table																																																																																										
		dBuV/m			dBuV			cm	deg																																																																																										
1	1050.00	36.41	54.00	-17.59	45.62	-9.21	Average	---	---																																																																																										
2	1050.00	46.63	74.00	-27.37	55.84	-9.21	Peak	---	---																																																																																										
3	5418.50	40.83	54.00	-13.17	35.71	5.12	Average	---	---																																																																																										
4	5418.50	53.25	74.00	-20.75	48.13	5.12	Peak	---	---																																																																																										
5	11160.00	51.34	54.00	-2.66	36.16	15.18	Average	---	---																																																																																										
6	11160.00	65.98	74.00	-8.02	50.80	15.18	Peak	---	---																																																																																										
Note 1: “>20dB” means spurious emission levels that exceed the level of 20 dB below the applicable limit. Note 2: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.																																																																																																			



International Certification Corp.

No. 3-1, Lane 6, Wen San 3rd St., Kwei Shan Hsiang, Tao Yuan Hsien 333, Taiwan, R.O.C.

Tel: 886-3-271-8666

Fax: 886-3-318-0155

Polarization	Horizontal		Test Freq. (MHz)		5700																																																																										
Test Configuration	2																																																																														
Level (dBuV/m) Frequency (MHz) <table><tr><th></th><th>Freq. MHz</th><th>Emission level dBuV/m</th><th>Limit dBuV/m</th><th>Margin dB</th><th>SA reading dBuV</th><th>Factor dB</th><th>Remark</th><th>ANT High cm</th><th>Turn Table deg</th></tr><tr><td>1</td><td>1050.00</td><td>35.42</td><td>54.00</td><td>-18.58</td><td>44.63</td><td>-9.21</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>2</td><td>1050.00</td><td>45.62</td><td>74.00</td><td>-28.38</td><td>54.83</td><td>-9.21</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>3</td><td>5725.00</td><td>41.89</td><td>54.00</td><td>-12.11</td><td>36.33</td><td>5.56</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>4</td><td>5725.00</td><td>57.83</td><td>74.00</td><td>-16.17</td><td>52.27</td><td>5.56</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>5</td><td>11400.00</td><td>47.72</td><td>54.00</td><td>-6.28</td><td>32.69</td><td>15.03</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>6</td><td>11400.00</td><td>61.91</td><td>74.00</td><td>-12.09</td><td>46.88</td><td>15.03</td><td>Peak</td><td>---</td><td>---</td></tr></table>											Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg	1	1050.00	35.42	54.00	-18.58	44.63	-9.21	Average	---	---	2	1050.00	45.62	74.00	-28.38	54.83	-9.21	Peak	---	---	3	5725.00	41.89	54.00	-12.11	36.33	5.56	Average	---	---	4	5725.00	57.83	74.00	-16.17	52.27	5.56	Peak	---	---	5	11400.00	47.72	54.00	-6.28	32.69	15.03	Average	---	---	6	11400.00	61.91	74.00	-12.09	46.88	15.03	Peak	---	---
	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg																																																																						
1	1050.00	35.42	54.00	-18.58	44.63	-9.21	Average	---	---																																																																						
2	1050.00	45.62	74.00	-28.38	54.83	-9.21	Peak	---	---																																																																						
3	5725.00	41.89	54.00	-12.11	36.33	5.56	Average	---	---																																																																						
4	5725.00	57.83	74.00	-16.17	52.27	5.56	Peak	---	---																																																																						
5	11400.00	47.72	54.00	-6.28	32.69	15.03	Average	---	---																																																																						
6	11400.00	61.91	74.00	-12.09	46.88	15.03	Peak	---	---																																																																						
Note 1: “>20dB” means spurious emission levels that exceed the level of 20 dB below the applicable limit. Note 2: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.																																																																															




International Certification Corp.

No. 3-1, Lane 6, Wen San 3rd St., Kwei Shan Hsiang, Tao Yuan Hsien 333, Taiwan, R.O.C.

Tel: 886-3-271-8666

Fax: 886-3-318-0155

Polarization	Vertical			Test Freq. (MHz)			5700																																																																																												
Test Configuration	2																																																																																																		
 <table><tr><th></th><th>Freq.</th><th>Emission</th><th>Limit</th><th>Margin</th><th>SA</th><th>Factor</th><th>Remark</th><th>ANT</th><th>Turn</th></tr><tr><th></th><th>MHz</th><th>level</th><th></th><th></th><th>reading</th><th></th><th></th><th>High</th><th>Table</th></tr><tr><th></th><th></th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB</th><th></th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>1050.00</td><td>36.41</td><td>54.00</td><td>-17.59</td><td>45.62</td><td>-9.21</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>2</td><td>1050.00</td><td>46.70</td><td>74.00</td><td>-27.30</td><td>55.91</td><td>-9.21</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>3</td><td>5725.00</td><td>52.80</td><td>54.00</td><td>-1.20</td><td>47.24</td><td>5.56</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>4</td><td>5725.00</td><td>69.80</td><td>74.00</td><td>-4.20</td><td>64.24</td><td>5.56</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>5</td><td>11400.00</td><td>47.53</td><td>54.00</td><td>-6.47</td><td>32.50</td><td>15.03</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>6</td><td>11400.00</td><td>61.55</td><td>74.00</td><td>-12.45</td><td>46.52</td><td>15.03</td><td>Peak</td><td>---</td><td>---</td></tr></table>											Freq.	Emission	Limit	Margin	SA	Factor	Remark	ANT	Turn		MHz	level			reading			High	Table			dBuV/m	dBuV/m	dB	dBuV	dB		cm	deg	1	1050.00	36.41	54.00	-17.59	45.62	-9.21	Average	---	---	2	1050.00	46.70	74.00	-27.30	55.91	-9.21	Peak	---	---	3	5725.00	52.80	54.00	-1.20	47.24	5.56	Average	---	---	4	5725.00	69.80	74.00	-4.20	64.24	5.56	Peak	---	---	5	11400.00	47.53	54.00	-6.47	32.50	15.03	Average	---	---	6	11400.00	61.55	74.00	-12.45	46.52	15.03	Peak	---	---
	Freq.	Emission	Limit	Margin	SA	Factor	Remark	ANT	Turn																																																																																										
	MHz	level			reading			High	Table																																																																																										
		dBuV/m	dBuV/m	dB	dBuV	dB		cm	deg																																																																																										
1	1050.00	36.41	54.00	-17.59	45.62	-9.21	Average	---	---																																																																																										
2	1050.00	46.70	74.00	-27.30	55.91	-9.21	Peak	---	---																																																																																										
3	5725.00	52.80	54.00	-1.20	47.24	5.56	Average	---	---																																																																																										
4	5725.00	69.80	74.00	-4.20	64.24	5.56	Peak	---	---																																																																																										
5	11400.00	47.53	54.00	-6.47	32.50	15.03	Average	---	---																																																																																										
6	11400.00	61.55	74.00	-12.45	46.52	15.03	Peak	---	---																																																																																										
Note 1: “>20dB” means spurious emission levels that exceed the level of 20 dB below the applicable limit. Note 2: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.																																																																																																			



International Certification Corp.

No. 3-1, Lane 6, Wen San 3rd St., Kwei Shan Hsiang, Tao Yuan Hsien 333, Taiwan, R.O.C.

Tel: 886-3-271-8666

Fax: 886-3-318-0155

Polarization	Horizontal		Test Freq. (MHz)		5180																																																																
Test Configuration	3																																																																				
Level (dBuV/m) Frequency (MHz) <table><tr><th></th><th>Freq. MHz</th><th>Emission level dBuV/m</th><th>Limit dBuV/m</th><th>Margin dB</th><th>SA reading dBuV</th><th>Factor dB</th><th>Remark</th><th>ANT High cm</th><th>Turn Table deg</th></tr><tr><td>1</td><td>1050.00</td><td>35.53</td><td>54.00</td><td>-18.47</td><td>44.74</td><td>-9.21</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>2</td><td>1050.00</td><td>46.11</td><td>74.00</td><td>-27.89</td><td>55.32</td><td>-9.21</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>3</td><td>5150.00</td><td>47.51</td><td>54.00</td><td>-6.49</td><td>42.57</td><td>4.94</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>4</td><td>5150.00</td><td>63.13</td><td>74.00</td><td>-10.87</td><td>58.19</td><td>4.94</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>5</td><td>10360.00</td><td>60.99</td><td>68.30</td><td>-7.31</td><td>46.28</td><td>14.71</td><td>Peak</td><td>---</td><td>---</td></tr></table>											Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg	1	1050.00	35.53	54.00	-18.47	44.74	-9.21	Average	---	---	2	1050.00	46.11	74.00	-27.89	55.32	-9.21	Peak	---	---	3	5150.00	47.51	54.00	-6.49	42.57	4.94	Average	---	---	4	5150.00	63.13	74.00	-10.87	58.19	4.94	Peak	---	---	5	10360.00	60.99	68.30	-7.31	46.28	14.71	Peak	---	---
	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg																																																												
1	1050.00	35.53	54.00	-18.47	44.74	-9.21	Average	---	---																																																												
2	1050.00	46.11	74.00	-27.89	55.32	-9.21	Peak	---	---																																																												
3	5150.00	47.51	54.00	-6.49	42.57	4.94	Average	---	---																																																												
4	5150.00	63.13	74.00	-10.87	58.19	4.94	Peak	---	---																																																												
5	10360.00	60.99	68.30	-7.31	46.28	14.71	Peak	---	---																																																												
Note 1: “>20dB” means spurious emission levels that exceed the level of 20 dB below the applicable limit. Note 2: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.																																																																					




International Certification Corp.

No. 3-1, Lane 6, Wen San 3rd St., Kwei Shan Hsiang, Tao Yuan Hsien 333, Taiwan, R.O.C.

Tel: 886-3-271-8666

Fax: 886-3-318-0155

Polarization	Vertical	Test Freq. (MHz)	5180																																																												
Test Configuration	3																																																														
 <table><tr><th></th><th>Freq. MHz</th><th>Emission level dBuV/m</th><th>Limit dBuV/m</th><th>Margin dB</th><th>SA reading dBuV</th><th>Factor dB</th><th>Remark</th><th>ANT High cm</th><th>Turn Table deg</th></tr><tr><td>1</td><td>1050.00</td><td>35.31</td><td>54.00</td><td>-18.69</td><td>44.52</td><td>-9.21</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>2</td><td>1050.00</td><td>46.26</td><td>74.00</td><td>-27.74</td><td>55.47</td><td>-9.21</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>3</td><td>5150.00</td><td>46.30</td><td>54.00</td><td>-7.70</td><td>41.36</td><td>4.94</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>4</td><td>5150.00</td><td>62.22</td><td>74.00</td><td>-11.78</td><td>57.28</td><td>4.94</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>5</td><td>10360.00</td><td>65.57</td><td>68.30</td><td>-2.73</td><td>50.86</td><td>14.71</td><td>Peak</td><td>---</td><td>---</td></tr></table>					Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg	1	1050.00	35.31	54.00	-18.69	44.52	-9.21	Average	---	---	2	1050.00	46.26	74.00	-27.74	55.47	-9.21	Peak	---	---	3	5150.00	46.30	54.00	-7.70	41.36	4.94	Average	---	---	4	5150.00	62.22	74.00	-11.78	57.28	4.94	Peak	---	---	5	10360.00	65.57	68.30	-2.73	50.86	14.71	Peak	---	---
	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg																																																						
1	1050.00	35.31	54.00	-18.69	44.52	-9.21	Average	---	---																																																						
2	1050.00	46.26	74.00	-27.74	55.47	-9.21	Peak	---	---																																																						
3	5150.00	46.30	54.00	-7.70	41.36	4.94	Average	---	---																																																						
4	5150.00	62.22	74.00	-11.78	57.28	4.94	Peak	---	---																																																						
5	10360.00	65.57	68.30	-2.73	50.86	14.71	Peak	---	---																																																						
Note 1: “>20dB” means spurious emission levels that exceed the level of 20 dB below the applicable limit. Note 2: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.																																																															



International Certification Corp.

No. 3-1, Lane 6, Wen San 3rd St., Kwei Shan Hsiang, Tao Yuan Hsien 333, Taiwan, R.O.C.

Tel: 886-3-271-8666

Fax: 886-3-318-0155

Polarization	Horizontal		Test Freq. (MHz)		5200																																																																
Test Configuration	3																																																																				
Level (dBuV/m) Frequency (MHz) <table><tr><th></th><th>Freq. MHz</th><th>Emission level dBuV/m</th><th>Limit dBuV/m</th><th>Margin dB</th><th>SA reading dBuV</th><th>Factor dB</th><th>Remark</th><th>ANT High cm</th><th>Turn Table deg</th></tr><tr><td>1</td><td>1050.00</td><td>35.17</td><td>54.00</td><td>-18.83</td><td>44.38</td><td>-9.21</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>2</td><td>1050.00</td><td>46.46</td><td>74.00</td><td>-27.54</td><td>55.67</td><td>-9.21</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>3</td><td>5150.00</td><td>37.81</td><td>54.00</td><td>-16.19</td><td>32.87</td><td>4.94</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>4</td><td>5150.00</td><td>53.50</td><td>74.00</td><td>-20.50</td><td>48.56</td><td>4.94</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>5</td><td>10400.00</td><td>60.64</td><td>68.30</td><td>-7.66</td><td>45.89</td><td>14.75</td><td>Peak</td><td>---</td><td>---</td></tr></table>											Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg	1	1050.00	35.17	54.00	-18.83	44.38	-9.21	Average	---	---	2	1050.00	46.46	74.00	-27.54	55.67	-9.21	Peak	---	---	3	5150.00	37.81	54.00	-16.19	32.87	4.94	Average	---	---	4	5150.00	53.50	74.00	-20.50	48.56	4.94	Peak	---	---	5	10400.00	60.64	68.30	-7.66	45.89	14.75	Peak	---	---
	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg																																																												
1	1050.00	35.17	54.00	-18.83	44.38	-9.21	Average	---	---																																																												
2	1050.00	46.46	74.00	-27.54	55.67	-9.21	Peak	---	---																																																												
3	5150.00	37.81	54.00	-16.19	32.87	4.94	Average	---	---																																																												
4	5150.00	53.50	74.00	-20.50	48.56	4.94	Peak	---	---																																																												
5	10400.00	60.64	68.30	-7.66	45.89	14.75	Peak	---	---																																																												
Note 1: “>20dB” means spurious emission levels that exceed the level of 20 dB below the applicable limit. Note 2: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.																																																																					




International Certification Corp.

No. 3-1, Lane 6, Wen San 3rd St., Kwei Shan Hsiang, Tao Yuan Hsien 333, Taiwan, R.O.C.

Tel: 886-3-271-8666

Fax: 886-3-318-0155


Polarization	Vertical				Test Freq. (MHz)	5200																																																															
Test Configuration	3																																																																				
<table><tr><th></th><th>Freq. MHz</th><th>Emission level dBuV/m</th><th>Limit dBuV/m</th><th>Margin dB</th><th>SA reading dBuV</th><th>Factor dB</th><th>Remark</th><th>ANT High cm</th><th>Turn Table deg</th></tr><tr><td>1</td><td>1050.00</td><td>35.47</td><td>54.00</td><td>-18.53</td><td>44.68</td><td>-9.21</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>2</td><td>1050.00</td><td>46.53</td><td>74.00</td><td>-27.47</td><td>55.74</td><td>-9.21</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>3</td><td>5150.00</td><td>36.16</td><td>54.00</td><td>-17.84</td><td>31.22</td><td>4.94</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>4</td><td>5150.00</td><td>50.30</td><td>74.00</td><td>-23.70</td><td>45.36</td><td>4.94</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>5</td><td>10400.00</td><td>66.17</td><td>68.30</td><td>-2.13</td><td>51.42</td><td>14.75</td><td>Peak</td><td>---</td><td>---</td></tr></table>											Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg	1	1050.00	35.47	54.00	-18.53	44.68	-9.21	Average	---	---	2	1050.00	46.53	74.00	-27.47	55.74	-9.21	Peak	---	---	3	5150.00	36.16	54.00	-17.84	31.22	4.94	Average	---	---	4	5150.00	50.30	74.00	-23.70	45.36	4.94	Peak	---	---	5	10400.00	66.17	68.30	-2.13	51.42	14.75	Peak	---	---
	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg																																																												
1	1050.00	35.47	54.00	-18.53	44.68	-9.21	Average	---	---																																																												
2	1050.00	46.53	74.00	-27.47	55.74	-9.21	Peak	---	---																																																												
3	5150.00	36.16	54.00	-17.84	31.22	4.94	Average	---	---																																																												
4	5150.00	50.30	74.00	-23.70	45.36	4.94	Peak	---	---																																																												
5	10400.00	66.17	68.30	-2.13	51.42	14.75	Peak	---	---																																																												
Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit. Note 2: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.																																																																					



International Certification Corp.

No. 3-1, Lane 6, Wen San 3rd St., Kwei Shan Hsiang, Tao Yuan Hsien 333, Taiwan, R.O.C.
Tel: 886-3-271-8666 Fax: 886-3-318-0155

Polarization	Horizontal	Test Freq. (MHz)	5240
Test Configuration	3		



The graph displays the emission level in dBUV/m on the y-axis (0 to 117) against frequency in MHz on the x-axis (1000 to 40000). A red line represents the FCC PART15E (AVG) limit, which is constant at 50.22 dBUV/m. A blue line represents the measured signal, which is below the limit across the frequency range. The measured signal is below the limit across the frequency range.

	Freq. MHz	Emission level dBUV/m	Limit dBUV/m	Margin dB	SA reading dBUV	Factor dB	Remark	ANT High cm	Turn Table deg
1	1050.00	36.13	54.00	-17.87	45.34	-9.21	Average	---	---
2	1050.00	46.71	74.00	-27.29	55.92	-9.21	Peak	---	---
3	5150.00	36.81	54.00	-17.19	31.87	4.94	Average	---	---
4	5150.00	50.22	74.00	-23.78	45.28	4.94	Peak	---	---
5	10480.00	61.76	68.30	-6.54	46.92	14.84	Peak	---	---

Note 1: “>20dB” means spurious emission levels that exceed the level of 20 dB below the applicable limit.

Note 2: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.



International Certification Corp.

No. 3-1, Lane 6, Wen San 3rd St., Kwei Shan Hsiang, Tao Yuan Hsien 333, Taiwan, R.O.C.
Tel: 886-3-271-8666 Fax: 886-3-318-0155

Polarization	Vertical			Test Freq. (MHz)		5240																																																															
Test Configuration	3																																																																				
Level (dBuV/m) Frequency (MHz) <table><tr><th></th><th>Freq. MHz</th><th>Emission level dBuV/m</th><th>Limit dBuV/m</th><th>Margin dB</th><th>SA reading dBuV</th><th>Factor dB</th><th>Remark</th><th>ANT High cm</th><th>Turn Table deg</th></tr><tr><td>1</td><td>1050.00</td><td>35.60</td><td>54.00</td><td>-18.40</td><td>44.81</td><td>-9.21</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>2</td><td>1050.00</td><td>46.72</td><td>74.00</td><td>-27.28</td><td>55.93</td><td>-9.21</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>3</td><td>5150.00</td><td>34.46</td><td>54.00</td><td>-19.54</td><td>29.52</td><td>4.94</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>4</td><td>5150.00</td><td>49.32</td><td>74.00</td><td>-24.68</td><td>44.38</td><td>4.94</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>5</td><td>10480.00</td><td>66.32</td><td>68.30</td><td>-1.98</td><td>51.48</td><td>14.84</td><td>Peak</td><td>---</td><td>---</td></tr></table>											Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg	1	1050.00	35.60	54.00	-18.40	44.81	-9.21	Average	---	---	2	1050.00	46.72	74.00	-27.28	55.93	-9.21	Peak	---	---	3	5150.00	34.46	54.00	-19.54	29.52	4.94	Average	---	---	4	5150.00	49.32	74.00	-24.68	44.38	4.94	Peak	---	---	5	10480.00	66.32	68.30	-1.98	51.48	14.84	Peak	---	---
	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg																																																												
1	1050.00	35.60	54.00	-18.40	44.81	-9.21	Average	---	---																																																												
2	1050.00	46.72	74.00	-27.28	55.93	-9.21	Peak	---	---																																																												
3	5150.00	34.46	54.00	-19.54	29.52	4.94	Average	---	---																																																												
4	5150.00	49.32	74.00	-24.68	44.38	4.94	Peak	---	---																																																												
5	10480.00	66.32	68.30	-1.98	51.48	14.84	Peak	---	---																																																												
Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit. Note 2: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.																																																																					



International Certification Corp.

No. 3-1, Lane 6, Wen San 3rd St., Kwei Shan Hsiang, Tao Yuan Hsien 333, Taiwan, R.O.C.

Tel: 886-3-271-8666

Fax: 886-3-318-0155

Polarization	Vertical	Test Freq. (MHz)	5260																																																																						
Test Configuration	3																																																																								
The graph displays the emission level in dBuV/m on the y-axis (0 to 117) against frequency in MHz on the x-axis (1000 to 40000). Two red lines represent the FCC Part 15E limits: a stepped line for (74) and a flat line for (AVG). Blue vertical lines with markers indicate test results at 1050 MHz (points 1, 2), 5350 MHz (points 3, 4), and 10520 MHz (points 5, 6). The test results are summarized in the table below. <table><tr><th></th><th>Freq. MHz</th><th>Emission level dBuV/m</th><th>Limit dBuV/m</th><th>Margin dB</th><th>SA reading dBuV</th><th>Factor dB</th><th>Remark</th><th>ANT High cm</th><th>Turn Table deg</th></tr><tr><td>1</td><td>1050.00</td><td>35.64</td><td>54.00</td><td>-18.36</td><td>44.85</td><td>-9.21</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>2</td><td>1050.00</td><td>46.58</td><td>74.00</td><td>-27.42</td><td>55.79</td><td>-9.21</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>3</td><td>5350.00</td><td>37.01</td><td>54.00</td><td>-16.99</td><td>31.92</td><td>5.09</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>4</td><td>5350.00</td><td>50.04</td><td>74.00</td><td>-23.96</td><td>44.95</td><td>5.09</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>5</td><td>10520.00</td><td>52.69</td><td>54.00</td><td>-1.31</td><td>37.82</td><td>14.87</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>6</td><td>10520.00</td><td>67.70</td><td>74.00</td><td>-6.30</td><td>52.83</td><td>14.87</td><td>Peak</td><td>---</td><td>---</td></tr></table>					Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg	1	1050.00	35.64	54.00	-18.36	44.85	-9.21	Average	---	---	2	1050.00	46.58	74.00	-27.42	55.79	-9.21	Peak	---	---	3	5350.00	37.01	54.00	-16.99	31.92	5.09	Average	---	---	4	5350.00	50.04	74.00	-23.96	44.95	5.09	Peak	---	---	5	10520.00	52.69	54.00	-1.31	37.82	14.87	Average	---	---	6	10520.00	67.70	74.00	-6.30	52.83	14.87	Peak	---	---
	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg																																																																
1	1050.00	35.64	54.00	-18.36	44.85	-9.21	Average	---	---																																																																
2	1050.00	46.58	74.00	-27.42	55.79	-9.21	Peak	---	---																																																																
3	5350.00	37.01	54.00	-16.99	31.92	5.09	Average	---	---																																																																
4	5350.00	50.04	74.00	-23.96	44.95	5.09	Peak	---	---																																																																
5	10520.00	52.69	54.00	-1.31	37.82	14.87	Average	---	---																																																																
6	10520.00	67.70	74.00	-6.30	52.83	14.87	Peak	---	---																																																																
Note 1: “>20dB” means spurious emission levels that exceed the level of 20 dB below the applicable limit. Note 2: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.																																																																									




International Certification Corp.

No. 3-1, Lane 6, Wen San 3rd St., Kwei Shan Hsiang, Tao Yuan Hsien 333, Taiwan, R.O.C.

Tel: 886-3-271-8666

Fax: 886-3-318-0155

Polarization	Horizontal			Test Freq. (MHz)		5300																																																																									
Test Configuration	3																																																																														
Level (dBuV/m)  <table><tr><th></th><th>Freq. MHz</th><th>Emission level dBuV/m</th><th>Limit dBuV/m</th><th>Margin dB</th><th>SA reading dBuV</th><th>Factor dB</th><th>Remark</th><th>ANT High cm</th><th>Turn Table deg</th></tr><tr><td>1</td><td>1050.00</td><td>35.59</td><td>54.00</td><td>-18.41</td><td>44.80</td><td>-9.21</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>2</td><td>1050.00</td><td>46.48</td><td>74.00</td><td>-27.52</td><td>55.69</td><td>-9.21</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>3</td><td>5350.00</td><td>40.71</td><td>54.00</td><td>-13.29</td><td>35.62</td><td>5.09</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>4</td><td>5350.00</td><td>58.77</td><td>74.00</td><td>-15.23</td><td>53.68</td><td>5.09</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>5</td><td>10600.00</td><td>46.95</td><td>54.00</td><td>-7.05</td><td>32.01</td><td>14.94</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>6</td><td>10600.00</td><td>60.47</td><td>74.00</td><td>-13.53</td><td>45.53</td><td>14.94</td><td>Peak</td><td>---</td><td>---</td></tr></table>											Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg	1	1050.00	35.59	54.00	-18.41	44.80	-9.21	Average	---	---	2	1050.00	46.48	74.00	-27.52	55.69	-9.21	Peak	---	---	3	5350.00	40.71	54.00	-13.29	35.62	5.09	Average	---	---	4	5350.00	58.77	74.00	-15.23	53.68	5.09	Peak	---	---	5	10600.00	46.95	54.00	-7.05	32.01	14.94	Average	---	---	6	10600.00	60.47	74.00	-13.53	45.53	14.94	Peak	---	---
	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg																																																																						
1	1050.00	35.59	54.00	-18.41	44.80	-9.21	Average	---	---																																																																						
2	1050.00	46.48	74.00	-27.52	55.69	-9.21	Peak	---	---																																																																						
3	5350.00	40.71	54.00	-13.29	35.62	5.09	Average	---	---																																																																						
4	5350.00	58.77	74.00	-15.23	53.68	5.09	Peak	---	---																																																																						
5	10600.00	46.95	54.00	-7.05	32.01	14.94	Average	---	---																																																																						
6	10600.00	60.47	74.00	-13.53	45.53	14.94	Peak	---	---																																																																						
Note 1: “>20dB” means spurious emission levels that exceed the level of 20 dB below the applicable limit. Note 2: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.																																																																															



International Certification Corp.

No. 3-1, Lane 6, Wen San 3rd St., Kwei Shan Hsiang, Tao Yuan Hsien 333, Taiwan, R.O.C.
Tel: 886-3-271-8666 Fax: 886-3-318-0155

Polarization	Vertical	Test Freq. (MHz)	5300						
Test Configuration	3								
The graph displays the emission level in dBuV/m on the y-axis (0 to 117) against frequency in MHz on the x-axis (1000 to 40000). A red line represents the FCC PART15E limit, and a blue line represents the test results. The test results show a peak at 5350 MHz and a peak at 10600 MHz, both exceeding the limit. The graph also shows the average level (FCC PART15E (AVG)) and the peak level (FCC PART15E (PEAK)).									
	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	1050.00	36.11	54.00	-17.89	45.32	-9.21	Average	---	---
2	1050.00	46.76	74.00	-27.24	55.97	-9.21	Peak	---	---
3	5350.00	37.71	54.00	-16.29	32.62	5.09	Average	---	---
4	5350.00	50.67	74.00	-23.33	45.58	5.09	Peak	---	---
5	10600.00	52.95	54.00	-1.05	38.01	14.94	Average	---	---
6	10600.00	67.63	74.00	-6.37	52.69	14.94	Peak	---	---

Note 1: “>20dB” means spurious emission levels that exceed the level of 20 dB below the applicable limit.
Note 2: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.



Polarization	Horizontal		Test Freq. (MHz)		5320																																																																										
Test Configuration	3																																																																														
The graph displays the emission level in dBuV/m on the y-axis (ranging from 0 to 117) against frequency in MHz on the x-axis (ranging from 1000 to 40000). A red line represents the FCC PART15E limit, which is constant at 70 dBuV/m. A blue line represents the test results, showing a peak at 1050 MHz and a higher peak at 5350 MHz. The test results are summarized in the table below. <table><tr><th></th><th>Freq. MHz</th><th>Emission level dBuV/m</th><th>Limit dBuV/m</th><th>Margin dB</th><th>SA reading dBuV</th><th>Factor dB</th><th>Remark</th><th>ANT High cm</th><th>Turn Table deg</th></tr><tr><td>1</td><td>1050.00</td><td>35.55</td><td>54.00</td><td>-18.45</td><td>44.76</td><td>-9.21</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>2</td><td>1050.00</td><td>46.17</td><td>74.00</td><td>-27.83</td><td>55.38</td><td>-9.21</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>3</td><td>5350.00</td><td>48.94</td><td>54.00</td><td>-5.06</td><td>43.85</td><td>5.09</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>4</td><td>5350.00</td><td>63.78</td><td>74.00</td><td>-10.22</td><td>58.69</td><td>5.09</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>5</td><td>10640.00</td><td>46.17</td><td>54.00</td><td>-7.83</td><td>31.19</td><td>14.98</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>6</td><td>10640.00</td><td>59.76</td><td>74.00</td><td>-14.24</td><td>44.78</td><td>14.98</td><td>Peak</td><td>---</td><td>---</td></tr></table>											Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg	1	1050.00	35.55	54.00	-18.45	44.76	-9.21	Average	---	---	2	1050.00	46.17	74.00	-27.83	55.38	-9.21	Peak	---	---	3	5350.00	48.94	54.00	-5.06	43.85	5.09	Average	---	---	4	5350.00	63.78	74.00	-10.22	58.69	5.09	Peak	---	---	5	10640.00	46.17	54.00	-7.83	31.19	14.98	Average	---	---	6	10640.00	59.76	74.00	-14.24	44.78	14.98	Peak	---	---
	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg																																																																						
1	1050.00	35.55	54.00	-18.45	44.76	-9.21	Average	---	---																																																																						
2	1050.00	46.17	74.00	-27.83	55.38	-9.21	Peak	---	---																																																																						
3	5350.00	48.94	54.00	-5.06	43.85	5.09	Average	---	---																																																																						
4	5350.00	63.78	74.00	-10.22	58.69	5.09	Peak	---	---																																																																						
5	10640.00	46.17	54.00	-7.83	31.19	14.98	Average	---	---																																																																						
6	10640.00	59.76	74.00	-14.24	44.78	14.98	Peak	---	---																																																																						
Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit. Note 2: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.																																																																															



International Certification Corp.

No. 3-1, Lane 6, Wen San 3rd St., Kwei Shan Hsiang, Tao Yuan Hsien 333, Taiwan, R.O.C.

Tel: 886-3-271-8666

Fax: 886-3-318-0155

Polarization	Vertical			Test Freq. (MHz)		5320																																																																									
Test Configuration	3																																																																														
The graph displays the emission level in dBuV/m on the y-axis (0 to 117) against frequency in MHz on the x-axis (1000 to 40000). A red line represents the FCC PART15E limit, which is 70 dBuV/m for frequencies between 1000 and 10000 MHz, and 50 dBuV/m for frequencies above 10000 MHz. A blue line represents the test results, showing a peak at 5350 MHz and a peak at 10640 MHz. The test results are summarized in the table below. <table><tr><th></th><th>Freq. MHz</th><th>Emission level dBuV/m</th><th>Limit dBuV/m</th><th>Margin dB</th><th>SA reading dBuV</th><th>Factor dB</th><th>Remark</th><th>ANT High cm</th><th>Turn Table deg</th></tr><tr><td>1</td><td>1050.00</td><td>36.01</td><td>54.00</td><td>-17.99</td><td>45.22</td><td>-9.21</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>2</td><td>1050.00</td><td>46.70</td><td>74.00</td><td>-27.30</td><td>55.91</td><td>-9.21</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>3</td><td>5350.00</td><td>45.35</td><td>54.00</td><td>-8.65</td><td>40.26</td><td>5.09</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>4</td><td>5350.00</td><td>61.94</td><td>74.00</td><td>-12.06</td><td>56.85</td><td>5.09</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>5</td><td>10640.00</td><td>52.90</td><td>54.00</td><td>-1.10</td><td>37.92</td><td>14.98</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>6</td><td>10640.00</td><td>67.94</td><td>74.00</td><td>-6.06</td><td>52.96</td><td>14.98</td><td>Peak</td><td>---</td><td>---</td></tr></table>											Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg	1	1050.00	36.01	54.00	-17.99	45.22	-9.21	Average	---	---	2	1050.00	46.70	74.00	-27.30	55.91	-9.21	Peak	---	---	3	5350.00	45.35	54.00	-8.65	40.26	5.09	Average	---	---	4	5350.00	61.94	74.00	-12.06	56.85	5.09	Peak	---	---	5	10640.00	52.90	54.00	-1.10	37.92	14.98	Average	---	---	6	10640.00	67.94	74.00	-6.06	52.96	14.98	Peak	---	---
	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg																																																																						
1	1050.00	36.01	54.00	-17.99	45.22	-9.21	Average	---	---																																																																						
2	1050.00	46.70	74.00	-27.30	55.91	-9.21	Peak	---	---																																																																						
3	5350.00	45.35	54.00	-8.65	40.26	5.09	Average	---	---																																																																						
4	5350.00	61.94	74.00	-12.06	56.85	5.09	Peak	---	---																																																																						
5	10640.00	52.90	54.00	-1.10	37.92	14.98	Average	---	---																																																																						
6	10640.00	67.94	74.00	-6.06	52.96	14.98	Peak	---	---																																																																						
Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit. Note 2: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.																																																																															



Polarization	Horizontal		Test Freq. (MHz)		5500																																																																																														
Test Configuration	3																																																																																																		
The graph displays the emission level in dBuV/m on the y-axis (0 to 117) against frequency in MHz on the x-axis (1000 to 40000). A red line represents the FCC Part 15E (74) limit, and a lower red line represents the FCC Part 15E (AVG) limit. Blue vertical lines indicate test results at specific frequencies, with points 1 through 8 labeled. The test results show varying levels of emission, with some peaks exceeding the limits. <table><tr><th></th><th>Freq. MHz</th><th>Emission level dBuV/m</th><th>Limit dBuV/m</th><th>Margin dB</th><th>SA reading dBuV</th><th>Factor dB</th><th>Remark</th><th>ANT High cm</th><th>Turn Table deg</th></tr><tr><td>1</td><td>1050.00</td><td>36.15</td><td>54.00</td><td>-17.85</td><td>45.36</td><td>-9.21</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>2</td><td>1050.00</td><td>47.37</td><td>74.00</td><td>-26.63</td><td>56.58</td><td>-9.21</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>3</td><td>5460.00</td><td>44.75</td><td>54.00</td><td>-9.25</td><td>39.57</td><td>5.18</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>4</td><td>5460.00</td><td>60.53</td><td>74.00</td><td>-13.47</td><td>55.35</td><td>5.18</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>5</td><td>5470.00</td><td>51.29</td><td>54.00</td><td>-2.71</td><td>46.10</td><td>5.19</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>6</td><td>5470.00</td><td>67.74</td><td>74.00</td><td>-6.26</td><td>62.55</td><td>5.19</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>7</td><td>11000.00</td><td>49.09</td><td>54.00</td><td>-4.91</td><td>33.81</td><td>15.28</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>8</td><td>11000.00</td><td>61.85</td><td>74.00</td><td>-12.15</td><td>46.57</td><td>15.28</td><td>Peak</td><td>---</td><td>---</td></tr></table>											Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg	1	1050.00	36.15	54.00	-17.85	45.36	-9.21	Average	---	---	2	1050.00	47.37	74.00	-26.63	56.58	-9.21	Peak	---	---	3	5460.00	44.75	54.00	-9.25	39.57	5.18	Average	---	---	4	5460.00	60.53	74.00	-13.47	55.35	5.18	Peak	---	---	5	5470.00	51.29	54.00	-2.71	46.10	5.19	Average	---	---	6	5470.00	67.74	74.00	-6.26	62.55	5.19	Peak	---	---	7	11000.00	49.09	54.00	-4.91	33.81	15.28	Average	---	---	8	11000.00	61.85	74.00	-12.15	46.57	15.28	Peak	---	---
	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg																																																																																										
1	1050.00	36.15	54.00	-17.85	45.36	-9.21	Average	---	---																																																																																										
2	1050.00	47.37	74.00	-26.63	56.58	-9.21	Peak	---	---																																																																																										
3	5460.00	44.75	54.00	-9.25	39.57	5.18	Average	---	---																																																																																										
4	5460.00	60.53	74.00	-13.47	55.35	5.18	Peak	---	---																																																																																										
5	5470.00	51.29	54.00	-2.71	46.10	5.19	Average	---	---																																																																																										
6	5470.00	67.74	74.00	-6.26	62.55	5.19	Peak	---	---																																																																																										
7	11000.00	49.09	54.00	-4.91	33.81	15.28	Average	---	---																																																																																										
8	11000.00	61.85	74.00	-12.15	46.57	15.28	Peak	---	---																																																																																										
Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit. Note 2: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.																																																																																																			



International Certification Corp.

No. 3-1, Lane 6, Wen San 3rd St., Kwei Shan Hsiang, Tao Yuan Hsien 333, Taiwan, R.O.C.

Tel: 886-3-271-8666

Fax: 886-3-318-0155

Polarization	Vertical	Test Freq. (MHz)	5500																																																																																										
Test Configuration	3																																																																																												
The graph displays the emission level in dBuV/m on the y-axis (0 to 117) against frequency in MHz on the x-axis (1000 to 40000). A red stepped line represents the FCC Part 15E (74) limit, and a lower red line represents the FCC Part 15E (AVG) limit. Blue vertical lines with markers indicate specific test points. The data table below provides the numerical values for these points. <table><tr><th></th><th>Freq. MHz</th><th>Emission level dBuV/m</th><th>Limit dBuV/m</th><th>Margin dB</th><th>SA reading dBuV</th><th>Factor dB</th><th>Remark</th><th>ANT High cm</th><th>Turn Table deg</th></tr><tr><td>1</td><td>1050.00</td><td>35.41</td><td>54.00</td><td>-18.59</td><td>44.62</td><td>-9.21</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>2</td><td>1050.00</td><td>46.58</td><td>74.00</td><td>-27.42</td><td>55.79</td><td>-9.21</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>3</td><td>5460.00</td><td>43.77</td><td>54.00</td><td>-10.23</td><td>38.59</td><td>5.18</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>4</td><td>5460.00</td><td>58.01</td><td>74.00</td><td>-15.99</td><td>52.83</td><td>5.18</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>5</td><td>5470.00</td><td>49.56</td><td>54.00</td><td>-4.44</td><td>44.37</td><td>5.19</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>6</td><td>5470.00</td><td>65.43</td><td>74.00</td><td>-8.57</td><td>60.24</td><td>5.19</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>7</td><td>11000.00</td><td>51.30</td><td>54.00</td><td>-2.70</td><td>36.02</td><td>15.28</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>8</td><td>11000.00</td><td>65.71</td><td>74.00</td><td>-8.29</td><td>50.43</td><td>15.28</td><td>Peak</td><td>---</td><td>---</td></tr></table>					Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg	1	1050.00	35.41	54.00	-18.59	44.62	-9.21	Average	---	---	2	1050.00	46.58	74.00	-27.42	55.79	-9.21	Peak	---	---	3	5460.00	43.77	54.00	-10.23	38.59	5.18	Average	---	---	4	5460.00	58.01	74.00	-15.99	52.83	5.18	Peak	---	---	5	5470.00	49.56	54.00	-4.44	44.37	5.19	Average	---	---	6	5470.00	65.43	74.00	-8.57	60.24	5.19	Peak	---	---	7	11000.00	51.30	54.00	-2.70	36.02	15.28	Average	---	---	8	11000.00	65.71	74.00	-8.29	50.43	15.28	Peak	---	---
	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg																																																																																				
1	1050.00	35.41	54.00	-18.59	44.62	-9.21	Average	---	---																																																																																				
2	1050.00	46.58	74.00	-27.42	55.79	-9.21	Peak	---	---																																																																																				
3	5460.00	43.77	54.00	-10.23	38.59	5.18	Average	---	---																																																																																				
4	5460.00	58.01	74.00	-15.99	52.83	5.18	Peak	---	---																																																																																				
5	5470.00	49.56	54.00	-4.44	44.37	5.19	Average	---	---																																																																																				
6	5470.00	65.43	74.00	-8.57	60.24	5.19	Peak	---	---																																																																																				
7	11000.00	51.30	54.00	-2.70	36.02	15.28	Average	---	---																																																																																				
8	11000.00	65.71	74.00	-8.29	50.43	15.28	Peak	---	---																																																																																				
Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit. Note 2: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.																																																																																													



International Certification Corp.

No. 3-1, Lane 6, Wen San 3rd St., Kwei Shan Hsiang, Tao Yuan Hsien 333, Taiwan, R.O.C.
Tel: 886-3-271-8666 Fax: 886-3-318-0155

Polarization	Horizontal	Test Freq. (MHz)	5580
Test Configuration	3		

The graph plots Level (dBuV/m) on the y-axis (0 to 117) against Frequency (MHz) on the x-axis (1000 to 40000). A red line represents the FCC PART15E limit, which is 74 dBuV/m. A blue line represents the emission level, which is generally below the limit. The emission level is 60.09 dBuV/m at 11160 MHz. The graph also shows a red line for the FCC PART15E (AVG) limit, which is 54 dBuV/m. The emission level is 45.75 dBuV/m at 11160 MHz.

	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	1050.00	35.37	54.00	-18.63	44.58	-9.21	Average	---	---
2	1050.00	46.66	74.00	-27.34	55.87	-9.21	Peak	---	---
3	5418.50	38.18	54.00	-15.82	33.06	5.12	Average	---	---
4	5418.50	51.61	74.00	-22.39	46.49	5.12	Peak	---	---
5	11160.00	45.75	54.00	-8.25	30.57	15.18	Average	---	---
6	11160.00	60.09	74.00	-13.91	44.91	15.18	Peak	---	---

Note 1: “>20dB” means spurious emission levels that exceed the level of 20 dB below the applicable limit.

Note 2: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.



International Certification Corp.

No. 3-1, Lane 6, Wen San 3rd St., Kwei Shan Hsiang, Tao Yuan Hsien 333, Taiwan, R.O.C.
Tel: 886-3-271-8666 Fax: 886-3-318-0155

Polarization	Vertical	Test Freq. (MHz)	5580																																																																						
Test Configuration	3																																																																								
Level (dBuV/m) 117 110 90 70 50 30 10 0 1000 6000 10000 14000 18000 22000 26000 30000 34000 40000 Frequency (MHz) FCC PART15E FCC PART15E (AVG) <table><tr><th></th><th>Freq. MHz</th><th>Emission level dBuV/m</th><th>Limit dBuV/m</th><th>Margin dB</th><th>SA reading dBuV</th><th>Factor dB</th><th>Remark</th><th>ANT High cm</th><th>Turn Table deg</th></tr><tr><td>1</td><td>1050.00</td><td>35.02</td><td>54.00</td><td>-18.98</td><td>44.23</td><td>-9.21</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>2</td><td>1050.00</td><td>46.08</td><td>74.00</td><td>-27.92</td><td>55.29</td><td>-9.21</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>3</td><td>5418.50</td><td>32.23</td><td>54.00</td><td>-21.77</td><td>27.11</td><td>5.12</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>4</td><td>5418.50</td><td>47.80</td><td>74.00</td><td>-26.20</td><td>42.68</td><td>5.12</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>5</td><td>11160.00</td><td>49.07</td><td>54.00</td><td>-4.93</td><td>33.89</td><td>15.18</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>6</td><td>11160.00</td><td>63.75</td><td>74.00</td><td>-10.25</td><td>48.57</td><td>15.18</td><td>Peak</td><td>---</td><td>---</td></tr></table>					Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg	1	1050.00	35.02	54.00	-18.98	44.23	-9.21	Average	---	---	2	1050.00	46.08	74.00	-27.92	55.29	-9.21	Peak	---	---	3	5418.50	32.23	54.00	-21.77	27.11	5.12	Average	---	---	4	5418.50	47.80	74.00	-26.20	42.68	5.12	Peak	---	---	5	11160.00	49.07	54.00	-4.93	33.89	15.18	Average	---	---	6	11160.00	63.75	74.00	-10.25	48.57	15.18	Peak	---	---
	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg																																																																
1	1050.00	35.02	54.00	-18.98	44.23	-9.21	Average	---	---																																																																
2	1050.00	46.08	74.00	-27.92	55.29	-9.21	Peak	---	---																																																																
3	5418.50	32.23	54.00	-21.77	27.11	5.12	Average	---	---																																																																
4	5418.50	47.80	74.00	-26.20	42.68	5.12	Peak	---	---																																																																
5	11160.00	49.07	54.00	-4.93	33.89	15.18	Average	---	---																																																																
6	11160.00	63.75	74.00	-10.25	48.57	15.18	Peak	---	---																																																																
Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit. Note 2: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.																																																																									



3.7 Frequency Stability


3.7.1 Limit of Frequency Stability

Manufacturers of U-NII devices are responsible for ensuring frequency stability such that an emission is maintained within the band of operation under all conditions of normal operation as specified in the user's manual.

3.7.2 Test Procedures

1. The EUT is installed in an environment test chamber with external power source.
2. Set the chamber to operate at 50 centigrade and external power source to output at nominal voltage of EUT.
3. A sufficient stabilization period at each temperature is used prior to each frequency measurement.
4. When temperature is stabled, measure the frequency stability.
5. The test shall be performed under -30 to 50 centigrade and 85 to 115 percent of the nominal voltage. Change setting of chamber and external power source to complete all conditions.

3.7.3 Test Setup





3.7.4 Test Result of Frequency Stability

Frequency: 5320 MHz	Frequency Drift (ppm)			
Temperature (°C)	0 minute	2 minutes	5 minutes	10 minutes
T20°CVmax	7.00	6.87	6.75	7.46
T20°CVmin	9.16	8.68	9.13	9.14
T70°CVnom	9.29	8.55	9.09	8.97
T60°CVnom	8.86	9.40	8.67	8.87
T55°CVnom	8.23	8.20	8.04	8.25
T50°CVnom	7.46	7.50	7.73	7.86
T40°CVnom	7.17	7.04	7.21	6.71
T30°CVnom	8.80	8.56	7.54	8.04
T20°CVnom	7.29	7.60	7.71	7.70
T10°CVnom	7.33	7.22	7.13	6.95
T0°CVnom	8.35	7.81	8.37	7.83
T-10°CVnom	8.46	9.27	8.81	9.38
T-20°CVnom	7.07	7.29	7.28	8.12
T-30°CVnom	8.20	7.58	7.35	8.45
Vnom [V]: 110		Vmax [V]: 126.5		Vmin [V]: 93.5
Tnom [°C]: 20		Tmax [°C]: 70		Tmin [°C]: -30

==END==