

RF EXPOSURE MEASUREMENT AND TEST REPORT

For

JDTECK INC

215 Celebration Place, Suite 190 Kissimmee FL

FCC ID: SQX-JDCR-LCPA

Report Type: Original Report	Product Type: Wireless Cellular Repeater
Test Engineer: <u>Dean Liu</u>	<i>Dean Liu</i>
Report Number: <u>RDG151020003-00</u>	
Report Date: <u>2015-12-01</u>	
Reviewed By: <u>Sula Huang</u> RF Leader	<i>Sula Huang</i>
Test Laboratory:	Bay Area Compliance Laboratories Corp. (Dongguan) No.69 Pulongcun, Puxinhu Industrial Zone, Tangxia, Dongguan, Guangdong, China Tel: +86-769-86858888 Fax: +86-769-86858891 www.baclcorp.com.cn

Note: This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Dongguan).

FCC §1.1307(b) & §2.1091 - MAXIMUM PERMISSIBLE EXPOSURE (MPE)**Applicable Standard**

According to subpart §1.1310, systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

Limits for Maximum Permissible Exposure (MPE) (§1.1310, §2.1091)

(B) Limits for General Population/Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm²)	Averaging Time (minutes)
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f ²)	30
30–300	27.5	0.073	0.2	30
300–1500	/	/	f/1500	30
1500–100,000	/	/	1.0	30

f = frequency in MHz; * = Plane-wave equivalent power density;

According to §1.1310 and §2.1091 RF exposure is calculated.

Calculated Formulary:

Predication of MPE limit at a given distance

$S = PG/4\pi R^2$ = power density (in appropriate units, e.g. mW/cm²);

P = power input to the antenna (in appropriate units, e.g., mW);

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain;

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm);

Calculated Data:

Mode	Frequency Band	Antenna Gain		Cable Loss dB	Conducted Power		Evaluation Distance (cm)	Power Density (mW/cm ²)	MPE Limit (mW/cm ²)
		(dBi)	(numeric)		(dBm)	(mW)			
Uplink	698-716	10.00	10.00	0.70	21.00	125.89	20.00	0.21	0.47
	776-787	10.00	10.00	0.70	21.00	125.89	20.00	0.21	0.52
	824-849	10.00	10.00	0.70	21.00	125.89	20.00	0.21	0.55
	1710-1755	10.00	10.00	1.00	21.00	125.89	20.00	0.20	1.00
	1850-1910	10.00	10.00	1.00	21.00	125.89	20.00	0.20	1.00
Downlink	728-746	10.00	10.00	1.00	-5.00	0.31623	20.00	0.00050	0.49
	746-757	10.00	10.00	1.00	-5.00	0.31623	20.00	0.00050	0.50
	869-894	10.00	10.00	1.00	-5.00	0.31623	20.00	0.00050	0.58
	2110-2155	10.00	10.00	1.50	-5.00	0.31623	20.00	0.00045	1.00
	1930-1990	10.00	10.00	1.50	-5.00	0.31623	20.00	0.00045	1.00

Note: the power was used for evaluation is rated power including tolerance.

The worst antenna kitting is option 10 from outdoor antenna and option 11 for indoor antenna.
Please refer the user manual.

Result: The device meet FCC MPE at 20 cm distance.