

This is the label affixed to the top of the device on the inside of the enclosure.
 FCC ID: SRA-ATD003160
 and Canadian number
 IC: 7413A-ATD003160
 See picture below Actual size of label is first picture.

TAILBATTM RF
CONTROL UNIT
 FCC ID: SRA-ATD003160 IC: 7413A-ATD003160
TrailerTail by STEMCO Model: ATD003160

LED Color	Motion	LED Color			Fault Diagnostic
		(P10, 11)**	Light (Pin2)		
Green ☼	Stopped	Cyan ☼	Cyan ●	-	Shorted to +12 Volts
Green ●	< 35mph	Yellow ☼	Yellow ●	-	Shorted to 0 Volts
White ●	>= 35mph	Pink ☼	Pink ●	-	Current Draw Too Low
Blue ●	Reverse	White ☼	-	-	Latches Did Not Open
☼ = Blink		**AutoDeploy Mode = Latch		Red ☼	Pin 1 < 9V or >16V
● = Solid		Automatic Mode = Solenoid		Red ●	TracBat Signal Missing

This device complies with part 15 of the FCC Rules.
 Operation is subject to the following two conditions:
 (1) This device may not cause harmful interference, and
 (2) this device must accept any interference received,
 including interference that may cause undesired operation.

TAILBAT RF[™] CONTROL UNIT

FCC ID: SRA-ATD003160 IC: 7413A-ATD003160
TrailerTail by STEMCO Model: ATD003160

LED Color	Motion	LED Color (P10, 11)**	Light (Pin2)	Fault Diagnostic
Green *	Stopped	Cyan *	Cyan *	Shorted to +12 Volts
Green *	< 35mph	Yellow *	Yellow *	Shorted to 0 Volts
White *	>= 35mph	Pink *	Pink *	Current Draw Too Low
Blue *	Reverse	White *	White *	Latches Did Not Open
* - Blink		** AutoDeploy Mode - Latch	Red *	Pin 1 < 9V or > 16V
• - Solid		Automatic Mode - Solenoid	Red *	TracBat Signal Missing

This device complies with part 15 of the FCC Rules.
Operation is subject to the following two conditions:
(1) This device may not cause harmful interference, and
(2) this device must accept any interference received,
including interference that may cause undesired operation.

TAILBATTM RF CONTROL UNIT

FCC ID: SRA-ATD003160 IC: 7413A-ATD003160
TrailerTail by STEMCO Model: ATD003160

LED Color	Motion	LED Color			Fault Diagnostic
		(P10, 11)**	Light (Pin2)		
Green ☼	Stopped	Cyan ☼	Cyan ●	-	Shorted to +12 Volts
Green ●	< 35mph	Yellow ☼	Yellow ●	-	Shorted to 0 Volts
White ●	>= 35mph	Pink ☼	Pink ●	-	Current Draw Too Low
Blue ●	Reverse	White ☼	-	-	Latches Did Not Open
☼ = Blink		**AutoDeploy Mode = Latch		Red ☼	Pin 1 < 9V or >16V
● = Solid		Automatic Mode = Solenoid		Red ●	TracBat Signal Missing

This device complies with part 15 of the FCC Rules.

Operation is subject to the following two conditions:

- (1) This device may not cause harmful interference, and
- (2) this device must accept any interference received, including interference that may cause undesired operation.