Test Lab
Cert 2951.01

FCC TEST REPORT
(PART 27)

Product:	Mobile Broadband Internet Device
Model No.:	K88
FCC ID:	SRQ-K88
Applicant:	ZTE Corporation
Address:	ZTE Plaza, #55 Keji Road South, Hi-Tech, Industrial Park, Nanshan District
Manufacturer:	ZTE Corporation
Address:	ZTE Plaza, #55 Keji Road South, Hi-Tech, Industrial Park, Nanshan District
Prepared by:	Bureau Veritas Shenzhen Co., Ltd. Dongguan Branch
Lab Location:	No. 34, Chenwulu Section, Guantai Rd., Houjie Town, Dongguan City, Guangdong 523942, China
TEL:	+86 769 8593 5656
FAX:	+86 769 8593 1080
E-MAIL:	customerservice.dg@cn.bureauveritas.com
Report No.:	RF160418W001-5
Received Date:	Apr. 18, 2016
Test Date:	Apr. 19, 2016 ~ May 02, 2016
Issued Date:	May 03, 2016

This report should not be used by the client to claim product certification, approval, or endorsement by A2LA or any government agencies.

This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification

TABLE OF CONTENTS

RELEASE CONTROL RECORD 4

1 CERTIFICATION 5

2 SUMMARY OF TEST RESULTS 6

2.1 MEASUREMENT UNCERTAINTY 6
2.2 TEST SITE AND INSTRUMENTS 7

3 GENERAL INFORMATION 8

3.1 GENERAL DESCRIPTION OF EUT 8
3.2 CONFIGURATION OF SYSTEM UNDER TEST 11
3.3 DESCRIPTION OF SUPPORT UNITS 12
3.4 DESCRIPTION OF TEST MODES 12
3.5 GENERAL DESCRIPTION OF APPLIED STANDARDS 17

4 TEST TYPES AND RESULTS 18

4.1 OUTPUT POWER MEASUREMENT 18
4.1.1 LIMITS OF OUTPUT POWER MEASUREMENT 18
4.1.2 TEST PROCEDURES 18
4.1.3 TEST SETUP 19
4.1.4 TEST RESULTS 20
4.2 FREQUENCY STABILITY MEASUREMENT 36
4.2.1 LIMITS OF FREQUENCY STABILIITY MEASUREMENT 36
4.2.2 TEST PROCEDURE 36
4.2.3 TEST SETUP 36
4.2.4 TEST RESULTS 37
4.3 OCCUPIED BANDWIDTH MEASUREMENT 39
4.3.1 LIMITS OF OCCUPIED BANDWIDTH MEASUREMENT 39
4.3.2 TEST SETUP 39
4.3.3 TEST PROCEDURES 39
4.3.4 TEST RESULTS 40
4.4 PEAK TO AVERAGE RATIO 45
4.4.1 LIMITS OF PEAK TO AVERAGE RATIO MEASUREMENT 45
4.4.2 TEST SETUP 45
4.4.3 TEST PROCEDURES 45
4.4.4 TEST RESULTS 46
4.5 BAND EDGE MEASUREMENT 51
4.5.1 LIMITS OF BAND EDGE MEASUREMENT 51
4.5.2 TEST SETUP 51
4.5.3 TEST PROCEDURES 51
4.5.4 TEST RESULTS 53
4.6 CONDUCTED SPURIOUS EMISSIONS 63
4.6.1 LIMITS OF CONDUCTED SPURIOUS EMISSIONS MEASUREMENT 63
4.6.2 TEST PROCEDURE 63
4.6.3 TEST SETUP 63
4.6.4 TEST RESULTS 64
4.7 RADIATED EMISSION MEASUREMENT 67
4.7.1 LIMITS OF RADIATED EMISSION MEASUREMENT 67
4.7.2 TEST PROCEDURES 67
4.7.3 DEVIATION FROM TEST STANDARD 67
4.7.4 TEST SETUP 68

4.7.5 TEST RESULTS 69

5 INFORMATION ON THE TESTING LABORATORIES 91

6 APPENDIX A – MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB 92

RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
RF160418W001-5	Original release	May 03, 2016

1 CERTIFICATION

PRODUCT:	Mobile Broadband Internet Device
BRAND:	ZTE
MODEL NO.:	K88
APPLICANT:	ZTE Corporation
TESTED:	Apr. 19, 2016 ~ May 02, 2016
TEST SAMPLE:	Identical Prototype
TEST STANDARDS:	**FCC Part 27, Subpart C, L**
	FCC Part 2
	ANSI/TIE/EIA-603-D

The above equipment has been tested by **Bureau Veritas Shenzhen Co., Ltd. Dongguan Branch,** and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

TESTED BY : _____ **, DATE :** May 03, 2016

(Amyee Qian / Engineer)

APPROVED BY : _____ **, DATE :** May 03, 2016

(William Chung / Manager)

2 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC Part 27 & Part 2			
STANDARD SECTION	**TEST TYPE AND LIMIT**	**RESULT**	**REMARK**
2.1046 27.50(d)(4)	Maximum Peak Output Power	PASS	Meet the requirement of limit.
2.1055 27.54	Frequency Stability	PASS	Meet the requirement of limit.
2.1049 27.53(h)	Occupied Bandwidth	PASS	Meet the requirement of limit.
27.50(d)(5)	Peak to average ratio	PASS	Meet the requirement of limit.
27.53(h)	Band Edge Measurements	PASS	Meet the requirement of limit.
2.1051 27.53(h)	Conducted Spurious Emissions	PASS	Meet the requirement of limit.
2.1053 27.53(h)	Radiated Spurious Emissions	PASS	Meet the requirement of limit. Minimum passing margin is -11.56dB at 3470.00MHz.

2.1 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

MEASUREMENT	FREQUENCY	UNCERTAINTY
Conducted emissions	9kHz~30MHz	2.66dB
Radiated emissions	9KHz ~ 30MHz	2.74dB
	30MHz ~ 1GMHz	3.55dB
	1GHz ~ 18GHz	4.84dB
	18GHz ~ 40GHz	1.94dB

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

2.2 TEST SITE AND INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
EMI Test Receiver	Rohde&Schwarz	ESR7	101494	Apr. 05,16	Apr. 04,17
Signal and Spectrum Analyzer	Rohde&Schwarz	FSV40	101094	Apr. 05,16	Apr. 04,17
Bilog Antenna 1	Teseq	CBL 6111D	30643	Jun. 25,15	Jun. 24,16
Bilog Antenna 2	Teseq	CBL 6111D	27089	Jun. 25,15	Jun. 24,16
Horn Antenna	ETS-Lindgren	3117	00062558	May 30,14	May 09,17
Horn Antenna (15GHz-40GHz)	SCHWARZBECK	BBHA 9170	BBHA9170147	Jan. 21,14	Jan. 20,17
Amplifier	Burgeon	BPA-530	100220	Apr. 05,16	Apr. 04,17
Pre-Amplifier	HP	8449B	3008A00409	Apr. 25,15	Apr. 22,17
Pre-Amplifier (18GHz-40GHz)	EMCI	EMC 184045	980102	Nov. 11,15	Nov. 10,16
GPS Generator+ Antenna	TOJOIN	GNSS-5000A	E1-010119	Aug. 08, 14	Aug. 07, 16
3m Semi-anechoic Chamber	ETS-LINDGREN	9m*6m*6m	NSEMC003	Mar. 12,16	Mar. 11,18
Test Software	ADT	ADT_Radiated _V7.6.15.9.2	N/A	N/A	N/A
Power Meter	Anritsu	ML2495A	1139001	Feb.19,16	Feb. 18,17
Power Sensor	Anritsu	MA2411B	1126068	Feb.19,16	Feb. 18,17
Power Sensor	Keysight	U2021XA	MY55060016	May 27,15	May 27,17
Power Sensor	Keysight	U2021XA	MY55060018	May 27,15	May 25,17
Digital Multimeter	FLUKE	15B	A1220010DG	Oct. 12, 15	Oct.11, 16
Humid & Temp Programmable Tester	Haida	HD-2257	110807201	Sep.07,15	Sep. 06,16
Oscilloscope	Agilent	DSO9254A	MY51260160	Nov. 09,15	Nov. 08,16
Signal Analyzer	Rohde & Schwarz	FSV7	102331	Nov. 09,15	Nov. 08,16
Signal Generator	Agilent	N5183A	MY50140980	Apr. 22, 15	Apr. 19, 17
ESG Vector Signal Generator	Agilent	E4438C	MY49072505	Sep. 01,15	Aug. 31,16
BLUETOOTH TESTER	Rohde&Schwarz	CBT32	100811	Oct. 12, 15	Oct.11, 16

NOTE: 1. The calibration interval of the above test instruments is 12 months or 24 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.

2. The test was performed in Dongguan 966 Chamber.

3. The horn antenna are used only for the measurement of emission frequency above 1GHz if tested.

4. The FCC Site Registration No. is 502831.

3 GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

PRODUCT	Mobile Broadband Internet Device	
MODEL NO.	K88	
POWER SUPPLY	5.0Vdc (adapter or host equipment) 3.8Vdc (battery)	
MODULATION TECHNOLOGY	**LTE Band 4**	QPSK, 16QAM
	LTE Band 12	QPSK, 16QAM
FREQUENCY RANGE	**LTE Band 4 Channel Bandwidth: 1.4MHz**	1710.7MHz ~ 1754.3MHz
	LTE Band 4 Channel Bandwidth: 3MHz	1711.5MHz ~ 1753.5MHz
	LTE Band 4 Channel Bandwidth: 5MHz	1712.5MHz ~ 1752.5MHz
	LTE Band 4 Channel Bandwidth: 10MHz	1715.0MHz ~ 1750.0MHz
	LTE Band 4 Channel Bandwidth: 15MHz	1717.5MHz ~ 1747.5MHz
	LTE Band 4 Channel Bandwidth: 20MHz	1720.0MHz ~ 1745.0MHz
	LTE Band 12 Channel Bandwidth: 1.4MHz	699.7MHz ~ 715.3MHz
	LTE Band 12 Channel Bandwidth: 3MHz	700.5MHz ~ 714.5MHz
	LTE Band 12 Channel Bandwidth: 5MHz	701.5MHz ~ 713.5MHz
	LTE Band 12 Channel Bandwidth: 10MHz	704.0MHz ~ 711.0MHz
EMISSION DESIGNATOR	**LTE Band 4 Channel Bandwidth: 1.4MHz**	QPSK: 1M09G7D
		16QAM: 1M09W7D
	LTE Band 4 Channel Bandwidth: 3MHz	QPSK: 2M69G7D
		16QAM: 2M68W7D
	LTE Band 4 Channel Bandwidth: 5MHz	QPSK: 4M48G7D
		16QAM: 4M46W7D
	LTE Band 4 Channel Bandwidth: 10MHz	QPSK: 8M92G7D
		16QAM: 8M93W7D
	LTE Band 4 Channel Bandwidth: 15MHz	QPSK: 13M4G7D
		16QAM: 13M4W7D
	LTE Band 4 Channel Bandwidth: 20MHz	QPSK: 17M8G7D
		16QAM: 17M8W7D
	LTE Band 12 Channel Bandwidth: 1.4MHz	QPSK: 1M09G7D
		16QAM: 1M08W7D

EMISSION DESIGNATOR	**LTE Band 12 Channel Bandwidth: 3MHz**	QPSK: 2M69G7D
		16QAM: 2M68W7D
	LTE Band 12 Channel Bandwidth: 5MHz	QPSK: 4M47G7D
		16QAM: 4M47W7D
	LTE Band 12 Channel Bandwidth: 10MHz	QPSK: 8M94G7D
		16QAM: 8M94W7D
MAX. ERP/EIRP POWER	**LTE Band 4 Channel Bandwidth: 1.4MHz**	212mW
	LTE Band 4 Channel Bandwidth: 3MHz	209mW
	LTE Band 4 Channel Bandwidth: 5MHz	211mW
	LTE Band 4 Channel Bandwidth: 10MHz	214mW
	LTE Band 4 Channel Bandwidth: 15MHz	211mW
	LTE Band 4 Channel Bandwidth: 20MHz	190mW
	LTE Band 12 Channel Bandwidth: 1.4MHz	153mW
	LTE Band 12 Channel Bandwidth: 3MHz	155mW
	LTE Band 12 Channel Bandwidth: 5MHz	151mW
	LTE Band 12 Channel Bandwidth: 10MHz	137mW
ANTENNA TYPE	**LTE Band 4**	PIFA antenna with 2.1dBi gain
	LTE Band 12	PIFA antenna with -1.28dBi gain
HW VERSION	u91B	
SW VERSION	K88V1.0.0B05	
I/O PORTS	Refer to user's manual	
DATA CABLE	USB Cable: Shielded, Detachable, 1.0m	

NOTE:

1. For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.
2. The EUT was powered by the following adapter:

ADAPTER	
BRAND:	Salcomp
MODEL:	STC-A521A-Z
INPUT:	AC 100-240V, 400mA
OUTPUT:	DC 5V, 2100mA

3. The EUT matched the following USB cable:

USB CABLE	
BRAND:	ZTE
MODEL:	USB-TC20-W-100-M
SIGNAL LINE:	1.0 METER

4. For the test results, the EUT had been tested with all conditions. But only the worst case was shown in test report.

3.2 CONFIGURATION OF SYSTEM UNDER TEST

FOR RADIATION EMISSION TEST



FOR E.R.P./E.I.R.P TEST



3.3 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	DC source	LONG WEI	PS-6403D	010934269	N/A
2	PC	HP	A6608CN	3CR83825X3	N/A

NO.	SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	DC Line: Unshielded, Detachable 1.0m
2	AC Line: Unshielded, Detachable 1.5m

NOTE:

1. All power cords of the above support units are non shielded (1.8m).

3.4 DESCRIPTION OF TEST MODES

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, XYZ axis and antenna ports The worst case was found when positioned on Y-plane for ERP/EIRP and X-axis for radiated emission. Following channel(s) was (were) selected for the final test as listed below:

EUT CONFIGURE MODE	DESCRIPTION
A	**EUT + Adapter with LTE link**
B	EUT + Battery with **LTE link**

LTE BAND 4

EUT CONFIGURE MODE	TEST ITEM	AVAILABLE CHANNEL	TESTED CHANNEL	CHANNEL BANDWIDTH	MODULATION	MODE
B	EIRP	19957 to 20393	19957, 20175, 20393	1.4MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		19965 to 20385	19965, 20175, 20385	3MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		19975 to 20375	19975, 20175, 20375	5MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		20000 to 20350	20000, 20175, 20350	10MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		20025 to 20325	20025, 20175, 20325	15MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		20050 to 20300	20050, 20175, 20300	20MHz	QPSK, 16QAM	1 RB / 0 RB Offset
B	FREQUENCY STABILITY	19957 to 20393	20175	1.4MHz	QPSK	1 RB / 0 RB Offset
		19965 to 20385	20175	3MHz	QPSK	1 RB / 0 RB Offset
		19975 to 20375	20175	5MHz	QPSK	1 RB / 0 RB Offset
		20000 to 20350	20175	10MHz	QPSK	1 RB / 0 RB Offset
		20025 to 20325	20175	15MHz	QPSK	1 RB / 0 RB Offset
		20050 to 20300	20175	20MHz	QPSK	1 RB / 0 RB Offset
B	OCCUPIED BANDWIDTH	19957 to 20393	19957, 20175, 20393	1.4MHz	QPSK, 16QAM	6 RB / 0 RB Offset
		19965 to 20385	19965, 20175, 20385	3MHz	QPSK, 16QAM	15 RB / 0 RB Offset
		19975 to 20375	19975, 20175, 20375	5MHz	QPSK, 16QAM	25 RB / 0 RB Offset
		20000 to 20350	20000, 20175, 20350	10MHz	QPSK, 16QAM	50 RB / 0 RB Offset
		20025 to 20325	20025, 20175, 20325	15MHz	QPSK, 16QAM	75 RB / 0 RB Offset
		20050 to 20300	20050, 20175, 20300	20MHz	QPSK, 16QAM	100 RB / 0 RB Offset
B	PEAK TO AVERAGE RATIO	19957 to 20393	19957, 20175, 20393	1.4MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		19965 to 20385	19965, 20175, 20385	3MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		19975 to 20375	19975, 20175, 20375	5MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		20000 to 20350	20000, 20175, 20350	10MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		20025 to 20325	20025, 20175, 20325	15MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		20050 to 20300	20050, 20175, 20300	20MHz	QPSK, 16QAM	1 RB / 0 RB Offset
B	BAND EDGE	19957 to 20393	19957	1.4MHz	QPSK	1 RB / 0 RB Offset
						6 RB / 0 RB Offset
			20393	1.4MHz	QPSK	1 RB / 5 RB Offset
						6 RB / 0 RB Offset
		19965 to 20385	19965	3MHz	QPSK	1 RB / 0 RB Offset
						15 RB / 0 RB Offset
			20385	3MHz	QPSK	1 RB / 14 RB Offset
						15 RB / 0 RB Offset
		19975 to 20375	19975	5MHz	QPSK	1 RB / 0 RB Offset
						25 RB / 0 RB Offset
			20375	5MHz	QPSK	1 RB / 24 RB Offset
						25 RB / 0 RB Offset
		20000 to 20350	20000	10MHz	QPSK	1 RB / 0 RB Offset
						50 RB / 0 RB Offset
			20350	10MHz	QPSK	1 RB / 49 RB Offset
						50 RB / 0 RB Offset

B	BAND EDGE	20025 to 20325	20025	15MHz	QPSK	1 RB / 0 RB Offset
						75 RB / 0 RB Offset
			20325	15MHz	QPSK	1 RB / 74 RB Offset
						75 RB / 0 RB Offset
		20050 to 20300	20050	20MHz	QPSK	1 RB / 0 RB Offset
						100 RB / 0 RB Offset
			20300	20MHz	QPSK	1 RB / 99 RB Offset
						100 RB / 0 RB Offset
B	CONDCUDETED EMISSION	19957 to 20393	20175	1.4MHz	QPSK	1 RB / 0 RB Offset
		19965 to 20385	20175	3MHz	QPSK	1 RB / 0 RB Offset
		19975 to 20375	20175	5MHz	QPSK	1 RB / 0 RB Offset
		20000 to 20350	20175	10MHz	QPSK	1 RB / 0 RB Offset
		20025 to 20325	20175	15MHz	QPSK	1 RB / 0 RB Offset
		20050 to 20300	20175	20MHz	QPSK	1 RB / 0 RB Offset
A	RADIATED EMISSION	19957 to 20393	20175	1.4MHz	QPSK	1 RB / 0 RB Offset
		19965 to 20385	20175	3MHz	QPSK	1 RB / 0 RB Offset
		19975 to 20375	20175	5MHz	QPSK	1 RB / 0 RB Offset
		20000 to 20350	20175	10MHz	QPSK	1 RB / 0 RB Offset
		20025 to 20325	20175	15MHz	QPSK	1 RB / 0 RB Offset
		20050 to 20300	20175	20MHz	QPSK	1 RB / 0 RB Offset

Note: This device was tested under all bandwidths, RB configurations and modulations. The worst case was found in QPSK modulation.

LTE BAND 12

EUT CONFIGURE MODE	TEST ITEM	AVAILABLE CHANNEL	TESTED CHANNEL	CHANNEL BANDWIDTH	MODULATION	MODE
B	ERP	23017 to 23173	23017, 23095 , 23173	1.4MHz	QPSK,16QAM	1 RB / 0 RB Offset
		23025 to 23165	23025, 23095 ,23165	3MHz	QPSK,16QAM	1 RB / 0 RB Offset
		23035 to 23155	23035, 23095 ,23155	5MHz	QPSK,16QAM	1 RB / 0 RB Offset
		23060 to 23130	23060, 23095 ,23130	10MHz	QPSK,16QAM	1 RB / 0 RB Offset
B	FREQUENCY STABILITY	23017 to 23173	23095	1.4MHz	QPSK	1 RB / 0 RB Offset
		23025 to 23165	23095	3MHz	QPSK	1 RB / 0 RB Offset
		23035 to 23155	23095	5MHz	QPSK	1 RB / 0 RB Offset
		23060 to 23130	23095	10MHz	QPSK	1 RB / 0 RB Offset
B	OCCUPIED BANDWIDTH	23017 to 23173	23017, 23095 , 23173	1.4MHz	QPSK,16QAM	6 RB / 0 RB Offset
		23025 to 23165	23025, 23095 ,23165	3MHz	QPSK,16QAM	15 RB / 0 RB Offset
		23035 to 23155	23035, 23095 ,23155	5MHz	QPSK,16QAM	25 RB / 0 RB Offset
		23060 to 23130	23060, 23095 ,23130	10MHz	QPSK,16QAM	50 RB / 0 RB Offset
B	PEAK TO AVERAGE RATIO	23017 to 23173	23017, 23095 , 23173	1.4MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		23025 to 23165	23025, 23095 ,23165	3MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		23035 to 23155	23035, 23095 ,23155	5MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		23060 to 23130	23060, 23095 ,23130	10MHz	QPSK, 16QAM	1 RB / 0 RB Offset
B	BAND EDGE	23017 to 23173	23017	1.4MHz	QPSK	1 RB / 0 RB Offset
						6 RB / 0 RB Offset
			23173	1.4MHz	QPSK	1 RB / 5 RB Offset
						6 RB / 0 RB Offset
		23025 to 23165	23025	3MHz	QPSK	1 RB / 0 RB Offset
						15 RB / 0 RB Offset
			23165	3MHz	QPSK	1 RB / 14 RB Offset
						15 RB / 0 RB Offset
		23035 to 23155	23035	5MHz	QPSK	1 RB / 0 RB Offset
						25 RB / 0 RB Offset
			23155	5MHz	QPSK	1 RB / 24 RB Offset
						25 RB / 0 RB Offset
		23060 to 23130	23060	10MHz	QPSK	1 RB / 0 RB Offset
						50 RB / 0 RB Offset
			23130	10MHz	QPSK	1 RB / 49 RB Offset
						50 RB / 0 RB Offset
B	CONDCUDETED EMISSION	23017 to 23173	23095	1.4MHz	QPSK	1 RB / 0 RB Offset
		23025 to 23165	23095	3MHz	QPSK	1 RB / 0 RB Offset
		23035 to 23155	23095	5MHz	QPSK	1 RB / 0 RB Offset
		23060 to 23130	23095	10MHz	QPSK	1 RB / 0 RB Offset
A	RADIATED EMISSION	23017 to 23173	23095	1.4MHz	QPSK	1 RB / 0 RB Offset
		23025 to 23165	23095	3MHz	QPSK	1 RB / 0 RB Offset
		23035 to 23155	23095	5MHz	QPSK	1 RB / 0 RB Offset
		23060 to 23130	23095	10MHz	QPSK	1 RB / 0 RB Offset

Note: This device was tested under all bandwidths, RB configurations and modulations. The worst case was found in QPSK modulation.

TEST CONDITION:

TEST ITEM	ENVIRONMENTAL CONDITIONS	INPUT POWER	TESTED BY
EIRP(ERP)	24deg. C, 60%RH	3.8Vdc from Battery	Alex Chen
FREQUENCY STABILITY	24deg. C, 61%RH	3.8Vdc from Battery	Yuqiang Yin
OCCUPIED BANDWIDTH	24deg. C, 61%RH	3.8Vdc from Battery	Yuqiang Yin
PEAK TO AVERAGE RATIO	24deg. C, 61%RH	3.8Vdc from Battery	Yuqiang Yin
BAND EDGE	24deg. C, 61%RH	3.8Vdc from Battery	Yuqiang Yin
CONDCUDETED EMISSION	24deg. C, 61%RH	3.8Vdc from Battery	Yuqiang Yin
RADIATED EMISSION	24deg. C, 60%RH	5Vdc from adapter	Alex Chen

3.5 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC 47 CFR Part 2

FCC 47 CFR Part 27

KDB Publication 971168 D02

ANSI/TIA/EIA-603-D

NOTE: All test items have been performed and recorded as per the above standards.

4 TEST TYPES AND RESULTS

4.1 OUTPUT POWER MEASUREMENT

4.1.1 LIMITS OF OUTPUT POWER MEASUREMENT

Fixed, mobile, and portable (hand-held) stat ions operating in the 1710–1755 MHz band are limited to 1 watt EIRP.

Portable stations (hand-held devices) operating in the 699-716 MHz band are limited to 3 watts ERP.

4.1.2 TEST PROCEDURES

EIRP / ERP MEASUREMENT:

a. The EUT was set up for the maximum power with LTE link data modulation. The power was measured with R&S Spectrum Analyzer. All measurements were done at 3 channels (low, middle and high operational frequency range). RBW and VBW is 10MHz for LTE.

b. E.I.R.P power measurement. In the semi-anechoic chamber, EUT placed on the 0.8m height of Turn Table, rotated the table around 360 degrees to search the maximum radiation power and receiver antenna shall be rotated vertical and horizontal polarization and moved height from 1m to 4m to find the maximum polar radiated power. The “Read Value” is the spectrum reading the maximum power value.

c. The substitution horn antenna is substituted for EUT at the same position and signals generator export the CW signal to the substitution antenna via a TX cable. Rotated the Turn Table and moved receiving antenna to find the maximum radiation power. Adjust output power level of S.G to get a Value of spectrum reading equal to “Read Value” of step a. Record the power level of S.G

d. EIRP = Output power level of S.G – TX cable loss + Antenna gain of substitution horn

e. E.R.P = E.I.R.P- 2.15 dB

CONDUCTED POWER MEASUREMENT:

a. The EUT was set up for the maximum power with LTE link data modulation and link up with simulator.

b. Set the EUT to transmit under low, middle and high channel and record the power level shown on simulator.

4.1.3 TEST SETUP

EIRP / ERP MEASUREMENT:



For the actual test configuration, please refer to the attached file (Test Setup Photo).

CONDUCTED POWER MEASUREMENT:



For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.1.4 TEST RESULTS

AVERAGE CONDUCTED OUTPUT POWER (dBm)

LTE Band 4							
BW	Modulation	RB Size	RB Offset	Low CH 19957	Mid CH 20175	High CH 20393	MPR
				Frequency 1710.7 MHz	Frequency 1732.5 MHz	Frequency 1754.3 MHz	
1.4MHz	QPSK	1	0	23.36	23.22	23.37	0
		1	2	23.35	23.17	23.26	0
		1	5	23.34	23.14	23.15	0
		3	0	23.34	23.20	23.35	0
		3	1	23.33	23.15	23.24	0
		3	3	23.32	23.12	23.13	0
		6	0	22.26	22.25	22.27	1
	16QAM	1	0	22.35	22.05	22.21	1
		1	2	22.21	22.15	22.06	1
		1	5	21.99	22.16	22.07	1
		3	0	22.34	22.04	22.20	1
		3	1	22.20	22.14	22.05	1
		3	3	21.98	22.15	22.06	1
		6	0	21.20	21.29	21.14	2

LTE Band 4							
BW	Modulation	RB Size	RB Offset	Low CH 19965	Mid CH 20175	High CH 20385	MPR
				Frequency 1711.5 MHz	Frequency 1732.5 MHz	Frequency 1753.5 MHz	
3 MHz	QPSK	1	0	23.37	23.23	23.38	0
		1	7	23.36	23.18	23.27	0
		1	14	23.35	23.15	23.16	0
		8	0	22.42	22.41	22.52	1
		8	3	22.27	22.25	22.18	1
		8	7	22.27	22.37	22.36	1
		15	0	22.27	22.26	22.28	1
	16QAM	1	0	22.36	22.06	22.22	1
		1	7	22.22	22.16	22.07	1
		1	14	22.00	22.17	22.08	1
		8	0	21.18	21.38	21.16	2
		8	3	21.30	21.23	21.24	2
		8	7	21.29	21.39	21.41	2
		15	0	21.21	21.30	21.15	2
BW	Modulation	RB Size	RB Offset	Low CH 19975	Mid CH 20175	High CH 20375	MPR
				Frequency 1712.5 MHz	Frequency 1732.5 MHz	Frequency 1752.5 MHz	
5 MHz	QPSK	1	0	23.40	23.26	23.41	0
		1	12	23.39	23.21	23.30	0
		1	24	23.38	23.18	23.19	0
		12	0	22.45	22.44	22.55	1
		12	6	22.30	22.28	22.21	1
		12	13	22.30	22.40	22.39	1
		25	0	22.30	22.29	22.31	1
	16QAM	1	0	22.39	22.09	22.25	1
		1	12	22.25	22.19	22.10	1
		1	24	22.03	22.20	22.11	1
		12	0	21.21	21.41	21.19	2
		12	6	21.33	21.26	21.27	2
		12	13	21.32	21.42	21.44	2
		25	0	21.24	21.33	21.18	2

LTE Band 4							
BW	Modulation	RB Size	RB Offset	Low CH 20000	Mid CH 20175	High CH 20350	MPR
				Frequency 1715 MHz	Frequency 1732.5 MHz	Frequency 1750 MHz	
10 MHz	QPSK	1	0	23.44	23.30	23.45	0
		1	24	23.43	23.25	23.34	0
		1	49	23.42	23.22	23.23	0
		25	0	22.49	22.48	22.59	1
		25	12	22.34	22.32	22.25	1
		25	25	22.34	22.44	22.43	1
		50	0	22.34	22.33	22.35	1
	16QAM	1	0	22.43	22.13	22.29	1
		1	24	22.29	22.23	22.14	1
		1	49	22.07	22.24	22.15	1
		25	0	21.25	21.45	21.23	2
		25	12	21.37	21.30	21.31	2
		25	25	21.36	21.46	21.48	2
		50	0	21.28	21.37	21.22	2
BW	Modulation	RB Size	RB Offset	Low CH 20025	Mid CH 20175	High CH 20325	MPR
				Frequency 1717.5 MHz	Frequency 1732.5 MHz	Frequency 1747.5 MHz	
15 MHz	QPSK	1	0	23.50	23.36	23.51	0
		1	37	23.49	23.31	23.40	0
		1	74	23.48	23.28	23.29	0
		36	0	22.55	22.54	22.65	1
		36	19	22.40	22.38	22.31	1
		36	39	22.40	22.50	22.49	1
		75	0	22.40	22.39	22.41	1
	16QAM	1	0	22.49	22.19	22.35	1
		1	37	22.35	22.29	22.20	1
		1	74	22.13	22.30	22.21	1
		36	0	21.31	21.51	21.29	2
		36	19	21.43	21.36	21.37	2
		36	39	21.42	21.52	21.54	2
		75	0	21.34	21.43	21.28	2

LTE Band 4							
BW	Modulation	RB Size	RB Offset	Low CH 20050	Mid CH 20175	High CH 20300	MPR
				Frequency 1720 MHz	Frequency 1732.5 MHz	Frequency 1745 MHz	
20MHz	QPSK	1	0	23.53	23.39	**23.54**	0
		1	50	23.52	23.34	23.43	0
		1	99	23.51	23.31	23.32	0
		50	0	22.58	22.57	22.68	1
		50	25	22.43	22.41	22.34	1
		50	50	22.43	22.53	22.52	1
		100	0	22.43	22.42	22.44	1
	16QAM	1	0	22.52	22.22	22.38	1
		1	50	22.38	22.32	22.23	1
		1	99	22.16	22.33	22.24	1
		50	0	21.34	21.54	21.32	2
		50	25	21.46	21.39	21.40	2
		50	50	21.45	21.55	21.57	2
		100	0	21.37	21.46	21.31	2

LTE Band 12							
BW	Modulation	RB Size	RB Offset	Low CH 23017 Frequency 699.7 MHz	Mid CH 23095 Frequency 707.5 MHz	High CH 23173 Frequency 715.3 MHz	MPR
1.4 MHz	QPSK	1	0	23.60	23.54	23.58	0
		1	2	23.55	23.49	23.24	0
		1	5	23.24	23.51	23.45	0
		3	0	23.58	23.52	23.56	0
		3	1	23.53	23.47	23.22	0
		3	3	23.22	23.49	23.43	0
		6	0	22.49	22.38	22.32	1
	16QAM	1	0	22.04	22.08	22.38	1
		1	2	22.36	22.00	22.35	1
		1	5	22.18	21.99	22.34	1
		3	0	22.03	22.07	22.37	1
		3	1	22.35	21.99	22.34	1
		3	3	22.17	21.98	22.33	1
		6	0	21.42	21.44	21.38	2
BW	Modulation	RB Size	RB Offset	Low CH 23025 Frequency 700.5 MHz	Mid CH 23095 Frequency 707.5 MHz	High CH 23165 Frequency 714.5 MHz	MPR
3 MHz	QPSK	1	0	23.64	23.58	23.62	0
		1	7	23.59	23.53	23.28	0
		1	14	23.28	23.55	23.49	0
		8	0	22.41	22.40	22.37	1
		8	3	22.40	22.39	22.35	1
		8	7	22.40	22.37	22.36	1
		15	0	22.53	22.42	22.36	1
	16QAM	1	0	22.08	22.12	22.42	1
		1	7	22.40	22.04	22.39	1
		1	14	22.22	22.03	22.38	1
		8	0	21.41	21.45	21.45	2
		8	3	21.51	21.30	21.25	2
		8	7	21.38	21.40	21.37	2
		15	0	21.46	21.48	21.42	2

LTE Band 12							
BW	Modulation	RB Size	RB Offset	Low CH 23035	Mid CH 23095	High CH 23155	MPR
				Frequency 701.5 MHz	Frequency 707.5 MHz	Frequency 713.5 MHz	
5 MHz	QPSK	1	0	23.70	23.64	23.68	0
		1	12	23.65	23.59	23.34	0
		1	24	23.34	23.61	23.55	0
		12	0	22.47	22.46	22.43	1
		12	6	22.46	22.45	22.41	1
		12	13	22.46	22.43	22.42	1
		25	0	22.59	22.48	22.42	1
	16QAM	1	0	22.14	22.18	22.48	1
		1	12	22.46	22.10	22.45	1
		1	24	22.28	22.09	22.44	1
		12	0	21.47	21.51	21.51	2
		12	6	21.57	21.36	21.31	2
		12	13	21.44	21.46	21.43	2
		25	0	21.52	21.54	21.48	2
BW	Modulation	RB Size	RB Offset	Low CH 23060	Mid CH 23095	High CH 23130	MPR
				Frequency 704 MHz	Frequency 707.5 MHz	Frequency 711 MHz	
10 MHz	QPSK	1	0	**23.73**	23.67	23.71	0
		1	24	23.68	23.62	23.37	0
		1	49	23.37	23.64	23.58	0
		25	0	22.50	22.49	22.46	1
		25	12	22.49	22.48	22.44	1
		25	25	22.49	22.46	22.45	1
		50	0	22.62	22.51	22.45	1
	16QAM	1	0	22.17	22.21	22.51	1
		1	24	22.49	22.13	22.48	1
		1	49	22.31	22.12	22.47	1
		25	0	21.50	21.54	21.54	2
		25	12	21.60	21.39	21.34	2
		25	25	21.47	21.49	21.46	2
		50	0	21.55	21.57	21.51	2

EIRP

LTE BAND 4

CHANNEL BANDWIDTH: 1.4MHz QPSK

Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)	LIMIT (W)
19957	1710.7	-23.04	41.29	18.25	66.90	H	1
20175	1732.5	-23.01	41.36	18.35	68.39	H	1
20393	1754.3	-23.30	42.74	19.44	87.86	H	1
19957	1710.7	-21.64	44.25	22.61	182.18	V	1
20175	1732.5	-20.94	44.20	23.26	**211.84**	V	1
20393	1754.3	-21.28	44.09	22.81	190.77	V	1

NOTE: EIRP (dBm) = LVL (dBm) + Correction Factor (dB)

CHANNEL BANDWIDTH: 1.4MHz 16QAM

Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)	LIMIT (W)
19957	1710.7	-23.91	41.29	17.38	54.75	H	1
20175	1732.5	-23.94	41.36	17.42	55.21	H	1
20393	1754.3	-24.26	42.74	18.48	70.44	H	1
19957	1710.7	-22.51	44.25	21.74	149.11	V	1
20175	1732.5	-21.87	44.20	22.33	171.00	V	1
20393	1754.3	-22.24	44.09	21.85	152.93	V	1

NOTE: EIRP (dBm) = LVL (dBm) + Correction Factor (dB)

LTE BAND 4

CHANNEL BANDWIDTH: 3MHz QPSK

Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)	LIMIT (W)
19965	1711.5	-23.02	41.27	18.25	66.79	H	1
20175	1732.5	-23.07	41.36	18.29	67.45	H	1
20385	1753.5	-23.25	42.76	19.51	89.27	H	1
19965	1711.5	-21.62	44.26	22.64	183.74	V	1
20175	1732.5	-21.00	44.20	23.20	**208.93**	V	1
20385	1753.5	-21.23	44.23	23.00	199.62	V	1

NOTE: EIRP (dBm) = LVL (dBm) + Correction Factor (dB)

CHANNEL BANDWIDTH: 3MHz 16QAM

Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)	LIMIT (W)
19965	1711.5	-24.09	41.27	17.18	52.20	H	1
20175	1732.5	-23.96	41.36	17.40	54.95	H	1
20385	1753.5	-24.24	42.76	18.52	71.07	H	1
19965	1711.5	-22.69	44.26	21.57	143.62	V	1
20175	1732.5	-21.89	44.20	22.31	170.22	V	1
20385	1753.5	-22.22	44.23	22.01	158.93	V	1

NOTE: EIRP (dBm) = LVL (dBm) + Correction Factor (dB)

LTE BAND 4

CHANNEL BANDWIDTH: 5MHz QPSK

Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)	LIMIT (W)
19975	1712.5	-23.08	41.39	18.31	67.75	H	1
20175	1732.5	-23.02	41.36	18.34	68.23	H	1
20375	1752.5	-23.20	42.63	19.43	87.68	H	1
19975	1712.5	-21.68	44.17	22.49	177.26	V	1
20175	1732.5	-20.95	44.20	23.25	**211.35**	V	1
20375	1752.5	-21.18	44.35	23.17	207.25	V	1

NOTE: EIRP (dBm) = LVL (dBm) + Correction Factor (dB)

CHANNEL BANDWIDTH: 5MHz 16QAM

Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)	LIMIT (W)
19975	1712.5	-23.91	41.39	17.48	55.96	H	1
20175	1732.5	-24.04	41.36	17.32	53.95	H	1
20375	1752.5	-24.30	42.63	18.33	68.06	H	1
19975	1712.5	-22.51	44.17	21.66	146.42	V	1
20175	1732.5	-21.97	44.20	22.23	167.11	V	1
20375	1752.5	-22.28	44.35	22.07	160.88	V	1

NOTE: EIRP (dBm) = LVL (dBm) + Correction Factor (dB)

LTE BAND 4

CHANNEL BANDWIDTH: 10MHz QPSK

Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)	LIMIT (W)
20000	1715.0	-22.89	41.49	18.60	72.38	H	1
20175	1732.5	-22.96	41.36	18.40	69.18	H	1
20350	1750.0	-23.07	42.28	19.21	83.43	H	1
20000	1715.0	-21.49	44.06	22.57	180.84	V	1
20175	1732.5	-20.89	44.20	23.31	**214.29**	V	1
20350	1750.0	-21.05	44.43	23.38	217.77	V	1

NOTE: EIRP (dBm) = LVL (dBm) + Correction Factor (dB)

CHANNEL BANDWIDTH: 10MHz 16QAM

Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)	LIMIT (W)
20000	1715.0	-24.04	41.49	17.45	55.54	H	1
20175	1732.5	-24.06	41.36	17.30	53.70	H	1
20350	1750.0	-24.23	42.28	18.05	63.87	H	1
20000	1715.0	-22.64	44.06	21.42	138.77	V	1
20175	1732.5	-21.99	44.20	22.21	166.34	V	1
20350	1750.0	-22.21	44.43	22.22	166.72	V	1

NOTE: EIRP (dBm) = LVL (dBm) + Correction Factor (dB)

LTE BAND 4

CHANNEL BANDWIDTH: 15MHz QPSK

Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)	LIMIT (W)
20025	1717.5	-22.90	41.34	18.44	69.79	H	1
20175	1732.5	-23.03	41.36	18.33	68.08	H	1
20325	1747.5	-23.14	42.09	18.95	78.45	H	1
20025	1717.5	-21.50	44.04	22.54	179.64	V	1
20175	1732.5	-20.96	44.20	23.24	**210.86**	V	1
20325	1747.5	-21.12	44.22	23.10	203.94	V	1

NOTE: EIRP (dBm) = LVL (dBm) + Correction Factor (dB)

CHANNEL BANDWIDTH: 15MHz 16QAM

Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)	LIMIT (W)
20025	1717.5	-23.76	41.34	17.58	57.25	H	1
20175	1732.5	-23.90	41.36	17.46	55.72	H	1
20325	1747.5	-23.99	42.09	18.10	64.51	H	1
20025	1717.5	-22.36	44.04	21.68	147.37	V	1
20175	1732.5	-21.83	44.20	22.37	172.58	V	1
20325	1747.5	-21.97	44.22	22.25	167.69	V	1

NOTE: EIRP (dBm) = LVL (dBm) + Correction Factor (dB)

LTE BAND 4

CHANNEL BANDWIDTH: 20MHz QPSK

Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)	LIMIT (W)
20050	1720.0	-23.48	41.28	17.80	60.27	H	1
20175	1732.5	-23.48	41.36	17.88	61.39	H	1
20300	1745.0	-23.72	41.96	18.24	66.63	H	1
20050	1720.0	-22.08	44.14	22.06	160.51	V	1
20175	1732.5	-21.41	44.20	22.79	**189.93**	V	1
20300	1745.0	-21.70	43.88	22.18	165.27	V	1

NOTE: EIRP (dBm) = LVL (dBm) + Correction Factor (dB)

CHANNEL BANDWIDTH: 20MHz 16QAM

Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)	LIMIT (W)
20050	1720.0	-24.41	41.28	16.87	48.65	H	1
20175	1732.5	-24.55	41.36	16.81	47.98	H	1
20300	1745.0	-24.55	41.96	17.41	55.04	H	1
20050	1720.0	-23.01	44.14	21.13	129.57	V	1
20175	1732.5	-22.48	44.20	21.72	148.46	V	1
20300	1745.0	-22.53	43.88	21.35	136.52	V	1

NOTE: EIRP (dBm) = LVL (dBm) + Correction Factor (dB)

ERP

LTE BAND 12

CHANNEL BANDWIDTH: 1.4MHz QPSK

Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	ERP(dBm)	ERP(mW)	Polarization (H/V)	LIMIT (W)
23017	699.7	-8.76	32.77	21.86	**153.46**	H	3
23095	707.5	-9.27	33.23	21.81	151.71	H	3
23173	715.3	-9.86	33.14	21.13	129.66	H	3
23017	699.7	-13.54	32.42	16.73	47.05	V	3
23095	707.5	-14.21	32.60	16.24	42.07	V	3
23173	715.3	-13.79	32.19	16.25	42.13	V	3

NOTE: ERP (dBm) = LVL (dBm) + Correction Factor (dB)-2.15dB.

CHANNEL BANDWIDTH: 1.4MHz 16QAM

Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	ERP(dBm)	ERP(mW)	Polarization (H/V)	LIMIT (W)
23017	699.7	-9.59	32.77	21.03	126.77	H	3
23095	707.5	-10.29	33.23	20.79	119.95	H	3
23173	715.3	-10.96	33.14	20.03	100.65	H	3
23017	699.7	-14.37	32.42	15.90	38.87	V	3
23095	707.5	-15.23	32.60	15.22	33.27	V	3
23173	715.3	-14.89	32.19	15.15	32.70	V	3

NOTE: ERP (dBm) = LVL (dBm) + Correction Factor (dB)-2.15dB.

LTE BAND 12

CHANNEL BANDWIDTH: 3MHz QPSK

Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	ERP(dBm)	ERP(mW)	Polarization (H/V)	LIMIT (W)
23025	700.5	-8.57	32.63	21.91	**155.27**	H	3
23095	707.5	-9.21	33.23	21.87	153.82	H	3
23165	714.5	-9.73	33.21	21.33	135.68	H	3
23025	700.5	-13.35	32.33	16.83	48.16	V	3
23095	707.5	-14.15	32.60	16.30	42.66	V	3
23165	714.5	-13.66	32.30	16.49	44.58	V	3

NOTE: ERP (dBm) = LVL (dBm) + Correction Factor (dB)-2.15dB.

CHANNEL BANDWIDTH: 3MHz 16QAM

Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	ERP(dBm)	ERP(mW)	Polarization (H/V)	LIMIT (W)
23025	700.5	-9.72	32.63	20.76	119.15	H	3
23095	707.5	-10.31	33.23	20.77	119.40	H	3
23165	714.5	-10.89	33.21	20.17	103.87	H	3
23025	700.5	-14.50	32.33	15.68	36.96	V	3
23095	707.5	-15.25	32.60	15.20	33.11	V	3
23165	714.5	-14.82	32.30	15.33	34.13	V	3

NOTE: ERP (dBm) = LVL (dBm) + Correction Factor (dB)-2.15dB.

LTE BAND 12

CHANNEL BANDWIDTH: 5MHz QPSK

Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	ERP(dBm)	ERP(mW)	Polarization (H/V)	LIMIT (W)
23035	701.5	-8.58	32.53	21.80	151.18	H	3
23095	707.5	-9.28	33.23	21.80	**151.29**	H	3
23155	713.5	-9.80	33.29	21.34	136.05	H	3
23035	701.5	-13.36	32.25	16.74	47.25	V	3
23095	707.5	-14.22	32.60	16.23	41.98	V	3
23155	713.5	-13.73	32.39	16.51	44.73	V	3

NOTE: ERP (dBm) = LVL (dBm) + Correction Factor (dB)-2.15dB.

CHANNEL BANDWIDTH: 5MHz 16QAM

Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	ERP(dBm)	ERP(mW)	Polarization (H/V)	LIMIT (W)
23035	701.5	-9.44	32.53	20.94	124.02	H	3
23095	707.5	-10.15	33.23	20.93	123.82	H	3
23155	713.5	-10.65	33.29	20.49	111.87	H	3
23035	701.5	-14.22	32.25	15.88	38.76	V	3
23095	707.5	-15.09	32.60	15.36	34.36	V	3
23155	713.5	-14.58	32.39	15.66	36.78	V	3

NOTE: ERP (dBm) = LVL (dBm) + Correction Factor (dB)-2.15dB.

LTE BAND 12

CHANNEL BANDWIDTH: 10MHz QPSK

Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	ERP(dBm)	ERP(mW)	Polarization (H/V)	LIMIT (W)
23060	704.0	-9.16	32.68	21.37	**137.18**	H	3
23095	707.5	-9.73	33.23	21.35	136.46	H	3
23130	711.0	-10.38	33.39	20.86	121.81	H	3
23060	704.0	-13.94	32.37	16.28	42.44	V	3
23095	707.5	-14.67	32.60	15.78	37.84	V	3
23130	711.0	-14.31	32.56	16.10	40.69	V	3

NOTE: ERP (dBm) = LVL (dBm) + Correction Factor (dB)-2.15dB.

CHANNEL BANDWIDTH: 10MHz 16QAM

Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	ERP(dBm)	ERP(mW)	Polarization (H/V)	LIMIT (W)
23060	704.0	-10.09	32.68	20.44	110.74	H	3
23095	707.5	-10.80	33.23	20.28	106.66	H	3
23130	711.0	-11.21	33.39	20.03	100.62	H	3
23060	704.0	-14.87	32.37	15.35	34.26	V	3
23095	707.5	-15.74	32.60	14.71	29.58	V	3
23130	711.0	-15.14	32.56	15.27	33.61	V	3

NOTE: ERP (dBm) = LVL (dBm) + Correction Factor (dB)-2.15dB.

4.2 FREQUENCY STABILITY MEASUREMENT

4.2.1 LIMITS OF FREQUENCY STABILIITY MEASUREMENT

The frequency stability shall be sufficient to ensure that the fundamental emissions stay within the authorized bands of operation.

4.2.2 TEST PROCEDURE

a. Device is placed at the oven room. The oven room could control the temperatures and humidity. Power warm up is at least 15 min and power applied should perform before recording frequency error.

b. EUT is connected the external power supply to control the DC input power. The test voltage range is from minimum to maximum working voltage. Each step shall be record the frequency error rate.

c. The temperature range step is 10 degrees in this test items. All temperature levels shall be hold the ±0.5℃ during the measurement testing. The each temperature step shall be at least 0.5 hours, consider the EUT could be test under the stability condition.

NOTE: The frequency error was recorded frequency error from the communication simulator.

4.2.3 TEST SETUP



4.2.4 TEST RESULTS

LTE BAND 4

AFC FREQUENCY ERROR vs. VOLTAGE							
VOLTAGE (Volts)	FREQUENCY ERROR (ppm)						LIMIT (ppm)
	1.4MHz	3MHz	5MHz	10MHz	15MHz	20MHz	
3.8	0.0013	0.0019	0.0008	0.0016	0.0014	0.0017	2.5
3.6	-0.0020	-0.0015	-0.0013	-0.0016	-0.0018	-0.0018	2.5
4.35	-0.0022	-0.0013	-0.0017	-0.0017	-0.0015	-0.0017	2.5

NOTE: The applicant defined the normal working voltage of the battery is from 3.6Vdc to 4.35Vdc.

AFC FREQUENCY ERROR vs. TEMPERATURE							
TEMP. (℃)	FREQUENCY ERROR (ppm)						LIMIT (ppm)
	1.4MHz	3MHz	5MHz	10MHz	15MHz	20MHz	
-30	-0.0064	-0.0057	-0.0053	-0.0062	-0.0063	-0.0056	2.5
-20	-0.0057	-0.0051	-0.0045	-0.0055	-0.0056	-0.0049	2.5
-10	-0.0051	-0.0042	-0.0037	-0.0048	-0.0048	-0.0042	2.5
0	-0.0044	-0.0036	-0.0024	-0.0040	-0.0040	-0.0034	2.5
10	-0.0038	-0.0029	-0.0018	-0.0032	-0.0033	-0.0027	2.5
20	-0.0032	-0.0022	-0.0011	-0.0023	-0.0025	-0.0021	2.5
30	-0.0025	-0.0015	-0.0004	-0.0015	-0.0017	-0.0012	2.5
40	-0.0012	-0.0007	0.0002	-0.0007	-0.0011	-0.0006	2.5
50	-0.0006	-0.0002	0.0006	-0.0001	-0.0005	-0.0001	2.5
60	0.0001	0.0003	0.0013	0.0004	0.0001	0.0003	2.5

LTE BAND 12

VOLTAGE (Volts)	FREQUENCY ERROR (ppm)				LIMIT (ppm)
	1.4MHz	3MHz	5MHz	10MHz	
3.8	0.0029	0.0029	0.0030	0.0036	2.5
3.6	-0.0030	-0.0054	-0.0044	-0.0044	2.5
4.35	-0.0043	-0.0042	-0.0038	-0.0041	2.5

NOTE: The applicant defined the normal working voltage of the battery is from 3.6Vdc to 4.35Vdc.

VOLTAGE (Volts)	FREQUENCY ERROR (ppm)				LIMIT (ppm)
	1.4MHz	3MHz	5MHz	10MHz	
-30	-0.0145	-0.0150	-0.0162	-0.0145	2.5
-20	-0.0129	-0.0132	-0.0143	-0.0129	2.5
-10	-0.0113	-0.0113	-0.0127	-0.0109	2.5
0	-0.0097	-0.0090	-0.0109	-0.0088	2.5
10	-0.0077	-0.0072	-0.0092	-0.0069	2.5
20	-0.0058	-0.0052	-0.0072	-0.0049	2.5
30	-0.0041	-0.0035	-0.0052	-0.0030	2.5
40	-0.0021	-0.0016	-0.0030	-0.0015	2.5
50	-0.0002	-0.0008	-0.0012	0.0005	2.5
60	0.0012	0.0005	0.0005	0.0017	2.5

4.3 OCCUPIED BANDWIDTH MEASUREMENT

4.3.1 LIMITS OF OCCUPIED BANDWIDTH MEASUREMENT

The width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5 %of the total mean power of a given emission.

4.3.2 TEST SETUP



4.3.3 TEST PROCEDURES

a. The conducted occupied bandwidth used the power splitter via EUT RF power connector between simulation base station and spectrum analyzer.

b. Use OBW measurement function of Spectrum analyzer to measure 99 % occupied bandwidth.

4.3.4 TEST RESULTS

LTE BAND 4

CHANNEL BANDWIDTH: 1.4MHz				CHANNEL BANDWIDTH: 3MHz			
CHANNEL	Frequency (MHz)	99% OCCUPIED Bandwidth (MHz)		CHANNEL	Frequency (MHz)	99% OCCUPIED Bandwidth (MHz)	
		QPSK	16QAM			QPSK	16QAM
19957	1710.7	1.09	1.08	19965	1711.5	2.68	2.68
20175	1732.5	1.08	1.08	20175	1732.5	2.68	2.68
20393	1754.3	1.08	1.09	20385	1753.5	2.69	2.68

SPECTRUM PLOT OF WORST VALUE

1.4MHz / QPSK



1.4MHz / 16QAM



3MHz / QPSK



3MHz / 16QAM



LTE BAND 4

CHANNEL BANDWIDTH: 5MHz				CHANNEL BANDWIDTH: 10MHz			
CHANNEL	Frequency (MHz)	99% OCCUPIED Bandwidth (MHz)		CHANNEL	Frequency (MHz)	99% OCCUPIED Bandwidth (MHz)	
		QPSK	16QAM			QPSK	16QAM
19975	1712.5	4.47	4.46	20000	1715	8.92	8.93
20175	1732.5	4.48	4.46	20175	1732.5	8.91	8.89
20375	1752.5	4.47	4.46	20350	1750	8.91	8.92

SPECTRUM PLOT OF WORST VALUE

5MHz / QPSK



5MHz / 16QAM



10MHz / QPSK



10MHz / 16QAM



LTE BAND 4

CHANNEL BANDWIDTH: 15MHz				CHANNEL BANDWIDTH: 20MHz			
CHANNEL	FREQUENCY (MHz)	99% OCCUPIED BANDWIDTH (MHz)		CHANNEL	FREQUENCY (MHz)	99% OCCUPIED BANDWIDTH (MHz)	
		QPSK	16QAM			QPSK	16QAM
20025	1717.5	13.37	13.38	20050	1720	17.84	17.81
20175	1732.5	13.39	13.36	20175	1732.5	17.84	17.82
20325	1747.5	13.35	13.36	20300	1745	17.81	17.83

SPECTRUM PLOT OF WORST VALUE

15MHz / QPSK



15MHz / 16QAM



20MHz / QPSK



20MHz / 16QAM



LTE BAND 12

CHANNEL BANDWIDTH: 1.4MHz				CHANNEL BANDWIDTH: 3MHz			
CHANNEL	FREQUENCY (MHz)	99% OCCUPIED BANDWIDTH (MHz)		CHANNEL	FREQUENCY (MHz)	99% OCCUPIED BANDWIDTH (MHz)	
		QPSK	16QAM			QPSK	16QAM
23017	699.7	1.09	1.08	23025	700.5	2.68	2.68
23095	707.5	1.09	1.08	23095	707.5	2.69	2.68
23173	715.3	1.08	1.08	23165	714.5	2.68	2.68

SPECTRUM PLOT OF WORST VALUE

1.4MHz / QPSK



1.4MHz / 16QAM



3MHz / QPSK



3MHz / 16QAM



LTE BAND 12

CHANNEL BANDWIDTH: 5MHz				CHANNEL BANDWIDTH: 10MHz			
CHANNEL	Frequency (MHz)	99% OCCUPIED Bandwidth (MHz)		CHANNEL	Frequency (MHz)	99% OCCUPIED Bandwidth (MHz)	
		QPSK	16QAM			QPSK	16QAM
23035	701.5	4.47	4.46	23060	704	8.88	8.90
23095	707.5	4.47	4.47	23095	707.5	8.93	8.93
23155	713.5	4.47	4.47	23130	711	8.94	8.94

SPECTRUM PLOT OF WORST VALUE

5MHz / QPSK



5MHz / 16QAM



10MHz / QPSK



10MHz / 16QAM



4.4 PEAK TO AVERAGE RATIO

4.4.1 LIMITS OF PEAK TO AVERAGE RATIO MEASUREMENT

In measuring transmissions in this band using an average power technique, the peak to-average ratio (PAR) of the transmission may not exceed 13 dB

4.4.2 TEST SETUP



4.4.3 TEST PROCEDURES

1. Set resolution/measurement bandwidth ≥ signal's occupied bandwidth;
2. Set the number of counts to a value that stabilizes the measured CCDF curve;
3. Record the maximum PAPR level associated with a probability of 0.1%.

4.4.4 TEST RESULTS

LTE BAND 4

CHANNEL BANDWIDTH: 1.4MHz				CHANNEL BANDWIDTH: 3MHz			
CHANNEL	FREQUENCY (MHz)	PEAK TO AVERAGE RATIO (dB)		CHANNEL	FREQUENCY (MHz)	PEAK TO AVERAGE RATIO (dB)	
		QPSK	16QAM			QPSK	16QAM
19957	1710.7	4.78	5.28	19965	1711.5	4.99	5.45
20175	1732.5	4.90	5.59	20175	1732.5	4.98	5.53
20393	1754.3	4.75	5.16	20385	1753.5	4.87	5.30

SPECTRUM PLOT OF WORST VALUE

1.4MHz / QPSK



1.4MHz / 16QAM



3MHz / QPSK



3MHz / 16QAM



CHANNEL BANDWIDTH: 5MHz				CHANNEL BANDWIDTH: 10MHz			
CHANNEL	FREQUENCY (MHz)	PEAK TO AVERAGE RATIO (dB)		CHANNEL	FREQUENCY (MHz)	PEAK TO AVERAGE RATIO (dB)	
		QPSK	16QAM			QPSK	16QAM
19975	1712.5	4.99	5.54	20000	1715	5.03	5.51
20175	1732.5	5.04	5.51	20175	1732.5	4.99	5.39
20375	1752.5	4.92	5.48	20350	1750	4.86	5.27

SPECTRUM PLOT OF WORST VALUE

5MHz / QPSK



5MHz / 16QAM



10MHz / QPSK



10MHz / 16QAM



CHANNEL BANDWIDTH: 15MHz				CHANNEL BANDWIDTH: 20MHz			
CHANNEL	FREQUENCY (MHz)	PEAK TO AVERAGE RATIO (dB)		CHANNEL	FREQUENCY (MHz)	PEAK TO AVERAGE RATIO (dB)	
		QPSK	16QAM			QPSK	16QAM
20025	1717.5	5.03	5.60	20050	1720	5.05	5.63
20175	1732.5	4.96	5.48	20175	1732.5	5.05	5.59
20325	1747.5	4.89	5.40	20300	1745	4.88	5.55

SPECTRUM PLOT OF WORST VALUE

15MHz / QPSK



15MHz / 16QAM



20MHz / QPSK



20MHz / 16QAM



LTE BAND 12

CHANNEL BANDWIDTH: 1.4MHz				CHANNEL BANDWIDTH: 3MHz			
CHANNEL	FREQUENCY (MHz)	PEAK TO AVERAGE RATIO (dB)		CHANNEL	FREQUENCY (MHz)	PEAK TO AVERAGE RATIO (dB)	
		QPSK	16QAM			QPSK	16QAM
23017	699.7	4.05	4.92	23025	700.5	4.33	5.23
23095	707.5	4.18	5.10	23095	707.5	4.28	5.27
23173	715.3	3.61	4.49	23165	714.5	3.92	4.87

SPECTRUM PLOT OF WORST VALUE

1.4MHz / QPSK



1.4MHz / 16QAM



3MHz / QPSK



3MHz / 16QAM



CHANNEL BANDWIDTH: 5MHz				CHANNEL BANDWIDTH: 10MHz			
CHANNEL	FREQUENCY (MHz)	PEAK TO AVERAGE RATIO (dB)		CHANNEL	FREQUENCY (MHz)	PEAK TO AVERAGE RATIO (dB)	
		QPSK	16QAM			QPSK	16QAM
23035	701.5	4.60	5.38	23060	704	4.26	5.16
23095	707.5	4.61	5.48	23095	707.5	4.45	5.28
23155	713.5	4.39	5.21	23130	711	4.42	5.26

SPECTRUM PLOT OF WORST VALUE

5MHz / QPSK



5MHz / 16QAM



10MHz / QPSK



10MHz / 16QAM



4.5 BAND EDGE MEASUREMENT

4.5.1 LIMITS OF BAND EDGE MEASUREMENT

The power of any emission outside a licensee's frequency band(s) of operation shall be attenuated below the transmitter power (P) within the licensed band(s) of operation, measured in watts, by at least 43 + 10 log (P) dB. Compliance with this provision is based on the use of measurement instrumentation employing a resolution bandwidth of 100 kilohertz or greater.
However, in the 100 kilohertz bands immediately outside and adjacent to a licensee's frequency block, a resolution bandwidth of at least 30 kHz may be employed.

4.5.2 TEST SETUP



4.5.3 TEST PROCEDURES

a. The EUT was set up for the maximum peak power with LTE link data modulation. The power was measured with R&S Spectrum Analyzer. All measurements were done at 2 channels (low and high operational frequency range.).

b. The band edge measurement used the power splitter via EUT RF power connector between simulation base station and spectrum analyzer.

c. The center frequency of spectrum is the band edge frequency and span is 1~5 MHz. RB of the spectrum is 20kHz and VB of the spectrum is 100 kHz. (LTE bandwidth 1.4MHz)

d. The center frequency of spectrum is the band edge frequency and span is 1~5 MHz. RB of the spectrum is 30kHz and VB of the spectrum is 100kHz. (LTE bandwidth 3MHz)

e. The center frequency of spectrum is the band edge frequency and span is 1~5 MHz. RB of the spectrum is 50kHz and VB of the spectrum is 200kHz. (LTE bandwidth 5MHz)

f. The center frequency of spectrum is the band edge frequency and span is 1~5 MHz. RB of the spectrum is 100kHz and VB of the spectrum is 300kHz. (LTE bandwidth 10MHz)

g. The center frequency of spectrum is the band edge frequency and span is 1~5 MHz. RB of the spectrum is 200kHz and VB of the spectrum is 1MHz. (LTE bandwidth 15MHz)

h. he center frequency of spectrum is the band edge frequency and span is 1~5 MHz. RB of the spectrum is 200kHz and VB of the spectrum is 1MHz. (LTE bandwidth 20MHz)

i. Record the max trace plot into the test report.

4.5.4 TEST RESULTS

LTE BAND 4

Channel Bandwidth: 1.4MHz

CHANNEL	19957	1 RB	CHANNEL	20393	1 RB

CHANNEL	19957	Full RB	CHANNEL	20393	Full RB



LTE BAND 4

Channel Bandwidth: 3MHz

CHANNEL	19965	1 RB	CHANNEL	20385	1 RB

CHANNEL	19965	Full RB	CHANNEL	20385	Full RB



LTE BAND 4

Channel Bandwidth: 5MHz

CHANNEL	19975	1 RB	CHANNEL	20375	1 RB



CHANNEL	19975	Full RB	CHANNEL	20375	Full RB



LTE BAND 4

Channel Bandwidth: 10MHz

CHANNEL	20000	1 RB	CHANNEL	20350	1 RB

CHANNEL	20000	Full RB	CHANNEL	20350	Full RB

LTE BAND 4

Channel Bandwidth: 15MHz

CHANNEL	20025	1 RB	CHANNEL	20325	1 RB

CHANNEL	20025	Full RB	CHANNEL	20325	Full RB

LTE BAND 4

Channel Bandwidth: 20MHz

CHANNEL	20050	1 RB	CHANNEL	20300	1 RB

CHANNEL	20050	Full RB	CHANNEL	20300	Full RB



LTE BAND 12

Channel Bandwidth: 1.4MHz

CHANNEL	23017	1 RB	CHANNEL	23173	1 RB



CHANNEL	23017	Full RB	CHANNEL	23173	Full RB



LTE BAND 12

Channel Bandwidth: 3MHz

CHANNEL	23025	1 RB	CHANNEL	23165	1 RB

CHANNEL	23025	Full RB	CHANNEL	23165	Full RB



LTE BAND 12

Channel Bandwidth: 5MHz

CHANNEL	23035	1 RB	CHANNEL	23155	1 RB



CHANNEL	23035	Full RB	CHANNEL	23155	Full RB



LTE BAND 12

Channel Bandwidth: 10MHz

CHANNEL	23060	1 RB	CHANNEL	23130	1 RB





CHANNEL	23060	Full RB	CHANNEL	23130	Full RB



4.6 CONDUCTED SPURIOUS EMISSIONS

4.6.1 LIMITS OF CONDUCTED SPURIOUS EMISSIONS MEASUREMENT

The power of any emission outside a licensee's frequency block shall be attenuated below the transmitter power (P) by at least 43 +10 log10(P) dB. The limit of emission equal to –13dBm

4.6.2 TEST PROCEDURE

a. The EUT makes a phone call to the communication simulator. All measurements were done at middle operational frequency range.

b. Measuring frequency range is from 30 MHz to 19.1GHz for LTE Band 4 and 30 MHz to 9GHz for LTE Band 12&17. 10dB attenuation pad is connected with spectrum. RBW=1MHz and VBW=3MHz are used for conducted emission measurement.

4.6.3 TEST SETUP



4.6.4 TEST RESULTS

LTE BAND 4

CHANNEL 20175	CHANNEL 20175
1.4MHz / QPSK	3MHz / QPSK
FREQUENCY RANGE : 30MHz~19.1GHz	FREQUENCY RANGE : 30MHz~19.1GHz
	

LTE BAND 4

CHANNEL 20175	CHANNEL 20175
5MHz / QPSK	10MHz / QPSK
FREQUENCY RANGE : 30MHz~19.1GHz	FREQUENCY RANGE : 30MHz~19.1GHz
	

LTE BAND 4

CHANNEL 20175	CHANNEL 20175
15MHz / QPSK	20MHz / QPSK
FREQUENCY RANGE : 30MHz~19.1GHz	FREQUENCY RANGE : 30MHz~19.1GHz



LTE BAND 12

CHANNEL 23095	CHANNEL 23095
1.4MHz / QPSK	3MHz / QPSK
FREQUENCY RANGE : 30MHz~19.1GHz	FREQUENCY RANGE : 30MHz~19.1GHz





LTE BAND 12

CHANNEL 23095	CHANNEL 23095
5MHz / QPSK	10MHz / QPSK
FREQUENCY RANGE : 30MHz~19.1GHz	FREQUENCY RANGE : 30MHz~19.1GHz
	

4.7 RADIATED EMISSION MEASUREMENT

4.7.1 LIMITS OF RADIATED EMISSION MEASUREMENT

The power of any emission outside a licensee's frequency block shall be attenuated below the transmitter power (P) by at least 43 +10 log10(P) dB. The limit of emission equal to –13dBm

4.7.2 TEST PROCEDURES

a. Substitution method is used for E.I.R.P measurement. In the semi-anechoic chamber, EUT placed on the 0.8m height of Turn Table, rotated the table around 360 degrees to search the maximum radiation power and receiver antenna shall be rotated vertical and horizontal polarization and moved height from 1m to 4m to find the maximum polar radiated power. The “Read Value” is the spectrum reading the maximum power value.

b. The substitution horn antenna is substituted for EUT at the same position and signals generator export the CW signal to the substitution antenna via a TX cable. Rotated the Turn Table and moved receiving antenna to find the maximum radiation power. Adjust output power level of S.G to get a Value of spectrum reading equal to “Read Value” of step a. Record the power level of S.G

c. EIRP = Output power level of S.G – TX cable loss + Antenna gain of substitution horn.

d. E.R.P power can be calculated form E.I.R.P power by subtracting the gain of dipole, E.R.P power = E.I.P.R power - 2.15dBi.

NOTE: The resolution bandwidth of spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz.

4.7.3 DEVIATION FROM TEST STANDARD

No deviation

4.7.4 TEST SETUP



For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.7.5 TEST RESULTS

BELOW 1GHz WORST-CASE DATA

LTE Band 4:

MODE	TX channel20175	FREQUENCY RANGE	Below 1000MHz
ENVIRONMENTAL CONDITIONS	26deg. C, 56%RH	INPUT POWER	DC 5V from adapter
TESTED BY	Alex Chen		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			



	No.	Frequency MHz	Factor dB	Reading dBm	Emission dBm	Limit dBm	Margin dB	Tower / Table cm	deg
*	1	47.46	5.44	-60.08	-54.64	-13.00	-41.64	--	--
	2	77.53	-8.80	-49.00	-57.80	-13.00	-44.80	--	--
	3	166.77	-18.23	-66.64	-84.87	-13.00	-71.87	--	--
	4	432.55	-10.43	-74.02	-84.45	-13.00	-71.45	--	--
	5	716.76	-5.14	-73.06	-78.20	-13.00	-65.20	--	--
	6	909.79	-3.48	-73.20	-76.68	-13.00	-63.68	--	--

MODE	TX channel20175	FREQUENCY RANGE	Below 1000MHz
ENVIRONMENTAL CONDITIONS	26deg. C, 56%RH	INPUT POWER	DC 5V from adapter
TESTED BY	Alex Chen		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			



	No.	Frequency MHz	Factor dB	Reading dBm	Emission dBm	Limit dBm	Margin dB	Tower / Table cm	deg
*	1	45.52	-3.34	-44.41	-47.75	-13.00	-34.75	--	--
	2	80.44	-10.26	-46.01	-56.27	-13.00	-43.27	--	--
	3	310.33	-11.26	-74.23	-85.49	-13.00	-72.49	--	--
	4	522.76	-7.27	-75.07	-82.34	-13.00	-69.34	--	--
	5	676.02	-6.49	-74.71	-81.20	-13.00	-68.20	--	--
	6	896.21	-2.55	-67.53	-70.08	-13.00	-57.08	--	--

ABOVE 1GHz

LTE BAND 4

CHANNEL BANDWIDTH: 1.4MHz / QPSK

MODE	TX channel 20175	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	26deg. C, 56%RH	INPUT POWER	DC 5V from adapter
TESTED BY	Alex Chen		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			



	No.	Frequency MHz	Factor dB	Reading dBm	Emission dBm	Limit dBm	Margin dB	Tower / Table cm	deg
*	1	3470.00 (PK)	2.05	-30.99	-28.94	-13.00	-15.94	100	360
	2	5186.00 (PK)	8.59	-55.61	-47.02	-13.00	-34.02	100	360

MODE	TX channel 20175	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	26deg. C, 56%RH	INPUT POWER	DC 5V from adapter
TESTED BY	Alex Chen		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			



No.		Frequency MHz	Factor dB	Reading dBm	Emission dBm	Limit dBm	Margin dB	Tower / Table cm	deg
*	1	3470.00 (PK)	2.53	-33.29	-30.76	-13.00	-17.76	200	0
	2	5186.00 (PK)	7.98	-54.03	-46.05	-13.00	-33.05	200	0

CHANNEL BANDWIDTH: 3MHz / QPSK

MODE	TX channel 20175	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	26deg. C, 56%RH	INPUT POWER	DC 5V from adapter
TESTED BY	Alex Chen		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			



No.		Frequency MHz	Factor dB	Reading dBm	Emission dBm	Limit dBm	Margin dB	Tower / Table cm	deg
*	1	3470.00 (PK)	2.05	-29.18	-27.13	-13.00	-14.13	200	0
	2	5186.00 (PK)	8.59	-55.30	-46.71	-13.00	-33.71	200	0

MODE	TX channel 20175	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	26deg. C, 56%RH	INPUT POWER	DC 5V from adapter
TESTED BY	Alex Chen		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			



No.		Frequency MHz	Factor dB	Reading dBm	Emission dBm	Limit dBm	Margin dB	Tower / Table cm	deg
*	1	3470.00 (PK)	2.53	-36.75	-34.22	-13.00	-21.22	100	360
	2	5186.00 (PK)	7.98	-54.82	-46.84	-13.00	-33.84	100	360

CHANNEL BANDWIDTH: 5MHz / QPSK

MODE	TX channel 20175	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	26deg. C, 56%RH	INPUT POWER	DC 5V from adapter
TESTED BY	Alex Chen		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			



No.		Frequency MHz	Factor dB	Reading dBm	Emission dBm	Limit dBm	Margin dB	Tower / Table cm	deg
*	1	3470.00 (PK)	2.05	-26.61	-24.56	-13.00	-11.56	100	360
	2	5186.00 (PK)	8.59	-55.02	-46.43	-13.00	-33.43	100	360

MODE	TX channel 20175	**FREQUENCY RANGE**	Above 1000MHz
ENVIRONMENTAL CONDITIONS	26deg. C, 56%RH	**INPUT POWER**	DC 5V from adapter
TESTED BY	Alex Chen		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			



No.		Frequency MHz	Factor dB	Reading dBm	Emission dBm	Limit dBm	Margin dB	Tower / Table cm	deg
*	1	3470.00 (PK)	2.53	-32.10	-29.57	-13.00	-16.57	200	0
	2	5186.00 (PK)	7.98	-54.82	-46.84	-13.00	-33.84	200	0

CHANNEL BANDWIDTH: 10MHz / QPSK

MODE	TX channel 20175	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	26deg. C, 56%RH	INPUT POWER	DC 5V from adapter
TESTED BY	Alex Chen		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			



No.		Frequency MHz	Factor dB	Reading dBm	Emission dBm	Limit dBm	Margin dB	Tower / Table cm	deg
*	1	3444.00 (PK)	1.95	-29.60	-27.65	-13.00	-14.65	200	0
	2	5198.00 (PK)	8.61	-56.27	-47.66	-13.00	-34.66	200	0

MODE	TX channel 20175	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	26deg. C, 56%RH	INPUT POWER	DC 5V from adapter
TESTED BY	Alex Chen		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			



	No.	Frequency MHz	Factor dB	Reading dBm	Emission dBm	Limit dBm	Margin dB	Tower / Table cm	deg
*	1	3444.00 (PK)	2.50	-28.82	-26.32	-13.00	-13.32	100	360
	2	5186.00 (PK)	7.98	-55.40	-47.42	-13.00	-34.42	100	360

CHANNEL BANDWIDTH: 15MHz / QPSK

MODE	TX channel 20175	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	26deg. C, 56%RH	INPUT POWER	DC 5V from adapter
TESTED BY	Alex Chen		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			



No.		Frequency MHz	Factor dB	Reading dBm	Emission dBm	Limit dBm	Margin dB	Tower / Table cm	deg
*	1	3444.00 (PK)	1.95	-27.01	-25.06	-13.00	-12.06	200	0
	2	5186.00 (PK)	8.59	-54.41	-45.82	-13.00	-32.82	200	0

MODE	TX channel 20175	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	26deg. C, 56%RH	INPUT POWER	DC 5V from adapter
TESTED BY	Alex Chen		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			



No.		Frequency MHz	Factor dB	Reading dBm	Emission dBm	Limit dBm	Margin dB	Tower / Table cm	deg
*	1	3444.00 (PK)	2.50	-37.50	-35.00	-13.00	-22.00	100	360
	2	5186.00 (PK)	7.98	-54.89	-46.91	-13.00	-33.91	100	360

CHANNEL BANDWIDTH: 20MHz / QPSK

MODE	TX channel 20175	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	26deg. C, 56%RH	INPUT POWER	DC 5V from adapter
TESTED BY	Alex Chen		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			



	No.	Frequency MHz	Factor dB	Reading dBm	Emission dBm	Limit dBm	Margin dB	Tower / Table cm	deg
*	1	3444.00 (PK)	1.95	-31.26	-29.31	-13.00	-16.31	100	360
	2	5186.00 (PK)	8.59	-55.23	-46.64	-13.00	-33.64	100	360

MODE	TX channel 20175	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	26deg. C, 56%RH	INPUT POWER	DC 5V from adapter
TESTED BY	Alex Chen		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			



	No.	Frequency MHz	Factor dB	Reading dBm	Emission dBm	Limit dBm	Margin dB	Tower / Table cm	deg
*	1	3444.00 (PK)	2.50	-37.59	-35.09	-13.00	-22.09	200	0
	2	5186.00 (PK)	7.98	-54.88	-46.90	-13.00	-33.90	200	0

LTE BAND 12

CHANNEL BANDWIDTH: 1.4MHz / QPSK

MODE	TX channel 20175	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	26deg. C, 56%RH	INPUT POWER	DC 5V from adapter
TESTED BY	Alex Chen		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			



	No.	Frequency MHz	Factor dB	Reading dBm	Emission dBm	Limit dBm	Margin dB	Tower / Table cm	deg
	1	1415.00 (PK)	-6.72	-53.91	-60.63	-13.00	-47.63	100	360
*	2	2123.00 (PK)	-1.93	-53.93	-55.86	-13.00	-42.86	100	360

MODE	TX channel 20175	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	26deg. C, 56%RH	INPUT POWER	DC 5V from adapter
TESTED BY	Alex Chen		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			



	No.	Frequency MHz	Factor dB	Reading dBm	Emission dBm	Limit dBm	Margin dB	Tower / Table cm	deg
	1	1415.00 (PK)	-5.45	-53.29	-58.74	-13.00	-45.74	100	360
*	2	2123.00 (PK)	-0.24	-53.54	-53.78	-13.00	-40.78	100	360

CHANNEL BANDWIDTH: 3MHz / QPSK

MODE	TX channel 20175	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	26deg. C, 56%RH	INPUT POWER	DC 5V from adapter
TESTED BY	Alex Chen		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			



No.		Frequency MHz	Factor dB	Reading dBm	Emission dBm	Limit dBm	Margin dB	Tower / Table cm	deg
*	1	1415.00 (PK)	-6.72	-45.58	-52.30	-13.00	-39.30	100	0
	2	2123.00 (PK)	-1.93	-51.50	-53.43	-13.00	-40.43	100	0

MODE	TX channel 20175	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	26deg. C, 56%RH	INPUT POWER	DC 5V from adapter
TESTED BY	Alex Chen		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			



	No.	Frequency MHz	Factor dB	Reading dBm	Emission dBm	Limit dBm	Margin dB	Tower / Table cm	deg
	1	1415.00 (PK)	-5.45	-52.46	-57.91	-13.00	-44.91	100	0
*	2	2123.00 (PK)	-0.24	-51.59	-51.83	-13.00	-38.83	100	0

CHANNEL BANDWIDTH: 5MHz / QPSK

MODE	TX channel 20175	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	26deg. C, 56%RH	INPUT POWER	DC 5V from adapter
TESTED BY	Alex Chen		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			



	No.	Frequency MHz	Factor dB	Reading dBm	Emission dBm	Limit dBm	Margin dB	Tower / Table cm	deg
	1	1415.00 (PK)	-6.72	-53.39	-60.11	-13.00	-47.11	100	0
*	2	2123.00 (PK)	-1.93	-47.90	-49.83	-13.00	-36.83	100	0

MODE	TX channel 20175	**FREQUENCY RANGE**	Above 1000MHz
ENVIRONMENTAL CONDITIONS	26deg. C, 56%RH	**INPUT POWER**	DC 5V from adapter
TESTED BY	Alex Chen		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			



	No.	Frequency MHz	Factor dB	Reading dBm	Emission dBm	Limit dBm	Margin dB	Tower / Table cm	deg
	1	1415.00 (PK)	-5.45	-53.15	-58.60	-13.00	-45.60	100	0
*	2	2123.00 (PK)	-0.24	-43.61	-43.85	-13.00	-30.85	100	0

CHANNEL BANDWIDTH: 10MHz / QPSK

MODE	TX channel 20175	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	26deg. C, 56%RH	INPUT POWER	DC 5V from adapter
TESTED BY	Alex Chen		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			



No.		Frequency MHz	Factor dB	Reading dBm	Emission dBm	Limit dBm	Margin dB	Tower / Table cm	deg
*	1	1415.00 (PK)	-6.72	-52.13	-58.85	-13.00	-45.85	200	0
	2	2123.00 (PK)	-1.93	-61.04	-62.97	-13.00	-49.97	200	0

MODE	TX channel 20175	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	26deg. C, 56%RH	INPUT POWER	DC 5V from adapter
TESTED BY	Alex Chen		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			



No.		Frequency MHz	Factor dB	Reading dBm	Emission dBm	Limit dBm	Margin dB	Tower / Table cm	deg
*	1	1415.00 (PK)	-5.45	-48.09	-53.54	-13.00	-40.54	100	0
	2	2123.00 (PK)	-0.24	-53.77	-54.01	-13.00	-41.01	100	0

5 INFORMATION ON THE TESTING LABORATORIES

We, Bureau Veritas Shenzhen Co., Ltd. Dongguan Branch, were founded in 2002 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Dongguan EMC/RF Lab:
Tel: +86-769-85935656
Fax: +86-769-85931080

Email: customerservice.dg@cn.bureauveritas.com
Web Site: www.adt.com.tw

The address and road map of all our labs can be found in our web site also.

6 APPENDIX A – MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB

No modifications were made to the EUT by the lab during the test.

---END---