



FCC RF Test Report

APPLICANT : ZTE CORPORATION
EQUIPMENT : WCDMA/LTE CPE
BRAND NAME : ZTE
MODEL NAME : MF288
FCC ID : SRQ-MF288
STANDARD : FCC Part 15 Subpart E §15.407
CLASSIFICATION : (NII) Unlicensed National Information Infrastructure

The product was received on Aug. 09, 2017 and testing was completed on Sep. 26, 2017. We, Sporton International (KunShan) Inc., would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International (KunShan) Inc., the test report shall not be reproduced except in full.



Approved by: James Huang / Manager

Sporton International (Kunshan) Inc.

**No.3-2 Ping-Xiang Rd, Kunshan Development Zone Kunshan City Jiangsu Province 215335
China**



TABLE OF CONTENTS

1	GENERAL DESCRIPTION	5
1.1	Applicant	5
1.2	Manufacturer	5
1.3	Product Feature of Equipment Under Test.....	5
1.4	Product Specification of Equipment Under Test.....	6
1.5	Modification of EUT	6
1.6	Testing Location	7
1.7	Applicable Standards.....	7
2	TEST CONFIGURATION OF EQUIPMENT UNDER TEST	8
2.1	Carrier Frequency and Channel	8
2.2	Test Mode	9
2.3	Connection Diagram of Test System.....	10
2.4	Support Unit used in test configuration and system	11
2.5	EUT Operation Test Setup	11
2.6	Measurement Results Explanation Example.....	12
3	TEST RESULT	13
3.1	26dB & 99% Occupied Bandwidth Measurement	13
3.2	Maximum Conducted Output Power Measurement	15
3.3	Power Spectral Density Measurement	17
3.4	Unwanted Emissions Measurement.....	20
3.5	AC Conducted Emission Measurement.....	27
3.6	Frequency Stability Measurement.....	31
3.7	Automatically Discontinue Transmission	32
3.8	Antenna Requirements	33
4	LIST OF MEASURING EQUIPMENT	35
5	UNCERTAINTY OF EVALUATION	36
APPENDIX A. CONDUCTED TEST RESULTS		
APPENDIX B. RADIATED SPURIOUS EMISSION		
APPENDIX C. DUTY CYCLE PLOTS		
APPENDIX D. SETUP PHOTOGRAPHS		



REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR780901B	Rev. 01	Initial issue of report	Sep. 30, 2017



SUMMARY OF TEST RESULT

Report Section	FCC Rule	IC Rule	Description	Limit	Result	Remark
3.1	2.1049 15.403(i)	RSS-247 Section 6	26dB & 99% Bandwidth	-	Pass	-
3.2	15.407(a)	RSS-247 Section 6	Maximum Conducted Output Power	FCC ≤ 30 dBm (depend on band)	Pass	-
3.3	15.407(a)	RSS-247 Section 6	Power Spectral Density	FCC ≤ 17 dBm (depend on band)	Pass	-
3.4	15.407(b)	RSS-247 Section 6	Unwanted Emissions	15.407(b) 15.209(a)	Pass	Under limit 3.04 dB at 37.760 MHz for Quasi-Peak
3.5	15.207	RSS-Gen 8.8	AC Conducted Emission	15.207(a)	Pass	Under limit 5.48 dB at 0.426 MHz
3.6	15.407(g)	-	Frequency Stability	Within Operation Band	Pass	-
3.7	15.407(c)	RSS-247 6.4(a)	Automatically Discontinue Transmission	Discontinue Transmission	Pass	-
3.8	15.203 & 15.407(a)	N/A	Antenna Requirement	N/A	Pass	-



1 General Description

1.1 Applicant

ZTE CORPORATION

ZTE Plaza, Keji Road South, Hi-Tech, Industrial Park, Nanshan District, Shenzhen, Guangdong, 518057, P.R.China

1.2 Manufacturer

ZTE CORPORATION

ZTE Plaza, Keji Road South, Hi-Tech, Industrial Park, Nanshan District, Shenzhen, Guangdong, 518057, P.R.China

1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	WCDMA/LTE CPE
Brand Name	ZTE
Model Name	MF288
FCC ID	SRQ-MF288
EUT supports Radios application	WCDMA/HSPA/ HSPA+ (16QAM uplink is not supported)/LTE/ WLAN 2.4GHz 802.11b/g/n HT20/HT40 WLAN 5GHz 802.11a/n HT20/HT40 WLAN 5GHz 802.11ac VHT20/VHT40/VHT80
IMEI Code	Conducted: 866339030000579 Conduction: N/A Radiation: 866339030000017
HW Version	MF288HW1.0
SW Version	MF288UIV1.0.3
EUT Stage	Identical Prototype

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

1.4 Product Specification of Equipment Under Test

Standards-related Product Specification				
Tx/Rx Frequency Range	5180 MHz ~ 5240 MHz			
Maximum Output Power to Antenna	<5180 MHz ~ 5240 MHz> <Ant. 1> 802.11a : 14.90 dBm / 0.0309 W <Ant. 2> 802.11a : 14.81 dBm / 0.0303 W <Ant. 3> 802.11a : 14.83 dBm / 0.0304 W MIMO <Ant. 1 + 2 + 3> 802.11n HT20 : 12.75 dBm / 0.0188 W 802.11n HT40 : 14.40 dBm / 0.0275 W 802.11ac VHT80: 15.16 dBm / 0.0328 W			
99% Occupied Bandwidth	802.11a : 17.18 MHz 802.11n HT20 : 18.28 MHz 802.11n HT40 : 36.06 MHz 802.11ac VHT80 : 75.76 MHz			
Antenna Type / Gain	<5180 MHz ~ 5240 MHz> Ant. 1 : PIFA Antenna with gain 2.97 dBi Ant. 2 : PIFA Antenna with gain 2.53 dBi Ant. 3 : PIFA Antenna with gain 2.93 dBi			
Type of Modulation	802.11a/n : OFDM (BPSK / QPSK / 16QAM / 64QAM) 802.11ac : OFDM (BPSK / QPSK / 16QAM / 64QAM / 256QAM)			
Antenna Function Description		Ant.1	Ant.2	Ant.3
	802.11a SISO	V	V	V
	802.11n/ac MIMO	V	V	V

Note:

1. MIMO Ant. 1+2 + 3 is a calculated result from sum of the power MIMO Ant. 1, MIMO Ant. 2 and MIMO Ant. 3.
2. For 802.11n HT20 / ac VHT20 and 802.11n HT40 / ac VHT40 mode, the whole testing have assessed only 802.11an HT20/ HT40 by referring to their maximum conducted power.
3. Only 802.11n/ac support TX Beamforming.

1.5 Modification of EUT

No modifications are made to the EUT during all test items.



1.6 Testing Location

Sporton Lab is accredited to ISO 17025 by National Voluntary Laboratory Accreditation Program (NVLAP code: 600155-0) and the FCC designation No. is CN5013.

Test Site	Sporton International (Kunshan) Inc.			
Test Site Location	No.3-2 Ping-Xiang Rd, Kunshan Development Zone Kunshan City Jiangsu Province 215335 China TEL : +86-512-57900158 FAX : +86-512-57900958			
Test Site No.	Sporton Site No.			FCC Test Firm Registration No.
	TH01-KS	03CH03-KS	CO01-KS	630927

Note: The test site complies with ANSI C63.4 2014 requirement.

1.7 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- FCC Part 15 Subpart E
- FCC KDB 789033 D02 General UNII Test Procedures New Rules v01r04.
- FCC KDB 662911 D01 Multiple Transmitter Output v02r01.
- FCC KDB 644545 D03 Guidance for IEEE 802.11ac New Rules v01
- ANSI C63.10-2013
- IC RSS-247 Issue 2
- IC RSS-Gen Issue 4

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

2 Test Configuration of Equipment Under Test

The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conducted emission (150 kHz to 30 MHz) and radiated emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases were recorded in this report.

2.1 Carrier Frequency and Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
5180-5240 MHz Band 1 (U-NII-1)	36	5180	44	5220
	38*	5190	46*	5230
	40	5200	48	5240
	42 [#]	5210	-	-

Note:

1. The above Frequency and Channel in "*" were 802.11n HT40 and 802.11ac VHT40.
2. The above Frequency and Channel in "[#]" were 802.11ac VHT80.

2.2 Test Mode

Final test mode of conducted test items and radiated spurious emissions are considering the modulation and worse data rates as below table.

Single Antenna

Modulation	Data Rate
802.11a	6 Mbps

MIMO Antenna

Modulation	Data Rate
802.11n HT20	MCS0
802.11n HT40	MCS0
802.11ac VHT80	MCS0


Test Cases	
AC Conducted Emission	Mode 1 : WCDMA Band V Idle + Phone Link + WLAN Link(5G) + Adapter + Lan Link + Lan Load + U Disk + GNSS Rx + WWAN Internal Antenna

Ch. #		Band I : 5180-5240 MHz	Band I : 5180-5240 MHz	Band I : 5180-5240 MHz
		802.11a	802.11n HT20	802.11n HT40
L	Low	36	36	38
M	Middle	44	44	-
H	High	48	48	46


Ch. #		Band I : 5180-5240 MHz
		802.11ac VHT80
L	Low	-
M	Middle	42
H	High	-

2.3 Connection Diagram of Test System

<WLAN Tx Mode>



<AC Conducted Emission Mode>



2.4 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	System Simulator	R&S	CMU 200	N/A	N/A	Unshielded, 1.8m
2.	WLAN AP	LINKSYS	WRT600N	Q87-WRT600NV11	N/A	Unshielded, 1.8m
3.	GPS Station	ADIVIC	MP9000	N/A	N/A	Unshielded, 1.8m
4.	Glonass Station	RACELOGIC	RLLS03-2RP	N/A	N/A	Unshielded, 1.8m
5.	Notebook	Lenovo	G480	N/A	N/A	AC I/P: Unshielded, 1.8m DC O/P: Shielded, 1.8 m
6.	Monitor	Dell	IN1930MWc	Fcc DoC	N/A	Unshielded, 1.8m
7.	Telephone*2	BBK	HCD007(6082)TSD	N/A	N/A	N/A
8.	U Disk	SanDisk	SDCZ51-004G	N/A	N/A	N/A
9.	iPod	Apple	A1199	Fcc DoC	Shielded, 1.2m	N/A
10.	RJ45 Cable	N/A	N/A	N/A	Unshielded,1.8m	N/A
11.	RJ11 Cable	N/A	N/A	N/A	Unshielded,1.8m	N/A
12.	HDMI Cable	N/A	N/A	N/A	Unshielded,1.2m	N/A

2.5 EUT Operation Test Setup

For WLAN function, the engineering test program was provided and enabled to make EUT continuous transmit/receive.

For AC power line conducted emissions, the EUT was set to connect with the Notebook under large package sizes transmission.



2.6 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example:

The spectrum analyzer offset is derived from RF cable loss.

Offset = RF cable loss.

Following shows an offset computation example with cable loss 6.8dB.

Offset(dB) = RF cable loss(dB).

= 6.8 (dB)

3 Test Result

3.1 26dB & 99% Occupied Bandwidth Measurement

3.1.1 Description of 26dB & 99% Occupied Bandwidth

This section is for reporting purpose only.

There is no restriction limits for bandwidth.


3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.1.3 Test Procedures

1. The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v01r04.
Section C) Emission bandwidth
2. Set RBW = approximately 1% of the emission bandwidth.
3. Set the VBW > RBW.
4. Detector = Peak.
5. Trace mode = max hold
6. Measure the maximum width of the emission that is 26 dB down from the peak of the emission.
Compare this with the RBW setting of the analyzer. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is approximately 1%.
7. For 99% Bandwidth Measurement, the spectrum analyzer's resolution bandwidth (RBW) is set 1MHz and set the Video bandwidth (VBW) $\geq 3 * \text{RBW}$.
8. Measure and record the results in the test report.



3.1.4 Test Setup





3.1.5 Test Result of 26dB & 99% Occupied Bandwidth

Please refer to Appendix A.



Note: The occupied channel bandwidth is maintained within the band of operation for all of the modulations.



3.2 Maximum Conducted Output Power Measurement

3.2.1 Limit of Maximum Conducted Output Power

<FCC 14-30 CFR 15.407>

For Indoor AP devices in the 5.15–5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 1 W.

If transmitting antennas of directional gain greater than 6 dBi are used, the peak output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Note that U-NII-2 band, devices with a maximum e.i.r.p. greater than 500 mW shall implement TPC in order to have the capability to operate at least 6 dB below the maximum permitted e.i.r.p. of 1 W.

3.2.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.


3.2.3 Test Procedures

The testing follows Method PM of FCC KDB 789033 D02 General UNII Test Procedures New Rules v01r04.

Method PM (Measurement using an RF average power meter):

1. Measurement is performed using a wideband RF power meter.
2. The EUT is configured to transmit continuously with a consistent duty cycle at its maximum power control level.
3. Measure the average power of the transmitter, and the average power is corrected with duty factor, $10 \log(1/x)$, where x is the duty cycle.

3.2.4 Test Setup



3.2.5 Test Result of Maximum Conducted Output Power

Please refer to Appendix A.



3.3 Power Spectral Density Measurement

3.3.1 Limit of Power Spectral Density

<FCC 14-30 CFR 15.407>

For Indoor AP devices in the 5.15–5.25 GHz band, the maximum power spectral density shall not exceed 17dBm in any 1 megahertz band.

If transmitting antennas of directional gain greater than 6 dBi are used, the peak output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

3.3.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.3.3 Test Procedures

The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v01r04.

Section F) Maximum power spectral density.

Method SA-2


(trace averaging across on and off times of the EUT transmissions, followed by duty cycle correction).

1. The testing follows Method SA-2 of FCC KDB 789033 D02 General UNII Test Procedures New Rules v01r04.
 - Measure the duty cycle.
 - Set span to encompass the entire emission bandwidth (EBW) of the signal.
 - Set RBW = 1 MHz.
 - Set VBW $\geq$ 3 MHz.
 - Number of points in sweep $\geq$ 2 Span / RBW.
 - Sweep time = auto.
 - Detector = RMS
 - Trace average at least 100 traces in power averaging mode.
 - Add $10 \log(1/x)$, where x is the duty cycle, to the measured power in order to compute the average power during the actual transmission times. For example, add $10 \log(1/0.25) = 6$ dB if the duty cycle is 25 percent.
2. The RF output of EUT was connected to the spectrum analyzer by a low loss cable.
3. Each plot has already offset with cable loss, and attenuator loss. Measure the PPSD and record it.
4. For MIMO mode, calculation method follows FCC KDB 662911 D01 Multiple Transmitter Output v02r01.

Method (a): Measure and sum the spectra across the outputs.


The total final Power Spectral Density is from a device with 3 transmitter outputs. The spectrum measurements of the individual outputs are all performed with the same span and number of points, the spectrum value in the first spectral bin of output 1 is summed with that in the first spectral bin of output 2 and output 3 to obtain the value for the first frequency bin of the summed spectrum.

3.3.4 Test Setup



3.3.5 Test Result of Power Spectral Density

Please refer to Appendix A.



Note: Average Power Density (dB) = Measured value+ Duty Factor

3.4 Unwanted Emissions Measurement

This section is to measure unwanted emissions through radiated measurement for band edge spurious emissions and out of band emissions measurement.

3.4.1 Limit of Unwanted Emissions

- (1) For transmitters operating in the 5150-5250 MHz band: all emissions outside of the 5150-5350 MHz band shall not exceed an EIRP of -27dBm/MHz.
- (2) Unwanted spurious emissions fallen in restricted bands shall comply with the general field strength limits as below table

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

Note: The following formula is used to convert the EIRP to field strength.

$$E = \frac{1000000\sqrt{30P}}{3} \quad \mu\text{V/m, where P is the eirp (Watts)}$$



EIRP (dBm)	Field Strength at 3m (dBμV/m)
- 27	68.3

(3) KDB789033 D01 v01r04 G)2)c)

- (i) Section 15.407(b)(1) to (b)(3) specify the unwanted emission limits for the U-NII-1 and U-NII-2 bands. As specified, emissions above 1000 MHz that are outside of the restricted bands are subject to a peak emission limit of -27 dBm/MHz.³
- (ii) Section 15.407(b)(4) specifies the unwanted emission limit for the U-NII-3 band. A band emissions mask is specified in Section 15.407(b)(4)(i). The emission limits are in terms of a Peak detector. An alternative to the band emissions mask is specified in Section 15.407(b)(4)(ii). The alternative limits are based on the highest antenna gain specified in the filing. There are also marketing and importation restrictions for the devices using the alternative limit.⁴

Note 3: An out-of-band emission that complies with both the average and peak limits of Section 15.209 is not required to satisfy the -27 dBm/MHz peak emission limit.

Note 4: Only devices with antenna gains of 10 dBi or less may be approved using the emission limits specified in Section 15.247(d) till March 2, 2018; all other devices operating in this band must use the mask specified in Section 15.407(b)(4)(i).

3.4.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.4.3 Test Procedures

1. The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v01r04.

Section G) Unwanted emissions measurement.

(1) Procedure for Unwanted Emissions Measurements Below 1000MHz

- RBW = 120 kHz
- VBW = 300 kHz
- Detector = Peak
- Trace mode = max hold

(2) Procedure for Peak Unwanted Emissions Measurements Above 1000 MHz

- RBW = 1 MHz
- VBW $\geq$ 3 MHz
- Detector = Peak
- Sweep time = auto
- Trace mode = max hold

(3) Procedures for Average Unwanted Emissions Measurements Above 1000MHz

- RBW = 1 MHz
- VBW = 10 Hz, when duty cycle is no less than 98 percent.
- VBW $\geq$ 1/T, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.

(4) Procedures for Average Unwanted Emissions Measurements Above 1000MHz


- RBW = 1 MHz
- VBW = 3 MHz
- Detector = power averaging (rms), set sweep point $\geq$ 2 span / RBW.
- Averaging type = power averaging(RMS)
- The correction factor shall be offset is 10 log (1/x), where x is the duty cycle.




2. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
3. The EUT was set 3 meters from the interference receiving antenna which was mounted on the top of a variable height antenna tower.
4. The antenna is a broadband antenna and its height is adjusted between one meter and four meters above ground to find the maximum value of the field strength for both horizontal polarization and vertical polarization of the antenna.
5. For each suspected emission, the EUT was arranged to its worst case and then adjust the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading.
6. For testing below 1GHz, if the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then peak values of EUT will be reported, otherwise, the emissions will be repeated one by one using the CISPR quasi-peak method and reported.
7. For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than average limit (that means the emission level in average mode also complies with the limit in average mode), then peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.

3.4.4 Test Setup

For radiated emissions below 30MHz




For radiated emissions from 30MHz to 1GHz




For radiated emissions above 1GHz

Non-TXBF Mode



TXBF Mode



**3.4.5 Test Results of Radiated Spurious Emissions (9 kHz ~ 30 MHz)**

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

3.4.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix B.

3.4.7 Duty Cycle

Please refer to Appendix C.

3.4.8 Test Result of Radiated Spurious Emissions (30MHz ~ 10th Harmonic)

Please refer to Appendix B.

3.5 AC Conducted Emission Measurement

3.5.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.5.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.5.3 Test Procedures


1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode.

3.5.4 Test Setup



3.5.5 Test Result of AC Conducted Emission

Test Mode :	Mode 1	Temperature :	22~24℃
Test Engineer :	Amos Zhang	Relative Humidity :	44~47%
Test Voltage :	120Vac / 60Hz	Phase :	Line
Function Type :	WCDMA Band V Idle + Phone Link + WLAN Link(5G) + Adapter + Lan Link + Lan Load + U Disk + GNSS Rx + WWAN Internal Antenna		




Site : CO01-KS
Condition : FCC PART 15E LISN-L-161017-060103 LINE

	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV		dBuV	dBuV			
1	0.169	48.19	-16.84	65.03	37.20	0.44	10.55	QP
2	0.169	39.29	-15.74	55.03	28.30	0.44	10.55	Average
3	0.178	47.80	-16.79	64.59	36.90	0.38	10.52	QP
4	0.178	38.20	-16.39	54.59	27.30	0.38	10.52	Average
5	0.190	46.40	-17.62	64.02	35.60	0.32	10.48	QP
6	0.190	38.00	-16.02	54.02	27.20	0.32	10.48	Average
7	0.202	42.82	-20.72	63.54	32.10	0.27	10.45	QP
8	0.202	34.02	-19.52	53.54	23.30	0.27	10.45	Average
9	0.228	40.32	-22.20	62.52	29.60	0.27	10.45	QP
10	0.228	29.92	-22.60	52.52	19.20	0.27	10.45	Average
11	0.421	38.25	-19.17	57.42	27.60	0.27	10.38	QP
12 *	0.421	36.25	-11.17	47.42	25.60	0.27	10.38	Average



Test Mode :	Mode 1	Temperature :	22~24°C
Test Engineer :	Amos Zhang	Relative Humidity :	44~47%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Function Type :	WCDMA Band V Idle + Phone Link + WLAN Link(5G) + Adapter + Lan Link + Lan Load + U Disk + GNSS Rx + WWAN Internal Antenna		



Site : CO01-KS
Condition : FCC PART 15E LISN-N-161017-060103 NEUTRAL

	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.156	50.54	-15.15	65.69	39.60	0.34	10.60	QP
2	0.156	41.54	-14.15	55.69	30.60	0.34	10.60	Average
3	0.171	47.18	-17.72	64.90	36.29	0.34	10.55	QP
4	0.171	40.18	-14.72	54.90	29.29	0.34	10.55	Average
5	0.191	45.41	-18.57	63.98	34.60	0.33	10.48	QP
6	0.191	39.61	-14.37	53.98	28.80	0.33	10.48	Average
7	0.200	44.39	-19.23	63.62	33.60	0.33	10.46	QP
8	0.200	35.99	-17.63	53.62	25.20	0.33	10.46	Average
9	0.426	43.95	-13.38	57.33	33.20	0.37	10.38	QP
10 *	0.426	41.85	-5.48	47.33	31.10	0.37	10.38	Average
11	0.474	39.31	-17.14	56.45	28.60	0.38	10.33	QP
12	0.474	35.91	-10.54	46.45	25.20	0.38	10.33	Average
13	5.867	32.98	-27.02	60.00	22.30	0.36	10.32	QP
14	5.867	27.28	-22.72	50.00	16.60	0.36	10.32	Average

3.6 Frequency Stability Measurement

3.6.1 Limit of Frequency Stability

Manufacturers of U-NII devices are responsible for ensuring frequency stability such that an emission is maintained within the band of operation under all conditions of normal operation as specified in the user's manual.


3.6.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.6.3 Test Procedures

1. To ensure emission at the band edge is maintained within the authorized band, those values shall be measured by radiation emissions at upper and lower frequency points, and finally compensated by frequency deviation as procedures below.
2. The EUT was operated at the maximum output power, and connected to the spectrum analyzer, which is set to maximum hold function and peak detector. The peak value of the power envelope was measured and noted. The upper and lower frequency points were respectively measured relatively 10dB lower than the measured peak value.
3. The frequency deviation was calculated by adding the upper frequency point and the lower frequency point divided by two. Those detailed values of frequency deviation are provided in table below.

3.6.4 Test Setup



3.6.5 Test Result of Frequency Stability

Please refer to Appendix A.



3.7 Automatically Discontinue Transmission

3.7.1 Limit of Automatically Discontinue Transmission

The device shall automatically discontinue transmission in case of either absence of information to transmit or operational failure. These provisions are not intended to preclude the transmission of control or signaling information or the use of repetitive codes used by certain digital technologies to complete frame or burst intervals. Applicants shall include in their application for equipment authorization to describe how this requirement is met.

3.7.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.7.3 Test Result of Automatically Discontinue Transmission

While the EUT is not transmitting any information, the EUT can automatically discontinue transmission and become standby mode for power saving. The EUT can detect the controlling signal of ACK message transmitting from remote device and verify whether it shall resend or discontinue transmission.

3.8 Antenna Requirements

3.8.1 Standard Applicable

If transmitting antenna directional gain is greater than 6 dBi, both the peak transmit power and the peak power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

3.8.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

3.8.3 Antenna Gain

TXBF modes

FCC KDB 662911 D01 Multiple Transmitter Output v02r01

$$DirectionalGain = 10 \cdot \log \left[\frac{\sum_{j=1}^{N_{SS}} \left\{ \sum_{k=1}^{N_{ANT}} g_{j,k} \right\}^2}{N_{ANT}} \right]$$

where

Each antenna is driven by no more than one spatial stream;

N_{SS} = the number of independent spatial streams of data;

N_{ANT} = the total number of antennas

$g_{j,k} = 10^{G_k / 20}$ if the k th antenna is being fed by spatial stream j , or zero if it is not;
 G_k is the gain in dBi of the k th antenna.

The EUT supports beamforming for 802.11n/ac modes.

The directional gain calculation is following F)2)e)ii) of KDB 662911 D01 v02r01.

The power and PSD limit should be modified if the directional gain of EUT is over 6 dBi,

The directional gain "DG" is calculated as following table.



Antenna	DG for Power (dBi)	DG for PSD (dBi)	Power Limit Reduction (dB)	PSD Limit Reduction (dB)
1+2+3	7.59	7.59	1.59	1.59



4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSV40	101040	10Hz~40GHz	Aug. 08, 2017	Sep. 25, 2017~ Sep. 26, 2017	Aug. 07, 2018	Conducted (TH01-KS)
Pulse Power Sensor	Anritsu	MA2411B	0917070	300MHz~40GHz	Jan. 19, 2017	Sep. 25, 2017~ Sep. 26, 2017	Jan. 18, 2018	Conducted (TH01-KS)
Power Meter	Anritsu	ML2495A	1005002	50MHz Bandwidth	Jan. 19, 2017	Sep. 25, 2017~ Sep. 26, 2017	Jan. 18, 2018	Conducted (TH01-KS)
Thermal Chamber	Hongzhan	LP-150U	HZ014011440	-40~+150°C 20%~95%RH	Apr.18, 2017	Sep. 25, 2017~ Sep. 26, 2017	Apr. 17, 2018	Conducted (TH01-KS)
EMI Test Receiver	Keysight	N9038A	MY56400004	3Hz~8.5GHz; Max 30dBm	Oct. 22, 2016	Sep. 19, 2017	Oct. 21, 2017	Radiation (03CH03-KS)
EXA Spectrum Analyzer	Keysight	N9010A	MY55150244	10Hz~44GHz	Apr. 18, 2017	Sep. 19, 2017	Apr. 17, 2018	Radiation (03CH03-KS)
Loop Antenna	R&S	HFH2-Z2	100321	9kHz~30MHz	Nov. 23, 2016	Sep. 19, 2017	Nov. 22, 2017	Radiation (03CH03-KS)
Bilog Antenna	TeseQ	CBL6112D	35406	25MHz~2GHz	Apr. 22, 2017	Sep. 19, 2017	Apr. 21, 2018	Radiation (03CH03-KS)
Horn Antenna	Schwarzbeck	BBHA9120D	9120D-1356	1GHz~18GHz	Apr. 22, 2017	Sep. 19, 2017	Apr. 21, 2018	Radiation (03CH03-KS)
SHF-EHF Horn	com-power	AH-840	101070	18GHz~40GHz	Oct. 19, 2016	Sep. 19, 2017	Oct. 18, 2017	Radiation (03CH03-KS)
Amplifier	com-power	PA-103A	161069	1MHz~1000MHz / 32 dB	Apr. 18, 2017	Sep. 19, 2017	Apr. 17, 2018	Radiation (03CH03-KS)
Amplifier	MITEQ	TTA1840-35-HG	1887435	18GHz~40GHz	Oct. 13, 2016	Sep. 19, 2017	Oct. 12, 2017	Radiation (03CH03-KS)
high gain Amplifier	MITEQ	AMF-7D-0010 1800-30-10P	2025788	1GHz~18GHz	Apr. 18, 2017	Sep. 19, 2017	Apr. 17, 2018	Radiation (03CH03-KS)
Amplifier	Agilent	8449B	3008A02370	1GHz~26.5GHz	Oct. 13, 2016	Sep. 19, 2017	Oct. 12, 2017	Radiation (03CH03-KS)
AC Power Source	Chroma	61601	F104090004	N/A	NCR	Sep. 19, 2017	NCR	Radiation (03CH03-KS)
Turn Table	ChamPro	EM 1000-T	060762-T	0~360 degree	NCR	Sep. 19, 2017	NCR	Radiation (03CH03-KS)
Antenna Mast	ChamPro	EM 1000-A	060762-A	1 m~4 m	NCR	Sep. 19, 2017	NCR	Radiation (03CH03-KS)
EMI Receiver	R&S	ESCI7	100768	9kHz~7GHz;	Apr. 20, 2017	Sep. 11, 2017	Apr. 19, 2018	Conduction (CO01-KS)
AC LISN	MessTec	AN3016	060103	9kHz~30MHz	Oct. 13, 2016	Sep. 11, 2017	Oct. 12, 2017	Conduction (CO01-KS)
AC LISN (for auxiliary equipment)	MessTec	AN3016	060105	9kHz~30MHz	Oct. 13, 2016	Sep. 11, 2017	Oct. 12, 2017	Conduction (CO01-KS)
AC Power Source	Chroma	61602	ABP000000811	AC 0V~300V, 45Hz~1000Hz	Oct. 13, 2016	Sep. 11, 2017	Oct. 12, 2017	Conduction (CO01-KS)

NCR: No Calibration Required

5 Uncertainty of Evaluation

Uncertainty of Conducted Emission Measurement (150kHz ~ 30MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	2.3dB
---	-------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	4.6dB
---	-------

Uncertainty of Radiated Emission Measurement (1000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	4.5dB
---	-------

Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	4.7dB
---	-------



Appendix A. Conducted Test Results

Report Number : FR780901B

Test Engineer:	Silent Hai	Temperature:	21~25	°C
Test Date:	2017/9/25 ~ 2017/9/26	Relative Humidity:	51~55	%

TEST RESULTS DATA
26dB and 99% OBW

Band I																
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	26 dB Bandwidth (MHz)				99% Bandwidth (MHz)				IC 99% Bandwidth EIRP Limit (dBm)			
					Ant 1	Ant 2	Ant 3	Ant 4	Ant 1	Ant 2	Ant 3	Ant 4	Ant 1	Ant 2	Ant 3	Ant 4
11a	6Mbps	1	36	5180	20.78				17.18				22.35			
11a	6Mbps	1	44	5220	20.88				17.13				22.34			
11a	6Mbps	1	48	5240	20.83				17.13				22.34			
11a	6Mbps	1	36	5180		20.48				17.03				22.31		
11a	6Mbps	1	44	5220		20.88				17.18				22.35		
11a	6Mbps	1	48	5240		20.78				17.18				22.35		
11a	6Mbps	1	36	5180			20.93				17.13				22.34	
11a	6Mbps	1	44	5220			20.98				17.13				22.34	
11a	6Mbps	1	48	5240			20.93				17.13				22.34	

Band I																
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	26 dB Bandwidth (MHz)				99% Bandwidth (MHz)				IC 99% Bandwidth EIRP Limit (dBm)			
					Ant 1	Ant 2	Ant 3	Ant 4	Ant 1	Ant 2	Ant 3	Ant 4	Ant 1	Ant 2	Ant 3	Ant 4
HT20	MCS0	3	36	5180	21.38	21.23	21.53		18.08	18.08	18.28		22.57	22.57	22.62	
HT20	MCS0	3	44	5220	21.48	21.43	21.63		18.03	18.13	18.23		22.56	22.58	22.61	
HT20	MCS0	3	48	5240	21.43	21.43	21.88		18.03	18.08	18.23		22.56	22.57	22.61	
HT40	MCS0	3	38	5190	40.37	40.10	39.83		35.96	36.06	35.66		23.01	23.01	23.01	
HT40	MCS0	3	46	5230	40.1	40.46	40.01		35.96	36.06	35.76		23.01	23.01	23.01	
VHT80	MCS0	3	42	5210	83.6	83.28	82.32		75.76	75.76	75.40		23.01	23.01	23.01	

TEST RESULTS DATA
Average Power Table

FCC Band I															
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Ant	Average Conducted Power with duty factor (dBm)					FCC Power Limit (dBm)	DG (dBi)	FCC EIRP Power (dBm)	FCC EIRP Power Limit (dBm)	Pass/Fail
						Ant 1	Ant 2	Ant 3	Ant 4	SUM					
11a	6Mbps	1	36	5180	1	14.90				14.90	30.00	2.97	17.88	-	Pass
11a	6Mbps	1	44	5220	1	14.85				14.85	30.00	2.97	17.83	-	Pass
11a	6Mbps	1	48	5240	1	14.71				14.71	30.00	2.97	17.69	-	Pass
11a	6Mbps	1	36	5180	2		14.81			14.81	30.00	2.53	17.34	-	Pass
11a	6Mbps	1	44	5220	2		14.71			14.71	30.00	2.53	17.24	-	Pass
11a	6Mbps	1	48	5240	2		14.60			14.60	30.00	2.53	17.13	-	Pass
11a	6Mbps	1	36	5180	3			14.78		14.78	30.00	2.93	17.71	-	Pass
11a	6Mbps	1	44	5220	3			14.83		14.83	30.00	2.93	17.76	-	Pass
11a	6Mbps	1	48	5240	3			14.74		14.74	30.00	2.93	17.67	-	Pass

FCC Band I															
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Ant	Average Conducted Power with duty factor (dBm)					FCC Power Limit (dBm)	DG (dBi)	FCC EIRP Power (dBm)	FCC EIRP Power Limit (dBm)	Pass/Fail
						Ant 1	Ant 2	Ant 3	Ant 4	SUM					
HT20	MCS0	3	36	5180	1+2+3	8.51	8.28	6.51		12.62	28.41	7.59	20.21	-	Pass
HT20	MCS0	3	44	5220	1+2+3	8.61	8.21	6.95		12.75	28.41	7.59	20.34	-	Pass
HT20	MCS0	3	48	5240	1+2+3	8.41	7.99	6.98		12.60	28.41	7.59	20.19	-	Pass
HT40	MCS0	3	38	5190	1+2+3	10.05	9.88	8.68		14.35	28.41	7.59	21.94	-	Pass
HT40	MCS0	3	46	5230	1+2+3	10.21	9.75	8.79		14.40	28.41	7.59	21.99	-	Pass
VHT80	MCS0	3	42	5210	1+2+3	10.92	10.68	9.42		15.16	28.41	7.59	22.75	-	Pass

TEST RESULTS DATA
Power Spectral Density

FCC Band I													
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Ant	Duty Factor (dB)				Average PSD with Duty Factor (dBm/MHz)	PSD Limit (dBm/MHz)	DG (dBi)	Pass /Fail
						Ant 1	Ant 2	Ant 3	Ant 4				
11a	6Mbps	1	36	5180	1	0.13				3.92	17.00	2.97	Pass
11a	6Mbps	1	44	5220	1	0.13				3.35	17.00	2.97	Pass
11a	6Mbps	1	48	5240	1	0.13				3.33	17.00	2.97	Pass
11a	6Mbps	1	36	5180	2		0.13			3.45	17.00	2.53	Pass
11a	6Mbps	1	44	5220	2		0.13			3.18	17.00	2.53	Pass
11a	6Mbps	1	48	5240	2		0.13			2.93	17.00	2.53	Pass
11a	6Mbps	1	36	5180	3			0.13		3.31	17.00	2.93	Pass
11a	6Mbps	1	44	5220	3			0.13		3.31	17.00	2.93	Pass
11a	6Mbps	1	48	5240	3			0.13		3.39	17.00	2.93	Pass

FCC Band I													
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Ant	Duty Factor (dB)				Average PSD with Duty Factor (dBm/MHz)	PSD Limit (dBm/MHz)	DG (dBi)	Pass /Fail
						Ant 1	Ant 2	Ant 3	Ant 4				
HT20	MCS0	3	36	5180	1+2+3	0.06	0.06	0.06		1.21	15.41	7.59	Pass
HT20	MCS0	3	44	5220	1+2+3	0.06	0.06	0.06		1.37	15.41	7.59	Pass
HT20	MCS0	3	48	5240	1+2+3	0.06	0.06	0.06		1.18	15.41	7.59	Pass
HT40	MCS0	3	38	5190	1+2+3	0.10	0.10	0.10		0.28	15.41	7.59	Pass
HT40	MCS0	3	46	5230	1+2+3	0.10	0.10	0.10		0.24	15.41	7.59	Pass
VHT80	MCS0	3	42	5210	1+2+3	0.24	0.24	0.24		-2.48	15.41	7.59	Pass

TEST RESULTS DATA
Frequency Stability

Band I										
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Center Frequency (MHz)	Frequency Deviation (MHz)	Frequency Stability (ppm)	Temperature (°C)	Voltage (V)	Note
11a	6Mbps	1	36	5180	5180.000	0.000	0.00	20	3.4	
11a	6Mbps	1	36	5180	5180.000	0.000	0.00	20	4.35	
11a	6Mbps	1	36	5180	5180.000	0.000	0.00	20	3.8	
11a	6Mbps	1	36	5180	5180.025	0.025	4.83	-30	3.8	
11a	6Mbps	1	36	5180	5179.975	-0.025	-4.83	50	3.8	



Appendix B. Radiated Spurious Emission

Non-TXBF Mode

Band 1 - 5150~5250MHz

WIFI 802.11a (Band Edge @ 3m)

WIFI Ant.	Note	Frequency	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Ant Pos	Table Pos	Peak Avg.	Pol.
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11a CH 36 5180MHz		5118.08	51.36	-22.64	74	44.87	31.2	11.84	36.55	298	107	P	H
		5120	41.7	-12.3	54	35.21	31.2	11.84	36.55	298	107	A	H
	*	5186	106.6	-	-	100.05	31.14	11.93	36.52	298	107	P	H
	*	5186	98.94	-	-	92.39	31.14	11.93	36.52	298	107	A	H
		5144.32	50.55	-23.45	74	44.03	31.17	11.88	36.53	365	243	P	V
		5119.84	41.41	-12.59	54	34.92	31.2	11.84	36.55	365	243	A	V
	*	5182	105.37	-	-	98.82	31.14	11.93	36.52	365	243	P	V
	*	5182	98.43	-	-	91.88	31.14	11.93	36.52	365	243	A	V
802.11a CH 44 5220MHz		5117.44	51.39	-22.61	74	44.9	31.2	11.84	36.55	356	105	P	H
		5120.48	41.17	-12.83	54	34.68	31.2	11.84	36.55	356	105	A	H
	*	5218	106.31	-	-	99.73	31.11	11.97	36.5	356	105	P	H
	*	5218	98.63	-	-	92.05	31.11	11.97	36.5	356	105	A	H
		5398.02	48.58	-25.42	74	41.87	30.93	12.19	36.41	356	105	P	H
		5376.24	39.88	-14.12	54	33.19	30.96	12.15	36.42	356	105	A	H
		5117.44	50.52	-23.48	74	44.03	31.2	11.84	36.55	305	268	P	V
		5119.52	40.95	-13.05	54	34.46	31.2	11.84	36.55	305	268	A	V
	*	5224	104.67	-	-	98.09	31.11	11.97	36.5	305	268	P	V
	*	5224	97.36	-	-	90.78	31.11	11.97	36.5	305	268	A	V
		5372.28	48.07	-25.93	74	41.38	30.96	12.15	36.42	305	268	P	V
		5376.24	39.33	-14.67	54	32.64	30.96	12.15	36.42	305	268	A	V



802.11a CH 48 5240MHz	*	5238	105.98	-	-	99.39	31.09	11.99	36.49	325	103	P	H
	*	5238	98.59	-	-	92	31.09	11.99	36.49	325	103	A	H
		5387.22	48.27	-25.73	74	41.58	30.94	12.17	36.42	325	103	P	H
		5375.88	39.96	-14.04	54	33.27	30.96	12.15	36.42	325	103	A	H
	*	5242	105.82	-	-	99.22	31.07	12.01	36.48	355	249	P	V
	*	5242	98.18	-	-	91.58	31.07	12.01	36.48	355	249	A	V
		5353.92	48.35	-25.65	74	41.67	30.98	12.13	36.43	355	249	P	V
		5376.06	39.51	-14.49	54	32.82	30.96	12.15	36.42	355	249	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band 1 5150~5250MHz

WIFI 802.11a (Harmonic @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11a		10360	41.85	-32.15	74	54.95	37.4	15.65	66.15	100	360	P	H
CH 36 5180MHz		10360	42.36	-31.64	74	55.46	37.4	15.65	66.15	100	360	P	V
802.11a		10440	42.89	-31.11	74	55.84	37.47	15.68	66.1	100	360	P	H
CH 44 5220MHz		10440	44.2	-29.8	74	57.15	37.47	15.68	66.1	100	360	P	V
802.11a		10480	43.05	-30.95	74	55.9	37.52	15.7	66.07	100	360	P	H
CH 48 5240MHz		10480	43.8	-30.2	74	56.65	37.52	15.7	66.07	100	360	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												


Band 1 - 5150~5250MHz
WIFI 802.11a (Band Edge @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
2		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11a CH 36 5180MHz		5140	50.74	-23.26	74	44.22	31.17	11.88	36.53	332	151	P	H
		5139.2	41.03	-12.97	54	34.52	31.19	11.86	36.54	332	151	A	H
		5184	104.6	-	-	98.05	31.14	11.93	36.52	332	151	P	H
		5184	96.76	-	-	90.21	31.14	11.93	36.52	332	151	A	H
		5126.4	50.2	-23.8	74	43.69	31.19	11.86	36.54	100	91	P	V
		5137.44	40.62	-13.38	54	34.11	31.19	11.86	36.54	100	91	A	V
	*	5178	104.19	-	-	97.64	31.14	11.93	36.52	100	91	P	V
	*	5178	96.6	-	-	90.05	31.14	11.93	36.52	100	91	A	V

**Band 1 5150~5250MHz****WIFI 802.11a (Harmonic @ 3m)**

WIFI Ant. 2	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11a		10360	43.32	-30.68	74	56.42	37.4	15.65	66.15	100	360	P	H
CH 36 5180MHz		10360	42.52	-31.48	74	55.62	37.4	15.65	66.15	100	360	P	V


Band 1 - 5150~5250MHz
WIFI 802.11a (Band Edge @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
3		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11a CH 36 5180MHz		5120	52.77	-21.23	74	46.28	31.2	11.84	36.55	339	233	P	H
		5120	43.43	-10.57	54	36.94	31.2	11.84	36.55	339	233	A	H
		5182	108.42	-	-	101.87	31.14	11.93	36.52	339	233	P	H
	*	5182	101.05	-	-	94.5	31.14	11.93	36.52	339	233	A	H
		5146.72	51.45	-22.55	74	44.93	31.17	11.88	36.53	317	306	P	V
		5120	42.72	-11.28	54	36.23	31.2	11.84	36.55	317	306	A	V
	*	5182	107.41	-	-	100.86	31.14	11.93	36.52	317	306	P	V
	*	5182	100.2	-	-	93.65	31.14	11.93	36.52	317	306	A	V

**Band 1 5150~5250MHz****WIFI 802.11a (Harmonic @ 3m)**

WIFI Ant. 3	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11a		10360	42.54	-31.46	74	55.64	37.4	15.65	66.15	100	360	P	H
CH 36 5180MHz		10360	42.8	-31.2	74	55.9	37.4	15.65	66.15	100	360	P	V



Band 1 - 5150~5250MHz

WIFI 802.11n HT20 (Band Edge @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1+2+3		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11n HT20 CH 36 5180MHz		5116.48	49.29	-24.71	74	42.8	31.2	11.84	36.55	100	108	P	H
		5119.84	41.74	-12.26	54	35.25	31.2	11.84	36.55	100	108	A	H
	*	5182	104.78	-	-	98.23	31.14	11.93	36.52	100	108	P	H
	*	5182	96.85	-	-	90.3	31.14	11.93	36.52	100	108	A	H
		5114.08	48.9	-25.1	74	42.41	31.2	11.84	36.55	368	277	P	V
		5105.12	39.1	-14.9	54	32.62	31.22	11.82	36.56	368	277	A	V
	*	5182	103.35	-	-	96.8	31.14	11.93	36.52	368	277	P	V
	*	5182	96.01	-	-	89.46	31.14	11.93	36.52	368	277	A	V
802.11n HT20 CH 44 5220MHz		5119.84	48.97	-25.03	74	42.48	31.2	11.84	36.55	300	187	P	H
		5120	40.54	-13.46	54	34.05	31.2	11.84	36.55	300	187	A	H
	*	5222	104.7	-	-	98.12	31.11	11.97	36.5	300	187	P	H
	*	5222	97.24	-	-	90.66	31.11	11.97	36.5	300	187	A	H
		5397.12	47.1	-26.9	74	40.39	30.93	12.19	36.41	300	187	P	H
		5399.82	38.28	-15.72	54	31.57	30.93	12.19	36.41	300	187	A	H
		5104.8	50.32	-23.68	74	43.84	31.22	11.82	36.56	359	276	P	V
		5120	39.31	-14.69	54	32.82	31.2	11.84	36.55	359	276	A	V
	*	5220	101.9	-	-	95.32	31.11	11.97	36.5	359	276	P	V
	*	5220	96.07	-	-	89.49	31.11	11.97	36.5	359	276	A	V
		5398.38	47.89	-26.11	74	41.18	30.93	12.19	36.41	359	276	P	V
		5399.99	38.36	-15.64	54	31.65	30.93	12.19	36.41	359	276	A	V



802.11n HT20 CH 48 5240MHz	*	5242	104.62	-	-	98.02	31.07	12.01	36.48	100	104	P	H
	*	5242	97.3	-	-	90.7	31.07	12.01	36.48	100	104	A	H
		5352.66	48.76	-25.24	74	42.08	30.98	12.13	36.43	100	104	P	H
		5399.82	38.6	-15.4	54	31.89	30.93	12.19	36.41	100	104	A	H
	*	5244	101.47	-	-	94.87	31.07	12.01	36.48	343	281	P	V
	*	5244	94.22	-	-	87.62	31.07	12.01	36.48	343	281	A	V
		5352.3	47.38	-26.62	74	40.7	30.98	12.13	36.43	343	281	P	V
		5399.82	38.31	-15.69	54	31.6	30.93	12.19	36.41	343	281	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band 1 5150~5250MHz
WIFI 802.11n HT20 (Harmonic @ 3m)

WIFI Ant. 1+2+3	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT20 CH 36 5180MHz		10360	41.83	-32.17	74	54.93	37.4	15.65	66.15	100	360	P	H
		10360	42.08	-31.92	74	55.18	37.4	15.65	66.15	100	360	P	V
802.11n HT20 CH 44 5220MHz		10440	41.76	-32.24	74	54.71	37.47	15.68	66.1	100	360	P	H
		10440	45.9	-28.1	74	58.85	37.47	15.68	66.1	100	360	P	V
802.11n HT20 CH 48 5240MHz		10480	43.07	-30.93	74	55.92	37.52	15.7	66.07	100	360	P	H
		10480	43.6	-30.4	74	56.45	37.52	15.7	66.07	100	360	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band 1 5150~5250MHz

WIFI 802.11n HT40 (Band Edge @ 3m)

WIFI Ant. 1+2+3	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT40 CH 38 5190MHz		5143.2	50.08	-23.92	74	43.56	31.17	11.88	36.53	100	156	P	H
		5149.9	40.68	-13.32	54	34.16	31.17	11.88	36.53	100	156	A	H
	*	5182	104.25	-	-	97.7	31.14	11.93	36.52	100	156	P	H
	*	5182	97.17	-	-	90.62	31.14	11.93	36.52	100	156	A	H
		5354.64	49.12	-24.88	74	42.44	30.98	12.13	36.43	100	156	P	H
		5380.38	39.51	-14.49	54	32.82	30.94	12.17	36.42	100	156	A	H
		5135.52	49.7	-24.3	74	43.19	31.19	11.86	36.54	368	264	P	V
		5149.9	40.72	-13.28	54	34.2	31.17	11.88	36.53	368	264	A	V
	*	5198	101.76	-	-	95.2	31.12	11.95	36.51	368	264	P	V
	*	5198	94.51	-	-	87.95	31.12	11.95	36.51	368	264	A	V
		5384.7	47.98	-26.02	74	41.29	30.94	12.17	36.42	368	264	P	V
		5390.1	38.89	-15.11	54	32.2	30.94	12.17	36.42	368	264	A	V
802.11n HT40 CH 46 5230MHz		5145.12	49.39	-24.61	74	42.87	31.17	11.88	36.53	100	235	P	H
		5120	40.99	-13.01	54	34.5	31.2	11.84	36.55	100	235	A	H
	*	5236	102.71	-	-	96.12	31.09	11.99	36.49	100	235	P	H
	*	5236	96.59	-	-	90	31.09	11.99	36.49	100	235	A	H
		5354.82	48.46	-25.54	74	41.78	30.98	12.13	36.43	100	235	P	H
		5383.62	39.49	-14.51	54	32.8	30.94	12.17	36.42	100	235	A	H
		5104.32	49.11	-24.89	74	42.63	31.22	11.82	36.56	362	264	P	V
		5119.84	40.9	-13.1	54	34.41	31.2	11.84	36.55	362	264	A	V
	*	5240	102.31	-	-	95.72	31.09	11.99	36.49	362	264	P	V
	*	5240	94.57	-	-	87.98	31.09	11.99	36.49	362	264	A	V
		5398.38	48.31	-25.69	74	41.6	30.93	12.19	36.41	362	264	P	V
		5385.06	39.01	-14.99	54	32.32	30.94	12.17	36.42	362	264	A	V
Remark	1. No other spurious found.												
	2. All results are PASS against Peak and Average limit line.												



Band 1 5150~5250MHz
WIFI 802.11n HT40 (Harmonic @ 3m)

WIFI Ant. 1+2+3	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT40 CH 38 5190MHz		10380	42.73	-31.27	74	55.8	37.41	15.66	66.14	100	360	P	H
		10380	40.93	-33.07	74	54	37.41	15.66	66.14	100	360	P	V
802.11n HT40 CH 46 5230MHz		10460	43.05	-30.95	74	55.96	37.49	15.69	66.09	100	360	P	H
		10460	43.91	-30.09	74	56.82	37.49	15.69	66.09	100	360	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band 1 5150~5250MHz
WIFI 802.11ac VHT80 (Band Edge @ 3m)

WIFI Ant. 1+2+3	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11ac VHT80 CH 42 5210MHz		5131.36	52.23	-21.77	74	45.72	31.19	11.86	36.54	100	160	P	H
		5141.92	43.59	-10.41	54	37.07	31.17	11.88	36.53	100	160	A	H
	*	5222	101.83	-	-	95.25	31.11	11.97	36.5	100	160	P	H
	*	5222	94.6	-	-	88.02	31.11	11.97	36.5	100	160	A	H
		5352.48	49.62	-24.38	74	42.94	30.98	12.13	36.43	100	160	P	H
		5357.16	40.55	-13.45	54	33.87	30.98	12.13	36.43	100	160	A	H
		5118.56	50.84	-23.16	74	44.35	31.2	11.84	36.55	292	286	P	V
		5145.44	42.56	-11.44	54	36.04	31.17	11.88	36.53	292	286	A	V
	*	5224	98.75	-	-	92.17	31.11	11.97	36.5	292	286	P	V
	*	5224	91.13	-	-	84.55	31.11	11.97	36.5	292	286	A	V
		5400	48.94	-25.06	74	42.23	30.93	12.19	36.41	292	286	P	V
		5351.4	39.58	-14.42	54	32.9	30.98	12.13	36.43	292	286	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												


Band 1 5150~5250MHz
WIFI 802.11ac VHT80 (Harmonic @ 3m)

WIFI Ant. 1+2+3	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11ac		10420	42.39	-31.61	74	55.39	37.45	15.67	66.12	100	360	P	H
VHT80													
CH 42		10420	43.39	-30.61	74	56.39	37.45	15.67	66.12	100	360	P	V
5210MHz													
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												


Emission below 1GHz
WIFI 802.11ac VHT80 (LF @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1+2+3		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11n VHT 80 LF		30.97	27.41	-12.59	40	32.15	26.86	0.69	32.29	100	125	P	H
		117.3	23.17	-20.33	43.5	35.33	18.55	1.56	32.27	-	-	P	H
		216.24	21.41	-24.59	46	35.23	16.23	2.16	32.21	-	-	P	H
		457.77	26.92	-19.08	46	30.5	25.15	3.21	31.94	-	-	P	H
		650.8	28.44	-17.56	46	30.08	25.72	4.34	31.7	-	-	P	H
		794.36	31.28	-14.72	46	30.78	27.83	4.26	31.59	-	-	P	H
		36.79	37.81	-2.19	40	45	24.18	0.89	32.26	100	250	P	V
		66.86	22.99	-17.01	40	40.56	13.46	1.2	32.23	-	-	P	V
		323.91	27.14	-18.86	46	36.21	20.13	2.88	32.08	-	-	P	V
		456.8	27.02	-18.98	46	30.55	25.2	3.21	31.94	-	-	P	V
		644.01	27.82	-18.18	46	29.69	25.56	4.27	31.7	-	-	P	V
		870.02	32.1	-13.9	46	30.34	28.79	4.47	31.5	-	-	P	V
Remark		1. No other spurious found. 2. All results are PASS against limit line.											



TXBF Mode

Band 1 - 5150~5250MHz

WIFI 802.11n HT20 (Band Edge @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1+2+3		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11n HT20 CH 36 5180MHz		5144.16	49.03	-24.97	74	42.51	31.17	11.88	36.53	100	171	P	H
		5120	40.83	-13.17	54	34.34	31.2	11.84	36.55	100	171	A	H
	*	5186	105.18	-	-	98.63	31.14	11.93	36.52	100	171	P	H
	*	5186	97.15	-	-	90.6	31.14	11.93	36.52	100	171	A	H
		5123.52	49.42	-24.58	74	42.91	31.19	11.86	36.54	312	280	P	V
		5104.8	39.34	-14.66	54	32.86	31.22	11.82	36.56	312	280	A	V
	*	5184	102.66	-	-	96.11	31.14	11.93	36.52	312	280	P	V
	*	5184	96.27	-	-	89.72	31.14	11.93	36.52	312	280	A	V
802.11n HT20 CH 44 5220MHz		5119.68	49.77	-24.23	74	43.28	31.2	11.84	36.55	100	104	P	H
		5120	42.36	-11.64	54	35.87	31.2	11.84	36.55	100	104	A	H
	*	5224	105.1	-	-	98.52	31.11	11.97	36.5	100	104	P	H
	*	5224	98.41	-	-	91.83	31.11	11.97	36.5	100	104	A	H
		5385.78	48.34	-25.66	74	41.65	30.94	12.17	36.42	100	104	P	H
		5399.99	38.89	-15.11	54	32.18	30.93	12.19	36.41	100	104	A	H
		5103.68	49.12	-24.88	74	42.64	31.22	11.82	36.56	307	275	P	V
		5120	39.47	-14.53	54	32.98	31.2	11.84	36.55	307	275	A	V
	*	5222	104	-	-	97.42	31.11	11.97	36.5	307	275	P	V
	*	5222	96.07	-	-	89.49	31.11	11.97	36.5	307	275	A	V
		5391.9	47.51	-26.49	74	40.82	30.94	12.17	36.42	307	275	P	V
		5399.82	38.63	-15.37	54	31.92	30.93	12.19	36.41	307	275	A	V



802.11n HT20 CH 48 5240MHz	*	5242	105.27	-	-	98.67	31.07	12.01	36.48	100	108	P	H
	*	5242	98.18	-	-	91.58	31.07	12.01	36.48	100	108	A	H
		5392.62	48.67	-25.33	74	41.98	30.94	12.17	36.42	100	108	P	H
		5351.22	38.84	-15.16	54	32.16	30.98	12.13	36.43	100	108	A	H
	*	5244	102.6	-	-	96	31.07	12.01	36.48	310	311	P	V
	*	5244	95.52	-	-	88.92	31.07	12.01	36.48	310	311	A	V
		5370.66	48.14	-25.86	74	41.45	30.96	12.15	36.42	310	311	P	V
		5384.52	38.62	-15.38	54	31.93	30.94	12.17	36.42	310	311	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band 1 5150~5250MHz
WIFI 802.11n HT20 (Harmonic @ 3m)

WIFI Ant. 1+2+3	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT20 CH 36 5180MHz		10360	42.49	-31.51	74	55.59	37.4	15.65	66.15	100	360	P	H
		10360	44.46	-29.54	74	57.56	37.4	15.65	66.15	100	360	P	V
802.11n HT20 CH 44 5220MHz		10440	43.1	-30.9	74	56.05	37.47	15.68	66.1	100	360	P	H
		10440	44.37	-29.63	74	57.32	37.47	15.68	66.1	100	360	P	V
802.11n HT20 CH 48 5240MHz		10480	43.56	-30.44	74	56.41	37.52	15.7	66.07	100	360	P	H
		10480	46.21	-27.79	74	59.06	37.52	15.7	66.07	100	360	P	V
Remark	3. No other spurious found. 4. All results are PASS against Peak and Average limit line.												



Band 1 5150~5250MHz
WIFI 802.11n HT40 (Band Edge @ 3m)

WIFI Ant. 1+2+3	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT40 CH 38 5190MHz		5104.32	49.38	-24.62	74	42.9	31.22	11.82	36.56	100	157	P	H
		5149.9	41.27	-12.73	54	34.75	31.17	11.88	36.53	100	157	A	H
	*	5182	104.06	-	-	97.51	31.14	11.93	36.52	100	157	P	H
	*	5182	97.75	-	-	91.2	31.14	11.93	36.52	100	157	A	H
		5354.82	48.86	-25.14	74	42.18	30.98	12.13	36.43	100	157	P	H
		5383.98	39.66	-14.34	54	32.97	30.94	12.17	36.42	100	157	A	H
		5118.4	49.86	-24.14	74	43.37	31.2	11.84	36.55	340	243	P	V
		5120.16	41.55	-12.45	54	35.06	31.2	11.84	36.55	340	243	A	V
	*	5198	103.92	-	-	97.36	31.12	11.95	36.51	340	243	P	V
	*	5198	96.7	-	-	90.14	31.12	11.95	36.51	340	243	A	V
		5384.7	47.77	-26.23	74	41.08	30.94	12.17	36.42	340	243	P	V
		5353.92	38.97	-15.03	54	32.29	30.98	12.13	36.43	340	243	A	V
802.11n HT40 CH 46 5230MHz		5120.16	50.32	-23.68	74	43.83	31.2	11.84	36.55	100	104	P	H
		5120	43.74	-10.26	54	37.25	31.2	11.84	36.55	100	104	A	H
	*	5234	104.34	-	-	97.75	31.09	11.99	36.49	100	104	P	H
	*	5234	97.38	-	-	90.79	31.09	11.99	36.49	100	104	A	H
		5390.1	48.61	-25.39	74	41.92	30.94	12.17	36.42	100	104	P	H
		5377.86	39.7	-14.3	54	33.01	30.94	12.17	36.42	100	104	A	H
		5137.6	49.68	-24.32	74	43.17	31.19	11.86	36.54	326	268	P	V
		5120	40.3	-13.7	54	33.81	31.2	11.84	36.55	326	268	A	V
	*	5222	103.95	-	-	97.37	31.11	11.97	36.5	326	268	P	V
	*	5222	96.09	-	-	89.51	31.11	11.97	36.5	326	268	A	V
		5378.58	48.2	-25.8	74	41.51	30.94	12.17	36.42	326	268	P	V
		5350.86	39.2	-14.8	54	32.52	30.98	12.13	36.43	326	268	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band 1 5150~5250MHz
WIFI 802.11n HT40 (Harmonic @ 3m)

WIFI Ant. 1+2+3	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT40 CH 38 5190MHz		10380	42.07	-31.93	74	55.14	37.41	15.66	66.14	100	360	P	H
		10380	43.05	-30.95	74	56.12	37.41	15.66	66.14	100	360	P	V
802.11n HT40 CH 46 5230MHz		10460	43.37	-30.63	74	56.28	37.49	15.69	66.09	100	360	P	H
		10460	43.78	-30.22	74	56.69	37.49	15.69	66.09	100	360	P	V
Remark	3. No other spurious found. 4. All results are PASS against Peak and Average limit line.												



Band 1 5150~5250MHz
WIFI 802.11ac VHT80 (Band Edge @ 3m)

WIFI Ant. 1+2+3	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11ac VHT80 CH 42 5210MHz		5142.72	51.95	-22.05	74	45.43	31.17	11.88	36.53	100	154	P	H
		5144	43.92	-10.08	54	37.4	31.17	11.88	36.53	100	154	A	H
	*	5224	102.38	-	-	95.8	31.11	11.97	36.5	100	154	P	H
	*	5224	94.99	-	-	88.41	31.11	11.97	36.5	100	154	A	H
		5391.36	49.83	-24.17	74	43.14	30.94	12.17	36.42	100	154	P	H
		5351.58	40.42	-13.58	54	33.74	30.98	12.13	36.43	100	154	A	H
		5130.24	52.58	-21.42	74	46.07	31.19	11.86	36.54	361	265	P	V
		5141.12	43.16	-10.84	54	36.64	31.17	11.88	36.53	361	265	A	V
	*	5240	99.73	-	-	93.14	31.09	11.99	36.49	361	265	P	V
	*	5240	92.53	-	-	85.94	31.09	11.99	36.49	361	265	A	V
		5366.34	47.94	-26.06	74	41.25	30.96	12.15	36.42	361	265	P	V
		5350.5	39.53	-14.47	54	32.85	30.98	12.13	36.43	361	265	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												


Band 1 5150~5250MHz
WIFI 802.11ac VHT80 (Harmonic @ 3m)

WIFI Ant. 1+2+3	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11ac		10420	42.6	-31.4	74	55.6	37.45	15.67	66.12	100	360	P	H
VHT80													
CH 42		10420	42.19	-31.81	74	55.19	37.45	15.67	66.12	100	360	P	V
5210MHz													
Remark	3. No other spurious found. 4. All results are PASS against Peak and Average limit line.												



Emission below 1GHz

WIFI 802.11ac VHT80 (LF @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1+2+3		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11ac VHT80 LF		35.82	30.71	-9.29	40	37.28	24.84	0.87	32.28	-	-	P	H
		40.67	31.79	-8.21	40	41.39	21.65	0.96	32.21	100	31	P	H
		118.27	27.02	-16.48	43.5	39.2	18.53	1.56	32.27	-	-	P	H
		216.24	23.41	-22.59	46	37.23	16.23	2.16	32.21	-	-	P	H
		465.53	29.25	-16.75	46	33.13	24.81	3.24	31.93	-	-	P	H
		794.36	33.28	-12.72	46	32.78	27.83	4.26	31.59	-	-	P	H
		37.76	36.96	-3.04	40	44.79	23.52	0.9	32.25	100	98	QP	V
		66.86	27.99	-12.01	40	45.56	13.46	1.2	32.23	-	-	P	V
		76.56	26.68	-13.32	40	42.53	15.1	1.28	32.23	-	-	P	V
		323.91	30.14	-15.86	46	39.21	20.13	2.88	32.08	-	-	P	V
		456.8	28.02	-17.98	46	31.55	25.2	3.21	31.94	-	-	P	V
		889.42	32.44	-13.56	46	30.78	28.6	4.53	31.47	-	-	P	V
Remark	1. No other spurious found.												
	2. All results are PASS against limit line.												



Band 1 5150~5250MHz

Note symbol

*	Fundamental Frequency which can be ignored. However, the level of any unwanted emissions shall not exceed the level of the fundamental frequency.
!	Test result is over limit line.
P/A	Peak or Average
H/V	H orizontal or V ertical



A calculation example for radiated spurious emission is shown as below:

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11b		2390	55.45	-18.55	74	54.51	32.22	4.58	35.86	103	308	P	H
CH 01													
2412MHz		2390	43.54	-10.46	54	42.6	32.22	4.58	35.86	103	308	A	H

1. Level(dBμV/m) =

Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

2. Over Limit(dB) = Level(dBμV/m) – Limit Line(dBμV/m)

For Peak Limit @ 2390MHz:

1. Level(dBμV/m)

= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 54.51(dBμV) – 35.86 (dB)

= 55.45 (dBμV/m)

2. Over Limit(dB)

= Level(dBμV/m) – Limit Line(dBμV/m)

= 55.45(dBμV/m) – 74(dBμV/m)

= -18.55(dB)

For Average Limit @ 2390MHz:

1. Level(dBμV/m)

= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 42.6(dBμV) – 35.86 (dB)

= 43.54 (dBμV/m)

2. Over Limit(dB)

= Level(dBμV/m) – Limit Line(dBμV/m)

= 43.54(dBμV/m) – 54(dBμV/m)


= -10.46(dB)

Both peak and average measured complies with the limit line, so test result is “PASS”.

Appendix C. Duty Cycle Plots


Antenna	Band	Duty Cycle(%)	T(ms)	1/T(kHz)	VBW Setting
1	802.11 a	96.94	2.065	0.484	1kHz
2	802.11 a	96.94	2.065	0.484	1kHz
3	802.11 a	96.94	2.065	0.484	1kHz
1+2+3	802.11n HT20	98.71	-	-	10Hz
1+2+3	802.11n HT40	97.67	2.428	0.412	1kHz
1+2+3	802.11ac VHT80	94.61	1.145	0.873	1kHz

802.11a Ant.1






802.11a Ant.2






802.11a Ant.3






802.11n20 Ant.1+2+3





802.11n40 Ant.1+2+3





802.11acVHT80 Ant.1+2+3

