



RF TEST REPORT

Applicant ZTE Corporation
FCC ID SRQ-VFD513
Brand ZTE
Product LTE/WCDMA/GSM(GPRS)
Multi-Mode Digital Mobile Phone
Model VFD 513
Report No. RXC1703-0089RF02
Issue Date June 2, 2017

TA Technology (Shanghai) Co., Ltd. tested the above equipment in accordance with the requirements in **FCC CFR47 Part 2 (2017)/ FCC CFR 47 Part 22H (2017)**. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

Performed by: Xianqing Li

Approved by: Kai Xu

TA Technology (Shanghai) Co., Ltd.

No.145, Jintang Rd, Tangzhen Industry Park, Pudong Shanghai, China

TEL: +86-021-50791141/2/3

FAX: +86-021-50791141/2/3-8000



TABLE OF CONTENT

1. Test Laboratory	4
1.1. Notes of the Test Report	4
1.2. Test facility	4
1.3. Testing Location	5
2. General Description of Equipment under Test	6
3. Applied Standards	8
4. Test Configuration	9
5. Test Case Results	11
5.1. RF Power Output	11
5.2. Effective Radiated Power	15
5.3. Occupied Bandwidth	21
5.4. Band Edge Compliance	30
5.5. Peak-to-Average Power Ratio (PAPR)	38
5.6. Frequency Stability	41
5.7. Spurious Emissions at Antenna Terminals	45
5.8. Radiates Spurious Emission	51
6. Main Test Instruments	63
ANNEX A: EUT Appearance and Test Setup	64
A.1 EUT Appearance	64
A.2 Test Setup	66

Summary of measurement results

No.	Test Type	Clause in FCC rules	Verdict
1	RF power output	2.1046	PASS
2	Effective Radiated Power	22.913(a)(2)	PASS
3	Occupied Bandwidth	2.1049	PASS
4	Band Edge Compliance	2.1051 / 22.917(a)	PASS
5	Frequency Stability	2.1055 / 22.355	PASS
6	Spurious Emissions at Antenna Terminals	2.1051 / 22.917(a)	PASS
7	Radiates Spurious Emission	2.1053 / 22.917 (a)	PASS
8	Peak-to-Average Power Ratio	22.913(d)/KDB971168 D01(5.7)	PASS
Date of Testing: March 30, 2017~ May 10, 2017			
Note: PASS: The EUT complies with the essential requirements in the standard. FAIL: The EUT does not comply with the essential requirements in the standard.			



1. Test Laboratory

1.1. Notes of the Test Report

This report shall not be reproduced in full or partial, without the written approval of **TA technology (shanghai) co., Ltd.** The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein .Measurement Uncertainties were not taken into account and are published for informational purposes only. This report is written to support regulatory compliance of the applicable standards stated above. This report must not be used by the client to claim product certification, approval, or endorsement by any government agencies.

1.2. Test facility

CNAS (accreditation number: L2264)

TA Technology (Shanghai) Co., Ltd. has obtained the accreditation of China National Accreditation Service for Conformity Assessment (CNAS).

FCC (recognition number is 428261)

TA Technology (Shanghai) Co., Ltd. has been listed on the US Federal Communications Commission list of test facilities recognized to perform electromagnetic emissions measurements.

IC (recognition number is 8510A)

TA Technology (Shanghai) Co., Ltd. has been listed by industry Canada to perform electromagnetic emission measurement.

VCCI (recognition number is C-4595, T-2154, R-4113, G-10766)

TA Technology (Shanghai) Co., Ltd. has been listed by industry Japan to perform electromagnetic emission measurement.

A2LA (Certificate Number: 3857.01)

TA Technology (Shanghai) Co., Ltd. has been listed by American Association for Laboratory Accreditation to perform electromagnetic emission measurement.



1.3. Testing Location

Company: TA Technology (Shanghai) Co., Ltd.
Address: No.145, Jintang Rd, Tangzhen Industry Park, Pudong
City: Shanghai
Post code: 201201
Country: P. R. China
Contact: Xu Kai
Telephone: +86-021-50791141/2/3
Fax: +86-021-50791141/2/3-8000
Website: <http://www.ta-shanghai.com>
E-mail: xukai@ta-shanghai.com

2. General Description of Equipment under Test

Client Information

Applicant	ZTE Corporation
Applicant address	ZTE Plaza, Keji Road South, Hi-Tech Industrial Park, Nanshan District, Shenzhen, Guangdong, 518057, P.R. China
Manufacturer	ZTE Corporation
Manufacturer address	ZTE Plaza, Keji Road South, Hi-Tech Industrial Park, Nanshan District, Shenzhen, Guangdong, 518057, P.R. China

General Information

EUT Description			
Model:	VFD 513		
Product IMEI:	357850080011544		
Hardware Version	VFD 513 MP		
Software Version	VFD-513_ATPB03		
Power Supply	Battery/AC adapter		
Antenna Type	Internal Antenna		
Test Mode(s)	GSM 850; WCDMA Band V; LTE Band 5		
Test Modulation	(GSM)GMSK,8PSK; (WCDMA)QPSK; (LTE)QPSK 16QAM;		
GPRS Multislot Class	33		
EGPRS Multislot Class	33		
HSDPA UE Category	24		
HSUPA UE Category	6		
Maximum E.R.P.	GSM 850:	26.59dBm	
	WCDMA Band V:	18.67dBm	
	LTE Band 5:	18.90dBm	
Rated Power Supply Voltage	3.8V		
Extreme Voltage	Minimum: 3.6V Maximum: 4.35V		
Extreme Temperature	Lowest: -10°C Highest: +55°C		
Operating Frequency Range(s)	Band	Tx (MHz)	Rx (MHz)
	GSM850	824 ~ 849	869 ~ 894
	WCDMA Band V	824 ~ 849	869 ~ 894
	LTE Band 5	824 ~ 849	869 ~ 894
EUT Accessory			
Adapter (Note 3)	Manufacturer: DOKOCOM Model: STC-A51-I Input power:100-240 V ~ 50/60Hz 250mA		
Battery	Manufacturer: BYD Model: Li3822T43P4h736040		



	Power Rating: DC 3.8V, 2200mAh, Li-ion
Earphone	Manufacturer: Shen zhen FDC Electronic Co.,Ltd. Model: DEM-94A
Note: 1.The information of the EUT is declared by the manufacturer. 2. Please refer to the specifications or user manual for details. 3. The EUT don't have standard Adapter. The adapter used for testing in this report is the after-market accessory.	



3. Applied Standards

According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC CFR47 Part 2 (2017)

FCC CFR 47 Part 22H (2017)

ANSI/TIA-603-D (2010)

KDB 971168 D01 Power Meas License Digital Systems v02r02

4. Test Configuration

Radiated measurements are performed by rotating the EUT in three different orthogonal test planes. EUT stand-up position (Z axis), lie-down position (X, Y axis). Receiver antenna polarization (horizontal and vertical), the worst emission was found in position (Z axis, vertical polarization) and the worst case was recorded.

All mode and data rates and positions were investigated. Subsequently, only the worst case emissions are reported.

The following testing in GSMWCDMA is set based on the maximum RF Output Power.

Test modes are chosen to be reported as the worst case configuration below:

	Test items	Modes/Modulation	
		GSM 850	WCDMA Band V
Conducted Test cases	RF power output	GSM GPRS(1Tx slot) EGPRS(1Tx slot)	RMC HSDPA/HSUPA/ DC-HSDPA
	Occupied Bandwidth	GSM GPRS(1Tx slot) EGPRS(1Tx slot)	RMC
	Band Edge Compliance	GSM GPRS(1Tx slot) EGPRS(1Tx slot)	RMC
	Peak-to-Average Power Ratio	GSM GPRS(1Tx slot) EGPRS(1Tx slot)	RMC
	Frequency Stability	GSM GPRS(1Tx slot) EGPRS(1Tx slot)	RMC
	Spurious Emissions at Antenna Terminals	GSM	RMC
Radiated Test cases	Effective Radiated Power	GSM GPRS(1Tx slot) EGPRS(1Tx slot)	RMC
	Radiates Spurious Emission	GSM	RMC



Test modes are chosen as the worst case configuration below for LTE Band 5.

Test items	Bandwidth (MHz)				Modulation		RB			Test Channel		
	1.4	3	5	10	QPSK	16QAM	1	50%	100%	L	M	H
RF power output	O	O	O	O	O	O	O	O	O	O	O	O
Effective Isotropic Radiated power	O	O	O	O	O	O	-	-	O	O	O	O
Occupied Bandwidth	O	O	O	O	O	O	-	-	O	O	O	O
Band Edge Compliance	O	O	O	O	O	O	O	-	O	O	-	O
Peak-to-Average Power Ratio	O	O	O	O	O	O	-	-	O	O	O	O
Frequency Stability	O	O	O	O	O	O	-	-	O	-	O	-
Spurious Emissions at Antenna Terminals	O	O	O	O	O	-	O	-	-	O	O	O
Radiates Spurious Emission	O	O	O	O	O	-	O	-	-	O	O	O
Note	1. The mark "O" means that this configuration is chosen for testing. 2. The mark "-" means that this configuration is not testing.											

5. Test Case Results

5.1. RF Power Output


Ambient condition

Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa

Methods of Measurement

During the process of the testing, The EUT is controlled by the Base Station Simulator to ensure max power transmission and proper modulation.

Test Setup



The loss between RF output port of the EUT and the input port of the tester has been taken into consideration.

Limits

No specific RF power output requirements in part 2.1046.

Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor $k = 2$, $U = 0.4$ dB.

Test Results

GSM 850		Conducted Power(dBm)		
		Channel 128	Channel 190	Channel 251
		824.2 (MHz)	836.6 (MHz)	848.8 (MHz)
GSM	Results	33.15	33.21	33.17
GPRS (GMSK)	1TXslot	33.06	33.16	33.00
	2TXslots	30.91	30.97	30.72
	3TXslots	28.78	28.67	28.86
	4TXslots	26.93	26.88	27.00
EGPRS (8PSK)	1TXslot	26.60	26.33	26.67
	2TXslots	24.04	23.95	24.05
	3TXslots	22.13	22.04	22.18
	4TXslots	20.83	20.80	20.82

WCDMA Band V		Conducted Power(dBm)		
		Channel 4132	Channel 4183	Channel 4233
		826.4(MHz)	836.6(MHz)	846.6(MHz)
RMC		22.97	22.95	23.04
HSDPA	Sub - Test 1	22.87	22.78	22.88
	Sub - Test 2	22.81	22.79	22.87
	Sub - Test 3	22.30	22.39	22.45
	Sub - Test 4	22.31	22.38	22.47
HSUPA	Sub - Test 1	22.80	22.87	22.96
	Sub - Test 2	21.05	21.03	21.12
	Sub - Test 3	21.87	21.85	21.94
	Sub - Test 4	21.06	21.04	21.13
	Sub - Test 5	22.85	22.83	22.92
DC-HSDPA	Sub - Test 1	22.84	22.82	22.91
	Sub - Test 2	22.93	22.80	22.90
	Sub - Test 3	22.42	22.29	22.39
	Sub - Test 4	22.41	22.28	22.38



LTE FDD Band 5				Conducted Power(dBm)		
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency (MHz)		
				20407/824.7	20525/836.5	20643/848.3
1.4MHz	QPSK	1	0	23.58	23.64	23.73
		1	2	23.76	23.56	23.75
		1	5	23.66	23.55	23.68
		3	0	23.47	23.61	23.61
		3	2	23.50	23.45	23.59
		3	3	23.50	23.51	23.61
		6	0	22.55	22.57	22.73
	16QAM	1	0	22.80	22.81	22.87
		1	2	22.74	22.76	22.76
		1	5	22.75	22.77	22.65
		3	0	22.35	22.43	22.29
		3	2	22.35	22.42	22.61
		3	3	22.45	22.53	22.39
		6	0	21.61	21.66	21.54
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency (MHz)		
				20415/825.5	20525/836.5	20635/847.5
3MHz	QPSK	1	0	23.60	23.68	23.76
		1	7	23.79	23.61	23.79
		1	14	23.69	23.60	23.72
		8	0	22.57	22.73	22.74
		8	4	22.62	22.55	22.71
		8	7	22.60	22.62	22.71
		15	0	22.58	22.61	22.76
	16QAM	1	0	22.83	22.83	22.90
		1	7	22.77	22.81	22.80
		1	14	22.77	22.81	22.68
		8	0	21.46	21.56	21.41
		8	4	21.46	21.55	21.73
		8	7	21.55	21.65	21.52
		15	0	21.64	21.70	21.57
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency (MHz)		
				20425/826.5	20525/836.5	20625/846.5
5MHz	QPSK	1	0	23.57	23.66	23.72
		1	13	23.77	23.57	23.76
		1	24	23.66	23.55	23.68
		12	0	22.54	22.68	22.70
		12	6	22.60	22.51	22.66
		12	13	22.58	22.60	22.67
		25	0	22.56	22.60	22.74



	16QAM	1	0	22.80	22.79	22.87
		1	13	22.74	22.79	22.77
		1	24	22.74	22.79	22.64
		12	0	21.44	21.52	21.38
		12	6	21.43	21.50	21.69
		12	13	21.52	21.60	21.48
		25	0	21.62	21.66	21.52
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency (MHz)		
				20450/829	20525/836.5	20600/844
10MHz	QPSK	1	0	23.55	23.59	23.70
		1	25	23.77	23.57	23.75
		1	49	23.63	23.53	23.64
		25	0	22.52	22.64	22.67
		25	13	22.58	22.47	22.63
		25	25	22.54	22.56	22.64
		50	0	22.59	22.53	22.69
	16QAM	1	0	22.75	22.76	22.82
		1	25	22.71	22.78	22.74
		1	49	22.72	22.74	22.62
		25	0	21.41	21.51	21.36
		25	13	21.39	21.47	21.65
		25	25	21.50	21.56	21.45
		50	0	21.60	21.62	21.49

5.2. Effective Radiated Power

Ambient condition

Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa

Methods of Measurement


1. The testing follows FCC KDB 971168 v02r02 Section 5.8 and ANSI / TIA-603-D-2010 Section 2.2.12.
2. Above 30MHz: The EUT is placed on a turntable 0.8 meters above the ground in the chamber, 3 meter away from the antenna. The maximal emission value is acquired by adjusting the antenna height, polarisation and turntable azimuth. Normally, the height range of antenna is 1 m to 4 m, the azimuth range of turntable is 0° to 360°, and the receive antenna has two polarizations Vertical (V) and Horizontal (H). Above 1GHz: (Note: the FCC's permission to use 1.5m as an alternative per TCBC Conf call of Dec. 2, 2014.) The EUT is placed on a turntable 1.5 meters above the ground in the chamber, 3 meter away from the antenna. The maximal emission value is acquired by adjusting the antenna height, polarisation and turntable azimuth. Normally, the height range of antenna is 1 m to 4 m, the azimuth range of turntable is 0° to 360°, and the receive antenna has two polarizations Vertical (V) and Horizontal (H).
3. A log-periodic antenna or double-ridged waveguide horn antenna shall be substituted in place of the EUT. The log-periodic antenna will be driven by a signal generator and the level will be adjusted till the same power value on the spectrum analyzer or receiver. The level of the spurious emissions can be calculated through the level of the signal generator, cable loss, the gain of the substitution antenna and the reading of the spectrum analyzer or receiver.
4. The EUT is then put into continuously transmitting mode at its maximum power level during the test. Set Test Receiver or Spectrum RBW=1MHz, VBW=3MHz for above 1GHz and RBW=100kHz, VBW=300kHz for 30MHz to 1GHz, And the maximum value of the receiver should be recorded as (Pr).
5. The EUT shall be replaced by a substitution antenna. In the chamber, an substitution antenna for the frequency band of interest is placed at the reference point of the chamber. An RF Signal source for the frequency band of interest is connected to the substitution antenna with a cable that has been constructed to not interfere with the radiation pattern of the antenna. A power (PMea) is applied to the input of the substitution antenna, and adjust the level of the signal generator output until the value of the receiver reach the previously recorded (Pr). The power of signal source (PMea) is recorded. The test should be performed by rotating the test item and adjusting the receiving antenna polarization.
6. A amplifier should be connected to the Signal Source output port. And the cable should be connect between the Amplifier and the Substitution Antenna. The cable loss (Pcl), the Substitution Antenna Gain (Ga) and the Amplifier Gain (PAg) should be recorded after test.
7. The measurement results are obtained as described below:
$$\text{Power(EIRP)} = \text{PMea} - \text{PAg} - \text{Pcl} + \text{Ga}$$

The measurement results are amend as described below:
$$\text{Power(EIRP)} = \text{PMea} - \text{Pcl} + \text{Ga}$$


8. This value is EIRP since the measurement is calibrated using an antenna of known gain (2.15 dBi) and known input power. ERP can be calculated from EIRP by subtracting the gain of the dipole, $ERP = EIRP - 2.15\text{dBi}$.

Test setup

30MHz~~~ 1GHz



Above 1GHz



Note: Area side:2.4mX3.6m

**Limits**

Rule Part 22.913(a) specifies that "Mobile/portable stations are limited to 7 watts ERP".

Limit	$\leq 7\text{ W}$ (38.45 dBm)
-------	-------------------------------

Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor $k = 2$, $U = 1.19\text{ dB}$



Test Results:

Mode	Polarization	Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBd)	ERP (dBm)	Limit (dBm)	Conclusion
GSM 850	H	824.2	-20.77	-45.53	0.00	1.06	25.82	38.45	Pass
	H	836.6	-20.35	-45.38	0.00	1.24	26.27	38.45	Pass
	H	848.8	-20.16	-45.37	0.00	1.38	26.59	38.45	Pass
	V	824.2	-34.43	-45.65	0.00	1.06	12.28	38.45	Pass
	V	836.6	-33.60	-45.46	0.00	1.24	13.10	38.45	Pass
	V	848.8	-32.69	-45.49	0.00	1.38	14.18	38.45	Pass
GPRS 850	H	824.2	-24.45	-45.53	0.00	1.06	22.14	38.45	Pass
	H	836.6	-24.13	-45.38	0.00	1.24	22.49	38.45	Pass
	H	848.8	-23.95	-45.37	0.00	1.38	22.80	38.45	Pass
	V	824.2	-38.35	-45.65	0.00	1.06	8.36	38.45	Pass
	V	836.6	-37.50	-45.46	0.00	1.24	9.20	38.45	Pass
	V	848.8	-36.66	-45.49	0.00	1.38	10.21	38.45	Pass
EGPRS 850	H	824.2	-26.69	-45.53	0.00	1.06	19.90	38.45	Pass
	H	836.6	-25.94	-45.38	0.00	1.24	20.68	38.45	Pass
	H	848.8	-25.75	-45.37	0.00	1.38	21.00	38.45	Pass
	V	824.2	-40.35	-45.65	0.00	1.06	6.36	38.45	Pass
	V	836.6	-39.08	-45.46	0.00	1.24	7.62	38.45	Pass
	V	848.8	-38.28	-45.49	0.00	1.38	8.59	38.45	Pass
WCDMA Band V	H	826.4	-29.59	-45.44	0.00	1.13	16.98	38.45	Pass
	H	836.6	-27.95	-45.38	0.00	1.24	18.67	38.45	Pass
	H	846.6	-28.74	-45.38	0.00	1.35	17.99	38.45	Pass
	V	826.4	-43.48	-45.54	0.00	1.13	3.19	38.45	Pass
	V	836.6	-41.31	-45.46	0.00	1.24	5.39	38.45	Pass
	V	846.6	-41.48	-45.49	0.00	1.35	5.36	38.45	Pass

LTE Band 5									
bandwidth	Polarization	Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBd)	ERP (dBm)	Limit (dBm)	Conclusion
1.4 MHz (QPSK)	H	824.7	-30.04	-47.61	0.00	1.06	18.63	38.45	Pass
	H	836.5	-30.21	-47.75	0.00	1.24	18.78	38.45	Pass
	H	848.3	-31.02	-48.23	0.00	1.38	18.59	38.45	Pass
	V	824.7	-35.88	-47.29	0.00	1.06	12.48	38.45	Pass
	V	836.5	-35.23	-47.15	0.00	1.24	13.16	38.45	Pass
	V	848.3	-35.34	-47.48	0.00	1.38	13.52	38.45	Pass
1.4 MHz (16QAM)	H	824.7	-30.36	-47.61	0.00	1.06	18.31	38.45	Pass
	H	836.5	-30.85	-47.75	0.00	1.24	18.14	38.45	Pass



LTE Band 5									
bandwidth	Polarization	Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBd)	ERP (dBm)	Limit (dBm)	Conclusion
	H	848.3	-31.66	-48.23	0.00	1.38	17.95	38.45	Pass
	V	824.7	-36.52	-47.29	0.00	1.06	11.84	38.45	Pass
	V	836.5	-35.87	-47.15	0.00	1.24	12.52	38.45	Pass
	V	848.3	-35.59	-47.48	0.00	1.38	13.27	38.45	Pass
3 MHz (QPSK)	H	825.5	-30.53	-47.59	0.00	1.06	18.13	38.45	Pass
	H	836.5	-30.52	-47.75	0.00	1.24	18.47	38.45	Pass
	H	847.5	-30.82	-48.18	0.00	1.38	18.74	38.45	Pass
	V	825.5	-35.73	-47.26	0.00	1.06	12.60	38.45	Pass
	V	836.5	-35.06	-47.15	0.00	1.24	13.33	38.45	Pass
	V	847.5	-35.22	-47.44	0.00	1.38	13.61	38.45	Pass
3 MHz (16QAM)	H	825.5	-30.80	-47.59	0.00	1.06	17.86	38.45	Pass
	H	836.5	-30.79	-47.75	0.00	1.24	18.20	38.45	Pass
	H	847.5	-31.04	-48.18	0.00	1.38	18.52	38.45	Pass
	V	825.5	-36.14	-47.26	0.00	1.06	12.19	38.45	Pass
	V	836.5	-35.36	-47.15	0.00	1.24	13.03	38.45	Pass
	V	847.5	-35.61	-47.44	0.00	1.38	13.22	38.45	Pass
5 MHz (QPSK)	H	826.5	-31.25	-47.60	0.00	1.13	17.48	38.45	Pass
	H	836.5	-30.25	-47.75	0.00	1.24	18.74	38.45	Pass
	H	846.5	-31.08	-48.12	0.00	1.38	18.43	38.45	Pass
	V	826.5	-37.13	-47.24	0.00	1.13	11.24	38.45	Pass
	V	836.5	-34.75	-47.15	0.00	1.24	13.64	38.45	Pass
	V	846.5	-35.36	-47.40	0.00	1.38	13.42	38.45	Pass
5 MHz (16QAM)	H	826.5	-31.63	-47.60	0.00	1.13	17.10	38.45	Pass
	H	836.5	-30.80	-47.75	0.00	1.24	18.19	38.45	Pass
	H	846.5	-31.35	-48.12	0.00	1.38	18.16	38.45	Pass
	V	826.5	-37.34	-47.24	0.00	1.13	11.03	38.45	Pass
	V	836.5	-35.11	-47.15	0.00	1.24	13.28	38.45	Pass
	V	846.5	-35.76	-47.40	0.00	1.38	13.02	38.45	Pass
10 MHz (QPSK)	H	829	-31.30	-47.61	0.00	1.13	17.44	38.45	Pass
	H	836.5	-30.09	-47.75	0.00	1.24	18.90	38.45	Pass
	H	844	-30.53	-48.01	0.00	1.33	18.80	38.45	Pass
	V	829	-35.90	-47.19	0.00	1.13	12.42	38.45	Pass
	V	836.5	-34.93	-47.15	0.00	1.24	13.46	38.45	Pass
	V	844	-35.58	-47.29	0.00	1.33	13.03	38.45	Pass
10 MHz (16QAM)	H	829	-31.78	-47.61	0.00	1.13	16.96	38.45	Pass
	H	836.5	-30.46	-47.75	0.00	1.24	18.53	38.45	Pass
	H	844	-30.87	-48.01	0.00	1.33	18.46	38.45	Pass



LTE Band 5									
bandwidth	Polarization	Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBd)	ERP (dBm)	Limit (dBm)	Conclusion
	V	829	-36.18	-47.19	0.00	1.13	12.14	38.45	Pass
	V	836.5	-35.21	-47.15	0.00	1.24	13.18	38.45	Pass
	V	844	-35.97	-47.29	0.00	1.33	12.64	38.45	Pass

5.3. Occupied Bandwidth

Ambient condition

Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa

Method of Measurement

The EUT was connected to Spectrum Analyzer and Base Station Simulator via power Splitter. The occupied bandwidth is measured using spectrum analyzer.

RBW is set to 3kHz, VBW is set to 10kHz for GSM 850,


RBW is set to 51kHz, VBW is set to 160kHz for WCDMA Band V,

RBW is set to 51 kHz, VBW is set to 160 kHz for LTE Band 5 (1.4MHz),

RBW is set to 100 kHz, VBW is set to 300 kHz for LTE Band 5 (3MHz/5MHz/10MHz),

99% power and -26dBc occupied bandwidths are recorded. Spectrum analyzer plots are included on the following pages.

Test Setup



Limits

No specific occupied bandwidth requirements in part 2.1049.

Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor $k = 2$, $U = 624\text{Hz}$.

Test Result

Mode	Channel	Frequency (MHz)	99% Power Bandwidth (MHz)	-26dBc Bandwidth(MHz)
GSM 850 (GSM)	128	824.2	0.244	0.308
	190	836.6	0.246	0.315
	251	848.8	0.244	0.304
GPRS 850 (GMSK)	128	824.2	0.245	0.310
	190	836.6	0.242	0.315
	251	848.8	0.247	0.316
EGPRS 850 (8-PSK)	128	824.2	0.246	0.308
	190	836.6	0.245	0.299
	251	848.8	0.241	0.311
WCDMA Band V (RMC)	4132	826.4	4.145	4.693
	4183	836.6	4.130	4.699
	4233	846.6	4.135	4.666

LTE Band 5						
RB	Modulation	Bandwidth (MHz)	Channel	Frequency (MHz)	99% Power Bandwidth(MHz)	-26dBc Bandwidth(MHz)
100%	QPSK	1.4	20407	824.7	1.1256	1.346
			20525	836.5	1.1254	1.349
			20643	848.3	1.1381	1.341
		3	20415	825.5	2.7545	3.064
			20525	836.5	2.7543	3.088
			20635	847.5	2.7449	3.080
		5	20425	826.5	4.5221	5.046
			20525	836.5	4.5401	5.049
			20625	846.5	4.5131	5.032
		10	20450	829	9.0459	10.07
			20525	836.5	9.0720	10.17
			20600	844	9.0186	10.13
	16QAM	1.4	20407	824.7	1.1319	1.344
			20525	836.5	1.1218	1.327
			20643	848.3	1.1204	1.360



		3	20415	825.5	2.7368	3.064
			20525	836.5	2.7618	3.063
			20635	847.5	2.7569	3.078
		5	20425	826.5	4.5420	5.050
			20525	836.5	4.5240	5.048
			20625	846.5	4.5420	5.053
		10	20450	829	9.0342	10.02
			20525	836.5	9.0483	10.04
			20600	844	9.0269	10.09



GSM 850 CH-Low




GSM 850 GPRS CH-Low



GSM 850 CH-Middle



GSM 850 GPRS CH-Middle




GSM 850 CH-High



GSM 850 GPRS CH-High




GSM 850 EGPRS CH-Low




WCDMA Band V CH-Low



GSM 850 EGPRS CH-Middle



WCDMA Band V CH-Middle



GSM 850 EGPRS CH-High




WCDMA Band V CH-High







LTE Band 5 QPSK 1.4MHz CH-Low




LTE Band 5 QPSK 3MHz CH-Low




LTE Band 5 QPSK 1.4MHz CH-Middle




LTE Band 5 QPSK 3MHz CH-Middle



LTE Band 5 QPSK 1.4MHz CH-High




LTE Band 5 QPSK 3MHz CH-High






LTE Band 5 QPSK 5MHz CH-Low




LTE Band 5 QPSK 10MHz CH-Low




LTE Band 5 QPSK 5MHz CH-Middle




LTE Band 5 QPSK 10MHz CH-Middle



LTE Band 5 QPSK 5MHz CH-High




LTE Band 5 QPSK 10MHz CH-High







LTE Band 5 16QAM 1.4MHz CH-Low




LTE Band 5 16QAM 3MHz CH-Low




LTE Band 5 16QAM 1.4MHz CH-Middle




LTE Band 5 16QAM 3MHz CH-Middle



LTE Band 5 16QAM 1.4MHz CH-High




LTE Band 5 16QAM 3MHz CH-High







LTE Band 5 16QAM 5MHz CH-Low




LTE Band 5 16QAM 10MHz CH-Low




LTE Band 5 16QAM 5MHz CH-Middle




LTE Band 5 16QAM 10MHz CH-Middle



LTE Band 5 16QAM 5MHz CH-High



LTE Band 5 16QAM 10MHz CH-High



5.4. Band Edge Compliance

Ambient condition

Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa

Method of Measurement

The EUT was connected to Spectrum Analyzer and Base Station Simulator via power Splitter. The band edge of the lowest and highest channels were measured. The average detector is used.

RBW is set to 3kHz,VBW is set to 10kHz for GSM 850,

RBW is set to 51kHz,VBW is set to 160kHz for WCDMA Band V,

RBW is set to 15 kHz, VBW is set to 51 kHz for LTE Band 5 (1.4MHz),


RBW is set to 30 kHz, VBW is set to 100 kHz for LTE Band 5 (3MHz),

RBW is set to 51 kHz, VBW is set to 160 kHz for LTE Band 5 (5MHz),

RBW is set to 100 kHz, VBW is set to 300 kHz for LTE Band 5 (10MHz),

Spectrum analyzer plots are included on the following pages.

Test Setup



Limits

Rule Part 22.917(a) specifies that “The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.”

Limit	-13 dBm
-------	---------

Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor $k = 1.96$, $U=0.684$ dB.




Test Result:


GSM 850 CH-Low



GSM 850 CH-High



GSM 850 GPRS CH-Low




GSM 850 GPRS CH-High



GSM 850 EGPRS CH-Low



GSM 850 EGPRS CH-High






WCDMA Band V CH-Low




WCDMA Band V CH-High



LTE Band 5 QPSK 1.4MHz CH-Low 1RB



LTE Band 5 QPSK 1.4MHz CH-High 1RB



LTE Band 5 QPSK 1.4MHz CH-Low 100%RB




LTE Band 5 QPSK 1.4MHz CH-High 100%RB






LTE Band 5 QPSK 3MHz CH-Low 1RB




LTE Band 5 QPSK 3MHz CH-High 1RB




LTE Band 5 QPSK 3MHz CH-Low 100%RB




LTE Band 5 QPSK 3MHz CH-High 100%RB



LTE Band 5 QPSK 5MHz CH-Low 1RB




LTE Band 5 QPSK 5MHz CH-High 1RB






LTE Band 5 QPSK 5MHz CH-Low 100%RB




LTE Band 5 QPSK 5MHz CH-High 100%RB




LTE Band 5 QPSK 10MHz CH-Low 1RB



LTE Band 5 QPSK 10MHz CH-High 1RB



LTE Band 5 QPSK 10MHz CH-Low 100%RB




LTE Band 5 QPSK 10MHz CH-High 100%RB







LTE Band 5 16QAM 1.4MHz CH-Low 1RB




LTE Band 5 16QAM 1.4MHz CH-High 1RB




LTE Band 5 16QAM 1.4MHz CH-Low 100%RB




LTE Band 5 16QAM 1.4MHz CH-High 100%RB



LTE Band 5 16QAM 3MHz CH-Low 1RB



LTE Band 5 16QAM 3MHz CH-High 1RB






LTE Band 5 16QAM 3MHz CH-Low 100%RB




LTE Band 5 16QAM 3MHz CH-High 100%RB




LTE Band 5 16QAM 5MHz CH-Low 1RB



LTE Band 5 16QAM 5MHz CH-High 1RB



LTE Band 5 16QAM 5MHz CH-Low 100%RB




LTE Band 5 16QAM 5MHz CH-High 100%RB







LTE Band 5 16QAM 10MHz CH-Low 1RB




LTE Band 5 16QAM 10MHz CH-High 1RB



LTE Band 5 16QAM 10MHz CH-Low 100%RB



LTE Band 5 16QAM 10MHz CH-High 100%RB



5.5. Peak-to-Average Power Ratio (PAPR)

Ambient condition


Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa

Methods of Measurement

Measure the total peak power and record as P_{Pk} . And measure the total average power and record as P_{Avg} . Both the peak and average power levels must be expressed in the same logarithmic units (e.g., dBm). Determine the PAPR from:

$$PAPR (dB) = P_{Pk} (dBm) - P_{Avg} (dBm).$$

Test Setup



Limits

According to the Sec. 22.913(d), The peak-to-average ratio (PAR) of the transmission must not exceed 13 dB.

Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor $k = 2$, $U = 0.4$ dB.



Test Results

Mode	Channel	Frequency (MHz)	Peak (dBm)	Avg (dBm)	PAPR (dB)	Conclusion
GSM 850 (GSM)	128	824.2	33.73	33.05	0.68	PASS
	190	836.6	33.68	33.06	0.62	PASS
	251	848.8	33.60	32.91	0.69	PASS
GPRS 850 (GMSK)	128	824.2	27.70	27.04	0.66	PASS
	190	836.6	27.55	26.96	0.59	PASS
	251	848.8	27.71	27.09	0.62	PASS
EGPRS 850 (8-PSK)	128	824.2	21.36	20.94	0.42	PASS
	190	836.6	21.65	20.88	0.77	PASS
	251	848.8	21.46	20.91	0.55	PASS
WCDMA Band V (RMC)	4132	826.4	25.94	22.87	3.07	PASS
	4183	836.6	26.03	22.97	3.06	PASS
	4233	846.6	25.07	22.03	3.04	PASS

LTE Band 5								
Modulation	Bandwidth (MHz)	Channel	Frequency (MHz)	Peak (dBm)	Avg (dBm)	PAPR (dB)	Limit (dB)	Conclusion
QPSK	1.4	20407	824.7	27.81	22.55	5.26	≤13	PASS
		20525	836.5	27.72	22.57	5.15	≤13	PASS
		20643	848.3	28.00	22.73	5.27	≤13	PASS
	3	20415	825.5	27.88	22.58	5.30	≤13	PASS
		20525	836.5	28.30	22.61	5.69	≤13	PASS
		20635	847.5	27.92	22.76	5.16	≤13	PASS
	5	20425	826.5	27.94	22.56	5.38	≤13	PASS
		20525	836.5	27.95	22.60	5.35	≤13	PASS
		20625	846.5	28.01	22.74	5.27	≤13	PASS
	10	20450	829	27.21	22.59	4.62	≤13	PASS
		20525	836.5	27.16	22.53	4.63	≤13	PASS
		20600	844	27.35	22.69	4.66	≤13	PASS
16QAM	1.4	20407	824.7	27.72	21.61	6.11	≤13	PASS
		20525	836.5	27.62	21.66	5.96	≤13	PASS
		20643	848.3	27.54	21.54	6.00	≤13	PASS
	3	20415	825.5	27.78	21.64	6.14	≤13	PASS
		20525	836.5	27.86	21.70	6.16	≤13	PASS
		20635	847.5	27.42	21.57	5.85	≤13	PASS



	5	20425	826.5	27.48	21.62	5.86	≤13	PASS
		20525	836.5	27.78	21.66	6.12	≤13	PASS
		20625	846.5	27.55	21.52	6.03	≤13	PASS
	10	20450	829	27.65	21.60	6.05	≤13	PASS
		20525	836.5	27.72	21.62	6.10	≤13	PASS
		20600	844	27.58	21.49	6.09	≤13	PASS

5.6. Frequency Stability

Ambient condition

Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa

Method of Measurement

1. Frequency Stability (Temperature Variation)

The temperature inside the climate chamber is varied from -30°C to +50°C in 10°C step size,

(1) With all power removed, the temperature was decreased to 0°C and permitted to stabilize for three hours.

(2) Measure the carrier frequency with the test equipment in a “call mode”. These measurements should be made within 1 minute of powering up the mobile station, to prevent significant self warming.

(3) Repeat the above measurements at 10°C increments from -30°C to +50°C. Allow at least 1.5 hours at each temperature, un-powered, before making measurements. Frequency Stability (Voltage Variation)


The frequency stability shall be measured with variation of primary supply voltage as follows:

(1) Vary primary supply voltage from 85 to 115 percent of the nominal value for other than hand carried battery equipment.

(2) For hand carried, battery powered equipment, reduce primary supply voltage to the battery-operating end point which shall be specified by the manufacturer.

This transceiver is specified to operate with an input voltage of between 3.6 V and 4.35 V, with a nominal voltage of 3.8V.

Test setup



Limits

According to the Sec. 22.355, the frequency stability of the carrier shall be accurate to within 2.5 ppm of the received frequency for mobile stations.

Limits	≤ 2.5 ppm
--------	----------------

Measurement Uncertainty

The assessed measurement uncertainty to ensure 99.75% confidence level for the normal distribution is with the coverage factor $k = 3$, $U = 0.01$ ppm.

Test Result

Mode	Test status	Test Results (ppm)			Limit (ppm)	Conclusion
		GSM (GMSK)	GPRS (GMSK)	EGPRS (8PSK)		
GSM 850 Middle Channel	-30°C/Normal Voltage	-0.01300	0.02080	0.01860	2.5	PASS
	-20°C/Normal Voltage	0.01920	0.02180	0.02120	2.5	PASS
	-10°C/Normal Voltage	0.02610	0.01890	0.02210	2.5	PASS
	0°C/Normal Voltage	0.01950	0.02380	0.02100	2.5	PASS
	10°C/Normal Voltage	0.01420	0.02060	0.01880	2.5	PASS
	20°C/Normal Voltage	0.02700	0.02050	0.02370	2.5	PASS
	30°C/Normal Voltage	0.02410	0.02350	0.02130	2.5	PASS
	40°C/Normal Voltage	0.01670	0.01580	0.02530	2.5	PASS
	50°C/Normal Voltage	0.01760	0.02710	0.02220	2.5	PASS
	20°C/Minimum Voltage	-0.00500	0.02240	0.02160	2.5	PASS
	20°C/Maximum Voltage	0.00510	0.01500	0.02020	2.5	PASS
/	/	RMC			/	/
WCDMA Band V Middle Channel	-30°C/Normal Voltage	-0.00149			2.5	PASS
	-20°C/Normal Voltage	-0.00010			2.5	PASS
	-10°C/Normal Voltage	-0.00105			2.5	PASS
	0°C/Normal Voltage	0.00059			2.5	PASS
	10°C/Normal Voltage	0.00051			2.5	PASS
	20°C/Normal Voltage	-0.00010			2.5	PASS
	30°C/Normal Voltage	-0.00066			2.5	PASS
	40°C/Normal Voltage	-0.00006			2.5	PASS
	50°C/Normal Voltage	-0.00058			2.5	PASS
	20°C/Minimum Voltage	0.00004			2.5	PASS
	20°C/Maximum Voltage	-0.00029			2.5	PASS



Bandwidth	Test status	LTE Band 5 Middle Channel Test Results (ppm)			
		QPSK	16QAM	Limit (ppm)	Conclusion
1.4MHz	-30°C/Normal Voltage	0.00171	-0.00255	2.5	PASS
	-20°C/Normal Voltage	0.00017	0.00019	2.5	PASS
	-10°C/Normal Voltage	-0.00328	-0.00172	2.5	PASS
	0°C/Normal Voltage	-0.00126	0.00029	2.5	PASS
	10°C/Normal Voltage	-0.00270	-0.00098	2.5	PASS
	20°C/Normal Voltage	-0.00112	0.00139	2.5	PASS
	30°C/Normal Voltage	-0.00055	-0.00135	2.5	PASS
	40°C/Normal Voltage	-0.00241	0.00001	2.5	PASS
	50°C/Normal Voltage	-0.00157	-0.00209	2.5	PASS
	20°C/Minimum Voltage	-0.00149	0.00096	2.5	PASS
	20°C/Maximum Voltage	0.00117	-0.00130	2.5	PASS
3MHz	-30°C/Normal Voltage	-0.00330	0.00068	2.5	PASS
	-20°C/Normal Voltage	0.00172	0.00134	2.5	PASS
	-10°C/Normal Voltage	-0.00019	0.00169	2.5	PASS
	0°C/Normal Voltage	0.00013	0.00029	2.5	PASS
	10°C/Normal Voltage	-0.00152	-0.00171	2.5	PASS
	20°C/Normal Voltage	-0.00173	-0.00270	2.5	PASS
	30°C/Normal Voltage	-0.00212	-0.00383	2.5	PASS
	40°C/Normal Voltage	0.00056	-0.00259	2.5	PASS
	50°C/Normal Voltage	0.00091	0.00132	2.5	PASS
	20°C/Minimum Voltage	0.00134	-0.00033	2.5	PASS
	20°C/Maximum Voltage	0.00105	0.00082	2.5	PASS
5MHz	-30°C/Normal Voltage	0.00171	0.00086	2.5	PASS
	-20°C/Normal Voltage	0.00253	0.00216	2.5	PASS
	-10°C/Normal Voltage	0.00087	0.00149	2.5	PASS
	0°C/Normal Voltage	0.00135	0.00086	2.5	PASS
	10°C/Normal Voltage	-0.00148	-0.00262	2.5	PASS
	20°C/Normal Voltage	0.00152	-0.00224	2.5	PASS
	30°C/Normal Voltage	0.00013	-0.00170	2.5	PASS
	40°C/Normal Voltage	-0.00043	0.00209	2.5	PASS
	50°C/Normal Voltage	-0.00055	-0.00147	2.5	PASS
	20°C/Minimum Voltage	0.00186	-0.00241	2.5	PASS
	20°C/Maximum Voltage	-0.00094	-0.00030	2.5	PASS
10MHz	-30°C/Normal Voltage	-0.00136	0.00082	2.5	PASS
	-20°C/Normal Voltage	0.00072	0.00077	2.5	PASS
	-10°C/Normal Voltage	0.00136	-0.00056	2.5	PASS
	0°C/Normal Voltage	-0.00123	0.00195	2.5	PASS



	10°C/Normal Voltage	-0.00086	0.00096	2.5	PASS
	20°C/Normal Voltage	-0.00251	-0.00247	2.5	PASS
	30°C/Normal Voltage	-0.00041	-0.00231	2.5	PASS
	40°C/Normal Voltage	-0.00236	-0.00128	2.5	PASS
	50°C/Normal Voltage	0.00121	-0.00072	2.5	PASS
	20°C/Minimum Voltage	-0.00012	0.00182	2.5	PASS
	20°C/Maximum Voltage	-0.00146	-0.00104	2.5	PASS

5.7. Spurious Emissions at Antenna Terminals

Ambient condition


Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa

Method of Measurement

The EUT was connected to Spectrum Analyzer and Base Station Simulator via power Splitter. The measurement is carried out using a spectrum analyzer. The spectrum analyzer scans from 9kHz to the 10th harmonic of the carrier.

The peak detector is used. RBW are set to 100 kHz and VBW are set to 300 kHz for below 1G, RBW are set to 1MHz and VBW are set to 3MHz for above 1G, Sweep is set to ATUO.

Test setup



Limits

Rule Part 22.917(a) specifies that “The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log (P)$ dB.”

Limit	-13 dBm
-------	---------

Measurement Uncertainty

The assessed measurement uncertainty to ensure 99.75% confidence level for the normal distribution is with the coverage factor $k = 1.96$.

Frequency	Uncertainty
100kHz-2GHz	0.684 dB
2GHz-12.75GHz	1.407 dB


Test Result

Sweep from 9 kHz to 30MHz, and the emissions more than 20 dB below the permissible value are not reported.


If disturbances were found more than 20dB below limit line, the mark is not required for the EUT.

The signal beyond the limit is carrier.


GSM 850 CH-Low 30MHz~9GHz




WCDMA Band V CH-Low 30MHz~9GHz




GSM 850 CH-Middle 30MHz~9GHz




WCDMA Band V CH-Middle 30MHz~9GHz



GSM 850 CH-High 30MHz~9GHz




WCDMA Band V CH-High 30MHz~9GHz







LTE Band 5 1.4MHz CH-Low 30MHz~1.5GHz




LTE Band 5 1.4MHz CH-Low 1.5GHz~9GHz




LTE Band 5 1.4MHz CH-Middle 30MHz~1.5GHz




LTE Band 5 1.4MHz CH-Middle 1.5GHz~9GHz



LTE Band 5 1.4MHz CH-High 30MHz~1.5GHz




LTE Band 5 1.4MHz CH-High 1.5GHz~9GHz







LTE Band 5 3MHz CH-Low 30MHz~1.5GHz




LTE Band 5 3MHz CH-Low 1.5GHz~9GHz




LTE Band 5 3MHz CH-Middle 30MHz~1.5GHz




LTE Band 5 3MHz CH-Middle 1.5GHz~9GHz



LTE Band 5 3MHz CH-High 30MHz~1.5GHz




LTE Band 5 3MHz CH-High 1.5GHz~9GHz







LTE Band 5 5MHz CH-Low 30MHz~1.5GHz




LTE Band 5 5MHz CH-Low 1.5GHz~9GHz




LTE Band 5 5MHz CH-Middle 30MHz~1.5GHz




LTE Band 5 5MHz CH-Middle 1.5GHz~9GHz



LTE Band 5 5MHz CH-High 30MHz~1.5GHz




LTE Band 5 5MHz CH-High 1.5GHz~9GHz







LTE Band 5 10MHz CH-Low 30MHz~1.5GHz




LTE Band 5 10MHz CH-Low 1.5GHz~9GHz




LTE Band 5 10MHz CH-Middle 30MHz~1.5GHz




LTE Band 5 10MHz CH-Middle 1.5GHz~9GHz



LTE Band 5 10MHz CH-High 30MHz~1.5GHz



LTE Band 5 10MHz CH-High 1.5GHz~9GHz



5.8. Radiates Spurious Emission

Ambient condition

Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa

Method of Measurement


1. The testing follows FCC KDB 971168 v02r02 Section 5.8 and ANSI / TIA-603-D-2010 Section 2.2.12.
2. Above 30MHz: The EUT is placed on a turntable 0.8 meters above the ground in the chamber, 3 meter away from the antenna. The maximal emission value is acquired by adjusting the antenna height, polarisation and turntable azimuth. Normally, the height range of antenna is 1 m to 4 m, the azimuth range of turntable is 0° to 360°, and the receive antenna has two polarizations Vertical (V) and Horizontal (H). Above 1GHz: (Note: the FCC's permission to use 1.5m as an alternative per TCBC Conf call of Dec. 2, 2014.) The EUT is placed on a turntable 1.5 meters above the ground in the chamber, 3 meter away from the antenna. The maximal emission value is acquired by adjusting the antenna height, polarisation and turntable azimuth. Normally, the height range of antenna is 1 m to 4 m, the azimuth range of turntable is 0° to 360°, and the receive antenna has two polarizations Vertical (V) and Horizontal (H).
3. A log-periodic antenna or double-ridged waveguide horn antenna shall be substituted in place of the EUT. The log-periodic antenna will be driven by a signal generator and the level will be adjusted till the same power value on the spectrum analyzer or receiver. The level of the spurious emissions can be calculated through the level of the signal generator, cable loss, the gain of the substitution antenna and the reading of the spectrum analyzer or receiver.
4. The EUT is then put into continuously transmitting mode at its maximum power level during the test. Set Test Receiver or Spectrum RBW=1MHz, VBW=3MHz for above 1GHz and RBW=100kHz, VBW=300kHz for 30MHz to 1GHz, And the maximum value of the receiver should be recorded as (Pr).
5. The EUT shall be replaced by a substitution antenna. In the chamber, an substitution antenna for the frequency band of interest is placed at the reference point of the chamber. An RF Signal source for the frequency band of interest is connected to the substitution antenna with a cable that has been constructed to not interfere with the radiation pattern of the antenna. A power (PMea) is applied to the input of the substitution antenna, and adjust the level of the signal generator output until the value of the receiver reach the previously recorded (Pr). The power of signal source (PMea) is recorded. The test should be performed by rotating the test item and adjusting the receiving antenna polarization.
6. A amplifier should be connected to the Signal Source output port. And the cable should be connect between the Amplifier and the Substitution Antenna. The cable loss (Pcl), the Substitution Antenna Gain (Ga) and the Amplifier Gain (PAg) should be recorded after test.
7. The measurement results are obtained as described below:
$$\text{Power(EIRP)} = \text{PMea} - \text{PAg} - \text{Pcl} + \text{Ga}$$

The measurement results are amend as described below:
$$\text{Power(EIRP)} = \text{PMea} - \text{Pcl} + \text{Ga}$$


8. This value is EIRP since the measurement is calibrated using an antenna of known gain (2.15 dBi) and known input power. ERP can be calculated from EIRP by subtracting the gain of the dipole, $ERP = EIRP - 2.15\text{dBi}$.

Test setup

30MHz~~~ 1GHz



Above 1GHz



Note: Area side:2.4mX3.6m

Limits

Rule Part 22.917(a) specifies that “The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log (P)$ dB.”

Limit	-13 dBm
-------	---------

Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor $k = 1.96$, $U = 3.55$ dB.

**Test Result**

GSM 850 CH-Low

Harmonic	Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	Antenna Polarization	ERP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	1648	-51.60	2	10.15	Vertical	-45.6	-13.0	32.6	315
3	2473	-53.09	2.51	11.35	Vertical	-46.4	-13.0	33.4	270
4	3297	-54.60	4.2	10.85	Vertical	-50.1	-13.0	37.1	180
5	4121	-53.00	5.2	11.35	Vertical	-49.0	-13.0	36.0	315
6	4945	-51.50	5.5	11.95	Vertical	-47.2	-13.0	34.2	270
7	5769	-53.20	5.7	13.55	Vertical	-47.5	-13.0	34.5	45
8	6594	-50.20	6.3	13.75	Vertical	-44.9	-13.0	31.9	225
9	7418	-45.50	6.8	13.85	Vertical	-40.6	-13.0	27.6	270
10	8242	-45.80	6.9	14.25	Vertical	-40.6	-13.0	27.6	90

Note: 1.The other Spurious RF Radiated emissions level is no more than noise floor.

2.The worst emission was found in the antenna is vertical position.

GSM 850 CH-Middle

Harmonic	Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	Antenna Polarization	ERP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	1673	-57.00	2	10.75	Vertical	-50.4	-13.0	37.4	45
3	2498	-59.19	2.51	11.05	Vertical	-52.8	-13.0	39.8	225
4	3346	-55.40	4.2	11.15	Vertical	-50.6	-13.0	37.6	45
5	4183	-52.40	5.2	11.15	Vertical	-48.6	-13.0	35.6	90
6	5020	-52.00	5.5	11.95	Vertical	-47.7	-13.0	34.7	45
7	5856	-51.60	5.7	13.55	Vertical	-45.9	-13.0	32.9	0
8	6693	-49.60	6.3	13.75	Vertical	-44.3	-13.0	31.3	135
9	7529	-45.60	6.8	13.85	Vertical	-40.7	-13.0	27.7	180
10	8366	-46.40	6.9	14.25	Vertical	-41.2	-13.0	28.2	315

Note: 1.The other Spurious RF Radiated emissions level is no more than noise floor.

2.The worst emission was found in the antenna is vertical position.



GSM 850 CH-High

Harmonic	Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	Antenna Polarization	ERP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	1698	-60.80	2	10.15	Vertical	-54.8	-13.0	41.8	0
3	2546	-58.89	2.51	11.05	Vertical	-52.5	-13.0	39.5	135
4	3395	-54.00	4.2	11.15	Vertical	-49.2	-13.0	36.2	270
5	4244	-52.00	5.2	11.15	Vertical	-48.2	-13.0	35.2	315
6	5093	-50.50	5.5	11.95	Vertical	-46.2	-13.0	33.2	270
7	5942	-50.70	5.7	13.55	Vertical	-45.0	-13.0	32.0	45
8	6790	-47.00	6.3	13.75	Vertical	-41.7	-13.0	28.7	225
9	7639	-46.80	6.8	13.85	Vertical	-41.9	-13.0	28.9	270
10	8488	-45.00	6.9	14.25	Vertical	-39.8	-13.0	26.8	90

Note: 1.The other Spurious RF Radiated emissions level is no more than noise floor.

WCDMA Band V CH-Low

Harmonic	Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	Antenna Polarization	ERP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	1653	-61.70	2	10.15	Vertical	-55.7	-13.0	42.7	135
3	2479	-58.79	2.51	11.35	Vertical	-52.1	-13.0	39.1	180
4	3306	-53.30	4.2	10.85	Vertical	-48.8	-13.0	35.8	270
5	4132	-52.10	5.2	11.35	Vertical	-48.1	-13.0	35.1	90
6	4958	-51.70	5.5	11.95	Vertical	-47.4	-13.0	34.4	45
7	5785	-51.50	5.7	13.55	Vertical	-45.8	-13.0	32.8	90
8	6611	-47.60	6.3	13.75	Vertical	-42.3	-13.0	29.3	45
9	7438	-47.40	6.8	13.85	Vertical	-42.5	-13.0	29.5	0
10	8264	-46.70	6.9	14.25	Vertical	-41.5	-13.0	28.5	135

Note: 1.The other Spurious RF Radiated emissions level is no more than noise floor.

2.The worst emission was found in the antenna is vertical position.



WCDMA Band V CH-Middle

Harmonic	Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	Antenna Polarization	ERP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	1673	-61.60	2	10.75	Vertical	-55.0	-13.0	42.0	315
3	2510	-57.39	2.51	11.05	Vertical	-51.0	-13.0	38.0	270
4	3346	-54.70	4.2	11.15	Vertical	-49.9	-13.0	36.9	180
5	4183	-53.30	5.2	11.15	Vertical	-49.5	-13.0	36.5	315
6	5020	-50.50	5.5	11.95	Vertical	-46.2	-13.0	33.2	270
7	5856	-53.00	5.7	13.55	Vertical	-47.3	-13.0	34.3	315
8	6693	-50.90	6.3	13.75	Vertical	-45.6	-13.0	32.6	270
9	8366	-46.40	6.8	13.85	Vertical	-41.5	-13.0	28.5	45
10	3346	-46.70	6.9	14.25	Vertical	-41.5	-13.0	28.5	225

Note: 1.The other Spurious RF Radiated emissions level is no more than noise floor.

2.The worst emission was found in the antenna is vertical position.

WCDMA Band V CH-High

Harmonic	Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	Antenna Polarization	ERP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	1693	-59.50	2	10.15	Vertical	-53.5	-13.0	40.5	45
3	2540	-58.89	2.51	11.05	Vertical	-52.5	-13.0	39.5	225
4	3386	-53.90	4.2	11.15	Vertical	-49.1	-13.0	36.1	270
5	4233	-51.30	5.2	11.15	Vertical	-47.5	-13.0	34.5	90
6	5080	-51.90	5.5	11.95	Vertical	-47.6	-13.0	34.6	45
7	5926	-50.30	5.7	13.55	Vertical	-44.6	-13.0	31.6	90
8	6773	-48.70	6.3	13.75	Vertical	-43.4	-13.0	30.4	45
9	7619	-46.20	6.8	13.85	Vertical	-41.3	-13.0	28.3	0
10	8466	-46.20	6.9	14.25	Vertical	-41.0	-13.0	28.0	135

Note: 1.The other Spurious RF Radiated emissions level is no more than noise floor.

2.The worst emission was found in the antenna is vertical position.



LTE Band 5 1.4MHz CH-Low

Harmonic	Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	Antenna Polarization	ERP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	1649.4	-60.10	2.00	10.75	vertical	-53.5	-13.0	40.5	135
3	2474.1	-58.29	2.51	11.05	vertical	-51.9	-13.0	38.9	225
4	3298.8	-56.10	4.20	11.15	vertical	-51.3	-13.0	38.3	45
5	4123.5	-53.40	5.20	11.15	vertical	-49.6	-13.0	36.6	90
6	4948.2	-50.90	5.50	11.95	vertical	-46.6	-13.0	33.6	90
7	5772.9	-51.80	5.70	13.55	vertical	-46.1	-13.0	33.1	135
8	6597.6	-48.70	6.30	13.75	vertical	-43.4	-13.0	30.4	270
9	7422.3	-46.00	6.80	13.85	vertical	-41.1	-13.0	28.1	180
10	8247.0	-45.30	6.90	14.25	vertical	-40.1	-13.0	27.1	225

Note: 1.The other Spurious RF Radiated emissions level is no more than noise floor.

2.The worst emission was found in the antenna is vertical position.

LTE Band 5 1.4MHz CH-Middle

Harmonic	Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	Antenna Polarization	ERP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	1673.0	-59.50	2.00	10.75	vertical	-52.9	-13.0	39.9	135
3	2509.5	-59.29	2.51	11.05	vertical	-52.9	-13.0	39.9	135
4	3346.0	-55.90	4.20	11.15	vertical	-51.1	-13.0	38.1	225
5	4182.5	-52.10	5.20	11.15	vertical	-48.3	-13.0	35.3	45
6	5019.0	-50.50	5.50	11.95	vertical	-46.2	-13.0	33.2	90
7	5855.5	-50.90	5.70	13.55	vertical	-45.2	-13.0	32.2	90
8	6692.0	-49.60	6.30	13.75	vertical	-44.3	-13.0	31.3	135
9	7528.5	-47.70	6.80	13.85	vertical	-42.8	-13.0	29.8	270
10	8365.0	-46.20	6.90	14.25	vertical	-41.0	-13.0	28.0	180

Note: 1.The other Spurious RF Radiated emissions level is no more than noise floor.

2.The worst emission was found in the antenna is vertical position.

LTE Band 5 1.4MHz CH-High

Harmonic	Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	Antenna Polarization	ERP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	1696.6	-59.10	2.00	10.75	vertical	-52.5	-13.0	39.5	225
3	2544.9	-57.89	2.51	11.05	vertical	-51.5	-13.0	38.5	135
4	3393.2	-53.00	4.20	11.15	vertical	-48.2	-13.0	35.2	135
5	4241.5	-51.60	5.20	11.15	vertical	-47.8	-13.0	34.8	225
6	5089.8	-50.40	5.50	11.95	vertical	-46.1	-13.0	33.1	45
7	5938.1	-51.30	5.70	13.55	vertical	-45.6	-13.0	32.6	90
8	6786.4	-49.30	6.30	13.75	vertical	-44.0	-13.0	31.0	90
9	7634.7	-48.20	6.80	13.85	vertical	-43.3	-13.0	30.3	135
10	8483.0	-47.60	6.90	14.25	vertical	-42.4	-13.0	29.4	270

Note: 1.The other Spurious RF Radiated emissions level is no more than noise floor.

2.The worst emission was found in the antenna is vertical position.

LTE Band 5 3MHz CH-Low

Harmonic	Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	Antenna Polarization	ERP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	1651.0	-59.70	2.00	10.75	vertical	-53.1	-13.0	40.1	180
3	2476.5	-59.09	2.51	11.05	vertical	-52.7	-13.0	39.7	225
4	3302.0	-54.30	4.20	11.15	vertical	-49.5	-13.0	36.5	135
5	4127.5	-53.50	5.20	11.15	vertical	-49.7	-13.0	36.7	135
6	4953.0	-50.70	5.50	11.95	vertical	-46.4	-13.0	33.4	225
7	5778.5	-52.60	5.70	13.55	vertical	-46.9	-13.0	33.9	45
8	6604.0	-48.60	6.30	13.75	vertical	-43.3	-13.0	30.3	90
9	7429.5	-46.60	6.80	13.85	vertical	-41.7	-13.0	28.7	90
10	8255.0	-45.50	6.90	14.25	vertical	-40.3	-13.0	27.3	135

Note: 1.The other Spurious RF Radiated emissions level is no more than noise floor.

2.The worst emission was found in the antenna is vertical position.

LTE Band 5 3MHz CH-Middle

Harmonic	Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	Antenna Polarization	ERP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	1673.0	-60.10	2.00	10.75	vertical	-53.5	-13.0	40.5	270
3	2509.5	-59.39	2.51	11.05	vertical	-53.0	-13.0	40.0	180
4	3346.0	-53.30	4.20	11.15	vertical	-48.5	-13.0	35.5	225
5	4182.5	-53.30	5.20	11.15	vertical	-49.5	-13.0	36.5	135
6	5019.0	-50.30	5.50	11.95	vertical	-46.0	-13.0	33.0	135
7	5855.5	-50.60	5.70	13.55	vertical	-44.9	-13.0	31.9	225
8	6692.0	-48.00	6.30	13.75	vertical	-42.7	-13.0	29.7	45
9	7528.5	-46.60	6.80	13.85	vertical	-41.7	-13.0	28.7	90
10	8365.0	-46.50	6.90	14.25	vertical	-41.3	-13.0	28.3	90

Note: 1.The other Spurious RF Radiated emissions level is no more than noise floor.

2.The worst emission was found in the antenna is vertical position.

LTE Band 5 3MHz CH-High

Harmonic	Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	Antenna Polarization	ERP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	1695.0	-58.50	2.00	10.75	vertical	-51.9	-13.0	38.9	135
3	2542.5	-57.19	2.51	11.05	vertical	-50.8	-13.0	37.8	270
4	3390.0	-53.30	4.20	11.15	vertical	-48.5	-13.0	35.5	180
5	4237.5	-53.20	5.20	11.15	vertical	-49.4	-13.0	36.4	225
6	5085.0	-50.70	5.50	11.95	vertical	-46.4	-13.0	33.4	135
7	5932.5	-51.40	5.70	13.55	vertical	-45.7	-13.0	32.7	135
8	6780.0	-50.00	6.30	13.75	vertical	-44.7	-13.0	31.7	225
9	7627.5	-47.60	6.80	13.85	vertical	-42.7	-13.0	29.7	45
10	8475.0	-47.30	6.90	14.25	vertical	-42.1	-13.0	29.1	90

Note: 1.The other Spurious RF Radiated emissions level is no more than noise floor.

2.The worst emission was found in the antenna is vertical position.

LTE Band 5 5MHz CH-Low

Harmonic	Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	Antenna Polarization	ERP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	1653.0	-60.70	2.00	10.75	vertical	-54.1	-13.0	41.1	90
3	2479.5	-58.69	2.51	11.05	vertical	-52.3	-13.0	39.3	135
4	3306.0	-55.10	4.20	11.15	vertical	-50.3	-13.0	37.3	270
5	4132.5	-53.00	5.20	11.15	vertical	-49.2	-13.0	36.2	180
6	4959.0	-51.90	5.50	11.95	vertical	-47.6	-13.0	34.6	225
7	5785.5	-51.60	5.70	13.55	vertical	-45.9	-13.0	32.9	135
8	6612.0	-48.20	6.30	13.75	vertical	-42.9	-13.0	29.9	135
9	7438.5	-47.30	6.80	13.85	vertical	-42.4	-13.0	29.4	225
10	8265.0	-46.00	6.90	14.25	vertical	-40.8	-13.0	27.8	45

Note: 1.The other Spurious RF Radiated emissions level is no more than noise floor.

2.The worst emission was found in the antenna is vertical position.

LTE Band 5 5MHz CH-Middle

Harmonic	Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	Antenna Polarization	ERP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	1673.0	-60.80	2.00	10.75	vertical	-54.2	-13.0	41.2	90
3	2509.5	-58.99	2.51	11.05	vertical	-52.6	-13.0	39.6	90
4	3346.0	-54.80	4.20	11.15	vertical	-50.0	-13.0	37.0	135
5	4182.5	-53.20	5.20	11.15	vertical	-49.4	-13.0	36.4	270
6	5019.0	-50.30	5.50	11.95	vertical	-46.0	-13.0	33.0	180
7	5855.5	-51.90	5.70	13.55	vertical	-46.2	-13.0	33.2	225
8	6692.0	-48.60	6.30	13.75	vertical	-43.3	-13.0	30.3	135
9	7528.5	-47.10	6.80	13.85	vertical	-42.2	-13.0	29.2	135
10	8365.0	-46.40	6.90	14.25	vertical	-41.2	-13.0	28.2	225

Note: 1.The other Spurious RF Radiated emissions level is no more than noise floor.

2.The worst emission was found in the antenna is vertical position.

LTE Band 5 5MHz CH-High

Harmonic	Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	Antenna Polarization	ERP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	1693.0	-57.50	2.00	10.75	vertical	-50.9	-13.0	37.9	45
3	2539.5	-58.29	2.51	11.05	vertical	-51.9	-13.0	38.9	90
4	3386.0	-54.80	4.20	11.15	vertical	-50.0	-13.0	37.0	90
5	4232.5	-53.50	5.20	11.15	vertical	-49.7	-13.0	36.7	135
6	5079.0	-50.60	5.50	11.95	vertical	-46.3	-13.0	33.3	270
7	5925.5	-52.50	5.70	13.55	vertical	-46.8	-13.0	33.8	180
8	6772.0	-49.90	6.30	13.75	vertical	-44.6	-13.0	31.6	225
9	7618.5	-47.10	6.80	13.85	vertical	-42.2	-13.0	29.2	135
10	8465.0	-46.90	6.90	14.25	vertical	-41.7	-13.0	28.7	135
Note: 1.The other Spurious RF Radiated emissions level is no more than noise floor. 2.The worst emission was found in the antenna is vertical position.									

LTE Band 5 10MHz CH-Low

Harmonic	Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	Antenna Polarization	ERP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	1658.0	-59.90	2.00	10.75	vertical	-53.3	-13.0	40.3	225
3	2487.0	-58.29	2.51	11.05	vertical	-51.9	-13.0	38.9	45
4	3316.0	-54.70	4.20	11.15	vertical	-49.9	-13.0	36.9	90
5	4145.0	-53.70	5.20	11.15	vertical	-49.9	-13.0	36.9	90
6	4974.0	-51.30	5.50	11.95	vertical	-47.0	-13.0	34.0	135
7	5803.0	-51.20	5.70	13.55	vertical	-45.5	-13.0	32.5	270
8	6632.0	-49.10	6.30	13.75	vertical	-43.8	-13.0	30.8	180
9	7461.0	-45.10	6.80	13.85	vertical	-40.2	-13.0	27.2	225
10	8290.0	-46.30	6.90	14.25	vertical	-41.1	-13.0	28.1	135
Note: 1.The other Spurious RF Radiated emissions level is no more than noise floor. 2.The worst emission was found in the antenna is vertical position.									

LTE Band 5 10MHz CH-Middle

Harmonic	Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	Antenna Polarization	ERP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	1673.0	-59.40	2.00	10.75	vertical	-52.8	-13.0	39.8	135
3	2509.5	-59.29	2.51	11.05	vertical	-52.9	-13.0	39.9	225
4	3346.0	-55.80	4.20	11.15	vertical	-51.0	-13.0	38.0	45
5	4182.5	-53.70	5.20	11.15	vertical	-49.9	-13.0	36.9	90
6	5019.0	-50.80	5.50	11.95	vertical	-46.5	-13.0	33.5	90
7	5855.5	-51.10	5.70	13.55	vertical	-45.4	-13.0	32.4	135
8	6692.0	-48.70	6.30	13.75	vertical	-43.4	-13.0	30.4	270
9	7528.5	-45.60	6.80	13.85	vertical	-40.7	-13.0	27.7	180
10	8365.0	-46.40	6.90	14.25	vertical	-41.2	-13.0	28.2	225

Note: 1.The other Spurious RF Radiated emissions level is no more than noise floor.

2. The worst emission was found in the antenna is vertical position.

LTE Band 5 10MHz CH-High

Harmonic	Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	Antenna Polarization	ERP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	1688.0	-58.50	2.00	10.75	vertical	-51.9	-13.0	38.9	135
3	2532.0	-58.69	2.51	11.05	vertical	-52.3	-13.0	39.3	90
4	3376.0	-56.20	4.20	11.15	vertical	-51.4	-13.0	38.4	135
5	4220.0	-52.20	5.20	11.15	vertical	-48.4	-13.0	35.4	270
6	5064.0	-50.80	5.50	11.95	vertical	-46.5	-13.0	33.5	180
7	5908.0	-50.70	5.70	13.55	vertical	-45.0	-13.0	32.0	225
8	6752.0	-49.20	6.30	13.75	vertical	-43.9	-13.0	30.9	135
9	7596.0	-47.30	6.80	13.85	vertical	-42.4	-13.0	29.4	225
10	8440.0	-46.50	6.90	14.25	vertical	-41.3	-13.0	28.3	45

Note: 1.The other Spurious RF Radiated emissions level is no more than noise floor.

2. The worst emission was found in the antenna is vertical position.

6. Main Test Instruments

Name	Type	Manufacturer	Serial Number	Calibration Date	Expiration Time
Base Station Simulator	CMW500	R&S	113645	2017-05-14	2018-05-13
Power Splitter	SHX-GF2-2-13	Hua Xiang	10120101	2017-05-14	2018-05-13
Spectrum Analyzer	N9010A	Agilent	MY47191109	2017-05-20	2018-05-19
Universal Radio Communication Tester	E5515C	Agilent	MY48367192	2017-05-20	2018-05-19
Signal Analyzer	FSV30	R&S	100815	2016-12-16	2017-12-15
Signal generator	SMB 100A	R&S	102594	2017-05-14	2018-05-13
Signal generator	SMR27	R&S	100365	2017-05-14	2018-05-13
EMI Test Receiver	ESCI	R&S	100948	2016-12-16	2017-12-15
Trilog Antenna	VUBL 9163	SCHWARZBECK	9163-201	2014-12-06	2017-12-05
Horn Antenna	HF907	R&S	100126	2014-12-06	2017-12-05
Horn Antenna	HF907	R&S	100125	2014-12-06	2017-12-05
Climatic Chamber	PT-30B	Re Ce	20101891	2015-07-18	2018-07-17
RF Cable	SMA 15cm	Agilent	0001	2017-02-06	2017-08-05

*****END OF REPORT *****

ANNEX A: EUT Appearance and Test Setup

A.1 EUT Appearance




Front Side



Back Side


a: EUT



b: Battery

Picture 1 EUT and Accessory

A.2 Test Setup



Picture 2: Radiated Spurious Emissions Test setup