



FCC RF Test Report

APPLICANT : ZTE CORPORATION
EQUIPMENT : LTE/CDMA Dual-Mode Digital Mobile Phone
BRAND NAME : ZTE
MODEL NAME : Z717VL
FCC ID : SRQ-Z717VL
STANDARD : FCC Part 15 Subpart C §15.247
CLASSIFICATION : (DTS) Digital Transmission System

The product was received on Oct. 23, 2015 and testing was completed on Nov. 18, 2015. We, SPORTON INTERNATIONAL (KUNSHAN) INC., would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL (KUNSHAN) INC., the test report shall not be reproduced except in full.

Prepared by: James Huang / Manager

Approved by: Jones Tsai / Manager



SPORTON INTERNATIONAL (KUNSHAN) INC.
No. 3-2, PingXiang Road, Kunshan, Jiangsu Province, P. R. China



TABLE OF CONTENTS

REVISION HISTORY	3
SUMMARY OF TEST RESULT	4
1 GENERAL DESCRIPTION	5
1.1 Applicant	5
1.2 Manufacturer	5
1.3 Product Feature of Equipment Under Test.....	5
1.4 Product Specification subjective to this standard	5
1.5 Modification of EUT	6
1.6 Testing Location	6
1.7 Applicable Standards.....	6
2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST	7
2.1 Carrier Frequency Channel	7
2.2 Pre-Scanned RF Power	8
2.3 Test Mode	9
2.4 Connection Diagram of Test System.....	10
2.5 Support Unit used in test configuration and system	11
2.6 EUT Operation Test Setup	11
2.7 Measurement Results Explanation Example.....	11
3 TEST RESULT	12
3.1 6dB Bandwidth Measurement	12
3.2 Output Power Measurement.....	14
3.3 Power Spectral Density Measurement	15
3.4 Conducted Band Edges and Spurious Emission Measurement	17
3.5 Radiated Band Edges and Spurious Emission Measurement	27
3.6 AC Conducted Emission Measurement.....	31
3.7 Antenna Requirements.....	36
4 LIST OF MEASURING EQUIPMENT	37
5 UNCERTAINTY OF EVALUATION	38
APPENDIX A. CONDUCTED TEST RESULTS	
APPENDIX B. RADIATED TEST RESULTS	
APPENDIX C. SETUP PHOTOGRAPHS	



REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR5O2305C	Rev. 01	Initial issue of report	Dec. 16, 2015
FR5O2305C	Rev. 02	Updated report for revising HW version	Dec. 30, 2015

SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	15.247(a)(2)	6dB Bandwidth	$\geq 0.5\text{MHz}$	Pass	-
3.2	15.247(b)	Power Output Measurement	$\leq 30\text{dBm}$	Pass	-
3.3	15.247(e)	Power Spectral Density	$\leq 8\text{dBm}/3\text{kHz}$	Pass	-
3.4	15.247(d)	Conducted Band Edges	$\leq 20\text{dBc}$	Pass	-
		Conducted Spurious Emission		Pass	-
3.5	15.247(d)	Radiated Band Edges and Radiated Spurious Emission	15.209(a) & 15.247(d)	Pass	Under limit 1.75 dB at 2389.830 MHz
3.6	15.207	AC Conducted Emission	15.207(a)	Pass	Under limit 10.48 dB at 3.290 MHz
3.7	15.203 & 15.247(b)	Antenna Requirement	N/A	Pass	-



1 General Description

1.1 Applicant

ZTE CORPORATION

ZTE Plaza, Keji Road South, Hi-Tech Industrial Park, Nanshan District, Shenzhen, Guangdong, 518057,
P. R. China

1.2 Manufacturer

ZTE CORPORATION

ZTE Plaza, Keji Road South, Hi-Tech Industrial Park, Nanshan District, Shenzhen, Guangdong, 518057,
P. R. China

1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	LTE/CDMA Dual-Mode Digital Mobile Phone
Brand Name	ZTE
Model Name	Z717VL
FCC ID	SRQ-Z717VL
EUT supports Radios application	CDMA/EV-DO/LTE WLAN2.4GHz 802.11b/g/n HT20 Bluetooth v2.1+EDR Bluetooth v4.0 LE
MEID Code	Conducted: 99000675000942 Radiation: 99000675000891 Conduction: 99000675000903
HW Version	Z717VLHWV1.1
SW Version	Z717VLV1.0.0B03
EUT Stage	Production Unit

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

1.4 Product Specification subjective to this standard

Product Specification subjective to this standard	
Tx/Rx Channel Frequency Range	802.11b/g/n : 2412 MHz ~ 2462 MHz
Maximum (Peak) Output Power to Antenna	802.11b : 18.35 dBm (0.0684 W) 802.11g : 22.64 dBm (0.1837 W) 802.11n HT20 : 21.17 dBm (0.1309 W)
Antenna Type	PIFA Antenna with gain -4.00 dBi
Type of Modulation	802.11b : DSSS (DBPSK / DQPSK / CCK) 802.11g/n : OFDM (BPSK / QPSK / 16QAM / 64QAM)

1.5 Modification of EUT

No modifications are made to the EUT during all test items.

1.6 Testing Location

Test Site	SPORTON INTERNATIONAL (KUNSHAN) INC.			
Test Site Location	No. 3-2, PingXiang Road, Kunshan, Jiangsu Province, P. R. China TEL: +86-0512-5790-0158 FAX: +86-0512-5790-0958			
Test Site No.	Sporton Site No.			FCC Registration No.
	TH01-KS	03CH03-KS	CO01-KS	306251

Note: The test site complies with ANSI C63.4 2014 requirement.

1.7 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC Part 15 Subpart C §15.247
- ♦ FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r03
- ♦ ANSI C63.10-2013

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

2 Test Configuration of Equipment Under Test

The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conducted emission (150 kHz to 30 MHz) and radiated emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases (X plane) were recorded in this report.

The final configuration from all the combinations and the worst-case data rates were investigated by measuring the maximum power across all the data rates and modulation modes under section 2.2.

Based on the worst configuration found above, the RF power setting is set individually to meet FCC compliance limit for the final conducted and radiated tests shown in section 2.3.

2.1 Carrier Frequency Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
2400-2483.5 MHz	1	2412	7	2442
	2	2417	8	2447
	3	2422	9	2452
	4	2427	10	2457
	5	2432	11	2462
	6	2437	-	-

2.2 Pre-Scanned RF Power

Preliminary tests were performed in different data rate and data rate associated with the highest power were chosen for full test shown in the following tables.

2.4GHz 802.11b RF Output Power (dBm)						
Power vs. Channel			Power vs. Data Rate			
Channel	Frequency (MHz)	Data Rate 1Mbps	Channel	2Mbps	5.5Mbps	11Mbps
CH 01	2412 MHz	18.35	CH 01	18.23	18.31	18.33
CH 06	2437 MHz	17.16				
CH 11	2462 MHz	16.88				

2.4GHz 802.11g RF Output Power (dBm)										
Power vs. Channel			Power vs. Data Rate							
Channel	Frequency (MHz)	Data Rate 6Mbps	Channel	9Mbps	12Mbps	18Mbps	24Mbps	36Mbps	48Mbps	54Mbps
CH 01	2412 MHz	22.64	CH 01	22.40	22.46	22.51	22.45	22.56	22.54	22.60
CH 06	2437 MHz	21.60								
CH 11	2462 MHz	21.42								

2.4GHz 802.11n HT20 RF Output Power (dBm)										
Power vs. Channel			Power vs. MCS Index							
Channel	Frequency (MHz)	MCS Index MCS0	Channel	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7
CH 01	2412 MHz	21.17	CH 01	20.94	20.98	21.05	21.14	21.11	21.08	21.12
CH 06	2437 MHz	20.14								
CH 11	2462 MHz	19.52								

2.3 Test Mode

Final test mode of conducted test items and radiated spurious emissions are considering the modulation and worse data rates from the power table described in section 2.2.

Modulation	Data Rate
802.11b	1 Mbps
802.11g	6 Mbps
802.11n HT20	MCS0


Test Cases	
AC Conducted Emission	Mode 1 : CDMA2000 BC0 Idle + Bluetooth Link + WLAN Link + Earphone + USB Cable (Charging from Adapter)

2.4 Connection Diagram of Test System

<WLAN Tx Mode>



<AC Conducted Emission Mode>



2.5 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	System Simulator	R&S	CMU 200	N/A	N/A	Unshielded, 1.8 m
2.	WLAN AP	D-Link	DIR-855	KIA2DIR855A2	N/A	Unshielded, 1.8 m
3.	Notebook	Lenovo	G480	N/A	N/A	AC I/P: Unshielded, 1.8 m DC O/P: Shielded, 1.8 m
4.	Bluetooth Earphone	Nokia	BH-102	PYAHS-107W	N/A	N/A
5.	Earphone	Lenovo	SH100	N/A	Unshielded,1.2m	N/A

2.6 EUT Operation Test Setup

For WLAN RF test items, an engineering test program was provided and enabled to make EUT continuous transmit/receive.

For AC power line conducted emissions, the EUT was set to connect with the WLAN AP under large package sizes transmission.

2.7 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example:

The spectrum analyzer offset is RF cable loss.

Offset = RF cable loss.

Following shows an offset computation example with cable loss 5.5 dB.

$$\begin{aligned}
 \text{Offset(dB)} &= \text{RF cable loss(dB)}. \\
 &= 5.5 \text{ (dB)}
 \end{aligned}$$

3 Test Result

3.1 6dB Bandwidth Measurement

3.1.1 Limit of 6dB Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.


3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.1.3 Test Procedures

1. The testing follows FCC KDB Publication No. 558074 DTS D01 Meas. Guidance v03r03.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6 dB bandwidth must be greater than 500 kHz.
5. Measure and record the results in the test report.


3.1.4 Test Setup





3.1.5 Test Result of 6dB Bandwidth

Please refer to Appendix A of this test report.



3.2 Output Power Measurement

3.2.1 Limit of Output Power

For systems using digital modulation in the 2400-2483.5MHz, the limit for peak output power is 30dBm. If transmitting Antenna of directional gain greater than 6dBi are used the peak output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the Antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the Antenna exceeds 6dBi.


3.2.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.2.3 Test Procedures

1. The testing follows the Measurement Procedure of FCC KDB No. 558074 DTS D01 Meas. Guidance v03r03 section 9.1.2 PKPM1 Peak power meter method.
2. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Measure the conducted output power and record the results in the test report.

3.2.4 Test Setup



3.2.5 Test Result of Peak Output Power

Please refer to Appendix A of this test report.

3.2.6 Test Result of Average output Power (Reporting Only)

Please refer to Appendix A of this test report.

3.3 Power Spectral Density Measurement

3.3.1 Limit of Power Spectral Density

The peak power spectral density shall not be greater than 8dBm in any 3kHz band at any time interval of continuous transmission.


3.3.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.3.3 Test Procedures

1. The testing follows Measurement Procedure 10.2 Method PKPSD of FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r03
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 3 kHz. Video bandwidth VBW = 10 kHz In order to make an accurate measurement, set the span to 1.5 times DTS Channel Bandwidth. (6dB BW)
5. Detector = peak, Sweep time = auto couple, Trace mode = max hold, Allow trace to fully stabilize. Use the peak marker function to determine the maximum power level.
6. Measure and record the results in the test report.


3.3.4 Test Setup





3.3.5 Test Result of Power Spectral Density

Please refer to Appendix A of this test report.



3.4 Conducted Band Edges and Spurious Emission Measurement

3.4.1 Limit of Conducted Band Edges and Spurious Emission Measurement

In any 100 kHz bandwidth outside of the authorized frequency band, the emissions which fall in the non-restricted bands shall be attenuated at least 20 dB / 30dB relative to the maximum PSD level in 100 kHz by RF conducted measurement and radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a).


3.4.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.4.3 Test Procedures

1. The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r03.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Set RBW = 100 kHz, VBW=300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB per 15.247(d).
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

3.4.4 Test Setup






3.4.5 Test Result of Conducted Band Edges and Spurious Emission

Test Mode :	802.11b	Temperature :	24~25℃
Test Band :	2.4GHz Low	Relative Humidity :	49~51%
Test Channel :	01	Test Engineer :	Issac Song


WLAN 802.11b Channel 01

100kHz PSD reference Level




Date: 12.NOV.2015 02:00:25

Low Channel Plot




Date: 12.NOV.2015 02:01:10

Spurious Emission 30MHz~3GHz



Date: 12.NOV.2015 02:01:29

Spurious Emission 2GHz~25GHz




Date: 12.NOV.2015 02:01:38



Test Mode :	802.11b	Temperature :	24~25°C
Test Band :	2.4GHz Mid	Relative Humidity :	49~51%
Test Channel :	06	Test Engineer :	Issac Song


WLAN 802.11b Channel 06

100kHz PSD reference Level




Date: 12.NOV.2015 02:06:53

Spurious Emission 30MHz~3GHz



Date: 12.NOV.2015 02:08:03

Spurious Emission 2GHz~25GHz




Date: 12.NOV.2015 02:08:12



Test Mode :	802.11b	Temperature :	24~25°C
Test Band :	2.4GHz High	Relative Humidity :	49~51%
Test Channel :	11	Test Engineer :	Issac Song


WLAN 802.11b Channel 11

100kHz PSD reference Level




Date: 12.NOV.2015 02:12:43

High Channel Plot




Date: 12.NOV.2015 02:13:21

Spurious Emission 30MHz~3GHz



Date: 12.NOV.2015 02:13:43

Spurious Emission 2GHz~25GHz




Date: 12.NOV.2015 02:13:51



Test Mode :	802.11g	Temperature :	24~25°C
Test Band :	2.4GHz Low	Relative Humidity :	49~51%
Test Channel :	01	Test Engineer :	Issac Song


WLAN 802.11g Channel 01

100kHz PSD reference Level




Date: 12.NOV.2015 02:21:02

Low Channel Plot




Date: 12.NOV.2015 02:21:59

Spurious Emission 30MHz~3GHz



Date: 12.NOV.2015 02:25:18

Spurious Emission 2GHz~25GHz




Date: 12.NOV.2015 02:25:26

Test Mode :	802.11g	Temperature :	24~25℃
Test Band :	2.4GHz Mid	Relative Humidity :	49~51%
Test Channel :	06	Test Engineer :	Issac Song


WLAN 802.11g Channel 06

100kHz PSD reference Level




Date: 12.NOV.2015 02:29:05

Spurious Emission 30MHz~3GHz



Date: 12.NOV.2015 02:29:56

Spurious Emission 2GHz~25GHz




Date: 12.NOV.2015 02:30:04



Test Mode :	802.11g	Temperature :	24~25°C
Test Band :	2.4GHz High	Relative Humidity :	49~51%
Test Channel :	11	Test Engineer :	Issac Song


WLAN 802.11g Channel 11

100kHz PSD reference Level




Date: 12.NOV.2015 02:32:43

High Channel Plot




Date: 12.NOV.2015 02:33:01

Spurious Emission 30MHz~3GHz



Date: 12.NOV.2015 02:33:19

Spurious Emission 2GHz~25GHz




Date: 12.NOV.2015 02:33:27



Test Mode :	802.11n HT20	Temperature :	24~25°C
Test Band :	2.4GHz Low	Relative Humidity :	49~51%
Test Channel :	01	Test Engineer :	Issac Song


WLAN 802.11n HT20 Channel 01

100kHz PSD reference Level




Date: 12.NOV.2015 02:36:34

Low Channel Plot




Date: 12.NOV.2015 02:37:18

Spurious Emission 30MHz~3GHz



Date: 12.NOV.2015 02:37:56

Spurious Emission 2GHz~25GHz




Date: 12.NOV.2015 02:38:05

Test Mode :	802.11n HT20	Temperature :	24~25℃
Test Band :	2.4GHz Mid	Relative Humidity :	49~51%
Test Channel :	06	Test Engineer :	Issac Song


WLAN 802.11n HT20 Channel 06

100kHz PSD reference Level




Date: 12.NOV.2015 02:40:53

Spurious Emission 30MHz~3GHz



Date: 12.NOV.2015 02:41:07

Spurious Emission 2GHz~25GHz




Date: 12.NOV.2015 02:41:15



Test Mode :	802.11n HT20	Temperature :	24~25°C
Test Band :	2.4GHz High	Relative Humidity :	49~51%
Test Channel :	11	Test Engineer :	Issac Song


WLAN 802.11n HT20 Channel 11

100kHz PSD reference Level




Date: 12.NOV.2015 02:44:15

High Channel Plot




Date: 12.NOV.2015 02:44:36

Spurious Emission 30MHz~3GHz



Date: 12.NOV.2015 02:44:49

Spurious Emission 2GHz~25GHz



Date: 12.NOV.2015 02:44:58



3.5 Radiated Band Edges and Spurious Emission Measurement

3.5.1 Limit of Radiated band edge and Spurious Emission Measurement

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. If the output power of this device was measured by spectrum analyzer, the attenuation under this paragraph shall be 30 dB instead of 20 dB. In addition, radiated emissions which fall in the restricted bands must also comply with the FCC section 15.209 limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.5.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.5.3 Test Procedures

1. The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r03.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.
3. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
6. For measurement below 1GHz, If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.
7. Use the following spectrum analyzer settings:
 - (1) Span shall wide enough to fully capture the emission being measured;
 - (2) Set RBW=100 kHz for $f < 1$ GHz; VBW $\geq$ RBW; Sweep = auto; Detector function = peak; Trace = max hold;
 - (3) Set RBW = 1 MHz, VBW= 3MHz for $f \geq 1$ GHz for peak measurement.


For average measurement:

 - VBW = 10 Hz, when duty cycle is no less than 98 percent.
 - VBW $\geq 1/T$, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.


Band	Duty Cycle(%)	T(ms)	1/T(kHz)	VBW Setting
802.11b	97.65	8.21	0.12	300Hz
802.11g	87.10	1.36	0.74	1kHz
2.4GHz 802.11n HT20	87.09	1.28	0.78	1kHz

3.5.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



3.5.5 Test Results of Radiated Spurious Emissions (9kHz ~ 30MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not reported.

3.5.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix B.

3.5.7 Test Result of Radiated Spurious Emission (30MHz ~ 10th Harmonic)

Please refer to Appendix B.

3.6 AC Conducted Emission Measurement

3.6.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of Emission (MHz)	Conducted Limit (dB μ V)	
	Quasi-Peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.6.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.6.3 Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room, and it was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF bandwidth = 9kHz) with Maximum Hold Mode.


3.6.4 Test Setup





3.6.5 Test Result of AC Conducted Emission

Test Mode :	Mode 1	Temperature :	22~24℃
Test Engineer :	Amos Mo	Relative Humidity :	44~46%
Test Voltage :	120Vac / 60Hz	Phase :	Line
Function Type :	CDMA2000 BC0 Idle + Bluetooth Link + WLAN Link + Earphone + USB Cable (Charging from Adapter)		




Site : CO01-KS
Condition : FCC PART 15C LISN-L20141025 LINE

mode : Mode 1
: 99000675000903

	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	2.32	40.75	-15.25	56.00	30.49	0.11	10.15	QP
2	2.32	33.15	-12.85	46.00	22.89	0.11	10.15	Average
3	2.57	42.17	-13.83	56.00	31.90	0.12	10.15	QP
4	2.57	34.47	-11.53	46.00	24.20	0.12	10.15	Average
5	2.76	41.18	-14.82	56.00	30.90	0.13	10.15	QP
6	2.76	34.68	-11.32	46.00	24.40	0.13	10.15	Average
7	2.99	42.19	-13.81	56.00	31.90	0.14	10.15	QP
8	2.99	35.49	-10.51	46.00	25.20	0.14	10.15	Average
9	3.29	42.52	-13.48	56.00	32.20	0.16	10.16	QP
10 *	3.29	35.52	-10.48	46.00	25.20	0.16	10.16	Average
11	3.55	41.53	-14.47	56.00	31.20	0.17	10.16	QP
12	3.55	34.63	-11.37	46.00	24.30	0.17	10.16	Average
13	3.90	42.05	-13.95	56.00	31.71	0.18	10.16	QP
14	3.90	34.55	-11.45	46.00	24.21	0.18	10.16	Average
15	4.57	40.97	-15.03	56.00	30.60	0.19	10.18	QP
16	4.57	33.07	-12.93	46.00	22.70	0.19	10.18	Average



Test Mode :	Mode 1	Temperature :	22~24°C
Test Engineer :	Amos Mo	Relative Humidity :	44~46%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Function Type :	CDMA2000 BC0 Idle + Bluetooth Link + WLAN Link + Earphone + USB Cable (Charging from Adapter)		




Site : CO01-KS
Condition : FCC PART 15C LISN-N20141025 NEUTRAL

mode : Mode 1
: 99000675000903

	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	1.86	38.74	-17.26	56.00	28.50	0.10	10.14	QP
2	1.86	29.44	-16.56	46.00	19.20	0.10	10.14	Average
3	2.09	38.55	-17.45	56.00	28.31	0.10	10.14	QP
4	2.09	31.05	-14.95	46.00	20.81	0.10	10.14	Average
5	2.45	40.06	-15.94	56.00	29.80	0.11	10.15	QP
6	2.45	32.76	-13.24	46.00	22.50	0.11	10.15	Average
7	2.58	40.87	-15.13	56.00	30.60	0.12	10.15	QP
8	2.58	32.87	-13.13	46.00	22.60	0.12	10.15	Average
9	2.71	41.47	-14.53	56.00	31.20	0.12	10.15	QP
10	2.71	33.87	-12.13	46.00	23.60	0.12	10.15	Average
11	3.07	42.10	-13.90	56.00	31.81	0.14	10.15	QP
12 *	3.07	34.50	-11.50	46.00	24.21	0.14	10.15	Average
13	3.44	41.53	-14.47	56.00	31.20	0.17	10.16	QP
14	3.44	33.13	-12.87	46.00	22.80	0.17	10.16	Average
15	3.68	41.54	-14.46	56.00	31.20	0.18	10.16	QP
16	3.68	32.54	-13.46	46.00	22.20	0.18	10.16	Average
17	3.88	43.05	-12.95	56.00	32.71	0.18	10.16	QP



Test Mode :	Mode 1	Temperature :	22~24℃
Test Engineer :	Amos Mo	Relative Humidity :	44~46%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Function Type :	CDMA2000 BC0 Idle + Bluetooth Link + WLAN Link + Earphone + USB Cable (Charging from Adapter)		



Site : CO01-KS
Condition : FCC PART 15C LISN-N20141025 NEUTRAL
mode : Mode 1
: 99000675000903

	Freq	Level	Over	Limit	Read	LISN	Cable	
	MHz	dBuV	Limit	Line	Level	Factor	Loss	Remark
			dB	dBuV	dBuV	dB	dB	
18	3.88	33.25	-12.75	46.00	22.91	0.18	10.16	Average
19	4.38	41.96	-14.04	56.00	31.60	0.19	10.17	QP
20	4.38	32.16	-13.84	46.00	21.80	0.19	10.17	Average
21	4.87	40.28	-15.72	56.00	29.90	0.20	10.18	QP
22	4.87	30.58	-15.42	46.00	20.20	0.20	10.18	Average



3.7 Antenna Requirements

3.7.1 Standard Applicable

If directional gain of transmitting antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. For the fixed point-to-point operation, the power shall be reduced by one dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the FCC rule.

3.7.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

3.7.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.



4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSP40	100319	9kHz~40GHz	Oct. 24, 2015	Nov. 12, 2015	Oct. 23, 2016	Conducted (TH01-KS)
Pulse Power Sensor	Anritsu	MA2411B	0917070	30MHz~40GHz	Jan. 23, 2015	Nov. 12, 2015	Jan. 22, 2016	Conducted (TH01-KS)
Power Meter	Anritsu	ML2495A	1005002	50MHz Bandwidth	Jan. 23, 2015	Nov. 12, 2015	Jan. 22, 2016	Conducted (TH01-KS)
EMI Test Receiver	R&S	ESR7	101403	9kHz~7GHz;Ma x 30dBm	Sep. 10, 2015	Nov. 18, 2015	Sep. 09, 2016	Radiation (03CH03-KS)
EXA Spectrum Analyzer	Keysight	N9010A	MY55150244	10Hz~44GHz	Jun. 05, 2015	Nov. 18, 2015	Jun. 04, 2016	Radiation (03CH03-KS)
Loop Antenna	R&S	HFH2-Z2	100321	9kHz~30MHz	Nov. 10, 2015	Nov. 18, 2015	Nov. 09, 2016	Radiation (03CH03-KS)
Bilog Antenna	TeseQ	CBL6112D	35406	25MHz~2GHz	Jun. 25, 2015	Nov. 18, 2015	Jun. 24, 2016	Radiation (03CH03-KS)
Horn Antenna	Schwarzbeck	BBHA9120D	9120D-1356	1GHz~18GHz	Jun. 25, 2015	Nov. 18, 2015	Jun. 24, 2016	Radiation (03CH03-KS)
SHF-EHF Horn	Schwarzbeck	BBHA 9170	BBHA170249	15GHz ~40GHz	Mar. 03, 2015	Nov. 18, 2015	Mar. 02, 2016	Radiation (03CH03-KS)
Amplifier	Burgeon	BPA-530	102212	0.01MHz~3000MHz	Aug.10, 2015	Nov. 18, 2015	Aug. 09, 2016	Radiation (03CH03-KS)
Amplifier	Agilent	8449B	3008A02370	1GHz~26.5GHz	Oct. 24, 2015	Nov. 18, 2015	Oct. 23, 2016	Radiation (03CH03-KS)
AC Power Source	Chroma	61601	F104090004	N/A	NCR	Nov. 18, 2015	NCR	Radiation (03CH03-KS)
Turn Table	ChamPro	EM 1000-T	060762-T	0~360 degree	NCR	Nov. 18, 2015	NCR	Radiation (03CH03-KS)
Antenna Mast	ChamPro	EM 1000-A	060762-A	1 m~4 m	NCR	Nov. 18, 2015	NCR	Radiation (03CH03-KS)
EMI Test Receiver	R&S	ESR7	101403	9kHz~7GHz;Ma x 30dBm	Sep. 10, 2015	Nov. 07, 2015	Sep. 09, 2016	Conduction (CO01-KS)
AC LISN	MessTec	AN3016	060103	9kHz~30MHz	Oct. 24, 2015	Nov. 07, 2015	Oct. 23, 2016	Conduction (CO01-KS)
AC LISN (for auxiliary equipment)	MessTec	AN3016	060105	9kHz~30MHz	Oct. 24, 2015	Nov. 07, 2015	Oct. 23, 2016	Conduction (CO01-KS)
AC Power Source	Chroma	61602	ABP00000811	AC 0V~300V, 45Hz~1000Hz	Oct. 24, 2015	Nov. 07, 2015	Oct. 23, 2016	Conduction (CO01-KS)



5 Uncertainty of Evaluation

Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	2.3dB
---	-------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	4.5dB
---	-------



Appendix A. Conducted Test Results

A1 - DTS Part

Test Engineer:	Issac Song	Temperature:	24~25	°C
Test Date:	Nov. 12, 2015	Relative Humidity:	49~51	%

TEST RESULTS DATA
6dB Bandwidth

2.4GHz Band							
Mod.	Data Rate	Ntx	CH.	Freq. (MHz)	6dB BW (MHz)	6dB BW Limit (MHz)	Pass/Fail
11b	1Mbps	1	1	2412	8.04	0.50	Pass
11b	1Mbps	1	6	2437	8.04	0.50	Pass
11b	1Mbps	1	11	2462	8.02	0.50	Pass
11g	6Mbps	1	1	2412	16.36	0.50	Pass
11g	6Mbps	1	6	2437	16.36	0.50	Pass
11g	6Mbps	1	11	2462	16.36	0.50	Pass
HT20	MCS0	1	1	2412	17.56	0.50	Pass
HT20	MCS0	1	6	2437	17.60	0.50	Pass
HT20	MCS0	1	11	2462	17.60	0.50	Pass

TEST RESULTS DATA
Peak Power Table

2.4GHz Band										
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Peak Conducted Power (dBm)	Conducted Power Limit (dBm)	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass /Fail
11b	1Mbps	1	1	2412	18.35	30.00	-4.00	14.35	36.00	Pass
11b	1Mbps	1	6	2437	17.16	30.00	-4.00	13.16	36.00	Pass
11b	1Mbps	1	11	2462	16.88	30.00	-4.00	12.88	36.00	Pass
11g	6Mbps	1	1	2412	22.64	30.00	-4.00	18.64	36.00	Pass
11g	6Mbps	1	6	2437	21.60	30.00	-4.00	17.60	36.00	Pass
11g	6Mbps	1	11	2462	21.42	30.00	-4.00	17.42	36.00	Pass
HT20	MCS0	1	1	2412	21.17	30.00	-4.00	17.17	36.00	Pass
HT20	MCS0	1	6	2437	20.14	30.00	-4.00	16.14	36.00	Pass
HT20	MCS0	1	11	2462	19.52	30.00	-4.00	15.52	36.00	Pass

TEST RESULTS DATA
Average Power Table
(Reporting Only)

2.4GHz Band						
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Duty Factor (dB)	Average Conducted Power (dBm)
11b	1Mbps	1	1	2412	0.10	15.38
11b	1Mbps	1	6	2437	0.10	14.22
11b	1Mbps	1	11	2462	0.10	13.94
11g	6Mbps	1	1	2412	0.60	12.97
11g	6Mbps	1	6	2437	0.60	11.68
11g	6Mbps	1	11	2462	0.60	11.46
HT20	MCS0	1	1	2412	0.60	10.88
HT20	MCS0	1	6	2437	0.60	9.51
HT20	MCS0	1	11	2462	0.60	9.31

TEST RESULTS DATA
Peak Power Density

2.4GHz Band								
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Peak PSD (dBm /3kHz)	DG (dBi)	Peak PSD Limit (dBm /3kHz)	Pass/Fail
11b	1Mbps	1	1	2412	-7.42	-4.00	8.00	Pass
11b	1Mbps	1	6	2437	-7.75	-4.00	8.00	Pass
11b	1Mbps	1	11	2462	-7.94	-4.00	8.00	Pass
11g	6Mbps	1	1	2412	-12.57	-4.00	8.00	Pass
11g	6Mbps	1	6	2437	-13.51	-4.00	8.00	Pass
11g	6Mbps	1	11	2462	-14.30	-4.00	8.00	Pass
HT20	MCS0	1	1	2412	-15.58	-4.00	8.00	Pass
HT20	MCS0	1	6	2437	-14.85	-4.00	8.00	Pass
HT20	MCS0	1	11	2462	-15.48	-4.00	8.00	Pass



Appendix B. Radiated Spurious Emission

2.4GHz 2400~2483.5MHz

WIFI 802.11b (Band Edge @ 3m)

WIFI	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11b CH 01 2412MHz	*	2412.024	101.03	-	-	105.29	27.13	5.61	37	141	19	P	H
	*	2413.11	98.49	-	-	102.75	27.13	5.61	37	141	19	A	H
		2331.69	51.38	-22.62	74	56.07	26.82	5.5	37.01	141	19	P	H
		2389.56	41.55	-12.45	54	45.98	27	5.59	37.02	141	19	A	H
	*	2412.024	96.29	-	-	100.55	27.13	5.61	37	100	66	P	V
	*	2413.11	93.73	-	-	97.99	27.13	5.61	37	100	66	A	V
		2316.57	50.86	-23.14	74	55.63	26.77	5.47	37.01	100	66	P	V
		2389.11	40.58	-13.42	54	45.01	27	5.59	37.02	100	66	A	V
802.11b CH 06 2437MHz	*	2438.159	102.95	-	-	106.88	27.39	5.65	36.97	112	20	P	H
	*	2438.159	100.3	-	-	104.23	27.39	5.65	36.97	112	20	A	H
	*	2438.076	97.12	-	-	101.05	27.39	5.65	36.97	100	272	P	V
	*	2438.159	94.6	-	-	98.53	27.39	5.65	36.97	100	272	A	V
802.11b CH 11 2462MHz	*	2461.957	102.85	-	-	106.63	27.51	5.67	36.96	100	20	P	H
	*	2460.955	99.38	-	-	103.16	27.51	5.67	36.96	100	20	A	H
		2486.4	51.83	-22.17	74	55.44	27.64	5.69	36.94	100	20	P	H
		2483.64	41.83	-12.17	54	45.44	27.64	5.69	36.94	100	20	A	H
	*	2462.041	97.82	-	-	101.6	27.51	5.67	36.96	101	185	P	V
	*	2461.039	94.22	-	-	98	27.51	5.67	36.96	101	185	A	V
		2486.12	51.55	-22.45	74	55.16	27.64	5.69	36.94	101	185	P	V
		2487.56	41.4	-12.6	54	44.85	27.77	5.71	36.93	101	185	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												

**2.4GHz 2400~2483.5MHz****WIFI 802.11b (Harmonic @ 3m)**

WIFI	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11b CH 01 2412MHz		4824	42.24	-31.76	74	39.56	31.51	7.85	36.68	168	79	P	H
		4824	41.48	-32.52	74	38.8	31.51	7.85	36.68	100	0	P	V
802.11b CH 06 2437MHz		4875	42.5	-31.5	74	39.68	31.59	7.89	36.66	121	20	P	H
		7311	45.68	-28.32	74	38.76	34.03	9.58	36.69	125	23	P	H
		4875	43.49	-30.51	74	40.67	31.59	7.89	36.66	100	288	P	V
		7311	47.55	-26.45	74	40.63	34.03	9.58	36.69	102	275	P	V
802.11b CH 11 2462MHz		4923	44.05	-29.95	74	41.11	31.67	7.92	36.65	169	227	P	H
		7386	46.73	-27.27	74	39.46	34.29	9.76	36.78	182	206	P	H
		4923	42.63	-31.37	74	39.69	31.67	7.92	36.65	116	43	P	V
		7386	47.13	-26.87	74	39.86	34.29	9.76	36.78	105	228	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz
WIFI 802.11g (Band Edge @ 3m)

WIFI	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11g CH 01 2412MHz	*	2415.865	102.62	-	-	106.88	27.13	5.61	37	139	18	P	H
	*	2418.203	93.88	-	-	98.14	27.13	5.61	37	139	18	A	H
		2389.2	67.87	-6.13	74	72.3	27	5.59	37.02	139	18	P	H
	!	2389.83	52.25	-1.75	54	56.68	27	5.59	37.02	139	18	A	H
	*	2415.281	97.55	-	-	101.81	27.13	5.61	37	100	69	P	V
	*	2417.034	88.79	-	-	93.05	27.13	5.61	37	100	69	A	V
		2387.49	61.36	-12.64	74	65.79	27	5.59	37.02	100	69	P	V
		2389.83	47.06	-6.94	54	51.49	27	5.59	37.02	100	69	A	V
802.11g CH 06 2437MHz	*	2438.076	102.13	-	-	106.06	27.39	5.65	36.97	114	21	P	H
	*	2443.503	94.49	-	-	98.42	27.39	5.65	36.97	114	21	A	H
	*	2440.247	97.73	-	-	101.66	27.39	5.65	36.97	100	122	P	V
	*	2442	89.4	-	-	93.33	27.39	5.65	36.97	100	122	A	V
802.11g CH 11 2462MHz	*	2457.031	101.86	-	-	105.64	27.51	5.67	36.96	100	20	P	H
	*	2456.363	93.77	-	-	97.55	27.51	5.67	36.96	100	20	A	H
		2483.56	67.39	-6.61	74	71	27.64	5.69	36.94	100	20	P	H
	!	2483.84	48.35	-5.65	54	51.96	27.64	5.69	36.94	100	20	A	H
	*	2460.371	97.46	-	-	101.24	27.51	5.67	36.96	100	184	P	V
	*	2458.199	88.96	-	-	92.74	27.51	5.67	36.96	100	184	A	V
		2483.6	61.31	-12.69	74	64.92	27.64	5.69	36.94	100	184	P	V
		2483.52	44.53	-9.47	54	48.14	27.64	5.69	36.94	100	184	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz

WIFI 802.11g (Harmonic @ 3m)

WIFI	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11g CH 01 2412MHz		4824	42.26	-31.74	74	39.58	31.51	7.85	36.68	100	11	P	H
		4824	41.72	-32.28	74	39.04	31.51	7.85	36.68	132	199	P	V
802.11g CH 06 2437MHz		4875	43.6	-30.4	74	40.78	31.59	7.89	36.66	100	31	P	H
		7311	45.6	-28.4	74	38.68	34.03	9.58	36.69	100	25	P	H
		4875	43.55	-30.45	74	40.73	31.59	7.89	36.66	100	207	P	V
		7311	46.36	-27.64	74	39.44	34.03	9.58	36.69	100	182	P	V
802.11g CH 11 2462MHz		4923	43.21	-30.79	74	40.27	31.67	7.92	36.65	115	22	P	H
		7386	45.91	-28.09	74	38.64	34.29	9.76	36.78	135	192	P	H
		4923	42.28	-31.72	74	39.34	31.67	7.92	36.65	134	216	P	V
		7386	45.62	-28.38	74	38.35	34.29	9.76	36.78	152	221	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz

WIFI 802.11n HT20 (Band Edge @ 3m)

WIFI	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT20 CH 01 2412MHz		2389.38	65.44	-8.56	74	69.87	27	5.59	37.02	100	5	P	H
	!	2389.92	49.68	-4.32	54	54.11	27	5.59	37.02	100	5	A	H
	*	2415.948	99.43	-	-	103.69	27.13	5.61	37	100	5	P	H
	*	2419.456	91.08	-	-	95.34	27.13	5.61	37	100	5	A	H
		2389.65	57.7	-16.3	74	62.13	27	5.59	37.02	126	117	P	V
		2389.92	44.16	-9.84	54	48.59	27	5.59	37.02	126	117	A	V
	*	2408.183	94.22	-	-	98.48	27.13	5.61	37	126	117	P	V
	*	2407.431	85.97	-	-	90.23	27.13	5.61	37	126	117	A	V
802.11n HT20 CH 06 2437MHz	*	2438.41	100.06	-	-	103.99	27.39	5.65	36.97	118	21	P	H
	*	2441.667	92.31	-	-	96.24	27.39	5.65	36.97	118	21	A	H
	*	2440.665	94.21	-	-	98.14	27.39	5.65	36.97	100	203	P	V
	*	2442.585	86.5	-	-	90.43	27.39	5.65	36.97	100	203	A	V
802.11n HT20 CH 11 2462MHz	*	2455.945	98.95	-	-	102.73	27.51	5.67	36.96	105	189	P	H
	*	2454.525	90.85	-	-	94.63	27.51	5.67	36.96	105	189	A	H
		2484.08	61.75	-12.25	74	65.36	27.64	5.69	36.94	105	189	P	H
		2483.52	45.08	-8.92	54	48.69	27.64	5.69	36.94	105	189	A	H
	*	2457.281	95.39	-	-	99.17	27.51	5.67	36.96	100	67	P	V
	*	2455.277	87.32	-	-	91.1	27.51	5.67	36.96	100	67	A	V
		2483.76	60.04	-13.96	74	63.65	27.64	5.69	36.94	100	67	P	V
		2483.88	43.66	-10.34	54	47.27	27.64	5.69	36.94	100	67	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz
WIFI 802.11n HT20 (Harmonic @ 3m)

WIFI	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT20 CH 01 2412MHz		4824	41.92	-32.08	74	39.24	31.51	7.85	36.68	100	66	P	H
		4824	43.43	-30.57	74	40.75	31.51	7.85	36.68	132	177	P	V
802.11n HT20 CH 06 2437MHz		4874	42.5	-31.5	74	39.68	31.59	7.89	36.66	116	35	P	H
		7311	46.07	-27.93	74	39.15	34.03	9.58	36.69	180	22	P	H
		4875	42.39	-31.61	74	39.57	31.59	7.89	36.66	100	201	P	V
		7311	45.42	-28.58	74	38.5	34.03	9.58	36.69	100	166	P	V
802.11n HT20 CH 11 2462MHz		4923	43.63	-30.37	74	40.69	31.67	7.92	36.65	100	31	P	H
		7386	45.7	-28.3	74	38.43	34.29	9.76	36.78	112	88	P	H
		4923	43.06	-30.94	74	40.12	31.67	7.92	36.65	137	201	P	V
		7386	45.52	-28.48	74	38.25	34.29	9.76	36.78	105	191	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												

**Emission below 1GHz****2.4GHz WIFI 802.11g (LF)**

WIFI	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
2.4GHz 802.11g LF		33.88	22.05	-17.95	40	34.25	18.04	0.7	30.94	135	255	P	H
		107.6	13.88	-29.62	43.5	29.82	13.21	1.25	30.4	-	-	P	H
		216.24	13.44	-32.56	46	30.62	11.52	1.73	30.43	-	-	P	H
		323.91	18.82	-27.18	46	31.83	15.33	2.21	30.55	-	-	P	H
		755.56	22.51	-23.49	46	28.63	20.9	3.48	30.5	-	-	P	H
		914.64	24.62	-21.38	46	28.26	23.04	3.89	30.57	-	-	P	H
		32.91	33.64	-6.36	40	45.75	18.18	0.69	30.98	134	341	P	V
		91.11	17.72	-25.78	43.5	35.01	12.04	1.15	30.48	-	-	P	V
		288.02	23.54	-22.46	46	37.5	14.5	2.04	30.5	-	-	P	V
		306.45	23.91	-22.09	46	37.24	15.02	2.16	30.51	-	-	P	V
		323.91	27.05	-18.95	46	40.06	15.33	2.21	30.55	-	-	P	V
		936.95	25.42	-20.58	46	28.61	23.4	3.94	30.53	-	-	P	V
Remark	1. No other spurious found. 2. All results are PASS against limit line.												



Note symbol

*	Fundamental Frequency which can be ignored. However, the level of any unwanted emissions shall not exceed the level of the fundamental frequency.
!	Test result is over limit line.
P/A	P eak or A verage
H/V	H orizontal or V ertical



A calculation example for radiated spurious emission is shown as below:

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11b CH 01		2390	55.45	-18.55	74	54.51	32.22	4.58	35.86	103	308	P	H
2412MHz		2390	43.54	-10.46	54	42.6	32.22	4.58	35.86	103	308	A	H

1. Level(dBμV/m) =

Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

2. Over Limit(dB) = Level(dBμV/m) – Limit Line(dBμV/m)

For Peak Limit @ 2390MHz:

1. Level(dBμV/m)

= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 54.51(dBμV) – 35.86 (dB)

= 55.45 (dBμV/m)

2. Over Limit(dB)

= Level(dBμV/m) – Limit Line(dBμV/m)

= 55.45(dBμV/m) – 74(dBμV/m)

= -18.55(dB)

For Average Limit @ 2390MHz:

1. Level(dBμV/m)

= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 42.6(dBμV) – 35.86 (dB)

= 43.54 (dBμV/m)

2. Over Limit(dB)

= Level(dBμV/m) – Limit Line(dBμV/m)

= 43.54(dBμV/m) – 54(dBμV/m)

= -10.46(dB)

Both peak and average measured complies with the limit line, so test result is “PASS”.