


FCC Test Report


APPLICANT : ZTE CORPORATION
EQUIPMENT : CDMA 1X EVDO Mobile Phone
BRAND NAME : ZTE
MODEL NAME : Z793C
FCC ID : SRQ-Z793C
STANDARD : FCC 47 CFR FCC Part 15 Subpart B
CLASSIFICATION : Certification

The product was received on Mar. 11, 2015 and testing was completed on Apr. 07, 2015. We, SPORTON INTERNATIONAL (KUNSHAN) INC., would like to declare that the tested sample has been evaluated in accordance with the test procedures given in ANSI C63.4-2009 and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL (KUNSHAN) INC., the test report shall not be reproduced except in full.



Reviewed by: Louis Wu / Manager



Approved by: Jones Tsai / Manager



SPORTON INTERNATIONAL (KUNSHAN) INC.
No. 3-2, PingXiang Road, Kunshan, Jiangsu Province, P. R. China



TABLE OF CONTENTS

REVISION HISTORY.....	3
SUMMARY OF TEST RESULT	4
1. GENERAL DESCRIPTION	5
1.1. Applicant.....	5
1.2. Manufacturer	5
1.3. Feature of Equipment Under Test.....	5
1.4. Product Specification of Equipment Under Test	6
1.5. Modification of EUT	7
1.6. Test Site	7
1.7. Applied Standards	7
2. TEST CONFIGURATION OF EQUIPMENT UNDER TEST	8
2.1. Test Mode	8
2.2. Connection Diagram of Test System	10
2.3. Support Unit used in test configuration and system.....	12
2.4. EUT Operation Test Setup	13
3. TEST RESULT	14
3.1. Test of AC Conducted Emission Measurement	14
3.2. Test of Radiated Emission Measurement	21
4. LIST OF MEASURING EQUIPMENT	27
5. UNCERTAINTY OF EVALUATION	28
APPENDIX A. SETUP PHOTOGRAPHS	



REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FC531101	Rev. 01	Initial issue of report	Apr. 09, 2015



SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	15.107	AC Conducted Emission	< 15.107 limits	PASS	Under limit 4.18 dB at 0.520 MHz
3.2	15.109	Radiated Emission	< 15.109 limits	PASS	Under limit 3.04 dB at 35.820 MHz



1. General Description

1.1. Applicant

ZTE CORPORATION

ZTE Plaza, Keji Road South, Hi-Tech, Industrial Park, Nanshan District, Shenzhen, Guangdong, 518057, P.R.China

1.2. Manufacturer

ZTE CORPORATION

ZTE Plaza, Keji Road South, Hi-Tech, Industrial Park, Nanshan District, Shenzhen, Guangdong, 518057, P.R.China

1.3. Product Feature of Equipment Under Test

Product Feature	
Equipment	CDMA 1X EVDO Mobile Phone
Brand Name	ZTE
Model Name	Z793C
FCC ID	SRQ-Z793C
EUT supports Radios application	CDMA/EV-DO/WLAN 2.4GHz 802.11b/g/n HT20 Bluetooth v3.0 + EDR/Bluetooth v4.0 LE
HW Version	Z793CHWV1.0
SW Version	Z793CV1.0.0B04
EUT Stage	Identical Prototype

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

1.4. Product Specification subjective to this standard

Product Specification subjective to this standard	
Tx Frequency	CDMA2000 BC0 : 824.70 MHz ~ 848.31 MHz CDMA2000 BC1 : 1851.25 MHz ~ 1908.75 MHz 802.11b/g/n: 2412 MHz ~ 2462 MHz Bluetooth: 2402 MHz ~ 2480 MHz
Rx Frequency	CDMA2000 BC0 : 869.70 MHz ~ 893.31 MHz CDMA2000 BC1 : 1931.25 MHz ~ 1988.75 MHz 802.11b/g/n: 2412 MHz ~ 2462 MHz Bluetooth: 2402 MHz ~ 2480 MHz GPS : 1.57542 GHz Glonass : 1602 MHz + $n \times 0.5625\text{MHz}$ ($n=-7,-6,-5,...,0,...,6$)
Antenna Type	WWAN : PIFA Antenna WLAN : PIFA Antenna Bluetooth : PIFA Antenna GPS : PIFA Antenna Glonass : PIFA Antenna
Type of Modulation	CDMA2000 : QPSK CDMA2000 1xEV-DO : QPSK/8PSK 802.11b : DSSS (DBPSK / DQPSK / CCK) 802.11g/n : OFDM (BPSK / QPSK / 16QAM / 64QAM) Bluetooth LE : GFSK Bluetooth (1Mbps) : GFSK Bluetooth (2Mbps) : $\pi/4$ -DQPSK Bluetooth (3Mbps) : 8-DPSK GPS : BPSK Glonass : BPSK

1.5. Modification of EUT

No modifications are made to the EUT during all test items.

1.6. Test Location

Test Site	SPORTON INTERNATIONAL (KUNSHAN) INC.		
Test Site Location	No. 3-2, PingXiang Road, Kunshan, Jiangsu Province, P. R. China TEL: +86-0512-5790-0158 FAX: +86-0512-5790-0958		
Test Site No.	Sporton Site No.		FCC Registration No.
	CO01-KS	03CH01-KS	149928

1.7. Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC 47 CFR FCC Part 15 Subpart B
- ♦ ANSI C63.4-2009

Remark: All test items were verified and recorded according to the standards and without any deviation during the test.

2. Test Configuration of Equipment Under Test

2.1. Test Mode

The EUT has been associated with peripherals pursuant to ANSI C63.4-2009 and configuration operated in a manner tended to maximize its emission characteristics in a typical application.

Frequency range investigated: conduction (150 kHz to 30 MHz), radiation (30MHz to the 5th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower).

The following tables are showing the test modes as the worst cases and recorded in this report.


Item	EUT Configuration	Test Condition		
		EMI AC	EMI RE<1G	EMI RE≥1G
1.	Charging Mode (EUT with adapter)	☒	☒	☒
2.	Data application transferred mode (EUT connected with notebook)	☒	☒	☒

Abbreviations:


- EMI AC: AC conducted emissions
- EMI RE ≥ 1G: EUT radiated emissions ≥ 1GHz
- EMI RE < 1G: EUT radiated emissions < 1GHz

Test Items	EUT Configure Mode	Function Type
AC Conducted Emission	1/2	Mode 1: CDMA2000 BC0 Idle + Bluetooth Idle + WLAN Idle + USB Cable (Charging from Adapter) + Earphone + Camera <Fig.1> Mode 2: CDMA2000 BC1 Idle + Bluetooth Idle + WLAN Idle + USB Cable (Charging from Adapter) + Earphone + MPEG4 <Fig.1> Mode 3: CDMA2000 BC0 Idle + Bluetooth Idle + WLAN Idle + USB Cable (Data Link with Notebook) + Earphone + GPS Rx <Fig.2> Mode 4: CDMA2000 BC1 Idle + Bluetooth Idle + WLAN Idle + USB Cable (Charging from Adapter) + Earphone + Glonass Rx<Fig.3>
Radiated Emissions < 1GHz	1/2	Mode 1: CDMA2000 BC0 Idle + Bluetooth Idle + WLAN Idle + USB Cable (Charging from Adapter) + Earphone + Camera <Fig.1> Mode 2: CDMA2000 BC1 Idle + Bluetooth Idle + WLAN Idle + USB Cable (Charging from Adapter) + Earphone + MPEG4 <Fig.1> Mode 3: CDMA2000 BC0 Idle + Bluetooth Idle + WLAN Idle + USB Cable (Data Link with Notebook) + Earphone + GPS Rx <Fig.2> Mode 4: CDMA2000 BC1 Idle + Bluetooth Idle + WLAN Idle + USB Cable (Charging from Adapter) + Earphone + Glonass Rx<Fig.3>
Radiated Emissions ≥ 1GHz	1	Mode 1: CDMA2000 BC1 Idle + Bluetooth Idle + WLAN Idle + USB Cable (Charging from Adapter) + Earphone + MPEG4 <Fig.1> Mode 2: CDMA2000 BC0 Idle + Bluetooth Idle + WLAN Idle + USB Cable (Data Link with Notebook) + Earphone + GPS Rx<Fig.2>
Remark: - The worst case of AC is mode 1, and the USB Link mode of AC is mode 3, the test data of these modes were reported. - The worst case of RE < 1G is mode 2; and the USB Link mode of RE is mode 3, the test data of these modes were reported. - Link with Notebook means data application transferred mode between EUT and Notebook.		


2.2. Connection Diagram of Test System



<Fig.1>



<Fig.2>



<Fig.3>

2.3. Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	System Simulator	R&S	CMU 200	N/A	N/A	Unshielded, 1.8 m
2.	GPS Station	ADIVIC	MP9000	N/A	N/A	Unshielded, 1.8 m
3.	WLAN AP	D-Link	DIR-855	KA2DIR855A2	N/A	Unshielded, 1.8m
4.	Bluetooth Earphone	Nokia	BH-106	QTLBH-106	N/A	N/A
5.	Bluetooth Earphone	Lenovo	LBH301	N/A	N/A	N/A
6.	Notebook	Lenovo	G480	N/A	N/A	AC I/P: Unshielded, 0.8 m DC O/P: Shielded, 1.8 m
7.	iPod	Apple	A1199	FCC DoC	Unshielded, 1.2 m	N/A
8.	Glonass Station	RACELOGIC	RLLS03-2P	FCC DoC	N/A	N/A



2.4. EUT Operation Test Setup

The EUT was in CDMA2000 idle mode during the testing. The EUT was synchronized to the BCCH, and was in continuous receiving mode by setting system simulator's paging reorganization.

At the same time, the EUT was attached to the Bluetooth earphone or WLAN AP, and the following programs installed in the EUT were programmed during the test.

1. Data application is transferred between Laptop and EUT via USB cable.
2. Execute "GPS Test" to make the EUT receive continuous signals from GPS station.
3. Execute "Glonass Test" to make the EUT receive continuous signals from Glonass station.
4. Execute "Video Player" to play MPEG4 files.
5. Turn on camera to capture images.

3. Test Result

3.1. Test of AC Conducted Emission Measurement

3.1.1 Limits of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.1.3 Test Procedure


1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.

3.1.4 Test Setup



3.1.5 Test Result of AC Conducted Emission

Test Mode :	Mode 1	Temperature :	20~22℃
Test Engineer :	Morris Li	Relative Humidity :	40~42%
Test Voltage :	120Vac / 60Hz	Phase :	Line
Function Type :	CDMA2000 BC0 Idle + Bluetooth Idle + WLAN Idle + USB Cable (Charging from Adapter) + Earphone + Camera		




Site : CO01-KS
 Condition : FCC CLASS-B LISN-L20140306 LINE
 Project : (FC) 531101
 mode : Mode 1

	Freq	Level	Over	Limit	Read	LISN	Cable	Remark
	MHz	dBuV	Limit	Line	Level	Factor	Loss	
			dB	dBuV	dBuV	dB	dB	
1	0.42	45.51	-11.91	57.42	34.61	0.28	10.62	QP
2	0.42	31.71	-15.71	47.42	20.81	0.28	10.62	Average
3	0.43	45.29	-11.91	57.20	34.40	0.27	10.62	QP
4	0.43	30.69	-16.51	47.20	19.80	0.27	10.62	Average
5	0.44	46.28	-10.74	57.02	35.40	0.26	10.62	QP
6	0.44	34.48	-12.54	47.02	23.60	0.26	10.62	Average
7	0.45	46.47	-10.42	56.89	35.60	0.25	10.62	QP
8	0.45	35.27	-11.62	46.89	24.40	0.25	10.62	Average
9 *	0.53	48.43	-7.57	56.00	37.60	0.20	10.63	QP
10	0.53	38.43	-7.57	46.00	27.60	0.20	10.63	Average
11	0.56	43.73	-12.27	56.00	32.90	0.20	10.63	QP
12	0.56	32.63	-13.37	46.00	21.80	0.20	10.63	Average
13	0.57	45.43	-10.57	56.00	34.60	0.20	10.63	QP
14	0.57	34.63	-11.37	46.00	23.80	0.20	10.63	Average
15	0.65	43.04	-12.96	56.00	32.20	0.20	10.64	QP
16	0.65	32.64	-13.36	46.00	21.80	0.20	10.64	Average
17	0.68	39.74	-16.26	56.00	28.90	0.20	10.64	QP
18	0.68	28.44	-17.56	46.00	17.60	0.20	10.64	Average
19	0.70	41.44	-14.56	56.00	30.60	0.20	10.64	QP
20	0.70	31.34	-14.66	46.00	20.50	0.20	10.64	Average
21	0.72	43.24	-12.76	56.00	32.41	0.19	10.64	QP
22	0.72	33.34	-12.66	46.00	22.51	0.19	10.64	Average
23	0.78	43.22	-12.78	56.00	32.41	0.17	10.64	QP
24	0.78	32.22	-13.78	46.00	21.41	0.17	10.64	Average
25	0.85	43.19	-12.81	56.00	32.40	0.14	10.65	QP



Test Mode :	Mode 1	Temperature :	20~22℃
Test Engineer :	Morris Li	Relative Humidity :	40~42%
Test Voltage :	120Vac / 60Hz	Phase :	Line
Function Type :	CDMA2000 BC0 Idle + Bluetooth Idle + WLAN Idle + USB Cable (Charging from Adapter) + Earphone + Camera		




Site : CO01-KS
 Condition : FCC CLASS-B LISN-L20140306 LINE
 Project : (FC) 531101
 mode : Mode 1

	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
26	0.85	31.89	-14.11	46.00	21.10	0.14	10.65	Average
27	4.82	41.54	-14.46	56.00	30.49	0.20	10.85	QP
28	4.82	32.44	-13.56	46.00	21.39	0.20	10.85	Average
29	4.93	42.55	-13.45	56.00	31.50	0.20	10.85	QP
30	4.93	33.55	-12.45	46.00	22.50	0.20	10.85	Average



Test Mode :	Mode 1	Temperature :	20~22℃
Test Engineer :	Morris Li	Relative Humidity :	40~42%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Function Type :	CDMA2000 BC0 Idle + Bluetooth Idle + WLAN Idle + USB Cable (Charging from Adapter) + Earphone + Camera		




Site : CO01-KS
Condition : FCC CLASS-B LISN-N20140306 NEUTRAL
Project : (FC) 531101
mode : Mode 1

	Freq	Level	Over	Limit	Read	LISN	Cable	
	MHz	dBuV	Limit	Line	Level	Factor	Loss	Remark
		dBuV	dB	dBuV	dBuV	dB	dB	
1	0.43	44.59	-12.74	57.33	33.60	0.37	10.62	QP
2	0.43	31.59	-15.74	47.33	20.60	0.37	10.62	Average
3	0.44	45.37	-11.61	56.98	34.40	0.35	10.62	QP
4	0.44	35.37	-11.61	46.98	24.40	0.35	10.62	Average
5	0.46	45.16	-11.55	56.71	34.21	0.33	10.62	QP
6	0.46	37.46	-9.25	46.71	26.51	0.33	10.62	Average
7	0.52	48.72	-7.28	56.00	37.80	0.29	10.63	QP
8 *	0.52	41.82	-4.18	46.00	30.90	0.29	10.63	Average
9	0.53	44.11	-11.89	56.00	33.20	0.28	10.63	QP
10	0.53	36.51	-9.49	46.00	25.60	0.28	10.63	Average
11	0.56	42.00	-14.00	56.00	31.10	0.27	10.63	QP
12	0.56	32.50	-13.50	46.00	21.60	0.27	10.63	Average
13	0.59	42.68	-13.32	56.00	31.80	0.25	10.63	QP
14	0.59	33.78	-12.22	46.00	22.90	0.25	10.63	Average
15	4.67	41.14	-14.86	56.00	30.10	0.20	10.84	QP
16	4.67	34.14	-11.86	46.00	23.10	0.20	10.84	Average
17	4.90	40.65	-15.35	56.00	29.60	0.20	10.85	QP
18	4.90	34.55	-11.45	46.00	23.50	0.20	10.85	Average
19	5.03	41.45	-18.55	60.00	30.40	0.20	10.85	QP
20	5.03	34.55	-15.45	50.00	23.50	0.20	10.85	Average



Test Mode :	Mode 3	Temperature :	20~22℃
Test Engineer :	Morris Li	Relative Humidity :	40~42%
Test Voltage :	120Vac / 60Hz	Phase :	Line
Function Type :	CDMA2000 BC0 Idle + Bluetooth Idle + WLAN Idle + USB Cable (Data Link with Notebook) + Earphone + GPS Rx		




Site : CO01-KS
Condition : FCC CLASS-B LISN-L20140306 LINE
Project : (FC) 531101
mode : Mode 3

	Freq	Level	Over	Limit	Read	LISN	Cable	Remark
	MHz	dBuV	Limit	Line	Level	Factor	Loss	
			dB	dBuV	dBuV	dB	dB	
1	0.43	36.80	-20.49	57.29	25.90	0.28	10.62	QP
2 *	0.43	35.20	-12.09	47.29	24.30	0.28	10.62	Average
3	0.49	34.33	-21.81	56.14	23.50	0.21	10.62	QP
4	0.49	31.73	-14.41	46.14	20.90	0.21	10.62	Average
5	0.55	31.53	-24.47	56.00	20.70	0.20	10.63	QP
6	0.55	25.73	-20.27	46.00	14.90	0.20	10.63	Average
7	4.60	33.84	-22.16	56.00	22.80	0.20	10.84	QP
8	4.60	28.54	-17.46	46.00	17.50	0.20	10.84	Average
9	4.95	34.95	-21.05	56.00	23.90	0.20	10.85	QP
10	4.95	29.45	-16.55	46.00	18.40	0.20	10.85	Average
11	5.71	34.37	-25.63	60.00	23.30	0.20	10.87	QP
12	5.71	29.27	-20.73	50.00	18.20	0.20	10.87	Average



Test Mode :	Mode 3	Temperature :	20~22℃
Test Engineer :	Morris Li	Relative Humidity :	40~42%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Function Type :	CDMA2000 BC0 Idle + Bluetooth Idle + WLAN Idle + USB Cable (Data Link with Notebook) + Earphone + GPS Rx		



Site : CO01-KS
Condition : FCC CLASS-B LISN-N20140306 NEUTRAL
Project : (FC) 531101
mode : Mode 3

	Freq	Level	Over	Limit	Read	LISN	Cable	Remark
	MHz	dBuV	Limit	Line	Level	Factor	Loss	
			dB	dBuV	dBuV	dB	dB	
1	0.50	35.72	-20.29	56.01	24.80	0.30	10.62	QP
2 *	0.50	33.22	-12.79	46.01	22.30	0.30	10.62	Average
3	1.86	34.60	-21.40	56.00	23.80	0.10	10.70	QP
4	1.86	27.00	-19.00	46.00	16.20	0.10	10.70	Average
5	2.31	35.73	-20.27	56.00	24.90	0.11	10.72	QP
6	2.31	26.63	-19.37	46.00	15.80	0.11	10.72	Average
7	2.64	33.66	-22.34	56.00	22.80	0.12	10.74	QP
8	2.64	26.66	-19.34	46.00	15.80	0.12	10.74	Average
9	4.90	36.25	-19.75	56.00	25.20	0.20	10.85	QP
10	4.90	28.95	-17.05	46.00	17.90	0.20	10.85	Average
11	5.48	36.46	-23.54	60.00	25.40	0.20	10.86	QP
12	5.48	27.36	-22.64	50.00	16.30	0.20	10.86	Average

3.2. Test of Radiated Emission Measurement

3.2.1. Limit of Radiated Emission

The emissions from an unintentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.2.2. Measuring Instruments


The measuring equipment is listed in the section 4 of this test report.

3.2.3. Test Procedures


1. The EUT was placed on a turntable with 0.8 meter above ground.
2. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
3. The table was rotated 360 degrees to determine the position of the highest radiation.
4. The antenna is a Bi-Log antenna and its height is adjusted between one to four meters above ground to find the maximum value of the field strength for both horizontal polarization and vertical polarization of the antenna.
5. For each suspected emission, the EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading.
6. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode (RBW=120kHz/VBW=300kHz for frequency below 1GHz; RBW=1MHz VBW=3MHz (Peak), RBW=1MHz/VBW=10Hz (Average) for frequency above 1GHz).
7. If the emission level of the EUT in peak mode was 3 dB lower than the limit specified, peak values of EUT will be reported. Otherwise, the emission will be repeated by using the quasi-peak method and reported.
8. Emission level (dB μ V/m) = 20 log Emission level (μ V/m)
9. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamplifier Factor = Level

3.2.4. Test Setup of Radiated Emission

For radiated emissions from 30MHz to 1GHz




For radiated emissions above 1GHz






3.2.5. Test Result of Radiated Emission





Test Mode :	Mode 2	Temperature :	22~23°C
Test Engineer :	Simon Lu	Relative Humidity :	42~43%
Test Distance :	3m	Polarization :	Vertical
Function Type :	CDMA2000 BC1 Idle + Bluetooth Idle + WLAN Idle + USB Cable (Charging from Adapter) + Earphone + MPEG4		




Site : 03CH01-KS
Condition : FCC CLASS-B 3m LF_ANT_37879 VERTICAL
Project : (FC)531101
Mode : 2

	Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark	Pol/Phas
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1	35.82	36.96	-3.04	40.00	52.53	16.26	0.79	32.62	120	235	Peak VERTICAL
2	47.46	31.38	-8.62	40.00	53.00	10.23	0.79	32.64	---	---	Peak VERTICAL
3	170.65	24.64	-18.86	43.50	44.79	10.92	1.44	32.51	---	---	Peak VERTICAL
4	212.36	20.30	-23.20	43.50	40.80	10.38	1.61	32.49	---	---	Peak VERTICAL
5	386.96	23.52	-22.48	46.00	37.43	16.12	2.28	32.31	---	---	Peak VERTICAL
6	943.74	27.39	-18.61	46.00	33.70	21.73	3.68	31.72	---	---	Peak VERTICAL
7	1590.00	44.31	-29.69	74.00	51.31	28.62	5.01	40.63	---	---	Peak VERTICAL
8	2244.00	48.31	-25.69	74.00	48.03	31.14	6.01	36.87	---	---	Peak VERTICAL
9	3448.00	47.75	-26.25	74.00	40.55	33.40	7.48	33.68	---	---	Peak VERTICAL
10	4374.00	50.05	-23.95	74.00	41.13	34.74	8.52	34.34	---	---	Peak VERTICAL
11	5780.00	49.47	-24.53	74.00	43.26	35.32	9.66	38.77	---	---	Peak VERTICAL
12	6750.00	50.67	-23.33	74.00	43.84	35.58	10.44	39.19	---	---	Peak VERTICAL



Test Mode :	Mode 3	Temperature :	22~23°C
Test Engineer :	Simon Lu	Relative Humidity :	42~43%
Test Distance :	3m	Polarization :	Horizontal
Function Type :	CDMA2000 BC0 Idle + Bluetooth Idle + WLAN Idle + USB Cable (Data Link with Notebook) + Earphone + GPS Rx		
Remark :	#7 is system simulator signal which can be ignored.		




Site : 03CH01-KS
 Condition : FCC CLASS-B 3m LF_ANT_37879 HORIZONTAL
 Project : (FC)531101
 Mode : 3

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level Factor	Cable Loss	Preamp Factor	A/Pos	T/Pos	Remark	
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1	30.97	19.38	-20.62	40.00	32.54	18.71	0.79	32.66	---	---	Peak
2	55.22	18.82	-21.18	40.00	43.23	7.40	0.79	32.60	---	---	Peak
3	99.84	22.85	-20.65	43.50	43.14	11.30	1.04	32.63	---	---	Peak
4	193.93	33.61	-9.89	43.50	54.45	10.02	1.61	32.47	120	341	Peak
5	283.17	31.68	-14.32	46.00	49.52	12.70	1.90	32.44	---	---	Peak
6	480.08	34.36	-11.64	46.00	46.84	17.18	2.51	32.17	---	---	Peak
7	881.66	38.55			44.77	22.08	3.50	31.80	---	---	Peak
8	1688.00	44.66	-29.34	74.00	50.79	28.90	5.13	40.16	---	---	Peak
9	2624.00	49.07	-24.93	74.00	46.04	31.81	6.48	35.26	---	---	Peak
10	3320.00	47.51	-26.49	74.00	40.64	33.16	7.34	33.63	---	---	Peak
11	4782.00	49.67	-24.33	74.00	42.51	34.86	8.71	36.41	---	---	Peak
12	5298.00	48.89	-25.11	74.00	43.36	35.09	9.18	38.74	---	---	Peak
13	6466.00	50.22	-23.78	74.00	43.68	35.55	10.20	39.21	---	---	Peak



Test Mode :	Mode 3	Temperature :	22~23°C
Test Engineer :	Simon Lu	Relative Humidity :	42~43%
Test Distance :	3m	Polarization :	Vertical
Function Type :	CDMA2000 BC0 Idle + Bluetooth Idle + WLAN Idle + USB Cable (Data Link with Notebook) + Earphone + GPS Rx		
Remark :	#7 is system simulator signal which can be ignored.		



Site : 03CH01-KS
Condition : FCC CLASS-B 3m LF_ANT_37879 VERTICAL
Project : (FC)531101
Mode : 3

	Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark
	MHz	dBuV/m	Limit	Line	Level	Loss	Factor	cm	deg	
			dB	dBuV/m	dBuV	dB/m	dB	dB		
1	30.97	27.01	-12.99	40.00	40.17	18.71	0.79	32.66	---	Peak
2	59.10	27.42	-12.58	40.00	52.87	6.36	0.79	32.60	100	0 Peak
3	133.79	25.03	-18.47	43.50	44.82	11.57	1.23	32.59	---	Peak
4	196.84	28.72	-14.78	43.50	49.67	9.91	1.61	32.47	---	Peak
5	203.63	29.33	-14.17	43.50	50.22	9.98	1.61	32.48	---	Peak
6	524.70	32.17	-13.83	46.00	43.74	17.98	2.64	32.19	---	Peak
7	881.66	39.93			46.15	22.08	3.50	31.80	---	Peak
8	1234.00	43.15	-30.85	74.00	52.65	28.08	4.26	41.84	---	Peak
9	2750.00	49.14	-24.86	74.00	45.07	32.22	6.62	34.77	---	Peak
10	3448.00	47.75	-26.25	74.00	40.55	33.40	7.48	33.68	---	Peak
11	4664.00	49.99	-24.01	74.00	42.43	34.80	8.63	35.87	---	Peak
12	5502.00	48.54	-25.46	74.00	42.86	35.16	9.40	38.88	---	Peak
13	6148.00	49.98	-24.02	74.00	43.37	35.47	9.98	38.84	---	Peak



4. List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
EMI Test Receiver	R&S	ESCI	100534	9kHz~3GHz	Oct. 25, 2014	Apr. 07, 2015	Oct. 24, 2015	Radiation (03CH01-KS)
Spectrum Analyzer	R&S	FSP30	101399	9kHz~30GHz	May 04, 2014	Apr. 07, 2015	May 03, 2015	Radiation (03CH01-KS)
Bilog Antenna	TeseQ	CBL6112D	37879	30Mhz~2Ghz	Sep. 13, 2014	Apr. 07, 2015	Sep. 12, 2015	Radiation (03CH01-KS)
Double Ridge Horn Antenna	ETS-Lindgren	3117	75957	1GHz~18GHz	Nov. 08, 2014	Apr. 07, 2015	Nov. 07, 2015	Radiation (03CH01-KS)
Amplifier	com-power	PA-103A	161073	1MHz~1GHz	May 04, 2014	Apr. 07, 2015	May 03, 2015	Radiation (03CH01-KS)
Amplifier	Agilent	8449B	3008A02371	1GHz~26.5GHz	Oct. 28, 2014	Apr. 07, 2015	Oct. 27, 2015	Radiation (03CH01-KS)
AC Power Source	Chroma	61601	F104090004	N/A	NCR	Apr. 07, 2015	NCR	Radiation (03CH01-KS)
Turn Table	MF	MF7802	N/A	0~360 degree	NCR	Apr. 07, 2015	NCR	Radiation (03CH01-KS)
Antenna Mast	MF	MF7802	N/A	1 m~4 m	NCR	Apr. 07, 2015	NCR	Radiation (03CH01-KS)
EMI TEST Receiver	R&S	ESCI7	100768	9kHz~3GHz	May 04, 2014	Mar. 13, 2015	May 03, 2015	Conduction (CO01-SZ)
AC LISN	EMCO	3816/2SH	00103912	9kHz~30MHz	Feb. 02, 2015	Mar. 13, 2015	Feb. 01, 2016	Conduction (CO01-SZ)
AC LISN (for auxiliary equipment)	EMCO	3816/2SH	00103892	9kHz~30MHz	Feb. 02, 2015	Mar. 13, 2015	Feb. 01, 2016	Conduction (CO01-SZ)
AC Power Source	Chroma	61602	616020000891	100Vac~250Vac	Sep. 29, 2014	Mar. 13, 2015	Sep. 28, 2015	Conduction (CO01-SZ)



5. Uncertainty of Evaluation

Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_c(y)$)	2.3dB
--	-------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_c(y)$)	2.5dB
--	-------