
TEST REPORT FOR WCDMA TESTING

Report No.: SRTC2022-9004(F)-22040703(B)

Product Name: LTE/WCDMA/GSM(GPRS) Multi-Mode Digital Mobile Phone

Product Model: ZTE 8045

Applicant: ZTE Corporation

Manufacturer: ZTE Corporation

Specification: FCC Part 24E, Part 22H, Part 27,Part 2 (2020)

FCC ID: SRQ-ZTE8045S

The State Radio_monitoring_center Testing Center (SRTC)

15th Building, No.30 Shixing Street, Shijingshan District, Beijing, P.R.China

Tel: 86-10-57996183 Fax: 86-10-57996388

CONTENTS

1. GENERAL INFORMATION	2
1.1 Notes of the test report	2
1.2 Information about the testing laboratory	2
1.3 Applicant's details	2
1.4 Manufacturer's details	2
1.5 Factory's details	2
1.6 Test Environment	3
2 DESCRIPTION OF THE DEVICE UNDER TEST	3
2.1 Final Equipment Build Status	3
2.2 Support Equipment	4
3 REFERENCE SPECIFICATION	4
4 KEY TO NOTES AND RESULT CODES	4
5 RESULT SUMMARY	5
6 TEST RESULT	6
6.1 RF Power Output	6
6.2 Effective Radiated Power and Effective Isotropic Radiated Power	7
6.3 Occupied Bandwidth	8
6.4 Emission Bandwidth	9
6.5 Spurious Emissions at antenna terminal	10
6.6 Band Edges Compliance	11
6.7 Frequency Stability	12
6.8 Radiated Spurious Emissions	13
6.9 Peak-Average Ratio	15
7 MEASUREMENT UNCERTAINTIES	16
8 TEST EQUIPMENTS	17
APPENDIX A – TEST DATA OF CONDUCTED EMISSION	18
APPENDIX B – TEST DATA OF RADIATED EMISSION	54

1. GENERAL INFORMATION

1.1 Notes of the test report

The test report may only be reproduced or published in full. Reproduction or publication of extracts from the report requires the prior written permission of The State Radio_monitoring_center Testing Center (SRTC). The test results relate only to individual items of the samples which have been tested. The certification and accreditation identifiers used in this report shall not be applicable to the tested or calibrated samples thereof. The manufacturer shall not mark the tested samples or items (or a separate part of the item) with the identifiers of certification and accreditation to mislead relevant parties about the tested samples or items.

1.2 Information about the testing laboratory

Company:	The State Radio_monitoring_center Testing Center (SRTC)
Address:	15th Building, No.30 Shixing Street, Shijingshan District, P.R.China
City:	Beijing
Country or Region:	P.R.China
Contacted person:	Liu Jia
Tel:	+86 10 57996183
Fax:	+86 10 57996388
Email:	liujiaf@srtc.org.cn
Designation Number:	CN1267
Registration number:	239125

1.3 Applicant's details

Company:	ZTE Corporation
Address:	ZTE Plaza, #55 Keji Road South, Hi-Tech, Industrial Park, Nanshan District, Shenzhen, Guangdong, 518057, P.R.China

1.4 Manufacturer's details

Company:	ZTE Corporation
Address:	ZTE Plaza, #55 Keji Road South, Hi-Tech, Industrial Park, Nanshan District, Shenzhen, Guangdong, 518057, P.R.China

1.5 Factory's details

Company:	ZTE Corporation
Address:	ZTE Plaza, #55 Keji Road South, Hi-Tech, Industrial Park, Nanshan District, Shenzhen, Guangdong, 518057, P.R.China

1.6 Test Environment

Date of Receipt of test sample at SRTC:	2022-04-07
Testing Start Date:	2022-04-09
Testing End Date:	2022-04-25

Environmental Data:	Temperature (°C)	Humidity (%)
Ambient:	25	40
Maximum Extreme:	55	---
Minimum Extreme:	-20	---

Normal Supply Voltage (V d.c.):	3.8
Maximum Extreme Supply Voltage (V d.c.):	4.2
Minimum Extreme Supply Voltage (V d.c.):	3.6

2 DESCRIPTION OF THE DEVICE UNDER TEST

2.1 Final Equipment Build Status

Frequency Range:	WCDMA Band II: Tx:1852.4~1907.6MHz Rx:1932.4~1987.6MHz WCDMA Band IV: Tx:1712.4~1752.6MHz Rx:2112.4~2152.6MHz WCDMA Band V: Tx:826.4~846.6MHz Rx:871.4~891.6MHz
Mode:	HSDPA/HSUPA
Emission Designator:	4M50F9W
Duplex Mode:	FDD
Duplex Spacing:	WCDMA Band II:80MHz WCDMA Band IV:400MHz WCDMA Band V:45MHz
Antenna Type:	IFA + Monopole
Antenna Gain:	W2: -1.4dBi W4: -1.4dBi W5: -2.5dBi ERP = EIRP(Power+Gain) – 2.15 (dB)
Power Supply:	Charger
Software Revision:	MyOS11.0.0_8045_GEN_PE
Hardware Revision:	ZTE 8045HW1.0
IMEI:	864341060000976 864341060000901

2.2 Support Equipment

The following support equipment was used to exercise the DUT during testing:N/A

3 REFERENCE SPECIFICATION

Specification	Version	Title
FCC Part2	2020	Frequency allocations and radio treaty matters; general rules and regulations
FCC Part22	2020	Public mobile services
FCC Part24	2020	Personal communications services
FCC Part27	2020	Miscellaneous wireless communications services
ANSI C63.26	2015	American national standard for compliance testing of transmitters used in licensed radio services
KDB 971168 D01	April 9, 2018	Measurement guidance for certification of licensed digital transmitters
TIA-603-E-2016	March 2016	Land Mobile FM or PM Communications Equipment Measurement and Performance Standards


4 KEY TO NOTES AND RESULT CODES

The following are the definition of the test result.

Code	Meaning
PASS	Test result shows that the requirements of the relevant specification have been met.
FAIL	Test result shows that the requirements of the relevant specification have not been met.
NT	Normal Temperature
NV	Nominal voltage
HV	High voltage
LV	Low voltage

5 RESULT SUMMARY

No.	Test case	FCC reference	Verdict
1	RF Power Output	2.1046	Pass
2	Effective Radiated Power and Effective Isotropic Radiated Power	22.913(a),24.232(c),27.50(d)(4)	Pass
3	Occupied Bandwidth	2.1049	Pass
4	Emission Bandwidth	2.1049	Pass
5	Spurious Emissions at antenna terminal	2.1051,22.917(a),24.238(a),27.53(h)	Pass
6	Band Edges Compliance	2.1051,22.917(a),24.238(b),27.53(h)	Pass
7	Frequency Stability	2.1055,22.355,24.235,27.54	Pass
8	Radiated Spurious Emissions	2.1053,22.917(a),24.238(a),27.53(h)	Pass
9	Peak-Average Ratio	24.232(d),27.50(d) (5)	Pass


This Test Report Is Issued by: Mr. Peng Zhen 	Checked by: Mr. Li Bin 
Tested by: Mr. Du Wei 	Issued date: 20220425

6 TEST RESULT

6.1 RF Power Output

Rule Part(s):
2.1046

Test Setup:



Test procedure:

After a radio link has been established between EUT and Tester, the output power of the cell signal of the testing equipment will be decreased until the output power of the EUT reach a maximum value. Then the test data can be read at the tester screen. The loss between RF output port of the EUT and the input port of the tester will be taken into consideration. The measurement will be conducted at three channels (Low, middle and High channels).

Limits: Limits: No specific conduct power requirements in part 2.1046.

Test result:


The test results are shown in Appendix A.

6.2 Effective Radiated Power and Effective Isotropic Radiated Power

Rule Part(s):

FCC: 22.913(a) (5), 24.232(c), 27.50(d) (4)

Test setup:



Test procedure:

KDB 971168 D01 v03r01 – Section 5.6

Test Settings

Subclause 5.2.5.5 of ANSI C63.26-2015 is applicable, along with the following provisions. For personal/portable radios utilizing an integral antenna, the factor LC is typically negligible. However, in a fixed station transmit system that utilizes a long cable run between the transmitter and the transmitting antenna, this factor can be significant. The minimum cable loss should be used in this equation.

The relevant equation for determining the ERP or EIRP from the conducted RF output power measured is:

$$\text{ERP/EIRP} = \text{PMeas} - \text{LC} + \text{GT}$$

Where:

ERP/EIRP = effective or equivalent radiated power, respectively (expressed in the same units as PMeas, typically dBW or dBm)

PMeas = measured transmitter output power or PSD, in dBW or dBm

LC = signal attenuation in the connecting cable between the transmitter and antenna in dB

GT = gain of the transmitting antenna, in dBd (ERP) or dBi (EIRP)

ERP/EIRP LIMIT

This value is EIRP since the measurement is calibrated using an antenna of known gain (2.15dB) and known input power. ERP can be calculated from EIRP by subtracting the gain of the dipole, $\text{ERP} = \text{EIRP} - 2.15 \text{ (dB)}$.

22.913(a) (5)

The ERP of mobile transmitters and auxiliary test transmitters must not exceed 7 watts.

24.232(c)

Mobile and portable stations are limited to 2 watts EIRP and the equipment must employ a means for limiting power to the minimum necessary for successful communications.

27.50(d) (4)

Fixed, mobile, and portable (hand-held) stations operating in the 1710-1755 MHz band and mobile and portable stations operating in the 1695-1710 MHz and 1755-1780 MHz bands are limited to 1 watt EIRP. Fixed stations operating in the 1710-1755 MHz band are limited to a maximum antenna height of 10 meters above ground. Mobile and portable stations operating in these bands must employ a means for limiting power to the minimum necessary for successful communications


Test result:

The test results are shown in Appendix A.

6.3 Occupied Bandwidth

Rule Part(s):
FCC: 2.1049

Test Setup:



Test procedure:
KDB 971168 D01 v03r01 – Section 4.2

Test Settings

1. The signal analyzer's automatic bandwidth measurement capability was used to perform the 99% occupied bandwidth and the 26dB bandwidth. The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.
2. RBW = 1 – 5% of the expected OBW
3. VBW $\geq 3 \times$ RBW
4. Detector = Peak
5. Trace mode = max hold
6. Sweep = auto couple
7. The trace was allowed to stabilize
8. If necessary, steps 2 – 7 were repeated after changing the RBW such that it would be within 1 – 5% of the 99% occupied bandwidth observed in Step 7

Limits: No specific occupied bandwidth requirements in part 2.1049


Test result:
The test results are shown in Appendix A.

6.4 Emission Bandwidth

Rule Part(s):

FCC: 2.1049

Test Setup:



Test procedure:

KDB 971168 D01 v03r01 – Section 4.2

Test Settings

1. The signal analyzer's automatic bandwidth measurement capability was used to perform the 26dB occupied bandwidth and the 26dB bandwidth. The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.
2. $RBW = 1 - 5\%$ of the expected OBW
3. $VBW \geq 3 \times RBW$
4. Detector = Peak
5. Trace mode = max hold
6. Sweep = auto couple
7. The trace was allowed to stabilize
8. If necessary, steps 2 – 7 were repeated after changing the RBW such that it would be within 1 – 5% of the emission bandwidth observed in Step 7

Limits: No specific occupied bandwidth requirements in part 2.1049

Test result:


The test results are shown in Appendix A.

6.5 Spurious Emissions at antenna terminal

Rule Part(s):

FCC: 2.1051, 22.917(a), 24.238(a), 27.53(h)

Test Setup:



Test procedure:

KDB 971168 D01 v03r01 – Section 6.0

Test Settings

1. Start frequency was set to 30MHz and stop frequency was set to 10GHz for Cell, 20GHz for PCS
2. RBW=100 kHz (For below 1GHz), 1MHz (For above 1GHz)
3. VBW $\geq 3 \times$ RBW
4. Detector = RMS
5. Trace mode = trace average for continuous emissions, max hold for pulse emissions
6. Sweep time = auto couple
7. The trace was allowed to stabilize

Limits:

The minimum permissible attenuation level of any spurious emission is $43 + \log_{10}(P_{\text{[Watts]}})$, where P is the transmitter power in Watts.

Test result:


The test results are shown in Appendix A.

6.6 Band Edges Compliance

Rule Part(s)

FCC: 2.1051, 22.917(a), 24.238(a), 27.53(c)

Test Setup:



Test procedure:

KDB 971168 D01 v03r01 – Section 6.0

Test Settings

1. Start and stop frequency were set such that the band edge would be placed in the center of the plot
2. Span=2MHz
3. RBW > 1% of the emission bandwidth
4. VBW > 3 x RBW
5. Detector = RMS
6. Number of sweep points $\geq 2 \times \text{Span}/\text{RBW}$
7. Trace mode = trace average for continuous emissions, max hold for pulse emissions
8. Sweep time = auto couple
9. The trace was allowed to stabilize

Limit: The minimum permissible attenuation level of any spurious emission is $43 + \log_{10}(P)$ [Watts], where P is the transmitter power in Watts.

Test result:


The test results are shown in Appendix A.

6.7 Frequency Stability

Rule Part(s)

FCC: 2.1055, 22.355, 24.235, 27.54

Test setup:



Test Procedure:

ANSI/TIA-603-E-2016

Test Settings

1. The carrier frequency of the transmitter is measured at room temperature (20°C to provide a reference).
2. The equipment is turned on in a “standby” condition for fifteen minutes before applying power to the transmitter. Measurement of the carrier frequency of the transmitter is made within one minute after applying power to the transmitter.
3. Frequency measurements are made at 10°C intervals ranging from -30°C to +50°C (The temperature range can be declared by the manufacturer). A period of at least one half-hour is provided to allow stabilization of the equipment at each temperature level.

Limits: For Part 22, the frequency stability of the transmitter shall be maintained within $\pm 0.00025\%$ (± 2.5 ppm) of the center frequency. For Part 24, the frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block.

Test result:


The test results are shown in Appendix A.

6.8 Radiated Spurious Emissions

Rule Part(s)

FCC: 2.1053, 22.917(a), 24.238(a), 27.53(h)

Test Setup:



Test procedure:

The measurements procedures in TIA-603-E-2016 are used.

The spectrum was scanned from 30MHz to the 10th harmonic of the highest frequency generated within the equipment.

Step 1:

The measurement is carried out in the chamber. EUT was placed on a 0.8m ($f < 1\text{GHz}$)/ 1.5m ($f > 1\text{GHz}$) high non-conductive table at a 3 meters test distance from the test receive antenna. A receiving antenna was placed on the antenna mast 3 meters from the EUT. The

height of receiving antenna from 1m to 4m and varies in certain range to find the maximum power value. A radio link shall be established between EUT and Tester. The output power of the cell signal of the tester will be decreased until the output power of the EUT reach a maximum value. A peak detector is used and RBW is set to 100 kHz ($f < 1\text{GHz}$)/1MHz ($f > 1\text{GHz}$). The antenna shall be performed under horizontal and vertical polarization. The turn table shall be rotated from 0 to 360 degrees for detecting the maximum power value on spectrum analyzer or receiver. The spectrum analyzer scans from 30MHz to 10th harmonic of the carrier. A notch filter is necessary in the band near to the carrier frequency. A high pass filter is needed to avoid the distortion of the testing equipment in the band above the carrier frequency.

Step 2:

A log-periodic antenna or double-ridged waveguide horn antenna shall be substituted in place of the EUT. The log-periodic antenna will be driven by a signal generator and the level will be adjusted till the same power value on the spectrum analyzer or receiver. The level of the spurious emissions can be calculated through the level of the signal generator, cable loss, the gain of the substitution antenna and the reading of the spectrum analyzer or receiver.

A power (P_{mea}) is applied to the input of the substitution antenna, and adjusts the level of the signal generator output until the value of the receiver reach the previously recorded (P_r). The power of signal source (P_{mea}) is recorded. The test should be performed by rotating the test item and adjusting the receiving antenna polarization.

A “reference path loss” should be calculated after test. The attenuation of “reference path loss” is the cable loss between the Signal Source with the Substitution Antenna (P_{ca}) and the Substitution Antenna Gain (G_a).

Calculation procedure:

The data of cable loss and antenna gain has been calibrated in full testing frequency range before the testing.

The power of the Radiated Spurious Emissions is calculated by adding the cable loss and antenna gain. The basic equation with a sample calculation is as followed:

$$\text{Power (EIRP)} = P_{\text{mea}} + P_{\text{ca}} + G_a$$

This value is EIRP since the measurement is calibrated using an antenna of known gain (2.15dB) and known input power. ERP can be calculated from EIRP by subtracting the gain of the dipole, $\text{ERP} = \text{EIRP} - 2.15 \text{ (dB)}$.

Assumed the power of signal source record is -20dBm. A cable loss of -30dB, and an antenna gain of 11dB are added.

$$P = P_{\text{mea}} + P_{\text{ca}} + G_a = (-20\text{dBm}) + (-30\text{dB}) + (11\text{dB}) = -39\text{dBm}$$

Note: We tested both horizontal and vertical polarization, but only the largest numerical polarity of the two polarities was recorded in the final report.

Test result:


The test results are shown in Appendix B.

6.9 Peak-Average Ratio

Rule Part(s)

FCC: 24.232(d), 27.50(d) (5)

Test Setup:



Test procedure:

KDB 971168 D01 v03r01 – Section 5.7.1

Test settings:

1. The signal analyzer's CCDF measurement profile is enabled
2. Frequency = carrier center frequency
3. Measurement BW > Emission bandwidth of signal
4. The signal analyzer was set to collect one million samples to generate the CCDF curve
5. The measurement interval was set depending on the type of signal analyzed. For continuous signals (>98% duty cycle), the measurement interval was set to 1ms. For burst transmissions, the spectrum analyzer is set to use an internal "RF Burst" trigger that is synced with an incoming pulse and the measurement interval is set to less than the duration of the "on time" of one burst to ensure that energy is only captured during a time in which the transmitter is operating at maximum power

Limits: the peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.

Test result:

The test results are shown in Appendix A

7 MEASUREMENT UNCERTAINTIES

Items	Uncertainty	
RF Power Output	0.6 dB	
Effective Radiated Power and Effective Isotropic Radiated Power	0.6 dB	
Occupied Bandwidth	3kHz	
Emission Bandwidth	3kHz	
Peak-Average Ratio	0.8dB	
Frequency Stability	48Hz	
Band Edges Compliance	1.2dB	
Spurious Emissions at antenna terminal	9kHz~2GHz	1.2dB
	2G~3.6GHz	1.4dB
	3.6G~8GHz	2.2dB
	8G~12.75GHz	2.7dB
Radiated Emission Measurement	30MHz~200MHz	4.88dB
	200MHz~1GHz	4.87dB
	1GHz~18GHz	4.58dB
	18GHz~40GHz	4.35dB

8 TEST EQUIPMENTS

No.	Name/Model	Manufacturer	S/N	Calibration Date	Calibration Due Date
1	Mobile Station Tester / MT8820C	Anritsu	6201300660	2021.06.21	2022.06.20
2	Radio Communication Station / CMW500	R&S	161702	2021.06.21	2022.06.20
3	Spectrum Analyzer / FSV40	R&S	101065	2021.06.21	2022.06.20
4	Spectrum Analyzer / N9020A	Agilent	MY48010771	2021.05.18	2022.05.17
5	Power Divider / 11667A	HP	19632	2021.06.21	2022.06.20
6	DC Power Supply / E3645A	Agilent	MY40000741	2022.04.22	2023.04.21
7	Temperature chamber / SH241	ESPEC	92013758	2021.06.21	2022.06.20
8	Fully-Anechoic Chamber / 12.65m×8.03m×7.50m	FRANKONIA	-----	-----	-----
9	Semi-Anechoic/Chamber / 23.18m×16.88m×9.60m	FRANKONIA	---	-----	-----
10	Turn table Diameter:1m	FRANKONIA	-----	-----	-----
11	Turn table Diameter:5m	FRANKONIA	-----	-----	-----
12	Antenna master FAC(MA4.0)	MATURO	-----	-----	-----
13	Antenna master SAC(MA4.0)	MATURO	-----	-----	-----
14	Shielding room / 9.080m×5.255m×3.525m	FRANKONIA	-----	-----	-----
15	Double-Ridged Waveguide Horn Antenna / HF 907	R&S	100512	2021.06.21	2022.06.20
16	Double-Ridged Waveguide Horn Antenna / HF 907	R&S	100513	2021.06.21	2022.06.20
17	Ultra log antenna / HL562	R&S	100016	2021.06.21	2022.06.20
18	Receive antenna /3160-09	SCHWARZ-BECK	002058-002	2021.06.21	2022.06.20
19	EMI test receiver / ESI 40	R&S	100015	2021.06.21	2022.06.20
20	EMI test receiver / ESCS30	R&S	100029	2021.06.21	2022.06.20
21	Receive antenna / HL562	R&S	100167	2021.06.21	2022.06.20
22	AMN / ENV216	R&S	3560.6550.12	2021.06.21	2022.06.20

APPENDIX A – TEST DATA OF CONDUCTED EMISSION

WCDMA band II

1. RF Power Output

WCDMA band II

Mode		Carrier frequency (MHz)	Channel No.	RF Power Output (dBm)
Release 99	RMC,12.2kbps	1852.4	9262	23.76
Release 99	RMC,12.2kbps	1880	9400	23.82
Release 99	RMC,12.2kbps	1907.6	9538	23.81

Mode		Carrier frequency (MHz)	Channel No.	RF Power Output (dBm)
HSDPA	Subtest1	1852.4	9262	23.72
HSDPA	Subtest1	1880	9400	23.82
HSDPA	Subtest1	1907.6	9538	23.65
HSDPA	Subtest2	1852.4	9262	23.3
HSDPA	Subtest2	1880	9400	23.43
HSDPA	Subtest2	1907.6	9538	23.24
HSDPA	Subtest3	1852.4	9262	22.38
HSDPA	Subtest3	1880	9400	22.57
HSDPA	Subtest3	1907.6	9538	22.46
HSDPA	Subtest4	1852.4	9262	23.08
HSDPA	Subtest4	1880	9400	23.2
HSDPA	Subtest4	1907.6	9538	23.07

Mode		Carrier frequency (MHz)	Channel No.	RF Power Output (dBm)
HSUPA	Subtest1	1852.4	9262	21.06
HSUPA	Subtest1	1880	9400	21.23
HSUPA	Subtest1	1907.6	9538	21.24
HSUPA	Subtest2	1852.4	9262	21.78
HSUPA	Subtest2	1880	9400	22.04
HSUPA	Subtest2	1907.6	9538	21.98
HSUPA	Subtest3	1852.4	9262	21.79
HSUPA	Subtest3	1880	9400	22.01
HSUPA	Subtest3	1907.6	9538	21.97
HSUPA	Subtest4	1852.4	9262	21.64
HSUPA	Subtest4	1880	9400	21.81
HSUPA	Subtest4	1907.6	9538	21.79
HSUPA	Subtest5	1852.4	9262	23.57
HSUPA	Subtest5	1880	9400	23.68
HSUPA	Subtest5	1907.6	9538	23.52

2. Occupied Bandwidth

WCDMA band II


Mode	Carrier frequency (MHz)	Channel No.	Bandwidth of 99% Power (MHz)
Release 99	1852.4	9262	4.16
Release 99	1880	9400	4.15
Release 99	1907.6	9538	4.15


Mode	Carrier frequency (MHz)	Channel No.	Bandwidth of 99% Power (MHz)
HSDPA	1852.4	9262	4.15
HSDPA	1880	9400	4.15
HSDPA	1907.6	9538	4.14

Mode	Carrier frequency (MHz)	Channel No.	Bandwidth of 99% Power (MHz)
HSUPA	1852.4	9262	4.13
HSUPA	1880	9400	4.14
HSUPA	1907.6	9538	4.14

WCDMA band II


Test Mode: Release 99






Channel 9538


Test Mode: HSDPA



Channel 9262




Channel 9400



Channel 9538

Test Mode: HSUPA



3. Emission Bandwidth


WCDMA band II

Mode	Carrier frequency (MHz)	Channel No.	Bandwidth of -26dBc Power (MHz)
Release 99	1852.4	9262	4.64
Release 99	1880	9400	4.65
Release 99	1907.6	9538	4.64


Mode	Carrier frequency (MHz)	Channel No.	Bandwidth of -26dBc Power (MHz)
HSDPA	1852.4	9262	4.66
HSDPA	1880	9400	4.62
HSDPA	1907.6	9538	4.61


Mode	Carrier frequency (MHz)	Channel No.	Bandwidth of -26dBc Power (MHz)
HSUPA	1852.4	9262	4.62
HSUPA	1880	9400	4.62
HSUPA	1907.6	9538	4.63

WCDMA band II
Test Mode: Release 99




Test Mode: HSDPA






Channel 9538


Test Mode: HSUPA



Channel 9262



Channel 9400




Channel 9538

4. Spurious Emissions at antenna terminal


WCDMA band II

Test Mode: Release 99




Note: The signal beyond the limit is the signal transmitted by EUT.

Test Mode: HSDPA



Note: The signal beyond the limit is the signal transmitted by EUT.

Test Mode: HSUPA




Note: The signal beyond the limit is the signal transmitted by EUT.


5. Band Edges Compliance

WCDMA band II


Test Mode: Release 99



Test Mode: HSDPA



Test Mode: HSUPA



6. Frequency Stability

WCDMA band II

Test Mode: Release 99

Name	Temperature(°C)	Test Result (ppm)@NV		
		Channel 9262	Channel 9400	Channel 9538
Release 99	-20	0.000	-0.009	-0.012
Release 99	-10	0.020	0.007	-0.026
Release 99	-0	0.032	-0.025	-0.006
Release 99	+10	-0.018	0.040	-0.012
Release 99	+20	-0.015	-0.003	-0.012
Release 99	+30	-0.003	0.035	-0.025
Release 99	+40	-0.016	-0.027	0.038
Release 99	+50	0.034	-0.021	-0.001
Release 99	+55	-0.030	-0.011	0.035
Name	Voltage	Test Result (ppm)@NT		
		Channel 9262	Channel 9400	Channel 9538
Release 99	LV	0.009	0.018	-0.001
Release 99	HV	0.033	-0.010	-0.008

Test Mode: HSDPA

Name	Temperature(°C)	Test Result (ppm)@NV		
		Channel 9262	Channel 9400	Channel 9538
Subtest1	-20	0.039	-0.025	-0.032
Subtest1	-10	-0.008	0.003	-0.025
Subtest1	-0	-0.032	-0.027	0.026
Subtest1	+10	0.002	-0.003	0.024
Subtest1	+20	0.010	0.021	-0.017
Subtest1	+30	0.027	-0.017	0.008
Subtest1	+40	0.010	0.026	-0.028
Subtest1	+50	0.010	0.032	0.019
Subtest1	+55	0.024	0.030	0.018
Name	Voltage	Test Result (ppm)@NT		
		Channel 9262	Channel 9400	Channel 9538
Subtest1	LV	-0.013	0.039	0.041
Subtest1	HV	0.044	0.010	0.019


Test Mode: HSUPA

Name	Temperature(°C)	Test Result (ppm)@NV		
		Channel 9262	Channel 9400	Channel 9538
Subtest1	-20	0.007	0.029	0.015
Subtest1	-10	0.033	-0.006	-0.032
Subtest1	-0	-0.024	0.000	0.033
Subtest1	+10	-0.013	-0.026	-0.025
Subtest1	+20	0.012	0.033	0.001
Subtest1	+30	-0.034	-0.004	0.027
Subtest1	+40	-0.028	-0.009	-0.025
Subtest1	+50	-0.003	0.015	0.009
Subtest1	+55	0.027	-0.034	-0.026
Name	Voltage	Test Result (ppm)@NT		
		Channel 9262	Channel 9400	Channel 9538
Subtest1	LV	-0.012	-0.021	-0.029
Subtest1	HV	0.025	0.008	0.030


7. Peak-Average Ratio

WCDMA band II

Test Mode: Release 99




Test Mode: HSDPA



Test Mode: HSUPA





8. Effective Radiated Power and Effective Isotropic Radiated Power WCDMA band II

Mode		Carrier frequency (MHz)	Channel No.	Conducted Power (dBm)	ERP/EIRP (dBm)	ERP/EIRP (W)
Release 99	RMC, 12.2kbps	1852.4	9262	23.76	22.36	0.172
Release 99	RMC, 12.2kbps	1880	9400	23.82	22.42	0.175
Release 99	RMC, 12.2kbps	1907.6	9538	23.81	22.41	0.174
Mode		Carrier frequency (MHz)	Channel No.	Conducted Power (dBm)	ERP/EIRP (dBm)	ERP/EIRP (W)
HSDPA	Subtest1	1852.4	9262	23.72	22.32	0.171
HSDPA	Subtest1	1880	9400	23.82	22.42	0.175
HSDPA	Subtest1	1907.6	9538	23.65	22.25	0.168
HSDPA	Subtest2	1852.4	9262	23.3	21.90	0.155
HSDPA	Subtest2	1880	9400	23.43	22.03	0.160
HSDPA	Subtest2	1907.6	9538	23.24	21.84	0.153
HSDPA	Subtest3	1852.4	9262	22.38	20.98	0.125
HSDPA	Subtest3	1880	9400	22.57	21.17	0.131
HSDPA	Subtest3	1907.6	9538	22.46	21.06	0.128
HSDPA	Subtest4	1852.4	9262	23.08	21.68	0.147
HSDPA	Subtest4	1880	9400	23.2	21.80	0.151
HSDPA	Subtest4	1907.6	9538	23.07	21.67	0.147
Mode		Carrier frequency (MHz)	Channel No.	Conducted Power (dBm)	ERP/EIRP (dBm)	ERP/EIRP (W)
HSUPA	Subtest1	1852.4	9262	21.06	19.66	0.092
HSUPA	Subtest1	1880	9400	21.23	19.83	0.096
HSUPA	Subtest1	1907.6	9538	21.24	19.84	0.096
HSUPA	Subtest2	1852.4	9262	21.78	20.38	0.109
HSUPA	Subtest2	1880	9400	22.04	20.64	0.116
HSUPA	Subtest2	1907.6	9538	21.98	20.58	0.114
HSUPA	Subtest3	1852.4	9262	21.79	20.39	0.109
HSUPA	Subtest3	1880	9400	22.01	20.61	0.115
HSUPA	Subtest3	1907.6	9538	21.97	20.57	0.114

HSUPA	Subtest4	1852.4	9262	21.64	20.24	0.106
HSUPA	Subtest4	1880	9400	21.81	20.41	0.110
HSUPA	Subtest4	1907.6	9538	21.79	20.39	0.109
HSUPA	Subtest5	1852.4	9262	23.57	22.17	0.165
HSUPA	Subtest5	1880	9400	23.68	22.28	0.169
HSUPA	Subtest5	1907.6	9538	23.52	22.12	0.163

WCDMA band IV

1. RF Power Output

WCDMA band IV

Mode		Carrier frequency (MHz)	Channel No.	RF Power Output (dBm)
Release 99	RMC,12.2kbps	1712.4	1312	24.1
Release 99	RMC,12.2kbps	1732.6	1412	23.97
Release 99	RMC,12.2kbps	1752.6	1513	23.74

Mode		Carrier frequency (MHz)	Channel No.	RF Power Output (dBm)
HSDPA	Subtest1	1712.4	1312	24.15
HSDPA	Subtest1	1732.6	1412	23.87
HSDPA	Subtest1	1752.6	1513	23.81
HSDPA	Subtest2	1712.4	1312	24.04
HSDPA	Subtest2	1732.6	1412	23.76
HSDPA	Subtest2	1752.6	1513	23.7
HSDPA	Subtest3	1712.4	1312	23.97
HSDPA	Subtest3	1732.6	1412	23.71
HSDPA	Subtest3	1752.6	1513	23.66
HSDPA	Subtest4	1712.4	1312	23.98
HSDPA	Subtest4	1732.6	1412	23.73
HSDPA	Subtest4	1752.6	1513	23.66

Mode		Carrier frequency (MHz)	Channel No.	RF Power Output (dBm)
HSUPA	Subtest1	1712.4	1312	23.55
HSUPA	Subtest1	1732.6	1412	22.97
HSUPA	Subtest1	1752.6	1513	23.18
HSUPA	Subtest2	1712.4	1312	23.81
HSUPA	Subtest2	1732.6	1412	23.42
HSUPA	Subtest2	1752.6	1513	23.65
HSUPA	Subtest3	1712.4	1312	23.93
HSUPA	Subtest3	1732.6	1412	23.65
HSUPA	Subtest3	1752.6	1513	23.65
HSUPA	Subtest4	1712.4	1312	23.7
HSUPA	Subtest4	1732.6	1412	23.48
HSUPA	Subtest4	1752.6	1513	23.45
HSUPA	Subtest5	1712.4	1312	24.02
HSUPA	Subtest5	1732.6	1412	23.7
HSUPA	Subtest5	1752.6	1513	23.77

2. Occupied Bandwidth

WCDMA band IV


Mode	Carrier frequency (MHz)	Channel No.	Bandwidth of 99% Power (MHz)
Release 99	1712.4	1312	4.14
Release 99	1732.6	1412	4.14
Release 99	1752.6	1513	4.16


Mode	Carrier frequency (MHz)	Channel No.	Bandwidth of 99% Power (MHz)
HSDPA	1712.4	1312	4.15
HSDPA	1732.6	1412	4.14
HSDPA	1752.6	1513	4.16

Mode	Carrier frequency (MHz)	Channel No.	Bandwidth of 99% Power (MHz)
HSUPA	1712.4	1312	4.14
HSUPA	1732.6	1412	4.15
HSUPA	1752.6	1513	4.14

WCDMA band IV


Test Mode: Release 99






Channel 1513


Test Mode: HSDPA



Channel 1312




Channel 1412



Channel 1513

Test Mode: HSUPA



3. Emission Bandwidth


WCDMA band IV

Mode	Carrier frequency (MHz)	Channel No.	Bandwidth of -26dBc Power (MHz)
Release 99	1712.4	1312	4.64
Release 99	1732.6	1412	4.63
Release 99	1752.6	1513	4.63


Mode	Carrier frequency (MHz)	Channel No.	Bandwidth of -26dBc Power (MHz)
HSDPA	1712.4	1312	4.62
HSDPA	1732.6	1412	4.62
HSDPA	1752.6	1513	4.63


Mode	Carrier frequency (MHz)	Channel No.	Bandwidth of -26dBc Power (MHz)
HSUPA	1712.4	1312	4.63
HSUPA	1732.6	1412	4.61
HSUPA	1752.6	1513	4.62

WCDMA band IV
Test Mode: Release 99




Test Mode: HSDPA






Channel 1513


Test Mode: HSUPA



Channel 1312



Channel 1412




Channel 1513

4. Spurious Emissions at antenna terminal


WCDMA band IV

Test Mode: Release 99




Note: The signal beyond the limit is the signal transmitted by EUT.

Test Mode: HSDPA



Note: The signal beyond the limit is the signal transmitted by EUT.

Test Mode: HSUPA




Note: The signal beyond the limit is the signal transmitted by EUT.


5. Band Edges Compliance

WCDMA band IV


Test Mode: Release 99



Test Mode: HSDPA



Test Mode: HSUPA



6. Frequency Stability

WCDMA band IV

Test Mode: Release 99

Name	Temperature(°C)	Test Result (ppm)@NV		
		Channel 1312	Channel 1412	Channel 1513
Release 99	-20	-0.009	0.067	-0.058
Release 99	-10	-0.058	-0.035	-0.021
Release 99	-0	-0.043	0.062	0.036
Release 99	+10	0.026	-0.052	-0.033
Release 99	+20	-0.033	-0.029	-0.023
Release 99	+30	0.016	-0.020	0.050
Release 99	+40	0.030	-0.048	-0.017
Release 99	+50	0.044	0.010	0.052
Release 99	+55	-0.058	0.044	0.024
Name	Voltage	Test Result (ppm)@NT		
		Channel 1312	Channel 1412	Channel 1513
Release 99	LV	0.021	-0.030	-0.017
Release 99	HV	-0.039	-0.014	0.060

Test Mode: HSDPA

Name	Temperature(°C)	Test Result (ppm)@NV		
		Channel 1312	Channel 1412	Channel 1513
Subtest1	-20	0.069	-0.009	0.008
Subtest1	-10	-0.056	0.013	0.067
Subtest1	-0	-0.041	0.065	0.027
Subtest1	+10	0.064	0.059	-0.048
Subtest1	+20	0.007	0.025	-0.019
Subtest1	+30	-0.051	-0.037	0.040
Subtest1	+40	-0.002	-0.058	-0.021
Subtest1	+50	0.007	-0.042	0.056
Subtest1	+55	0.051	-0.054	0.034
Name	Voltage	Test Result (ppm)@NT		
		Channel 1312	Channel 1412	Channel 1513
Subtest1	LV	-0.045	-0.028	0.026
Subtest1	HV	-0.047	-0.012	0.037


Test Mode: HSUPA

Name	Temperature(°C)	Test Result (ppm)@NV		
		Channel 1312	Channel 1412	Channel 1513
Subtest1	-20	-0.045	0.036	-0.013
Subtest1	-10	-0.034	0.061	-0.025
Subtest1	-0	0.015	0.000	-0.031
Subtest1	+10	-0.052	0.056	-0.015
Subtest1	+20	-0.031	-0.022	-0.002
Subtest1	+30	0.051	-0.042	0.005
Subtest1	+40	0.013	0.055	-0.031
Subtest1	+50	0.060	0.010	-0.002
Subtest1	+55	-0.017	-0.045	0.052
Name	Voltage	Test Result (ppm)@NT		
		Channel 1312	Channel 1412	Channel 1513
Subtest1	LV	-0.046	0.054	0.048
Subtest1	HV	0.013	-0.016	-0.024


7. Peak-Average Ratio

WCDMA band IV


Test Mode: Release 99




Test Mode: HSDPA



Channel 1312




Channel 1412




Channel 1513


Test Mode: HSUPA



Channel 1312



Channel 1412



8. Effective Radiated Power and Effective Isotropic Radiated Power

WCDMA band IV

Mode		Carrier frequency (MHz)	Channel No.	Conducted Power (dBm)	ERP/EIRP (dBm)	ERP/EIRP (W)
Release 99	RMC, 12.2kbps	1712.4	1312	24.1	22.70	0.186
Release 99	RMC, 12.2kbps	1732.6	1412	23.97	22.57	0.181
Release 99	RMC, 12.2kbps	1752.6	1513	23.74	22.34	0.171
Mode		Carrier frequency (MHz)	Channel No.	Conducted Power (dBm)	ERP/EIRP (dBm)	ERP/EIRP (W)
HSDPA	Subtest1	1712.4	1312	24.15	22.75	0.188
HSDPA	Subtest1	1732.6	1412	23.87	22.47	0.177
HSDPA	Subtest1	1752.6	1513	23.81	22.41	0.174
HSDPA	Subtest2	1712.4	1312	24.04	22.64	0.184
HSDPA	Subtest2	1732.6	1412	23.76	22.36	0.172
HSDPA	Subtest2	1752.6	1513	23.7	22.30	0.170
HSDPA	Subtest3	1712.4	1312	23.97	22.57	0.181
HSDPA	Subtest3	1732.6	1412	23.71	22.31	0.170
HSDPA	Subtest3	1752.6	1513	23.66	22.26	0.168
HSDPA	Subtest4	1712.4	1312	23.98	22.58	0.181
HSDPA	Subtest4	1732.6	1412	23.73	22.33	0.171
HSDPA	Subtest4	1752.6	1513	23.66	22.26	0.168
Mode		Carrier frequency (MHz)	Channel No.	Conducted Power (dBm)	ERP/EIRP (dBm)	ERP/EIRP (W)
HSUPA	Subtest1	1712.4	1312	23.55	22.15	0.164
HSUPA	Subtest1	1732.6	1412	22.97	21.57	0.144
HSUPA	Subtest1	1752.6	1513	23.18	21.78	0.151
HSUPA	Subtest2	1712.4	1312	23.81	22.41	0.174
HSUPA	Subtest2	1732.6	1412	23.42	22.02	0.159
HSUPA	Subtest2	1752.6	1513	23.65	22.25	0.168
HSUPA	Subtest3	1712.4	1312	23.93	22.53	0.179
HSUPA	Subtest3	1732.6	1412	23.65	22.25	0.168
HSUPA	Subtest3	1752.6	1513	23.65	22.25	0.168

HSUPA	Subtest4	1712.4	1312	23.7	22.30	0.170
HSUPA	Subtest4	1732.6	1412	23.48	22.08	0.161
HSUPA	Subtest4	1752.6	1513	23.45	22.05	0.160
HSUPA	Subtest5	1712.4	1312	24.02	22.62	0.183
HSUPA	Subtest5	1732.6	1412	23.7	22.30	0.170
HSUPA	Subtest5	1752.6	1513	23.77	22.37	0.173

1. RF Power Output

WCDMA band V

Mode		Carrier frequency (MHz)	Channel No.	RF Power Output (dBm)
Release 99	RMC,12.2kbps	826.4	4132	24.25
Release 99	RMC,12.2kbps	836.6	4183	24.14
Release 99	RMC,12.2kbps	846.6	4233	24.13

Mode		Carrier frequency (MHz)	Channel No.	RF Power Output (dBm)
HSDPA	Subtest1	826.4	4132	23.60
HSDPA	Subtest1	836.6	4183	23.33
HSDPA	Subtest1	846.6	4233	23.18
HSDPA	Subtest2	826.4	4132	23.23
HSDPA	Subtest2	836.6	4183	22.97
HSDPA	Subtest2	846.6	4233	22.84
HSDPA	Subtest3	826.4	4132	22.85
HSDPA	Subtest3	836.6	4183	22.72
HSDPA	Subtest3	846.6	4233	22.61
HSDPA	Subtest4	826.4	4132	22.79
HSDPA	Subtest4	836.6	4183	22.61
HSDPA	Subtest4	846.6	4233	22.50

Mode		Carrier frequency (MHz)	Channel No.	RF Power Output (dBm)
HSUPA	Subtest1	826.4	4132	21.64
HSUPA	Subtest1	836.6	4183	21.57
HSUPA	Subtest1	846.6	4233	21.27
HSUPA	Subtest2	826.4	4132	22.11
HSUPA	Subtest2	836.6	4183	21.98
HSUPA	Subtest2	846.6	4233	21.83
HSUPA	Subtest3	826.4	4132	22.05
HSUPA	Subtest3	836.6	4183	21.84
HSUPA	Subtest3	846.6	4233	21.75
HSUPA	Subtest4	826.4	4132	21.51
HSUPA	Subtest4	836.6	4183	21.42
HSUPA	Subtest4	846.6	4233	21.16
HSUPA	Subtest5	826.4	4132	23.75
HSUPA	Subtest5	836.6	4183	23.49
HSUPA	Subtest5	846.6	4233	23.39

2. Occupied Bandwidth

WCDMA band V


Mode	Carrier frequency (MHz)	Channel No.	Bandwidth of 99% Power (MHz)
Release 99	826.4	4132	4.15
Release 99	836.6	4183	4.15
Release 99	846.6	4233	4.14


Mode	Carrier frequency (MHz)	Channel No.	Bandwidth of 99% Power (MHz)
HSDPA	826.4	4132	4.15
HSDPA	836.6	4183	4.15
HSDPA	846.6	4233	4.13

Mode	Carrier frequency (MHz)	Channel No.	Bandwidth of 99% Power (MHz)
HSUPA	826.4	4132	4.15
HSUPA	836.6	4183	4.14
HSUPA	846.6	4233	4.14

WCDMA band V


Test Mode: Release 99






Channel 4233


Test Mode: HSDPA



Channel 4132



Channel 4183



Channel 4233