

FCC RF Test Report

APPLICANT : ZTE CORPORATION
EQUIPMENT : CDMA LTE multi-mode Digital Mobile Phone
BRAND NAME : ZTE
MODEL NAME : ZTE N9516
FCC ID : SRQ-ZTEN9516
STANDARD : FCC Part 15 Subpart C §15.247
CLASSIFICATION : (DTS) Digital Transmission System

The product was received on Jun. 14, 2014 and testing was completed on Jul. 24, 2014. We, SPORTON INTERNATIONAL (KUNSHAN) INC., would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL (KUNSHAN) INC., the test report shall not be reproduced except in full.



Reviewed by: Joseph Lin / Supervisor



Approved by: Jones Tsai / Manager



SPORTON INTERNATIONAL (KUNSHAN) INC.
No. 3-2, PingXiang Road, Kunshan, Jiangsu Province, P.R.C.



TABLE OF CONTENTS

REVISION HISTORY.....	3
SUMMARY OF TEST RESULT	4
1 GENERAL DESCRIPTION	5
1.1 Applicant.....	5
1.2 Manufacturer.....	5
1.3 Product Feature of Equipment Under Test.....	5
1.4 Product Specification subjective to this standard	5
1.5 Modification of EUT	6
1.6 Testing Location	6
1.7 Applicable Standards.....	6
2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST	7
2.1 Carrier Frequency Channel	7
2.2 Pre-Scanned RF Power.....	8
2.3 Test Mode.....	9
2.4 Connection Diagram of Test System.....	10
2.5 Support Unit used in test configuration and system	11
2.6 EUT Operation Test Setup	11
2.7 Measurement Results Explanation Example.....	11
3 TEST RESULT.....	12
3.1 6dB Bandwidth Measurement	12
3.2 Output Power Measurement.....	14
3.3 Power Spectral Density Measurement	17
3.4 Conducted Band Edges and Spurious Emission Measurement	19
3.5 Radiated Band Edges and Spurious Emission Measurement	29
3.6 AC Conducted Emission Measurement.....	46
3.7 Antenna Requirements.....	51
4 LIST OF MEASURING EQUIPMENT	52
5 UNCERTAINTY OF EVALUATION	53
APPENDIX A. SETUP PHOTOGRAPHS	



REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR461401C	Rev. 01	Initial issue of report	Jul. 29, 2014

SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	15.247(a)(2)	6dB Bandwidth	$\geq 0.5\text{MHz}$	Pass	-
3.2	15.247(b)	Power Output Measurement	$\leq 30\text{dBm}$	Pass	-
3.3	15.247(e)	Power Spectral Density	$\leq 8\text{dBm}/3\text{kHz}$	Pass	-
3.4	15.247(d)	Conducted Band Edges	$\leq 20\text{dBc}$	Pass	-
		Conducted Spurious Emission		Pass	-
3.5	15.247(d)	Radiated Band Edges and Radiated Spurious Emission	15.209(a) & 15.247(d)	Pass	Under limit 7.87 dB at 47.460 MHz
3.6	15.207	AC Conducted Emission	15.207(a)	Pass	Under limit 10.98 dB at 0.670 MHz
3.7	15.203 & 15.247(b)	Antenna Requirement	N/A	Pass	-

1 General Description

1.1 Applicant

ZTE CORPORATION

ZTE Plaza, Keji Road South, Hi-Tech Industrial Park, Nanshan District, Shenzhen, Guangdong, 518057, P.R.China

1.2 Manufacturer

ZTE CORPORATION

ZTE Plaza, Keji Road South, Hi-Tech Industrial Park, Nanshan District, Shenzhen, Guangdong, 518057, P.R.China

1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	CDMA LTE multi-mode Digital Mobile Phone
Brand Name	ZTE
Model Name	ZTE N9516
FCC ID	SRQ-ZTEN9516
EUT supports Radios application	CDMA/EV-DO/LTE WLAN2.4GHz 802.11b/g/n HT20 Bluetooth v3.0+EDR Bluetooth v4.0 LE
HW Version	cxyB
SW Version	N9516V1.0.0B01
EUT Stage	Identical Prototype

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

1.4 Product Specification subjective to this standard

Product Specification subjective to this standard	
Tx/Rx Channel Frequency Range	802.11b/g/n : 2412 MHz ~ 2462 MHz
Maximum (Peak) Output Power to Antenna	802.11b : 18.56 dBm (0.0718 W) 802.11g : 20.92 dBm (0.1236 W) 802.11n HT20 : 19.92 dBm (0.0982 W)
Antenna Type	802.11b/g/n : PIFA Antenna with gain -0.16 dBi
Type of Modulation	802.11b : DSSS (DBPSK / DQPSK / CCK) 802.11g/n : OFDM (BPSK / QPSK / 16QAM / 64QAM)

1.5 Modification of EUT

No modifications are made to the EUT during all test items.

1.6 Testing Location

Test Site	SPORTON INTERNATIONAL (KUNSHAN) INC.			
Test Site Location	No. 3-2, PingXiang Road, Kunshan, Jiangsu Province, P.R.C. TEL: +86-0512-5790-0158 FAX: +86-0512-5790-0958			
Test Site No.	Sporton Site No.			FCC Registration No.
	TH01-KS	CO01-KS	03CH01-KS	149928

1.7 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC Part 15 Subpart C §15.247
- ♦ FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r02
- ♦ ANSI C63.4-2003

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

2 Test Configuration of Equipment Under Test

The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conducted emission (150 kHz to 30 MHz) and radiated emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases (Y plane) were recorded in this report.

The final configuration from all the combinations and the worst-case data rates were investigated by measuring the maximum power across all the data rates and modulation modes under section 2.2.

Based on the worst configuration found above, the RF power setting is set individually to meet FCC compliance limit for the final conducted and radiated tests shown in section 2.3.

2.1 Carrier Frequency Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
2400-2483.5 MHz	1	2412	7	2442
	2	2417	8	2447
	3	2422	9	2452
	4	2427	10	2457
	5	2432	11	2462
	6	2437	-	-

2.2 Pre-Scanned RF Power

Preliminary tests were performed in different data rate and data rate associated with the highest power were chosen for full test shown in the following tables.

2.4GHz 802.11b RF Output Power (dBm)						
Power vs. Channel			Power vs. Data Rate			
Channel	Frequency (MHz)	Data Rate 1Mbps	Channel	2Mbps	5.5Mbps	11Mbps
CH 01	2412 MHz	17.61	CH 06	18.34	18.33	18.17
CH 06	2437 MHz	18.56				
CH 11	2462 MHz	16.77				

2.4GHz 802.11g RF Output Power (dBm)										
Power vs. Channel			Power vs. Data Rate							
Channel	Frequency (MHz)	Data Rate 6Mbps	Channel	9Mbps	12Mbps	18Mbps	24Mbps	36Mbps	48Mbps	54Mbps
CH 01	2412 MHz	20.06	CH 06	20.82	20.65	20.87	20.91	20.78	20.89	20.85
CH 06	2437 MHz	20.92								
CH 11	2462 MHz	19.89								

2.4GHz 802.11n HT20 RF Output Power (dBm)										
Power vs. Channel			Power vs. MCS Index							
Channel	Frequency (MHz)	MCS Index MCS0	Channel	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7
CH 01	2412 MHz	18.65	CH 06	19.86	19.58	19.86	19.78	19.78	19.87	19.72
CH 06	2437 MHz	19.92								
CH 11	2462 MHz	18.71								


2.3 Test Mode

Final results of test modes, data rates and test channels are shown as following table.


Test Cases				
Conducted TCs	Test Items	Mode	Data Rate	Test Channel
	6dB BW Power Spectral Density	802.11b	1 Mbps	1/6/11
		802.11g	6 Mbps	1/6/11
		802.11n HT20	MCS0	1/6/11
	Output Power	802.11b	1 Mbps	1/6/11
		802.11g	6 Mbps	1/6/11
		802.11n HT20	MCS0	1/6/11
	Conducted Band Edge	802.11b	1 Mbps	1/11
		802.11g	6 Mbps	1/11
		802.11n HT20	MCS0	1/11
	Conducted Spurious Emission	802.11b	1 Mbps	1/6/11
		802.11g	6 Mbps	1/6/11
		802.11n HT20	MCS0	1/6/11
Radiated TCs	Radiated Band Edge	802.11b	1 Mbps	1/11
		802.11g	6 Mbps	1/11
		802.11n HT20	MCS0	1/11
	Radiated Spurious Emission	802.11b	1 Mbps	1/6/11
		802.11g	6 Mbps	1/6/11
		802.11n HT20	MCS0	1/6/11
AC Conducted Emission	Mode 1 : CDMA2000 BC0 Idle + Bluetooth Link + WLAN Link + USB Cable (Charging from Adapter)			

2.4 Connection Diagram of Test System

<WLAN Tx Mode>



<AC Conducted Emission Mode>



2.5 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	System Simulator	R&S	CMU 200	N/A	N/A	Unshielded, 1.8 m
2.	Notebook	Lenovo	G480	N/A	N/A	AC I/P: Unshielded, 0.8 m DC O/P: Shielded, 1.8 m
3.	Bluetooth Earphone	Nokia	BH-106	QTLBH-106	N/A	N/A
4.	WLAN AP	D-Link	DIR-855	KA2DIR855A2	N/A	Unshielded, 1.8m

2.6 EUT Operation Test Setup

For WLAN function, the engineering test program was provided and enabled to make EUT continuous transmit/receive.

For AC power line conducted emissions, the EUT was set to connect with the WLAN AP under large package sizes transmission.

2.7 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example :

The spectrum analyzer offset is derived from RF cable loss.

Offset = RF cable loss

Following shows an offset computation example with cable loss 6.0 dB.

$$\begin{aligned} \text{Offset(dB)} &= \text{RF cable loss(dB)} \\ &= 6.0(\text{dB}) \end{aligned}$$

3 Test Result

3.1 6dB Bandwidth Measurement

3.1.1 Limit of 6dB Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.


3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.1.3 Test Procedures

1. The testing follows FCC KDB Publication No. 558074 DTS D01 Meas. Guidance v03r02.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6 dB bandwidth must be greater than 500 kHz.
5. Measure and record the results in the test report.


3.1.4 Test Setup



3.1.5 Test Result of 6dB Bandwidth

Test Band :	2.4GHz	Temperature :	23~25℃
Test Engineer :	Steven Hao	Relative Humidity :	47~48%

Mod.	Data Rate	N _{TX}	Channel	Freq. (MHz)	6dB Bandwidth (MHz)	6dB Bandwidth Min. Limit (MHz)	Pass/Fail
11b	1Mbps	1	1	2412	7.04	0.5	Pass
11b	1Mbps	1	6	2437	7.10	0.5	Pass
11b	1Mbps	1	11	2462	7.08	0.5	Pass
11g	6Mbps	1	1	2412	16.30	0.5	Pass
11g	6Mbps	1	6	2437	16.36	0.5	Pass
11g	6Mbps	1	11	2462	16.32	0.5	Pass
HT20	MCS0	1	1	2412	17.54	0.5	Pass
HT20	MCS0	1	6	2437	17.58	0.5	Pass
HT20	MCS0	1	11	2462	17.58	0.5	Pass



Note : The occupied channel bandwidth is maintained within the band of operation for all of the modulations.

3.2 Output Power Measurement

3.2.1 Limit of Output Power

For systems using digital modulation in the 2400-2483.5MHz, the limit for peak output power is 30dBm. If transmitting Antenna of directional gain greater than 6dBi are used the peak output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the Antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the Antenna exceeds 6dBi.


3.2.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.2.3 Test Procedures

1. The testing follows the Measurement Procedure of FCC KDB No. 558074 DTS D01 Meas. Guidance v03r02.
2. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Measure the conducted output power and record the results in the test report.

3.2.4 Test Setup





3.2.5 Test Result of Peak Output Power

Test Mode :	2.4GHz	Temperature :	23~25℃
Test Engineer :	Steven Hao	Relative Humidity :	47~48%

Mod.	Data Rate	N _{TX}	Channel	Freq. (MHz)	RF Output Power (dBm)	Power Limit (dBm)	DG (dBi)	Pass/Fail
11b	1Mbps	1	1	2412	17.61	30	-0.16	Pass
11b	1Mbps	1	6	2437	18.56	30	-0.16	Pass
11b	1Mbps	1	11	2462	16.77	30	-0.16	Pass
11g	6Mbps	1	1	2412	20.06	30	-0.16	Pass
11g	6Mbps	1	6	2437	20.92	30	-0.16	Pass
11g	6Mbps	1	11	2462	19.89	30	-0.16	Pass
HT20	MCS0	1	1	2412	18.65	30	-0.16	Pass
HT20	MCS0	1	6	2437	19.92	30	-0.16	Pass
HT20	MCS0	1	11	2462	18.71	30	-0.16	Pass

Note: Measured power (dBm) has offset with cable loss.

**3.2.6 Test Result of Average output Power (Reporting Only)**

Test Mode :	2.4GHz	Temperature :	23~25℃
Test Engineer :	Steven Hao	Relative Humidity :	47~48%

Mod.	Data Rate	N _{TX}	Channel	Freq. (MHz)	Duty Factor (dB)	Average Output Power (dBm)	Power Limit (dBm)	DG (dBi)	Pass/Fail
11b	1Mbps	1	1	2412	0.10	14.51	30	-0.16	Pass
11b	1Mbps	1	6	2437	0.10	15.47	30	-0.16	Pass
11b	1Mbps	1	11	2462	0.10	13.66	30	-0.16	Pass
11g	6Mbps	1	1	2412	0.60	12.09	30	-0.16	Pass
11g	6Mbps	1	6	2437	0.60	13.13	30	-0.16	Pass
11g	6Mbps	1	11	2462	0.60	11.35	30	-0.16	Pass
HT20	MCS0	1	1	2412	0.63	10.31	30	-0.16	Pass
HT20	MCS0	1	6	2437	0.63	11.10	30	-0.16	Pass
HT20	MCS0	1	11	2462	0.63	9.49	30	-0.16	Pass

Note: Measured power (dBm) has offset with cable loss and duty factor.

3.3 Power Spectral Density Measurement

3.3.1 Limit of Power Spectral Density

The peak power spectral density shall not be greater than 8dBm in any 3kHz band at any time interval of continuous transmission.


3.3.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.3.3 Test Procedures

1. The testing follows Measurement Procedure 10.2 Method PKPSD of FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r02
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 3 kHz. Video bandwidth VBW = 10 kHz In order to make an accurate measurement, set the span to 1.5 times DTS Channel Bandwidth. (6dB BW)
5. Detector = peak, Sweep time = auto couple, Trace mode = max hold, Allow trace to fully stabilize. Use the peak marker function to determine the maximum power level.
6. Measure and record the results in the test report.

3.3.4 Test Setup






3.3.5 Test Result of Power Spectral Density

Test Mode :	2.4GHz	Temperature :	23~25°C
Test Engineer :	Steven Hao	Relative Humidity :	47~48%

Mod.	Data Rate	N _{TX}	Channel	Freq. (MHz)	Peak Power Density (dBm/3kHz)	Max. Limits (dBm/3kHz)	DG (dBi)	Pass/Fail
11b	1Mbps	1	1	2412	-7.88	8	-0.16	Pass
11b	1Mbps	1	6	2437	-7.07	8	-0.16	Pass
11b	1Mbps	1	11	2462	-9.69	8	-0.16	Pass
11g	6Mbps	1	1	2412	-13.99	8	-0.16	Pass
11g	6Mbps	1	6	2437	-13.16	8	-0.16	Pass
11g	6Mbps	1	11	2462	-13.12	8	-0.16	Pass
HT20	MCS0	1	1	2412	-15.39	8	-0.16	Pass
HT20	MCS0	1	6	2437	-12.78	8	-0.16	Pass
HT20	MCS0	1	11	2462	-15.35	8	-0.16	Pass

Note: Measured power density (dBm) has offset with cable loss.



3.4 Conducted Band Edges and Spurious Emission Measurement

3.4.1 Limit of Conducted Band Edges and Spurious Emission Measurement

In any 100 kHz bandwidth outside of the authorized frequency band, the emissions which fall in the non-restricted bands shall be attenuated at least 20 dB / 30dB relative to the maximum PSD level in 100 kHz by RF conducted measurement and radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a).


3.4.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.4.3 Test Procedures

1. The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r02.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Set RBW = 100 kHz, VBW=300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB per 15.247(d).
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

3.4.4 Test Setup






3.4.5 Test Result of Conducted Band Edges and Spurious Emission

Test Mode :	802.11b	Temperature :	23~25°C
Test Band :	2.4GHz Low	Relative Humidity :	47~48%
Test Channel :	01	Test Engineer :	Steven Hao


WLAN 802.11b Channel 01

100kHz PSD reference Level




Date: 4.JUL.2014 11:55:51

Low Channel Plot




Date: 4.JUL.2014 11:56:05

Spurious Emission 30MHz~3GHz



Date: 4.JUL.2014 11:59:55

Spurious Emission 2GHz~25GHz




Date: 4.JUL.2014 12:00:14



Test Mode :	802.11b	Temperature :	23~25°C
Test Band :	2.4GHz Mid	Relative Humidity :	47~48%
Test Channel :	06	Test Engineer :	Steven Hao


WLAN 802.11b Channel 06

100kHz PSD reference Level




Date: 4.JUL.2014 12:02:27

Spurious Emission 30MHz~3GHz



Date: 4.JUL.2014 12:02:47

Spurious Emission 2GHz~25GHz




Date: 4.JUL.2014 12:03:06



Test Mode :	802.11b	Temperature :	23~25°C
Test Band :	2.4GHz High	Relative Humidity :	47~48%
Test Channel :	11	Test Engineer :	Steven Hao


WLAN 802.11b Channel 11

100kHz PSD reference Level




Date: 4.JUL.2014 12:05:24

High Channel Plot




Date: 4.JUL.2014 12:05:38

Spurious Emission 30MHz~3GHz



Date: 4.JUL.2014 12:05:57

Spurious Emission 2GHz~25GHz




Date: 4.JUL.2014 12:06:16



Test Mode :	802.11g	Temperature :	23~25°C
Test Band :	2.4GHz Low	Relative Humidity :	47~48%
Test Channel :	01	Test Engineer :	Steven Hao


WLAN 802.11g Channel 01

100kHz PSD reference Level




Date: 4.JUL.2014 12:09:29

Low Channel Plot




Date: 4.JUL.2014 12:09:42

Spurious Emission 30MHz~3GHz



Date: 4.JUL.2014 12:10:02

Spurious Emission 2GHz~25GHz




Date: 4.JUL.2014 12:10:20



Test Mode :	802.11g	Temperature :	23~25°C
Test Band :	2.4GHz Mid	Relative Humidity :	47~48%
Test Channel :	06	Test Engineer :	Steven Hao


WLAN 802.11g Channel 06

100kHz PSD reference Level




Date: 4.JUL.2014 12:12:43

Spurious Emission 30MHz~3GHz



Date: 4.JUL.2014 12:13:03

Spurious Emission 2GHz~25GHz




Date: 4.JUL.2014 12:13:22



Test Mode :	802.11g	Temperature :	23~25°C
Test Band :	2.4GHz High	Relative Humidity :	47~48%
Test Channel :	11	Test Engineer :	Steven Hao


WLAN 802.11g Channel 11

100kHz PSD reference Level




Date: 4.JUL.2014 12:17:19

High Channel Plot




Date: 4.JUL.2014 12:17:33

Spurious Emission 30MHz~3GHz



Date: 4.JUL.2014 12:18:50

Spurious Emission 2GHz~25GHz




Date: 4.JUL.2014 12:19:09



Test Mode :	802.11n HT20	Temperature :	23~25°C
Test Band :	2.4GHz Low	Relative Humidity :	47~48%
Test Channel :	01	Test Engineer :	Steven Hao


WLAN 802.11n HT20 Channel 01

100kHz PSD reference Level




Date: 4.JUL.2014 12:21:39

Low Channel Plot




Date: 4.JUL.2014 12:21:53

Spurious Emission 30MHz~3GHz



Date: 4.JUL.2014 12:22:12

Spurious Emission 2GHz~25GHz




Date: 4.JUL.2014 12:22:31



Test Mode :	802.11n HT20	Temperature :	23~25°C
Test Band :	2.4GHz Mid	Relative Humidity :	47~48%
Test Channel :	06	Test Engineer :	Steven Hao


WLAN 802.11n HT20 Channel 06

100kHz PSD reference Level




Date: 4.JUL.2014 12:24:22

Spurious Emission 30MHz~3GHz



Date: 4.JUL.2014 12:24:42

Spurious Emission 2GHz~25GHz




Date: 4.JUL.2014 12:25:01



Test Mode :	802.11n HT20	Temperature :	23~25°C
Test Band :	2.4GHz High	Relative Humidity :	47~48%
Test Channel :	11	Test Engineer :	Steven Hao


WLAN 802.11n HT20 Channel 11

100kHz PSD reference Level




Date: 4.JUL.2014 12:26:58

High Channel Plot




Date: 4.JUL.2014 12:27:12

Spurious Emission 30MHz~3GHz



Date: 4.JUL.2014 12:28:27

Spurious Emission 2GHz~25GHz



Date: 4.JUL.2014 12:28:46

3.5 Radiated Band Edges and Spurious Emission Measurement

3.5.1 Limit of Radiated band edge and Spurious Emission Measurement

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. If the output power of this device was measured by spectrum analyzer, the attenuation under this paragraph shall be 30 dB instead of 20 dB. In addition, radiated emissions which fall in the restricted bands must also comply with the FCC section 15.209 limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.5.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.5.3 Test Procedures

1. The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r02.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.
3. The EUT was placed on a turntable with 0.8 meter above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
6. For measurement below 1GHz, If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.
7. Use the following spectrum analyzer settings:
 - (1) Span shall wide enough to fully capture the emission being measured;
 - (2) Set RBW=100 kHz for $f < 1$ GHz; VBW $\geq$ RBW; Sweep = auto; Detector function = peak; Trace = max hold;
 - (3) Set RBW = 1 MHz, VBW= 3MHz for $f \geq 1$ GHz for peak measurement.


For average measurement:

 - VBW = 10 Hz, when duty cycle is no less than 98 percent.
 - VBW $\geq 1/T$, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.


Band	Duty Cycle(%)	T(ms)	1/T(kHz)	VBW Setting
802.11b	97.62	8.20	0.12	300Hz
802.11g	87.18	1.36	0.74	1kHz
2.4GHz 802.11n HT20	86.50	1.28	0.78	1kHz

3.5.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



3.5.5 Test Results of Radiated Spurious Emissions (9kHz ~ 30MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not reported.



3.5.6 Test Result of Radiated Spurious at Band Edges

Test Mode :	802.11b	Temperature :	22~23°C
Test Band :	Low	Relative Humidity :	42~43%
Test Channel :	01	Test Engineer :	Star Wei

ANTENNA POLARITY : HORIZONTAL										
Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2338.98	47.86	-26.14	74	44.76	32.78	3.56	33.24	197	147	Peak
2389.83	34.17	-19.83	54	30.98	32.86	3.59	33.26	197	147	Average

ANTENNA POLARITY : VERTICAL										
Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2346.27	47.17	-26.83	74	44.07	32.78	3.56	33.24	173	314	Peak
2375.97	34.12	-19.88	54	30.97	32.83	3.58	33.26	173	314	Average

Test Mode :	802.11b	Temperature :	22~23°C
Test Band :	High	Relative Humidity :	42~43%
Test Channel :	11	Test Engineer :	Star Wei

ANTENNA POLARITY : HORIZONTAL										
Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2490.61	47.83	-26.17	74	44.42	33.05	3.66	33.3	101	88	Peak
2498.89	33.81	-20.19	54	30.40	33.05	3.66	33.3	101	88	Average

ANTENNA POLARITY : VERTICAL										
Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2495.17	47.64	-26.36	74	44.23	33.05	3.66	33.3	159	316	Peak
2483.71	33.94	-20.06	54	30.57	33.01	3.65	33.29	159	316	Average



Test Mode :	802.11g	Temperature :	22~23°C
Test Band :	Low	Relative Humidity :	42~43%
Test Channel :	01	Test Engineer :	Star Wei

ANTENNA POLARITY : HORIZONTAL										
Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2389.92	50.32	-23.68	74	47.13	32.86	3.59	33.26	100	115	Peak
2389.74	34.58	-19.42	54	31.39	32.86	3.59	33.26	100	115	Average

ANTENNA POLARITY : VERTICAL										
Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2375.07	48.01	-25.99	74	44.86	32.83	3.58	33.26	168	273	Peak
2389.56	34.51	-19.49	54	31.32	32.86	3.59	33.26	168	273	Average

Test Mode :	802.11g	Temperature :	22~23°C
Test Band :	High	Relative Humidity :	42~43%
Test Channel :	11	Test Engineer :	Star Wei

ANTENNA POLARITY : HORIZONTAL										
Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2484.16	57.01	-16.99	74	53.64	33.01	3.65	33.29	189	325	Peak
2483.50	37.27	-16.73	54	33.90	33.01	3.65	33.29	189	325	Average

ANTENNA POLARITY : VERTICAL										
Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2483.71	51.79	-22.21	74	48.42	33.01	3.65	33.29	137	236	Peak
2484.31	34.2	-19.80	54	30.83	33.01	3.65	33.29	137	236	Average



Test Mode :	802.11n HT20	Temperature :	22~23°C
Test Band :	Low	Relative Humidity :	42~43%
Test Channel :	01	Test Engineer :	Star Wei

ANTENNA POLARITY : HORIZONTAL										
Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2389.38	47.77	-26.23	74	44.58	32.86	3.59	33.26	199	117	Peak
2390	34.2	-19.80	54	31.01	32.86	3.59	33.26	199	117	Average

ANTENNA POLARITY : VERTICAL										
Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2384.52	48.34	-25.66	74	45.19	32.83	3.58	33.26	131	299	Peak
2385.42	34.02	-19.98	54	30.87	32.83	3.58	33.26	131	299	Average

Test Mode :	802.11n HT20	Temperature :	22~23°C
Test Band :	High	Relative Humidity :	42~43%
Test Channel :	11	Test Engineer :	Star Wei

ANTENNA POLARITY : HORIZONTAL										
Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2484.28	49.53	-24.47	74	46.16	33.01	3.65	33.29	109	287	Peak
2483.62	34.98	-19.02	54	31.61	33.01	3.65	33.29	109	287	Average

ANTENNA POLARITY : VERTICAL										
Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2484.25	49.88	-24.12	74	46.51	33.01	3.65	33.29	132	291	Peak
2483.65	34.72	-19.28	54	31.35	33.01	3.65	33.29	132	291	Average

3.5.7 Test Result of Radiated Spurious Emission (30MHz ~ 10th Harmonic)

Note: Pre-scanned all test modes and only choose the worst case mode recorded in the test report for radiated spurious emission below 1GHz.

Test Mode :	802.11b	Temperature :	22~23°C
Test Channel :	01	Relative Humidity :	42~43%
Test Engineer :	Star Wei	Polarization :	Horizontal
Remark :	1. 2412 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2412	97.87	-	-	94.64	32.89	3.61	33.27	195	148	Peak
2412	93.45	-	-	90.22	32.89	3.61	33.27	195	148	Average
4824	48.43	-25.57	74	41.81	35.17	5.25	33.8	100	126	Peak

Test Mode :	802.11b	Temperature :	22~23°C
Test Channel :	01	Relative Humidity :	42~43%
Test Engineer :	Star Wei	Polarization :	Vertical
Remark :	1. 2412 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2412	97.44	-	-	94.21	32.89	3.61	33.27	107	294	Peak
2412	93.01	-	-	89.78	32.89	3.61	33.27	107	294	Average
4824	46.94	-27.06	74	40.32	35.17	5.25	33.8	100	58	Peak



Test Mode :	802.11b	Temperature :	22~23°C
Test Channel :	06	Relative Humidity :	42~43%
Test Engineer :	Star Wei	Polarization :	Horizontal
Remark :	1. 2437 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2437	99.09	-	-	95.79	32.95	3.63	33.28	191	94	Peak
2437	96.54	-	-	93.24	32.95	3.63	33.28	191	94	Average
4874	48.27	-25.73	74	41.61	35.18	5.28	33.8	100	41	Peak
7312	48.51	-25.49	74	39.83	36.2	6.61	34.13	100	174	Peak

Test Mode :	802.11b	Temperature :	22~23°C
Test Channel :	06	Relative Humidity :	42~43%
Test Engineer :	Star Wei	Polarization :	Vertical
Remark :	1. 2437 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2437	95.77	-	-	92.47	32.95	3.63	33.28	199	183	Peak
2437	93.40	-	-	90.1	32.95	3.63	33.28	199	183	Average
4874	47.48	-26.52	74	40.82	35.18	5.28	33.8	100	287	Peak
7312	48.33	-25.67	74	39.65	36.20	6.61	34.13	100	317	Peak



Test Mode :	802.11b	Temperature :	22~23°C
Test Channel :	11	Relative Humidity :	42~43%
Test Engineer :	Star Wei	Polarization :	Horizontal
Remark :	1. 2462 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2462	99.32	-	-	95.99	32.98	3.64	33.29	105	308	Peak
2462	92.78	-	-	89.45	32.98	3.64	33.29	105	308	Average
4924	49.08	-24.92	74	42.38	35.19	5.31	33.80	100	51	Peak
7386	48.65	-25.35	74	39.87	36.24	6.70	34.16	100	294	Peak

Test Mode :	802.11b	Temperature :	22~23°C
Test Channel :	11	Relative Humidity :	42~43%
Test Engineer :	Star Wei	Polarization :	Vertical
Remark :	1. 2462 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2462	94.57	-	-	91.24	32.98	3.64	33.29	158	294	Peak
2462	89.44	-	-	86.11	32.98	3.64	33.29	158	294	Average
4924	46.86	-27.14	74	40.16	35.19	5.31	33.80	100	128	Peak
7386	48.65	-25.35	74	39.87	36.24	6.70	34.16	100	211	Peak

Test Mode :	802.11g	Temperature :	22~23°C
Test Channel :	01	Relative Humidity :	42~43%
Test Engineer :	Star Wei	Polarization :	Horizontal
Remark :	1. 2412 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2412	98.44	-	-	95.21	32.89	3.61	33.27	200	159	Peak
2412	86.54	-	-	83.31	32.89	3.61	33.27	200	159	Average
4824	47.02	-26.98	74	40.40	35.17	5.25	33.80	100	49	Peak

Test Mode :	802.11g	Temperature :	22~23°C
Test Channel :	01	Relative Humidity :	42~43%
Test Engineer :	Star Wei	Polarization :	Vertical
Remark :	1. 2412 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2412	96.53	-	-	93.30	32.89	3.61	33.27	105	292	Peak
2412	84.64	-	-	81.41	32.89	3.61	33.27	105	292	Average
4824	47.31	-26.69	74	40.69	35.17	5.25	33.80	110	187	Peak



Test Mode :	802.11g	Temperature :	22~23°C
Test Channel :	06	Relative Humidity :	42~43%
Test Engineer :	Star Wei	Polarization :	Horizontal
Remark :	1. 2437 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2437	101.56	-	-	98.26	32.95	3.63	33.28	163	315	Peak
2437	90.15	-	-	86.85	32.95	3.63	33.28	163	315	Average
4874	45.95	-28.05	74	39.29	35.18	5.28	33.8	100	46	Peak
7312	50.22	-23.78	74	41.54	36.20	6.61	34.13	100	306	Peak

Test Mode :	802.11g	Temperature :	22~23°C
Test Channel :	06	Relative Humidity :	42~43%
Test Engineer :	Star Wei	Polarization :	Vertical
Remark :	1. 2437 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2437	97.08	-	-	93.78	32.95	3.63	33.28	105	299	Peak
2437	85.49	-	-	82.19	32.95	3.63	33.28	105	299	Average
4874	47.89	-26.11	74	41.23	35.18	5.28	33.80	100	152	Peak
7312	48.93	-25.07	74	40.25	36.20	6.61	34.13	100	37	Peak



Test Mode :	802.11g	Temperature :	22~23°C
Test Channel :	11	Relative Humidity :	42~43%
Test Engineer :	Star Wei	Polarization :	Horizontal
Remark :	1. 2462 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
81.41	22.81	-17.19	40	48.72	6.87	0.83	33.61	132	220	Peak
241.46	28.1	-17.90	46	48.51	11.61	1.44	33.46	-	-	Peak
359.8	26.63	-19.37	46	43.55	14.72	1.71	33.35	-	-	Peak
480.08	26.27	-19.73	46	40.56	16.87	2.00	33.16	-	-	Peak
720.64	26.26	-19.74	46	37.14	19.53	2.43	32.84	-	-	Peak
960.23	35.72	-18.28	54	44.54	20.79	2.83	32.44	-	-	Peak
2462	100.56	-	-	97.23	32.98	3.64	33.29	107	315	Peak
2462	90.16	-	-	86.83	32.98	3.64	33.29	107	315	Average
4924	46.44	-27.56	74	39.74	35.19	5.31	33.80	100	149	Peak
7386	49.60	-24.40	74	40.82	36.24	6.70	34.16	100	288	Peak



Test Mode :	802.11g	Temperature :	22~23°C
Test Channel :	11	Relative Humidity :	42~43%
Test Engineer :	Star Wei	Polarization :	Vertical
Remark :	1. 2462 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
47.46	32.13	-7.87	40	56.59	8.50	0.64	33.60	100	96	Peak
83.35	28.81	-11.19	40	54.24	7.34	0.84	33.61	-	-	Peak
239.52	26.74	-19.26	46	47.25	11.51	1.44	33.46	-	-	Peak
359.8	21.66	-24.34	46	38.58	14.72	1.71	33.35	-	-	Peak
479.11	25.31	-20.69	46	39.62	16.85	2.00	33.16	-	-	Peak
960.23	33.78	-20.22	54	42.60	20.79	2.83	32.44	-	-	Peak
2462	96.72	-	-	93.39	32.98	3.64	33.29	196	295	Peak
2462	85.12	-	-	81.79	32.98	3.64	33.29	196	295	Average
4924	48.01	-25.99	74	41.31	35.19	5.31	33.80	100	201	Peak
7386	49.08	-24.92	74	40.30	36.24	6.70	34.16	100	16	Peak



Test Mode :	2.4GHz 802.11n HT20	Temperature :	22~23°C
Test Channel :	01	Relative Humidity :	42~43%
Test Engineer :	Star Wei	Polarization :	Horizontal
Remark :	1. 2412 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2412	95.40	-	-	92.17	32.89	3.61	33.27	195	148	Peak
2412	84.56	-	-	81.33	32.89	3.61	33.27	195	148	Average
4824	46.98	-27.02	74	40.36	35.17	5.25	33.8	100	223	Peak

Test Mode :	2.4GHz 802.11n HT20	Temperature :	22~23°C
Test Channel :	01	Relative Humidity :	42~43%
Test Engineer :	Star Wei	Polarization :	Vertical
Remark :	1. 2412 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2412	94.44	-	-	91.21	32.89	3.61	33.27	134	300	Peak
2412	83.70	-	-	80.47	32.89	3.61	33.27	134	300	Average
4824	47.04	-26.96	74	40.42	35.17	5.25	33.8	100	191	Peak



Test Mode :	2.4GHz 802.11n HT20	Temperature :	22~23°C
Test Channel :	06	Relative Humidity :	42~43%
Test Engineer :	Star Wei	Polarization :	Horizontal
Remark :	1. 2437 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2437	96.37	-	-	93.07	32.95	3.63	33.28	100	144	Peak
2437	84.00	-	-	80.70	32.95	3.63	33.28	100	144	Average
4874	47.11	-26.89	74	40.45	35.18	5.28	33.8	100	358	Peak
7312	48.46	-25.54	74	39.78	36.20	6.61	34.13	100	159	Peak

Test Mode :	2.4GHz 802.11n HT20	Temperature :	22~23°C
Test Channel :	06	Relative Humidity :	42~43%
Test Engineer :	Star Wei	Polarization :	Vertical
Remark :	1. 2437 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2437	94.93	-	-	91.63	32.95	3.63	33.28	107	302	Peak
2437	82.81	-	-	79.51	32.95	3.63	33.28	107	302	Average
4874	47.55	-26.45	74	40.89	35.18	5.28	33.80	100	114	Peak
7312	48.92	-25.08	74	40.24	36.20	6.61	34.13	100	208	Peak



Test Mode :	2.4GHz 802.11n HT20	Temperature :	22~23°C
Test Channel :	11	Relative Humidity :	42~43%
Test Engineer :	Star Wei	Polarization :	Horizontal
Remark :	1. 2462 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2462	98.5	-	-	95.17	32.98	3.64	33.29	107	320	Peak
2462	87.54	-	-	84.21	32.98	3.64	33.29	107	320	Average
4924	47.60	-26.40	74	40.90	35.19	5.31	33.80	100	187	Peak
7386	49.64	-24.36	74	40.86	36.24	6.70	34.16	112	312	Peak

Test Mode :	2.4GHz 802.11n HT20	Temperature :	22~23°C
Test Channel :	11	Relative Humidity :	42~43%
Test Engineer :	Star Wei	Polarization :	Vertical
Remark :	1. 2462 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2462	93.74	-	-	90.41	32.98	3.64	33.29	160	298	Peak
2462	83.01	-	-	79.68	32.98	3.64	33.29	160	298	Average
4924	47.58	-26.42	74	40.88	35.19	5.31	33.8	100	261	Peak
7386	49.72	-24.28	74	40.94	36.24	6.70	34.16	100	220	Peak

3.6 AC Conducted Emission Measurement

3.6.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of Emission (MHz)	Conducted Limit (dB μ V)	
	Quasi-Peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.6.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.6.3 Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room, and it was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode.


3.6.4 Test Setup





3.6.5 Test Result of AC Conducted Emission

Test Mode :	Mode 1	Temperature :	22~24℃
Test Engineer :	Eligah Wang	Relative Humidity :	37~39%
Test Voltage :	120Vac / 60Hz	Phase :	Line
Function Type :	CDMA2000 BC0 Idle + Bluetooth Link + WLAN Link + USB Cable (Charging from Adapter)		




Site : C001-KS
Condition: FCC PART15C LISN-L20130306 LINE

	Freq	Level	Over	Limit	Read	LISN	Cable	
	MHz	dBμV	Limit	Line	Level	Factor	Loss	Remark
			dB	dBμV	dBμV	dB	dB	
1	0.45	43.32	-13.57	56.89	32.80	0.25	10.27	QP
2	0.45	30.12	-16.77	46.89	19.60	0.25	10.27	Average
3	0.54	30.06	-15.94	46.00	19.60	0.20	10.26	Average
4	0.54	41.06	-14.94	56.00	30.60	0.20	10.26	QP
5	0.56	30.75	-15.25	46.00	20.30	0.20	10.25	Average
6	0.56	40.75	-15.25	56.00	30.30	0.20	10.25	QP
7	0.59	41.04	-14.96	56.00	30.60	0.20	10.24	QP
8	0.59	28.54	-17.46	46.00	18.10	0.20	10.24	Average
9	0.67	32.72	-13.28	46.00	22.30	0.20	10.22	Average
10	0.67	45.02	-10.98	56.00	34.60	0.20	10.22	QP
11	0.81	41.26	-14.74	56.00	30.90	0.16	10.20	QP
12	0.81	30.96	-15.04	46.00	20.60	0.16	10.20	Average
13	0.93	43.20	-12.80	56.00	32.91	0.11	10.18	QP
14	0.93	27.90	-18.10	46.00	17.61	0.11	10.18	Average
15	0.97	43.19	-12.81	56.00	32.91	0.10	10.18	QP
16	0.97	32.19	-13.81	46.00	21.91	0.10	10.18	Average
17	1.07	42.68	-13.32	56.00	32.40	0.10	10.18	QP
18	1.07	30.88	-15.12	46.00	20.60	0.10	10.18	Average
19	1.14	44.18	-11.82	56.00	33.90	0.10	10.18	QP
20	1.14	31.58	-14.42	46.00	21.30	0.10	10.18	Average
21	1.21	31.58	-14.42	46.00	21.30	0.10	10.18	Average
22	1.21	41.58	-14.42	56.00	31.30	0.10	10.18	QP
23	1.34	32.58	-13.42	46.00	22.30	0.10	10.18	Average
24	1.34	43.88	-12.12	56.00	33.60	0.10	10.18	QP
25	1.41	32.08	-13.92	46.00	21.80	0.10	10.18	Average
26	1.41	41.18	-14.82	56.00	30.90	0.10	10.18	QP
27	1.51	41.09	-14.91	56.00	30.80	0.10	10.19	QP
28	1.51	31.19	-14.81	46.00	20.90	0.10	10.19	Average



Test Mode :	Mode 1	Temperature :	22~24℃
Test Engineer :	Eligah Wang	Relative Humidity :	37~39%
Test Voltage :	120Vac / 60Hz	Phase :	Line
Function Type :	CDMA2000 BC0 Idle + Bluetooth Link + WLAN Link + USB Cable (Charging from Adapter)		




Site : C001-KS
Condition: FCC PART15C LISN-L20130306 LINE

	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
29	1.71	29.19	-16.81	46.00	18.90	0.10	10.19	Average
30	1.71	40.39	-15.61	56.00	30.10	0.10	10.19	QP
31	1.78	29.69	-16.31	46.00	19.40	0.10	10.19	Average
32	1.78	39.19	-16.81	56.00	28.90	0.10	10.19	QP
33	2.40	39.91	-16.09	56.00	29.60	0.11	10.20	QP
34	2.40	30.41	-15.59	46.00	20.10	0.11	10.20	Average
35	2.54	41.62	-14.38	56.00	31.30	0.12	10.20	QP
36	2.54	31.92	-14.08	46.00	21.60	0.12	10.20	Average
37	2.69	41.23	-14.77	56.00	30.90	0.12	10.21	QP
38	2.69	31.73	-14.27	46.00	21.40	0.12	10.21	Average
39	2.84	39.24	-16.76	56.00	28.89	0.13	10.22	QP
40	2.84	30.94	-15.06	46.00	20.59	0.13	10.22	Average
41	6.70	41.81	-18.19	60.00	31.30	0.20	10.31	QP
42	6.70	33.41	-16.59	50.00	22.90	0.20	10.31	Average
43	7.10	41.82	-18.18	60.00	31.30	0.20	10.32	QP
44	7.10	33.32	-16.68	50.00	22.80	0.20	10.32	Average



Test Mode :	Mode 1	Temperature :	22~24°C
Test Engineer :	Eligah Wang	Relative Humidity :	37~39%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Function Type :	CDMA2000 BC0 Idle + Bluetooth Link + WLAN Link + USB Cable (Charging from Adapter)		



Site : C001-KS
Condition: FCC PART15C LISN-N20130306 NEUTRAL

	Freq	Level	Over	Limit	Read	LISN	Cable	
	MHz	dBuV	Limit	Line	Level	Factor	Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.54	31.33	-14.67	46.00	20.80	0.28	10.25	Average
2	0.54	38.43	-17.57	56.00	27.90	0.28	10.25	QP
3	0.56	38.12	-17.88	56.00	27.60	0.27	10.25	QP
4	0.56	31.82	-14.18	46.00	21.30	0.27	10.25	Average
5	0.64	37.35	-18.65	56.00	26.90	0.22	10.23	QP
6	0.64	30.05	-15.95	46.00	19.60	0.22	10.23	Average
7	1.32	38.88	-17.12	56.00	28.60	0.10	10.18	QP
8	1.32	30.88	-15.12	46.00	20.60	0.10	10.18	Average
9	1.40	37.88	-18.12	56.00	27.60	0.10	10.18	QP
10	1.40	30.18	-15.82	46.00	19.90	0.10	10.18	Average
11	1.61	30.19	-15.81	46.00	19.90	0.10	10.19	Average
12	1.61	36.89	-19.11	56.00	26.60	0.10	10.19	QP
13	2.36	31.21	-14.79	46.00	20.90	0.11	10.20	Average
14	2.36	37.91	-18.09	56.00	27.60	0.11	10.20	QP
15	2.51	37.92	-18.08	56.00	27.60	0.12	10.20	QP
16	2.51	30.92	-15.08	46.00	20.60	0.12	10.20	Average
17	2.72	29.93	-16.07	46.00	19.60	0.12	10.21	Average
18	2.72	37.93	-18.07	56.00	27.60	0.12	10.21	QP
19	4.07	37.03	-18.97	56.00	26.60	0.19	10.24	QP
20	4.07	29.03	-16.97	46.00	18.60	0.19	10.24	Average

3.7 Antenna Requirements

3.7.1 Standard Applicable

If directional gain of transmitting antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. For the fixed point-to-point operation, the power shall be reduced by one dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the FCC rule.

3.7.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

3.7.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.



4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSP40	100319	9kHz~40GHz	Dec. 28, 2013	Jul. 04, 2014	Dec. 27, 2014	Conducted (TH01-KS)
Pulse Power Sensor	Anritsu	MA2411B	0917070	30MHz~40GHz	Feb. 27, 2014	Jul. 04, 2014	Feb. 26, 2015	Conducted (TH01-KS)
Power Meter	Anritsu	ML2495A	1005002	50MHz Bandwidth	Feb. 27, 2014	Jul. 04, 2014	Feb. 26, 2015	Conducted (TH01-KS)
EMI Test Receiver	R&S	ESCI	100534	9kHz~3GHz	Nov. 05, 2013	Jul. 24, 2014	Nov. 04, 2014	Radiation (03CH01-KS)
Spectrum Analyzer	R&S	FSP30	101399	9kHz~30GHz	May 04, 2014	Jul. 24, 2014	May 03, 2015	Radiation (03CH01-KS)
Loop Antenna	R&S	HFH2-Z2	100321	9kHz~30MHz	Oct. 09, 2013	Jul. 24, 2014	Oct. 08, 2014	Radiation (03CH01-KS)
Bilog Antenna	SCHAFFNER	CBL6112D	23182	25MHz~2GHz	Jan. 08, 2014	Jul. 24, 2014	Jan. 07, 2015	Radiation (03CH01-KS)
Double Ridge Horn Antenna	ETS-Lindgren	3117	75959	1GHz~18GHz	Jan. 08, 2014	Jul. 24, 2014	Jan. 07, 2015	Radiation (03CH01-KS)
Active Horn Antenna	com-power	AHA-118	701030	1GHz~18GHz	Nov. 18, 2013	Jul. 24, 2014	Nov. 17, 2014	Radiation (03CH01-KS)
SHF-EHF Horn	Schwarzbeck	BBHA 9170	BBHA170249	15GHz~40GHz	Mar. 10, 2014	Jul. 24, 2014	Mar. 09, 2015	Radiation (03CH01-KS)
Amplifier	com-power	PA-103A	161073	1MHz~1GHz	May 04, 2014	Jul. 24, 2014	May 03, 2015	Radiation (03CH01-KS)
Amplifier	Agilent	8449B	3008A02371	1GHz~26.5GHz	Dec. 10, 2013	Jul. 24, 2014	Dec. 09, 2014	Radiation (03CH01-KS)
AC Power Source	Chroma	61601	F104090004	N/A	NCR	Jul. 24, 2014	NCR	Radiation (03CH01-KS)
Turn Table	MF	MF7802	N/A	0~360 degree	NCR	Jul. 24, 2014	NCR	Radiation (03CH01-KS)
Antenna Mast	MF	MF7802	N/A	1 m~4 m	NCR	Jul. 24, 2014	NCR	Radiation (03CH01-KS)
EMI Receiver	R&S	ESCI7	100768	9kHz~7GHz;	May 04, 2014	Jul. 23, 2014	May 03, 2015	Conduction (CO01-KS)
AC LISN	MessTec	AN3016	060103	9kHz~30MHz	Dec. 10, 2013	Jul. 23, 2014	Dec. 09, 2014	Conduction (CO01-KS)
AC LISN (for auxiliary equipment)	MessTec	AN3016	060105	9kHz~30MHz	Dec. 10, 2013	Jul. 23, 2014	Dec. 09, 2014	Conduction (CO01-KS)
AC Power Source	Chroma	61602	ABP000000811	AC 0V~300V, 45Hz~1000Hz	Nov. 12, 2013	Jul. 23, 2014	Nov. 11, 2014	Conduction (CO01-KS)

5 Uncertainty of Evaluation

Uncertainty of Conducted Emission Measurement (150kHz ~ 30MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_c(y)$)	2.3
--	-----

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_c(y)$)	2.5
--	-----