RF TEST REPORT

Applicant	ZTE Corporation
FCC ID	SRQ-ZTEZ999
Product	LTE/WCDMA/GSM Multi-Mode Digital Mobile Phone
Marketing	ZTE Axon M / ZTE AXON M / Axon M / AXON M
Model	Z999
Report No.	RXA1711-0362RF01
Issue Date	December 1, 2017

TA Technology (Shanghai) Co., Ltd. tested the above equipment in accordance with the requirements in **FCC CFR47 Part 2 (2017)/ FCC CFR 47 Part 22H (2017)**. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

Performed by: Jiangpeng Lan *Approved by: Kai Xu*

TA Technology (Shanghai) Co., Ltd.

No.145, Jintang Rd, Tangzhen Industry Park, Pudong Shanghai, China

TEL: +86-021-50791141/2/3

FAX: +86-021-50791141/2/3-8000

TABLE OF CONTENT

1. Test Laboratory 4
1.1. Notes of the Test Report 4
1.2. Test facility 4
1.3. Testing Location 5
2. General Description of Equipment under Test 6
3. Applied Standards 7
4. Test Configuration 8
5. Test Case Results 9
5.1. RF Power Output 9
5.2. Effective Radiated Power 11
5.3. Occupied Bandwidth 14
5.4. Band Edge Compliance 18
5.5. Peak-to-Average Power Ratio (PAPR) 21
5.6. Frequency Stability 23
5.7. Spurious Emissions at Antenna Terminals 25
5.8. Radiates Spurious Emission 27
6. Main Test Instruments 32
ANNEX A: EUT Appearance and Test Setup 33
A.1 EUT Appearance 33
A.2 Test Setup 35

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

Summary of measurement results

No.	Test Type	Clause in FCC rules	Verdict
1	RF power output	2.1046	PASS
2	Effective Radiated Power	22.913(a)(2)	PASS
3	Occupied Bandwidth	2.1049	PASS
4	Band Edge Compliance	2.1051 / 22.917(a)	PASS
5	Peak-to-Average Power Ratio	22.913(d)/ KDB 971168 D01(5.7)	PASS
6	Frequency Stability	2.1055 / 22.355	PASS
7	Spurious Emissions at Antenna Terminals	2.1051 / 22.917(a)	PASS
8	Radiates Spurious Emission	2.1053 / 22.917 (a)	PASS
Date of Testing: November 9, 2017 ~ November 24, 2017			
Note: PASS: The EUT complies with the essential requirements in the standard. FAIL: The EUT does not comply with the essential requirements in the standard.			

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

1. Test Laboratory

1.1. Notes of the Test Report

This report shall not be reproduced in full or partial, without the written approval of **TA technology (shanghai) co., Ltd.** The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein .Measurement Uncertainties were not taken into account and are published for informational purposes only. This report is written to support regulatory compliance of the applicable standards stated above. This report must not be used by the client to claim product certification, approval, or endorsement by any government agencies.

1.2. Test facility

CNAS (accreditation number: L2264)

TA Technology (Shanghai) Co., Ltd. has obtained the accreditation of China National Accreditation Service for Conformity Assessment (CNAS).

FCC (Designation number: CN1179, Test Firm Registration Number: 446626)

TA Technology (Shanghai) Co., Ltd. has been listed on the US Federal Communications Commission list of test facilities recognized to perform electromagnetic emissions measurements.

IC (recognition number is 8510A)

TA Technology (Shanghai) Co., Ltd. has been listed by industry Canada to perform electromagnetic emission measurement.

VCCI (recognition number is C-4595, T-2154, R-4113, G-10766)

TA Technology (Shanghai) Co., Ltd. has been listed by industry Japan to perform electromagnetic emission measurement.

A2LA (Certificate Number: 3857.01)

TA Technology (Shanghai) Co., Ltd. has been listed by American Association for Laboratory Accreditation to perform electromagnetic emission measurement.

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

1.3. Testing Location

Company:	TA Technology (Shanghai) Co., Ltd.
Address:	No.145, Jintang Rd, Tangzhen Industry Park, Pudong
City:	Shanghai
Post code:	201201
Country:	P. R. China
Contact:	Xu Kai
Telephone:	+86-021-50791141/2/3
Fax:	+86-021-50791141/2/3-8000
Website:	http://www.ta-shanghai.com
E-mail:	xukai@ta-shanghai.com

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

2. General Description of Equipment under Test

Client Information

Applicant	ZTE Corporation
Applicant address	ZTE Plaza, Keji Road South, Hi-Tech, Industrial Park, Nanshan District, Shenzhen, Guangdong, 518057, P.R.China
Manufacturer	ZTE Corporation
Manufacturer address	ZTE Plaza, Keji Road South, Hi-Tech, Industrial Park, Nanshan District, Shenzhen, Guangdong, 518057, P.R.China

General Information

EUT Description			
Model	Z999		
IMEI	866733030002454		
Hardware Version	ZTE AXON M MP		
Software Version	AXONMB01-DE_ACC01a		
Power Supply	Battery/AC adapter		
Antenna Type	Internal Antenna		
Test Mode(s)	GSM 850: WCDMA Band V		
Test Modulation	(GSM)GMSK,8PSK; (WCDMA)QPSK;		
GPRS Multislot Class	12		
EGPRS Multislot Class	12		
HSDPA UE Category	24		
HSUPA UE Category	6		
Maximum E.R.P.	GSM 850:	29.06dBm	
	WCDMA Band V:	18.35dBm	
Rated Power Supply Voltage	3.85V		
Extreme Voltage	Minimum: 3.6V Maximum: 4.4V		
Extreme Temperature	Lowest: -10°C Highest: +55°C		
Operating Frequency Range(s)	Band	Tx (MHz)	Rx (MHz)
	GSM850	824 ~ 849	869 ~ 894
	WCDMA Band V	824 ~ 849	869 ~ 894
EUT Accessory			
Battery	Manufacturer: SCUD (Fujian) Electronics Co., Ltd. Model: Li3931T44P8h686049		
Earphone	Manufacturer: KINGSTATE ELECTRONICS CORP. Model: KJAG4020AWKCB-2		
Note: The information of the EUT is declared by the manufacturer.			

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

3. Applied Standards

According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC CFR47 Part 2 (2017)

FCC CFR 47 Part 22H (2017)

ANSI/TIA-603-D (2010)

KDB 971168 D01 Power Meas License Digital Systems v03

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

4. Test Configuration

Radiated measurements are performed by rotating the EUT in three different orthogonal test planes. EUT stand-up position (Z axis), lie-down position (X, Y axis). Receiver antenna polarization (horizontal and vertical), the worst emission was found in position (X axis, horizontal polarization) and the worst case was recorded.

All mode and data rates and positions were investigated. Subsequently, only the worst case emissions are reported.
The following testing in GSMWCDMA is set based on the maximum RF Output Power.
Test modes are chosen to be reported as the worst case configuration below:

	Test items	**Modes/Modulation**	
		GSM 850	WCDMA Band V
Conducted Test cases	RF power output	GSM GPRS EGPRS	RMC HSDPA/HSUPA DC-HSDPA
	Occupied Bandwidth	GSM GPRS(1Tx slot) EGPRS(1Tx slot)	RMC
	Band Edge Compliance	GSM GPRS(1Tx slot) EGPRS(1Tx slot)	RMC
	Peak-to-Average Power Ratio	GSM GPRS(1Tx slot) EGPRS(1Tx slot)	RMC
	Frequency Stability	GSM GPRS(1Tx slot) EGPRS(1Tx slot)	RMC
	Spurious Emissions at Antenna Terminals	GSM	RMC
Radiated Test cases	Effective Radiated Power	GSM GPRS(1Tx slot) EGPRS(1Tx slot)	RMC
	Radiates Spurious Emission	GSM	RMC

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

5. Test Case Results

5.1. RF Power Output

Ambient condition

Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa

Methods of Measurement

During the process of the testing, The EUT is controlled by the Base Station Simulator to ensure max power transmission and proper modulation.

Test Setup



The loss between RF output port of the EUT and the input port of the tester has been taken into consideration.

Limits

No specific RF power output requirements in part 2.1046.

Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor k = 2, U= 0.4 dB.

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

Test Results

GSM 850		Conducted Power(dBm)		
		Channel 128	Channel 190	Channel 251
		824.2 (MHz)	836.6 (MHz)	848.8 (MHz)
GSM	Results	33.42	33.23	33.28
GPRS (GMSK)	1TXslot	33.45	33.28	33.25
	2TXslots	30.08	30.25	29.91
	3TXslots	28.22	28.28	27.84
	4TXslots	26.27	26.38	26.23
EGPRS (8PSK)	1TXslot	26.65	26.74	26.66
	2TXslots	24.64	24.65	24.68
	3TXslots	22.61	22.63	22.64
	4TXslots	20.58	20.61	20.59

WCDMA Band V		Conducted Power(dBm)		
		Channel 4132	Channel 4183	Channel 4233
		826.4(MHz)	836.6(MHz)	846.6(MHz)
RMC	12.2k	22.75	22.96	22.82
	64k	22.68	22.82	22.76
	144k	22.67	22.81	22.66
	384k	22.66	22.80	22.65
HSDPA	Sub - Test 1	21.67	21.80	21.75
	Sub - Test 2	21.63	21.73	21.85
	Sub - Test 3	21.13	21.26	21.30
	Sub - Test 4	21.19	21.32	21.35
HSUPA	Sub - Test 1	21.67	21.75	21.87
	Sub - Test 2	21.13	21.30	21.41
	Sub - Test 3	21.65	21.71	21.76
	Sub - Test 4	21.56	21.70	21.79
	Sub - Test 5	21.62	21.83	21.87
DC-HSDPA	Sub - Test 1	21.53	21.74	21.62
	Sub - Test 2	21.48	21.57	21.71
	Sub - Test 3	20.97	21.09	21.15
	Sub - Test 4	21.13	21.23	21.29

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

5.2. Effective Radiated Power

Ambient condition

Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa

Methods of Measurement

The testing follows FCC KDB 971168 v03 Section 5.8 and ANSI/TIA-603-D-2010.

a) Connect the equipment as illustrated. Mount the equipment with the manufacturer specified antenna in a vertical orientation on a manufacturer specified mounting surface located on a non-conducting rotating platform of a RF anechoic chamber (preferred) or a standard radiation site.

b) Key the transmitter, then rotate the EUT 360° azimuthally and record spectrum analyzer power level (LVL) measurements at angular increments that are sufficiently small to permit resolution of all peaks. If a standard radiation test site is used, raise and lower the test antenna to obtain a maximum reading at each angular increment. (Note: several batteries may be needed to offset the effect of battery voltage droop, which should not exceed 5% of the manufactured specified battery voltage during transmission).

c) Replace the transmitter under test with a vertically polarized half-wave dipole (or an antenna whose gain is known relative to an ideal half-wave dipole). The center of the antenna should be at the same location as the center of the antenna under test.

d) Connect the antenna to a signal generator with a known output power and record the path loss (in dB) as LOSS. If a standard radiation test site is used, raise and lower the test antenna to obtain a maximum reading.LOSS = Generator Output Power (dBm) – Analyzer reading (dBm)

e) Determine the effective radiated output power at each angular position from the readings in steps b) and d) using the following equation:ERP (dBm) = LVL (dBm) + LOSS (dB)

f) The maximum ERP is the maximum value determined in the preceding step.

g) When calculating ERP, in addition to knowing the antenna radiation and matching characteristics, it is necessary to know the loss values of all elements (e.g.transmission line attenuation, mismatches, filters, combiners) interposed between the point where transmitter output power is measured, and the point where power is applied to the antenna. ERP can then be calculated as follows:

ERP (dBm) = Output Power (dBm) - Losses (dB) + Antenna Gain (dBd)

where:dBd refers to gain relative to an ideal dipole.

EIRP (dBm) = ERP (dBm) + 2.15 (dB.)

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

Test setup





Limits

Rule Part 22.913(a) specifies that "Mobile/portable stations are limited to 7 watts ERP".

Limit	≤ 7 W (38.45 dBm)

Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor *k* = 2, *U*= 1.19 dB

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

Test Results:

The measurement is performed for both of horizontal and vertical antenna Polarization, and only the data of worst mode is recorded in this report.

Mode	Channel	Frequency (MHz)	Polarization	Output Power (dBm)	Losses (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Conclusion
GSM 850	Low	824.2	Horizontal	-17.91	-45.53	1.06	28.68	38.45	Pass
	Mid	836.6	Horizontal	-18.21	-45.38	1.24	28.41	38.45	Pass
	High	848.8	Horizontal	-19.57	-45.37	1.38	27.18	38.45	Pass
GPRS 850	Low	824.2	Horizontal	-17.53	-45.53	1.06	29.06	38.45	Pass
	Mid	836.6	Horizontal	-17.62	-45.38	1.24	29.00	38.45	Pass
	High	848.8	Horizontal	-18.77	-45.37	1.38	27.98	38.45	Pass
EGPRS 850	Low	824.2	Horizontal	-21.24	-45.53	1.06	25.35	38.45	Pass
	Mid	836.6	Horizontal	-21.89	-45.38	1.24	24.73	38.45	Pass
	High	848.8	Horizontal	-23.02	-45.37	1.38	23.73	38.45	Pass
WCDMA Band V	Low	826.4	Horizontal	-28.63	-45.44	1.13	17.94	38.45	Pass
	Mid	836.6	Horizontal	-28.32	-45.38	1.24	18.30	38.45	Pass
	High	846.6	Horizontal	-28.38	-45.38	1.35	18.35	38.45	Pass

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

5.3. Occupied Bandwidth

Ambient condition

Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa

Method of Measurement

The EUT was connected to Spectrum Analyzer and Base Station Simulator via power Splitter. The occupied bandwidth is measured using spectrum analyzer.
RBW is set to 3kHz, VBW is set to 10kHz for GSM 850,
RBW is set to 51kHz, VBW is set to 160kHz for WCDMA Band V,
99% power and -26dBc occupied bandwidths are recorded. Spectrum analyzer plots are included on the following pages.

Test Setup



Limits

No specific occupied bandwidth requirements in part 2.1049.

Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor k = 2, U= 624Hz.

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

Test Result

Mode	Channel	Frequency (MHz)	99% Power Bandwidth (MHz)	-26dBc Bandwidth(MHz)
GSM 850 (GSM)	128	824.2	0.24640	0.3077
	190	836.6	0.24671	0.3146
	251	848.8	0.24491	0.3154
GPRS 850 (GMSK)	128	824.2	0.24455	0.3106
	190	836.6	0.24633	0.3158
	251	848.8	0.24588	0.3153
EGPRS 850 (8-PSK)	128	824.2	0.24575	0.3133
	190	836.6	0.24416	0.3082
	251	848.8	0.24561	0.3109
WCDMA Band V (RMC)	4132	826.4	4.1180	4.696
	4183	836.6	4.1461	4.705
	4233	846.6	4.1214	4.691

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

GSM 850 CH-Low



GSM 850 GPRS CH-Low

GSM 850 CH-Middle

GSM 850 GPRS CH-Middle



GSM 850 CH-High

GSM 850 GPRS CH-High



This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

GSM 850 EGPRS CH-Low



WCDMA Band V CH-Low

GSM 850 EGPRS CH-Middle



WCDMA Band V CH-Middle



GSM 850 EGPRS CH-High

WCDMA Band V CH-High



This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

5.4. Band Edge Compliance

Ambient condition

Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa

Method of Measurement

The EUT was connected to Spectrum Analyzer and Base Station Simulator via power Splitter. The band edge of the lowest and highest channels were measured. The average detector is used.
RBW is set to 3kHz,VBW is set to 10kHz for GSM 850,
RBW is set to 51kHz,VBW is set to 160kHz for WCDMA Band V.
Spectrum analyzer plots are included on the following pages.

Test Setup



Limits

Rule Part 22.917(a) specifies that “The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least 43 + 10 log(P) dB.”

Limit	-13 dBm

Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor k = 1.96, U=0.684dB.

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

Test Result:

GSM 850 CH-Low



GSM 850 CH-High

GSM 850 GPRS CH-Low

GSM 850 GPRS CH-High

GSM 850 EGPRS CH-Low



GSM 850 EGPRS CH-High

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

WCDMA Band V CH-Low	WCDMA Band V CH-High
	

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

5.5. Peak-to-Average Power Ratio (PAPR)

Ambient condition

Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa

Methods of Measurement

Measure the total peak power and record as P_{Pk}. And measure the total average power and record as P_{Avg}. Both the peak and average power levels must be expressed in the same logarithmic units (*e.g.*, dBm). Determine the PAPR from:
PAPR (dB) = P_{Pk} (dBm) - P_{Avg} (dBm).

Test Setup



Limits

According to the Sec. 22.913(d), The peak-to-average ratio (PAR) of the transmission must not exceed 13 dB.

Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor *k* = 2, *U*= 0.4 dB.

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

Test Results

Mode	Channel	Frequency (MHz)	Peak (dBm)	Avg (dBm)	PAPR (dB)	Limit (dB)	Conclusion
GSM 850 (GSM)	128	824.2	34.31	33.42	0.32	≤13	PASS
	190	836.6	34.10	33.23	0.34	≤13	PASS
	251	848.8	34.19	33.28	0.29	≤13	PASS
GPRS 850 (GMSK)	128	824.2	27.20	26.27	0.27	≤13	PASS
	190	836.6	27.33	26.38	0.24	≤13	PASS
	251	848.8	27.20	26.23	0.21	≤13	PASS
EGPRS 850 (8-PSK)	128	824.2	21.64	20.58	0.31	≤13	PASS
	190	836.6	21.58	20.61	0.33	≤13	PASS
	251	848.8	21.72	20.59	0.35	≤13	PASS
WCDMA Band V (RMC)	4132	826.4	25.73	22.75	2.98	≤13	PASS
	4183	836.6	25.99	22.96	3.03	≤13	PASS
	4233	846.6	25.85	22.82	3.03	≤13	PASS

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

5.6. Frequency Stability

Ambient condition

Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa

Method of Measurement

1. Frequency Stability (Temperature Variation)

The temperature inside the climate chamber is varied from -30°C to +55°C in 10°C step size,

(1) With all power removed, the temperature was decreased to 0°C and permitted to stabilize for three hours.

(2) Measure the carrier frequency with the test equipment in a “call mode”. These measurements should be made within 1 minute of powering up the mobile station, to prevent significant self warming.

(3) Repeat the above measurements at 10°C increments from -30°C to +55°C. Allow at least 1.5 hours at each temperature, un-powered, before making measurements. Frequency Stability (Voltage Variation)

The frequency stability shall be measured with variation of primary supply voltage as follows:

(1) Vary primary supply voltage from 85 to 115 percent of the nominal value for other than hand carried battery equipment.

(2) For hand carried, battery powered equipment, reduce primary supply voltage to the battery-operating end point which shall be specified by the manufacturer.

This transceiver is specified to operate with an input voltage of between 3.6 V and 4.4 V, with a nominal voltage of 3.85V.

Test setup



This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

Limits

According to the Sec. 22.355, the frequency stability of the carrier shall be accurate to within 2.5 ppm of the received frequency for mobile stations.

Limits	≤ 2.5 ppm

Measurement Uncertainty

The assessed measurement uncertainty to ensure 99.75％ confidence level for the normal distribution is with the coverage factor *k* = 3, *U*= 0.01ppm.

Test Result

Mode	Test status	Test Results (ppm)			Limit (ppm)	Conclusion
		GSM (GMSK)	GPRS (GMSK)	EGPRS (8PSK)		
GSM 850 Middle Channel	-30°C/Normal Voltage	-0.0037	0.0237	0.0264	2.5	PASS
	-20°C/Normal Voltage	-0.0074	0.0299	0.0261	2.5	PASS
	-10°C/Normal Voltage	0.0098	0.0344	0.0288	2.5	PASS
	0°C/Normal Voltage	0.0104	0.0126	0.0267	2.5	PASS
	10°C/Normal Voltage	0.0141	0.0359	0.0276	2.5	PASS
	20°C/Normal Voltage	0.0109	0.0286	0.0263	2.5	PASS
	30°C/Normal Voltage	0.0086	0.0279	0.0270	2.5	PASS
	40°C/Normal Voltage	0.0087	0.0327	0.0297	2.5	PASS
	50°C/Normal Voltage	0.0097	0.0299	0.0283	2.5	PASS
	55°C/Normal Voltage	0.0123	0.0294	0.0264	2.5	PASS
	20°C/Minimum Voltage	0.0042	0.0231	0.0272	2.5	PASS
	20°C/Maximum Voltage	0.0082	0.0260	0.0247	2.5	PASS
/	/	RMC			/	/
WCDMA Band V Middle Channel	-30°C/Normal Voltage	-0.000070			2.5	PASS
	-20°C/Normal Voltage	0.000862			2.5	PASS
	-10°C/Normal Voltage	0.000649			2.5	PASS
	0°C/Normal Voltage	-0.000284			2.5	PASS
	10°C/Normal Voltage	0.000227			2.5	PASS
	20°C/Normal Voltage	-0.000355			2.5	PASS
	30°C/Normal Voltage	0.000421			2.5	PASS
	40°C/Normal Voltage	0.000089			2.5	PASS
	50°C/Normal Voltage	0.000334			2.5	PASS
	55°C/Normal Voltage	0.000347			2.5	PASS
	20°C/Minimum Voltage	0.000090			2.5	PASS
	20°C/Maximum Voltage	0.000212			2.5	PASS

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

5.7. Spurious Emissions at Antenna Terminals

Ambient condition

Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa

Method of Measurement

The EUT was connected to Spectrum Analyzer and Base Station Simulator via power Splitter. The measurement is carried out using a spectrum analyzer. The spectrum analyzer scans from 9kHz to the 10th harmonic of the carrier. The peak detector is used. RBW are set to 100 kHz and VBW are set to 300 kHz for below 1G, RBW are set to 1MHz and VBW are set to 3MHz for above 1G, Sweep is set to ATUO.

Test setup



Limits

Rule Part 22.917(a) specifies that “The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least 43 + 10 log (P) dB.”

Limit	-13 dBm

Measurement Uncertainty

The assessed measurement uncertainty to ensure 99.75% confidence level for the normal distribution is with the coverage factor *k* = 1.96.

Frequency	Uncertainty
100kHz-2GHz	0.684 dB
2GHz-18GHz	1.407 dB

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

Test Result

Sweep from 9 kHz to 30MHz, and the emissions more than 20 dB below the permissible value are not reported.

If disturbances were found more than 20dB below limit line, the mark is not required for the EUT.

The signal beyond the limit is carrier.

GSM 850 CH-Low 30MHz ~ 9GHz



WCDMA Band V CH-Low 30MHz ~ 9GHz



GSM 850 CH-Middle 30MHz ~ 9GHz



WCDMA Band V CH-Middle 30MHz ~ 9GHz



GSM 850 CH-High 30MHz ~ 9GHz



WCDMA Band V CH-High 30MHz ~ 9GHz



This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

5.8. Radiates Spurious Emission

Ambient condition

Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa

Method of Measurement

1. The testing follows FCC KDB 971168 v03 Section 5.8 and ANSI/TIA-603-D-2010.
2. The EUT is placed on a turntable 0.8 meters above the ground in the chamber, 3 meter away from the antenna. The maximal emission value is acquired by adjusting the antenna height, polarisation and turntable azimuth. Normally, the height range of antenna is 1 m to 4 m, the azimuth range of turntable is 0° to 360°, and the receive antenna has two polarizations Vertical (V) and Horizontal (H).
3. A log-periodic antenna or double-ridged waveguide horn antenna shall be substituted in place of the EUT. The log-periodic antenna will be driven by a signal generator and the level will be adjusted till the same power value on the spectrum analyzer or receiver. The level of the spurious emissions can be calculated through the level of the signal generator, cable loss, the gain of the substitution antenna and the reading of the spectrum analyzer or receiver.
4. The EUT is then put into continuously transmitting mode at its maximum power level during the test.Set Test Receiver or Spectrum RBW=1MHz,VBW=3MHz for above 1GHz and RBW=100kHz,VBW=300kHz for 30MHz to 1GHz,, And the maximum value of the receiver should be recorded as (Pr).
5. The EUT shall be replaced by a substitution antenna. In the chamber, an substitution antenna for the frequency band of interest is placed at the reference point of the chamber. An RF Signal source for the frequency band of interest is connected to the substitution antenna with a cable that has been constructed to not interfere with the radiation pattern of the antenna. A power (PMea) is applied to the input of the substitution antenna, and adjust the level of the signal generator output until the value of the receiver reach the previously recorded (Pr). The power of signal source (PMea) is recorded. The test should be performed by rotating the test item and adjusting the receiving antenna polarization.
6. A amplifier should be connected to the Signal Source output port. And the cable should be connect between the Amplifier and the Substitution Antenna. The cable loss (Pcl) ,the Substitution Antenna Gain (Ga) and the Amplifier Gain (PAg) should be recorded after test.
7. The measurement results are obtained as described below:

Power(EIRP)=PMea- PAg - Pcl + Ga

The measurement results are amend as described below:

Power(EIRP)=PMea- Pcl + Ga

8. This value is EIRP since the measurement is calibrated using an antenna of known gain (2.15 dBi) and known input power. ERP can be calculated from EIRP by subtracting the gain of the dipole, ERP = EIRP-2.15dBi.

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

Test setup

30MHz~~~ 1GHz



Above 1GHz



Note: Area side:2.4mX3.6m

Limits

Rule Part 22.917(a) specifies that "The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least 43 + 10 log (P) dB."

Limit	-13 dBm

Measurement Uncertainty

The assessed measurement uncertainty to ensure 95％ confidence level for the normal distribution is with the coverage factor *k* = 1.96, *U*= 3.55 dB.

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

Test Result

GSM 850 CH-Low

Harmonic	Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	Antenna Polarization	ERP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	1648	-54.40	2	10.15	Horizontal	-48.4	-13.0	35.4	45
3	2473	-37.09	2.51	11.35	Horizontal	-30.4	-13.0	17.4	90
4	3297	-55.10	4.2	10.85	Horizontal	-50.6	-13.0	37.6	270
5	4121	-53.10	5.2	11.35	Horizontal	-49.1	-13.0	36.1	180
6	4945	-51.90	5.5	11.95	Horizontal	-47.6	-13.0	34.6	270
7	5769	-52.30	5.7	13.55	Horizontal	-46.6	-13.0	33.6	135
8	6594	-50.20	6.3	13.75	Horizontal	-44.9	-13.0	31.9	45
9	7418	-46.60	6.8	13.85	Horizontal	-41.7	-13.0	28.7	180
10	8242	-47.40	6.9	14.25	Horizontal	-42.2	-13.0	29.2	270

Note: 1.The other Spurious RF Radiated emissions level is no more than noise floor.
2.The worst emission was found in the antenna is Horizontal position.

GSM 850 CH-Middle

Harmonic	Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	Antenna Polarization	ERP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	1673	-54.30	2	10.75	Horizontal	-47.7	-13.0	34.7	180
3	2498	-37.99	2.51	11.05	Horizontal	-31.6	-13.0	18.6	270
4	3346	-56.20	4.2	11.15	Horizontal	-51.4	-13.0	38.4	135
5	4183	-53.20	5.2	11.15	Horizontal	-49.4	-13.0	36.4	45
6	5020	-51.40	5.5	11.95	Horizontal	-47.1	-13.0	34.1	270
7	5856	-52.30	5.7	13.55	Horizontal	-46.6	-13.0	33.6	180
8	6693	-49.10	6.3	13.75	Horizontal	-43.8	-13.0	30.8	270
9	7529	-46.80	6.8	13.85	Horizontal	-41.9	-13.0	28.9	135
10	8366	-47.20	6.9	14.25	Horizontal	-42.0	-13.0	29.0	45

Note: 1.The other Spurious RF Radiated emissions level is no more than noise floor.
2.The worst emission was found in the antenna is Horizontal position.

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

GSM 850 CH-High

Harmonic	Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	Antenna Polarization	ERP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	1698	-50.90	2	10.15	Horizontal	-44.9	-13.0	31.9	225
3	2546	-50.99	2.51	11.05	Horizontal	-44.6	-13.0	31.6	135
4	3395	-56.80	4.2	11.15	Horizontal	-52.0	-13.0	39.0	180
5	4244	-53.30	5.2	11.15	Horizontal	-49.5	-13.0	36.5	270
6	5093	-50.90	5.5	11.95	Horizontal	-46.6	-13.0	33.6	135
7	5942	-52.90	5.7	13.55	Horizontal	-47.2	-13.0	34.2	45
8	6790	-49.80	6.3	13.75	Horizontal	-44.5	-13.0	31.5	270
9	7639	-47.60	6.8	13.85	Horizontal	-42.7	-13.0	29.7	180
10	8488	-48.10	6.9	14.25	Horizontal	-42.9	-13.0	29.9	270

Note: 1.The other Spurious RF Radiated emissions level is no more than noise floor.
2.The worst emission was found in the antenna is Horizontal position.

WCDMA Band V CH-Low

Harmonic	Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	Antenna Polarization	ERP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	1653	-58.00	2	10.15	Horizontal	-52.0	-13.0	39.0	180
3	2479	-59.49	2.51	11.35	Horizontal	-52.8	-13.0	39.8	90
4	3306	-54.20	4.2	10.85	Horizontal	-49.7	-13.0	36.7	180
5	4132	-51.30	5.2	11.35	Horizontal	-47.3	-13.0	34.3	270
6	4958	-50.20	5.5	11.95	Horizontal	-45.9	-13.0	32.9	135
7	5785	-48.60	5.7	13.55	Horizontal	-42.9	-13.0	29.9	45
8	6611	-49.40	6.3	13.75	Horizontal	-44.1	-13.0	31.1	270
9	7438	-47.60	6.8	13.85	Horizontal	-42.7	-13.0	29.7	180
10	8264	-46.80	6.9	14.25	Horizontal	-41.6	-13.0	28.6	270

Note: 1.The other Spurious RF Radiated emissions level is no more than noise floor.
2.The worst emission was found in the antenna is Horizontal position.

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

WCDMA Band V CH-Middle

Harmonic	Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	Antenna Polarization	ERP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	1673	-58.50	2	10.75	Horizontal	-51.9	-13.0	38.9	135
3	2510	-57.79	2.51	11.05	Horizontal	-51.4	-13.0	38.4	270
4	3346	-55.60	4.2	11.15	Horizontal	-50.8	-13.0	37.8	135
5	4183	-51.50	5.2	11.15	Horizontal	-47.7	-13.0	34.7	180
6	5020	-50.00	5.5	11.95	Horizontal	-45.7	-13.0	32.7	270
7	5856	-50.90	5.7	13.55	Horizontal	-45.2	-13.0	32.2	135
8	6693	-48.80	6.3	13.75	Horizontal	-43.5	-13.0	30.5	45
9	8366	-46.70	6.8	13.85	Horizontal	-41.8	-13.0	28.8	270
10	3346	-46.10	6.9	14.25	Horizontal	-40.9	-13.0	27.9	180

Note: 1.The other Spurious RF Radiated emissions level is no more than noise floor.
2.The worst emission was found in the antenna is Horizontal position.

WCDMA Band V CH-High

Harmonic	Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	Antenna Polarization	ERP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	1693	-61.10	2	10.15	Horizontal	-55.1	-13.0	42.1	225
3	2540	-58.49	2.51	11.05	Horizontal	-52.1	-13.0	39.1	45
4	3386	-55.20	4.2	11.15	Horizontal	-50.4	-13.0	37.4	270
5	4233	-52.00	5.2	11.15	Horizontal	-48.2	-13.0	35.2	135
6	5080	-49.80	5.5	11.95	Horizontal	-45.5	-13.0	32.5	90
7	5926	-50.90	5.7	13.55	Horizontal	-45.2	-13.0	32.2	225
8	6773	-49.20	6.3	13.75	Horizontal	-43.9	-13.0	30.9	90
9	7619	-47.50	6.8	13.85	Horizontal	-42.6	-13.0	29.6	135
10	8466	-45.90	6.9	14.25	Horizontal	-40.7	-13.0	27.7	225

Note: 1.The other Spurious RF Radiated emissions level is no more than noise floor.
2.The worst emission was found in the antenna is Horizontal position.

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

6. Main Test Instruments

Name	Manufacturer	Type	Serial Number	Calibration Date	Expiration Date
Power Splitter	Hua Xiang	SHX-GF2-2-13	10120101	2017-05-14	2018-05-13
Spectrum Analyzer	Agilent	N9010A	MY47191109	2017-05-20	2018-05-19
Universal Radio Communication Tester	Agilent	E5515C	MY48367192	2017-05-20	2018-05-19
Signal Analyzer	R&S	FSV30	100815	2016-12-16	2017-12-15
EMI Test Receiver	R&S	ESCI	100948	2017-05-20	2018-05-19
Signal generator	R&S	SMB 100A	102594	2017-05-14	2018-05-13
Signal generator	R&S	SMR27	100365	2017-05-14	2018-05-13
Trilog Antenna	SCHWARZBECK	VUBL 9163	9163-201	2014-12-06	2017-12-05
Horn Antenna	R&S	HF907	100126	2014-12-06	2017-12-05
Horn Antenna	ETS-Lindgren	3160-09	00102644	2015-01-30	2018-01-29
Climatic Chamber	Re Ce	PT-30B	20101891	2015-07-18	2018-07-17
RF Cable	Agilent	SMA 15cm	0001	2017-08-04	2018-02-03
Preampflier	R&S	SCU18	102327	2017-06-18	2018-06-17
Software	R&S	EMC32	V 8.52.0	NA	NA

*******END OF REPORT *******

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

ANNEX A: EUT Appearance and Test Setup

A.1 EUT Appearance

Front Side



Back Side

For Single Screen Mode

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.



Front Side

Back Side

For Double Screen Mode

Picture 1 EUT and Accessory

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.

A.2 Test Setup





Picture 2: Radiated Spurious Emissions Test setup

This report shall not be reproduced except in full, without the written approval of TA Technology (Shanghai) Co., Ltd.