



TEST REPORT

Application No.: SZEM2011011220CR
Applicant: SZ DJI TECHNOLOGY CO., LTD.
Address of Applicant: 14th floor, West Wing, Skyworth Semiconductor Design Building NO.18
Gaoxin South 4th Ave, Nanshan District, Shenzhen, Guangdong, China
Manufacturer: SZ DJI TECHNOLOGY CO., LTD.
Address of Manufacturer: 14th floor, West Wing, Skyworth Semiconductor Design Building NO.18
Gaoxin South 4th Ave, Nanshan District, Shenzhen, Guangdong, China
Equipment Under Test (EUT):
EUT Name: DJI AIR 2S
Model No.: DA2SUE1
Trade mark: DJI
FCC ID: SS3-DA2SUE12011
Standard(s) : 47 CFR Part 15, Subpart C 15.247
Date of Receipt: 2020-11-06
Date of Test: 2020-11-10 to 2020-12-03
Date of Issue: 2020-12-08

Test Result:	Pass*
---------------------	--------------

* In the configuration tested, the EUT complied with the standards specified above.

Keny Xu

Keny Xu
EMC Laboratory Manager



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/terms-and-conditions/terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.
Attention: To check the authenticity of testing/inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch EMC Laboratory

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn
中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com




SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

Report No.: SZEM201101122002

Page: 2 of 348

Revision Record				
Version	Chapter	Date	Modifier	Remark
01		2020-12-08		Original

Authorized for issue by:			
			
		Harry Wu/Project Engineer	
			
		Eric Fu/Reviewer	



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.
Attention: To check the authenticity of testing/inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

2 Test Summary

Radio Spectrum Technical Requirement				
Item	Standard	Method	Requirement	Result
Antenna Requirement	47 CFR Part 15, Subpart C 15.247	N/A	47 CFR Part 15, Subpart C 15.203 & 15.247(b)(4)	Pass

Radio Spectrum Matter Part				
Item	Standard	Method	Requirement	Result
Conducted Peak Output Power	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 11.9.1	47 CFR Part 15, Subpart C 15.247(b)(3)	Pass
Minimum 6dB Bandwidth	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 11.8.1	47 CFR Part 15, Subpart C 15.247a(2)	Pass
Power Spectrum Density	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 11.10.2	47 CFR Part 15, Subpart C 15.247(e)	Pass
Conducted Band Edges Measurement	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 11.13.3.2	47 CFR Part 15, Subpart C 15.247(d)	Pass
Conducted Spurious Emissions	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 11.11	47 CFR Part 15, Subpart C 15.247(d)	Pass
Radiated Emissions which fall in the restricted bands	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 6.10.5	47 CFR Part 15, Subpart C 15.205 & 15.209	Pass
Radiated Spurious Emissions	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 6.4,6.5,6.6	47 CFR Part 15, Subpart C 15.205 & 15.209	Pass

3 Contents

	Page
1 COVER PAGE	1
2 TEST SUMMARY	3
3 CONTENTS	4
4 GENERAL INFORMATION	6
4.1 DETAILS OF E.U.T.	6
4.2 CABLE	6
4.3 DESCRIPTION OF SUPPORT UNITS	6
4.4 MEASUREMENT UNCERTAINTY	7
4.5 TEST LOCATION.....	8
4.6 TEST FACILITY.....	8
4.7 DEVIATION FROM STANDARDS.....	8
4.8 ABNORMALITIES FROM STANDARD CONDITIONS	8
5 EQUIPMENT LIST.....	9
6 RADIO SPECTRUM TECHNICAL REQUIREMENT	12
6.1 ANTENNA REQUIREMENT	12
6.1.1 Test Requirement:	12
7 RADIO SPECTRUM MATTER TEST RESULTS.....	13
7.1 CONDUCTED PEAK OUTPUT POWER.....	13
7.1.1 E.U.T. Operation	13
7.1.1 Test Mode Description	13
7.1.2 Test Setup Diagram	14
7.1.3 Measurement Procedure and Data.....	14
7.2 MINIMUM 6dB BANDWIDTH.....	15
7.2.1 E.U.T. Operation	15
7.2.2 Test Mode Description	15
7.2.3 Test Setup Diagram	16
7.2.4 Measurement Procedure and Data.....	16
7.3 POWER SPECTRUM DENSITY.....	17
7.3.1 E.U.T. Operation	17
7.3.2 Test Mode Description	17
7.3.3 Test Setup Diagram	18
7.3.4 Measurement Procedure and Data.....	18
7.4 CONDUCTED BAND EDGES MEASUREMENT	19
7.4.1 E.U.T. Operation	19
7.4.2 Test Mode Description	19
7.4.3 Test Setup Diagram	20
7.4.4 Measurement Procedure and Data.....	20
7.5 CONDUCTED SPURIOUS EMISSIONS.....	21
7.5.1 E.U.T. Operation	21
7.5.2 Test Mode Description	21
7.5.3 Test Setup Diagram	22
7.5.4 Measurement Procedure and Data.....	22



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing/inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com
 No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.ssgsgroup.com.cn
 中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com



7.6	RADIATED EMISSIONS WHICH FALL IN THE RESTRICTED BANDS	23
7.6.1	E.U.T. Operation	23
7.6.2	Test Mode Description	23
7.6.3	Test Setup Diagram	24
7.6.4	Measurement Procedure and Data	24
7.7	RADIATED SPURIOUS EMISSIONS	81
7.7.1	E.U.T. Operation	81
7.7.2	Test Mode Description	81
7.7.3	Test Setup Diagram	82
7.7.4	Measurement Procedure and Data	83
8	TEST SETUP PHOTO	128
9	EUT CONSTRUCTIONAL DETAILS (EUT PHOTOS)	128
10	APPENDIX	129-348



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing/inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn
中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

4 General Information

4.1 Details of E.U.T.

Power adapter:	Model: P2C38 Input: AC100-240V,50-60Hz,1.3A Output: DC13.2V,2.82A(Main),DC5.0V,2.0A
Battery:	DC11.55V lithium-ion Polymer battery(3500mAh)
Operation Frequency:	1.4MHz BW:2403.5MHz-2469.5MHz; 1.4MHz BW CA:2405.12MHz-2471.12MHz; 3MHz BW:2408.5MHz-2465.5MHz; 3MHz BW CA:2411.2MHz-2468.2MHz; 10MHz BW:2407.5MHz-2467.5MHz; 20MHz BW:2412.5MHz-2462.5MHz; 40MHz BW:2422.5MHz-2452.5MHz
Modulation Type:	OFDM
Number of Channels:	1.4MHz BW:34; 1.4MHz BW CA:34; 3MHz BW:20; 3MHz BW CA:20; 10MHz BW:61; 20MHz BW:51; 40MHz BW:31
Channel Spacing:	1.4MHz BW:2MHz; 1.4MHz BW CA:2MHz; 3MHz BW:3MHz; 3MHz BW CA:3MHz; 10MHz BW:1MHz; 20MHz BW:1MHz; 40MHz BW:1MHz
Antenna Type:	FPC Antenna
Antenna Gain:	Antenna 1&2: 2.5dBi, Antenna 3&4: 1.5dBi
Antenna Combination:	Antenna 1+Antenna 2, Antenna 1+Antenna 4, Antenna 2+Antenna 3, Antenna 3+Antenna 4

4.2 Cable

Cable	Length	Shielding	Core
AC Cable	1meter	Unshielded	Non-Core
Type C Cable	1meter	Unshielded	Non-Core

4.3 Description of Support Units

Description	Manufacturer	Model No.	Serial No.
--	--	--	--

The EUT has been tested as an independent unit.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing/inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.ssgroup.com.cn
中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com



4.4 Measurement Uncertainty

Test Item	Measurement Uncertainty
Conducted Peak Output Power	$\pm 0.75\text{dB}$
Minimum 6dB Bandwidth	$\pm 3\%$
Power Spectrum Density	$\pm 2.84\text{dB}$
Conducted Band Edges Measurement	$\pm 0.75\text{dB}$
Conducted Spurious Emissions	$\pm 0.75\text{dB}$
Radiated Emissions which fall in the restricted bands	$\pm 4.5\text{dB}$ (Below 1GHz); $\pm 4.8\text{dB}$ (Above 1GHz)
Radiated Spurious Emissions	$\pm 4.5\text{dB}$ (Below 1GHz); $\pm 4.8\text{dB}$ (Above 1GHz)

Remark:

The U_{lab} (lab Uncertainty) is less than U_{CISPR} (CISPR Uncertainty), so the test results

- compliance is deemed to occur if no measured disturbance level exceeds the disturbance limit;
- non-compliance is deemed to occur if any measured disturbance level exceeds the disturbance limit.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.
Attention: To check the authenticity of testing/inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Docscheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn
中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

4.5 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen Branch

No. 1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, Guangdong, China. 518057.

Tel: +86 755 2601 2053 Fax: +86 755 2671 0594

No tests were sub-contracted.

4.6 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **A2LA (Certificate No. 3816.01)**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 3816.01.

- **VCCI**

The 3m Fully-anechoic chamber for above 1GHz, 10m Semi-anechoic chamber for below 1GHz, Shielded Room for Mains Port Conducted Interference Measurement and Telecommunication Port Conducted Interference Measurement of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-20026, R-14188, C-12383 and T-11153 respectively.

- **FCC –Designation Number: CN1178**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized as an accredited testing laboratory.

Designation Number: CN1178. Test Firm Registration Number: 406779.

- **Innovation, Science and Economic Development Canada**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized by ISED as an accredited testing laboratory.

CAB identifier: CN0006.

IC#: 4620C.

4.7 Deviation from Standards

None

4.8 Abnormalities from Standard Conditions

None



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing/inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com
 No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.ssgroup.com.cn
 中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

5 Equipment List

Conducted Peak Output Power					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
Shielding Room	SAEMC	MSR733	SEM001-09	2019-06-13	2022-06-12
DC Power Supply	Rohde & Schwarz	NGSM 32/10	SEM011-04	2020-03-24	2021-03-23
Spectrum Analyzer	Rohde & Schwarz	FSU43	SEM004-08	2020-04-01	2021-03-31
Measurement Software	TST	TST PASS V1.0.5	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM031-02	2020-07-10	2021-07-09
Attenuator	Huber+Suhner	6620_SMA-50-1	SEM021-09	2020-05-21	2021-05-20

Minimum 6dB Bandwidth					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
Shielding Room	SAEMC	MSR733	SEM001-09	2019-06-13	2022-06-12
DC Power Supply	Rohde & Schwarz	NGSM 32/10	SEM011-04	2020-03-24	2021-03-23
Spectrum Analyzer	Rohde & Schwarz	FSU43	SEM004-08	2020-04-01	2021-03-31
Measurement Software	TST	TST PASS V1.0.5	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM031-02	2020-07-10	2021-07-09
Attenuator	Huber+Suhner	6620_SMA-50-1	SEM021-09	2020-05-21	2021-05-20

Power Spectrum Density					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
Shielding Room	SAEMC	MSR733	SEM001-09	2019-06-13	2022-06-12
DC Power Supply	Rohde & Schwarz	NGSM 32/10	SEM011-04	2020-03-24	2021-03-23
Spectrum Analyzer	Rohde & Schwarz	FSU43	SEM004-08	2020-04-01	2021-03-31
Measurement Software	TST	TST PASS V1.0.5	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM031-02	2020-07-10	2021-07-09
Attenuator	Huber+Suhner	6620_SMA-50-1	SEM021-09	2020-05-21	2021-05-20

Conducted Band Edges Measurement					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
Shielding Room	SAEMC	MSR733	SEM001-09	2019-06-13	2022-06-12
DC Power Supply	Rohde & Schwarz	NGSM 32/10	SEM011-04	2020-03-24	2021-03-23
Spectrum Analyzer	Rohde & Schwarz	FSU43	SEM004-08	2020-04-01	2021-03-31
Measurement Software	TST	TST PASS V1.0.5	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM031-02	2020-07-10	2021-07-09



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained herein reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing/inspection report & certificate, please contact us at telephone: (86-755) 83071443, or email: CN.Doccheck@sgs.com
No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

Attenuator	Huber+Suhner	6620_SMA-50-1	SEM021-09	2020-05-21	2021-05-20
------------	--------------	---------------	-----------	------------	------------

Conducted Spurious Emissions

Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
Shielding Room	SAEMC	MSR733	SEM001-09	2019-06-13	2022-06-12
DC Power Supply	Rohde & Schwarz	NGSM 32/10	SEM011-04	2020-03-24	2021-03-23
Spectrum Analyzer	Rohde & Schwarz	FSU43	SEM004-08	2020-04-01	2021-03-31
Measurement Software	TST	TST PASS V1.0.5	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM031-02	2020-07-10	2021-07-09
Attenuator	Huber+Suhner	6620_SMA-50-1	SEM021-09	2020-05-21	2021-05-20

Radiated Emissions which fall in the restricted bands

Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
3m Semi-Anechoic Chamber	AUDIX	N/A	SEM001-02	2018-03-13	2021-03-12
EXA Signal Analyzer	Agilent Technologies Inc	N9010A	SEM004-12	2020-04-09	2021-04-08
Horn Antenna	Rohde&Schwarz	HF907	SEM003-07	2018-04-13	2021-04-12
Pre-Amplifier	Compliance Directions Systems Inc.	PAP-0126	SEM004-11	2020-09-23	2021-09-22
Measurement Software	AUDIX	e3 V8.2014-6-27	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM026-01	2020-07-10	2021-07-09
Horn Antenna	Schwarzbeck	BBHA 9170	SEM003-15	2020-11-14	2023-11-13
Pre-Amplifier	Compliance Directions Systems Inc.	PAP-2640-50	SEM005-08	2020-04-01	2021-03-31

Radiated Spurious Emissions

Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
3m Semi-Anechoic Chamber	ETS-LINDGREN	N/A	SEM001-01	2020-07-19	2023-07-18
MXE EMI Receiver	Agilent Technologies	N9038A	SEM004-15	2020-11-02	2021-11-01
BiConiLog Antenna	ETS-LINDGREN	3142C	SEM003-02	2019-05-24	2022-05-23
Pre-Amplifier	Agilent Technologies	8447D	SEM005-01	2020-04-01	2021-03-31
Measurement Software	AUDIX	e3 V8.2014-6-27	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM025-01	2020-07-10	2021-07-09
3m Semi-Anechoic Chamber	AUDIX	N/A	SEM001-02	2018-03-13	2021-03-12



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained herein reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com
 No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
 中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

EXA Signal Analyzer	Agilent Technologies Inc	N9010A	SEM004-12	2020-04-09	2021-04-08
Horn Antenna	Rohde&Schwarz	HF907	SEM003-07	2018-04-13	2021-04-12
Pre-Amplifier	Compliance Directions Systems Inc.	PAP-0126	SEM004-11	2020-09-23	2021-09-22
Measurement Software	AUDIX	e3 V8.2014-6-27	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM026-01	2020-07-10	2021-07-09
Horn Antenna	Schwarzbeck	BBHA 9170	SEM003-15	2020-11-14	2023-11-13
Pre-Amplifier	Compliance Directions Systems Inc.	PAP-2640-50	SEM005-08	2020-04-01	2021-03-31

General used equipment					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
Humidity/ Temperature Indicator	Shanghai Meteorological Industry Factory	ZJ1-2B	SEM002-04	2020-09-15	2021-09-14
Humidity/ Temperature Indicator	Mingle	N/A	SEM002-08	2020-09-15	2021-09-14
Barometer	Changchun Meteorological Industry Factory	DYM3	SEM002-01	2020-04-07	2021-04-06



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing/inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn
中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

6 Radio Spectrum Technical Requirement

6.1 Antenna Requirement

6.1.1 Test Requirement:

47 CFR Part 15, Subpart C 15.203 & 15.247(b)(4)

Limit:

Standard Requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

15.247(b) (4) requirement:

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

EUT Antenna:

The antenna is integrated on the main PCB and no consideration of replacement. The best case gain of the antennas Antenna 1&2: 2.5dBi, Antenna 3&4: 1.5dBi.

Antenna location: Refer to Internal photos.

7 Radio Spectrum Matter Test Results

7.1 Conducted Peak Output Power

Test Requirement 47 CFR Part 15, Subpart C 15.247(b)(3)

Test Method: ANSI C63.10 (2013) Section 11.9.1

Limit:

Frequency range(MHz)	Output power of the intentional radiator(watt)
902-928	1 for ≥ 50 hopping channels
	0.25 for $25 \leq$ hopping channels < 50
	1 for digital modulation
2400-2483.5	1 for ≥ 75 non-overlapping hopping channels
	0.125 for all other frequency hopping systems
	1 for digital modulation
5725-5850	1 for frequency hopping systems and digital modulation

7.1.1 E.U.T. Operation


Operating Environment:

Temperature: 23.5 °C Humidity: 50.1 % RH Atmospheric Pressure: 1010 mbar

7.1.1 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	00	TX mode(2.4GHz Band-1.4MHz)_Keep the EUT in continuously transmitting mode with modulation
Final test	01	TX mode(2.4GHz Band-1.4MHz CA)_Keep the EUT in continuously transmitting mode with modulation
Final test	02	TX mode(2.4GHz Band-3MHz)_Keep the EUT in continuously transmitting mode with modulation
Final test	03	TX mode(2.4GHz Band-3MHz CA)_Keep the EUT in continuously transmitting mode with modulation
Final test	04	TX mode(2.4GHz Band-10MHz)_Keep the EUT in continuously transmitting mode with modulation
Final test	05	TX mode(2.4GHz Band-20MHz)_Keep the EUT in continuously transmitting mode with modulation
Final test	06	TX mode(2.4GHz Band-40MHz)_Keep the EUT in continuously transmitting mode with modulation

7.1.2 Test Setup Diagram



7.1.3 Measurement Procedure and Data

Please Refer To Appendix For Details

7.2 Minimum 6dB Bandwidth

Test Requirement 47 CFR Part 15, Subpart C 15.247a(2)

Test Method: ANSI C63.10 (2013) Section 11.8.1

Limit: ≥ 500 kHz

7.2.1 E.U.T. Operation


Operating Environment:

Temperature: 23.5 °C Humidity: 50.1 % RH Atmospheric Pressure: 1010 mbar

7.2.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	00	TX mode(2.4GHz Band-1.4MHz)_Keep the EUT in continuously transmitting mode with modulation
Final test	01	TX mode(2.4GHz Band-1.4MHz CA)_Keep the EUT in continuously transmitting mode with modulation
Final test	02	TX mode(2.4GHz Band-3MHz)_Keep the EUT in continuously transmitting mode with modulation
Final test	03	TX mode(2.4GHz Band-3MHz CA)_Keep the EUT in continuously transmitting mode with modulation
Final test	04	TX mode(2.4GHz Band-10MHz)_Keep the EUT in continuously transmitting mode with modulation
Final test	05	TX mode(2.4GHz Band-20MHz)_Keep the EUT in continuously transmitting mode with modulation
Final test	06	TX mode(2.4GHz Band-40MHz)_Keep the EUT in continuously transmitting mode with modulation

7.2.3 Test Setup Diagram



7.2.4 Measurement Procedure and Data

Please Refer To Appendix For Details

7.3 Power Spectrum Density

Test Requirement 47 CFR Part 15, Subpart C 15.247(e)
Test Method: ANSI C63.10 (2013) Section 11.10.2

Limit: $\leq 8\text{dBm}$ in any 3 kHz band during any time interval of continuous transmission

7.3.1 E.U.T. Operation


Operating Environment:

Temperature: 23.5 °C Humidity: 50.1 % RH Atmospheric Pressure: 1010 mbar

7.3.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	00	TX mode(2.4GHz Band-1.4MHz)_Keep the EUT in continuously transmitting mode with modulation
Final test	01	TX mode(2.4GHz Band-1.4MHz CA)_Keep the EUT in continuously transmitting mode with modulation
Final test	02	TX mode(2.4GHz Band-3MHz)_Keep the EUT in continuously transmitting mode with modulation
Final test	03	TX mode(2.4GHz Band-3MHz CA)_Keep the EUT in continuously transmitting mode with modulation
Final test	04	TX mode(2.4GHz Band-10MHz)_Keep the EUT in continuously transmitting mode with modulation
Final test	05	TX mode(2.4GHz Band-20MHz)_Keep the EUT in continuously transmitting mode with modulation
Final test	06	TX mode(2.4GHz Band-40MHz)_Keep the EUT in continuously transmitting mode with modulation

7.3.3 Test Setup Diagram



7.3.4 Measurement Procedure and Data

Please Refer To Appendix For Details

7.4 Conducted Band Edges Measurement

Test Requirement 47 CFR Part 15, Subpart C 15.247(d)
Test Method: ANSI C63.10 (2013) Section 11.13.3.2

Limit:

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

7.4.1 E.U.T. Operation


Operating Environment:

Temperature: 23.5 °C Humidity: 50.1 % RH Atmospheric Pressure: 1010 mbar

7.4.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	00	TX mode(2.4GHz Band-1.4MHz)_Keep the EUT in continuously transmitting mode with modulation
Final test	01	TX mode(2.4GHz Band-1.4MHz CA)_Keep the EUT in continuously transmitting mode with modulation
Final test	02	TX mode(2.4GHz Band-3MHz)_Keep the EUT in continuously transmitting mode with modulation
Final test	03	TX mode(2.4GHz Band-3MHz CA)_Keep the EUT in continuously transmitting mode with modulation
Final test	04	TX mode(2.4GHz Band-10MHz)_Keep the EUT in continuously transmitting mode with modulation
Final test	05	TX mode(2.4GHz Band-20MHz)_Keep the EUT in continuously transmitting mode with modulation
Final test	06	TX mode(2.4GHz Band-40MHz)_Keep the EUT in continuously transmitting mode with modulation

7.4.3 Test Setup Diagram



7.4.4 Measurement Procedure and Data

Please Refer To Appendix For Details

7.5 Conducted Spurious Emissions

Test Requirement 47 CFR Part 15, Subpart C 15.247(d)

Test Method: ANSI C63.10 (2013) Section 11.11

Limit:

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

7.5.1 E.U.T. Operation


Operating Environment:

Temperature: 23.5 °C Humidity: 50.1 % RH Atmospheric Pressure: 1010 mbar

7.5.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	00	TX mode(2.4GHz Band-1.4MHz)_Keep the EUT in continuously transmitting mode with modulation
Final test	01	TX mode(2.4GHz Band-1.4MHz CA)_Keep the EUT in continuously transmitting mode with modulation
Final test	02	TX mode(2.4GHz Band-3MHz)_Keep the EUT in continuously transmitting mode with modulation
Final test	03	TX mode(2.4GHz Band-3MHz CA)_Keep the EUT in continuously transmitting mode with modulation
Final test	04	TX mode(2.4GHz Band-10MHz)_Keep the EUT in continuously transmitting mode with modulation
Final test	05	TX mode(2.4GHz Band-20MHz)_Keep the EUT in continuously transmitting mode with modulation
Final test	06	TX mode(2.4GHz Band-40MHz)_Keep the EUT in continuously transmitting mode with modulation

7.5.3 Test Setup Diagram



7.5.4 Measurement Procedure and Data

Please Refer To Appendix For Details

7.6 Radiated Emissions which fall in the restricted bands

Test Requirement 47 CFR Part 15, Subpart C 15.205 & 15.209

Test Method: ANSI C63.10 (2013) Section 6.10.5

Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

7.6.1 E.U.T. Operation

Operating Environment:

Temperature: 22.7 °C

Humidity: 51.4 % RH

Atmospheric Pressure: 1010 mbar

7.6.2 Test Mode Description


Pre-scan / Final test	Mode Code	Description
Final test	00	TX mode(2.4GHz Band-1.4MHz)_Keep the EUT in continuously transmitting mode with modulation
Final test	01	TX mode(2.4GHz Band-1.4MHz CA)_Keep the EUT in continuously transmitting mode with modulation
Final test	02	TX mode(2.4GHz Band-3MHz)_Keep the EUT in continuously transmitting mode with modulation
Final test	03	TX mode(2.4GHz Band-3MHz CA)_Keep the EUT in continuously transmitting mode with modulation
Final test	04	TX mode(2.4GHz Band-10MHz)_Keep the EUT in continuously transmitting mode with modulation
Final test	05	TX mode(2.4GHz Band-20MHz)_Keep the EUT in continuously transmitting mode with modulation
Final test	06	TX mode(2.4GHz Band-40MHz)_Keep the EUT in continuously transmitting mode with modulation



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com
No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

7.6.3 Test Setup Diagram



7.6.4 Measurement Procedure and Data


- a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- d. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- f. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- g. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- h. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- j. Repeat above procedures until all frequencies measured was complete.

Remark 1: Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor

Remark 2: For frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.

Antenna 1,2,3,4,1+2,1+4,2+3 and 3+4 were tested. Only the worst case(Antenna 1+2) was recorded in the report.


Test Mode: 00; Polarity: Horizontal; Channel:Low



Site : chamber
Condition: 3m HORIZONTAL
Job No : 11220CR\11219CR
Mode : 2403.5 Band edge
Note : 1.4M

		Cable	Ant	Preamp	Read		Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2388.637	4.34	28.52	0.00	27.03	59.89	74.00	-14.11	peak
2	2390.000	4.34	28.52	0.00	24.93	57.79	74.00	-16.21	peak
3 *	2403.500	4.37	28.54	0.00	86.84	119.75	74.00	45.75	peak

Test Mode: 00; Polarity: Horizontal; Channel: Low



Site : chamber
Condition: 3m HORIZONTAL
Job No : 11220CR\11219CR
Mode : 2403.5 Band edge
Note : 1.4M

		Cable	Ant	Preamp	Read		Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2389.242	4.34	28.52	0.00	15.50	48.36	54.00	-5.64	Average
2	2390.000	4.34	28.52	0.00	15.45	48.31	54.00	-5.69	Average
3 *	2403.500	4.37	28.54	0.00	78.36	111.27	54.00	57.27	Average




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing/inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn
中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

Test Mode: 00; Polarity: Vertical; Channel: Low



Site : chamber
Condition: 3m VERTICAL
Job No : 11220CR\11219CR
Mode : 2403.5 Band edge
Note : 1.4M

		Cable	Ant	Preamp	Read		Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2370.801	4.31	28.49	0.00	26.81	59.61	74.00	-14.39	Peak
2	2390.000	4.34	28.52	0.00	24.55	57.41	74.00	-16.59	Peak
3 *	2403.500	4.37	28.54	0.00	78.30	111.21	74.00	37.21	Peak




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing/inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn
中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

Test Mode: 00; Polarity: Vertical; Channel: Low



Site : chamber
Condition: 3m VERTICAL
Job No : 11220CR\11219CR
Mode : 2403.5 Band edge
Note : 1.4M

		Cable	Ant	Preamp	Read		Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2382.838	4.33	28.51	0.00	15.47	48.31	54.00	-5.69	Average
2	2390.000	4.34	28.52	0.00	15.39	48.25	54.00	-5.75	Average
3 *	2403.500	4.37	28.54	0.00	70.38	103.29	54.00	49.29	Average




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing/inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn
中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com


Test Mode: 00; Polarity: Horizontal; Channel: High



Site : chamber
Condition: 3m HORIZONTAL
Job No : 11220CR\11219CR
Mode : 2469.5 Band edge
Note : 1.4M

	Cable	Ant	Preamp	Read		Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 * 2469.500	4.47	28.65	0.00	87.39	120.51	74.00	46.51	peak
2 2483.500	4.49	28.67	0.00	26.44	59.60	74.00	-14.40	peak
3 2498.687	4.52	28.70	0.00	27.71	60.93	74.00	-13.07	peak


Test Mode: 00; Polarity: Horizontal; Channel: High



Site : chamber
Condition: 3m HORIZONTAL
Job No : 11220CR\11219CR
Mode : 2469.5 Band edge
Note : 1.4M

		Cable	Ant	Preamp	Read		Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 *	2469.500	4.47	28.65	0.00	79.26	112.38	54.00	58.38	Average
2	2483.500	4.49	28.67	0.00	15.73	48.89	54.00	-5.11	Average
3	2499.394	4.52	28.70	0.00	15.82	49.04	54.00	-4.96	Average


Test Mode: 00; Polarity: Vertical; Channel: High



Site : chamber
Condition: 3m VERTICAL
Job No : 11220CR\11219CR
Mode : 2469.5 Band edge
Note : 1.4M

	Cable	Ant	Preamp	Read		Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 * 2469.500	4.47	28.65	0.00	78.94	112.06	74.00	38.06	Peak
2 2483.500	4.49	28.67	0.00	24.35	57.51	74.00	-16.49	Peak
3 2491.177	4.51	28.69	0.00	26.67	59.87	74.00	-14.13	Peak


Test Mode: 00; Polarity: Vertical; Channel: High



Site : chamber
Condition: 3m VERTICAL
Job No : 11220CR\11219CR
Mode : 2469.5 Band edge
Note : 1.4M

		Cable	Ant	Preamp	Read		Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 *	2469.500	4.47	28.65	0.00	71.14	104.26	54.00	50.26	Average
2	2483.500	4.49	28.67	0.00	15.67	48.83	54.00	-5.17	Average
3	2497.880	4.52	28.70	0.00	15.82	49.04	54.00	-4.96	Average

Test Mode: 01; Polarity: Horizontal; Channel:Low



Site : chamber
Condition: 3m HORIZONTAL
Job No : 11220CR\11219CR
Mode : 2405.12 Band edge
Note : 1.4M CA

		Cable	Ant	Preamp	Read		Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2339.788	4.26	28.43	0.00	27.78	60.47	74.00	-13.53	peak
2	2390.000	4.34	28.52	0.00	25.41	58.27	74.00	-15.73	peak
3 *	2405.120	4.37	28.54	0.00	86.34	119.25	74.00	45.25	peak




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing/inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

Test Mode: 01; Polarity: Horizontal; Channel:Low



Site : chamber
Condition: 3m HORIZONTAL
Job No : 11220CR\11219CR
Mode : 2405.12 Band edge
Note : 1.4M CA

		Cable	Ant	Preamp	Read		Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2384.166	4.34	28.51	0.00	15.47	48.32	54.00	-5.68	Average
2	2390.000	4.34	28.52	0.00	15.46	48.32	54.00	-5.68	Average
3 *	2405.120	4.37	28.54	0.00	78.05	110.96	54.00	56.96	Average




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing/inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn
中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

Test Mode: 01; Polarity: Vertical; Channel: Low



Site : chamber
Condition: 3m VERTICAL
Job No : 11220CR\11219CR
Mode : 2405.12 Band edge
Note : 1.4M CA

		Cable	Ant	Preamp	Read		Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2388.516	4.34	28.52	0.00	26.71	59.57	74.00	-14.43	Peak
2	2390.000	4.34	28.52	0.00	24.55	57.41	74.00	-16.59	Peak
3 *	2405.120	4.37	28.54	0.00	77.85	110.76	74.00	36.76	Peak




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing/inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

Test Mode: 01; Polarity: Vertical; Channel:Low



Site : chamber
Condition: 3m VERTICAL
Job No : 11220CR\11219CR
Mode : 2405.12 Band edge
Note : 1.4M CA

		Cable	Ant	Preamp	Read		Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2385.252	4.34	28.51	0.00	15.50	48.35	54.00	-5.65	Average
2	2390.000	4.34	28.52	0.00	15.38	48.24	54.00	-5.76	Average
3 *	2405.120	4.37	28.54	0.00	70.54	103.45	54.00	49.45	Average




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing/inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn
中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com


Test Mode: 01; Polarity: Horizontal; Channel: High



Site : chamber
Condition: 3m HORIZONTAL
Job No : 11220CR\11219CR
Mode : 2471.12 Band edge
Note : 1.4M CA

	Cable	Ant	Preamp	Read		Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 * 2471.120	4.47	28.65	0.00	86.93	120.05	74.00	46.05	peak
2 2483.500	4.49	28.67	0.00	25.30	58.46	74.00	-15.54	peak
3 2490.070	4.50	28.68	0.00	27.34	60.52	74.00	-13.48	peak


Test Mode: 01; Polarity: Horizontal; Channel: High



Site : chamber
Condition: 3m HORIZONTAL
Job No : 11220CR\11219CR
Mode : 2471.12 Band edge
Note : 1.4M CA

		Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 * 2471.120	4.47	28.65	0.00	79.05	112.17	54.00	58.17	Average
2 2483.500	4.49	28.67	0.00	15.74	48.90	54.00	-5.10	Average
3 2494.702	4.51	28.69	0.00	15.83	49.03	54.00	-4.97	Average


Test Mode: 01; Polarity: Vertical; Channel: High



Site : chamber
Condition: 3m VERTICAL
Job No : 11220CR\11219CR
Mode : 2471.12 Band edge
Note : 1.4M CA

	Cable	Ant	Preamp	Read		Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 * 2471.120	4.47	28.65	0.00	78.39	111.51	74.00	37.51	Peak
2 2483.500	4.49	28.67	0.00	24.74	57.90	74.00	-16.10	Peak
3 2488.863	4.50	28.68	0.00	27.64	60.82	74.00	-13.18	Peak

Test Mode: 01; Polarity: Vertical; Channel: High



Site : chamber
Condition: 3m VERTICAL
Job No : 11220CR\11219CR
Mode : 2471.12 Band edge
Note : 1.4M CA


		Cable	Ant	Preamp	Read		Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 *	2471.120	4.47	28.65	0.00	70.57	103.69	54.00	49.69	Average
2	2483.500	4.49	28.67	0.00	15.73	48.89	54.00	-5.11	Average
3	2499.646	4.52	28.70	0.00	15.83	49.05	54.00	-4.95	Average



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing/inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com
No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn
中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

Test Mode: 02; Polarity: Horizontal; Channel:Low



Site : chamber
Condition: 3m HORIZONTAL
Job No : 11220CR\11219CR
Mode : 2408.5 Band edge
Note : 3M

		Cable	Ant	Preamp	Read		Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2388.154	4.34	28.52	0.00	27.05	59.91	74.00	-14.09	peak
2	2390.000	4.34	28.52	0.00	25.36	58.22	74.00	-15.78	peak
3 *	2408.500	4.37	28.55	0.00	84.30	117.22	74.00	43.22	peak




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing/inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

Test Mode: 02; Polarity: Horizontal; Channel:Low



Site : chamber
Condition: 3m HORIZONTAL
Job No : 11220CR\11219CR
Mode : 2408.5 Band edge
Note : 3M

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2386.944	4.34	28.51	0.00	15.48	48.33	54.00	-5.67	Average
2	2390.000	4.34	28.52	0.00	15.34	48.20	54.00	-5.80	Average
3 *	2408.500	4.37	28.55	0.00	76.45	109.37	54.00	55.37	Average




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing/inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn
中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

Test Mode: 02; Polarity: Vertical; Channel: Low



Site : chamber
Condition: 3m VERTICAL
Job No : 11220CR\11219CR
Mode : 2408.5 Band edge
Note : 3M


		Cable	Ant	Preamp	Read		Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2378.257	4.33	28.50	0.00	27.19	60.02	74.00	-13.98	Peak
2	2390.000	4.34	28.52	0.00	25.33	58.19	74.00	-15.81	Peak
3 *	2408.500	4.37	28.55	0.00	75.46	108.38	74.00	34.38	Peak



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing/inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

Test Mode: 02; Polarity: Vertical; Channel: Low



Site : chamber
Condition: 3m VERTICAL
Job No : 11220CR\11219CR
Mode : 2408.5 Band edge
Note : 3M


	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2385.736	4.34	28.51	0.00	15.47	48.32	54.00	-5.68	Average
2	2390.000	4.34	28.52	0.00	15.37	48.23	54.00	-5.77	Average
3 *	2408.500	4.37	28.55	0.00	68.50	101.42	54.00	47.42	Average



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing/inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com
No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn
中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

Test Mode: 02; Polarity: Horizontal; Channel: High



Site : chamber
Condition: 3m HORIZONTAL
Job No : 11220CR\11219CR
Mode : 2465.5 Band edge
Note : 3M


	Cable	Ant	Preamp	Read		Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 * 2465.500	4.47	28.64	0.00	85.96	119.07	74.00	45.07	peak
2 2483.500	4.49	28.67	0.00	25.50	58.66	74.00	-15.34	peak
3 2486.250	4.50	28.68	0.00	26.93	60.11	74.00	-13.89	peak



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing/inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com
No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

Test Mode: 02; Polarity: Horizontal; Channel: High



Site : chamber
Condition: 3m HORIZONTAL
Job No : 11220CR\11219CR
Mode : 2465.5 Band edge
Note : 3M

	Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 * 2465.500	4.47	28.64	0.00	78.47	111.58	54.00	57.58 Average
2 2483.500	4.49	28.67	0.00	15.55	48.71	54.00	-5.29 Average
3 2497.173	4.52	28.70	0.00	15.68	48.90	54.00	-5.10 Average




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing/inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn
中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com


Test Mode: 02; Polarity: Vertical; Channel: High



Site : chamber
Condition: 3m VERTICAL
Job No : 11220CR\11219CR
Mode : 2465.5 Band edge
Note : 3M

	Cable	Ant	Preamp	Read		Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 * 2465.500	4.47	28.64	0.00	76.21	109.32	74.00	35.32	Peak
2 2483.500	4.49	28.67	0.00	25.59	58.75	74.00	-15.25	Peak
3 2494.954	4.51	28.69	0.00	26.75	59.95	74.00	-14.05	Peak


Test Mode: 02; Polarity: Vertical; Channel: High



Site : chamber
Condition: 3m VERTICAL
Job No : 11220CR\11219CR
Mode : 2465.5 Band edge
Note : 3M

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 *	2465.500	4.47	28.64	0.00	68.87	101.98	54.00	47.98	Average
2	2483.500	4.49	28.67	0.00	15.58	48.74	54.00	-5.26	Average
3	2497.930	4.52	28.70	0.00	15.69	48.91	54.00	-5.09	Average

Test Mode: 03; Polarity: Horizontal; Channel:Low



Site : chamber
Condition: 3m HORIZONTAL
Job No : 11220CR\11219CR
Mode : 2411.2 Band edge
Note : 3M CA

		Cable	Ant	Preamp	Read		Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2358.347	4.29	28.46	0.00	26.92	59.67	74.00	-14.33	peak
2	2390.000	4.34	28.52	0.00	25.64	58.50	74.00	-15.50	peak
3 *	2411.200	4.38	28.55	0.00	85.67	118.60	74.00	44.60	peak




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing/inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com


Test Mode: 03; Polarity: Horizontal; Channel:Low



Site : chamber
Condition: 3m HORIZONTAL
Job No : 11220CR\11219CR
Mode : 2411.2 Band edge
Note : 3M CA

		Cable	Ant	Preamp	Read		Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2381.993	4.33	28.50	0.00	15.51	48.34	54.00	-5.66	Average
2	2390.000	4.34	28.52	0.00	15.38	48.24	54.00	-5.76	Average
3 *	2411.200	4.38	28.55	0.00	77.58	110.51	54.00	56.51	Average

Test Mode: 03; Polarity: Vertical; Channel: Low



Site : chamber
Condition: 3m VERTICAL
Job No : 11220CR\11219CR
Mode : 2411.2 Band edge
Note : 3M CA

		Cable	Ant	Preamp	Read		Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2381.511	4.33	28.50	0.00	26.71	59.54	74.00	-14.46	Peak
2	2390.000	4.34	28.52	0.00	24.85	57.71	74.00	-16.29	Peak
3 *	2411.200	4.38	28.55	0.00	77.45	110.38	74.00	36.38	Peak




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing/inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com


Test Mode: 03; Polarity: Vertical; Channel: Low



Site : chamber
Condition: 3m VERTICAL
Job No : 11220CR\11219CR
Mode : 2411.2 Band edge
Note : 3M CA

		Cable	Ant	Preamp	Read		Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2388.516	4.34	28.52	0.00	15.50	48.36	54.00	-5.64	Average
2	2390.000	4.34	28.52	0.00	15.41	48.27	54.00	-5.73	Average
3 *	2411.200	4.38	28.55	0.00	70.09	103.02	54.00	49.02	Average

Test Mode: 03; Polarity: Horizontal; Channel: High



Site : chamber
Condition: 3m HORIZONTAL
Job No : 11220CR\11219CR
Mode : 2468.2 Band edge
Note : 3M CA


		Cable	Ant	Preamp	Read		Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 *	2468.200	4.47	28.65	0.00	85.77	118.89	74.00	44.89	peak
2	2483.500	4.49	28.67	0.00	25.08	58.24	74.00	-15.76	peak
3	2498.132	4.52	28.70	0.00	27.28	60.50	74.00	-13.50	peak



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing/inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com
No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

Test Mode: 03; Polarity: Horizontal; Channel: High



Site : chamber
Condition: 3m HORIZONTAL
Job No : 11220CR\11219CR
Mode : 2468.2 Band edge
Note : 3M CA

		Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 * 2468.200	4.47	28.65	0.00	77.73	110.85	54.00	56.85	Average
2 2483.500	4.49	28.67	0.00	15.70	48.86	54.00	-5.14	Average
3 2499.848	4.52	28.70	0.00	15.80	49.02	54.00	-4.98	Average




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing/inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn
中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com


Test Mode: 03; Polarity: Vertical; Channel: High



Site : chamber
Condition: 3m VERTICAL
Job No : 11220CR\11219CR
Mode : 2468.2 Band edge
Note : 3M CA

		Cable	Ant	Preamp	Read		Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 *	2468.200	4.47	28.65	0.00	77.79	110.91	74.00	36.91	Peak
2	2483.500	4.49	28.67	0.00	24.53	57.69	74.00	-16.31	Peak
3	2494.198	4.51	28.69	0.00	27.16	60.36	74.00	-13.64	Peak


Test Mode: 03; Polarity: Vertical; Channel: High



Site : chamber
Condition: 3m VERTICAL
Job No : 11220CR\11219CR
Mode : 2468.2 Band edge
Note : 3M CA

		Cable	Ant	Preamp	Read		Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 *	2468.200	4.47	28.65	0.00	70.12	103.24	54.00	49.24	Average
2	2483.500	4.49	28.67	0.00	15.72	48.88	54.00	-5.12	Average
3	2494.249	4.51	28.69	0.00	15.89	49.09	54.00	-4.91	Average

Test Mode: 04; Polarity: Horizontal; Channel:Low



Site : chamber
Condition: 3m HORIZONTAL
Job No : 11220CR\11219CR
Mode : 2407.5 Band edge
Note : 10M

		Cable	Ant	Preamp	Read		Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2369.960	4.31	28.48	0.00	27.47	60.26	74.00	-13.74	peak
2	2390.000	4.34	28.52	0.00	25.41	58.27	74.00	-15.73	peak
3 *	2407.500	4.37	28.55	0.00	89.74	122.66	74.00	48.66	peak




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing/inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

Test Mode: 04; Polarity: Horizontal; Channel:Low



Site : chamber
Condition: 3m HORIZONTAL
Job No : 11220CR\11219CR
Mode : 2407.5 Band edge
Note : 10M

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2389.121	4.34	28.52	0.00	15.55	48.41	54.00	-5.59	Average
2	2390.000	4.34	28.52	0.00	15.47	48.33	54.00	-5.67	Average
3 *	2407.500	4.37	28.55	0.00	79.88	112.80	54.00	58.80	Average




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing/inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn
中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

Test Mode: 04; Polarity: Vertical; Channel:Low



Site : chamber
Condition: 3m VERTICAL
Job No : 11220CR\11219CR
Mode : 2407.5 Band edge
Note : 10M

		Cable	Ant	Preamp	Read		Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2332.807	4.25	28.42	0.00	26.65	59.32	74.00	-14.68	Peak
2	2390.000	4.34	28.52	0.00	24.59	57.45	74.00	-16.55	Peak
3 *	2407.500	4.37	28.55	0.00	81.58	114.50	74.00	40.50	Peak




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing/inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

Test Mode: 04; Polarity: Vertical; Channel:Low



Site : chamber
Condition: 3m VERTICAL
Job No : 11220CR\11219CR
Mode : 2407.5 Band edge
Note : 10M

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2383.562	4.33	28.51	0.00	15.45	48.29	54.00	-5.71	Average
2	2390.000	4.34	28.52	0.00	15.38	48.24	54.00	-5.76	Average
3 *	2407.500	4.37	28.55	0.00	72.90	105.82	54.00	51.82	Average




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing/inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn
中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

Test Mode: 04; Polarity: Horizontal; Channel: High



Site : chamber
Condition: 3m HORIZONTAL
Job No : 11220CR\11219CR
Mode : 2467.5 Band edge
Note : 10M


		Cable	Ant	Preamp	Read		Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 *	2467.500	4.47	28.65	0.00	90.06	123.18	74.00	49.18	peak
2	2483.500	4.49	28.67	0.00	25.25	58.41	74.00	-15.59	peak
3	2493.493	4.51	28.69	0.00	27.96	61.16	74.00	-12.84	peak



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing/inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com
No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.ssgroup.com.cn
中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

Test Mode: 04; Polarity: Horizontal; Channel: High



Site : chamber
Condition: 3m HORIZONTAL
Job No : 11220CR\11219CR
Mode : 2467.5 Band edge
Note : 10M

		Cable	Ant	Preamp	Read		Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 *	2467.500	4.47	28.65	0.00	80.60	113.72	54.00	59.72	Average
2	2483.500	4.49	28.67	0.00	15.85	49.01	54.00	-4.99	Average
3	2496.770	4.51	28.69	0.00	15.91	49.11	54.00	-4.89	Average




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing/inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn
中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

Test Mode: 04; Polarity: Vertical; Channel: High



Site : chamber
Condition: 3m VERTICAL
Job No : 11220CR\11219CR
Mode : 2467.5 Band edge
Note : 10M

	Cable	Ant	Preamp	Read		Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 * 2467.500	4.47	28.65	0.00	82.30	115.42	74.00	41.42	Peak
2 2483.500	4.49	28.67	0.00	25.15	58.31	74.00	-15.69	Peak
3 2494.249	4.51	28.69	0.00	27.17	60.37	74.00	-13.63	Peak




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing/inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn
中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com


Test Mode: 04; Polarity: Vertical; Channel: High



Site : chamber
Condition: 3m VERTICAL
Job No : 11220CR\11219CR
Mode : 2467.5 Band edge
Note : 10M

	Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 * 2467.500	4.47	28.65	0.00	73.26	106.38	54.00	52.38 Average
2 2483.500	4.49	28.67	0.00	15.74	48.90	54.00	-5.10 Average
3 2499.949	4.52	28.70	0.00	15.90	49.12	54.00	-4.88 Average

Test Mode: 05; Polarity: Horizontal; Channel:Low



Site : chamber
Condition: 3m HORIZONTAL
Job No : 11220CR\11219CR
Mode : 2412.5 Band edge
Note : 20M

		Cable	Ant	Preamp	Read		Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2348.835	4.28	28.45	0.00	26.80	59.53	74.00	-14.47	peak
2	2390.000	4.34	28.52	0.00	25.52	58.38	74.00	-15.62	peak
3 *	2412.500	4.38	28.56	0.00	88.37	121.31	74.00	47.31	peak




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing/inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

Test Mode: 05; Polarity: Horizontal; Channel:Low



Site : chamber
Condition: 3m HORIZONTAL
Job No : 11220CR\11219CR
Mode : 2412.5 Band edge
Note : 20M

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2388.925	4.34	28.52	0.00	15.72	48.58	54.00	-5.42	Average
2	2390.000	4.34	28.52	0.00	15.71	48.57	54.00	-5.43	Average
3 *	2412.500	4.38	28.56	0.00	76.83	109.77	54.00	55.77	Average




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing/inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn
中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

Test Mode: 05; Polarity: Vertical; Channel:Low



Site : chamber
Condition: 3m VERTICAL
Job No : 11220CR\11219CR
Mode : 2412.5 Band edge
Note : 20M

		Cable	Ant	Preamp	Read		Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2365.742	4.30	28.48	0.00	26.55	59.33	74.00	-14.67	Peak
2	2390.000	4.34	28.52	0.00	25.19	58.05	74.00	-15.95	Peak
3 *	2412.500	4.38	28.56	0.00	79.87	112.81	74.00	38.81	Peak




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing/inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

Test Mode: 05; Polarity: Vertical; Channel: Low



Site : chamber
Condition: 3m VERTICAL
Job No : 11220CR\11219CR
Mode : 2412.5 Band edge
Note : 20M

		Cable	Ant	Preamp	Read		Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2381.122	4.33	28.50	0.00	15.80	48.63	54.00	-5.37	Average
2	2390.000	4.34	28.52	0.00	15.62	48.48	54.00	-5.52	Average
3 *	2412.500	4.38	28.56	0.00	69.33	102.27	54.00	48.27	Average




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing/inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn
中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

Test Mode: 05; Polarity: Horizontal; Channel: High



Site : chamber
Condition: 3m HORIZONTAL
Job No : 11220CR\11219CR
Mode : 2462.5 Band edge
Note : 20M

	Cable	Ant	Preamp	Read		Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 * 2462.500	4.46	28.64	0.00	88.18	121.28	74.00	47.28	peak
2 2483.500	4.49	28.67	0.00	25.11	58.27	74.00	-15.73	peak
3 2493.193	4.51	28.69	0.00	27.42	60.62	74.00	-13.38	peak




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing/inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

Test Mode: 05; Polarity: Horizontal; Channel: High



Site : chamber
Condition: 3m HORIZONTAL
Job No : 11220CR\11219CR
Mode : 2462.5 Band edge
Note : 20M

		Cable	Ant	Preamp	Read		Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 *	2462.500	4.46	28.64	0.00	76.54	109.64	54.00	55.64	Average
2	2483.500	4.49	28.67	0.00	16.26	49.42	54.00	-4.58	Average
3	2484.147	4.50	28.67	0.00	16.22	49.39	54.00	-4.61	Average




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing/inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn
中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

Test Mode: 05; Polarity: Vertical; Channel: High



Site : chamber
Condition: 3m VERTICAL
Job No : 11220CR\11219CR
Mode : 2462.5 Band edge
Note : 20M

	Cable	Ant	Preamp	Read		Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 * 2462.500	4.46	28.64	0.00	79.22	112.32	74.00	38.32	Peak
2 2483.500	4.49	28.67	0.00	25.16	58.32	74.00	-15.68	Peak
3 2498.155	4.52	28.70	0.00	26.95	60.17	74.00	-13.83	Peak




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing/inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com


Test Mode: 05; Polarity: Vertical; Channel: High



Site : chamber
Condition: 3m VERTICAL
Job No : 11220CR\11219CR
Mode : 2462.5 Band edge
Note : 20M

		Cable	Ant	Preamp	Read		Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 *	2462.500	4.46	28.64	0.00	68.10	101.20	54.00	47.20	Average
2	2483.500	4.49	28.67	0.00	15.96	49.12	54.00	-4.88	Average
3	2490.717	4.51	28.68	0.00	16.05	49.24	54.00	-4.76	Average

Test Mode: 06; Polarity: Horizontal; Channel:Low



Site : chamber
Condition: 3m HORIZONTAL
Job No : 11220CR\11219CR
Mode : 2422.5 Band edge
Note : 40M

		Cable	Ant	Preamp	Read		Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2372.449	4.32	28.49	0.00	26.76	59.57	74.00	-14.43	peak
2	2390.000	4.34	28.52	0.00	24.79	57.65	74.00	-16.35	peak
3 *	2422.500	4.40	28.57	0.00	83.19	116.16	74.00	42.16	peak




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing/inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

Test Mode: 06; Polarity: Horizontal; Channel:Low



Site : chamber
Condition: 3m HORIZONTAL
Job No : 11220CR\11219CR
Mode : 2422.5 Band edge
Note : 40M

		Cable	Ant	Preamp	Read		Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2389.677	4.34	28.52	0.00	15.70	48.56	54.00	-5.44	Average
2	2390.000	4.34	28.52	0.00	15.68	48.54	54.00	-5.46	Average
3 *	2422.500	4.40	28.57	0.00	71.61	104.58	54.00	50.58	Average




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing/inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn
中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

Test Mode: 06; Polarity: Vertical; Channel: Low



Site : chamber
Condition: 3m VERTICAL
Job No : 11220CR\11219CR
Mode : 2422.5 Band edge
Note : 40M

		Cable	Ant	Preamp	Read		Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2380.224	4.33	28.50	0.00	26.18	59.01	74.00	-14.99	Peak
2	2390.000	4.34	28.52	0.00	25.15	58.01	74.00	-15.99	Peak
3 *	2422.500	4.40	28.57	0.00	74.94	107.91	74.00	33.91	Peak




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing/inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

Test Mode: 06; Polarity: Vertical; Channel: Low



Site : chamber
Condition: 3m VERTICAL
Job No : 11220CR\11219CR
Mode : 2422.5 Band edge
Note : 40M

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2369.466	4.31	28.48	0.00	15.72	48.51	54.00	-5.49	Average
2	2390.000	4.34	28.52	0.00	15.57	48.43	54.00	-5.57	Average
3 *	2422.500	4.40	28.57	0.00	63.93	96.90	54.00	42.90	Average




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing/inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn
中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com


Test Mode: 06; Polarity: Horizontal; Channel: High



Site : chamber
Condition: 3m HORIZONTAL
Job No : 11220CR\11219CR
Mode : 2452.5 Band edge
Note : 40M

	Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 * 2452.500	4.45	28.62	0.00	83.66	116.73	74.00	42.73 peak
2 2483.500	4.49	28.67	0.00	25.61	58.77	74.00	-15.23 peak
3 2488.313	4.50	28.68	0.00	27.23	60.41	74.00	-13.59 peak

Test Mode: 06; Polarity: Horizontal; Channel: High



Site : chamber
Condition: 3m HORIZONTAL
Job No : 11220CR\11219CR
Mode : 2452.5 Band edge
Note : 40M

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 *	2452.500	4.45	28.62	0.00	70.84	103.91	54.00	49.91	Average
2	2483.500	4.49	28.67	0.00	16.13	49.29	54.00	-4.71	Average
3	2486.405	4.50	28.68	0.00	16.22	49.40	54.00	-4.60	Average




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing/inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn
中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com


Test Mode: 06; Polarity: Vertical; Channel: High



Site : chamber
Condition: 3m VERTICAL
Job No : 11220CR\11219CR
Mode : 2452.5 Band edge
Note : 40M

	Cable	Ant	Preamp	Read		Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 * 2452.500	4.45	28.62	0.00	73.38	106.45	74.00	32.45	Peak
2 2483.500	4.49	28.67	0.00	25.12	58.28	74.00	-15.72	Peak
3 2498.793	4.52	28.70	0.00	26.77	59.99	74.00	-14.01	Peak

Test Mode: 06; Polarity: Vertical; Channel: High



Site : chamber
Condition: 3m VERTICAL
Job No : 11220CR\11219CR
Mode : 2452.5 Band edge
Note : 40M

	Cable	Ant	Preamp	Read		Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 * 2452.500	4.45	28.62	0.00	62.42	95.49	54.00	41.49	Average
2 2483.500	4.49	28.67	0.00	15.91	49.07	54.00	-4.93	Average
3 2495.885	4.51	28.69	0.00	16.10	49.30	54.00	-4.70	Average



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing/inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn
中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

7.7 Radiated Spurious Emissions

Test Requirement 47 CFR Part 15, Subpart C 15.205 & 15.209

Test Method: ANSI C63.10 (2013) Section 6.4,6.5,6.6

Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

7.7.1 E.U.T. Operation

Operating Environment:

Temperature: 25.2 °C

Humidity: 51.3 % RH

Atmospheric Pressure: 1015 mbar

7.7.2 Test Mode Description


Pre-scan / Final test	Mode Code	Description
Final test	00	TX mode(2.4GHz Band-1.4MHz)_Keep the EUT in continuously transmitting mode with modulation
Final test	01	TX mode(2.4GHz Band-1.4MHz CA)_Keep the EUT in continuously transmitting mode with modulation
Final test	02	TX mode(2.4GHz Band-3MHz)_Keep the EUT in continuously transmitting mode with modulation
Final test	03	TX mode(2.4GHz Band-3MHz CA)_Keep the EUT in continuously transmitting mode with modulation
Final test	04	TX mode(2.4GHz Band-10MHz)_Keep the EUT in continuously transmitting mode with modulation
Final test	05	TX mode(2.4GHz Band-20MHz)_Keep the EUT in continuously transmitting mode with modulation
Final test	06	TX mode(2.4GHz Band-40MHz)_Keep the EUT in continuously transmitting mode with modulation



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com
No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

7.7.3 Test Setup Diagram



7.7.4 Measurement Procedure and Data


- a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- d. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- f. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- g. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- h. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- j. Repeat above procedures until all frequencies measured was complete.

Remark:

- 1) For emission below 1GHz, through pre-scan found the worst case is the lowest channel. Only the worst case is recorded in the report.
- 2) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:
Final Test Level = Receiver Reading + Antenna Factor + Cable Factor - Preamplifier Factor
- 3) Scan from 9kHz to 25GHz, the disturbance above 18GHz and below 30MHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.
- 4) For frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.

Antenna 1,2,3,4,1+2,1+4,2+3 and 3+4 were tested. Only the worst case(Antenna 1+2) was recorded in the report.
Below 1GHz (Worst Case):

Test Mode: 00; Polarity: Horizontal




Condition: 3m HORIZONTAL

Job No. : 11220CR

Test Mode: 00

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	30.32	0.60	22.76	27.73	24.81	20.44	40.00	-19.56	QP
2	241.68	1.57	17.87	27.02	42.21	34.63	46.00	-11.37	QP
3	273.23	1.82	18.53	26.93	38.35	31.77	46.00	-14.23	QP
4	286.98	1.91	18.33	26.90	35.76	29.10	46.00	-16.90	QP
5	361.71	2.20	21.79	27.21	30.36	27.14	46.00	-18.86	QP
6 pp	719.20	2.98	27.48	27.88	33.60	36.18	46.00	-9.82	QP

Test Mode: 00; Polarity: Vertical



Condition: 3m VERTICAL


Job No. : 11220CR

Test Mode: 00

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	30.96	0.61	22.27	27.73	25.60	20.75	40.00	-19.25	QP
2	90.54	1.29	13.21	27.62	29.52	16.40	43.50	-27.10	QP
3	243.38	1.59	17.94	27.01	31.23	23.75	46.00	-22.25	QP
4	361.71	2.20	21.79	27.21	27.65	24.43	46.00	-21.57	QP
5 pp	719.20	2.98	27.48	27.88	34.10	36.68	46.00	-9.32	QP
6	916.07	3.52	29.14	27.08	27.80	33.38	46.00	-12.62	QP

Above 1GHz:


Test Mode: 00; Polarity: Horizontal; Modulation: OFDM; Channel: Low



Site : chamber
Condition: 3m HORIZONTAL
Job No : 11220CR\11219CR
Mode : 2403.5 TX SE
Note : 1.4M

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1682.477	3.42	26.60	40.05	47.77	37.74	74.00	-36.26	peak
2	4279.589	6.56	33.22	41.67	49.05	47.16	74.00	-26.84	peak
3	4808.000	7.10	33.98	42.14	50.08	49.02	74.00	-24.98	peak
4	6451.353	8.28	35.55	42.07	50.10	51.86	74.00	-22.14	peak
5	7212.000	8.74	36.07	41.50	47.16	50.47	74.00	-23.53	peak
6	9616.000	10.80	37.67	37.75	43.08	53.80	74.00	-20.20	peak


Test Mode: 00; Polarity: Vertical; Modulation: OFDM; Channel: Low



Site : chamber
Condition: 3m VERTICAL
Job No : 11220CR\11219CR
Mode : 2403.5 TX SE
Note : 1.4M

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1335.141	3.00	25.17	39.85	49.19	37.51	74.00	-36.49	peak
2	4469.214	6.73	33.55	41.85	48.52	46.95	74.00	-27.05	peak
3	4808.000	7.10	33.98	42.14	48.43	47.37	74.00	-26.63	peak
4	6717.762	8.40	35.73	41.89	48.30	50.54	74.00	-23.46	peak
5	7212.000	8.74	36.07	41.50	46.84	50.15	74.00	-23.85	peak
6	9616.000	10.80	37.67	37.75	42.57	53.29	74.00	-20.71	peak


Test Mode: 00; Polarity: Horizontal; Modulation: OFDM; Channel: middle



Site : chamber
Condition: 3m HORIZONTAL
Job No : 11220CR\11219CR
Mode : 2435.5 TX SE
Note : 1.4M

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1335.141	3.00	25.17	39.85	48.33	36.65	74.00	-37.35	peak
2	4443.453	6.71	33.50	41.82	48.68	47.07	74.00	-26.93	peak
3	4874.000	7.17	34.05	42.20	50.30	49.32	74.00	-24.68	peak
4	6395.654	8.28	35.50	42.11	48.83	50.50	74.00	-23.50	peak
5	7311.000	8.84	36.15	41.41	48.09	51.67	74.00	-22.33	peak
6	9748.000	10.76	37.75	37.52	42.83	53.82	74.00	-20.18	peak


Test Mode: 00; Polarity: Vertical; Modulation: OFDM; Channel: middle



Site : chamber
Condition: 3m VERTICAL
Job No : 11220CR\11219CR
Mode : 2435.5 TX SE
Note : 1.4M

		Cable	Ant	Preamp	Read		Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1335.141	3.00	25.17	39.85	51.05	39.37	74.00	-34.63	peak
2	4495.125	6.76	33.59	41.87	47.83	46.31	74.00	-27.69	peak
3	4874.000	7.17	34.05	42.20	48.74	47.76	74.00	-26.24	peak
4	6340.436	8.27	35.44	42.15	49.09	50.65	74.00	-23.35	peak
5	7311.000	8.84	36.15	41.41	47.33	50.91	74.00	-23.09	peak
6	9748.000	10.76	37.75	37.52	42.99	53.98	74.00	-20.02	peak


Test Mode: 00; Polarity: Horizontal; Modulation: OFDM; Channel: High



Site : chamber
Condition: 3m HORIZONTAL
Job No : 11220CR\11219CR
Mode : 2469.5 TX SE
Note : 1.4M

		Cable	Ant	Preamp	Read		Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1592.571	3.34	26.22	40.00	47.27	36.83	74.00	-37.17	peak
2	4482.150	6.74	33.57	41.86	48.26	46.71	74.00	-27.29	peak
3	4936.000	7.23	34.13	42.25	48.91	48.02	74.00	-25.98	peak
4	6340.436	8.27	35.44	42.15	49.06	50.62	74.00	-23.38	peak
5	7404.000	8.92	36.23	41.32	46.39	50.22	74.00	-23.78	peak
6	9872.000	10.73	37.82	37.31	42.31	53.55	74.00	-20.45	peak


Test Mode: 00; Polarity: Vertical; Modulation: OFDM; Channel: High



Site : chamber
Condition: 3m VERTICAL
Job No : 11220CR\11219CR
Mode : 2469.5 TX SE
Note : 1.4M

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1335.141	3.00	25.17	39.85	49.68	38.00	74.00	-36.00	peak
2	4482.150	6.74	33.57	41.86	47.56	46.01	74.00	-27.99	peak
3	4936.000	7.23	34.13	42.25	48.88	47.99	74.00	-26.01	peak
4	6874.906	8.48	35.83	41.78	48.80	51.33	74.00	-22.67	peak
5	7404.000	8.92	36.23	41.32	46.28	50.11	74.00	-23.89	peak
6	9872.000	10.73	37.82	37.31	42.01	53.25	74.00	-20.75	peak


Test Mode: 01; Polarity: Horizontal; Modulation: OFDM; Channel: Low



Site : chamber
Condition: 3m HORIZONTAL
Job No : 11220CR\11219CR
Mode : 2405.12 TX SE
Note : 1.4M CA

		Cable	Ant	Preamp	Read		Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1687.347	3.42	26.62	40.05	47.65	37.64	74.00	-36.36	peak
2	4109.872	6.39	32.91	41.51	50.62	48.41	74.00	-25.59	peak
3	4810.000	7.10	33.98	42.14	48.21	47.15	74.00	-26.85	peak
4	6995.172	8.54	35.90	41.70	48.18	50.92	74.00	-23.08	peak
5	7215.000	8.75	36.08	41.50	46.84	50.17	74.00	-23.83	peak
6	9620.000	10.80	37.67	37.74	42.50	53.23	74.00	-20.77	peak


Test Mode: 01; Polarity: Vertical; Modulation: OFDM; Channel: Low



Site : chamber
 Condition: 3m VERTICAL
 Job No : 11220CR\11219CR
 Mode : 2405.12 TX SE
 Note : 1.4M CA

		Cable	Ant	Preamp	Read		Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1335.141	3.00	25.17	39.85	50.56	38.88	74.00	-35.12	peak
2	4443.453	6.71	33.50	41.82	49.02	47.41	74.00	-26.59	peak
3	4810.000	7.10	33.98	42.14	48.36	47.30	74.00	-26.70	peak
4	6583.209	8.32	35.65	41.98	49.58	51.57	74.00	-22.43	peak
5	7215.000	8.75	36.08	41.50	47.83	51.16	74.00	-22.84	peak
6	9620.000	10.80	37.67	37.74	42.70	53.43	74.00	-20.57	peak


Test Mode: 01; Polarity: Horizontal; Modulation: OFDM; Channel: middle



Site : chamber
Condition: 3m HORIZONTAL
Job No : 11220CR\11219CR
Mode : 2437.12 TX SE
Note : 1.4M CA

		Cable	Ant	Preamp	Read		Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1335.141	3.00	25.17	39.85	51.77	40.09	74.00	-33.91	peak
2	4354.454	6.63	33.35	41.74	49.47	47.71	74.00	-26.29	peak
3	4874.000	7.17	34.05	42.20	48.04	47.06	74.00	-26.94	peak
4	6737.207	8.41	35.75	41.87	48.84	51.13	74.00	-22.87	peak
5	7311.000	8.84	36.15	41.41	47.13	50.71	74.00	-23.29	peak
6	9748.000	10.76	37.75	37.52	42.26	53.25	74.00	-20.75	peak


Test Mode: 01; Polarity: Vertical; Modulation: OFDM; Channel: middle



Site : chamber
 Condition: 3m VERTICAL
 Job No : 11220CR\11219CR
 Mode : 2437.12 TX SE
 Note : 1.4M CA

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1335.141	3.00	25.17	39.85	49.68	38.00	74.00	-36.00	peak
2	4279.589	6.56	33.22	41.67	49.14	47.25	74.00	-26.75	peak
3	4874.000	7.17	34.05	42.20	47.75	46.77	74.00	-27.23	peak
4	6698.373	8.39	35.72	41.90	48.64	50.85	74.00	-23.15	peak
5	7311.000	8.84	36.15	41.41	47.84	51.42	74.00	-22.58	peak
6	9748.000	10.76	37.75	37.52	42.11	53.10	74.00	-20.90	peak


Test Mode: 01; Polarity: Horizontal; Modulation: OFDM; Channel: High



Site : chamber
Condition: 3m HORIZONTAL
Job No : 11220CR\11219CR
Mode : 2471.12 TX SE
Note : 1.4M CA

		Cable	Ant	Preamp	Read		Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1692.231	3.42	26.64	40.06	47.13	37.13	74.00	-36.87	peak
2	4291.977	6.57	33.24	41.68	49.15	47.28	74.00	-26.72	peak
3	4942.000	7.24	34.13	42.25	48.95	48.07	74.00	-25.93	peak
4	6914.763	8.50	35.85	41.76	47.63	50.22	74.00	-23.78	peak
5	7413.000	8.93	36.23	41.31	46.51	50.36	74.00	-23.64	peak
6	9884.000	10.72	37.83	37.29	42.37	53.63	74.00	-20.37	peak


Test Mode: 01; Polarity: Vertical; Modulation: OFDM; Channel: High



Site : chamber
Condition: 3m VERTICAL
Job No : 11220CR\11219CR
Mode : 2471.12 TX SE
Note : 1.4M CA

		Cable	Ant	Preamp	Read		Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1611.091	3.36	26.30	40.01	48.58	38.23	74.00	-35.77	peak
2	4230.396	6.51	33.13	41.63	49.62	47.63	74.00	-26.37	peak
3	4942.000	7.24	34.13	42.25	46.93	46.05	74.00	-27.95	peak
4	6995.172	8.54	35.90	41.70	48.80	51.54	74.00	-22.46	peak
5	7413.000	8.93	36.23	41.31	47.51	51.36	74.00	-22.64	peak
6	9884.000	10.72	37.83	37.29	42.07	53.33	74.00	-20.67	peak


Test Mode: 02; Polarity: Horizontal; Modulation: OFDM; Channel: Low



Site : chamber
Condition: 3m HORIZONTAL
Job No : 11220CR\11219CR
Mode : 2408.5 TX SE
Note : 3M

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1606.441	3.35	26.28	40.01	48.88	38.50	74.00	-35.50	peak
2	4367.058	6.64	33.37	41.75	49.42	47.68	74.00	-26.32	peak
3	4816.000	7.11	33.99	42.15	48.16	47.11	74.00	-26.89	peak
4	6414.167	8.28	35.52	42.10	49.04	50.74	74.00	-23.26	peak
5	7224.000	8.75	36.08	41.49	47.63	50.97	74.00	-23.03	peak
6	9632.000	10.80	37.68	37.72	42.86	53.62	74.00	-20.38	peak


Test Mode: 02; Polarity: Vertical; Modulation: OFDM; Channel: Low



Site : chamber
Condition: 3m VERTICAL
Job No : 11220CR\11219CR
Mode : 2408.5 TX SE
Note : 3M

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1335.141	3.00	25.17	39.85	50.92	39.24	74.00	-34.76	peak
2	4443.453	6.71	33.50	41.82	49.27	47.66	74.00	-26.34	peak
3	4816.000	7.11	33.99	42.15	48.72	47.67	74.00	-26.33	peak
4	6717.762	8.40	35.73	41.89	48.12	50.36	74.00	-23.64	peak
5	7224.000	8.75	36.08	41.49	47.60	50.94	74.00	-23.06	peak
6	9632.000	10.80	37.68	37.72	42.58	53.34	74.00	-20.66	peak


Test Mode: 02; Polarity: Horizontal; Modulation: OFDM; Channel: middle



Site : chamber
Condition: 3m HORIZONTAL
Job No : 11220CR\11219CR
Mode : 2435.5 TX SE
Note : 3M

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1335.141	3.00	25.17	39.85	49.36	37.68	74.00	-36.32	peak
2	4417.841	6.68	33.46	41.80	48.70	47.04	74.00	-26.96	peak
3	4866.000	7.16	34.05	42.19	47.61	46.63	74.00	-27.37	peak
4	6974.982	8.53	35.89	41.72	48.14	50.84	74.00	-23.16	peak
5	7299.000	8.82	36.14	41.42	46.25	49.79	74.00	-24.21	peak
6	9732.000	10.77	37.74	37.55	42.62	53.58	74.00	-20.42	peak


Test Mode: 02; Polarity: Vertical; Modulation: OFDM; Channel: middle



Site : chamber
Condition: 3m VERTICAL
Job No : 11220CR\11219CR
Mode : 2435.5 TX SE
Note : 3M

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1335.141	3.00	25.17	39.85	51.30	39.62	74.00	-34.38	peak
2	4279.589	6.56	33.22	41.67	49.69	47.80	74.00	-26.20	peak
3	4866.000	7.16	34.05	42.19	47.80	46.82	74.00	-27.18	peak
4	6602.265	8.33	35.66	41.97	48.65	50.67	74.00	-23.33	peak
5	7299.000	8.82	36.14	41.42	47.12	50.66	74.00	-23.34	peak
6	9732.000	10.77	37.74	37.55	42.55	53.51	74.00	-20.49	peak

Test Mode: 02; Polarity: Horizontal; Modulation: OFDM; Channel: High



Site : chamber
Condition: 3m HORIZONTAL
Job No : 11220CR\11219CR
Mode : 2465.5 TX SE
Note : 3M

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1697.129	3.43	26.66	40.06	46.87	36.90	74.00	-37.10	peak
2	4443.453	6.71	33.50	41.82	49.19	47.58	74.00	-26.42	peak
3	4930.000	7.23	34.12	42.24	49.92	49.03	74.00	-24.97	peak
4	6756.708	8.42	35.76	41.86	48.59	50.91	74.00	-23.09	peak
5	7395.000	8.91	36.22	41.33	46.94	50.74	74.00	-23.26	peak
6	9860.000	10.73	37.82	37.33	42.65	53.87	74.00	-20.13	peak




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing/inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn
中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com


Test Mode: 02; Polarity: Vertical; Modulation: OFDM; Channel: High



Site : chamber
Condition: 3m VERTICAL
Job No : 11220CR\11219CR
Mode : 2465.5 TX SE
Note : 3M

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1335.141	3.00	25.17	39.85	51.09	39.41	74.00	-34.59	peak
2	4456.315	6.72	33.53	41.84	48.81	47.22	74.00	-26.78	peak
3	4930.000	7.23	34.12	42.24	47.51	46.62	74.00	-27.38	peak
4	6602.265	8.33	35.66	41.97	48.92	50.94	74.00	-23.06	peak
5	7395.000	8.91	36.22	41.33	47.33	51.13	74.00	-22.87	peak
6	9860.000	10.73	37.82	37.33	42.25	53.47	74.00	-20.53	peak


Test Mode: 03; Polarity: Horizontal; Modulation: OFDM; Channel: Low



Site : chamber
Condition: 3m HORIZONTAL
Job No : 11220CR\11219CR
Mode : 2411.2 TX SE
Note : 3M CA

		Cable	Ant	Preamp	Read		Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1335.141	3.00	25.17	39.85	49.58	37.90	74.00	-36.10	peak
2	4443.453	6.71	33.50	41.82	48.94	47.33	74.00	-26.67	peak
3	4822.000	7.11	33.99	42.15	47.65	46.60	74.00	-27.40	peak
4	6432.732	8.28	35.54	42.08	48.59	50.33	74.00	-23.67	peak
5	7233.000	8.76	36.09	41.48	46.46	49.83	74.00	-24.17	peak
6	9644.000	10.80	37.69	37.70	42.63	53.42	74.00	-20.58	peak

Test Mode: 03; Polarity: Vertical; Modulation: OFDM; Channel: Low



Site : chamber
Condition: 3m VERTICAL
Job No : 11220CR\11219CR
Mode : 2411.2 TX SE
Note : 3M CA

		Cable	Ant	Preamp	Read		Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1335.141	3.00	25.17	39.85	49.56	37.88	74.00	-36.12	peak
2	4291.977	6.57	33.24	41.68	49.30	47.43	74.00	-26.57	peak
3	4822.000	7.11	33.99	42.15	48.47	47.42	74.00	-26.58	peak
4	6894.806	8.49	35.84	41.77	48.65	51.21	74.00	-22.79	peak
5	7233.000	8.76	36.09	41.48	48.73	52.10	74.00	-21.90	peak
6	9644.000	10.80	37.69	37.70	42.56	53.35	74.00	-20.65	peak




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing/inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn
中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com


Test Mode: 03; Polarity: Horizontal; Modulation: OFDM; Channel: middle



Site : chamber
Condition: 3m HORIZONTAL
Job No : 11220CR\11219CR
Mode : 2438.2 TX SE
Note : 3M CA

		Cable	Ant	Preamp	Read		Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1538.281	3.29	25.98	39.97	48.63	37.93	74.00	-36.07	peak
2	4379.699	6.65	33.39	41.77	49.04	47.31	74.00	-26.69	peak
3	4876.000	7.17	34.06	42.20	47.60	46.63	74.00	-27.37	peak
4	6488.754	8.28	35.59	42.04	48.90	50.73	74.00	-23.27	peak
5	7314.000	8.84	36.15	41.40	47.11	50.70	74.00	-23.30	peak
6	9752.000	10.76	37.75	37.52	42.54	53.53	74.00	-20.47	peak


Test Mode: 03; Polarity: Vertical; Modulation: OFDM; Channel: middle



Site : chamber
Condition: 3m VERTICAL
Job No : 11220CR\11219CR
Mode : 2438.2 TX SE
Note : 3M CA

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1335.141	3.00	25.17	39.85	51.36	39.68	74.00	-34.32	peak
2	4443.453	6.71	33.50	41.82	48.44	46.83	74.00	-27.17	peak
3	4876.000	7.17	34.06	42.20	47.53	46.56	74.00	-27.44	peak
4	6679.040	8.38	35.71	41.91	48.29	50.47	74.00	-23.53	peak
5	7314.000	8.84	36.15	41.40	46.99	50.58	74.00	-23.42	peak
6	9752.000	10.76	37.75	37.52	42.42	53.41	74.00	-20.59	peak


Test Mode: 03; Polarity: Horizontal; Modulation: OFDM; Channel: High



Site : chamber
Condition: 3m HORIZONTAL
Job No : 11220CR\11219CR
Mode : 2468.2 TX SE
Note : 3M CA

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1644.019	3.38	26.44	40.03	47.13	36.92	74.00	-37.08	peak
2	4279.589	6.56	33.22	41.67	49.11	47.22	74.00	-26.78	peak
3	4936.000	7.23	34.13	42.25	49.54	48.65	74.00	-25.35	peak
4	6249.464	8.27	35.35	42.22	49.02	50.42	74.00	-23.58	peak
5	7404.000	8.92	36.23	41.32	45.76	49.59	74.00	-24.41	peak
6	9872.000	10.73	37.82	37.31	42.13	53.37	74.00	-20.63	peak


Test Mode: 03; Polarity: Vertical; Modulation: OFDM; Channel: High



Site : chamber
Condition: 3m VERTICAL
Job No : 11220CR\11219CR
Mode : 2468.2 TX SE
Note : 3M CA

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1335.141	3.00	25.17	39.85	50.71	39.03	74.00	-34.97	peak
2	4279.589	6.56	33.22	41.67	49.00	47.11	74.00	-26.89	peak
3	4936.000	7.23	34.13	42.25	47.91	47.02	74.00	-26.98	peak
4	6451.353	8.28	35.55	42.07	48.58	50.34	74.00	-23.66	peak
5	7404.000	8.92	36.23	41.32	46.21	50.04	74.00	-23.96	peak
6	9872.000	10.73	37.82	37.31	42.38	53.62	74.00	-20.38	peak


Test Mode: 04; Polarity: Horizontal; Modulation: OFDM; Channel: Low



Site : chamber
Condition: 3m HORIZONTAL
Job No : 11220CR\11219CR
Mode : 2407.5 TX SE
Note : 10M

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1335.141	3.00	25.17	39.85	49.70	38.02	74.00	-35.98	peak
2	4379.699	6.65	33.39	41.77	49.34	47.61	74.00	-26.39	peak
3	4814.000	7.11	33.98	42.15	53.05	51.99	74.00	-22.01	peak
4	6954.852	8.52	35.87	41.73	48.22	50.88	74.00	-23.12	peak
5	7221.000	8.75	36.08	41.49	46.12	49.46	74.00	-24.54	peak
6	9628.000	10.80	37.68	37.73	42.36	53.11	74.00	-20.89	peak


Test Mode: 04; Polarity: Vertical; Modulation: OFDM; Channel: Low



Site : chamber
Condition: 3m VERTICAL
Job No : 11220CR\11219CR
Mode : 2407.5 TX SE
Note : 10M

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1335.141	3.00	25.17	39.85	48.99	37.31	74.00	-36.69	peak
2	4456.315	6.72	33.53	41.84	48.49	46.90	74.00	-27.10	peak
3	4814.000	7.11	33.98	42.15	48.52	47.46	74.00	-26.54	peak
4	6995.172	8.54	35.90	41.70	47.77	50.51	74.00	-23.49	peak
5	7221.000	8.75	36.08	41.49	46.95	50.29	74.00	-23.71	peak
6	9628.000	10.80	37.68	37.73	42.71	53.46	74.00	-20.54	peak


Test Mode: 04; Polarity: Horizontal; Modulation: OFDM; Channel: middle



Site : chamber
Condition: 3m HORIZONTAL
Job No : 11220CR\11219CR
Mode : 2436.5 TX SE
Note : 10M

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1672.779	3.41	26.56	40.05	47.89	37.81	74.00	-36.19	peak
2	4392.376	6.66	33.42	41.78	48.26	46.56	74.00	-27.44	peak
3	4874.000	7.17	34.05	42.20	54.49	53.51	74.00	-20.49	peak
4	6835.278	8.46	35.80	41.81	47.95	50.40	74.00	-23.60	peak
5	7311.000	8.84	36.15	41.41	47.44	51.02	74.00	-22.98	peak
6	9748.000	10.76	37.75	37.52	42.53	53.52	74.00	-20.48	peak


Test Mode: 04; Polarity: Vertical; Modulation: OFDM; Channel: middle



Site : chamber
Condition: 3m VERTICAL
Job No : 11220CR\11219CR
Mode : 2436.5 TX SE
Note : 10M

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1538.281	3.29	25.98	39.97	48.66	37.96	74.00	-36.04	peak
2	4341.886	6.61	33.33	41.73	48.57	46.78	74.00	-27.22	peak
3	4874.000	7.17	34.05	42.20	52.84	51.86	74.00	-22.14	peak
4	6874.906	8.48	35.83	41.78	47.74	50.27	74.00	-23.73	peak
5	7311.000	8.84	36.15	41.41	47.09	50.67	74.00	-23.33	peak
6	9748.000	10.76	37.75	37.52	42.54	53.53	74.00	-20.47	peak


Test Mode: 04; Polarity: Horizontal; Modulation: OFDM; Channel: High



Site : chamber
Condition: 3m HORIZONTAL
Job No : 11220CR\11219CR
Mode : 2467.5 TX SE
Note : 10M

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1485.841	3.24	25.75	39.94	48.22	37.27	74.00	-36.73	peak
2	4443.453	6.71	33.50	41.82	48.98	47.37	74.00	-26.63	peak
3	4932.000	7.23	34.12	42.24	49.38	48.49	54.00	-5.51	Average
4	4932.000	7.23	34.12	42.24	55.24	54.35	74.00	-19.65	peak
5	6322.136	8.27	35.43	42.16	50.47	52.01	74.00	-21.99	peak
6	7398.000	8.92	36.22	41.33	46.94	50.75	74.00	-23.25	peak
7	9864.000	10.73	37.82	37.33	42.32	53.54	74.00	-20.46	peak


Test Mode: 04; Polarity: Vertical; Modulation: OFDM; Channel: High



Site : chamber
Condition: 3m VERTICAL
Job No : 11220CR\11219CR
Mode : 2467.5 TX SE
Note : 10M

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1335.141	3.00	25.17	39.85	50.21	38.53	74.00	-35.47	peak
2	4193.872	6.47	33.06	41.59	49.18	47.12	74.00	-26.88	peak
3	4932.000	7.23	34.12	42.24	52.88	51.99	74.00	-22.01	peak
4	6874.906	8.48	35.83	41.78	47.87	50.40	74.00	-23.60	peak
5	7398.000	8.92	36.22	41.33	46.49	50.30	74.00	-23.70	peak
6	9864.000	10.73	37.82	37.33	41.92	53.14	74.00	-20.86	peak


Test Mode: 05; Polarity: Horizontal; Modulation: OFDM; Channel: Low



Site : chamber
Condition: 3m HORIZONTAL
Job No : 11220CR\11219CR
Mode : 2412.5 TX SE
Note : 20M

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1538.281	3.29	25.98	39.97	48.24	37.54	74.00	-36.46	peak
2	4367.058	6.64	33.37	41.75	48.91	47.17	74.00	-26.83	peak
3	4824.000	7.12	34.00	42.16	49.34	48.30	74.00	-25.70	peak
4	6974.982	8.53	35.89	41.72	47.85	50.55	74.00	-23.45	peak
5	7236.000	8.77	36.09	41.48	47.37	50.75	74.00	-23.25	peak
6	9648.000	10.79	37.69	37.69	42.97	53.76	74.00	-20.24	peak


Test Mode: 05; Polarity: Vertical; Modulation: OFDM; Channel: Low



Site : chamber
 Condition: 3m VERTICAL
 Job No : 11220CR\11219CR
 Mode : 2412.5 TX SE
 Note : 20M

		Cable	Ant	Preamp	Read		Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1335.141	3.00	25.17	39.85	52.49	40.81	74.00	-33.19	peak
2	4329.354	6.60	33.30	41.72	48.63	46.81	74.00	-27.19	peak
3	4824.000	7.12	34.00	42.16	47.34	46.30	74.00	-27.70	peak
4	6564.209	8.31	35.64	41.99	48.61	50.57	74.00	-23.43	peak
5	7236.000	8.77	36.09	41.48	46.98	50.36	74.00	-23.64	peak
6	9648.000	10.79	37.69	37.69	42.82	53.61	74.00	-20.39	peak


Test Mode: 05; Polarity: Horizontal; Modulation: OFDM; Channel: middle



Site : chamber
Condition: 3m HORIZONTAL
Job No : 11220CR\11219CR
Mode : 2436.5 TX SE
Note : 20M

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1538.281	3.29	25.98	39.97	47.87	37.17	74.00	-36.83	peak
2	4469.214	6.73	33.55	41.85	49.31	47.74	74.00	-26.26	peak
3	4874.000	7.17	34.05	42.20	52.02	51.04	74.00	-22.96	peak
4	6776.265	8.43	35.77	41.85	48.02	50.37	74.00	-23.63	peak
5	7311.000	8.84	36.15	41.41	47.12	50.70	74.00	-23.30	peak
6	9748.000	10.76	37.75	37.52	42.29	53.28	74.00	-20.72	peak


Test Mode: 05; Polarity: Vertical; Modulation: OFDM; Channel: middle



Site : chamber
Condition: 3m VERTICAL
Job No : 11220CR\11219CR
Mode : 2436.5 TX SE
Note : 20M

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1335.141	3.00	25.17	39.85	49.77	38.09	74.00	-35.91	peak
2	4392.376	6.66	33.42	41.78	48.45	46.75	74.00	-27.25	peak
3	4874.000	7.17	34.05	42.20	50.26	49.28	74.00	-24.72	peak
4	6954.852	8.52	35.87	41.73	47.99	50.65	74.00	-23.35	peak
5	7311.000	8.84	36.15	41.41	47.90	51.48	74.00	-22.52	peak
6	9748.000	10.76	37.75	37.52	41.74	52.73	74.00	-21.27	peak


Test Mode: 05; Polarity: Horizontal; Modulation: OFDM; Channel: High



Site : chamber
Condition: 3m HORIZONTAL
Job No : 11220CR\11219CR
Mode : 2462.5 TX SE
Note : 20M

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1677.621	3.41	26.58	40.05	47.17	37.11	74.00	-36.89	peak
2	4379.699	6.65	33.39	41.77	48.97	47.24	74.00	-26.76	peak
3	4924.000	7.22	34.11	42.24	54.76	53.85	74.00	-20.15	peak
4	6894.806	8.49	35.84	41.77	47.57	50.13	74.00	-23.87	peak
5	7386.000	8.91	36.21	41.34	46.06	49.84	74.00	-24.16	peak
6	9848.000	10.73	37.81	37.35	42.31	53.50	74.00	-20.50	peak


Test Mode: 05; Polarity: Vertical; Modulation: OFDM; Channel: High



Site : chamber
Condition: 3m VERTICAL
Job No : 11220CR\11219CR
Mode : 2462.5 TX SE
Note : 20M

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1335.141	3.00	25.17	39.85	51.05	39.37	74.00	-34.63	peak
2	4367.058	6.64	33.37	41.75	48.54	46.80	74.00	-27.20	peak
3	4924.000	7.22	34.11	42.24	48.57	47.66	74.00	-26.34	peak
4	6583.209	8.32	35.65	41.98	48.82	50.81	74.00	-23.19	peak
5	7386.000	8.91	36.21	41.34	45.69	49.47	74.00	-24.53	peak
6	9848.000	10.73	37.81	37.35	42.39	53.58	74.00	-20.42	peak

Test Mode: 06; Polarity: Horizontal; Modulation: OFDM; Channel: Low



Site : chamber
Condition: 3m HORIZONTAL
Job No : 11220CR\11219CR
Mode : 2422.5 TX SE
Note : 40M

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1538.281	3.29	25.98	39.97	48.34	37.64	74.00	-36.36	peak
2	4354.454	6.63	33.35	41.74	49.26	47.50	74.00	-26.50	peak
3	4844.000	7.14	34.02	42.17	47.87	46.86	74.00	-27.14	peak
4	6564.209	8.31	35.64	41.99	48.43	50.39	74.00	-23.61	peak
5	7266.000	8.79	36.12	41.45	47.23	50.69	74.00	-23.31	peak
6	9688.000	10.78	37.71	37.63	42.64	53.50	74.00	-20.50	peak




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing/inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn
中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com


Test Mode: 06; Polarity: Vertical; Modulation: OFDM; Channel: Low



Site : chamber
Condition: 3m VERTICAL
Job No : 11220CR\11219CR
Mode : 2422.5 TX SE
Note : 40M

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1335.141	3.00	25.17	39.85	52.40	40.72	74.00	-33.28	peak
2	4379.699	6.65	33.39	41.77	48.77	47.04	74.00	-26.96	peak
3	4844.000	7.14	34.02	42.17	47.43	46.42	74.00	-27.58	peak
4	6934.778	8.51	35.86	41.74	48.32	50.95	74.00	-23.05	peak
5	7266.000	8.79	36.12	41.45	47.15	50.61	74.00	-23.39	peak
6	9688.000	10.78	37.71	37.63	42.54	53.40	74.00	-20.60	peak

Test Mode: 06; Polarity: Horizontal; Modulation: OFDM; Channel: middle



Site : chamber
Condition: 3m HORIZONTAL
Job No : 11220CR\11219CR
Mode : 2436.5 TX SE
Note : 40M

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1152.148	2.67	24.37	39.72	49.28	36.60	74.00	-37.40	peak
2	4367.058	6.64	33.37	41.75	48.62	46.88	74.00	-27.12	peak
3	4874.000	7.17	34.05	42.20	50.18	49.20	74.00	-24.80	peak
4	5713.856	8.22	34.82	42.37	49.83	50.50	74.00	-23.50	peak
5	7311.000	8.84	36.15	41.41	46.84	50.42	74.00	-23.58	peak
6	9748.000	10.76	37.75	37.52	42.11	53.10	74.00	-20.90	peak




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing/inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn
中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

Test Mode: 06; Polarity: Vertical; Modulation: OFDM; Channel: middle



Site : chamber
Condition: 3m VERTICAL
Job No : 11220CR\11219CR
Mode : 2436.5 TX SE
Note : 40M

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1335.141	3.00	25.17	39.85	49.79	38.11	74.00	-35.89	peak
2	4482.150	6.74	33.57	41.86	48.58	47.03	74.00	-26.97	peak
3	4874.000	7.17	34.05	42.20	49.43	48.45	74.00	-25.55	peak
4	6507.536	8.28	35.60	42.03	48.60	50.45	74.00	-23.55	peak
5	7311.000	8.84	36.15	41.41	46.86	50.44	74.00	-23.56	peak
6	9748.000	10.76	37.75	37.52	42.09	53.08	74.00	-20.92	peak




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing/inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn
中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com


Test Mode: 06; Polarity: Horizontal; Modulation: OFDM; Channel: High



Site : chamber
Condition: 3m HORIZONTAL
Job No : 11220CR\11219CR
Mode : 2452.5 TX SE
Note : 40M

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1516.210	3.27	25.87	39.96	47.39	36.57	74.00	-37.43	peak
2	4482.150	6.74	33.57	41.86	48.75	47.20	74.00	-26.80	peak
3	4904.000	7.20	34.09	42.22	47.69	46.76	74.00	-27.24	peak
4	6659.763	8.37	35.70	41.93	48.54	50.68	74.00	-23.32	peak
5	7356.000	8.88	36.19	41.37	46.87	50.57	74.00	-23.43	peak
6	9808.000	10.75	37.79	37.42	42.13	53.25	74.00	-20.75	peak

Test Mode: 06; Polarity: Vertical; Modulation: OFDM; Channel: High



Site : chamber
Condition: 3m VERTICAL
Job No : 11220CR\11219CR
Mode : 2452.5 TX SE
Note : 40M

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1335.141	3.00	25.17	39.85	50.38	38.70	74.00	-35.30	peak
2	4218.186	6.50	33.11	41.61	50.63	48.63	74.00	-25.37	peak
3	4904.000	7.20	34.09	42.22	49.19	48.26	74.00	-25.74	peak
4	6602.265	8.33	35.66	41.97	48.49	50.51	74.00	-23.49	peak
5	7356.000	8.88	36.19	41.37	47.99	51.69	74.00	-22.31	peak
6	9808.000	10.75	37.79	37.42	42.13	53.25	74.00	-20.75	peak

8 Test Setup Photo

Please refer to setup photos.

9 EUT Constructional Details (EUT Photos)

Please refer to external and internal photos for details.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing/inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn
中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

10 Appendix

Appendix for 15.247



1.4M,1.4M-CA,3M,3M-CA-SISO

1. Duty Cycle

1.1 Test Result

Test Mode	Channel Frequency(MHz)	TX Type	ANT No.	T_on (ms)	Period (ms)	Duty Cycle (%)	Duty Cycle Correction Factor (dB)
1.4M TX	2403.5	SISO	1	100.000	100.000	100.00	0.00
	2437.5	SISO	1	100.000	100.000	100.00	0.00
	2469.5	SISO	1	100.000	100.000	100.00	0.00
1.4M_CA TX	2405.12	SISO	1	100.000	100.000	100.00	0.00
	2437.12	SISO	1	100.000	100.000	100.00	0.00
	2471.12	SISO	1	100.000	100.000	100.00	0.00
3M TX	2408.5	SISO	1	100.000	100.000	100.00	0.00
	2438.5	SISO	1	100.000	100.000	100.00	0.00
	2465.5	SISO	1	100.000	100.000	100.00	0.00
3M_CA TX	2411.2	SISO	1	100.000	100.000	100.00	0.00
	2438.2	SISO	1	100.000	100.000	100.00	0.00
	2468.2	SISO	1	100.000	100.000	100.00	0.00



1.2 Test Graph







Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.



Attention: To check the authenticity of testing inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com



No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com













2. Bandwidth

2.1 Test Result

Test Mode	Frequency (MHz)	TX Type	ANT No.	6dB Bandwidth		Verdict
				Test Result (MHz)	Limits (MHz)	
1.4M TX	2403.5	SISO	1	1.096	≥ 0.5	PASS
	2437.5	SISO	1	1.100	≥ 0.5	PASS
	2469.5	SISO	1	1.101	≥ 0.5	PASS
1.4M_CA TX	2405.12	SISO	1	1.099	≥ 0.5	PASS
	2437.12	SISO	1	1.100	≥ 0.5	PASS
	2471.12	SISO	1	1.094	≥ 0.5	PASS
3M TX	2408.5	SISO	1	2.185	≥ 0.5	PASS
	2438.5	SISO	1	2.185	≥ 0.5	PASS
	2465.5	SISO	1	2.184	≥ 0.5	PASS
3M_CA TX	2411.2	SISO	1	2.184	≥ 0.5	PASS
	2438.2	SISO	1	2.186	≥ 0.5	PASS
	2468.2	SISO	1	2.190	≥ 0.5	PASS





Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.



Attention: To check the authenticity of testing/inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: QM.Docscheck@sgs.com



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch



No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com



2.2 Test Graph - 6dB Bandwidth















3. Maximum Conducted Output Power

3.1 Test Result


Test Mode	Frequency (MHz)	Tx Type	Measured Average Output Power (dBm)				Limits (dBm)	Verdict
			Ant 1	Ant 2	Ant 3	Ant 4		
1.4M TX	2403.5	SISO	16.50	16.53	17.26	16.17	30	PASS
	2437.5	SISO	16.44	17.35	17.49	17.19	30	PASS
	2469.5	SISO	16.26	17.16	17.17	17.89	30	PASS
1.4M_CA TX	2405.12	SISO	16.62	16.16	17.08	17.12	30	PASS
	2437.12	SISO	16.86	17.21	17.51	17.45	30	PASS
	2471.12	SISO	16.08	16.82	16.90	17.53	30	PASS
3M TX	2408.5	SISO	16.44	17.04	17.19	17.52	30	PASS
	2438.5	SISO	16.54	17.32	17.05	17.04	30	PASS
	2465.5	SISO	16.17	16.79	16.85	17.08	30	PASS
3M_CA TX	2411.2	SISO	16.51	16.76	17.60	17.22	30	PASS
	2438.2	SISO	16.94	17.72	17.51	17.41	30	PASS
	2468.2	SISO	15.82	17.31	17.03	17.49	30	PASS



4. Maximum Power Spectral Density (PSD)



4.1 Test Result



Test Mode	Frequency (MHz)	Tx Type	Maximum Power Spectral Density (dBm/3KHz)				Limits (dBm/3KHz)	Verdict
			Ant 1	Ant 2	Ant 3	Ant 4		
1.4M TX	2403.5	SISO	1.61	1.61	2.31	1.26	≤8	PASS
	2437.5	SISO	1.45	2.41	2.50	2.27	≤8	PASS
	2469.5	SISO	1.34	2.21	2.21	2.97	≤8	PASS
1.4M_CA TX	2405.12	SISO	1.61	1.19	2.11	2.16	≤8	PASS
	2437.12	SISO	1.98	2.18	2.53	2.51	≤8	PASS
	2471.12	SISO	0.99	1.84	1.86	2.59	≤8	PASS
3M TX	2408.5	SISO	-3.01	-1.94	-1.97	-1.89	≤8	PASS
	2438.5	SISO	-2.78	-1.96	-1.94	-2.09	≤8	PASS
	2465.5	SISO	-3.03	-2.24	-2.18	-2.03	≤8	PASS
3M_CA TX	2411.2	SISO	-2.69	-2.30	-1.45	-1.89	≤8	PASS
	2438.2	SISO	-2.25	-1.37	-1.98	-1.69	≤8	PASS
	2468.2	SISO	-3.24	-1.81	-1.98	-1.54	≤8	PASS



4.2 Test Graph





























Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing/inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com







Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.



Attention: To check the authenticity of testing/inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch



No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com
















































Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing/inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com



5. Unwanted Emissions in Non-restricted Frequency Bands

5.1 Test Result

Test Mode	Frequency (MHz)	TX Type	ANT No.	Spurious Conducted Emission (dBm)	Limits (dBm)	Verdict
1.4M TX	2403.5	SISO	1	Refer to test graph	-12.90	PASS
			2	Refer to test graph	-12.90	PASS
			3	Refer to test graph	-12.90	PASS
			4	Refer to test graph	-12.90	PASS
	2437.5	SISO	1	Refer to test graph	-12.90	PASS
			2	Refer to test graph	-12.90	PASS
			3	Refer to test graph	-12.90	PASS
			4	Refer to test graph	-12.90	PASS
	2469.5	SISO	1	Refer to test graph	-12.90	PASS
			2	Refer to test graph	-12.90	PASS
			3	Refer to test graph	-12.90	PASS
			4	Refer to test graph	-12.90	PASS
1.4M_CA TX	2405.12	SISO	1	Refer to test graph	-13.22	PASS
			2	Refer to test graph	-13.22	PASS
			3	Refer to test graph	-13.22	PASS
			4	Refer to test graph	-13.22	PASS

	2437.12	SISO	1	Refer to test graph	-13.22	PASS
			2	Refer to test graph	-13.22	PASS
			3	Refer to test graph	-13.22	PASS
			4	Refer to test graph	-13.22	PASS
	2471.12	SISO	1	Refer to test graph	-13.22	PASS
			2	Refer to test graph	-13.22	PASS
			3	Refer to test graph	-13.22	PASS
			4	Refer to test graph	-13.22	PASS
3M TX	2408.5	SISO	1	Refer to test graph	-15.67	PASS
			2	Refer to test graph	-15.67	PASS
			3	Refer to test graph	-15.67	PASS
			4	Refer to test graph	-15.67	PASS
	2438.5	SISO	1	Refer to test graph	-15.67	PASS
			2	Refer to test graph	-15.67	PASS
			3	Refer to test graph	-15.67	PASS
			4	Refer to test graph	-15.67	PASS
	2465.5	SISO	1	Refer to test graph	-15.67	PASS
			2	Refer to test graph	-15.67	PASS
			3	Refer to test graph	-15.67	PASS
			4	Refer to test graph	-15.67	PASS
3M_CA TX	2411.2	SISO	1	Refer to test graph	-15.53	PASS
			2	Refer to test graph	-15.53	PASS
			3	Refer to test graph	-15.53	PASS
			4	Refer to test graph	-15.53	PASS
	2438.2	SISO	1	Refer to test graph	-15.53	PASS
			2	Refer to test graph	-15.53	PASS
			3	Refer to test graph	-15.53	PASS
			4	Refer to test graph	-15.53	PASS
	2468.2	SISO	1	Refer to test graph	-15.53	PASS
			2	Refer to test graph	-15.53	PASS
			3	Refer to test graph	-15.53	PASS
			4	Refer to test graph	-15.53	PASS

5.2 Test Graph

