

Prüfbericht-Nr.: Test report no.:	CN23SNJ4 003	Auftrags-Nr.: Order no.:	168413420	Seite 1 von 24 Page 1 of 24
Kunden-Referenz-Nr.: Client reference no.:	N/A	Auftragsdatum: Order date:	2023-02-07	
Auftraggeber: Client:	SZ DJI TECHNOLOGY CO., LTD. Lobby of T2, DJI Sky City, No. 53 Xianyuan Road, Xili Community, Xili Street, Nanshan District, Shenzhen, China			
Prüfgegenstand: Test item:	Matrice 350 RTK			
Bezeichnung / Typ-Nr.: Identification / Type no.:	M350 RTK (Trademark: DJI)			
Auftrags-Inhalt: Order content:	Test Report			
Prüfgrundlage: Test specification:	RSS-247 Issue 2 February 2017 RSS-Gen Issue 5 March 2019			
Wareneingangsdatum: Date of sample receipt:	2023-02-23	Please refer to photo documents		
Prüfmuster-Nr.: Test sample no.:	A003417729-004 A003419622-002			
Prüfzeitraum: Testing period:	2023-03-09 - 2023-03-30			
Ort der Prüfung: Place of testing:	TÜV Rheinland (Shenzhen) Co., Ltd.			
Prüflaboratorium: Testing laboratory:	TÜV Rheinland (Shenzhen) Co., Ltd.			
Prüfergebnis*: Test result*:	Pass			
geprüft von: tested by:	X <u>Breeze Jiang</u>		genehmigt von: authorized by:	X <u>Lin Lin</u>
Datum: Date: 2023-04-20	Signed by: Breeze Jiang		Ausstellungsdatum: Issue date: 2023-04-20	Signed by: Lin Lin
Stellung / Position:	Sachverständige(r)/Expert		Stellung / Position:	Sachverständige(r)/Expert
Sonstiges / Other:	IC: 11805A-M3502301, HVIN: M350 RTK This report is for 5.8GHz SDR.			
Zustand des Prüfgegenstandes bei Anlieferung: Condition of the test item at delivery:	Prüfmuster vollständig und unbeschädigt Test item complete and undamaged			
* Legende: P(ass) = entspricht o.g. Prüfgrundlage(n) F(ail) = entspricht nicht o.g. Prüfgrundlage(n) N/A = nicht anwendbar N/T = nicht getestet * Legend: P(ass) = passed a.m. test specification(s) F(ail) = failed a.m. test specification(s) N/A = not applicable N/T = not tested				
Dieser Prüfbericht bezieht sich nur auf das o.g. Prüfmuster und darf ohne Genehmigung der Prüfstelle nicht auszugsweise vervielfältigt werden. Dieser Bericht berechtigt nicht zur Verwendung eines Prüfzeichens. <i>This test report only relates to the above mentioned test sample. Without permission of the test center this test report is not permitted to be duplicated in extracts. This test report does not entitle to carry any test mark.</i>				

Prüfbericht - Nr.: CN23SNJ4 003
Test Report No.:

Seite 2 von 24
Page 2 of 24

TEST SUMMARY

5.1.1 ANTENNA REQUIREMENT

RESULT: Pass

5.1.2 MAXIMUM OUTPUT POWER

RESULT: Pass

5.1.3 POWER SPECTRAL DENSITY

RESULT: Pass

5.1.4 FREQUENCY STABILITY

RESULT: Pass

5.1.5 99% BANDWIDTH

RESULT: Pass

5.1.6 6dB BANDWIDTH

RESULT: Pass

5.1.7 RADIATED SPURIOUS EMISSION

RESULT: Pass

TABLE OF CONTENTS

1.	GENERAL REMARKS	4
1.1	COMPLEMENTARY MATERIALS	4
2.	TEST SITES	5
2.1	TEST FACILITIES	5
2.2	LIST OF TEST AND MEASUREMENT INSTRUMENTS.....	5
2.3	TRACEABILITY	6
2.4	CALIBRATION	6
2.5	UNCERTAINTY OF MEASUREMENT.....	6
2.6	LOCATION OF ORIGINAL DATA.....	6
2.7	STATUS OF FACILITY USED FOR TESTING.....	6
3.	GENERAL PRODUCT INFORMATION	7
3.1	PRODUCT FUNCTION AND INTENDED USE.....	7
3.2	RATINGS AND SYSTEM DETAILS	7
3.3	INDEPENDENT OPERATION MODES	13
3.4	NOISE GENERATING AND NOISE SUPPRESSING PARTS	13
3.5	SUBMITTED DOCUMENTS	13
4.	TEST SET-UP AND OPERATION MODES	14
4.1	PRINCIPLE OF CONFIGURATION SELECTION.....	14
4.2	TEST OPERATION	14
4.3	SPECIAL ACCESSORIES AND AUXILIARY EQUIPMENT	14
4.4	COUNTERMEASURES TO ACHIEVE ERM COMPLIANCE	14
4.5	TEST SETUP DIAGRAM	15
5.	TEST RESULTS	16
5.1	RADIO TEST REQUIREMENT & TEST SUITES (5GHz BANDS)	16
5.1.1	Antenna Requirement	16
5.1.2	Maximum output power.....	17
5.1.3	Power Spectral Density.....	19
5.1.4	Frequency Stability.....	20
5.1.5	99% Bandwidth	21
5.1.6	6dB Bandwidth	22
5.1.7	Radiated Spurious Emission.....	23
6.	PHOTOGRAPHS OF THE TEST SET-UP	24
7.	LIST OF TABLES	24

Prüfbericht - Nr.: CN23SNJ4 003
Test Report No.:

Seite 4 von 24
Page 4 of 24

1. General Remarks

1.1 Complementary Materials

All attachments are integral parts of this test report. This applies especially to the following appendix:

Appendix A: Test Results of 5.8G SDR

Appendix B: Photographs of the Test Set-up

2. Test Sites

2.1 Test Facilities

TÜV Rheinland (Shenzhen) Co., Ltd.

No. 362 Huanguan Road Middle, Longhua District, Shenzhen 518110, People's Republic of China

FCC Accreditation Designation No.: CN1260

ISED Wireless Device Testing Laboratory: 25069

A2LA Certificate Number: 5162.01

2.2 List of Test and Measurement Instruments

Table 1: List of Test and Measurement Equipment

Radio Spectrum Testing (SRD-Tonscend)				
Equipment	Manufacturer	Model	Serial No.	Cal. until
EXA Signal Analyzer, Multi-touch	Keysight	N9010B	MY60241175	2023-10-10
MXG X-Series RF Vector Signal Generator	Keysight	N5182B	MY61250137	2023-10-10
EXG X-Series Microwave Analog Signal Generator	Keysight	N5173B	MY61250141	2023-10-10
DC power supply	Keysight	E3642A	MY61276100	2023-10-10
Power Control Unit	Tonscend	JS0806-4ADC	N/A	2023-10-10
Automation Control Unit	Tonscend	JS0806-2	21C8060396	2023-10-10
Test Software	Tonscend	JS1120-3	N/A	N/A
Control PC	Lenovo	TianYi510S-071MB	YLX23JMF	N/A
Shielding Room 8#	Albatross	SR8	APC17151-SR8	2024-06-22
Unwanted Emission Testing (TS9975)				
Equipment	Manufacturer	Model	Serial No.	Cal. until
EMI Test Receiver	R&S	ESR 7	102021	2023-08-02
Signal Analyzer	R&S	FSV 40	101439	2023-08-01
System Controller Interface	R&S	SCI-100	S10010038	N/A
Filterbank	R&S	Wlan	100759	2023-08-01
OSP	R&S	OSP 120	102040	N/A
Pre-amplifier	R&S	SCU08F1	08320031	2023-08-02
Amplifier	R&S	SCU-18F	180070	2023-08-02
Amplifier	R&S	SCU40A	100475	2023-08-02
Trilog Broadband Antenna (30 MHz - 7 GHz)	Schwarzbeck	VULB 9162	193	2024-08-06
Double-Ridged Antenna (1 -18 GHz)	ETS-LINDGREN	3117	00218717	2024-08-06
Wideband Ridged Horn Antenna (18-40 GHz)	Steatite	QMS-00880	19067	2024-08-27
Active Loop Antenna	Schwarzbeck	FMZB 1513	302	2023-08-06
Test software	R&S	EMC32 (V10.60.10)	N/A	N/A
Control PC	Dell	OptiPlex 7050	36NV9P2	N/A
3m Semi-Anechoic Chamber	Albatross	SAC-3m	APC17151-SAC	2024-06-22

2.3 Traceability

All measurement equipment calibrations are traceable to NIM (National Institute of Metrology) or where calibration is performed in other countries, to equivalent nationally recognized standards organizations.

2.4 Calibration

Equipment requiring calibration is calibrated periodically by the manufacturer or according to manufacturer's specifications. Additionally all equipment is verified for proper performance on a regular basis using in house standards or comparisons.

2.5 Uncertainty of Measurement

The value of the measurement uncertainty of each parameter is listed as below:

Table 2: Measurement Uncertainty

Parameter	Uncertainty
RF output power, conducted	± 0.99 dB
Occupied Channel Bandwidth	± 2.08 %
RF power density, conducted	± 0.99 dB
Unwanted Emissions, conducted	± 0.89 dB
Radiated Emission of Transmitter, valid up to 26.5 GHz	± 4.17 dB
Radiated Emission of Receiver, valid up to 26.5 GHz	± 4.17 dB

2.6 Location of Original Data

The original copies of all test data taken during actual testing were attached at Appendix A & B of this report and delivered to the applicant. A copy has been retained in the TÜV Rheinland (Shenzhen) Co., Ltd. file for certification follow-up purposes.

2.7 Status of Facility Used for Testing

The TÜV Rheinland (Shenzhen) Co., Ltd. Test facility located at No. 362 Huanguan Road Middle, Longhua District, Shenzhen 518110, People's Republic of China is listed on the US Federal Communications Commission list of facilities approved to perform measurements.

3. General Product Information

3.1 Product Function and Intended Use

The EUT (Equipment Under Test) is an Aircraft. It supports 2.4GHz SDR, 5.8GHz SDR, GNSS and ADS-B functions.

*remark: SDR means specific defined radio, and cannot changes radio specification via software/firmware by end-users.

For details refer to the User Manual, Technical Description and Circuit Diagram.

3.2 Ratings and System Details

Table 3: Technical Specification

General Information of EUT	Value
Kind of Equipment	Matrice 350 RTK
Type Designation	M350 RTK
Trademark	DJI
Operating Temperature Range	-20 °C ~ +50 °C
Operating Voltage	Battery operated (DC 44.76V@5880mAh, Li-ion battery)
Testing Voltage	Fully charged battery
Radiofrequency operating mode	1) 2.4GHz SDR: operating within 2400-2483.5MHz, supports 1.4MHz/3MHz/10MHz/20MHz/40MHz Bandwidth 2) 5.8GHz SDR: operating within 5725-5850MHz, supports 1.4MHz/3MHz/10MHz/20MHz/40MHz Bandwidth 3) GPS & BDS & Galileo & Glonass (receiver): operating within 1559-1610MHz 4) ADS-B (receiver): operating at 978MHz (1MHz Bandwidth) and 1090MHz (2MHz Bandwidth)
Technical Specification of 5.8GHz SDR	
Operating Frequency	5728.5-5846.5MHz for 1.4MHz Bandwidth 5730.12-5848.12MHz for 1.4MHz Bandwidth (CA mode) 5727.5-5844.5MHz for 3MHz Bandwidth 5730.2-5847.2MHz for 3MHz Bandwidth (CA mode) 5730.5-5844.5MHz for 10MHz Bandwidth 5735.5-5839.5MHz for 20MHz Bandwidth 5745.5-5829.5MHz for 40MHz Bandwidth
Type of Modulation	OFDM (QPSK, 16QAM, 64QAM)
Channel Number	60 channels for 1.4MHz Bandwidth 60 channels for 1.4MHz Bandwidth (CA mode) 40 channels for 3MHz Bandwidth 40 channels for 3MHz Bandwidth (CA mode) 115 channels for 10MHz Bandwidth 105 channels for 20MHz Bandwidth 85 channels for 40MHz Bandwidth
Channel Separation	2MHz for 1.4MHz Bandwidth 2MHz for 1.4MHz Bandwidth (CA mode)

Prüfbericht - Nr.: CN23SNJ4 003
Test Report No.:
Seite 8 von 24
Page 8 of 24

	3MHz for 3MHz Bandwidth 3MHz for 3MHz Bandwidth (CA mode) 1MHz for 10MHz Bandwidth 1MHz for 20MHz Bandwidth 1MHz for 40MHz Bandwidth
Antenna Type	Integral Antenna
Antenna Number	1Tx4Rx for SISO mode (ANT0 or ANT1 or ANT2 or ANT3) 2Tx4Rx for MIMO mode (ANT0+ANT1 or ANT0+ANT3 or ANT2+ANT1 or ANT2+ANT3), Un-correlated signals.
Antenna Gain	4.5dBi for ANT0 4.5dBi for ANT1 4.4dBi for ANT2 4.4dBi for ANT3
The type of wideband data transmission equipment	Non-FHSS

Table 4: RF Channel and Frequency of 5.8GHz SDR

5.8GHz 1.4MHzBandwidth (5728.5MHz-5846.5MHz)					
RF Channel	Frequency (MHz)	RF Channel	Frequency (MHz)	RF Channel	Frequency (MHz)
1	5728.5	21	5768.5	41	5808.5
2	5730.5	22	5770.5	42	5810.5
3	5732.5	23	5772.5	43	5812.5
4	5734.5	24	5774.5	44	5814.5
5	5736.5	25	5776.5	45	5816.5
6	5738.5	26	5778.5	46	5818.5
7	5740.5	27	5780.5	47	5820.5
8	5742.5	28	5782.5	48	5822.5
9	5744.5	29	5784.5	49	5824.5
10	5746.5	30	5786.5	50	5826.5
11	5748.5	31	5788.5	51	5828.5
12	5750.5	32	5790.5	52	5830.5
13	5752.5	33	5792.5	53	5832.5
14	5754.5	34	5794.5	54	5834.5
15	5756.5	35	5796.5	55	5836.5
16	5758.5	36	5798.5	56	5838.5
17	5760.5	37	5800.5	57	5840.5
18	5762.5	38	5802.5	58	5842.5
19	5764.5	39	5804.5	59	5844.5
20	5766.5	40	5806.5	60	5846.5

5.8GHz 1.4MHz Bandwidth (CA Mode) (5730.12MHz-5848.12MHz)					
RF Channel	Frequency (MHz)	RF Channel	Frequency (MHz)	RF Channel	Frequency (MHz)
1	5730.12	21	5770.12	41	5810.12
2	5732.12	22	5772.12	42	5812.12
3	5734.12	23	5774.12	43	5814.12
4	5736.12	24	5776.12	44	5816.12
5	5738.12	25	5778.12	45	5818.12
6	5740.12	26	5780.12	46	5820.12
7	5742.12	27	5782.12	47	5822.12
8	5744.12	28	5784.12	48	5824.12
9	5746.12	29	5786.12	49	5826.12
10	5748.12	30	5788.12	50	5828.12
11	5750.12	31	5790.12	51	5830.12
12	5752.12	32	5792.12	52	5832.12
13	5754.12	33	5794.12	53	5834.12
14	5756.12	34	5796.12	54	5836.12
15	5758.12	35	5798.12	55	5838.12
16	5760.12	36	5800.12	56	5840.12
17	5762.12	37	5802.12	57	5842.12
18	5764.12	38	5804.12	58	5844.12
19	5766.12	39	5806.12	59	5846.12
20	5768.12	40	5808.12	60	5848.12

5.8GHz 3MHz Bandwidth (5727.5MHz-5844.5MHz)					
RF Channel	Frequency (MHz)	RF Channel	Frequency (MHz)	RF Channel	Frequency (MHz)
1	5727.5	15	5769.5	29	5811.5
2	5730.5	16	5772.5	30	5814.5
3	5733.5	17	5775.5	31	5817.5
4	5736.5	18	5778.5	32	5820.5
5	5739.5	19	5781.5	33	5823.5
6	5742.5	20	5784.5	34	5826.5
7	5745.5	21	5787.5	35	5829.5
8	5748.5	22	5790.5	36	5832.5
9	5751.5	23	5793.5	37	5835.5
10	5754.5	24	5796.5	38	5838.5
11	5757.5	25	5799.5	39	5841.5
12	5760.5	26	5802.5	40	5844.5
13	5763.5	27	5805.5		
14	5766.5	28	5808.5		

5.8GHz 3MHz Bandwidth (CA Mode) (5730.2MHz-5847.2MHz)					
RF Channel	Frequency (MHz)	RF Channel	Frequency (MHz)	RF Channel	Frequency (MHz)
1	5730.2	15	5772.2	29	5814.2
2	5733.2	16	5775.2	30	5817.2
3	5736.2	17	5778.2	31	5820.2
4	5739.2	18	5781.2	32	5823.2
5	5742.2	19	5784.2	33	5826.2
6	5745.2	20	5787.2	34	5829.2
7	5748.2	21	5790.2	35	5832.2
8	5751.2	22	5793.2	36	5835.2
9	5754.2	23	5796.2	37	5838.2
10	5757.2	24	5799.2	38	5841.2
11	5760.2	25	5802.2	39	5844.2
12	5763.2	26	5805.2	40	5847.2
13	5766.2	27	5808.2		
14	5769.2	28	5811.2		

5.8GHz 10MHzBandwidth (5730.5MHz-5844.5MHz)					
RF Channel	Frequency (MHz)	RF Channel	Frequency (MHz)	RF Channel	Frequency (MHz)
1	5730.5	40	5769.5	79	5808.5
2	5731.5	41	5770.5	80	5809.5
3	5732.5	42	5771.5	81	5810.5
4	5733.5	43	5772.5	82	5811.5
5	5734.5	44	5773.5	83	5812.5
6	5735.5	45	5774.5	84	5813.5
7	5736.5	46	5775.5	85	5814.5
8	5737.5	47	5776.5	86	5815.5
9	5738.5	48	5777.5	87	5816.5
10	5739.5	49	5778.5	88	5817.5
11	5740.5	50	5779.5	89	5818.5
12	5741.5	51	5780.5	90	5819.5
13	5742.5	52	5781.5	91	5820.5
14	5743.5	53	5782.5	92	5821.5
15	5744.5	54	5783.5	93	5822.5
16	5745.5	55	5784.5	94	5823.5
17	5746.5	56	5785.5	95	5824.5
18	5747.5	57	5786.5	96	5825.5
19	5748.5	58	5787.5	97	5826.5
20	5749.5	59	5788.5	98	5827.5
21	5750.5	60	5789.5	99	5828.5
22	5751.5	61	5790.5	100	5829.5

Prüfbericht - Nr.: CN23SNJ4 003
Test Report No.:
Seite 11 von 24
Page 11 of 24

23	5752.5	62	5791.5	101	5830.5
24	5753.5	63	5792.5	102	5831.5
25	5754.5	64	5793.5	103	5832.5
26	5755.5	65	5794.5	104	5833.5
27	5756.5	66	5795.5	105	5834.5
28	5757.5	67	5796.5	106	5835.5
29	5758.5	68	5797.5	107	5836.5
30	5759.5	69	5798.5	108	5837.5
31	5760.5	70	5799.5	109	5838.5
32	5761.5	71	5800.5	110	5839.5
33	5762.5	72	5801.5	111	5840.5
34	5763.5	73	5802.5	112	5841.5
35	5764.5	74	5803.5	113	5842.5
36	5765.5	75	5804.5	114	5843.5
37	5766.5	76	5805.5	115	5844.5
38	5767.5	77	5806.5		
39	5768.5	78	5807.5		

**5.8GHz 20MHz Bandwidth
(5735.5MHz-5839.5MHz)**

RF Channel	Frequency (MHz)	RF Channel	Frequency (MHz)	RF Channel	Frequency (MHz)
1	5735.5	36	5770.5	71	5805.5
2	5736.5	37	5771.5	72	5806.5
3	5737.5	38	5772.5	73	5807.5
4	5738.5	39	5773.5	74	5808.5
5	5739.5	40	5774.5	75	5809.5
6	5740.5	41	5775.5	76	5810.5
7	5741.5	42	5776.5	77	5811.5
8	5742.5	43	5777.5	78	5812.5
9	5743.5	44	5778.5	79	5813.5
10	5744.5	45	5779.5	80	5814.5
11	5745.5	46	5780.5	81	5815.5
12	5746.5	47	5781.5	82	5816.5
13	5747.5	48	5782.5	83	5817.5
14	5748.5	49	5783.5	84	5818.5
15	5749.5	50	5784.5	85	5819.5
16	5750.5	51	5785.5	86	5820.5
17	5751.5	52	5786.5	87	5821.5
18	5752.5	53	5787.5	88	5822.5
19	5753.5	54	5788.5	89	5823.5
20	5754.5	55	5789.5	90	5824.5
21	5755.5	56	5790.5	91	5825.5
22	5756.5	57	5791.5	92	5826.5
23	5757.5	58	5792.5	93	5827.5

Prüfbericht - Nr.: CN23SNJ4 003
Test Report No.:
Seite 12 von 24
Page 12 of 24

24	5758.5	59	5793.5	94	5828.5
25	5759.5	60	5794.5	95	5829.5
26	5760.5	61	5795.5	96	5830.5
27	5761.5	62	5796.5	97	5831.5
28	5762.5	63	5797.5	98	5832.5
29	5763.5	64	5798.5	99	5833.5
30	5764.5	65	5799.5	100	5834.5
31	5765.5	66	5800.5	101	5835.5
32	5766.5	67	5801.5	102	5836.5
33	5767.5	68	5802.5	103	5837.5
34	5768.5	69	5803.5	104	5838.5
35	5769.5	70	5804.5	105	5839.5

5.8GHz 40MHz Bandwidth (5745.5MHz-5829.5MHz)					
RF Channel	Frequency (MHz)	RF Channel	Frequency (MHz)	RF Channel	Frequency (MHz)
1	5745.5	30	5774.5	59	5803.5
2	5746.5	31	5775.5	60	5804.5
3	5747.5	32	5776.5	61	5805.5
4	5748.5	33	5777.5	62	5806.5
5	5749.5	34	5778.5	63	5807.5
6	5750.5	35	5779.5	64	5808.5
7	5751.5	36	5780.5	65	5809.5
8	5752.5	37	5781.5	66	5810.5
9	5753.5	38	5782.5	67	5811.5
10	5754.5	39	5783.5	68	5812.5
11	5755.5	40	5784.5	69	5813.5
12	5756.5	41	5785.5	70	5814.5
13	5757.5	42	5786.5	71	5815.5
14	5758.5	43	5787.5	72	5816.5
15	5759.5	44	5788.5	73	5817.5
16	5760.5	45	5789.5	74	5818.5
17	5761.5	46	5790.5	75	5819.5
18	5762.5	47	5791.5	76	5820.5
19	5763.5	48	5792.5	77	5821.5
20	5764.5	49	5793.5	78	5822.5
21	5765.5	50	5794.5	79	5823.5
22	5766.5	51	5795.5	80	5824.5
23	5767.5	52	5796.5	81	5825.5
24	5768.5	53	5797.5	82	5826.5
25	5769.5	54	5798.5	83	5827.5
26	5770.5	55	5799.5	84	5828.5
27	5771.5	56	5800.5	85	5829.5
28	5772.5	57	5801.5		

29	5773.5	58	5802.5	
----	--------	----	--------	--

3.3 Independent Operation Modes

The basic operation modes are:

- A. On, 5.8GHz SDR wireless transmitting mode
 - 1) Low Channel
 - 2) Middle Channel
 - 3) High Channel
- B. On, Normal Operation
- C. Off

3.4 Noise Generating and Noise Suppressing Parts

Refer to the Circuit Diagram.

3.5 Submitted Documents

- Circuit Diagram
- Instruction Manual
- Bill of Material
- Rating Label

4. Test Set-up and Operation Modes

4.1 Principle of Configuration Selection

Radio Spectrum: The equipment under test (EUT) was configured at its highest power output in order to measure its highest possible radiation and conducted level. The test modes were adapted accordingly in reference to the instructions for use.

Emission: The equipment under test (EUT) was configured to measure its highest possible radiation level. The test modes were adapted accordingly in reference to the instructions for use.

4.2 Test Operation

Test operation refers to test setup in chapter 5. All tests were performed according to the procedures in ANSI C63.10: 2013 and ANSI C63.4: 2014.

According to clause 3.1, all tests were performed on model M350 RTK in this report.

Note: All testing were carried out on SISO mode and MIMO mode, but only the worst case(Ant0+3) was presented in this report.

4.3 Special Accessories and Auxiliary Equipment

Table 5: List of Accessories and Auxiliary Equipment

Description	Manufacturer	Model	S/N
Laptop	Lenovo	T480	PF-16A6N8

4.4 Countermeasures to Achieve ERM Compliance

The test sample which has been tested contained the noise suppression parts as described in the Technical Construction File (TCF). No additional measures were employed to achieve compliance.

4.5 Test Setup Diagram

Diagram of Measurement Configuration for Radiation Test (Below 1GHz)




Diagram of Measurement Configuration for Radiation Test (Above 1GHz)





Diagram of Measurement Configuration for Conducted Transmitter Measurement



Prüfbericht - Nr.: CN23SNJ4 003
Test Report No.:**Seite 16 von 24**
Page 16 of 24

5. Test Results

5.1 Radio Test Requirement & Test Suites (5GHz Bands)

5.1.1 Antenna Requirement

RESULT:**Pass****Test Specification**

Test standard : RSS-Gen Section 6.8

According to the manufacturer declared, the EUT has Integral antennas, the maximum antenna gain of SISO is 4.5dBi for 5.8GHz SDR, the maximum uncorrelated antenna gain of MIMO is 4.45dBi for 5.8GHz SDR, and the antenna connector is designed unique, prefer to EUT photos for details.

Therefore the EUT is considered sufficient to comply with the provision.

Refer to EUT Photo for further details.

5.1.2 Maximum output power

RESULT:

Pass

Test Specification

Test standard : RSS-247 clause 6.2
Basic standard : ANSI C63.10:2013
Limits : <1W (30dBm) (5725-5850MHz)
Kind of test site : Shielded Room

Test Setup

Date of testing : 2023-03-09 to 2023-03-14
Input voltage : Fully charged battery
Operation mode : A
Test channel : Low / Middle / High
Ambient temperature : 25 °C
Relative humidity : 45 %
Atmospheric pressure : 101 kPa

For details refer to following test result.

Table 6: Test Result of Maximum Conducted Output Power

Worst case for SISO mode Ant 0

Test Mode	Test Channel (MHz)	Measured Power		Limit (W)
		(dBm)	(W)	
1.4MHz BW	5728.5	17.04	0.0506	< 1.0
	5786.5	16.41	0.0438	
	5846.5	16.99	0.0500	
1.4MHz BW CA	5730.12	17.14	0.0518	
	5788.12	16.48	0.0445	
	5848.12	17.09	0.0512	
3MHz BW	5727.5	17.08	0.0511	
	5784.5	16.84	0.0483	
	5844.5	16.93	0.0493	
3MHz BW CA	5730.2	17.04	0.0506	
	5787.2	16.8	0.0479	
	5847.2	16.91	0.0491	
10MHz BW	5730.5	27.13	0.5164	
	5787.5	26.95	0.4955	
	5844.5	26.66	0.4634	
20MHz BW	5735.5	27.07	0.5093	
	5787.5	27.00	0.5012	
	5839.5	26.78	0.4764	
40MHz BW	5745.5	23.51	0.2244	
	5755.5	24.75	0.2985	
	5760.5	25.43	0.3491	
	5787.5	26.46	0.4426	
	5800.5	25.35	0.3428	
	5820.5	24.72	0.2965	
	5829.5	24.23	0.26489	

Max. e.i.r.p.=27.13dBm+4.5dBi=31.63dBm, which is less than 36dBm=4W.

Worst case for MIMO mode (Ant 0+3)

Test Mode	Test Channel (MHz)	Measured Average Power		Limit (W)
		(dBm)	(W)	
1.4MHz BW	5728.5	17.51	0.0564	< 1.0
	5786.5	17.12	0.0515	
	5846.5	17.25	0.0531	
1.4MHz BW CA	5730.12	17.60	0.0575	
	5788.12	17.13	0.0516	
	5848.12	17.26	0.0532	
3MHz BW	5727.5	17.26	0.0532	
	5784.5	16.97	0.0498	
	5844.5	16.92	0.0492	
3MHz BW CA	5730.2	17.50	0.0562	
	5787.2	16.95	0.0495	
	5847.2	16.74	0.0472	
10MHz BW	5730.5	27.22	0.5272	
	5787.5	27.09	0.5117	
	5844.5	26.60	0.4571	
20MHz BW	5735.5	26.86	0.4853	
	5787.5	27.14	0.5176	
	5839.5	26.46	0.4426	
40MHz BW	5745.5	23.27	0.2123	
	5755.5	24.66	0.2924	
	5760.5	25.61	0.3639	
	5787.5	26.89	0.4887	
	5800.5	26.06	0.4036	
	5820.5	24.79	0.3013	
	5829.5	23.30	0.2138	
Max. e.i.r.p.=27.22dBm+4.45dBi=31.67dBm, which is less than 36dBm=4W.				

Note:

- 1) The cable loss is taken into account in results.
- 2) Antenna gain(G) of 5.8GHz SDR: 4.5dBi (Ant 0)
4.45dBi (uncorrelated antenna gain MIMO)

Prüfbericht - Nr.: CN23SNJ4 003
Test Report No.:

Seite 19 von 24
Page 19 of 24

5.1.3 Power Spectral Density

RESULT:

Pass

Test Specification

Test standard	: RSS-247 clause 6.2
Basic standard	: ANSI C63.10:2013
Limits	: <30dBm/500KHz (5725-5850MHz)
Kind of test site	: Shielded Room

Test Setup

Date of testing	: 2023-03-09 to 2023-03-14
Input voltage	: Fully charged battery
Operation mode	: A
Test channel	: Low / Middle / High
Ambient temperature	: 25°C
Relative humidity	: 45%
Atmospheric pressure	: 101 kPa

Refer to attached Appendix A for details of test data.

Prüfbericht - Nr.: CN23SNJ4 003
Test Report No.:

Seite 20 von 24
Page 20 of 24

5.1.4 Frequency Stability

RESULT:

Pass

Test Specification

Test standard	: RSS-Gen Clause 6.11
Basic standard	: ANSI C63.10:2013
Limits	: Within assigned bands
Kind of test site	: Shielded Room

Test Setup

Date of testing	: 2023-03-09 to 2023-03-14
Input voltage	: Fully charged battery
Operation mode	: A
Test channel	: Low / Middle / High
Ambient temperature	: 25°C
Relative humidity	: 45%
Atmospheric pressure	: 101 kPa

Refer to attached Appendix A for details of test data.

Prüfbericht - Nr.: CN23SNJ4 003
Test Report No.:

Seite 21 von 24
Page 21 of 24

5.1.5 99% Bandwidth

RESULT:

Pass

Test Specification

Test standard	: RSS-Gen Clause 6.6
Basic standard	: ANSI C63.10:2013
Limits	: N/A
Kind of test site	: Shielded Room

Test Setup

Date of testing	: 2023-03-09 to 2023-03-14
Input voltage	: Fully charged battery
Operation mode	: A
Test channel	: Low / Middle / High
Ambient temperature	: 25°C
Relative humidity	: 45%
Atmospheric pressure	: 101 kPa

Refer to attached Appendix A for details of test data.

Prüfbericht - Nr.: CN23SNJ4 003
Test Report No.:

Seite 22 von 24
Page 22 of 24

5.1.6 6dB Bandwidth

RESULT:

Pass

Test Specification

Test standard	: RSS-247 clause 6.2.4.1
Basic standard	: ANSI C63.10:2013
Limits	: At least 500KHz (5725-5850MHz)
Kind of test site	: Shielded Room

Test Setup

Date of testing	: 2023-03-09 to 2023-03-14
Input voltage	: Fully charged battery
Operation mode	: A
Test channel	: Low / Middle / High
Ambient temperature	: 25°C
Relative humidity	: 45%
Atmospheric pressure	: 101 kPa

Refer to attached Appendix A for details of test data.

5.1.7 Radiated Spurious Emission**RESULT:****Pass****Test Specification**

Test standard	:	RSS-247 clause 6.2 & RSS-GEN clause 8.9 and 8.10
Basic standard	:	ANSI C63.10:2013
Limits	:	• For transmitters operating in the 5.725-5.85 GHz band: All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge. • Restricted Bands meet the requirement of 15.209 limit • Restricted Bands meet the requirement of RSS-GEN
Kind of test site	:	3m Semi-Anechoic Chamber

Test Setup

Date of testing	:	2023-03-23 to 2023-03-28
Input voltage	:	Fully charged battery
Operation mode	:	A
Test channel	:	Low / Middle / High
Ambient temperature	:	Refer to test result
Relative humidity	:	Refer to test result
Atmospheric pressure	:	101 kPa

Refer to attached Appendix A for details of test data.

6. Photographs of the Test Set-Up

For photographs of the test set-up, refer to the appendix B.

7. List of Tables

Table 1: List of Test and Measurement Equipment.....	5
Table 2: Measurement Uncertainty	6
Table 3: Technical Specification	7
Table 4: RF Channel and Frequency of 5.8GHz SDR.....	8
Table 5: List of Accessories and Auxiliary Equipment	14
Table 6: Test Result of Maximum Conducted Output Power	17