

TEST REPORT

Application No.: SZEM2004003232CR
Applicant: SZ DJI TECHNOLOGY CO., LTD.
Address of Applicant: 14th floor, West Wing, Skyworth Semiconductor Design Building NO.18
Gaoxin South 4th Ave, Nanshan, Shenzhen, Guangdong, China
Manufacturer: SZ DJI TECHNOLOGY CO., LTD.
Address of Manufacturer: 14th floor, West Wing, Skyworth Semiconductor Design Building NO.18
Gaoxin South 4th Ave, Nanshan, Shenzhen, Guangdong, China
Factory: SZ DJI TECHNOLOGY CO., LTD.
Address of Factory: 14th floor, West Wing, Skyworth Semiconductor Design Building NO.18
Gaoxin South 4th Ave, Nanshan, Shenzhen, Guangdong, China
Equipment Under Test (EUT):
EUT Name: RoboMaster EP Core
Model No.: RMEPCORE
FCC ID: SS3-RMEPCORE
Standard(s) : 47 CFR Part 15, Subpart C 15.247
Date of Receipt: 2020-04-29
Date of Test: 2020-05-08 to 2020-05-19
Date of Issue: 2020-05-21

Test Result:	Pass*
---------------------	--------------

* In the configuration tested, the EUT complied with the standards specified above.

Keny Xu

Keny Xu
EMC Laboratory Manager



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.
Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

Revision Record				
Version	Chapter	Date	Modifier	Remark
01		2020-05-21		Original

Authorized for issue by:			
			
		Calvin Weng /Project Engineer	
			
		Eric Fu /Reviewer	



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

2 Test Summary

Radio Spectrum Technical Requirement				
Item	Standard	Method	Requirement	Result
Antenna Requirement	47 CFR Part 15, Subpart C 15.247	N/A	47 CFR Part 15, Subpart C 15.203 & 15.247(b)(4)	Pass

Radio Spectrum Matter Part				
Item	Standard	Method	Requirement	Result
Minimum 6dB Bandwidth	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 11.8.1	47 CFR Part 15, Subpart C 15.247a(2)	Pass
Conducted Average Output Power	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 11.9.1	47 CFR Part 15, Subpart C 15.247(b)(3)	Pass
Power Spectrum Density	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 11.10.2	47 CFR Part 15, Subpart C 15.247(e)	Pass
Conducted Band Edges Measurement	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 11.13.3.2	47 CFR Part 15, Subpart C 15.247(d)	Pass
Conducted Spurious Emissions	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 11.11	47 CFR Part 15, Subpart C 15.247(d)	Pass
Radiated Emissions which fall in the restricted bands	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 6.10.5	47 CFR Part 15, Subpart C 15.209 & 15.247(d)	Pass
Radiated Spurious Emissions	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 6.4,6.5,6.6	47 CFR Part 15, Subpart C 15.209 & 15.247(d)	Pass

Remark:1. the two antennas can transmit at the same time.

2. all the radiated test are performed with two antennas transmit simultaneously.

3. in this report, directional gain= $4.5+10*\log(2)=7.51\text{dBi}$.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.
 Attention: To check the authenticity of testing /inspection report and certificate, please contact us at telephone: (86-755) 83071443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
 Shenzhen Branch, Inspection & Testing Services Laboratory

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn
 中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

3 Contents

	Page
1 COVER PAGE	1
2 TEST SUMMARY	3
3 CONTENTS	4
4 GENERAL INFORMATION	6
4.1 DETAILS OF E.U.T.	6
4.2 DESCRIPTION OF SUPPORT UNITS	6
4.3 MEASUREMENT UNCERTAINTY	7
4.4 TEST LOCATION	8
4.5 TEST FACILITY	8
4.6 DEVIATION FROM STANDARDS	8
4.7 ABNORMALITIES FROM STANDARD CONDITIONS	8
5 EQUIPMENT LIST	9
6 RADIO SPECTRUM TECHNICAL REQUIREMENT	13
6.1 ANTENNA REQUIREMENT	13
6.1.1 Test Requirement:	13
6.1.2 Conclusion	13
7 RADIO SPECTRUM MATTER TEST RESULTS	14
7.1 MINIMUM 6DB BANDWIDTH	14
7.1.1 E.U.T. Operation	14
7.1.2 Test Setup Diagram	14
7.1.3 Measurement Procedure and Data	14
7.2 CONDUCTED AVERAGE OUTPUT POWER	15
7.2.1 E.U.T. Operation	16
7.2.2 Test Setup Diagram	16
7.2.3 Measurement Procedure and Data	16
7.3 POWER SPECTRUM DENSITY	17
7.3.1 E.U.T. Operation	17
7.3.2 Test Setup Diagram	17
7.3.3 Measurement Procedure and Data	17
7.4 CONDUCTED BAND EDGES MEASUREMENT	18
7.4.1 E.U.T. Operation	19
7.4.2 Test Setup Diagram	19
7.4.3 Measurement Procedure and Data	19
7.5 CONDUCTED SPURIOUS EMISSIONS	20
7.5.1 E.U.T. Operation	21
7.5.2 Test Setup Diagram	21
7.5.3 Measurement Procedure and Data	21
7.6 RADIATED EMISSIONS WHICH FALL IN THE RESTRICTED BANDS	22
7.6.1 E.U.T. Operation	22
7.6.2 Test Setup Diagram	22



7.6.3	Measurement Procedure and Data.....	23
7.7	RADIATED SPURIOUS EMISSIONS	88
7.7.1	E.U.T. Operation.....	89
7.7.2	Test Setup Diagram.....	89
7.7.3	Measurement Procedure and Data.....	90
8	PHOTOGRAPHS	117
8.1	TEST SETUP	117
8.2	EUT CONSTRUCTIONAL DETAILS (EUT PHOTOS)	117
9	APPENDIX.....	118
9.1	APPENDIX 15.247	118-193



4 General Information

4.1 Details of E.U.T.

Power Supply:	DC10.8V by Lithium-ion battery(2400mAh) Recharge input: DC12.6V 2.2A by power adapter adapter input: AC100-240V, 1A, 50/60Hz adapter M/N: E1C28
Cable:	AC power cable: 1m unshielded cable without ferrite core Micro USB cable: 0.6m unshielded cable
Operation Frequency:	802.11b/g/n(HT20): 2412MHz to 2462MHz 802.11n(HT40): 2422MHz to 2452MHz
Modulation Type:	802.11b: DSSS (CCK, DQPSK, DBPSK) 802.11g/n: OFDM (64QAM, 16QAM, QPSK, BPSK)
Number of Channels:	802.11b/g/n(HT20):11 802.11n(HT40):7
Channel Spacing:	5MHz
Antenna Type:	Integral antenna
Antenna Gain:	4.5dBi

4.2 Description of Support Units

The EUT has been tested as an independent unit.

4.3 Measurement Uncertainty

No.	Item	Measurement Uncertainty
1	Radio Frequency	$\pm 7.25 \times 10^{-8}$
2	Duty cycle	$\pm 0.37\%$
3	Occupied Bandwidth	$\pm 3\%$
4	RF conducted power	$\pm 0.75\text{dB}$
5	RF power density	$\pm 2.84\text{dB}$
6	Conducted Spurious emissions	$\pm 0.75\text{dB}$
7	Radiated Spurious emission test	$\pm 4.5\text{dB}$ (Below 1GHz)
		$\pm 4.8\text{dB}$ (Above 1GHz)
8	Temperature test	$\pm 1^\circ\text{C}$
9	Humidity test	$\pm 3\%$
10	Supply voltages	$\pm 1.5\%$
11	Time	$\pm 3\%$



4.4 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen Branch

No. 1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, Guangdong, China. 518057.

Tel: +86 755 2601 2053 Fax: +86 755 2671 0594

No tests were sub-contracted.

4.5 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **A2LA (Certificate No. 3816.01)**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 3816.01.

- **VCCI**

The 3m Fully-anechoic chamber for above 1GHz, 10m Semi-anechoic chamber for below 1GHz, Shielded Room for Mains Port Conducted Interference Measurement and Telecommunication Port Conducted Interference Measurement of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-20026, R-14188, C-12383 and T-11153 respectively.

- **FCC –Designation Number: CN1178**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized as an accredited testing laboratory.

Designation Number: CN1178. Test Firm Registration Number: 406779.

- **Innovation, Science and Economic Development Canada**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized by ISED as an accredited testing laboratory.

CAB identifier: CN0006.

IC#: 4620C.

4.6 Deviation from Standards

None

4.7 Abnormalities from Standard Conditions

None



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.
Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch EMC Laboratory

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn
中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

5 Equipment List

Minimum 6dB Bandwidth					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
Shielding Room	SAEMC	MSR733	SEM001-09	2019-06-13	2022-06-12
DC Power Supply	Rohde & Schwarz	NGSM 32/10	SEM011-04	2020-03-24	2021-03-23
Spectrum Analyzer	Rohde & Schwarz	FSP	SEM004-06	2019-09-24	2020-09-23
Measurement Software	JS Tonscend	JS1120-2 BT/WIFI V2.	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM031-02	2019-07-11	2020-07-10
Attenuator	Weinschel Associates	WA41	SEM021-09	N/A	N/A
Signal Generator	KEYSIGHT	N5173B	SEM006-05	2019-09-24	2020-09-23
Power Meter	Rohde & Schwarz	NRVS	SEM014-02	2019-09-24	2020-09-23
Electric and Magnetic Field Analyzer	Narda	EHP-50F	SEM022-05	2019-11-28	2020-11-27
Electric Field Probe	WANDEL & GOLTERMANN	EMR-20	EMC0907	2019-05-21	2020-05-20
EMF Tester	Narda	ELT-400	SZE039-4	2019-07-08	2020-07-07

Conducted Average Output Power					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
Shielding Room	SAEMC	MSR733	SEM001-09	2019-06-13	2022-06-12
DC Power Supply	Rohde & Schwarz	NGSM 32/10	SEM011-04	2020-03-24	2021-03-23
Spectrum Analyzer	Rohde & Schwarz	FSP	SEM004-06	2019-09-24	2020-09-23
Measurement Software	JS Tonscend	JS1120-2 BT/WIFI V2.	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM031-02	2019-07-11	2020-07-10
Attenuator	Weinschel Associates	WA41	SEM021-09	N/A	N/A
Signal Generator	KEYSIGHT	N5173B	SEM006-05	2019-09-24	2020-09-23
Power Sensor	KEYSIGHT	U2021XA	SEM009-13	2020-03-23	2021-03-22
Power Meter	Rohde & Schwarz	NRVS	SEM014-02	2019-09-24	2020-09-23
Electric and Magnetic Field Analyzer	Narda	EHP-50F	SEM022-05	2019-11-28	2020-11-27
Electric Field Probe	WANDEL & GOLTERMANN	EMR-20	EMC0907	2019-05-21	2020-05-20
EMF Tester	Narda	ELT-400	SZE039-4	2019-07-08	2020-07-07



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.
Attention: To check the authenticity of testing / inspection report and certificate, please contact us at telephone: (86-755) 83071443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch (SGS-CSTC) Laboratory

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn
中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

Power Spectrum Density					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
Shielding Room	SAEMC	MSR733	SEM001-09	2019-06-13	2022-06-12
DC Power Supply	Rohde & Schwarz	NGSM 32/10	SEM011-04	2020-03-24	2021-03-23
Spectrum Analyzer	Rohde & Schwarz	FSP	SEM004-06	2019-09-24	2020-09-23
Measurement Software	JS Tonscend	JS1120-2 BT/WIFI V2.	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM031-02	2019-07-11	2020-07-10
Attenuator	Weinschel Associates	WA41	SEM021-09	N/A	N/A
Signal Generator	KEYSIGHT	N5173B	SEM006-05	2019-09-24	2020-09-23
Power Meter	Rohde & Schwarz	NRVS	SEM014-02	2019-09-24	2020-09-23
Electric and Magnetic Field Analyzer	Narda	EHP-50F	SEM022-05	2019-11-28	2020-11-27
Electric Field Probe	WANDEL & GOLTERMANN	EMR-20	EMC0907	2019-05-21	2020-05-20
EMF Tester	Narda	ELT-400	SZE039-4	2019-07-08	2020-07-07

Conducted Band Edges Measurement					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
Shielding Room	SAEMC	MSR733	SEM001-09	2019-06-13	2022-06-12
DC Power Supply	Rohde & Schwarz	NGSM 32/10	SEM011-04	2020-03-24	2021-03-23
Spectrum Analyzer	Rohde & Schwarz	FSP	SEM004-06	2019-09-24	2020-09-23
Measurement Software	JS Tonscend	JS1120-2 BT/WIFI V2.	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM031-02	2019-07-11	2020-07-10
Attenuator	Weinschel Associates	WA41	SEM021-09	N/A	N/A
Signal Generator	KEYSIGHT	N5173B	SEM006-05	2019-09-24	2020-09-23
Power Meter	Rohde & Schwarz	NRVS	SEM014-02	2019-09-24	2020-09-23
Electric and Magnetic Field Analyzer	Narda	EHP-50F	SEM022-05	2019-11-28	2020-11-27
Electric Field Probe	WANDEL & GOLTERMANN	EMR-20	EMC0907	2019-05-21	2020-05-20
EMF Tester	Narda	ELT-400	SZE039-4	2019-07-08	2020-07-07



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 83071443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch (SGS-CSTC Laboratory)

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

Conducted Spurious Emissions					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
Shielding Room	SAEMC	MSR733	SEM001-09	2019-06-13	2022-06-12
DC Power Supply	Rohde & Schwarz	NGSM 32/10	SEM011-04	2020-03-24	2021-03-23
Spectrum Analyzer	Rohde & Schwarz	FSP	SEM004-06	2019-09-24	2020-09-23
Measurement Software	JS Tonscend	JS1120-2 BT/WIFI V2.	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM031-02	2019-07-11	2020-07-10
Attenuator	Weinschel Associates	WA41	SEM021-09	N/A	N/A
Signal Generator	KEYSIGHT	N5173B	SEM006-05	2019-09-24	2020-09-23
Power Meter	Rohde & Schwarz	NRVS	SEM014-02	2019-09-24	2020-09-23
Electric and Magnetic Field Analyzer	Narda	EHP-50F	SEM022-05	2019-11-28	2020-11-27
Electric Field Probe	WANDEL & GOLTERMANN	EMR-20	EMC0907	2019-05-21	2020-05-20
EMF Tester	Narda	ELT-400	SZE039-4	2019-07-08	2020-07-07

Radiated Emissions which fall in the restricted bands					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
3m Semi-Anechoic Chamber	AUDIX	N/A	SEM001-02	2018-03-13	2021-03-12
Measurement Software	AUDIX	e3 V8.2014-6-27	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM026-01	2019-07-11	2020-07-10
EXA Spectrum Analyzer	Agilent Technologies Inc	N9010A	SEM004-12	2020-04-09	2021-04-08
Horn Antenna	Rohde & Schwarz	HF907	SEM003-07	2018-04-13	2021-04-12
Horn Antenna	Schwarzbeck	BBHA 9170	SEM003-15	2017-10-17	2020-10-16
Pre-Amplifier	Compliance Directions Systems Inc.	PAP-0126	SEM004-11	2019-09-24	2020-09-23
Pre-amplifier	Rohde & Schwarz	CH14-H052	SEM005-17	2020-04-01	2021-03-31
Pre-amplifier	Compliance Directions Systems Inc.	PAP-2640-50	SEM005-08	2020-04-01	2021-03-31
DC Power Supply	Zhao Xin	KXN-6020D	SEM011-08	2019-09-24	2020-09-23
Active Loop Antenna	ETS-Lindgren	6502	SEM003-08	2017-08-22	2020-08-21



Radiated Spurious Emissions					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
10m Semi-Anechoic Chamber	SAEMC	FSAC1018	SEM001-03	2018-03-31	2021-03-30
Measurement Software	AUDIX	e3 V8.2014-6-27	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM029-01	2019-07-11	2020-07-10
MXE EMI receiver	KEYSIGHT	N9038A	SEM004-16	2019-12-16	2020-12-15
Trilog-Broadband Antenna	Schwarzbeck	VULB9168	SEM003-18	2019-08-08	2022-08-07
Pre-amplifier	Sonoma Instrument Co	310N	SEM005-04	2020-04-09	2021-04-08
3m Semi-Anechoic Chamber	AUDIX	N/A	SEM001-02	2018-03-13	2021-03-12
Measurement Software	AUDIX	e3 V8.2014-6-27	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM026-01	2019-07-11	2020-07-10
EXA Spectrum Analyzer	Agilent Technologies Inc	N9010A	SEM004-12	2020-04-09	2021-04-08
Horn Antenna	Rohde & Schwarz	HF907	SEM003-07	2018-04-13	2021-04-12
Horn Antenna	Schwarzbeck	BBHA 9170	SEM003-15	2017-10-17	2020-10-16
Pre-Amplifier	Compliance Directions Systems Inc.	PAP-0126	SEM004-11	2019-09-24	2020-09-23
Pre-amplifier	Rohde & Schwarz	CH14-H052	SEM005-17	2020-04-01	2021-03-31
Pre-amplifier	Compliance Directions Systems Inc.	PAP-2640-50	SEM005-08	2020-04-01	2021-03-31
DC Power Supply	Zhao Xin	KXN-6020D	SEM011-08	2019-09-24	2020-09-23
Active Loop Antenna	ETS-Lindgren	6502	SEM003-08	2017-08-22	2020-08-21

General used equipment					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
Humidity/ Temperature Indicator	Shanghai Meteorological Industry Factory	ZJ1-2B	SEM002-03	2019-09-26	2020-09-25
Humidity/ Temperature Indicator	Shanghai Meteorological Industry Factory	ZJ1-2B	SEM002-04	2019-09-26	2020-09-25
Humidity/ Temperature Indicator	Mingle	N/A	SEM002-08	2019-09-26	2020-09-25
Barometer	Changchun Meteorological Industry Factory	DYM3	SEM002-01	2020-04-07	2021-04-06



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 83071443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch (CMA, CNAS, ILAC Laboratory)

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

6 Radio Spectrum Technical Requirement

6.1 Antenna Requirement

6.1.1 Test Requirement:

47 CFR Part 15, Subpart C 15.203 & 15.247(b)(4)

6.1.2 Conclusion

Standard Requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

15.247(b) (4) requirement:

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

EUT Antenna:

The antenna is integrated on the main PCB and no consideration of replacement. The best case gain of the antenna is 4.5dBi, directional gain is 7.51dBi.

Antenna location: Refer to internal photo.

7 Radio Spectrum Matter Test Results

7.1 Minimum 6dB Bandwidth

Test Requirement 47 CFR Part 15, Subpart C 15.247a(2)
Test Method: ANSI C63.10 (2013) Section 11.8.1
Limit: ≥ 500 kHz


7.1.1 E.U.T. Operation

Operating Environment:

Temperature: 30 °C Humidity: 37.8 % RH Atmospheric Pressure: 1005 mbar

Test mode a:TX mode_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); data rate @ 13.5Mbps is the worst case of IEEE 802.11n(HT40). Only the data of worst case is recorded in the report.

7.1.2 Test Setup Diagram



7.1.3 Measurement Procedure and Data

The detailed test data see: Appendix 15.247

7.2 Conducted Average Output Power

Test Requirement 47 CFR Part 15, Subpart C 15.247(b)(3)

Test Method: ANSI C63.10 (2013) Section 11.9.1

Limit:

Frequency range(MHz)	Output power of the intentional radiator(watt)
902-928	1 for ≥ 50 hopping channels
	0.25 for $25 \leq$ hopping channels < 50
	1 for digital modulation
2400-2483.5	1 for ≥ 75 non-overlapping hopping channels
	0.125 for all other frequency hopping systems
	1 for digital modulation
5725-5850	1 for frequency hopping systems and digital modulation

Remark: if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.


7.2.1 E.U.T. Operation

Operating Environment:

Temperature: 30 °C Humidity: 37.7 % RH Atmospheric Pressure: 1005 mbar

Test mode a:TX mode_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); data rate @ 13.5Mbps is the worst case of IEEE 802.11n(HT40). Only the data of worst case is recorded in the report.

7.2.2 Test Setup Diagram



7.2.3 Measurement Procedure and Data

The detailed test data see: Appendix 15.247

7.3 Power Spectrum Density

Test Requirement 47 CFR Part 15, Subpart C 15.247(e)
Test Method: ANSI C63.10 (2013) Section 11.10.2
Limit: $\leq 8\text{dBm}$ in any 3 kHz band during any time interval of continuous transmission


7.3.1 E.U.T. Operation

Operating Environment:

Temperature: 30 °C Humidity: 37.7 % RH Atmospheric Pressure: 1005 mbar

Test mode a:TX mode_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); data rate @ 13.5Mbps is the worst case of IEEE 802.11n(HT40). Only the data of worst case is recorded in the report.

7.3.2 Test Setup Diagram



7.3.3 Measurement Procedure and Data

The detailed test data see: Appendix 15.247

7.4 Conducted Band Edges Measurement

Test Requirement 47 CFR Part 15, Subpart C 15.247(d)

Test Method: ANSI C63.10 (2013) Section 11.13.3.2

Limit: In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c))




7.4.1 E.U.T. Operation

Operating Environment:

Temperature: 30 °C Humidity: 37.7 % RH Atmospheric Pressure: 1005 mbar

Test mode a:TX mode_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); data rate @ 13.5Mbps is the worst case of IEEE 802.11n(HT40). Only the data of worst case is recorded in the report.

7.4.2 Test Setup Diagram



7.4.3 Measurement Procedure and Data

The detailed test data see: Appendix 15.247

7.5 Conducted Spurious Emissions

Test Requirement 47 CFR Part 15, Subpart C 15.247(d)

Test Method: ANSI C63.10 (2013) Section 11.11

Limit: In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c))




7.5.1 E.U.T. Operation

Operating Environment:

Temperature: 30 °C Humidity: 37.7 % RH Atmospheric Pressure: 1005 mbar

Test mode a:TX mode_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); data rate @ 13.5Mbps is the worst case of IEEE 802.11n(HT40). Only the data of worst case is recorded in the report.

7.5.2 Test Setup Diagram



7.5.3 Measurement Procedure and Data

The detailed test data see: Appendix 15.247

7.6 Radiated Emissions which fall in the restricted bands

Test Requirement 47 CFR Part 15, Subpart C 15.209 & 15.247(d)

Test Method: ANSI C63.10 (2013) Section 6.10.5

Measurement Distance: 3m

Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.


7.6.1 E.U.T. Operation

Operating Environment:

Temperature: 24.4 °C Humidity: 64.7 % RH Atmospheric Pressure: 1010 mbar

Test mode a:TX mode_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); data rate @ 13.5Mbps is the worst case of IEEE 802.11n(HT40). Only the data of worst case is recorded in the report.

7.6.2 Test Setup Diagram



7.6.3 Measurement Procedure and Data


- a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- d. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- f. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- g. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- h. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- j. Repeat above procedures until all frequencies measured was complete.

Remark 1: Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor

Remark 2: For frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.

B

Mode:a; Polarization:Horizontal; Modulation Type:802.11b; bandwidth:20MHz; Channel 2412




Site : chamber
Condition: 3m HORIZONTAL
Job No : 03232CR/03233CR/03234CR
Mode : 2412 Band edge
Note : 2.4G WIFI 11B

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	2310.000	4.22	28.38	40.94	46.61	38.27	54.00	-15.73 Average
2	2390.000	3.69	28.52	40.97	46.75	37.99	54.00	-16.01 Average
3 *	2412.000	3.68	28.56	40.98	99.39	90.65	54.00	36.65 Average



Mode:a; Polarization:Horizontal; Modulation Type:802.11b; bandwidth:20MHz; Channel 2412




Site : chamber
Condition: 3m HORIZONTAL
Job No : 03232CR/03233CR/03234CR
Mode : 2412 Band edge
Note : 2.4G WIFI 11B

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	2330.800	4.08	28.42	40.95	57.58	49.13	74.00	-24.87 peak
2	2390.000	3.69	28.52	40.97	56.33	47.57	74.00	-26.43 peak
3 *	2412.000	3.68	28.56	40.98	101.63	92.89	74.00	18.89 peak



Mode:a; Polarization:Vertical; Modulation Type:802.11b; bandwidth:20MHz; Channel:2412




Site : chamber
Condition: 3m VERTICAL
Job No : 03232CR/03233CR/03234CR
Mode : 2412 Band edge
Note : 2.4G WIFI 11B

		Cable	Ant	Preamp	Read	Limit	Over	
Freq		Loss	Factor	Factor	Level	Line	Limit	Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dB	
1	2389.605	3.69	28.52	40.97	50.73	41.97	54.00	-12.03 Average
2	2390.000	3.69	28.52	40.97	50.71	41.95	54.00	-12.05 Average
3 *	2412.000	3.68	28.56	40.98	110.41	101.67	54.00	47.67 Average



Mode:a; Polarization:Vertical; Modulation Type:802.11b; bandwidth:20MHz; Channel:2412




Site : chamber
Condition: 3m VERTICAL
Job No : 03232CR/03233CR/03234CR
Mode : 2412 Band edge
Note : 2.4G WIFI 11B

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	2311.755	4.21	28.38	40.94	60.07	51.72	74.00	-22.28 peak
2	2390.000	3.69	28.52	40.97	60.41	51.65	74.00	-22.35 peak
3 *	2412.000	3.68	28.56	40.98	112.65	103.91	74.00	29.91 peak



Mode:a; Polarization:Horizontal; Modulation Type:802.11b; bandwidth:20MHz; Channel:2417




Site : chamber
Condition: 3m HORIZONTAL
Job No : 03232CR/03233CR/03234CR
Mode : 2417 Band edge
Note : 2.4G WIFI 11B

		Cable	Ant	Preamp	Read	Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	2389.968	3.69	28.52	40.97	47.08	38.32	54.00	-15.68 Average
2	2390.000	3.69	28.52	40.97	47.08	38.32	54.00	-15.68 Average
3 *	2415.766	3.69	28.56	40.98	102.53	93.80	54.00	39.80 Peak



Mode:a; Polarization:Horizontal; Modulation Type:802.11b; bandwidth:20MHz; Channel:2417




Site : chamber
Condition: 3m HORIZONTAL
Job No : 03232CR/03233CR/03234CR
Mode : 2417 Band edge
Note : 2.4G WIFI 11B

		Cable	Ant	Preamp	Read	Limit	Over	
Freq		Loss	Factor	Factor	Level	Line	Limit	Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	2388.154	3.70	28.52	40.97	57.89	49.14	74.00	-24.86 peak
2	2390.000	3.69	28.52	40.97	55.50	46.74	74.00	-27.26 peak
3 *	2416.011	3.69	28.56	40.98	104.80	96.07	74.00	22.07 Peak



Mode:a; Polarization:Vertical; Modulation Type:802.11b; bandwidth:20MHz; Channel:2417




Site : chamber
Condition: 3m VERTICAL
Job No : 03232CR/03233CR/03234CR
Mode : 2417 Band edge
Note : 2.4G WIFI 11B

		Cable	Ant	Preamp	Read	Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	2389.968	3.69	28.52	40.97	52.23	43.47	54.00	-10.53 Average
2	2390.000	3.69	28.52	40.97	52.23	43.47	54.00	-10.53 Average
3 *	2415.766	3.69	28.56	40.98	113.35	104.62	54.00	50.62 Peak



Mode:a; Polarization:Vertical; Modulation Type:802.11b; bandwidth:20MHz; Channel:2417




Site : chamber
Condition: 3m VERTICAL
Job No : 03232CR/03233CR/03234CR
Mode : 2417 Band edge
Note : 2.4G WIFI 11B

		Cable	Ant	Preamp	Read	Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	2389.968	3.69	28.52	40.97	61.53	52.77	74.00	-21.23 peak
2	2390.000	3.69	28.52	40.97	61.53	52.77	74.00	-21.23 peak
3 *	2415.522	3.69	28.56	40.98	115.64	106.91	74.00	32.91 Peak



Mode:a; Polarization:Horizontal; Modulation Type:802.11b; bandwidth:20MHz; Channel 2457




Site : chamber
Condition: 3m HORIZONTAL
Job No : 03232CR/03233CR/03234CR
Mode : 2457 Band edge
Note : 2.4G WIFI 11B

		Cable	Ant	Preamp	Read	Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 *	2457.000	3.88	28.63	41.00	101.16	92.67	54.00	38.67 Average
2	2483.500	4.01	28.67	41.01	46.98	38.65	54.00	-15.35 Average
3	2489.123	4.03	28.68	41.01	47.10	38.80	54.00	-15.20 Average



Mode:a; Polarization:Horizontal; Modulation Type:802.11b; bandwidth:20MHz; Channel 2457



Site : chamber
Condition: 3m HORIZONTAL
Job No : 03232CR/03233CR/03234CR
Mode : 2457 Band edge
Note : 2.4G WIFI 11B

		Cable	Ant	Preamp	Read	Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 *	2457.000	3.88	28.63	41.00	103.36	94.87	74.00	20.87 peak
2	2483.500	4.01	28.67	41.01	55.60	47.27	74.00	-26.73 peak
3	2495.055	4.06	28.69	41.02	57.43	49.16	74.00	-24.84 peak




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.
Attention: To check the authenticity of testing /inspection report and certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch (China) EMC Laboratory

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn
中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

Mode:a; Polarization:Vertical; Modulation Type:802.11b; bandwidth:20MHz; Channel:2457



Site : chamber
Condition: 3m VERTICAL
Job No : 03232CR/03233CR/03234CR
Mode : 2457 Band edge
Note : 2.4G WIFI 11B

		Cable	Ant	Preamp	Read	Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 *	2457.000	3.88	28.63	41.00	111.90	103.41	54.00	49.41 Average
2	2483.500	4.01	28.67	41.01	51.54	43.21	54.00	-10.79 Average
3	2483.869	4.01	28.67	41.01	51.40	43.07	54.00	-10.93 Average




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.
Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch (China) EMC Laboratory

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn
中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

Mode:a; Polarization:Vertical; Modulation Type:802.11b; bandwidth:20MHz; Channel:2457




Site : chamber
Condition: 3m VERTICAL
Job No : 03232CR/03233CR/03234CR
Mode : 2457 Band edge
Note : 2.4G WIFI 11B

		Cable	Ant	Preamp	Read	Limit	Over	
Freq		Loss	Factor	Factor	Level	Line	Limit	Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dB	
1 *	2457.000	3.88	28.63	41.00	114.11	105.62	74.00	31.62 peak
2	2483.500	4.01	28.67	41.01	60.28	51.95	74.00	-22.05 peak
3	2485.361	4.01	28.68	41.01	61.35	53.03	74.00	-20.97 peak



Mode:a; Polarization:Horizontal; Modulation Type:802.11b; bandwidth:20MHz; Channel:2462



Site : chamber
Condition: 3m HORIZONTAL
Job No : 03232CR/03233CR/03234CR
Mode : 2462 Band edge
Note : 2.4G WIFI 11B

		Cable	Ant	Preamp	Read	Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 *	2462.000	3.91	28.64	41.00	99.57	91.12	54.00	37.12 Average
2	2483.500	4.01	28.67	41.01	47.05	38.72	54.00	-15.28 Average
3	2487.958	4.03	28.68	41.01	47.06	38.76	54.00	-15.24 Average




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.
Attention: To check the authenticity of testing /inspection report and certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch (China) SGS-CSTC Laboratory

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn
中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

Mode:a; Polarization:Horizontal; Modulation Type:802.11b; bandwidth:20MHz; Channel:2462




Site : chamber
Condition: 3m HORIZONTAL
Job No : 03232CR/03233CR/03234CR
Mode : 2462 Band edge
Note : 2.4G WIFI 11B

		Cable	Ant	Preamp	Read	Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 *	2462.000	3.91	28.64	41.00	101.81	93.36	74.00	19.36 peak
2	2483.500	4.01	28.67	41.01	56.20	47.87	74.00	-26.13 peak
3	2494.450	4.05	28.69	41.02	58.20	49.92	74.00	-24.08 peak



Mode:a; Polarization:Vertical; Modulation Type:802.11b; bandwidth:20MHz; Channel:2462




Site : chamber
Condition: 3m VERTICAL
Job No : 03232CR/03233CR/03234CR
Mode : 2462 Band edge
Note : 2.4G WIFI 11B

		Cable	Ant	Preamp	Read	Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 *	2462.000	3.91	28.64	41.00	110.11	101.66	54.00	47.66 Average
2	2483.500	4.01	28.67	41.01	51.35	43.02	54.00	-10.98 Average
3	2487.355	4.02	28.68	41.01	51.20	42.89	54.00	-11.11 Average



Mode:a; Polarization:Vertical; Modulation Type:802.11b; bandwidth:20MHz; Channel:2462




Site : chamber
Condition: 3m VERTICAL
Job No : 03232CR/03233CR/03234CR
Mode : 2462 Band edge
Note : 2.4G WIFI 11B

		Cable	Ant	Preamp	Read	Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 *	2462.000	3.91	28.64	41.00	112.31	103.86	74.00	29.86 peak
2	2483.500	4.01	28.67	41.01	60.95	52.62	74.00	-21.38 peak
3	2491.177	4.04	28.69	41.01	61.17	52.89	74.00	-21.11 peak



G

Mode:a; Polarization:Horizontal; Modulation Type:802.11g; bandwidth:20MHz; Channel 2412




Site : chamber
Condition: 3m HORIZONTAL
Job No : 03232CR/03233CR/03234CR
Mode : 2412 Band edge
Note : 2.4G WIFI 11G

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	2389.726	3.69	28.52	40.97	48.03	39.27	54.00	-14.73 Average
2	2390.000	3.69	28.52	40.97	47.97	39.21	54.00	-14.79 Average
3 *	2412.000	3.68	28.56	40.98	97.19	88.45	54.00	34.45 Average



Mode:a; Polarization:Horizontal; Modulation Type:802.11g; bandwidth:20MHz; Channel 2412




Site : chamber
Condition: 3m HORIZONTAL
Job No : 03232CR/03233CR/03234CR
Mode : 2412 Band edge
Note : 2.4G WIFI 11G

		Cable	Ant	Preamp	Read	Limit	Over	
Freq		Loss	Factor	Factor	Level	Line	Limit	Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	2346.433	3.98	28.44	40.95	57.31	48.78	74.00	-25.22 peak
2	2390.000	3.69	28.52	40.97	56.64	47.88	74.00	-26.12 peak
3 *	2412.000	3.68	28.56	40.98	104.05	95.31	74.00	21.31 peak



Mode:a; Polarization:Vertical; Modulation Type:802.11g; bandwidth:20MHz; Channel:2412




Site : chamber
Condition: 3m VERTICAL
Job No : 03232CR/03233CR/03234CR
Mode : 2412 Band edge
Note : 2.4G WIFI 11G

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	2389.968	3.69	28.52	40.97	57.68	48.92	54.00	-5.08 Average
2	2390.000	3.69	28.52	40.97	57.68	48.92	54.00	-5.08 Average
3 *	2412.000	3.68	28.56	40.98	108.88	100.14	54.00	46.14 Average



Mode:a; Polarization:Vertical; Modulation Type:802.11g; bandwidth:20MHz; Channel:2412




Site : chamber
Condition: 3m VERTICAL
Job No : 03232CR/03233CR/03234CR
Mode : 2412 Band edge
Note : 2.4G WIFI 11G

		Cable	Ant	Preamp	Read	Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	2389.847	3.69	28.52	40.97	69.69	60.93	74.00	-13.07 peak
2	2390.000	3.69	28.52	40.97	69.34	60.58	74.00	-13.42 peak
3 *	2412.000	3.68	28.56	40.98	115.83	107.09	74.00	33.09 peak



Mode:a; Polarization:Horizontal; Modulation Type:802.11g; bandwidth:20MHz; Channel:2417




Site : chamber
Condition: 3m HORIZONTAL
Job No : 03232CR/03233CR/03234CR
Mode : 2417 Band edge
Note : 2.4G WIFI 11G

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dB	
1	2389.484	3.69	28.52	40.97	48.77	40.01	54.00	-13.99 Average
2	2390.000	3.69	28.52	40.97	48.74	39.98	54.00	-14.02 Average
3 *	2412.000	3.68	28.56	40.98	101.30	92.56	54.00	38.56 Average



Mode:a; Polarization:Horizontal; Modulation Type:802.11g; bandwidth:20MHz; Channel:2417




Site : chamber
Condition: 3m HORIZONTAL
Job No : 03232CR/03233CR/03234CR
Mode : 2417 Band edge
Note : 2.4G WIFI 11G

		Cable	Ant	Preamp	Read	Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	2389.605	3.69	28.52	40.97	61.18	52.42	74.00	-21.58 peak
2	2390.000	3.69	28.52	40.97	57.24	48.48	74.00	-25.52 peak
3 *	2412.000	3.68	28.56	40.98	108.28	99.54	74.00	25.54 peak



Mode:a; Polarization:Vertical; Modulation Type:802.11g; bandwidth:20MHz; Channel:2417




Site : chamber
Condition: 3m VERTICAL
Job No : 03232CR/03233CR/03234CR
Mode : 2417 Band edge
Note : 2.4G WIFI 11G

		Cable	Ant	Preamp	Read	Limit	Over	
Freq		Loss	Factor	Factor	Level	Line	Limit	Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dB	
1	2389.847	3.69	28.52	40.97	56.01	47.25	54.00	-6.75 Average
2	2390.000	3.69	28.52	40.97	55.95	47.19	54.00	-6.81 Average
3 *	2412.832	3.68	28.56	40.98	110.91	102.17	54.00	48.17 Peak



Mode:a; Polarization:Vertical; Modulation Type:802.11g; bandwidth:20MHz; Channel:2417




Site : chamber
Condition: 3m VERTICAL
Job No : 03232CR/03233CR/03234CR
Mode : 2417 Band edge
Note : 2.4G WIFI 11G

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	2389.484	3.69	28.52	40.97	68.72	59.96	74.00	-14.04 peak
2	2390.000	3.69	28.52	40.97	66.86	58.10	74.00	-15.90 peak
3 *	2412.000	3.68	28.56	40.98	118.03	109.29	74.00	35.29 peak



Mode:a; Polarization:Horizontal; Modulation Type:802.11g; bandwidth:20MHz; Channel 2457




Site : chamber
Condition: 3m HORIZONTAL
Job No : 03232CR/03233CR/03234CR
Mode : 2457 Band edge
Note : 2.4G WIFI 11G

		Cable	Ant	Preamp	Read	Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 *	2457.000	3.88	28.63	41.00	99.81	91.32	54.00	37.32 Average
2	2483.500	4.01	28.67	41.01	47.72	39.39	54.00	-14.61 Average
3	2483.869	4.01	28.67	41.01	47.85	39.52	54.00	-14.48 Average



Mode:a; Polarization:Horizontal; Modulation Type:802.11g; bandwidth:20MHz; Channel 2457




Site : chamber
Condition: 3m HORIZONTAL
Job No : 03232CR/03233CR/03234CR
Mode : 2457 Band edge
Note : 2.4G WIFI 11G

		Cable	Ant	Preamp	Read	Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 *	2457.000	3.88	28.63	41.00	106.82	98.33	74.00	24.33 peak
2	2483.500	4.01	28.67	41.01	56.03	47.70	74.00	-26.30 peak
3	2497.999	4.07	28.70	41.02	57.73	49.48	74.00	-24.52 peak



Mode:a; Polarization:Vertical; Modulation Type:802.11g; bandwidth:20MHz; Channel:2457




Site : chamber
Condition: 3m VERTICAL
Job No : 03232CR/03233CR/03234CR
Mode : 2457 Band edge
Note : 2.4G WIFI 11G

		Cable	Ant	Preamp	Read	Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 *	2457.000	3.88	28.63	41.00	109.63	101.14	54.00	47.14 Average
2	2483.500	4.01	28.67	41.01	53.18	44.85	54.00	-9.15 Average
3	2484.034	4.01	28.67	41.01	53.22	44.89	54.00	-9.11 Average



Mode:a; Polarization:Vertical; Modulation Type:802.11g; bandwidth:20MHz; Channel:2457




Site : chamber
Condition: 3m VERTICAL
Job No : 03232CR/03233CR/03234CR
Mode : 2457 Band edge
Note : 2.4G WIFI 11G

		Cable	Ant	Preamp	Read	Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 *	2457.000	3.88	28.63	41.00	116.79	108.30	74.00	34.30 peak
2	2483.500	4.01	28.67	41.01	61.77	53.44	74.00	-20.56 peak
3	2485.195	4.01	28.68	41.01	64.12	55.80	74.00	-18.20 peak



Mode:a; Polarization:Horizontal; Modulation Type:802.11g; bandwidth:20MHz; Channel:2462




Site : chamber
Condition: 3m HORIZONTAL
Job No : 03232CR/03233CR/03234CR
Mode : 2462 Band edge
Note : 2.4G WIFI 11G

		Cable	Ant	Preamp	Read	Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 *	2462.000	3.91	28.64	41.00	96.54	88.09	54.00	34.09 Average
2	2483.500	4.01	28.67	41.01	48.00	39.67	54.00	-14.33 Average
3	2483.790	4.01	28.67	41.01	47.89	39.56	54.00	-14.44 Average



Mode:a; Polarization:Horizontal; Modulation Type:802.11g; bandwidth:20MHz; Channel:2462




Site : chamber
Condition: 3m HORIZONTAL
Job No : 03232CR/03233CR/03234CR
Mode : 2462 Band edge
Note : 2.4G WIFI 11G

		Cable	Ant	Preamp	Read	Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 *	2462.000	3.91	28.64	41.00	103.58	95.13	74.00	21.13 peak
2	2483.500	4.01	28.67	41.01	55.33	47.00	74.00	-27.00 peak
3	2496.467	4.06	28.69	41.02	57.36	49.09	74.00	-24.91 peak



Mode:a; Polarization:Vertical; Modulation Type:802.11g; bandwidth:20MHz; Channel:2462




Site : chamber
Condition: 3m VERTICAL
Job No : 03232CR/03233CR/03234CR
Mode : 2462 Band edge
Note : 2.4G WIFI 11G

		Cable	Ant	Preamp	Read	Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 *	2462.000	3.91	28.64	41.00	107.05	98.60	54.00	44.60 Average
2	2483.500	4.01	28.67	41.01	54.39	46.06	54.00	-7.94 Average
3	2483.990	4.01	28.67	41.01	54.14	45.81	54.00	-8.19 Average



Mode:a; Polarization:Vertical; Modulation Type:802.11g; bandwidth:20MHz; Channel:2462




Site : chamber
Condition: 3m VERTICAL
Job No : 03232CR/03233CR/03234CR
Mode : 2462 Band edge
Note : 2.4G WIFI 11G

		Cable	Ant	Preamp	Read	Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 *	2462.000	3.91	28.64	41.00	114.23	105.78	74.00	31.78 peak
2	2483.500	4.01	28.67	41.01	65.10	56.77	74.00	-17.23 peak
3	2484.492	4.01	28.67	41.01	65.51	57.18	74.00	-16.82 peak



N20

Mode:a; Polarization:Horizontal; Modulation Type:802.11n; bandwidth:20MHz; Channel 2412




Site : chamber
Condition: 3m HORIZONTAL
Job No : 03232CR/03233CR/03234CR
Mode : 2412 Band edge
Note : 2.4G WIFI 11N20

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	2389.605	3.69	28.52	40.97	48.33	39.57	54.00	-14.43 Average
2	2390.000	3.69	28.52	40.97	48.22	39.46	54.00	-14.54 Average
3 *	2412.000	3.68	28.56	40.98	96.76	88.02	54.00	34.02 Average



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.
Attention: To check the authenticity of testing / inspection report and certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

Mode:a; Polarization:Horizontal; Modulation Type:802.11n; bandwidth:20MHz; Channel 2412




Site : chamber
Condition: 3m HORIZONTAL
Job No : 03232CR/03233CR/03234CR
Mode : 2412 Band edge
Note : 2.4G WIFI 11N20

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	2389.968	3.69	28.52	40.97	58.97	50.21	74.00	-23.79 peak
2	2390.000	3.69	28.52	40.97	58.97	50.21	74.00	-23.79 peak
3 *	2412.000	3.68	28.56	40.98	103.79	95.05	74.00	21.05 peak



Mode:a; Polarization:Vertical; Modulation Type:802.11n; bandwidth:20MHz; Channel:2412




Site : chamber
Condition: 3m VERTICAL
Job No : 03232CR/03233CR/03234CR
Mode : 2412 Band edge
Note : 2.4G WIFI 11N20

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	2389.968	3.69	28.52	40.97	56.31	47.55	54.00	-6.45 Average
2	2390.000	3.69	28.52	40.97	56.31	47.55	54.00	-6.45 Average
3 *	2412.000	3.68	28.56	40.98	106.71	97.97	54.00	43.97 Average



Mode:a; Polarization:Vertical; Modulation Type:802.11n; bandwidth:20MHz; Channel:2412




Site : chamber
Condition: 3m VERTICAL
Job No : 03232CR/03233CR/03234CR
Mode : 2412 Band edge
Note : 2.4G WIFI 11N20

		Cable	Ant	Preamp	Read	Limit	Over	
Freq		Loss	Factor	Factor	Level	Line	Limit	Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	2389.968	3.69	28.52	40.97	70.15	61.39	74.00	-12.61 peak
2	2390.000	3.69	28.52	40.97	70.15	61.39	74.00	-12.61 peak
3 *	2412.000	3.68	28.56	40.98	113.65	104.91	74.00	30.91 peak



Mode:a; Polarization:Horizontal; Modulation Type:802.11n; bandwidth:20MHz; Channel:2417




Site : chamber
Condition: 3m HORIZONTAL
Job No : 03232CR/03233CR/03234CR
Mode : 2417 Band edge
Note : 2.4G WIFI 11N20

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	2389.847	3.69	28.52	40.97	48.93	40.17	54.00	-13.83 Average
2	2390.000	3.69	28.52	40.97	48.77	40.01	54.00	-13.99 Average
3 *	2412.000	3.68	28.56	40.98	101.00	92.26	54.00	38.26 Average



Mode:a; Polarization:Horizontal; Modulation Type:802.11n; bandwidth:20MHz; Channel:2417




Site : chamber
Condition: 3m HORIZONTAL
Job No : 03232CR/03233CR/03234CR
Mode : 2417 Band edge
Note : 2.4G WIFI 11N20

		Cable	Ant	Preamp	Read	Limit	Over	
Freq		Loss	Factor	Factor	Level	Line	Limit	Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dB	
1	2389.484	3.69	28.52	40.97	61.34	52.58	74.00	-21.42 peak
2	2390.000	3.69	28.52	40.97	58.32	49.56	74.00	-24.44 peak
3 *	2412.000	3.68	28.56	40.98	108.22	99.48	74.00	25.48 peak



Mode:a; Polarization:Vertical; Modulation Type:802.11n; bandwidth:20MHz; Channel:2417




Site : chamber
Condition: 3m VERTICAL
Job No : 03232CR/03233CR/03234CR
Mode : 2417 Band edge
Note : 2.4G WIFI 11N20

		Cable	Ant	Preamp	Read	Limit	Over	
Freq		Loss	Factor	Factor	Level	Line	Limit	Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dB	
1	2389.726	3.69	28.52	40.97	56.56	47.80	54.00	-6.20 Average
2	2390.000	3.69	28.52	40.97	56.42	47.66	54.00	-6.34 Average
3 *	2412.588	3.68	28.56	40.98	110.52	101.78	54.00	47.78 Peak



Mode:a; Polarization:Vertical; Modulation Type:802.11n; bandwidth:20MHz; Channel:2417




Site : chamber
Condition: 3m VERTICAL
Job No : 03232CR/03233CR/03234CR
Mode : 2417 Band edge
Note : 2.4G WIFI 11N20

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	2388.879	3.69	28.52	40.97	69.84	61.08	74.00	-12.92 peak
2	2390.000	3.69	28.52	40.97	66.68	57.92	74.00	-16.08 peak
3 *	2412.710	3.68	28.56	40.98	117.77	109.03	74.00	35.03 Peak



Mode:a; Polarization:Horizontal; Modulation Type:802.11n; bandwidth:20MHz; Channel 2457




Site : chamber
Condition: 3m HORIZONTAL
Job No : 03232CR/03233CR/03234CR
Mode : 2457 Band edge
Note : 2.4G WIFI 11N20

		Cable	Ant	Preamp	Read	Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 *	2457.000	3.88	28.63	41.00	99.54	91.05	54.00	37.05 Average
2	2483.500	4.01	28.67	41.01	47.74	39.41	54.00	-14.59 Average
3	2483.869	4.01	28.67	41.01	47.81	39.48	54.00	-14.52 Average



Mode:a; Polarization:Horizontal; Modulation Type:802.11n; bandwidth:20MHz; Channel 2457




Site : chamber
Condition: 3m HORIZONTAL
Job No : 03232CR/03233CR/03234CR
Mode : 2457 Band edge
Note : 2.4G WIFI 11N20

		Cable	Ant	Preamp	Read	Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 *	2457.000	3.88	28.63	41.00	106.86	98.37	74.00	24.37 peak
2	2483.500	4.01	28.67	41.01	56.31	47.98	74.00	-26.02 peak
3	2492.559	4.05	28.69	41.01	57.92	49.65	74.00	-24.35 peak



Mode:a; Polarization:Vertical; Modulation Type:802.11n; bandwidth:20MHz; Channel:2457




Site : chamber
Condition: 3m VERTICAL
Job No : 03232CR/03233CR/03234CR
Mode : 2457 Band edge
Note : 2.4G WIFI 11N20

		Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 * 2457.000	3.88	28.63	41.00	109.17	100.68	54.00	46.68	Average
2 2483.500	4.01	28.67	41.01	53.30	44.97	54.00	-9.03	Average
3 2484.034	4.01	28.67	41.01	53.25	44.92	54.00	-9.08	Average



Mode:a; Polarization:Vertical; Modulation Type:802.11n; bandwidth:20MHz; Channel:2457




Site : chamber
Condition: 3m VERTICAL
Job No : 03232CR/03233CR/03234CR
Mode : 2457 Band edge
Note : 2.4G WIFI 11N20

		Cable	Ant	Preamp	Read	Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 *	2457.000	3.88	28.63	41.00	116.54	108.05	74.00	34.05 peak
2	2483.500	4.01	28.67	41.01	62.24	53.91	74.00	-20.09 peak
3	2484.421	4.01	28.67	41.01	65.19	56.86	74.00	-17.14 peak



Mode:a; Polarization:Horizontal; Modulation Type:802.11n; bandwidth:20MHz; Channel:2462




Site : chamber
Condition: 3m HORIZONTAL
Job No : 03232CR/03233CR/03234CR
Mode : 2462 Band edge
Note : 2.4G WIFI 11N20

		Cable	Ant	Preamp	Read	Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 *	2462.000	3.91	28.64	41.00	96.23	87.78	54.00	33.78 Average
2	2483.500	4.01	28.67	41.01	48.08	39.75	54.00	-14.25 Average
3	2484.392	4.01	28.67	41.01	48.08	39.75	54.00	-14.25 Average



Mode:a; Polarization:Horizontal; Modulation Type:802.11n; bandwidth:20MHz; Channel:2462




Site : chamber
Condition: 3m HORIZONTAL
Job No : 03232CR/03233CR/03234CR
Mode : 2462 Band edge
Note : 2.4G WIFI 11N20

		Cable	Ant	Preamp	Read	Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 *	2462.000	3.91	28.64	41.00	103.31	94.86	74.00	20.86 peak
2	2483.500	4.01	28.67	41.01	56.70	48.37	74.00	-25.63 peak
3	2496.114	4.06	28.69	41.02	57.78	49.51	74.00	-24.49 peak



Mode:a; Polarization:Vertical; Modulation Type:802.11n; bandwidth:20MHz; Channel:2462




Site : chamber
Condition: 3m VERTICAL
Job No : 03232CR/03233CR/03234CR
Mode : 2462 Band edge
Note : 2.4G WIFI 11N20

		Cable	Ant	Preamp	Read	Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 *	2462.000	3.91	28.64	41.00	106.47	98.02	54.00	44.02 Average
2	2483.500	4.01	28.67	41.01	55.51	47.18	54.00	-6.82 Average
3	2483.890	4.01	28.67	41.01	55.31	46.98	54.00	-7.02 Average



Mode:a; Polarization:Vertical; Modulation Type:802.11n; bandwidth:20MHz; Channel:2462




Site : chamber
Condition: 3m VERTICAL
Job No : 03232CR/03233CR/03234CR
Mode : 2462 Band edge
Note : 2.4G WIFI 11N20

		Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 * 2462.000	3.91	28.64	41.00	113.47	105.02	74.00	31.02	peak
2 2483.500	4.01	28.67	41.01	68.21	59.88	74.00	-14.12	peak
3 2484.442	4.01	28.67	41.01	66.78	58.45	74.00	-15.55	peak



N40

Mode:a; Polarization:Horizontal; Modulation Type:802.11n; bandwidth:40MHz; Channel 2422




Site : chamber
Condition: 3m HORIZONTAL
Job No : 03232CR/03233CR/03234CR
Mode : 2422 Band edge
Note : 2.4G WIFI 11N40

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	2389.492	3.69	28.52	40.97	51.02	42.26	54.00	-11.74 Average
2	2390.000	3.69	28.52	40.97	50.99	42.23	54.00	-11.77 Average
3 *	2422.000	3.72	28.57	40.99	94.45	85.75	54.00	31.75 Average



Mode:a; Polarization:Horizontal; Modulation Type:802.11n; bandwidth:40MHz; Channel 2422




Site : chamber
Condition: 3m HORIZONTAL
Job No : 03232CR/03233CR/03234CR
Mode : 2422 Band edge
Note : 2.4G WIFI 11N40

		Cable	Ant	Preamp	Read	Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	2388.649	3.69	28.52	40.97	61.57	52.81	74.00	-21.19 peak
2	2390.000	3.69	28.52	40.97	59.59	50.83	74.00	-23.17 peak
3 *	2422.000	3.72	28.57	40.99	101.79	93.09	74.00	19.09 peak



Mode:a; Polarization:Vertical; Modulation Type:802.11n; bandwidth:40MHz; Channel:2422




Site : chamber
Condition: 3m VERTICAL
Job No : 03232CR/03233CR/03234CR
Mode : 2422 Band edge
Note : 2.4G WIFI 11N40

		Cable	Ant	Preamp	Read	Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	2389.914	3.69	28.52	40.97	58.16	49.40	54.00	-4.60 Average
2	2390.000	3.69	28.52	40.97	58.27	49.51	54.00	-4.49 Average
3 *	2422.000	3.72	28.57	40.99	102.39	93.69	54.00	39.69 Average



Mode:a; Polarization:Vertical; Modulation Type:802.11n; bandwidth:40MHz; Channel:2422




Site : chamber
Condition: 3m VERTICAL
Job No : 03232CR/03233CR/03234CR
Mode : 2422 Band edge
Note : 2.4G WIFI 11N40

		Cable	Ant	Preamp	Read	Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	2389.633	3.69	28.52	40.97	68.76	60.00	74.00	-14.00 peak
2	2390.000	3.69	28.52	40.97	67.59	58.83	74.00	-15.17 peak
3 *	2422.000	3.72	28.57	40.99	109.34	100.64	74.00	26.64 peak



Mode:a; Polarization:Horizontal; Modulation Type:802.11n; bandwidth:40MHz; Channel:2427




Site : chamber
Condition: 3m HORIZONTAL
Job No : 03232CR/03233CR/03234CR
Mode : 2427 Band edge
Note : 2.4G WIFI 11N40

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	2389.633	3.69	28.52	40.97	53.00	44.24	54.00	-9.76 Average
2	2390.000	3.69	28.52	40.97	52.94	44.18	54.00	-9.82 Average
3 *	2422.000	3.72	28.57	40.99	96.37	87.67	54.00	33.67 Average



Mode:a; Polarization:Horizontal; Modulation Type:802.11n; bandwidth:40MHz; Channel:2427




Site : chamber
Condition: 3m HORIZONTAL
Job No : 03232CR/03233CR/03234CR
Mode : 2427 Band edge
Note : 2.4G WIFI 11N40

		Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2387.243	3.70	28.51	40.97	62.35	53.59	74.00	-20.41 peak
2	2390.000	3.69	28.52	40.97	60.83	52.07	74.00	-21.93 peak
3 *	2422.000	3.72	28.57	40.99	103.18	94.48	74.00	20.48 peak



Mode:a; Polarization:Vertical; Modulation Type:802.11n; bandwidth:40MHz; Channel:2427




Site : chamber
Condition: 3m VERTICAL
Job No : 03232CR/03233CR/03234CR
Mode : 2427 Band edge
Note : 2.4G WIFI 11N40

		Cable	Ant	Preamp	Read	Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	2389.914	3.69	28.52	40.97	57.70	48.94	54.00	-5.06 Average
2	2390.000	3.69	28.52	40.97	57.47	48.71	54.00	-5.29 Average
3 *	2422.000	3.72	28.57	40.99	102.37	93.67	54.00	39.67 Average



Mode:a; Polarization:Vertical; Modulation Type:802.11n; bandwidth:40MHz; Channel:2427




Site : chamber
Condition: 3m VERTICAL
Job No : 03232CR/03233CR/03234CR
Mode : 2427 Band edge
Note : 2.4G WIFI 11N40

		Cable	Ant	Preamp	Read	Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	2388.930	3.69	28.52	40.97	67.69	58.93	74.00	-15.07 peak
2	2390.000	3.69	28.52	40.97	66.25	57.49	74.00	-16.51 peak
3 *	2422.000	3.72	28.57	40.99	109.18	100.48	74.00	26.48 peak



Mode:a; Polarization:Horizontal; Modulation Type:802.11n; bandwidth:40MHz; Channel 2447




Site : chamber
Condition: 3m HORIZONTAL
Job No : 03232CR/03233CR/03234CR
Mode : 2447 Band edge
Note : 2.4G WIFI 11N40

		Cable	Ant	Preamp	Read	Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 *	2447.000	3.84	28.61	41.00	95.65	87.10	54.00	33.10 Average
2	2483.500	4.01	28.67	41.01	48.74	40.41	54.00	-13.59 Average
3	2484.276	4.01	28.67	41.01	48.89	40.56	54.00	-13.44 Average



Mode:a; Polarization:Horizontal; Modulation Type:802.11n; bandwidth:40MHz; Channel 2447




Site : chamber
Condition: 3m HORIZONTAL
Job No : 03232CR/03233CR/03234CR
Mode : 2447 Band edge
Note : 2.4G WIFI 11N40

		Cable	Ant	Preamp	Read	Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 *	2447.000	3.84	28.61	41.00	102.65	94.10	74.00	20.10 peak
2	2483.500	4.01	28.67	41.01	55.89	47.56	74.00	-26.44 peak
3	2485.407	4.01	28.68	41.01	58.65	50.33	74.00	-23.67 peak



Mode:a; Polarization:Vertical; Modulation Type:802.11n; bandwidth:40MHz; Channel:2447




Site : chamber
Condition: 3m VERTICAL
Job No : 03232CR/03233CR/03234CR
Mode : 2447 Band edge
Note : 2.4G WIFI 11N40

		Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 * 2447.000	3.84	28.61	41.00	105.34	96.79	54.00	42.79	Average
2 2483.500	4.01	28.67	41.01	58.49	50.16	54.00	-3.84	Average
3 2484.680	4.01	28.68	41.01	58.54	50.22	54.00	-3.78	Average



Mode:a; Polarization:Vertical; Modulation Type:802.11n; bandwidth:40MHz; Channel:2447




Site : chamber
Condition: 3m VERTICAL
Job No : 03232CR/03233CR/03234CR
Mode : 2447 Band edge
Note : 2.4G WIFI 11N40

		Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 * 2447.000	3.84	28.61	41.00	112.18	103.63	74.00	29.63	peak
2 2483.500	4.01	28.67	41.01	68.80	60.47	74.00	-13.53	peak
3 2484.195	4.01	28.67	41.01	70.47	62.14	74.00	-11.86	peak



Mode:a; Polarization:Horizontal; Modulation Type:802.11n; bandwidth:40MHz; Channel:2452




Site : chamber
Condition: 3m HORIZONTAL
Job No : 03232CR/03233CR/03234CR
Mode : 2452 Band edge
Note : 2.4G WIFI 11N40

		Cable	Ant	Preamp	Read	Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 *	2452.000	3.86	28.62	41.00	92.99	84.47	54.00	30.47 Average
2	2483.500	4.01	28.67	41.01	48.97	40.64	54.00	-13.36 Average
3	2484.782	4.01	28.68	41.01	48.93	40.61	54.00	-13.39 Average



Mode:a; Polarization:Horizontal; Modulation Type:802.11n; bandwidth:40MHz; Channel:2452




Site : chamber
Condition: 3m HORIZONTAL
Job No : 03232CR/03233CR/03234CR
Mode : 2452 Band edge
Note : 2.4G WIFI 11N40

		Cable	Ant	Preamp	Read	Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 *	2452.000	3.86	28.62	41.00	99.85	91.33	74.00	17.33 peak
2	2483.500	4.01	28.67	41.01	58.09	49.76	74.00	-24.24 peak
3	2484.500	4.01	28.67	41.01	57.91	49.58	74.00	-24.42 peak



Mode:a; Polarization:Vertical; Modulation Type:802.11n; bandwidth:40MHz; Channel:2452




Site : chamber
Condition: 3m VERTICAL
Job No : 03232CR/03233CR/03234CR
Mode : 2452 Band edge
Note : 2.4G WIFI 11N40

		Cable	Ant	Preamp	Read	Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 *	2452.000	3.86	28.62	41.00	102.64	94.12	54.00	40.12 Average
2	2483.500	4.01	28.67	41.01	57.68	49.35	54.00	-4.65 Average
3	2483.935	4.01	28.67	41.01	57.31	48.98	54.00	-5.02 Average



Mode:a; Polarization:Vertical; Modulation Type:802.11n; bandwidth:40MHz; Channel:2452



Site : chamber
Condition: 3m VERTICAL
Job No : 03232CR/03233CR/03234CR
Mode : 2452 Band edge
Note : 2.4G WIFI 11N40

		Cable	Ant	Preamp	Read	Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 *	2452.000	3.86	28.62	41.00	109.55	101.03	74.00	27.03 peak
2	2483.500	4.01	28.67	41.01	68.02	59.69	74.00	-14.31 peak
3	2484.147	4.01	28.67	41.01	67.98	59.65	74.00	-14.35 peak



7.7 Radiated Spurious Emissions

Test Requirement 47 CFR Part 15, Subpart C 15.209 & 15.247(d)

Test Method: ANSI C63.10 (2013) Section 6.4,6.5,6.6

Measurement Distance: 10m below 1GHz, 3m above 1GHz

Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

limit @10m from 30MHz to 1GHz shall be converted from 3m, with a reduction factor of $20 \cdot \log(10/3)$



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch (Shenzhen EMC Laboratory)

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn
中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com


7.7.1 E.U.T. Operation

Operating Environment:

Temperature: 25 °C Humidity: 45 % RH Atmospheric Pressure: 1005 mbar

Test mode a:TX mode_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); data rate @ 13.5Mbps is the worst case of IEEE 802.11n(HT40). Only the data of worst case is recorded in the report.

7.7.2 Test Setup Diagram



7.7.3 Measurement Procedure and Data


- a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- d. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- f. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- g. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- h. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- j. Repeat above procedures until all frequencies measured was complete.

Remark:

- 1) For emission below 1GHz, through pre-scan found the worst case is the lowest channel. Only the worst case is recorded in the report.
- 2) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:
Final Test Level = Receiver Reading + Antenna Factor + Cable Factor – Preamplifier Factor
- 3) Scan from 9kHz to 25GHz, the disturbance above 18GHz and below 30MHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.
- 4) For frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.

Below 1GHz

Mode: a; Polarization: Horizontal;



Condition: 10m HORIZONTAL


Job No. : 03232CR

Test Mode: a

		Ant	Preamp	Cable	Read		Limit	Over	
	Freq	Factor	Factor	Loss	Level	Level	Line	Limit	Remark
	MHz	dB/m	dB	dB	dBuV	dBuV/m	dBuV/m	dB	
1	53.882	20.09	32.44	1.01	25.39	14.05	29.50	-15.45	QP
2	73.359	16.56	32.38	1.11	25.58	10.87	29.50	-18.63	QP
3	145.861	20.00	32.30	1.46	26.61	15.77	33.00	-17.23	QP
4	472.176	23.70	32.37	2.81	27.40	21.54	35.60	-14.06	QP
5	595.133	25.91	32.05	3.16	27.60	24.62	35.60	-10.98	QP
6 pp	922.516	29.80	31.40	3.45	26.13	27.98	35.60	-7.62	QP



Mode :a; Polarization: Vertical



Condition: 10m VERTICAL

Job No. : 03232CR


Test Mode: a

	Ant Freq	Preamp Factor	Cable Factor	Cable Loss	Read Level	Limit Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dB	dB	dBuV	dBuV/m	dBuV/m	dB	
1	32.067	18.72	32.39	0.87	29.67	16.87	29.50	-12.63	QP
2	58.407	19.58	32.43	1.03	26.81	14.99	29.50	-14.51	QP
3	70.832	17.31	32.38	1.09	25.35	11.37	29.50	-18.13	QP
4	148.963	20.15	32.30	1.47	25.97	15.29	33.00	-17.71	QP
5	490.745	23.91	32.44	2.89	26.43	20.79	35.60	-14.81	QP
6 pp	929.008	29.80	31.36	3.46	26.92	28.82	35.60	-6.78	QP



Above 1GHz

Mode:a; Polarization:Horizontal; Modulation:802.11b; bandwidth:20MHz; Channel:Low




Site : chamber
Condition: 3m HORIZONTAL
Job No : 03232CR/03233CR/03234CR
Mode : 2412 TX SE
Note : 2.4G WIFI 11B

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1702.042	3.30	26.68	40.63	46.29	35.64	74.00	-38.36	peak
2	4456.315	6.51	33.53	42.52	47.89	45.41	74.00	-28.59	peak
3	4824.000	6.86	34.00	42.78	45.99	44.07	74.00	-29.93	peak
4	6142.019	7.55	35.25	42.16	48.35	48.99	74.00	-25.01	peak
5	7236.000	8.43	36.09	41.56	45.36	48.32	74.00	-25.68	peak
6	9648.000	9.41	37.69	38.51	43.28	51.87	74.00	-22.13	peak



Mode:a; Polarization:Vertical; Modulation:802.11b; bandwidth:20MHz; Channel:Low




Site : chamber
Condition: 3m VERTICAL
Job No : 03232CR/03233CR/03234CR
Mode : 2412 TX SE
Note : 2.4G WIFI 11B

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1687.347	3.27	26.62	40.62	46.72	35.99	74.00	-38.01	peak
2	4430.628	6.59	33.48	42.50	47.97	45.54	74.00	-28.46	peak
3	4824.000	6.86	34.00	42.78	47.07	45.15	74.00	-28.85	peak
4	6659.763	8.21	35.70	41.86	47.69	49.74	74.00	-24.26	peak
5	7236.000	8.43	36.09	41.56	45.90	48.86	74.00	-25.14	peak
6	9648.000	9.41	37.69	38.51	43.06	51.65	74.00	-22.35	peak



Mode:a; Polarization:Horizontal; Modulation:802.11b; bandwidth:20MHz; Channel:middle




Site : chamber
Condition: 3m HORIZONTAL
Job No : 03232CR/03233CR/03234CR
Mode : 2437 TX SE
Note : 2.4G WIFI 11B

	Freq	Cable Loss	Ant Factor	Preamplifier Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1672.779	3.21	26.56	40.62	46.26	35.41	74.00	-38.59	peak
2	4392.376	6.66	33.42	42.47	47.54	45.15	74.00	-28.85	peak
3	4874.000	7.01	34.05	42.82	45.62	43.86	74.00	-30.14	peak
4	6602.265	8.00	35.66	41.89	47.30	49.07	74.00	-24.93	peak
5	7311.000	8.38	36.15	41.53	45.10	48.10	74.00	-25.90	peak
6	9748.000	9.41	37.75	38.37	40.23	49.02	74.00	-24.98	peak



Mode:a; Polarization:Vertical; Modulation:802.11b; bandwidth:20MHz; Channel:middle




Site : chamber
Condition: 3m VERTICAL
Job No : 03232CR/03233CR/03234CR
Mode : 2437 TX SE
Note : 2.4G WIFI 11B

	Freq	Cable Loss	Ant Factor	Preamplifier Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1697.129	3.30	26.66	40.63	44.94	34.27	74.00	-39.73	peak
2	4367.058	6.56	33.37	42.45	47.05	44.53	74.00	-29.47	peak
3	4874.000	7.01	34.05	42.82	46.13	44.37	74.00	-29.63	peak
4	6717.762	8.28	35.73	41.83	47.34	49.52	74.00	-24.48	peak
5	7311.000	8.38	36.15	41.53	44.97	47.97	74.00	-26.03	peak
6	9748.000	9.41	37.75	38.37	40.81	49.60	74.00	-24.40	peak



Mode:a; Polarization:Horizontal; Modulation:802.11b; bandwidth:20MHz; Channel:High




Site : chamber
Condition: 3m HORIZONTAL
Job No : 03232CR/03233CR/03234CR
Mode : 2462 TX SE
Note : 2.4G WIFI 11B

	Freq	Cable Loss	Ant Factor	Preamplifier Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1672.779	3.21	26.56	40.62	46.19	35.34	74.00	-38.66	peak
2	4354.454	6.51	33.35	42.44	47.73	45.15	74.00	-28.85	peak
3	4924.000	7.06	34.11	42.85	44.99	43.31	74.00	-30.69	peak
4	6640.542	8.14	35.69	41.87	46.03	47.99	74.00	-26.01	peak
5	7386.000	8.21	36.21	41.49	45.26	48.19	74.00	-25.81	peak
6	9848.000	9.02	37.81	38.22	41.75	50.36	74.00	-23.64	peak



Mode:a; Polarization:Vertical; Modulation:802.11b; bandwidth:20MHz; Channel:High




Site : chamber
Condition: 3m VERTICAL
Job No : 03232CR/03233CR/03234CR
Mode : 2462 TX SE
Note : 2.4G WIFI 11B

	Freq	Cable Loss	Ant Factor	Preamplifier Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1677.621	3.23	26.58	40.62	45.47	34.66	74.00	-39.34	peak
2	4456.315	6.51	33.53	42.52	47.10	44.62	74.00	-29.38	peak
3	4924.000	7.06	34.11	42.85	45.72	44.04	74.00	-29.96	peak
4	6564.209	7.79	35.64	41.92	47.54	49.05	74.00	-24.95	peak
5	7386.000	8.21	36.21	41.49	44.57	47.50	74.00	-26.50	peak
6	9848.000	9.02	37.81	38.22	40.36	48.97	74.00	-25.03	peak



Mode:a; Polarization:Horizontal; Modulation:802.11g; bandwidth:20MHz; Channel:Low




Site : chamber
Condition: 3m HORIZONTAL
Job No : 03232CR/03233CR/03234CR
Mode : 2412 TX SE
Note : 2.4G WIFI 11G

	Freq	Cable Loss	Ant Factor	Preamplifier Factor	Read Level	Level	Limit	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1256.512	2.79	24.84	40.33	47.84	35.14	74.00	-38.86	peak
2	4392.376	6.66	33.42	42.47	46.21	43.82	74.00	-30.18	peak
3	4824.000	6.86	34.00	42.78	46.27	44.35	74.00	-29.65	peak
4	6470.026	7.50	35.57	41.97	46.90	48.00	74.00	-26.00	peak
5	7236.000	8.43	36.09	41.56	44.43	47.39	74.00	-26.61	peak
6	9648.000	9.41	37.69	38.51	41.31	49.90	74.00	-24.10	peak



Mode:a; Polarization:Vertical; Modulation:802.11g; bandwidth:20MHz; Channel:Low




Site : chamber
Condition: 3m VERTICAL
Job No : 03232CR/03233CR/03234CR
Mode : 2412 TX SE
Note : 2.4G WIFI 11G

	Freq	Cable Loss	Ant Factor	Preamplifier Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1682.477	3.25	26.60	40.62	45.97	35.20	74.00	-38.80	peak
2	4405.090	6.67	33.44	42.48	46.92	44.55	74.00	-29.45	peak
3	4824.000	6.86	34.00	42.78	45.07	43.15	74.00	-30.85	peak
4	6451.353	7.54	35.55	41.98	47.82	48.93	74.00	-25.07	peak
5	7236.000	8.43	36.09	41.56	44.12	47.08	74.00	-26.92	peak
6	9648.000	9.41	37.69	38.51	40.69	49.28	74.00	-24.72	peak



Mode:a; Polarization:Horizontal; Modulation:802.11g; bandwidth:20MHz; Channel:middle




Site : chamber
Condition: 3m HORIZONTAL
Job No : 03232CR/03233CR/03234CR
Mode : 2437 TX SE
Note : 2.4G WIFI 11G

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1697.129	3.30	26.66	40.63	45.63	34.96	74.00	-39.04	peak
2	4405.090	6.67	33.44	42.48	47.76	45.39	74.00	-28.61	peak
3	4874.000	7.01	34.05	42.82	45.31	43.55	74.00	-30.45	peak
4	6488.754	7.46	35.59	41.96	47.79	48.88	74.00	-25.12	peak
5	7311.000	8.38	36.15	41.53	44.01	47.01	74.00	-26.99	peak
6	9748.000	9.41	37.75	38.37	41.70	50.49	74.00	-23.51	peak



Mode:a; Polarization:Vertical; Modulation:802.11g; bandwidth:20MHz; Channel:middle




Site : chamber
Condition: 3m VERTICAL
Job No : 03232CR/03233CR/03234CR
Mode : 2437 TX SE
Note : 2.4G WIFI 11G

	Freq	Cable Loss	Ant Factor	Preamplifier Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1702.042	3.30	26.68	40.63	45.28	34.63	74.00	-39.37	peak
2	4230.396	6.18	33.13	42.34	47.34	44.31	74.00	-29.69	peak
3	4874.000	7.01	34.05	42.82	46.59	44.83	74.00	-29.17	peak
4	6640.542	8.14	35.69	41.87	45.72	47.68	74.00	-26.32	peak
5	7311.000	8.38	36.15	41.53	45.31	48.31	74.00	-25.69	peak
6	9748.000	9.41	37.75	38.37	40.30	49.09	74.00	-24.91	peak



Mode:a; Polarization:Horizontal; Modulation:802.11g; bandwidth:20MHz; Channel:High




Site : chamber
Condition: 3m HORIZONTAL
Job No : 03232CR/03233CR/03234CR
Mode : 2462 TX SE
Note : 2.4G WIFI 11G

	Freq	Cable Loss	Ant Factor	Preamplifier Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1682.477	3.25	26.60	40.62	44.96	34.19	74.00	-39.81	peak
2	4443.453	6.55	33.50	42.51	47.27	44.81	74.00	-29.19	peak
3	4924.000	7.06	34.11	42.85	45.70	44.02	74.00	-29.98	peak
4	6776.265	8.07	35.77	41.80	45.80	47.84	74.00	-26.16	peak
5	7386.000	8.21	36.21	41.49	44.42	47.35	74.00	-26.65	peak
6	9848.000	9.02	37.81	38.22	42.37	50.98	74.00	-23.02	peak



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.
Attention: To check the authenticity of testing / inspection report and certificate, please contact us at telephone: (86-755) 83071443, or email: CN.Doccheck@sgs.com

Mode:a; Polarization:Vertical; Modulation:802.11g; bandwidth:20MHz; Channel:High




Site : chamber
Condition: 3m VERTICAL
Job No : 03232CR/03233CR/03234CR
Mode : 2462 TX SE
Note : 2.4G WIFI 11G

	Freq	Cable Loss	Ant Factor	Preamplifier Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1592.571	2.95	26.22	40.57	46.37	34.97	74.00	-39.03	peak
2	4304.400	6.32	33.26	42.40	47.34	44.52	74.00	-29.48	peak
3	4924.000	7.06	34.11	42.85	45.80	44.12	74.00	-29.88	peak
4	6395.654	7.64	35.50	42.01	47.37	48.50	74.00	-25.50	peak
5	7386.000	8.21	36.21	41.49	44.48	47.41	74.00	-26.59	peak
6	9848.000	9.02	37.81	38.22	42.61	51.22	74.00	-22.78	peak



Mode:a; Polarization:Horizontal; Modulation:802.11n; bandwidth:20MHz; Channel:Low




Site : chamber
Condition: 3m HORIZONTAL
Job No : 03232CR/03233CR/03234CR
Mode : 2412 TX SE
Note : 2.4G WIFI 11N20

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1682.477	3.25	26.60	40.62	45.36	34.59	74.00	-39.41	peak
2	4379.699	6.61	33.39	42.46	46.76	44.30	74.00	-29.70	peak
3	4824.000	6.86	34.00	42.78	45.05	43.13	74.00	-30.87	peak
4	6995.172	7.81	35.90	41.69	46.59	48.61	74.00	-25.39	peak
5	7236.000	8.43	36.09	41.56	43.94	46.90	74.00	-27.10	peak
6	9648.000	9.41	37.69	38.51	40.95	49.54	74.00	-24.46	peak



Mode:a; Polarization:Vertical; Modulation:802.11n; bandwidth:20MHz; Channel:Low




Site : chamber
Condition: 3m VERTICAL
Job No : 03232CR/03233CR/03234CR
Mode : 2412 TX SE
Note : 2.4G WIFI 11N20

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1702.042	3.30	26.68	40.63	45.22	34.57	74.00	-39.43	peak
2	4469.214	6.47	33.55	42.53	47.57	45.06	74.00	-28.94	peak
3	4824.000	6.86	34.00	42.78	44.99	43.07	74.00	-30.93	peak
4	6795.879	8.00	35.78	41.79	46.21	48.20	74.00	-25.80	peak
5	7236.000	8.43	36.09	41.56	44.81	47.77	74.00	-26.23	peak
6	9648.000	9.41	37.69	38.51	41.28	49.87	74.00	-24.13	peak



Mode:a; Polarization:Horizontal; Modulation:802.11n; bandwidth:20MHz; Channel:middle




Site : chamber
Condition: 3m HORIZONTAL
Job No : 03232CR/03233CR/03234CR
Mode : 2437 TX SE
Note : 2.4G WIFI 11N20

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1677.621	3.23	26.58	40.62	46.62	35.81	74.00	-38.19	peak
2	4443.453	6.55	33.50	42.51	46.55	44.09	74.00	-29.91	peak
3	4874.000	7.01	34.05	42.82	45.83	44.07	74.00	-29.93	peak
4	6679.040	8.27	35.71	41.85	46.21	48.34	74.00	-25.66	peak
5	7311.000	8.38	36.15	41.53	45.62	48.62	74.00	-25.38	peak
6	9748.000	9.41	37.75	38.37	40.64	49.43	74.00	-24.57	peak



Mode:a; Polarization:Vertical; Modulation:802.11n; bandwidth:20MHz; Channel:middle




Site : chamber
Condition: 3m VERTICAL
Job No : 03232CR/03233CR/03234CR
Mode : 2437 TX SE
Note : 2.4G WIFI 11N20

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1677.621	3.23	26.58	40.62	45.33	34.52	74.00	-39.48	peak
2	4379.699	6.61	33.39	42.46	47.46	45.00	74.00	-29.00	peak
3	4874.000	7.01	34.05	42.82	46.34	44.58	74.00	-29.42	peak
4	6640.542	8.14	35.69	41.87	46.66	48.62	74.00	-25.38	peak
5	7311.000	8.38	36.15	41.53	46.07	49.07	74.00	-24.93	peak
6	9748.000	9.41	37.75	38.37	40.80	49.59	74.00	-24.41	peak



Mode:a; Polarization:Horizontal; Modulation:802.11n; bandwidth:20MHz; Channel:High




Site : chamber
Condition: 3m HORIZONTAL
Job No : 03232CR/03233CR/03234CR
Mode : 2462 TX SE
Note : 2.4G WIFI 11N20

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1538.281	2.97	25.98	40.53	46.66	35.08	74.00	-38.92	peak
2	4482.150	6.43	33.57	42.54	47.75	45.21	74.00	-28.79	peak
3	4924.000	7.06	34.11	42.85	47.05	45.37	74.00	-28.63	peak
4	6583.209	7.90	35.65	41.91	46.15	47.79	74.00	-26.21	peak
5	7386.000	8.21	36.21	41.49	44.73	47.66	74.00	-26.34	peak
6	9848.000	9.02	37.81	38.22	41.38	49.99	74.00	-24.01	peak



Mode:a; Polarization:Vertical; Modulation:802.11n; bandwidth:20MHz; Channel:High




Site : chamber
Condition: 3m VERTICAL
Job No : 03232CR/03233CR/03234CR
Mode : 2462 TX SE
Note : 2.4G WIFI 11N20

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1625.121	3.04	26.36	40.59	45.82	34.63	74.00	-39.37	peak
2	4379.699	6.61	33.39	42.46	46.69	44.23	74.00	-29.77	peak
3	4924.000	7.06	34.11	42.85	45.36	43.68	74.00	-30.32	peak
4	6545.263	7.68	35.63	41.93	47.44	48.82	74.00	-25.18	peak
5	7386.000	8.21	36.21	41.49	42.86	45.79	74.00	-28.21	peak
6	9848.000	9.02	37.81	38.22	40.63	49.24	74.00	-24.76	peak



Mode:a; Polarization:Horizontal; Modulation:802.11n; bandwidth:40MHz; Channel:Low




Site : chamber
Condition: 3m HORIZONTAL
Job No : 03232CR/03233CR/03234CR
Mode : 2422 TX SE
Note : 2.4G WIFI 11N40

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1592.571	2.95	26.22	40.57	46.29	34.89	74.00	-39.11	peak
2	4230.396	6.18	33.13	42.34	47.61	44.58	74.00	-29.42	peak
3	4844.000	6.92	34.02	42.79	45.48	43.63	74.00	-30.37	peak
4	6488.754	7.46	35.59	41.96	47.05	48.14	74.00	-25.86	peak
5	7266.000	8.42	36.12	41.55	45.42	48.41	74.00	-25.59	peak
6	9688.000	9.66	37.71	38.45	41.77	50.69	74.00	-23.31	peak



Mode:a; Polarization:Vertical; Modulation:802.11n; bandwidth:40MHz; Channel:Low




Site : chamber
Condition: 3m VERTICAL
Job No : 03232CR/03233CR/03234CR
Mode : 2422 TX SE
Note : 2.4G WIFI 11N40

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1677.621	3.23	26.58	40.62	45.68	34.87	74.00	-39.13	peak
2	4354.454	6.51	33.35	42.44	46.54	43.96	74.00	-30.04	peak
3	4844.000	6.92	34.02	42.79	45.91	44.06	74.00	-29.94	peak
4	6894.806	7.84	35.84	41.74	46.60	48.54	74.00	-25.46	peak
5	7266.000	8.42	36.12	41.55	44.27	47.26	74.00	-26.74	peak
6	9688.000	9.66	37.71	38.45	42.27	51.19	74.00	-22.81	peak



Mode:a; Polarization:Horizontal; Modulation:802.11n; bandwidth:40MHz; Channel:middle




Site : chamber
Condition: 3m HORIZONTAL
Job No : 03232CR/03233CR/03234CR
Mode : 2437 TX SE
Note : 2.4G WIFI 11N40

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1583.392	2.96	26.18	40.56	46.34	34.92	74.00	-39.08	peak
2	4316.859	6.37	33.28	42.41	47.30	44.54	74.00	-29.46	peak
3	4874.000	7.01	34.05	42.82	45.62	43.86	74.00	-30.14	peak
4	6855.063	7.90	35.82	41.76	46.05	48.01	74.00	-25.99	peak
5	7311.000	8.38	36.15	41.53	46.56	49.56	74.00	-24.44	peak
6	9748.000	9.41	37.75	38.37	42.30	51.09	74.00	-22.91	peak



Mode:a; Polarization:Vertical; Modulation:802.11n; bandwidth:40MHz; Channel:middle




Site : chamber
Condition: 3m VERTICAL
Job No : 03232CR/03233CR/03234CR
Mode : 2437 TX SE
Note : 2.4G WIFI 11N40

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1697.129	3.30	26.66	40.63	45.65	34.98	74.00	-39.02	peak
2	4354.454	6.51	33.35	42.44	47.40	44.82	74.00	-29.18	peak
3	4874.000	7.01	34.05	42.82	45.62	43.86	74.00	-30.14	peak
4	6855.063	7.90	35.82	41.76	46.17	48.13	74.00	-25.87	peak
5	7311.000	8.38	36.15	41.53	45.56	48.56	74.00	-25.44	peak
6	9748.000	9.41	37.75	38.37	41.34	50.13	74.00	-23.87	peak



Mode:a; Polarization:Horizontal; Modulation:802.11n; bandwidth:40MHz; Channel:High




Site : chamber
Condition: 3m HORIZONTAL
Job No : 03232CR/03233CR/03234CR
Mode : 2452 TX SE
Note : 2.4G WIFI 11N40

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1677.621	3.23	26.58	40.62	44.92	34.11	74.00	-39.89	peak
2	4469.214	6.47	33.55	42.53	48.34	45.83	74.00	-28.17	peak
3	4904.000	7.08	34.09	42.84	46.04	44.37	74.00	-29.63	peak
4	6621.375	8.07	35.67	41.88	47.38	49.24	74.00	-24.76	peak
5	7356.000	8.28	36.19	41.50	45.11	48.08	74.00	-25.92	peak
6	9808.000	9.05	37.79	38.28	41.44	50.00	74.00	-24.00	peak



Mode:a; Polarization:Vertical; Modulation:802.11n; bandwidth:40MHz; Channel:High



Site : chamber
Condition: 3m VERTICAL
Job No : 03232CR/03233CR/03234CR
Mode : 2452 TX SE
Note : 2.4G WIFI 11N40

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1663.137	3.18	26.52	40.61	45.61	34.70	74.00	-39.30	peak
2	4304.400	6.32	33.26	42.40	46.69	43.87	74.00	-30.13	peak
3	4904.000	7.08	34.09	42.84	46.03	44.36	74.00	-29.64	peak
4	6395.654	7.64	35.50	42.01	48.07	49.20	74.00	-24.80	peak
5	7356.000	8.28	36.19	41.50	46.18	49.15	74.00	-24.85	peak
6	9808.000	9.05	37.79	38.28	41.80	50.36	74.00	-23.64	peak



8 Photographs

8.1 Test Setup

Please refer to setup photos.

8.2 EUT Constructional Details (EUT Photos)


Please Refer to external and internal photos for details.


9 Appendix



9.1 Appendix 15.247


1.6dB Bandwidth



Test Mode	Test	Ant	EBW[MHz]	Limit[MHz]	Verdict
11B	2412	Ant1	9.630	>=0.5	PASS
11B	2412	Ant2	9.600	>=0.5	PASS
11B	2437	Ant1	9.690	>=0.5	PASS
11B	2437	Ant2	10.110	>=0.5	PASS
11B	2462	Ant1	9.870	>=0.5	PASS
11B	2462	Ant2	9.870	>=0.5	PASS
11G	2412	Ant1	15.960	>=0.5	PASS
11G	2412	Ant2	15.990	>=0.5	PASS
11G	2437	Ant1	15.810	>=0.5	PASS
11G	2437	Ant2	15.810	>=0.5	PASS
11G	2462	Ant1	15.780	>=0.5	PASS
11G	2462	Ant2	16.110	>=0.5	PASS
11N20SISO	2412	Ant1	16.380	>=0.5	PASS
11N20SISO	2412	Ant2	16.380	>=0.5	PASS
11N20SISO	2437	Ant1	16.410	>=0.5	PASS
11N20SISO	2437	Ant2	16.770	>=0.5	PASS
11N20SISO	2462	Ant1	17.220	>=0.5	PASS
11N20SISO	2462	Ant2	16.410	>=0.5	PASS
11N40SISO	2422	Ant1	35.280	>=0.5	PASS
11N40SISO	2422	Ant2	35.280	>=0.5	PASS
11N40SISO	2437	Ant1	35.580	>=0.5	PASS
11N40SISO	2437	Ant2	35.820	>=0.5	PASS
11N40SISO	2452	Ant1	35.220	>=0.5	PASS
11N40SISO	2452	Ant2	35.220	>=0.5	PASS




























Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained herein reflects the Company's findings at the time of its intervention only and within the limits of its Client's instructions, if any. The Company's sole responsibility is to its Client and the document is not a commercial paper and is not a transaction document. The Company's obligations under the transaction documents are not affected by the document and the document cannot be produced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only. Attention is drawn to the fact that the test report and certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com.

中国·深圳·科技园中区M-10栋十楼一单元 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sqs.china@sqs.com




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of its Client's instructions, if any. The Company's sole responsibility is limited to the content of the document and is not a general guarantor of the information contained therein, nor of their legal obligations under the transaction documents. The document can be produced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only. (Attention: if checked for a certificate of testing/inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com).


中国·深圳·科技园中区M-10栋十楼一单元 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sqs.china@sqs.com



6dB Bandwidth_11N40SISO_2452_Ant1



6dB Bandwidth_11N40SISO_2452_Ant2



3. Maximum average conducted output power

Test Mode	Test Channel	Ant	Power[dBm]	Limit[dBm]	Verdict
11B	2412	Ant1	13.54	<30	PASS
11B	2412	Ant2	13.17	<30	PASS
11B	2417	Ant1	16.51	<30	PASS
11B	2417	Ant2	16.08	<30	PASS
11B	2437	Ant1	19.05	<30	PASS
11B	2437	Ant2	19.41	<30	PASS
11B	2457	Ant1	16.92	<30	PASS
11B	2457	Ant2	16.54	<30	PASS
11B	2462	Ant1	15.25	<30	PASS
11B	2462	Ant2	15.75	<30	PASS
11G	2412	Ant1	13.57	<30	PASS
11G	2412	Ant2	13.94	<30	PASS
11G	2417	Ant1	16.2	<30	PASS
11G	2417	Ant2	16.1	<30	PASS
11G	2437	Ant1	20.16	<30	PASS
11G	2437	Ant2	19.92	<30	PASS
11G	2457	Ant1	16.89	<30	PASS
11G	2457	Ant2	16.63	<30	PASS
11G	2462	Ant1	14.72	<30	PASS
11G	2462	Ant2	14.81	<30	PASS
11N20SISO	2412	Ant1	13.58	<30	PASS
11N20SISO	2412	Ant2	13.45	<30	PASS
11N20SISO	2417	Ant1	16.02	<30	PASS
11N20SISO	2417	Ant2	15.97	<30	PASS
11N20SISO	2437	Ant1	20.28	<30	PASS
11N20SISO	2437	Ant2	19.6	<30	PASS
11N20SISO	2457	Ant1	16.71	<30	PASS
11N20SISO	2457	Ant2	16.48	<30	PASS
11N20SISO	2462	Ant1	14.3	<30	PASS



11N20SISO	2462	Ant2	14.68	<30	PASS
11N40SISO	2422	Ant1	11.8	<30	PASS
11N40SISO	2422	Ant2	11.48	<30	PASS
11N40SISO	2427	Ant1	12.92	<30	PASS
11N40SISO	2427	Ant2	12.71	<30	PASS
11N40SISO	2437	Ant1	19.91	<30	PASS
11N40SISO	2437	Ant2	19.32	<30	PASS
11N40SISO	2447	Ant1	14.74	<30	PASS
11N40SISO	2447	Ant2	14.56	<30	PASS
11N40SISO	2452	Ant1	13.75	<30	PASS
11N40SISO	2452	Ant2	13.29	<30	PASS

Test Mode	Test Channel	Ant	Directional gain	Power[dBm]	Limit[dBm]	Verdict
11B	2412	Ant1+Ant2	7.51	16.37	<28.49	PASS
11B	2417	Ant1+Ant2	7.51	19.31	<28.49	PASS
11B	2437	Ant1+Ant2	7.51	22.24	<28.49	PASS
11B	2457	Ant1+Ant2	7.51	19.74	<28.49	PASS
11B	2462	Ant1+Ant2	7.51	18.52	<28.49	PASS
11G	2412	Ant1+Ant2	7.51	16.77	<28.49	PASS
11G	2417	Ant1+Ant2	7.51	19.16	<28.49	PASS
11G	2437	Ant1+Ant2	7.51	23.05	<28.49	PASS
11G	2457	Ant1+Ant2	7.51	19.77	<28.49	PASS
11G	2462	Ant1+Ant2	7.51	17.78	<28.49	PASS
11N20SISO	2412	Ant1+Ant2	7.51	16.53	<28.49	PASS
11N20SISO	2417	Ant1+Ant2	7.51	19.01	<28.49	PASS
11N20SISO	2437	Ant1+Ant2	7.51	22.96	<28.49	PASS
11N20SISO	2457	Ant1+Ant2	7.51	19.61	<28.49	PASS
11N20SISO	2462	Ant1+Ant2	7.51	17.50	<28.49	PASS
11N40SISO	2422	Ant1+Ant2	7.51	14.65	<28.49	PASS
11N40SISO	2427	Ant1+Ant2	7.51	15.83	<28.49	PASS
11N40SISO	2437	Ant1+Ant2	7.51	22.64	<28.49	PASS
11N40SISO	2447	Ant1+Ant2	7.51	17.66	<28.49	PASS



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing/inspection report & certificate, please contact us at telephone: (86-755) 83071443, or email: CN.Doecheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn
中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com



11N40SISO	2452	Ant1+Ant2	7.51	16.54	<28.49	PASS
-----------	------	-----------	------	-------	--------	------

Remark: for MIMO data, power limit=30-(7.51-6)=28.49dBm



4.Maximum Peak power spectral density

Test Mode	Test Channel	Ant	PSD[dBm/3kHz]	Limit[dBm/3kHz]	Verdict
11B	2412	Ant1	-11.81	<8.00	PASS
11B	2412	Ant2	-12.11	<8.00	PASS
11B	2437	Ant1	-6.06	<8.00	PASS
11B	2437	Ant2	-6.03	<8.00	PASS
11B	2462	Ant1	-10.14	<8.00	PASS
11B	2462	Ant2	-9.43	<8.00	PASS
11G	2412	Ant1	-11.48	<8.00	PASS
11G	2412	Ant2	-11.99	<8.00	PASS
11G	2437	Ant1	-5.22	<8.00	PASS
11G	2437	Ant2	-4.48	<8.00	PASS
11G	2462	Ant1	-10.59	<8.00	PASS
11G	2462	Ant2	-9.47	<8.00	PASS
11N20SISO	2412	Ant1	-11.46	<8.00	PASS
11N20SISO	2412	Ant2	-11.75	<8.00	PASS
11N20SISO	2437	Ant1	-2.71	<8.00	PASS
11N20SISO	2437	Ant2	-4.93	<8.00	PASS
11N20SISO	2462	Ant1	-9.39	<8.00	PASS
11N20SISO	2462	Ant2	-9.62	<8.00	PASS
11N40SISO	2422	Ant1	-13.38	<8.00	PASS
11N40SISO	2422	Ant2	-13.28	<8.00	PASS
11N40SISO	2437	Ant1	-4.3	<8.00	PASS
11N40SISO	2437	Ant2	-4.55	<8.00	PASS
11N40SISO	2452	Ant1	-11.2	<8.00	PASS
11N40SISO	2452	Ant2	-15.4	<8.00	PASS

Test Mode	Test Channel	Ant	PSD[dBm/3kHz]	Limit[dBm/3kHz]	Verdict
11B	2412	Ant1+Ant2	-8.95	<8.00	PASS
11B	2437	Ant1+Ant2	-3.03	<8.00	PASS
11B	2462	Ant1+Ant2	-6.76	<8.00	PASS



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 83071443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch - 科技园中区M-10栋一号楼

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·深圳·科技园中区M-10栋一号楼 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

11G	2412	Ant1+Ant2	-8.72	<8.00	PASS
11G	2437	Ant1+Ant2	-1.82	<8.00	PASS
11G	2462	Ant1+Ant2	-6.98	<8.00	PASS
11N20SISO	2412	Ant1+Ant2	-8.59	<8.00	PASS
11N20SISO	2437	Ant1+Ant2	-0.67	<8.00	PASS
11N20SISO	2462	Ant1+Ant2	-6.49	<8.00	PASS
11N40SISO	2422	Ant1+Ant2	-10.32	<8.00	PASS
11N40SISO	2437	Ant1+Ant2	-1.41	<8.00	PASS
11N40SISO	2452	Ant1+Ant2	-9.80	<8.00	PASS




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 83071443, or email: CN.Doccheck@sgs.com


SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch (China) (SGS) Laboratory

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn
中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com


Maximum Peak power spectral density_11B_2412_Ant1




Maximum Peak power spectral density_11B_2412_Ant2



Maximum Peak power spectral density_11B_2437_Ant1




Maximum Peak power spectral density_11B_2437_Ant2




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Maximum Peak power spectral density_11B_2462_Ant1




Maximum Peak power spectral density_11B_2462_Ant2




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Maximum Peak power spectral density_11G_2412_Ant1




Maximum Peak power spectral density_11G_2412_Ant2




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report and certificate, please contact us at telephone: (86-755) 83071443, or email: CN.Doccheck@sgs.com


Maximum Peak power spectral density_11G_2437_Ant1




Maximum Peak power spectral density_11G_2437_Ant2



Maximum Peak power spectral density_11G_2462_Ant1




Maximum Peak power spectral density_11G_2462_Ant2




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report and certificate, please contact us at telephone: (86-755) 83071443, or email: CN.Doccheck@sgs.com


Maximum Peak power spectral density_11N20SISO_2412_Ant1




Maximum Peak power spectral density_11N20SISO_2412_Ant2



Maximum Peak power spectral density_11N20SISO_2437_Ant1




Maximum Peak power spectral density_11N20SISO_2437_Ant2




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.


Maximum Peak power spectral density_11N20SISO_2462_Ant1




Maximum Peak power spectral density_11N20SISO_2462_Ant2




Maximum Peak power spectral density_11N40SISO_2422_Ant1




Maximum Peak power spectral density_11N40SISO_2422_Ant2



Maximum Peak power spectral density_11N40SISO_2437_Ant1




Maximum Peak power spectral density_11N40SISO_2437_Ant2




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 83071443, or email: CN.Doccheck@sgs.com

Maximum Peak power spectral density_11N40SISO_2452_Ant1




Maximum Peak power spectral density_11N40SISO_2452_Ant2




5.Band-edge for RF Conducted Emissions

Test Mode	Test Channel	Ant	Carrier Power[dBm]	Max. Spurious Level [dBm]	Limit [dBm]	Verdict
11B	2412	Ant1	3.320	-52.625	<-26.68	PASS
11B	2412	Ant2	3.150	-52.978	<-26.85	PASS
11B	2462	Ant1	4.990	-51.161	<-25.01	PASS
11B	2462	Ant2	5.250	-52.485	<-24.75	PASS
11G	2412	Ant1	4.240	-48.997	<-25.76	PASS
11G	2412	Ant2	4.190	-47.777	<-25.81	PASS
11G	2462	Ant1	5.520	-48.652	<-24.48	PASS
11G	2462	Ant2	5.830	-47.377	<-24.17	PASS
11N20SISO	2412	Ant1	4.400	-48.070	<-25.6	PASS
11N20SISO	2412	Ant2	4.030	-47.090	<-25.97	PASS
11N20SISO	2462	Ant1	5.780	-47.656	<-24.22	PASS
11N20SISO	2462	Ant2	5.830	-46.262	<-24.17	PASS
11N40SISO	2422	Ant1	1.940	-41.019	<-28.06	PASS
11N40SISO	2422	Ant2	1.020	-41.157	<-28.98	PASS
11N40SISO	2452	Ant1	4.770	-38.793	<-25.23	PASS
11N40SISO	2452	Ant2	0.360	-45.005	<-29.64	PASS

Band-edge for RF Conducted Emissions_11B_2412_Ant1




Band-edge for RF Conducted Emissions_11B_2412_Ant2




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.



Attention: To check the authenticity of testing / inspection report and certificate, please contact us at telephone: (86-755) 83071443, or email: CN.Doccheck@sgs.com

Band-edge for RF Conducted Emissions_11B_2462_Ant1




Band-edge for RF Conducted Emissions_11B_2462_Ant2







Band-edge for RF Conducted Emissions_11G_2462_Ant1




Band-edge for RF Conducted Emissions_11G_2462_Ant2




Band-edge for RF Conducted Emissions_11N20SISO_2412_Ant1




Band-edge for RF Conducted Emissions_11N20SISO_2412_Ant2





Band-edge for RF Conducted Emissions_11N20SISO_2462_Ant1





Band-edge for RF Conducted Emissions_11N20SISO_2462_Ant2





Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained herein reflects the Company's findings at the time of its intervention only and within the limits of its Client's instructions, if any. The Company's sole responsibility is to its Client and the document is not a commercial paper and is not a transaction document. The Company's obligations under the transaction documents are not affected by the document and the document cannot be produced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only. (Attention: if checked for testing, inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com).

中国·深圳·科技园中区M-10栋十楼一单元 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sqs.china@sqs.com



6.RF Conducted Spurious Emissions

Test Mode	Test Channel	StartFre [MHz]	StopFre [MHz]	RBW [kHz]	VBW [kHz]	Pref[dBm]	Max. Level [dBm]	Limit [dBm]	Verdict
11B	2412	30	10000	100	300	3.23	-45.860	<-26.77	PASS
11B	2412	10000	25000	100	300	3.23	-53.240	<-26.77	PASS
11B	2412	30	10000	100	300	2.95	-46.320	<-27.05	PASS
11B	2412	10000	25000	100	300	2.95	-52.580	<-27.05	PASS
11B	2437	30	10000	100	300	8.81	-35.840	<-21.19	PASS
11B	2437	10000	25000	100	300	8.81	-52.900	<-21.19	PASS
11B	2437	30	10000	100	300	8.73	-35.730	<-21.27	PASS
11B	2437	10000	25000	100	300	8.73	-53.780	<-21.27	PASS
11B	2462	30	10000	100	300	4.7	-43.320	<-25.3	PASS
11B	2462	10000	25000	100	300	4.7	-52.590	<-25.3	PASS
11B	2462	30	10000	100	300	5.23	-42.500	<-24.77	PASS
11B	2462	10000	25000	100	300	5.23	-53.720	<-24.77	PASS
11G	2412	30	10000	100	300	4.02	-48.550	<-25.98	PASS
11G	2412	10000	25000	100	300	4.02	-53.640	<-25.98	PASS
11G	2412	30	10000	100	300	3.92	-51.460	<-26.08	PASS
11G	2412	10000	25000	100	300	3.92	-52.290	<-26.08	PASS
11G	2437	30	10000	100	300	11.85	-38.840	<-18.15	PASS
11G	2437	10000	25000	100	300	11.85	-52.780	<-18.15	PASS
11G	2437	30	10000	100	300	10.88	-42.740	<-19.12	PASS
11G	2437	10000	25000	100	300	10.88	-53.050	<-19.12	PASS
11G	2462	30	10000	100	300	5.34	-50.910	<-24.66	PASS
11G	2462	10000	25000	100	300	5.34	-53.210	<-24.66	PASS
11G	2462	30	10000	100	300	5.34	-49.160	<-24.66	PASS
11G	2462	10000	25000	100	300	5.34	-52.710	<-24.66	PASS
11N20SISO	2412	30	10000	100	300	3.71	-51.980	<-26.29	PASS
11N20SISO	2412	10000	25000	100	300	3.71	-52.420	<-26.29	PASS
11N20SISO	2412	30	10000	100	300	3.97	-50.550	<-26.03	PASS
11N20SISO	2412	10000	25000	100	300	3.97	-52.980	<-26.03	PASS



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing/inspection report and certificate, please contact us at telephone: (86-755) 83071443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

11N20SISO	2437	30	10000	100	300	11.43	-39.830	<-18.57	PASS
11N20SISO	2437	10000	25000	100	300	11.43	-53.300	<-18.57	PASS
11N20SISO	2437	30	10000	100	300	10.84	-41.890	<-19.16	PASS
11N20SISO	2437	10000	25000	100	300	10.84	-53.310	<-19.16	PASS
11N20SISO	2462	30	10000	100	300	5.59	-50.260	<-24.41	PASS
11N20SISO	2462	10000	25000	100	300	5.59	-53.170	<-24.41	PASS
11N20SISO	2462	30	10000	100	300	5.61	-50.580	<-24.39	PASS
11N20SISO	2462	10000	25000	100	300	5.61	-52.870	<-24.39	PASS
11N40SISO	2422	30	10000	100	300	2.19	-53.300	<-27.81	PASS
11N40SISO	2422	10000	25000	100	300	2.19	-53.520	<-27.81	PASS
11N40SISO	2422	30	10000	100	300	1.33	-44.760	<-28.67	PASS
11N40SISO	2422	10000	25000	100	300	1.33	-53.340	<-28.67	PASS
11N40SISO	2437	30	10000	100	300	11.88	-40.920	<-18.12	PASS
11N40SISO	2437	10000	25000	100	300	11.88	-53.300	<-18.12	PASS
11N40SISO	2437	30	10000	100	300	10.94	-37.820	<-19.06	PASS
11N40SISO	2437	10000	25000	100	300	10.94	-52.440	<-19.06	PASS
11N40SISO	2452	30	10000	100	300	0.37	-46.760	<-29.63	PASS
11N40SISO	2452	10000	25000	100	300	0.37	-53.220	<-29.63	PASS




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 83071443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch (SGS-CSTC) Laboratory

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn
中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com




CSE_2



Ref 20 dBm *RBW 100 kHz Marker 1 [T1]
*Att 20 dB *VBW 300 kHz -53.24 dBm
SWT 1.5 s 22.376875000 GHz

1 PK
VIEW




RF Conducted Spurious Emissions_11B_2412_Ant2

Pref




Ref 20 dBm *RBW 100 kHz Marker 1 [T1]
*Att 20 dB *VBW 300 kHz 2.95 dBm
SWT 10 ms 2.412950000 GHz

1 PK
VIEW





Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.
Attention: To check the authenticity of testing / inspection report and certificate, please contact us at telephone: (86-755) 83071443, or email: CN.Doccheck@sgs.com


CSE_1




CSE_2









RF Conducted Spurious Emissions_11B_2437_Ant2





CSE_1




CSE_2









RF Conducted Spurious Emissions_11B_2462_Ant2




CSE_1



CSE_2





Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.


Attention: To check the authenticity of testing / inspection report and certificate, please contact us at telephone: (86-755) 83071443, or email: CN.Doccheck@sgs.com

CSE_2



Ref 20 dBm *Att 20 dB RBW 100 kHz Marker 1 [T1]
VBW 300 kHz -53.64 dBm
SWT 1.5 s 18.16750000 GHz

1 PK
VIEW




RF Conducted Spurious Emissions_11G_2412_Ant2

Pref




Ref 20 dBm *Att 20 dB RBW 100 kHz Marker 1 [T1]
VBW 300 kHz 3.92 dBm
SWT 10 ms 2.414450000 GHz


1 PK
VIEW



CSE_1




CSE_2




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report and certificate, please contact us at telephone: (86-755) 83071443, or email: CN.Doccheck@sgs.com




CSE_2



RF Conducted Spurious Emissions_11G_2437_Ant2


Pref




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.


Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 83071443, or email: CN.Doccheck@sgs.com

CSE_1




CSE_2






CSE_2




RF Conducted Spurious Emissions_11G_2462_Ant2

Pref




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

CSE_1




CSE_2




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 83071443, or email: CN.Doccheck@sgs.com




CSE_2




RF Conducted Spurious Emissions_11N20SISO_2412_Ant2

Pref





Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

CSE_1



CSE_2






CSE_2



Ref 20 dBm *Att 20 dB RBW 100 kHz Marker 1 [T1] -53.30 dBm
VBW 300 kHz SWT 1.5 s 22.81750000 GHz




RF Conducted Spurious Emissions_11N20ISO_2437_Ant2

Pref




Ref 20 dBm *Att 20 dB RBW 100 kHz Marker 1 [T1] 10.84 dBm
VBW 300 kHz SWT 10 ms 2.44200000 GHz





Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

CSE_1



CSE_2






CSE_2



Ref 20 dBm *Att 20 dB *RBW 100 kHz Marker 1 [T1] -53.17 dBm
*VBW 300 kHz 21.210625000 GHz
SWT 1.5 s




RF Conducted Spurious Emissions_11N20SISO_2462_Ant2

Pref




Ref 20 dBm *Att 20 dB *RBW 100 kHz Marker 1 [T1] 5.61 dBm
*VBW 300 kHz 2.457000000 GHz
SWT 10 ms





Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.
Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 83071443, or email: CN.Doccheck@sgs.com

CSE_1



CSE_2





Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed on the reverse, available on request or available at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a dispute from their own responsibility in settling the dispute. This document is not to be used for any other purpose, in whole or in part, except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443.


SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch (Testing Center EEC Laboratory)

No. 1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn
 中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

CSE_2



Ref 20 dBm *Att 20 dB *RBW 100 kHz Marker 1 [T1] -53.52 dBm
*VBW 300 kHz 19.99000000 GHz
SWT 1.5 s




RF Conducted Spurious Emissions_11N40ISO_2422_Ant2

Pref




Ref 20 dBm *Att 20 dB *RBW 100 kHz Marker 1 [T1] 1.33 dBm
*VBW 300 kHz 2.41320000 GHz
SWT 10 ms





Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

CSE_1



CSE_2






CSE_2



Ref 20 dBm *Att 20 dB *RBW 100 kHz Marker 1 [T1] -53.30 dBm
*VBW 300 kHz 20.070625000 GHz
SWT 1.5 s

1 PK
VIEW




RF Conducted Spurious Emissions_11N40SISO_2437_Ant2

Pref




Ref 20 dBm *Att 20 dB *RBW 100 kHz Marker 1 [T1] 10.94 dBm
*VBW 300 kHz 2.450800000 GHz
SWT 10 ms

1 PK
VIEW




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.
Attention: To check the authenticity of testing / inspection report and certificate, please contact us at telephone: (86-755) 83071443, or email: CN.Doccheck@sgs.com

CSE_1



CSE_2




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

RF Conducted Spurious Emissions_11N40SISO_2452_Ant1

Pref




1 PK
VIEW



CSE_1




1 PK
VIEW




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.


Attention: To check the authenticity of testing / inspection report and certificate, please contact us at telephone: (86-755) 83071443, or email: CN.Doccheck@sgs.com




RF Conducted Spurious Emissions_11N40SISO_2452_Ant2



CSE_1



CSE_2



- End of the Report -

