



▪ DSS BT(BDR/EDR)

TEST REPORT

Report No: KST-FCR-140005

Applicant	Name	Bluebird Inc.
	Address	(Dogok-dong, SEI Tower 13,14) 39, Eonjuro30-gil, Gangnam-gu, Seoul, South Korea
Manufacturer	Name	Bluebird Inc.
	Address	(Dogok-dong, SEI Tower 13,14) 39, Eonjuro30-gil, Gangnam-gu, Seoul, South Korea
Equipment	Name	Handheld Mobile Computer
	Model No	BM180
	Brand	None
	FCC ID	SS4BM180M
Test Standard	FCC CFR 47, Part 15. Subpart C-15.247	
Test Date(s)	2014. 07. 28 ~ 2014. 08. 12	
Issue Date	2014. 08. 13	
Test Result	Compliance	
Note	This equipment contained the certified module for GSM850/1900, WCDMA Band II/V and not certified modules for WLAN 802.11abgn, Bluetooth 4.0, NFC.	

Supplementary Information

The device bearing the brand name and FCC ID specified above has been shown to comply with the applicable technical standards as indicated in the measurement report and was tested in accordance with measurement procedures specified in ANSI C 63.10-2009.

We attest to the accuracy of data and all measurements reported herein were performed by KOSTEC Co., Ltd. and were made under Chief Engineer's supervision. We assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

Tested by Mi Young, Lee

Approved by Gyeong Hyeon, Park

Signature

Signature

Table of Contents

1. GENERAL INFORMATION	3
1.1 Test Facility	3
1.2 Location	3
2. EQUIPMENT DESCRIPTION	4
3. SYSTEM CONFIGURATION FOR TEST	6
3.1 Characteristics of equipment.....	6
3.2 Used peripherals list.....	6
3.3 Product Modification	6
3.4 Operating Mode	6
3.5 Test Setup of EUT	6
3.6 Parameters of Test Software Setting.....	7
3.7 Table for Test condition	7
3.8 Used Test Equipment List.....	8
4. SUMMARY TEST RESULTS	10
5. MEASUREMENT RESULTS	11
5.1 Carrier Frequency Separation	11
5.2 Number of hopping frequencies	16
5.3 Time of occupancy (Dwell Time)	18
5.4 Max. Conducted peak output power	21
5.5 Band-edge Compliance of RF Conducted emissions	25
5.6 Spurious RF Conducted emissions	28
5.7 Spurious RF Radiated emissions	31
5.8 Antenna requirement	36
5.9 AC Power Conducted emissions	37

1. GENERAL INFORMATION

1.1 Test Facility

Test laboratory and address

KOSTEC Co., Ltd.

128(175-20,Annyeong-dong)406-gil sejaro, Hwaseong-si Gyeonggi-do, Korea

The open area field test site and conducted measurement facility are used for these testing. This site at was fully described in a reports submitted to the Federal Communications Commission (FCC).

The details of these reports have been found to be in complies with the requirements of Section 2.948 of the FCC Rules on November 14, 2002. The facility also complies with the radiated and conducted test site criteria set forth in ANSI C 63.10-2009.

The Federal Communications Commission (FCC) has the reports on file and KOSTEC Co., Ltd. is listed under FCC Registration No.525762. The test site has been approved by the FCC for public use and is List in the FCC Public Access Link CORES (Commission Registration System)

Registration information

KCC (Korea Communications Commission) Number : KR0041

KOLAS(Korea Laboratory Accreditation Scheme) Number : 232

FCC Registration Number(FRN) : 525762

VCCI Registration Number : R-1657 / C –1763

IC Registration Site Number : 8305A-1

1.2 Location



2. EQUIPMENT DESCRIPTION

The product specification described herein was declared by manufacturer. And refer to user's manual for the details.

Equipment Name	Handheld Mobile Computer
Model No	BM180
Usage	Handheld Mobile Computer
Serial Number	Proto type
Data connection Type	FHSS(frequency hopping spread spectrum system)
Modulation type	GSM: GMSK, 8PSK WCDMA: QPSK 802.11b: DSSS (DBPSK / DQPSK / CCK) 802.11a/g/n: OFDM (BPSK / QPSK / 16QAM / 64QAM) Bluetooth 2.1 BDR (1Mbps) : GFSK Bluetooth 2.1 EDR (2Mbps) : $\pi/4$ -DQPSK Bluetooth 2.1 EDR (3Mbps) : 8-DPSK Bluetooth 4.0 LE: GFSK NFC: ASK
Max peak output	3.15 dBm
Operated Frequency	GSM 850: 824.2 MHz - 848.8 MHz GSM1900: 1850.2 MHz - 1909.8 MHz WCDMA Band II: 1 852.4 MHz - 1 907.6 MHz WCDMA Band V: 826.4 MHz - 846.6 MHz 802.11b/g: 2 412 MHz - 2 462 MHz 802.11a: 5 180 MHz - 5 240 MHz (UNII Band I) 5 745 MHz - 5 825 MHz (UNII Band IV) 802.11n(HT20): 2 412 MHz - 2 462 MHz 5 180 MHz - 5 240 MHz (UNII Band I) 5 745 MHz - 5 825 MHz (UNII Band IV) 802.11n(HT40): 2 422 MHz - 2 452 MHz 5 190 MHz - 5 230 MHz (UNII Band I) 5 755 MHz - 5 795 MHz (UNII Band IV) Bluetooth: 2 402 MHz - 2 480 MHz NFC: 13.561 MHz
Channel Number	79 CH
Operation temperature	- 20 °C ~ + 55 °C
Power Source	AC/DC adapter Input : AC 100-240 V, 0.3 A, 50 - 60 Hz Output : DC 5 V, 1.0 A Battery : Li-ion DC 3.7 V
Antenna Description	Type : Internal PCB Antenna
FCC ID	SS4BM180M

Remark	1. Regarding to the operation frequency, the lowest, middle and highest frequency are selected to perform the test. 2. The radiation measurements are performed in X, Y, Z axis positioning. Only the worst case is shown in the report. 3. Bluetooth operation was evaluated at both 1Mb/s and 3Mb/s data rates. For $\pi/4$ QPSK its same modulation type with 8-DPSK, and based exploratory test, there is no significant difference of that two types test result, after the preliminary scan, 8-DPSK will have higher emission, so except output power, all other items final test were only performed with the worse case 8-DPSK and GFSK. 4. This report only for Bluetooth BDR(1Mbps) and EDR(2Mbps, 3Mbps) mode of EUT,for Bluetooth 4.0-LE mode and etc modes were reported in another test report 5. The above DUT's information was declared by manufacturer. Please refer to the specifications or user manual for more detailed description.
Test Mode	Mode 1: Transmit - 1Mbps (GFSK) Mode 2: Transmit - 3Mbps (8DPSK)

** it is maximum peak conducted power in only BT(BDR,EDR).

3. SYSTEM CONFIGURATION FOR TEST

3.1 Characteristics of equipment

The Equipment Under Test (EUT) contains the following capabilities:
GSM850/1900, WCDMA Band II/V, WLAN 802.11abgn, Bluetooth 4.0, NFC.

The test data contained in this report pertains only to the emissions due to the BT(BDR,EDR) transmitter of the EUT. Bluetooth chip Communication type is frequency hopping spread spectrum system(FHSS), and it support the EDR mode (Enhanced data rate), used frequency band is 2 402 MHz - 2 480 MHz.

3.2 Used peripherals list

Description	Model No.	Serial No.	Manufacture	Remark
Battery	EG-520	-	Egen	Li-ion 3.7 V
AC/DC adapter	PSAI05R-050Q CH	-	Phihong (Dongguan) Electronics Co.,Ltd	Output: 5.0 V
Bluetooth tester	TC-3000B	3000B6A0166	TESCOM CO., LTD.	Due cal date: 2015.07.14

3.3 Product Modification


N/A

3.4 Operating Mode

* All measurements were intended to emit maximum RF signal from EUT continuously.

3.5 Test Setup of EUT

The measurements were taken in continuous transmit / receive mode using the Bluetooth tester.
Communication between the device and the emulator was established by air link and conducted link.



3.6 Parameters of Test Software Setting

During testing, for channel & mode and un-mod, hopping setting is controlled using the Bluetooth tester. Communication between the device and the emulator was established by air link and conducted link.

3.7 Table for Test condition

Test Items	Channel No	Frequency (MHz)	Operated Condition
Carrier frequency separation	39, 40, 41	2 440, 2 441, 2 442	Hopping on and continuous modulation setting mode
Number of hopping frequencies	1 ~ 79	2 402 ~ 2 480	Hopping on mode
Time of occupancy (Dwell Time)	40	2 441	Hopping on mode
Conducted peak output power	1	2 402	Hopping off and continuous modulation setting mode
	40	2 441	
	79	2 480	
Band-edge Compliance	1	2 402	Hopping off and continuous modulation setting mode
	79	2 480	
Spurious RF conducted emissions	-	-	Frequency band setting by required standard (FCC Rules)*
Spurious radiated emissions	-	-	

*Note Channel number is selected lowest, middle, highest channel and also hopping on/off mode operation

3.8 Used Test Equipment List

No.	Instrument	Model	S/N	Manufacturer	Due to cal date	Cal interval	used
1	T & H Chamber	EY-101	90E14260	TABAI ESPEC	2014.10.05	1 year	☒
2	Constant switch Tester	DS-COT	None	Dong sung Ele.	N/A	N/A	☐
3	Vibration Tester	70UA	L90016	IDEX Co.,Ltd	N/A	N/A	☐
4	Vibration Meter	VM-6360	N225098	LANDTEK	2015.04.04	18 month	☐
5	Falling Tester	SWD-8000	None	Sinwoo	N/A	N/A	☐
6	Spectrum Analyzer	8563E	3846A10662	Agilent Technology	2015.02.07	1 year	☐
7	Spectrum Analyzer	8593E	3710A02859	Agilent Technology	2015.02.07	1 year	☐
8	Spectrum Analyzer	FSV30	20-353063	Rohde& Schwarz	2015.02.07	1 year	☒
9	EMI Test Receiver	ESCI7	100823	Rohde& Schwarz	2015.02.05	1 year	☒
10	EMI Test Receiver	ESI	834000/002	Rohde& Schwarz	2015.02.05	1 year	☒
11	Vector Signal Analyzer	89441A	3416A02620	Agilent Technology	2015.02.07	1 year	☐
12	Network Analyzer	8753ES	US39172348	AGILENT	2014.10.05	1 year	☐
13	EPM Series Power meter	E4418B	GB39512547	Agilent Technology	2015.02.07	1 year	☐
14	RF Power Sensor	E9300A	MY41496631	Agilent Technology	2015.02.07	1 year	☐
15	Microwave Frequency Counter	5352B	2908A00480	Agilent Technology	2015.02.07	1 year	☐
16	Modulation Analyzer	8901A	3538A07071	Agilent Technology	2015.02.07	1 year	☐
17	Audio Analyzer	8903B	3514A16919	Agilent Technology	2015.02.07	1 year	☐
18	Audio Telephone Analyzer	DD-5601CID	520010281	CREDIX	2015.02.07	1 year	☐
19	Digital storage Oscilloscope	TDS3052	B015962	Tektronix	2014.10.05	1 year	☐
20	ESG-D Series Signal Generator	E4436B	US39260458	Agilent Technology	2015.02.07	1 year	☒
21	ESG Vector Signal Generator	E4438C	MY42083133	Agilent Technology	2014.10.05	1 year	☐
22	Vector Signal Generator	SMBV100A	257557	Rohde & Schwarz	2015.01.21	1 year	☐
23	Tracking Source	85645A	070521-A1	Agilent Technology	2015.02.07	1 year	☐
24	Signal Generator	SML03	100692	Rohde& Schwarz	2015.02.07	1 year	☐
25	SLIDAC	None	0207-4	Myoung sung Ele.	2015.02.07	1 year	☐
26	DC Power supply	DRP-5030	9028029	Digital Electronic Co.,Ltd	2015.02.07	1 year	☐
27	DC Power supply	6038A	3440A12674	Agilent Technology	2015.02.07	1 year	☐
28	DC Power supply	E3610A	KR24104505	Agilent Technology	2015.02.07	1 year	☒
29	DC Power supply	UP-3005T	68	Unicon Co.,Ltd	2015.02.07	1 year	☐
30	DC Power Supply	SM 3004-D	114701000117	DELTAELEKTRONIKA	2015.02.07	1 year	☐
31	Dummy Load	8173	3780	Bird Electronic Co., Corp	2015.02.07	1 year	☐
32	Attenuator	50FH-030-500	140410 9433	JEW Industries Inc.	2015.02.07	1 year	☐
33	Attenuator	765-20	9703	Narda	2014.10.05	1 year	☐
34	Attenuator	8498A	3318A09485	HP	2015.02.07	1 year	☐
35	Step Attenuator	8494B	3308A32809	HP	2015.02.07	1 year	☐
36	Step Attenuator	8495D	3308A01464	HP	2015.02.07	1 year	☐
37	Power divider	11636B	51212	HP	2014.10.05	1 year	☒
38	3Way Power divider	KPDSU3W	00070365	KMW	2015.02.07	1 year	☐
39	Band rejection filter	WTR-BRF2442-84NN	09020001	WAVE TECH Co.,LTD	2015.02.07	1 year	☐
40	White noise audio filter	ST31EQ	101902	SoundTech	2014.10.05	1 year	☐
41	Dual directional coupler	778D	17693	HEWLETT PACKARD	2015.02.07	1 year	☐
42	Dual directional coupler	772D	2839A00924	HEWLETT PACKARD	2015.02.07	1 year	☐
43	Band rejection filter	3TNF-0006	26	DOVER Tech	2015.02.07	1 year	☐
44	Band rejection filter	3TNF-0008	317	DOVER Tech	2015.02.07	1 year	☐
45	Band rejection filter	3TNF-0007	311	DOVER Tech	2015.02.07	1 year	☐
46	Highpass Filter	WHJS1100-10EF	1	WAINWRIGHT	2015.02.07	1 year	☐
47	Highpass Filter	WHJS3000-10EF	1	WAINWRIGHT	2015.02.07	1 year	☐
48	Radio Communication Alalyzer	MT8815A	6200429622	ANRITSU	2015.02.07	1 year	☐
49	CDMA Mobile Station Test Set	E8285A	US40081298	AGILENT	2015.02.07	1 year	☐
50	WideBand Radio Communication Tester	CMW500	102276	Rohde & Schwarz	2015.04.10	1 year	☐

No.	Instrument	Model	S/N	Manufacturer	Due to cal date	Cal interval	used
51	RF Up/Down Converter	DCP-1780	980901003	CREDIX	2015.02.07	1 year	☐
52	DECT Test set	8923B	3829U00364	HP	2015.02.07	1 year	☐
53	DECT Test set	CMD60	840677/005	Rohde & Schwarz	2014.12.04	1 year	☐
54	Loop Antenna	6502	9203-0493	EMCO	2015.05.31	2 year	☒
55	Dipole Antenna	HZ-12	100005	Rohde & Schwarz	2016.07.01	2 year	☐
56	Dipole Antenna	HZ-13	100007	Rohde & Schwarz	2016.07.01	2 year	☐
57	BiconiLog Antenna	HL562	100076	Rohde & Schwarz	2014.12.10	2 year	☒
58	Horn Antenna	3115	9605-4834	EMCO	2016.06.16	2 year	☒
59	Horn Antenna	3115	2996	EMCO	2016.02.26	2 year	☐
60	Horn Antenna	BBHA9170	BBHA9170152	SCHWARZBECK	2015.05.27	2 year	☒
61	Signal Generator	SMT-06	100552	Rohde & Schwarz	2015.02.07	1 year	☐
62	HYGRO-Thermograph	NSII-Q	1611545	SATO	2014.10.05	1 year	☐
63	Barometer	7612	81134	SATO	2016.01.20	2 year	☐
64	Multi meter	DM-313	S60901832	LG Precision Co.,Ltd	2015.02.07	1 year	☐
65	Antenna Mast(OSA)	AT14	None	Daeil EMC	N/A	N/A	☐
66	Turn table(OSA)	None	None	Daeil EMC	N/A	N/A	☐
67	RF Amplifier(OSA)	8447D	2944A07881	AGILENT	2015.02.04	1 year	☐
68	Antenna Master(3)	AT13	None	AUDIX	N/A	N/A	☒
69	Turn Table(3)	None	None	AUDIX	N/A	N/A	☒
70	PREAMPLIFIER(3)	8449B	3008A02577	Agilent	2015.02.05	1 year	☒
71	Antenna Master(10)	MA4000-EP	None	inno systems GmbH	N/A	N/A	☒
72	Turn Table(10)	None	None	inno systems GmbH	N/A	N/A	☒
73	AMPLIFIER(10)	TK-PA6S	120009	TESTEK	2015.02.05	1 year	☐
74	Vernier Calipers	None	8280373	Mitutoyo	2014.10.05	1 year	☐

4. SUMMARY TEST RESULTS

Description of Test	FCC Rule	Reference Clause	Used	Test Result
Carrier frequency separation (20 dB bandwidth)	15.247(a)(1)	Clause 5.1	☒	Compliance
Number of hopping frequencies	15.247(a)(1)(iii)	Clause 5.2	☒	Compliance
Time of occupancy (Dwell Time)	15.247(a)(1)(iii)	Clause 5.3	☒	Compliance
Max. Conducted peak output power	15.247(b)(1)	Clause 5.4	☒	Compliance
Band edge compliance of RF conducted emissions	15.247(d)	Clause 5.5	☒	Compliance
Spurious RF conducted emissions	15.247(d)	Clause 5.6	☒	Compliance
Spurious RF radiated emissions	15.247(d), 15.209	Clause 5.7	☒	Compliance
Antenna requirement	15.203, 15.247	Clause 5.8	☒	Compliance
AC Conducted emission	15.207	Clause 5.9	☒	Compliance
Compliance/pass : The EUT complies with the essential requirements in the standard. Not Compliance : The EUT does not comply with the essential requirements in the standard. N/A : The test was not applicable in the standard.				

5. MEASUREMENT RESULTS

5.1 Carrier Frequency Separation

5.1.1 Standard Applicable [FCC §15.247(a),(1)]

Frequency hopping systems operating in the (2 400 ~ 2 483.5) MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.

5.1.2 Test Environment conditions

- Ambient temperature : (22 - 23) °C ,
- Relative Humidity : (58 - 67) % R.H.

5.1.3 Measurement Procedure

After place the EUT on the table and set it in transmitting mode, remove the antenna from EUT and then connect a RF cable from the antenna port to the spectrum analyzer.

The carrier frequency separation was measured with a spectrum analyzer connected to the antenna terminal while EUT had its hopping function enabled. After the trace being stable, the reading value between the peak of the adjacent channels using the marker- Delta function was recorded as the measurement results.

The spectrum analyzer is set to the as follows :


- Span : 10 MHz
- RBW : 100 kHz
- VBW : 300 kHz
- Sweep : auto
- Detector function : peak
- Trace : max hold

5.1.4 Measurement Result


Mode	Channel separation (MHz)	20dB Bandwidth (MHz)	Result	Limit (MHz) 2/3 of 20dB bandwidth
GFSK hopping off Tx Mode (DH5)	0.99	0.94	Compliance	0.62
8-DPSK hopping off Tx Mode(3-DH5)	1.00	1.25	Compliance	0.83

5.1.5 Test Plot (Carrier Frequency Separation)

GFSK




8-DPSK




Test Plot (20 dB bandwidth) GFSK


CH Low (2 402 MHz)



CH Middle (2 441 MHz)




CH High (2 480 MHz)




Test Plot (20 dB bandwidth) 8-DPSK


CH Low (2 402 MHz)



CH Middle (2 441 MHz)



CH High (2 480 MHz)



* Note : 20 dB bandwidth

▪ Limit : Intentional radiators operating under the alternative provisions to the general emission limits, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated.

▪ Test setup : The spectrum analyzer is set to the as follows :

- Span : 5-30 % greater than the EBW
- RBW : 30 kHz
- VBW : 100 kHz
- Sweep : auto
- Detector function : peak
- Trace : max hold

5.2 Number of hopping frequencies

5.2.1 Standard Applicable [FCC §15.247(a),(1)(iii)]

Frequency hopping systems in the (2 400 ~ 2 483.5) MHz band shall use at least 15 channels

5.2.2 Test Environment conditions

- Ambient temperature : (22 - 23) °C ,
- Relative Humidity : (58 - 67) % R.H.

5.2.3 Measurement Procedure

The number of hopping frequencies was measured with a spectrum analyzer connected to the antenna Terminal to get higher resolution, two frequency ranges within the (2 400 ~ 2 483.5) MHz Frequency hopping band were examined. The EUT must have its hoping function enabled. After the trace being stable, it may prove necessary to break the span up to sections, in order to clearly show all of the hopping frequencies.

The spectrum analyzer is set to the as follows :


- Span : Start 2 400 MHz, Stop 2 483.5 MHz
- RBW : 100 kHz
- VBW : 300 kHz
- Sweep : auto
- Detector function : peak
- Trace : max hold

5.2.4 Measurement Result


Channel Number	Mode	Hopping frequency band (MHz)	Test Results		
			Measured total number of Hopping Channels	Limit	Result
1 ~ 79	GFSK hopping on Tx Mode	(2 402 ~ 2 480) MHz	79	≥ 15	Compliance
1 ~ 79	8-DPSK hopping on Tx Mode	(2 402 ~ 2 480) MHz	79	≥ 15	Compliance

5.2.5 Test Plot

GFSK hopping off Tx Mode



8-DPSK hopping off Tx Mode



5.3 Time of occupancy (Dwell Time)

5.3.1 Standard Applicable [FCC §15.247(a),(1)(iii)]

According to §15.247(a),(1)(iii), Frequency hopping systems operating in the 2 400 MHz – 2 483.5 MHz.
The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

5.3.2 Test Environment conditions

- Ambient temperature : (22 - 23) °C ,
- Relative Humidity : (58 - 67) % R.H.

5.3.3 Measurement Procedure

The dwell time was measured with a spectrum analyzer connected to the antenna terminal, while EUT had its hopping function enabled. After used the marker-delta function to determine the dwell time.

The spectrum analyzer is set to the as follows :

- Span : Zero , Centered on a hopping channel
- Resolution (or IF) Bandwidth(RBW) : 1 MHz
- Video (or Average) Bandwidth(VBW) : ≥ RBW
- Detector function : peak
- Trace : max hold

5.3.4 Measurement Result

Mode	Pulse Width [ms]	Max. number of transmissions in 31.6 sec	Dwell time Pulse Width * Max. number of transmissions[ms]	Limit [s]	Result
GFSK DH1	0.396	640	253.44	≤ 0.4	Compliance
DH3	1.648	214	352.67	≤ 0.4	Compliance
DH5	2.900	128	371.20	≤ 0.4	Compliance
8-DPSK 3-DH1	0.402	640	257.28	≤ 0.4	Compliance
3-DH3	1.626	214	347.96	≤ 0.4	Compliance
3-DH5	2.915	128	373.12	≤ 0.4	Compliance

Dwell time = total hops * pulse's on time.

Note:

The channel staying time of 0.4 s within a 31.6 second period in data mode is constant for Bluetooth® devices and independent from the packet type (packet length). The calculation for a 31.6 second period is a follows:

Channel staying time = time slot length * hop rate / number of hopping channels * 31.6 s

Example for a DH1 packet (with a maximum length of one time slot) Channel staying time = 625 μs * 1600*1/s / 79 * 31.6 s = 0.4 s (in a 31.6 s period)


For multi-slot packets the hopping is reduced according to the length of the packet.

Example for a DH3 packet (with a maximum length of three time slots) Channel staying time = 3 * 625 μs * 1600/3 *1/s / 79 * 31.6 s = 0.4 s (in a 31.6 s period)


Example for a DH5 packet (with a maximum length of five time slots) Channel staying time = 5 * 625 μs * 1600/5 *1/s / 79 * 31.6 s = 0.4 s (in a 31.6 s period)

5.3.5 Test Plot (Time slot) GFSK


DH1



DH3




DH5




Test Plot (Time slot) 8-DPSK


3DH1



3DH3



3DH5



5.4 Max. Conducted peak output power

5.4.1 Standard Applicable [FCC §15.247(b)(1)]

For frequency hopping systems operating in the 2 400 - 2 483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5 725 – 5 850 MHz band : 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power.

5.4.2 Test Environment conditions

- Ambient temperature : (22 - 23) °C ,
- Relative Humidity : (58 - 67) % R.H.

5.4.3 Measurement Procedure

The transmitter output was connected to the spectrum analyzer with an attenuator. The maximum peak output power was measured and recorded with the spectrum analyzer. EUT was programmed to be in continuously transmitting mode. All conducted power tests were performed using a test receiver in accordance with ANSI C63.10, 2009; tested to FHSS test procedure of FCC Public Notice DA 00-705 for compliance to FCC 47CFR 15.247 requirements.

*The spectrum analyzer is set to the as follows ;

- Span : approximately 5 times the 20 dB bandwidth
- RBW : > 20 dB bandwidth of the emission being measured
- VBW : ≥ RBW
- Sweep : auto
- Detector function : peak
- Trace : max hold


* Above measurement frequency is selected to the lowest, Middle and Highest channel

5.4.4 Measurement Result

Mode	Freq(MHz)	Test Results		
		Measured power [dBm]	Limit [dBm]	Result
GFSK hopping off Tx Mode	2402	3.03	≤ 30	Compliance
	2441	3.15	≤ 30	Compliance
	2480	2.99	≤ 30	Compliance
π/4 DQPSK hopping off Tx Mode	2402	2.62	≤ 30	Compliance
	2441	2.79	≤ 30	Compliance
	2480	2.66	≤ 30	Compliance
8-DPSK hopping off Tx Mode	2402	2.97	≤ 30	Compliance
	2441	3.11	≤ 30	Compliance
	2480	2.95	≤ 30	Compliance

5.4.6 Test Plot (GFSK)

CH Low (2 402 MHz)



CH Middle (2 441 MHz)




CH High (2 480 MHz)



Test Plot ($\pi/4$ QPSK)


CH Low (2 402 MHz)



CH Middle (2 441 MHz)




CH High (2 480 MHz)




Test Plot (8-DPSK)


CH Low (2 402 MHz)



CH Middle (2 441 MHz)



CH High (2 480 MHz)



5.5 Band-edge Compliance of RF Conducted emissions

5.5.1 Standard Applicable [FCC §15.247(d)]

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on RF conducted.

5.5.2 Test Environment conditions

- Ambient temperature : (22 - 23) °C ,
- Relative Humidity : (58 - 67) % R.H.

5.5.3 Measurement Procedure

- ① Pre-calibration for the spectrum analyzer has to be done first through a reference CW signal from CAL OUT(-10 dBm)
- ② Reference frequency generated from the signal generator is supply to spectrum analyzer input port via RF cable and attenuator, and then, it's apply to offset value on spectrum analyzer as follows ;
on spectrum analyzer [Amplitude→1 More of 3→REF LVL OFFSET(measured loss dB)]
- ③ Remove the antenna from the EUT and then, connected to spectrum analyzer via a dc Block, suitable low loss RF cable and attenuator.
- ④ set on the emission at the band-edge
- ⑤ After the trace being stable, Use the marker-to-peak function to move the marker to the peak of the in-band emission.
- ⑥ The marker-delta value now displayed must comply with the limit specified in above standard.
- ⑦ please refer to the detailed procedure method FCC Public Notice(DA 00-705)

The spectrum analyzer is set to the as follows :


- Span : 5 MHz - 10 MHz
- RBW : 100 kHz (≥ 1 % of the span)
- VBW : 300 kHz
- Sweep : auto
- Detector function : peak
- Trace : Max hold

5.5.5 Measurement Result


Setting Channel		Mode	Test Results		
			Measured value [dB]	Limit [dB]	Result
CH Low (2 402 MHz)	~ 2 400 MHz	GFSK DH5	44.31	≤ 20	Compliance
CH High (2 480 MHz)	2 483.5 MHz ~		58.01		Compliance
CH Low (2 402 MHz)	~ 2 400 MHz	8-DPSK 3-DH5	48.99		Compliance
CH High (2 480 MHz)	2 483.5 MHz ~		58.94		Compliance
All restriction band have been tested, and only the worst case is shown in report. Hopping on and hopping off mode all have been test, hopping off mode is worst case and reported only.					

5.5.6 Test Plot (GFSK)

CH Low (2 402 MHz)




CH High (2 480 MHz)




Test Plot (8-DPSK)

CH Low (2 402 MHz)



CH High (2 480 MHz)



5.6 Spurious RF Conducted emissions

5.6.1 Standard Applicable [FCC §15.247(d)]

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power.

5.6.2 Test Environment conditions

- Ambient temperature : (22 - 23) °C
- Relative Humidity : (58 - 67) % R.H.

5.6.3 Measurement Procedure

- ① Pre-calibration for the spectrum analyzer has to be done first through a reference CW signal from CAL OUT(-10 dBm)
- ② Reference frequency generated from the signal generator is supply to spectrum analyzer input port via RF cable and attenuator, and then, it's apply to offset value on spectrum analyzer as follows ;
on spectrum analyzer [Amplitude→1 More of 3→REF LVL OFFSET(measured loss dB)]
- ③ Remove the antenna from the EUT and then, connected to spectrum analyzer via a dc Block, suitable low loss RF cable and attenuator.
- ④ set on the emission at the band-edge
- ⑤ After the trace being stable, Use the marker-to-peak function to move the marker to the peak of the in-band emission.
- ⑥ The marker-delta value now displayed must comply with the limit specified in above standard.
- ⑦ please refer to the detailed procedure method FCC Public Notice(DA 00-705)

The spectrum analyzer is set to the as follows :

- Span : wide enough to capture the peak level of the in-band emission and all spurious emissions from the Lowest frequency generated in the EUT up through the 10th harmonic. Typically, several plots are required to cover this entire span.
- RBW : 100 kHz (≥ 1 % of the span)
- VBW : 300 kHz
- Sweep : auto
- Detector function : peak
- Trace : Max hold

5.6.4 Measurement Result

No non-compliance noted.


Please refer as following plots

*Note: All restriction band have been tested, and only the worst case is shown in report.


Hopping on and hopping off mode all have been test, hopping off mode is worst case and reported only.

5.6.5 Test Plot (GFSK DH5)


CH Low (2 402 MHz)



CH Middle (2 441 MHz)




CH High (2 480 MHz)




Test Plot (8-DPSK 3-DH5)


CH Low (2 402 MHz)



CH Middle (2 441 MHz)



CH High (2 480 MHz)



5.7 Spurious RF Radiated emissions

5.7.1 Standard Applicable [FCC §15.247(d)]

All other emissions outside these bands shall not exceed the general radiated emission limits specified in §15.209(a). And according to §15.33(a)(1), for an intentional radiator operates below 10 GHz, the frequency Range of measurements : to the tenth harmonic of the highest fundamental frequency or to 40 GHz, Whichever is lower. In addition, radiated emissions which fall in the restricted bands, as defined in Sec.15.205(a), must also comply with the radiated emission limits specified in Sec. 15.209(a)

§15.209. [Table 1] limits for radiated emissions measurements (distance at 3m)

Frequency Band [MHz]	DISTANCE[Meters]	Limit [$\mu V/m$]	Limit [dB $\mu V/m$]	Detector
0.009 ~ 0.490	300	2400/F(kHz)	67.6-20log(F)	Peak
0.490 ~ 1.705	30	24000/F(kHz)	87.6-20log(F)	Peak
1.705 ~ 30.0	30	30	29.54	Peak
30 - 88	3	100 **	40.00	Quasi peak
88 - 216	3	150 **	43.52	Quasi peak
216 - 960	3	200 **	46.02	Quasi peak
Above 960	3	500	54.00	Average
Above 1000	3	74.0 dB(μV)/m (Peak), 54.0 dB(μV)/m (Average)		

** fundamental emissions from intentional radiators operation under this Section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz, or 470-806 MHz. However, operation within these Frequency bands is permitted under other sections of this Part Section 15.231 and 15.241

§15.205. [Table 2] Restrict Band of Operation

Only spurious emissions are permitted in any of the frequency bands listed below ;			
[MHz]	[MHz]	[MHz]	[GHz]
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
0.495 - 0.505**	16.694 75 - 16.695 25	608 - 614	5.35 - 5.46
2.173 5 - 2.190 5	16.804 25 - 16.804 75	960 - 1 240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1 300 - 1 427	8.025 - 8.
4.177 25 - 4.177 75	37.5 -38.25	1 435 - 1 626.5	9.0 - 9.2
4.207 25 - 4.207 75	73 - 74.6	1 645.5 - 1 646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1 660 - 1 710	10.6 - 12.7
6.267 75 - 6.268 25	108 - 121.94	1 718.8 - 1 722.2	13.25 - 13.
6.311 75 - 6.312 25	123 - 138	2 200 - 2 300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2 310 - 2 390	15.35 - 16.2
8.362 - 8.366	156.524 75 - 156.525 25	2 483.5 - 2 500	17.7 - 21.4
8.376 25 - 8.38 6 75	156.7 - 156.9	2 690 - 2 900	22.01 - 23.12
8.414 25 - 8.414 75	162.012 5 - 167.17	3 260 - 3 267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3 332 - 3 339	31.2 - 31.8
12.519 75 - 12.520 25	240 - 285	3 345.8 - 3 358	36.43 - 36.5
12.576 75 - 12.577 25	322 - 335.4	3 600 - 4 400	Above 38.6

** Until February 1, 1999, this restricted band shall be 0.490-0.510

5.7.2 Test Environment conditions

- Ambient temperature : (22 - 23) °C
- Relative Humidity : (58 - 67) % R.H.

5.7.3 Measurement Procedure

The measurements procedure of the transmitter radiated E-field is as following describe method.

The test is performed in a Shield chamber to determine the accurate frequencies, after maximum emissions level will be checked on a test chamber and measuring distance is 3 m from EUT to test antenna.

(The chamber is ensured that comply with at least 6 dB above the ambient noise level)


- ① The EUT was powered ON with continuously operating mode and placed on a 0.8 meter high non-conductive table on the reference ground plane.
 - ② The test antenna was used on Horn antenna for above 1 GHz, and if the below 1 GHz, broad-band antenna and Loop antenna were used for below 30 MHz and it's antenna positioned in both the horizontal and vertical plane was location at EUT during the test for maximized the emission measurement.
 - ③ The output of the test antenna will be connected to a measuring receiver, and it is set to tuned over the frequency range according to required standard
 - ④ The resolution bandwidth below 30MHz setting on the field strength meter is 9kHz and 30MHz~1GHz is 120kHz and above 1GHz, both Peak and Average level were measured with Spectrum Analyzer, and the RBW is set at 1MHz, VBW is set at 3MHz for Peak measure; RBW is set at 1MHz, VBW is set at 10Hz for Average measure(according ANSI C63.10:2009 clause 4.2.3.2.3 procedure for average measure). Both PK and AV level test, PK detector is used.
 - ⑤ The fundamental frequency at which a relevant radiated signal component is detected, the test antenna will be raised and lowered through the specified range of heights in horizontal and vertical polarized orientation, until an maximum signal level is detected on the measuring receiver.
 - ⑥ The transmitter is position x,y,z axis on rotating through 360 degrees, until the maximum signal level is detected by the measuring receiver.
 - ⑦ The receiver is scanned from requested measuring frequency band and then the maximum meter reading is recorded. The radiated emissions were measured with required standard.
- The measurement results are obtained as described below:
$$\text{Result(dB } \mu\text{V/m)} = \text{Reading(dB } \mu\text{V)} + \text{Antenna factor(dB/m)} + \text{CL(dB)} + \text{other applicable factor (dB)}$$
 - According to §15.33 (a)(1), Frequency range of radiated measurement is performed the tenth harmonic.

5.7.4 Measurement Uncertainty


All measurements involve certain levels of uncertainties. The factors contributing to uncertainties are test receiver, Cable loss, Antenna factor calibration, antenna directivity, antenna factor variation with height, antenna phase center variation, Antenna frequency interpolation, measurement distance variation, Site imperfection, mismatch, and system repeatability based on NIS 80.81, The measurement uncertainty level with a 95 % confidence level were apply to Uncertainty of a radiation emissions measurement at Chamber of KOSTEC is ± 6.0 dB

5.7.5 Test Configuration


Radiated emission setup, Below 30 MHz



Radiated emission setup, Below 1 000 MHz



Radiated emission setup, Above 1 GHz



5.7.6 Measurement Result

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates.

Following channel(s) was (were) selected for the final test as listed below.

Freq band	Mode	Measured CH
Below 1 GHz	GFSK(1Mbps) DH5	2441
Above 1 GHz	GFSK(1Mbps) DH5	2402, 2441, 2480
	8-DPSK(1Mbps) 3-DH5	2402, 2441, 2480

■ Below 1 GHz

CH MID (2 441 MHz)

Freq. (MHz)	Reading (dB μ V/m)	Table (Deg)	Antenna			CL (dB)	Pre AMP (dB)	Meas Result (dB μ V/m)	Limit (dB μ V/m)	Mgn (dB)	Result
			Height (m)	Pol. (H/V)	Fctr. (dB/m)						
38.52	26.03	110	1.0	V	15.33	1.20	-	42.56	46	3.44	Compliance
50.70	26.92	120	1.0	V	8.53	1.41	-	36.86	46	9.14	Compliance
160.02	26.66	120	4.0	H	8.46	2.63		37.75	46	8.25	Compliance
310.02	16.65	120	1.0	V	12.01	3.80		32.46	46	13.54	Compliance
Below 30MHz, Above 310.02 MHz Nil emission											

■ Above 1 GHz

GFSK :CH LOW (2 402 MHz)

Freq. (GHz)	Reading (dB μ V/m)		Table (Deg)	Antenna			CL+Pre AMP (dB)	Meas Result (dB μ V/m)		Limit (dB μ V/m)		Mgn. (dB)		Result
	PK	AV		Height (m)	Pol. (H/V)	Fctr. (dB/m)		PK	AV	PK	AV	PK	AV	
2.138	35.03	17.80	120	1.0	H	27.85	2.38	65.26	48.03	74	54	8.74	5.97	Compliance
Above 2.138 GHz Nil emission														

GFSK :CH Middle (2 441 MHz)

Freq. (GHz)	Reading (dB μ V/m)		Table (Deg)	Antenna			CL+Pre AMP (dB)	Meas Result (dB μ V/m)		Limit (dB μ V/m)		Mgn. (dB)		Result
	PK	AV		Height (m)	Pol. (H/V)	Fctr. (dB/m)		PK	AV	PK	AV	PK	AV	
2.138	35.85	18.02	120	1.0	H	27.85	2.38	66.08	48.25	74	54	7.92	5.75	Compliance
Above 2.138 GHz Nil emission														

GFSK :CH High (2 480 MHz)

Freq. (GHz)	Reading (dB μ V/m)		Table (Deg)	Antenna			CL+PreAMP (dB)	Meas Result (dB μ V/m)		Limit (dB μ V/m)		Mgn. (dB)		Result
	PK	AV		Height (m)	Pol. (H/V)	Fctr. (dB/m)		PK	AV	PK	AV	PK	AV	
2.138	34.48	17.26	120	1	H	27.85	2.38	64.71	47.49	74	54	9.29	6.51	Compliance
Above 2.138 GHz Nil emission														

8-DPSK :CH LOW (2 402 Mhz)

Freq. (GHz)	Reading (dB μ V/m)		Table (Deg)	Antenna			CL+Pre AMP (dB)	Meas Result (dB μ V/m)		Limit (dB μ V/m)		Mgn. (dB)		Result
	PK	AV		Height (m)	Pol. (H/V)	Fctr. (dB/m)		PK	AV	PK	AV	PK	AV	
2.138	35.63	18.21	120	1	H	27.85	2.38	65.86	48.44	74	54	8.14	5.56	Compliance
Above 2.138 GHz Nil emission														

8-DPSK :CH Middle (2 441 Mhz)

Freq. (GHz)	Reading (dB μ V/m)		Table (Deg)	Antenna			CL+Pre AMP (dB)	Meas Result (dB μ V/m)		Limit (dB μ V/m)		Mgn. (dB)		Result
	PK	AV		Height (m)	Pol. (H/V)	Fctr. (dB/m)		PK	AV	PK	AV	PK	AV	
2.138	35.14	17.96	120	1	H	27.85	2.38	65.37	48.19	74	54	8.63	5.81	Compliance
Above 2.138 GHz Nil emission														

8-DPSK :CH High (2 480 Mhz)

Freq. (GHz)	Reading (dB μ V/m)		Table (Deg)	Antenna			CL+PreAMP (dB)	Meas Result (dB μ V/m)		Limit (dB μ V/m)		Mgn. (dB)		Result
	PK	AV		Height (m)	Pol. (H/V)	Fctr. (dB/m)		PK	AV	PK	AV	PK	AV	
2.138	34.12	17.05	120	1	H	27.85	2.38	64.35	47.28	74	54	9.65	6.72	Compliance
Above 2.138 GHz Nil emission														

※ Note

- Above 1 GHz is measured average and peak detector mode on Spectrum analyzer in accordance with FCC Rule15.35
- Limit: 54 dB μ V/m(Average), 74 dB μ V/m(Peak), Attenuated more than 20 dB below the permissible value.
- For the below 30 MHz, measured any other signal is not detected on test receiver
- It is not recorded on the report that the reading of emissions are attenuated more than 20 dB below the permissible limits or the field strength is too small to measured.
- For emissions below 1 GHz, according exploratory explorer test, when change Tx mode and channel, have no distinct influence on emissions level, so for emissions below 1 GHz, the final test was only performed with EUT working in GFSK, Tx 2441 MHz mode.
- The transmitter radiated spectrum was investigated from 9 kHz to 25 GHz

Freq.(MHz) : Measurement frequency, Reading(dB μ V/m) : Indicated value for test receiver,

Table (Deg) : Directional degree of Turn table,

Antenna (Height, Pol, Fctr) : Antenna Height, Polarization and Factor

Cbl(dB) : Cable loss, Pre AMP(dB) : Preamplifier gain(dB)

Meas Result (dB μ V/m) : Reading(dB μ V/m)+ Antenna factor.(dB/m) + CL(dB) - Pre AMP(dB)

Limit(dB μ V/m): Limit value specified with FCC Rule, Mgn(dB) : FCC Limit (dB μ V/m) – Meas Result(dB μ V/m)

5.8 Antenna requirement

5.8.1 Standard applicable [FCC §15.203, §15.247(4)(1)]

For intentional device, according to §15.203, an intentional radiator shall be designed to ensure that no antenna other than furnished by responsible party shall be used with the device.

The use of a permanently attached antenna or of an antenna that user a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

The manufacturer may design the unit So that broken antenna can be replaced by the user, but the Use of a standard antenna jack or electrical connector is prohibited.

And according to §15.247(4)(1), the conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi.

According to above requirement standard's This product's antenna type is an PCB type and it's gain is -1.0 dBi, So radiated emission field strength from EUT is below requirement standard limit

5.8.2 Antenna gain

Frequency Band	Gain [dBi]	Limit [dBi]	Results
(2 400 ~ 2 485) MHz	1.56	≤ 6	Compliance

5.9 AC Power Conducted emissions

5.9.1 Standard Applicable [FCC §15.207(a)]

For intentional radiator that is designed to be connected to the public utility(AC)power line, the radio frequency. Voltage that is conducted back onto the AC power line on any frequencies hopping mode within the band 150 kHz to 30 MHz shall not exceed the limits in the following table, as measured using a 50 uH/50 ohms line Impedance stabilization network(LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the boundary between the frequency ranges.

§15.207 limits for AC line conducted emissions;

Frequency of Emission(MHz)	Conducted Limit (dB μ V)	
	Quasi-peak	Average
0.15 ~ 0.5	66 to 56 *	56 to 46 *
0.5 ~ 5	56	46
5 ~ 30	60	50

* Decreases with the logarithm of the frequency

5.9.2 Test Environment conditions

- Ambient temperature : (22 - 23) °C
- Relative Humidity : (58 - 67) % R.H.

5.9.3 Measurement Procedure

The measurements were performed in a shielded room. EUT was placed on a non-metallic table Height of 0.4 m above the reference ground plane. They were folded back and forth forming a bundle 30 cm to 40 cm long and were hanged at a 40 cm height to the ground plane. Each EUT power lead, except ground (safety) lead, was individually connected through a LISN to Input power source. Both lines of power cord, live and neutral, were measured.

5.9.4 Used equipment

Equipment	Model No.	Serial No.	Manufacturer	Next cal date	Cal interval	Used
Test receiver	ESCS30	100111	Rohde & Schwarz	2015.02.05	1 year	●
LISN	ESH3-Z5	100147	R&S	2015.02.05	1 year	●

*Test Program: " ESXS-K1 V2.2"

Measurement uncertainty

Conducted Emission measurement: 3.5 dB (CL: Approx 95%, k=2)

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

Following channel(s) was (were) selected for the final test as listed below.

Freq band	Mode	Measured CH
Below 1 GHz	GFSK(1Mbps) DH5	2441

5.9.5 Measurement Result

Line. Live

Kostec Co., Ltd.

01 Aug 2014 18:13

Conducted Emission


EUT: BM180
 Manuf: Bluebird Inc.
 Op Cond: a.c. 120 V, 60 Hz
 Operator:
 Test Spec:
 Comment: Live
 RF EMC_BT
 Result File: 0920_I.dat : New Measurement

Scan Settings (1 Range)

Frequencies			Receiver Settings						
Start	Stop	Step	IF BW	Detector	M-Time	Atten	Preamp	OpRge	
150kHz	30MHz	3.9063kHz	9kHz	PK+AV	10msec	15 dB	OFF	60dB	

Transducer	No.	Start	Stop	Name
	12	9kHz	30MHz	CNEFactor

Final Measurement: Detectors: X QP / + AV
 Meas Time: 1sec
 Subranges: 25
 Acc Margin: 50 dB



PAGE 1

Line. Live

Kostec Co., Ltd.

01 Aug 2014 18:13

Conducted Emission

EUT: BM180
Manuf: Bluebird Inc.
Op Cond: a.c. 120 V, 60 Hz
Operator:
Test Spec:
Comment: Live
RF EMC_BT
Result File: 0920_I.dat : New Measurement

Scan Settings (1 Range)

Frequencies			Receiver Settings			
Start	Stop	Step	IF BW	Detector	M-Time	Atten
150kHz	30MHz	3.9063kHz	9kHz	PK+AV	10msec	15 dB

Transducer	No.	Start	Stop	Name
	12	9kHz	30MHz	CNEFactor

Final Measurement: Detectors: X QP / + AV
Meas Time: 1sec
Subranges: 25
Acc Margin: 50 dB

Final Measurement Results

Frequency MHz	QP Level dBuV	QP Limit dBuV	QP Delta dB
0.15781	46.37	65.58	19.21
0.19687	45.02	63.74	18.72
0.23593	46.74	62.24	15.50
0.275	43.99	60.97	16.98
0.31796	46.20	59.76	13.56
0.39218	43.80	58.02	14.22
0.67343	44.26	56.00	11.74
1.15	42.71	56.00	13.29
1.61875	42.52	56.00	13.48
10.41953	44.10	60.00	15.90
14.86093	48.86	60.00	11.14
16.5289	47.83	60.00	12.17
18.87265	48.80	60.00	11.20

Frequency MHz	AV Level dBuV	AV Limit dBuV	AV Delta dB
0.15781	43.47	55.58	12.11
0.19687	41.55	53.74	12.19
0.23593	42.86	52.24	9.38
0.275	39.72	50.97	11.25
0.31796	40.52	49.76	9.24
0.39218	38.30	48.02	9.72
0.67343	37.14	46.00	8.86
1.15	32.99	46.00	13.01
1.61875	33.93	46.00	12.07
10.41953	33.21	50.00	16.79
14.86093	35.74	50.00	14.26
16.5289	32.35	50.00	17.65
18.87265	31.16	50.00	18.84

* limit exceeded

PAGE 2

Line. Neutral

Kostec Co., Ltd.

01 Aug 2014 18:28

Conducted Emission


EUT: BM180
 Manuf: Bluebird Inc.
 Op Cond: a.c. 120 V, 60 Hz
 Operator:
 Test Spec:
 Comment: Neutral
 RF EMC_BT
 Result File: 0920_n.dat : New Measurement

Scan Settings (1 Range)

Frequencies			Receiver Settings					
Start	Stop	Step	IF BW	Detector	M-Time	Atten	Preampl	OpRge
150kHz	30MHz	3.9063kHz	9kHz	PK+AV	10msec	15 dB	OFF	60dB

Transducer	No.	Start	Stop	Name
	12	9kHz	30MHz	CNEFactor

Final Measurement: Detectors: X QP / + AV
 Meas Time: 1sec
 Subranges: 25
 Acc Margin: 50 dB



Line. Neutral

Kostec Co., Ltd.

01 Aug 2014 18:28

Conducted Emission

EUT: BM180
Manuf: Bluebird Inc.
Op Cond: a.c. 120 V, 60 Hz
Operator:
Test Spec:
Comment: Neutral
RF EMC_BT
Result File: 0920_n.dat : New Measurement

Scan Settings (1 Range)

Frequencies			Receiver Settings					
Start	Stop	Step	IF BW	Detector	M-Time	Atten	Preamp	OpRge
150kHz	30MHz	3.9063kHz	9kHz	PK+AV	10msec	15 dB	OFF	60dB

Transducer No. Start Stop Name
12 9kHz 30MHz CNEFactor

Final Measurement: Detectors: X QP / + AV
Meas Time: 1sec
Subranges: 25
Acc Margin: 50 dB

Final Measurement Results

Frequency MHz	QP Level dBuV	QP Limit dBuV	QP Delta dB
0.15781	41.25	65.58	24.33
0.19687	38.88	63.74	24.86
0.23984	39.67	62.10	22.43
0.31406	43.34	59.86	16.52
0.35703	37.07	58.80	21.73
0.39218	40.05	58.02	17.97
0.67343	42.50	56.00	13.50
1.14218	41.40	56.00	14.60
2.41953	37.86	56.00	18.14
10.45859	40.02	60.00	19.98
15.09921	44.15	60.00	15.85
17.47812	42.82	60.00	17.18
18.98593	44.79	60.00	15.21

Frequency MHz	AV Level dBuV	AV Limit dBuV	AV Delta dB
0.15781	37.44	55.58	18.14
0.19687	31.09	53.74	22.65
0.23984	30.76	52.10	21.34
0.31406	37.08	49.86	12.78
0.35703	32.95	48.80	15.85
0.39218	31.79	48.02	16.23
0.67343	36.47	46.00	9.53
1.14218	33.53	46.00	12.47
2.41953	27.77	46.00	18.23
10.45859	28.56	50.00	21.44
15.09921	30.91	50.00	19.09
17.47812	25.09	50.00	24.91
18.98593	26.97	50.00	23.03

* limit exceeded

PAGE 2