

TEST REPORT

Applicant: BLUEBIRD INC.**EUT Description:** Handheld Managed RFID Computer**Model:** S10**Brand:****FCC ID:** SS4S10R**Standards:** FCC 47 CFR Part 15 Subpart C**Date of Receipt:** 2026/02/12**Date of Test:** 2026/02/12 to 2026/05/18**Date of Issue:** 2026/05/19

TOWE. tested the above equipment in accordance with the requirements set forth in the above standards. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

the results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. It is the manufacturer's responsibility to assure that additional production units of the model are manufactured with identical electrical and mechanical components. All sample tested were in good operating condition throughout the entire test program. Measurement Uncertainties are published for informational purposes only and were not taken into account unless noted otherwise. without written approval of TOWE, the test report shall not be reproduced except in full.

Jim Huang
Approved By:

Carey Chen
Reviewed By:

Revision History

Rev.	Issue Date	Description	Revised by
01	2026/05/19	Original	Carey Chen

Summary of Test Results

Clause	FCC Part	Test Items	Result
4.1	§15.203/15.247(b)	Antenna Requirement	PASS
4.2	§15.207	AC Power Line Conducted Emission	PASS
4.3	§15.247 (b)(3)	Output Power	PASS
4.4	§15.247 (a)(2)	Occupied Bandwidth	Reporting purposes only
4.5	§15.247 (e)	Power Spectral Density	PASS
4.6	§15.247(d)	Band Edge for Conducted Emissions	PASS
4.7	§15.247(d)	Spurious RF Conducted Emissions	PASS
4.8	§15.205/15.209	Radiated Spurious emissions and Band Edge	PASS
Test Method: ANSI C63.10-2020+Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024, KDB 558074 D01 15.247 Mesa Guidance v05r02. Remark: Pass is EUT meets standard requirements.			

Table of Contents

1	General Description	5
1.1	Lab Information	5
1.1.1	Testing Location	5
1.1.2	Test Facility / Accreditations	5
1.2	Client Information.....	5
1.2.1	Applicant.....	5
1.2.2	Manufacturer	5
1.3	Product Information	6
2	Test Configuration	7
2.1	Test Channel	7
2.2	Worst-case configuration and Mode	7
2.3	Support Unit used in test.....	8
2.4	Test Environment	8
2.5	Test RF Cable.....	8
2.6	Modifications	8
2.7	Test Setup Diagram.....	9
2.7.1	Conducted Configuration	9
2.7.2	Radiated Configuration	10
3	Equipment and Measurement Uncertainty.....	11
3.1	Test Equipment List	11
3.2	Measurement Uncertainty	13
4	Test Results.....	14
4.1	Antenna Requirement	14
4.2	AC Power Line Conducted Emissions	15
4.3	Output Power	18
4.4	Occupied Bandwidth.....	19
4.5	Power Spectral Density	20
4.6	Band Edge for Conducted Emissions.....	21
4.7	Spurious RF Conducted Emissions	22
4.8	Radiated Spurious Emissions and Band Edge	23
5	Test Setup Photos.....	25
	Appendix.....	26

1 General Description

1.1 Lab Information

1.1.1 Testing Location

These measurements tests were conducted at the Sushi TOWE Wireless Testing(Shenzhen) Co., Ltd. facility located at F401 and F101, Building E, Hongwei Industrial Zone, Liuxian 3rd Road, Bao'an District, Shenzhen, China. The measurement facility is compliant with the test site requirements specified in ANSI C63.4-2014
Tel.: +86-755-27212361
Contact Email: info@towewireless.com

1.1.2 Test Facility / Accreditations

A2LA (Certificate Number: 7088.01)

This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2017 General requirements for the competence of testing and calibration laboratories. This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (refer to joint ISO-ILAC-IAF Communiqué dated April 2017).

FCC Designation No.: CN1353

Sushi TOWE Wireless Testing(Shenzhen) Co., Ltd. has been recognized as an accredited testing laboratory.
Test Firm Registration Number: 684095
Designation Number: CN1353.

ISED CAB identifier: CN0152

Sushi TOWE Wireless Testing(Shenzhen) Co., Ltd. has been recognized by ISED as an accredited testing laboratory.
CAB identifier: CN0152
Company Number: 31000

1.2 Client Information

1.2.1 Applicant

Applicant:	BLUEBIRD INC.
Address:	3F, 115, Irwon-ro, Gangnam-gu, Seoul, Republic of Korea

1.2.2 Manufacturer

Manufacturer:	BLUEBIRD INC.
Address:	3F, 115, Irwon-ro, Gangnam-gu, Seoul, Republic of Korea

1.3 Product Information

EUT Description:	Handheld Managed RFID Computer		
Model No.:	S10		
Brand:	 BLUEBIRD A TSC Company		
Hardware Version:	V1.5		
Software Version:	20260309		
SN.:	RF Conducted	S10ANLJRNBA153	
	RSE & AC power line	S10ANLJRNBA156	
Modulation Type:	802.11b:	DSSS-DBPSK, DQPSK, CCK	
	802.11g/n:	OFDM-BPSK, QPSK, 16QAM, 64QAM	
Smart System:	☒ SISO	802.11b/g/n	/
	☐ MIMO	802.11n	()TX()RX
	☐ CDD	802.11b/g	()TX()RX
Frequency Range:	2400 ~ 2483.5MHz		
Channel Frequency:	20M bandwidth Channel: 2412 ~ 2462MHz		
	40M bandwidth Channel: 2422 ~ 2452MHz		
Channel Number:	11:	802.11b/g/n20	
	7:	802.11n40	
Antenna Type:	☐ External, ☒ Integrated,		
Antenna Gain:	Ant (dBi)		
	0.26		
Remark: The above EUT's information was declared by applicant, please refer to the specifications or user's manual for more detailed description.			

2 Test Configuration

2.1 Test Channel

Frequency Channels							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2412MHz	4	2427MHz	7	2442MHz	10	2457MHz
2	2417MHz	5	2432MHz	8	2447MHz	11	2462MHz
3	2422MHz	6	2437MHz	9	2452MHz	/	

Remark:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Modulation Type	Test Channel	Test Frequency
802.11b/g/n20	The Lowest channel (CH1)	2412MHz
	The Middle channel (CH6)	2437MHz
	The Highest channel (CH11)	2462MHz
Modulation Type	Test Channel	Test Frequency
802.11n40	The Lowest channel (CH3)	2422MHz
	The Middle channel (CH6)	2437MHz
	The Highest channel (CH9)	2452MHz

2.2 Worst-case configuration and Mode

Modulation Type	SISO - Data Rate
802.11b	1 Mbps
802.11g	6 Mbps
802.11n20	MCS0 (6.5 Mbps)
802.11n40	MCS0 (13.5 Mbps)
Transmitting mode:	Keep the EUT was programmed to be in continuously transmitting mode.
Normal Link:	Keep the EUT operation to normal function.

2.3 Support Unit used in test

The EUT has been tested as an independent unit.

2.4 Test Environment

Temperature:	Normal: 15°C ~ 35°C
Humidity:	45 ~ 56 % RH Ambient
Voltage:	DC 3.65V
AC Voltage:	AC 120V/60Hz for Conducted Emissions
Remark: The testing environment is within the scope of the EUT user manual and meets the requirements of the standard testing environment.	

2.5 Test RF Cable

For all conducted test items: The offset level is set spectrum analyzer to compensate the RF cable loss and attenuator factor between RF conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level will be exactly the RF output level.

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.


Offset = RF cable loss + attenuator factor.

2.6 Modifications


No modifications were made during testing.

2.7 Test Setup Diagram

2.7.1 Conducted Configuration



2.7.2 Radiated Configuration



3 Equipment and Measurement Uncertainty

All test and measuring equipment utilized to perform the tests documented in this report are calibrated on a regular basis, whichever is less, and where applicable is traceable to recognized national standards.

3.1 Test Equipment List

RF Conducted					
Description	Manufacturer	Model	S.N.	Last Due	Cal Due
Signal Analyzer	Keysight	N9020A	US46470429	2025/03/14	2026/03/13
				2026/03/05	2027/03/04
Signal Generator	R&S	SMR20	101027	2025/03/11	2026/03/10
				2026/03/05	2027/03/04
Vector Signal Generator	R&S	SMM100A	549353	2025/05/29	2026/05/28
Power Sensor	Anritsu	MA24408A	12520	2025/05/29	2026/05/28
RF Control Unit	Tonscend	JS0806-2	23C80620671	2025/05/29	2026/05/28
EXA Signal Analyzer, Multi-touch	Keysight	N9010B	MY63440541	2025/05/29	2026/05/28
Attenuator	Yin Saige	SMA-10dBm	N/A	N/A	N/A
Measurement Software	Tonscend	TS1120-3	10659	N/A	N/A

Radiated Emission					
Description	Manufacturer	Model	S.N.	Last Due	Cal Due
Double-Ridged Horn Antennas	Tonscend	HA32-18	806HA003608251015	2025/12/13	2028/12/12
Biconic Logarithmic Periodic Antennas	Tonscend	BLA32-30	80SBLA001011251010	2025/12/13	2028/12/12
Broad-Band Horn Antenna	Schwarzbeck	BBHA 9170	1290	2023/06/25	2026/06/24
Loop Antenna	Schwarzbeck	FMZB 1519C	1519C-028	2023/06/29	2026/06/28
Signal Analyzer	Keysight	N9020A	MY57120015	2026/01/19	2028/01/18
EXA Signal Analyzer, Multi-touch	Keysight	N9010B	MY63440541	2025/05/29	2026/05/28
EMI Tester Receiver	Rohde & Schwarz	ESR7	102719	2025/05/29	2026/05/28
Low Noise Amplifier	Tonscend	TAP9K3G40	806JSAP044710251054	2026/01/19	2028/01/18
Low Noise Amplifier	Tonscend	TAP01018050	806JSAF044509251052	2026/01/19	2028/01/18
Low Noise Amplifier	Tonscend	TAP18040048	AP22G806247	2025/03/11	2027/03/10
Hygrometer	BINGYU	HTC-1	N/A	2025/07/25	2026/07/24
Radio Frequency Switch	Townshend	JS0806s	806JSSX019811251028	N/A	N/A
Test Software	Tonscend	TS+	Version: 5.0.0	N/A	N/A

Conducted Emission					
Description	Manufacturer	Model	S.N.	Last Due	Cal Due
EMI Tester Receiver	Rohde & Schwarz	ESR3	103108	2025/05/29	2026/05/28
LISN	Rohde & Schwarz	ENV 216	102836	2026/01/19	2027/01/18
Test software	Rohde & Schwarz	ELEKTRA V4.61	N/A	N/A	N/A

3.2 Measurement Uncertainty

Parameter	U _{lab}
Frequency Error	679.98Hz
Output Power	0.76dB
Conducted Spurious Emissions	2.22dB
Conducted Emissions(150kHz~30MHz)	2.43dB
Radiated Emissions(9kHz~30MHz)	2.40dB
Radiated Emissions(30MHz~1000MHz)	4.66dB
Radiated Emissions(1GHz~18GHz)	5.42dB
Radiated Emissions(18GHz~40GHz)	5.46dB

Uncertainty figures are valid to a confidence level of 95%

4 Test Results

4.1 Antenna Requirement

Standard Applicable:	47 CFR Part 15C Section 15.203 /247(b)
15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. 15.247(b) (4) requirement: The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.	
The antenna gain and type as provided by the manufacturer are as follows: The antenna Type is Integrated. With Antenna gain is 0.26dBi. Antenna Anti-Replacement Construction: An embedded-in antenna design is used.	

4.2 AC Power Line Conducted Emissions

Limits

Frequency range (MHz)	Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

* Decreases with the logarithm of the frequency.


Test Procedure

ANSI C63.10-2020+Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024, Section 6.2.

Test Settings


1. The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a $50\Omega/50\mu\text{H} + 5\Omega$ linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded.
2. The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane.
3. The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2.
4. Set the test-receiver system to Peak detect function and specified bandwidth (if bandwidth =9kHz) with maximum hold mode. Then measurement is also conducted by average detector and Quasi-Peak detector function respectively.
5. Both sides of AC line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10 on conducted measurement.


Test Setup



Measuring Instruments

The measuring equipment is listed in the section 3.1 of this test report.

Test Result:



4.3 Output Power

Limits

If with directional antenna gains less than 6 dBi, the limit is 30dBm.

Test Procedure

ANSI C63.10-2020+Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024 Section 11.9.1.2(PKPM1) or 11.9.2.3.2(AVGPM-G)

Test Settings

1. Set to the maximum power setting and enable the EUT transmit continuously.
2. The power output was measured on the EUT antenna port using RF Cable with an attenuator connected to a power sensor. Output power was read directly from the power sensor.
3. Measure and record the results in the test report.

Test Setup

Refer to section 2.7.1 Setup 1 for details.

Measuring Instruments

The measuring equipment is listed in the section 3.1 of this test report.

Test Result

The detailed test data see: **Appendix**.

4.4 Occupied Bandwidth

Limits

DTSBW: The minimum 6 dB bandwidth shall be at least 500 kHz.

99%BW: None, for reporting purposes only.

Test Procedure

ANSI C63.10-2020+Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024 Section 11.8.2 and 6.9.3

Test Settings

1. Set to the maximum power setting and enable the EUT transmit continuously.
2. The transmitter output is connected to a spectrum analyzer:
3. RBW = shall be in the range of 1% to 5% of the OBW but not less than 100 kHz(DTS)
4. RBW = 1% - 5%(99%BW)
5. VBW $\geq$ 3 times the RBW
6. Sweep = Auto
7. Detector = Peak
8. Trace = Max hold
9. The trace was allowed to stabilize
10. Measure and record the results in the test report.

Test Notes

DTS: The signal analyzers' automatic bandwidth measurement capability of the spectrum analyzer was used to perform the 6dB bandwidth measurement. The "X" dB bandwidth parameter was set to X= 6. The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.

Test Setup

Refer to section 2.7.1 Setup 2 for details.

Measuring Instruments

The measuring equipment is listed in the section 3.1 of this test report.

Test Result

The detailed test data see: **Appendix**.

4.5 Power Spectral Density

Limits

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

Test Procedure

ANSI C63.10-2020+Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024 Section 11.10.2(PKPSD)

Test Settings

1. Set to the maximum power setting and enable the EUT transmit continuously
2. The transmitter output is connected to a spectrum analyzer
3. $3\text{kHz} \leq \text{RBW} \leq 100\text{ kHz}$
(If measured value exceeds requirement, then reduce RBW (but no less than 3 kHz) and repeat.)
4. $\text{VBW} \geq 3$ times the RBW
5. Span = 1.5 times the DTS bandwidth
6. Sweep = Auto
7. Detector = Peak
8. Trace = Max hold
9. The trace was allowed to stabilize
10. Measure and record the results in the test report.

Test Setup

Refer to section 2.7.1 Setup 2 for details.

Measuring Instruments

The measuring equipment is listed in the section 3.1 of this test report.

Test Result

The detailed test data see: **Appendix**.

4.6 Band Edge for Conducted Emissions

Limits

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits.

If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph 15.247(b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.

Test Procedure

ANSI C63.10-2020+Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024 Section 11.11.3

Test Settings

1. Set to the maximum power setting and enable the EUT transmit continuously
2. The transmitter output is connected to a spectrum analyzer
3. RBW = 100kHz
4. VBW = 300kHz
5. Point $\geq 2 \times \text{span/RBW}$
6. Sweep = Auto
7. Detector = Peak
8. Trace = Max hold
9. The trace was allowed to stabilize
10. Measure and record the results in the test report

Test Setup

Refer to section 2.7.1 Setup 2 for details.

Measuring Instruments

The measuring equipment is listed in the section 3.1 of this test report.

Test Result

The detailed test data see: **Appendix**.

4.7 Spurious RF Conducted Emissions

Limits

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits.

If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph 15.247(b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.

Test Procedure

ANSI C63.10-2020+Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024 Section 11.11.3

Test Settings

1. Set to the maximum power setting and enable the EUT transmit continuously.
2. Activate frequency hopping function if necessary.
3. The transmitter output is connected to a spectrum analyzer
4. The spectrum from 30MHz - 26.5GHz
5. RBW = 100kHz
6. VBW = 300kHz
7. Sweep = Auto
8. Detector = Peak
9. Trace = Max hold
10. The trace was allowed to stabilize
11. Measure and record the results in the test report

Test Setup

Refer to section 2.7.1 Setup 2 for details.

Measuring Instruments

The measuring equipment is listed in the section 3.1 of this test report.

Test Result

The detailed test data see: **Appendix**.

4.8 Radiated Spurious Emissions and Band Edge

Limits

Spurious emissions are permitted in an of the frequency bands:

MHz	MHz	MHz	MHz	GHz	GHz
0.090 - 0.110	12.29 - 12.293	149.9 - 150.05	1660 - 1710	4.5 - 5.15	14.47 - 14.5
0.495 - 0.505	12.51975 - 12.52025	156.52475 - 156.52525	1718.8 - 1722.2	5.35 - 5.46	15.35 - 16.2
2.1735 - 2.1905	12.5767 - 12.57725	156.7 - 156.9	2200 - 2300	7.25 - 7.75	17.7 - 21.4
4.125 - 128	13.36 - 13.41	162.0125 - 167.17	2310 - 2390	8.025 - 8.5	22.01 - 23.12
4.17725 - 4.17775	16.42 - 16.423	167.72 - 173.2	2483.5 - 2500	9.0 - 9.2	23.6 - 24.0
4.20725 - 4.20775	16.69475 - 16.69525	240 - 285	2655 - 2900	9.3 - 9.5	31.2 - 31.8
6.215 - 6.218	1680425 - 1680475	322 - 335.4	3260 - 3267	10.6 - 12.7	36.43 - 36.5
6.26775 - 6.26825	25.5 - 25.67	399.9 - 410	3332 - 3339	13.25 - 13.4	
6.31175 - 6.31225	37.5 - 38.25	608 - 614	3345.8 - 3358		
8.291 - 8.294	73 - 74.6	960 - 1240	3600 - 4400		
8.362 - 8.366	74.8 - 75.2	1300 - 1427			
8.37625 - 8.38675	108 - 121.94	1435 - 1626.5			
8.41425 - 8.41475	123 - 138	1645.5 - 1646.5			

Radiated disturbance of an intentional radiator:

Frequency	Field strength (μV/m)	Limit (dBμV/m)	Remark	Measurement distance (m)
0.009MHz-0.490MHz	2400/F(kHz)	-	-	300
0.490MHz-1.705MHz	24000/F(kHz)	-	-	30
1.705MHz-30MHz	30	-	-	30
30MHz-88MHz	100	40.0	Quasi-peak	3
88MHz-216MHz	150	43.5	Quasi-peak	3
216MHz-960MHz	200	46.0	Quasi-peak	3
960MHz-1GHz	500	54.0	Quasi-peak	3
Above 1GHz	500	74.0	Peak	3
		54.0	Average	

Test Procedure

ANSI C63.10-2020+Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024 Section 6.4 & 6.5 & 6.6

Test Settings

- For radiated emissions measurements performed at frequencies less than or equal to 1GHz, the EUT shall be placed on a RF-transparent table or support at a nominal height of 80cm above the reference ground plane.
- For radiated emissions measurements performed at frequencies above 1GHz, the EUT shall be placed on a RF-transparent table or support at a nominal height of 150cm above the ground plane.
- Radiated measurements shall be made with the measurement antenna positioned in both horizontal and vertical polarization. The measurement antenna shall be varied from 1m to 4m in height above the reference ground in a search for the relative positioning that produces the maximum radiated signal level (i.e, field strength or received power), when orienting the measurement antenna in vertical polarization, the minimum height of the lowest element of the antenna shall clear the site reference ground plane by at least 25cm.
- For each suspected emission, the EUT was ranged its worst case and then tune the antenna tower(from 1~4m) and turntable(from 0~360°) find the maximum reading. Preamplifier and a high pass filter are used for the test in order get better signal level comply with the guidelines.
- Set to the maximum power setting and enable the EUT transmit continuously.
- The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.
- spectrum analyzer setting:
Measurements 30MHz ~ 1000MHz: RBW = 120 kHz; VBW ≥ 300 kHz; Detector = Peak

Measurements Above 1000MHz: RBW = 1 MHz; VBW $\geq$ 3 MHz; Detector = Peak

Average Measurements Above 1000MHz:

RBW = 1 MHz, VBW $\geq$ 1/T, with peak detector for average measurements.

8. The field strength is calculated by adding the Antenna Factor, Cable Factor. The basic equation with a sample calculation is as follows:

Level = Reading(dB μ V) + Factor(dB):

Factor = Cable Factor(dB) + AF(dB/m) - Preamplifier gain(dB)

AF = Antenna Factor(dB/m)

Margin = Limit(dB μ V/m) – Level(dB μ V/m)

9. Repeat above procedures until all frequencies measured was complete.
10. Measure and record the results in the test report.

Test Notes

1. Emissions below 18GHz were measured at a 3-meter test distance while emissions above 18GHz were measured at a 1-meter test distance with the application of a distance correction factor.
2. Radiated spurious emissions were investigated from 9kHz to 30MHz, 30MHz-1GHz and above 1GHz. the disturbance between 9kHz to 30MHz and 18GHz to 40GHz was very low. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be recorded, so only the harmonics had been displayed.
3. These frequencies which near "-" should be ignored because they are Fundamental frequency.

Test Setup

Refer to section 2.7.2 for details.

Measuring Instruments

The measuring equipment is listed in the section 3.1 of this test report.

Test Result

The detailed test data see: **Appendix.**

5 Test Setup Photos

The detailed test data see: **Appendix A - BTWIFI Setup Photos**


Appendix

DTS Bandwidth Test Result

TestMode	Antenna	Frequency[MHz]	DTS BW [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
11b	Ant1	2412	8.480	2407.480	2415.960	0.5	PASS
11b	Ant1	2437	9.040	2432.480	2441.520	0.5	PASS
11b	Ant1	2462	8.000	2458.000	2466.000	0.5	PASS
11g	Ant1	2412	14.920	2404.880	2419.800	0.5	PASS
11g	Ant1	2437	15.400	2429.440	2444.840	0.5	PASS
11g	Ant1	2462	13.880	2454.440	2468.320	0.5	PASS
11n20SISO	Ant1	2412	15.040	2404.520	2419.560	0.5	PASS
11n20SISO	Ant1	2437	16.960	2428.520	2445.480	0.5	PASS
11n20SISO	Ant1	2462	15.920	2453.640	2469.560	0.5	PASS
11n40SISO	Ant1	2422	35.600	2404.480	2440.080	0.5	PASS
11n40SISO	Ant1	2437	35.440	2419.480	2454.920	0.5	PASS
11n40SISO	Ant1	2452	35.040	2434.640	2469.680	0.5	PASS

Test Graphs







Occupied Channel Bandwidth Test Result

TestMode	Antenna	Channel Frequency[MHz]	OCB [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
11b	Ant1	2412	13.727	2405.2208	2418.9478	---	---
11b	Ant1	2437	13.794	2430.1317	2443.9257	---	---
11b	Ant1	2462	13.635	2455.0489	2468.6839	---	---
11g	Ant1	2412	16.953	2403.5886	2420.5416	---	---
11g	Ant1	2437	16.943	2428.5884	2445.5314	---	---
11g	Ant1	2462	16.938	2453.4625	2470.4005	---	---
11n20SISO	Ant1	2412	18.030	2403.0238	2421.0538	---	---
11n20SISO	Ant1	2437	18.085	2428.0051	2446.0901	---	---
11n20SISO	Ant1	2462	18.028	2452.9179	2470.9459	---	---
11n40SISO	Ant1	2422	36.390	2403.9303	2440.3203	---	---
11n40SISO	Ant1	2437	36.299	2418.9449	2455.2439	---	---
11n40SISO	Ant1	2452	36.406	2433.7807	2470.1867	---	---

Test Graphs






**Maximum conducted output power
Test Result**


TestMode	Frequency [MHz]	Conducted Average Power[dBm]	Conducted Peak Power[dBm]	Conducted Limit[dBm]	Verdict
11b	2412	16.767	19.256	≤30.00	Pass
	2437	17.358	19.702	≤30.00	Pass
	2462	16.598	19.025	≤30.00	Pass
11g	2412	15.429	20.321	≤30.00	Pass
	2437	15.724	20.383	≤30.00	Pass
	2462	15.308	20.106	≤30.00	Pass
11n20SISO	2412	15.321	20.264	≤30.00	Pass
	2437	15.606	20.277	≤30.00	Pass
	2462	15.193	20.097	≤30.00	Pass
11n40SISO	2422	16.069	22.331	≤30.00	Pass
	2437	16.288	22.641	≤30.00	Pass
	2452	16.201	22.593	≤30.00	Pass

Maximum power spectral density Test Result

TestMode	Antenna	Frequency[MHz]	Result[dBm/3-100kHz]	Limit[dBm/3kHz]	Verdict
11b	Ant1	2412	-5.81	≤8.00	PASS
11b	Ant1	2437	-5.98	≤8.00	PASS
11b	Ant1	2462	-6.24	≤8.00	PASS
11g	Ant1	2412	-9.32	≤8.00	PASS
11g	Ant1	2437	-8.33	≤8.00	PASS
11g	Ant1	2462	-9.12	≤8.00	PASS
11n20SISO	Ant1	2412	-9.28	≤8.00	PASS
11n20SISO	Ant1	2437	-10.21	≤8.00	PASS
11n20SISO	Ant1	2462	-10.35	≤8.00	PASS
11n40SISO	Ant1	2422	-12.68	≤8.00	PASS
11n40SISO	Ant1	2437	-12.37	≤8.00	PASS
11n40SISO	Ant1	2452	-11.90	≤8.00	PASS

Test Graphs






Band edge measurements

Test Result

TestMode	Antenna	ChName	Frequency[MHz]	RefLevel[dBm]	Result[dBm]	Limit[dBm]	Verdict
11b	Ant1	Low	2412	6.72	-43.97	≤-13.28	PASS
11b	Ant1	High	2462	6.18	-54.9	≤-13.82	PASS
11g	Ant1	Low	2412	4.27	-27.3	≤-15.73	PASS
11g	Ant1	High	2462	2.12	-50.81	≤-17.88	PASS
11n20SISO	Ant1	Low	2412	3.06	-25.68	≤-16.94	PASS
11n20SISO	Ant1	High	2462	3.85	-49.58	≤-16.15	PASS
11n40SISO	Ant1	Low	2422	1.59	-34.19	≤-18.42	PASS
11n40SISO	Ant1	High	2452	0.97	-40.11	≤-19.03	PASS

Test Graphs





11n40SISO-Ant1-2422-PASS





11n40SISO-Ant1-2452-PASS


Conducted Spurious Emission Test Result


TestMode	Antenna	Frequency[MHz]	FreqRange [Mhz]	RefLevel [dBm]	Result [dBm]	Limit [dBm]	Verdict
11b	Ant1	2412	0~Reference	6.72	6.72	---	PASS
11b	Ant1	2412	30~1000	6.72	-48.94	≤-13.28	PASS
11b	Ant1	2412	1000~26500	6.72	-40.2	≤-13.28	PASS
11b	Ant1	2437	0~Reference	6.07	6.07	---	PASS
11b	Ant1	2437	30~1000	6.07	-48.57	≤-13.93	PASS
11b	Ant1	2437	1000~26500	6.07	-39.89	≤-13.93	PASS
11b	Ant1	2462	0~Reference	6.16	6.16	---	PASS
11b	Ant1	2462	30~1000	6.16	-49.26	≤-13.84	PASS
11b	Ant1	2462	1000~26500	6.16	-40.07	≤-13.84	PASS
11g	Ant1	2412	0~Reference	2.17	2.17	---	PASS
11g	Ant1	2412	30~1000	2.17	-48.58	≤-17.83	PASS
11g	Ant1	2412	1000~26500	2.17	-39.54	≤-17.83	PASS
11g	Ant1	2437	0~Reference	4.30	4.30	---	PASS
11g	Ant1	2437	30~1000	4.30	-47.35	≤-15.7	PASS
11g	Ant1	2437	1000~26500	4.30	-40.18	≤-15.7	PASS
11g	Ant1	2462	0~Reference	2.80	2.80	---	PASS
11g	Ant1	2462	30~1000	2.80	-48.11	≤-17.2	PASS
11g	Ant1	2462	1000~26500	2.80	-39.79	≤-17.2	PASS
11n20SISO	Ant1	2412	0~Reference	4.05	4.05	---	PASS
11n20SISO	Ant1	2412	30~1000	4.05	-48.8	≤-15.95	PASS
11n20SISO	Ant1	2412	1000~26500	4.05	-39.79	≤-15.95	PASS
11n20SISO	Ant1	2437	0~Reference	4.98	4.98	---	PASS
11n20SISO	Ant1	2437	30~1000	4.98	-48.86	≤-15.02	PASS
11n20SISO	Ant1	2437	1000~26500	4.98	-39.25	≤-15.02	PASS
11n20SISO	Ant1	2462	0~Reference	4.27	4.27	---	PASS
11n20SISO	Ant1	2462	30~1000	4.27	-49.2	≤-15.73	PASS
11n20SISO	Ant1	2462	1000~26500	4.27	-40.23	≤-15.73	PASS
11n40SISO	Ant1	2422	0~Reference	0.99	0.99	---	PASS
11n40SISO	Ant1	2422	30~1000	0.99	-48.95	≤-19.01	PASS
11n40SISO	Ant1	2422	1000~26500	0.99	-39.92	≤-19.01	PASS
11n40SISO	Ant1	2437	0~Reference	1.80	1.80	---	PASS
11n40SISO	Ant1	2437	30~1000	1.80	-47.94	≤-18.2	PASS
11n40SISO	Ant1	2437	1000~26500	1.80	-39.59	≤-18.2	PASS
11n40SISO	Ant1	2452	0~Reference	1.15	1.15	---	PASS
11n40SISO	Ant1	2452	30~1000	1.15	-48.73	≤-18.85	PASS
11n40SISO	Ant1	2452	1000~26500	1.15	-38.95	≤-18.85	PASS


Test Graphs













Duty Cycle Test Result

TestMode	Antenna	Frequency[MHz]	Transmission Duration [ms]	Transmission Period [ms]	Duty Cycle [%]	Factor
11b	Ant1	2412	12.44	12.60	98.73	0.06
11b	Ant1	2437	12.43	12.58	98.81	0.05
11b	Ant1	2462	12.20	12.24	99.67	0.01
11g	Ant1	2412	2.03	2.07	98.07	0.08
11g	Ant1	2437	2.03	2.07	98.07	0.08
11g	Ant1	2462	2.03	2.07	98.07	0.08
11n20SISO	Ant1	2412	1.70	1.74	97.70	0.10
11n20SISO	Ant1	2437	1.70	1.73	98.27	0.08
11n20SISO	Ant1	2462	1.70	1.74	97.70	0.10
11n40SISO	Ant1	2422	0.84	0.89	94.38	0.25
11n40SISO	Ant1	2437	0.84	0.89	94.38	0.25
11n40SISO	Ant1	2452	0.84	0.89	94.38	0.25

Test Graphs






Radiated Spurious Emissions

Test Result Below 1GHz

Project Information			
Mode:	802.11b	Band:	-
Bandwidth	20MHz	Channel	6
SN:	S10ANLJRNBA156	Engineer:	Oushuyan
Remark:	X;		

Test Graph




Data List								
NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Verdict
1	36.16	52.04	-31.03	21.01	40.00	18.99	Horizontal	PASS
2	144.47	57.10	-30.36	26.74	43.50	16.76	Horizontal	PASS
3	175.36	59.69	-28.76	30.93	43.50	12.57	Horizontal	PASS
4	238.95	55.56	-24.99	30.57	47.00	16.43	Horizontal	PASS
5	276.49	52.02	-24.43	27.59	47.00	19.41	Horizontal	PASS
6	310.78	50.16	-23.33	26.83	47.00	20.17	Horizontal	PASS

Project Information

Mode:	802.11b	Band:	-
Bandwidth	20MHz	Channel	6
SN:	S10ANLJRNBA156	Engineer:	Oushuyan
Remark:	X;		

Test Graph




Data List

NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Verdict
1	30.10	60.14	-30.21	29.93	40.00	10.07	Vertical	PASS
2	38.05	56.12	-29.55	26.57	40.00	13.43	Vertical	PASS
3	44.36	52.27	-27.06	25.21	40.00	14.79	Vertical	PASS
4	143.35	56.80	-30.44	26.36	43.50	17.14	Vertical	PASS
5	172.40	58.77	-29.35	29.42	43.50	14.08	Vertical	PASS

Test Result Above 1GHz


Project Information			
Mode:	802.11b	Band:	-
Bandwidth	20MHz	Channel	1
IMEI:	S10ANLJRNBA156	Engineer:	Tian Shuo
Remark:	Z; Power 16		

Test Graph



Data List								
NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Verdict
1	4824.50	42.79	-6.96	35.83	54.00	18.17	Horizontal	PASS
2	6960.50	44.63	-1.53	43.10	54.00	10.90	Horizontal	PASS
3	17974.50	29.37	16.92	46.29	54.00	7.71	Horizontal	PASS
4	2412.87	98.77	-0.18	98.59	-	-	Horizontal	NA
5	4823.50	48.50	-6.97	41.53	74.00	32.47	Horizontal	PASS
6	6960.00	47.82	-1.53	46.29	74.00	27.71	Horizontal	PASS
7	17902.00	39.08	15.91	54.99	74.00	19.01	Horizontal	PASS

Project Information			
Mode:	802.11b	Band:	-
Bandwidth	20MHz	Channel	1
IMEI:	S10ANLJRNBA156	Engineer:	Tian Shuo
Remark:	Z; Power 16		


Test Graph**Data List**

NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Verdict
1	4824.50	52.11	-6.96	45.15	54.00	8.85	Vertical	PASS
2	6960.50	44.16	-1.53	42.63	54.00	11.37	Vertical	PASS
3	17951.00	29.43	16.59	46.02	54.00	7.98	Vertical	PASS
4	2411.13	104.09	-0.20	103.89	-	-	Vertical	NA
5	4824.00	54.37	-6.96	47.41	74.00	26.59	Vertical	PASS
6	6960.00	47.29	-1.53	45.76	74.00	28.24	Vertical	PASS
7	17969.00	37.12	16.85	53.97	74.00	20.03	Vertical	PASS

Project Information

Mode:	802.11b	Band:	-
Bandwidth	20MHz	Channel	6
IMEI:	S10ANLJRNBA156	Engineer:	Tian Shuo
Remark:	Z; Power 16		

Test Graph




Data List

NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Verdict
1	4874.50	43.66	-6.39	37.27	54.00	16.73	Horizontal	PASS
2	6960.50	44.73	-1.53	43.20	54.00	10.80	Horizontal	PASS
3	17977.00	29.61	16.96	46.57	54.00	7.43	Horizontal	PASS
4	2437.87	99.35	0.13	99.48	-	-	Horizontal	NA
5	4874.50	48.23	-6.39	41.84	74.00	32.16	Horizontal	PASS
6	6960.00	48.34	-1.53	46.81	74.00	27.19	Horizontal	PASS
7	17956.50	37.57	16.67	54.24	74.00	19.76	Horizontal	PASS

Project Information

Mode:	802.11b	Band:	-
Bandwidth	20MHz	Channel	6
IMEI:	S10ANLJRNBA156	Engineer:	Tian Shuo
Remark:	Z; Power 16		


Test Graph



Data List


NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Verdict
1	4874.50	48.70	-6.39	42.31	54.00	11.69	Vertical	PASS
2	6960.50	44.91	-1.53	43.38	54.00	10.62	Vertical	PASS
3	17944.50	29.94	16.50	46.44	54.00	7.56	Vertical	PASS
4	2436.13	103.08	0.10	103.18	-	-	Vertical	NA
5	4874.00	51.58	-6.40	45.18	74.00	28.82	Vertical	PASS
6	6960.00	47.95	-1.53	46.42	74.00	27.58	Vertical	PASS
7	17985.50	36.60	17.07	53.67	74.00	20.33	Vertical	PASS

Project Information			
Mode:	802.11b	Band:	-
Bandwidth	20MHz	Channel	11
IMEI:	S10ANLJRNBA156	Engineer:	Tian Shuo
Remark:	Z; Power 16		

Test Graph**Data List**

NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Verdict
1	4924.50	41.69	-6.06	35.63	54.00	18.37	Horizontal	PASS
2	6960.50	44.01	-1.53	42.48	54.00	11.52	Horizontal	PASS
3	17952.50	29.82	16.61	46.43	54.00	7.57	Horizontal	PASS
4	2461.07	98.96	0.40	99.36	-	-	Horizontal	NA
5	4985.00	47.65	-6.09	41.56	74.00	32.44	Horizontal	PASS
6	6960.00	47.61	-1.53	46.08	74.00	27.92	Horizontal	PASS
7	17954.50	36.90	16.64	53.54	74.00	20.46	Horizontal	PASS

Project Information			
Mode:	802.11b	Band:	-
Bandwidth	20MHz	Channel	11
IMEI:	S10ANLJRNBA156	Engineer:	Tian Shuo
Remark:	Z; Power 16		


Test Graph**Data List**

NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Verdict
1	4924.50	51.25	-6.06	45.19	54.00	8.81	Vertical	PASS
2	6960.50	45.15	-1.53	43.62	54.00	10.38	Vertical	PASS
3	17981.00	29.66	17.01	46.67	54.00	7.33	Vertical	PASS
4	2462.87	102.68	0.43	103.11	-	-	Vertical	NA
5	4924.00	53.23	-6.06	47.17	74.00	26.83	Vertical	PASS
6	6959.50	48.07	-1.53	46.54	74.00	27.46	Vertical	PASS
7	17976.50	36.90	16.95	53.85	74.00	20.15	Vertical	PASS

Project Information

Mode:	802.11g	Band:	-
Bandwidth	20MHz	Channel	6
IMEI:	S10ANLJRNBA156	Engineer:	Tian Shuo
Remark:	Z; Power 15		

Test Graph




Data List

NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Verdict
1	5241.50	41.04	-6.07	34.97	54.00	19.03	Horizontal	PASS
2	6960.50	44.71	-1.53	43.18	54.00	10.82	Horizontal	PASS
3	17952.00	30.02	16.61	46.63	54.00	7.37	Horizontal	PASS
4	2436.20	99.66	0.10	99.76	-	-	Horizontal	NA
5	5317.00	48.20	-5.60	42.60	74.00	31.40	Horizontal	PASS
6	6758.00	46.97	-1.33	45.64	74.00	28.36	Horizontal	PASS
7	17969.50	37.38	16.85	54.23	74.00	19.77	Horizontal	PASS

Project Information

Mode:	802.11g	Band:	-
Bandwidth	20MHz	Channel	6
IMEI:	S10ANLJRNBA156	Engineer:	Tian Shuo
Remark:	Z; Power 15		

Test Graph




Data List

NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Verdict
1	4880.00	40.62	-6.34	34.28	54.00	19.72	Vertical	PASS
2	6960.50	45.54	-1.53	44.01	54.00	9.99	Vertical	PASS
3	17933.50	29.96	16.34	46.30	54.00	7.70	Vertical	PASS
4	2434.73	103.51	0.09	103.60	-	-	Vertical	NA
5	4879.50	48.47	-6.34	42.13	74.00	31.87	Vertical	PASS
6	6960.00	48.96	-1.53	47.43	74.00	26.57	Vertical	PASS
7	17987.00	36.73	17.10	53.83	74.00	20.17	Vertical	PASS

Project Information

Mode:	802.11n20	Band:	-
Bandwidth	20MHz	Channel	6
IMEI:	S10ANLJRNBA156	Engineer:	Tian Shuo
Remark:	Z; Power 15		


Test Graph



Data List

NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Verdict
1	4631.50	40.77	-7.28	33.49	54.00	20.51	Horizontal	PASS
2	6960.50	43.69	-1.53	42.16	54.00	11.84	Horizontal	PASS
3	17982.00	29.35	17.03	46.38	54.00	7.62	Horizontal	PASS
4	2438.33	100.44	0.13	100.57	-	-	Horizontal	NA
5	4632.50	48.47	-7.28	41.19	74.00	32.81	Horizontal	PASS
6	6960.50	47.99	-1.53	46.46	74.00	27.54	Horizontal	PASS
7	17932.50	37.58	16.33	53.91	74.00	20.09	Horizontal	PASS

Project Information			
Mode:	802.11n20	Band:	-
Bandwidth	20MHz	Channel	6
IMEI:	S10ANLJRNBA156	Engineer:	Tian Shuo
Remark:	Z; Power 15		


Test Graph**Data List**

NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Verdict
1	4601.00	40.56	-7.36	33.20	54.00	20.80	Vertical	PASS
2	6960.50	43.71	-1.53	42.18	54.00	11.82	Vertical	PASS
3	17935.50	30.38	16.37	46.75	54.00	7.25	Vertical	PASS
4	2435.73	105.31	0.10	105.41	-	-	Vertical	NA
5	4547.00	48.53	-7.67	40.86	74.00	33.14	Vertical	PASS
6	6960.00	47.10	-1.53	45.57	74.00	28.43	Vertical	PASS
7	17982.00	36.79	17.03	53.82	74.00	20.18	Vertical	PASS

Project Information

Mode:	802.11n40	Band:	-
Bandwidth	40MHz	Channel	6
IMEI:	S10ANLJRNBA156	Engineer:	Tian Shuo
Remark:	Z; Power 15		

Test Graph




Data List

NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Verdict
1	5405.00	41.54	-5.00	36.54	54.00	17.46	Horizontal	PASS
2	8837.00	37.73	1.16	38.89	54.00	15.11	Horizontal	PASS
3	17962.50	30.05	16.75	46.80	54.00	7.20	Horizontal	PASS
4	2438.93	98.75	0.15	98.90	-	-	Horizontal	NA
5	5253.50	49.13	-6.02	43.11	74.00	30.89	Horizontal	PASS
6	8254.00	45.26	0.94	46.20	74.00	27.80	Horizontal	PASS
7	17985.00	36.92	17.07	53.99	74.00	20.01	Horizontal	PASS

Project Information

Mode:	802.11n40	Band:	-
Bandwidth	40MHz	Channel	6
IMEI:	S10ANLJRNBA156	Engineer:	Tian Shuo
Remark:	Z; Power 15		

Test Graph



Data List


NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Verdict
1	5683.00	40.81	-3.78	37.03	54.00	16.97	Vertical	PASS
2	9565.50	36.09	3.18	39.27	54.00	14.73	Vertical	PASS
3	17974.50	29.63	16.92	46.55	54.00	7.45	Vertical	PASS
4	2438.67	102.47	0.13	102.60	-	-	Vertical	NA
5	5404.00	50.28	-5.01	45.27	74.00	28.73	Vertical	PASS
6	9584.50	44.45	3.24	47.69	74.00	26.31	Vertical	PASS
7	17963.50	37.37	16.76	54.13	74.00	19.87	Vertical	PASS

Radiated Band Edge

Test Result


Project Information			
Mode:	802.11b	Band:	-
Bandwidth	20MHz	Channel	1
SN:	S10ANLJRNBA156	Engineer:	Oushuyan
Remark:	Z; Power 16		

Test Graph




Data List								
NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Verdict
1	2340.18	37.75	-0.70	37.05	54.00	16.95	Horizontal	PASS
2	2366.28	37.89	-0.53	37.36	54.00	16.64	Horizontal	PASS
3	2388.91	38.03	-0.39	37.64	54.00	16.36	Horizontal	PASS
4	2343.28	49.36	-0.68	48.68	74.00	25.32	Horizontal	PASS
5	2365.50	49.82	-0.55	49.27	74.00	24.73	Horizontal	PASS
6	2386.82	49.81	-0.41	49.40	74.00	24.60	Horizontal	PASS

Project Information			
Mode:	802.11b	Band:	-
Bandwidth	20MHz	Channel	1
SN:	S10ANLJRNBA156	Engineer:	Oushuyan
Remark:	Z; Power 16		

Test Graph**Data List**


NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Verdict
1	2340.55	37.85	-0.70	37.15	54.00	16.85	Vertical	PASS
2	2383.01	38.35	-0.44	37.91	54.00	16.09	Vertical	PASS
3	2386.89	38.88	-0.41	38.47	54.00	15.53	Vertical	PASS
4	2343.54	50.76	-0.68	50.08	74.00	23.92	Vertical	PASS
5	2382.64	50.08	-0.44	49.64	74.00	24.36	Vertical	PASS
6	2389.02	49.79	-0.39	49.40	74.00	24.60	Vertical	PASS
7	2411.13	103.55	-0.20	103.35	-	-	Vertical	NA

Project Information			
Mode:	802.11b	Band:	-
Bandwidth	20MHz	Channel	11
SN:	S10ANLJRNBA156	Engineer:	Oushuyan
Remark:	Z; Power 16		

Test Graph**Data List**


NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Verdict
1	2483.55	37.92	0.68	38.60	54.00	15.40	Horizontal	PASS
2	2484.90	37.86	0.70	38.56	54.00	15.44	Horizontal	PASS
3	2491.91	37.62	0.78	38.40	54.00	15.60	Horizontal	PASS
4	2483.67	50.63	0.68	51.31	74.00	22.69	Horizontal	PASS
5	2484.70	51.30	0.70	52.00	74.00	22.00	Horizontal	PASS
6	2492.24	50.00	0.79	50.79	74.00	23.21	Horizontal	PASS

Project Information			
Mode:	802.11b	Band:	-
Bandwidth	20MHz	Channel	11
SN:	S10ANLJRNBA156	Engineer:	Oushuyan
Remark:	Z; Power 16		

Test Graph**Data List**


NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Verdict
1	2483.84	38.45	0.69	39.14	54.00	14.86	Vertical	PASS
2	2492.53	37.90	0.79	38.69	54.00	15.31	Vertical	PASS
3	2497.65	37.75	0.85	38.60	54.00	15.40	Vertical	PASS
4	2485.11	50.23	0.70	50.93	74.00	23.07	Vertical	PASS
5	2491.60	49.89	0.78	50.67	74.00	23.33	Vertical	PASS
6	2497.02	49.49	0.85	50.34	74.00	23.66	Vertical	PASS

Project Information			
Mode:	802.11g	Band:	-
Bandwidth	20MHz	Channel	1
SN:	S10ANLJRNBA156	Engineer:	Oushuyan
Remark:	Z; Power 15		

Test Graph**Data List**


NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Verdict
1	2381.03	37.75	-0.45	37.30	54.00	16.70	Horizontal	PASS
2	2387.16	39.46	-0.41	39.05	54.00	14.95	Horizontal	PASS
3	2388.80	40.48	-0.39	40.09	54.00	13.91	Horizontal	PASS
4	2382.38	48.89	-0.44	48.45	74.00	25.55	Horizontal	PASS
5	2386.52	49.84	-0.41	49.43	74.00	24.57	Horizontal	PASS
6	2389.36	51.54	-0.39	51.15	74.00	22.85	Horizontal	PASS

Project Information			
Mode:	802.11g	Band:	-
Bandwidth	20MHz	Channel	1
SN:	S10ANLJRNBA156	Engineer:	Oushuyan
Remark:	Z; Power 15		

Test Graph**Data List**


NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Verdict
1	2383.61	39.65	-0.44	39.21	54.00	14.79	Vertical	PASS
2	2387.23	42.63	-0.41	42.22	54.00	11.78	Vertical	PASS
3	2389.55	44.61	-0.39	44.22	54.00	9.78	Vertical	PASS
4	2384.13	51.44	-0.42	51.02	74.00	22.98	Vertical	PASS
5	2386.71	52.83	-0.41	52.42	74.00	21.58	Vertical	PASS
6	2389.47	56.15	-0.39	55.76	74.00	18.24	Vertical	PASS

Project Information			
Mode:	802.11g	Band:	-
Bandwidth	20MHz	Channel	11
SN:	S10ANLJRNBA156	Engineer:	Oushuyan
Remark:	Z; Power 15		

Test Graph**Data List**


NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Verdict
1	2484.61	40.15	0.70	40.85	54.00	13.15	Horizontal	PASS
2	2488.04	38.21	0.73	38.94	54.00	15.06	Horizontal	PASS
3	2493.06	37.63	0.79	38.42	54.00	15.58	Horizontal	PASS
4	2484.44	51.88	0.69	52.57	74.00	21.43	Horizontal	PASS
5	2487.92	50.28	0.73	51.01	74.00	22.99	Horizontal	PASS
6	2492.58	49.46	0.79	50.25	74.00	23.75	Horizontal	PASS

Project Information			
Mode:	802.11g	Band:	-
Bandwidth	20MHz	Channel	11
SN:	S10ANLJRNBA156	Engineer:	Oushuyan
Remark:	Z; Power 15		

Test Graph**Data List**


NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Verdict
1	2483.79	42.39	0.69	43.08	54.00	10.92	Vertical	PASS
2	2484.85	41.57	0.70	42.27	54.00	11.73	Vertical	PASS
3	2487.97	39.30	0.73	40.03	54.00	13.97	Vertical	PASS
4	2483.89	53.29	0.69	53.98	74.00	20.02	Vertical	PASS
5	2484.46	52.96	0.69	53.65	74.00	20.35	Vertical	PASS
6	2486.46	51.43	0.72	52.15	74.00	21.85	Vertical	PASS

Project Information			
Mode:	802.11n20	Band:	-
Bandwidth	20MHz	Channel	1
SN:	S10ANLJRNBA156	Engineer:	Oushuyan
Remark:	Z; Power 15		

Test Graph**Data List**


NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Verdict
1	2383.68	38.18	-0.44	37.74	54.00	16.26	Horizontal	PASS
2	2386.71	39.19	-0.41	38.78	54.00	15.22	Horizontal	PASS
3	2389.43	41.58	-0.39	41.19	54.00	12.81	Horizontal	PASS
4	2385.66	49.70	-0.42	49.28	74.00	24.72	Horizontal	PASS
5	2387.27	52.43	-0.41	52.02	74.00	21.98	Horizontal	PASS
6	2389.81	54.16	-0.39	53.77	74.00	20.23	Horizontal	PASS

Project Information			
Mode:	802.11n20	Band:	-
Bandwidth	20MHz	Channel	1
SN:	S10ANLJRNBA156	Engineer:	Oushuyan
Remark:	Z; Power 15		

Test Graph**Data List**


NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Verdict
1	2383.76	40.01	-0.43	39.58	54.00	14.42	Vertical	PASS
2	2386.67	42.35	-0.41	41.94	54.00	12.06	Vertical	PASS
3	2389.81	46.72	-0.39	46.33	54.00	7.67	Vertical	PASS
4	2385.77	52.23	-0.42	51.81	74.00	22.19	Vertical	PASS
5	2388.80	56.90	-0.39	56.51	74.00	17.49	Vertical	PASS
6	2389.88	61.28	-0.39	60.89	74.00	13.11	Vertical	PASS

Project Information			
Mode:	802.11n20	Band:	-
Bandwidth	20MHz	Channel	11
SN:	S10ANLJRNBA156	Engineer:	Oushuyan
Remark:	Z; Power 15		

Test Graph**Data List**


NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Verdict
1	2484.01	40.14	0.69	40.83	54.00	13.17	Horizontal	PASS
2	2485.42	39.43	0.70	40.13	54.00	13.87	Horizontal	PASS
3	2486.43	38.81	0.72	39.53	54.00	14.47	Horizontal	PASS
4	2483.94	51.46	0.69	52.15	74.00	21.85	Horizontal	PASS
5	2485.69	50.57	0.70	51.27	74.00	22.73	Horizontal	PASS
6	2486.53	50.13	0.72	50.85	74.00	23.15	Horizontal	PASS

Project Information			
Mode:	802.11n20	Band:	-
Bandwidth	20MHz	Channel	11
SN:	S10ANLJRNBA156	Engineer:	Oushuyan
Remark:	Z; Power 15		

Test Graph**Data List**


NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Verdict
1	2483.89	41.96	0.69	42.65	54.00	11.35	Vertical	PASS
2	2485.86	40.28	0.71	40.99	54.00	13.01	Vertical	PASS
3	2488.45	38.74	0.74	39.48	54.00	14.52	Vertical	PASS
4	2484.06	54.05	0.69	54.74	74.00	19.26	Vertical	PASS
5	2485.86	55.44	0.71	56.15	74.00	17.85	Vertical	PASS
6	2488.64	49.70	0.74	50.44	74.00	23.56	Vertical	PASS

Project Information			
Mode:	802.11n40	Band:	-
Bandwidth	40MHz	Channel	3
SN:	S10ANLJRNBA156	Engineer:	Oushuyan
Remark:	Z; Power 15		

Test Graph**Data List**


NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Verdict
1	2384.47	44.69	-0.42	44.27	54.00	9.73	Horizontal	PASS
2	2387.64	46.28	-0.41	45.87	54.00	8.13	Horizontal	PASS
3	2389.53	47.80	-0.39	47.41	54.00	6.59	Horizontal	PASS
4	2385.00	55.98	-0.42	55.56	74.00	18.44	Horizontal	PASS
5	2387.82	57.85	-0.41	57.44	74.00	16.56	Horizontal	PASS
6	2388.92	57.39	-0.39	57.00	74.00	17.00	Horizontal	PASS

Project Information			
Mode:	802.11n40	Band:	-
Bandwidth	40MHz	Channel	3
SN:	S10ANLJRNBA156	Engineer:	Oushuyan
Remark:	Z; Power 15		

Test Graph**Data List**


NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Verdict
1	2385.71	50.46	-0.42	50.04	54.00	3.96	Vertical	PASS
2	2388.39	50.97	-0.41	50.56	54.00	3.44	Vertical	PASS
3	2389.80	52.33	-0.39	51.94	54.00	2.06	Vertical	PASS
4	2386.15	61.29	-0.42	60.87	74.00	13.13	Vertical	PASS
5	2388.70	61.58	-0.40	61.18	74.00	12.82	Vertical	PASS
6	2389.45	62.44	-0.39	62.05	74.00	11.95	Vertical	PASS

Project Information			
Mode:	802.11n40	Band:	-
Bandwidth	40MHz	Channel	9
SN:	S10ANLJRNBA156	Engineer:	Oushuyan
Remark:	Z; Power 15		

Test Graph**Data List**

NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Verdict
1	2483.88	45.28	0.69	45.97	54.00	8.03	Horizontal	PASS
2	2485.20	43.95	0.70	44.65	54.00	9.35	Horizontal	PASS
3	2486.73	41.84	0.72	42.56	54.00	11.44	Horizontal	PASS
4	2483.71	55.29	0.68	55.97	74.00	18.03	Horizontal	PASS
5	2485.47	55.06	0.70	55.76	74.00	18.24	Horizontal	PASS
6	2485.98	53.74	0.71	54.45	74.00	19.55	Horizontal	PASS

Project Information			
Mode:	802.11n40	Band:	-
Bandwidth	40MHz	Channel	9
SN:	S10ANLJRNBA156	Engineer:	Oushuyan
Remark:	Z; Power 15		

Test Graph**Data List**

NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Verdict
1	2483.67	48.00	0.68	48.68	54.00	5.32	Vertical	PASS
2	2485.13	46.85	0.70	47.55	54.00	6.45	Vertical	PASS
3	2486.84	45.06	0.72	45.78	54.00	8.22	Vertical	PASS
4	2484.15	59.24	0.69	59.93	74.00	14.07	Vertical	PASS
5	2485.07	58.88	0.70	59.58	74.00	14.42	Vertical	PASS
6	2486.09	57.25	0.71	57.96	74.00	16.04	Vertical	PASS

~The End~