



FCC PART 15.247

TEST REPORT

For

Modern Electronics Factory Limited.

Flat C, 10/F., Phase 4, Kwun Tong Industrial Centre, 472-478 Kwun Tong Road,
Kwun Tong, Kowloon, Hong Kong

FCC ID: SSMMEF1208

Report Type: Original Report	Product Type: Portable Bluetooth Wireless Speaker
Test Engineer: <u>Rocky Kang</u>	
Report Number: <u>RSZ140207801-00B</u>	
Report Date: <u>2014-02-19</u>	
Reviewed By: <u>Jimmy Xiao</u>	
Prepared By: <u>RF Engineer</u>	
Bay Area Compliance Laboratories Corp. (Shenzhen) 6/F, the 3rd Phase of WanLi Industrial Building ShiHua Road, FuTian Free Trade Zone Shenzhen, Guangdong, China Tel: +86-755-33320018 Fax: +86-755-33320008 www.baclcorp.com.cn	

Note: This test report is prepared for the customer shown above and for the equipment described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp.

TABLE OF CONTENTS

GENERAL INFORMATION.....	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT).....	4
OBJECTIVE	4
RELATED SUBMITTAL(S)/GRANT(S).....	4
TEST METHODOLOGY	4
TEST FACILITY	5
SYSTEM TEST CONFIGURATION.....	6
DESCRIPTION OF TEST CONFIGURATION	6
EUT EXERCISE SOFTWARE	6
SPECIAL ACCESSORIES.....	6
EQUIPMENT MODIFICATIONS	6
SUPPORT EQUIPMENT LIST AND DETAILS	6
EXTERNAL I/O CABLE.....	6
BLOCK DIAGRAM OF TEST SETUP	7
SUMMARY OF TEST RESULTS.....	8
FCC §15.247 (i) & §2.1093 – RF EXPOSURE	9
APPLICABLE STANDARD	9
RESULT	9
FCC §15.203 – ANTENNA REQUIREMENT	10
APPLICABLE STANDARD	10
ANTENNA CONNECTOR CONSTRUCTION	10
FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS	11
APPLICABLE STANDARD	11
MEASUREMENT UNCERTAINTY.....	11
EUT SETUP	11
EMI TEST RECEIVER SETUP.....	12
TEST PROCEDURE	12
TEST EQUIPMENT LIST AND DETAILS.....	12
CORRECTED FACTOR & MARGIN CALCULATION	12
TEST RESULTS SUMMARY.....	13
TEST DATA	13
FCC §15.205, §15.209 & §15.247(d) – RADIATED EMISSIONS.....	16
APPLICABLE STANDARD	16
MEASUREMENT UNCERTAINTY.....	16
EUT SETUP	16
EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP	17
TEST PROCEDURE	17
CORRECTED AMPLITUDE & MARGIN CALCULATION	17
TEST EQUIPMENT LIST AND DETAILS.....	17
TEST RESULTS SUMMARY.....	18
TEST DATA	18
FCC §15.247(a) (1)-CHANNEL SEPARATION TEST	21
APPLICABLE STANDARD	21
TEST PROCEDURE	21
TEST EQUIPMENT LIST AND DETAILS.....	21

TEST DATA	21
FCC §15.247(a) (1) – 20 dB EMISSION BANDWIDTH.....	28
APPLICABLE STANDARD	28
TEST PROCEDURE	28
TEST EQUIPMENT LIST AND DETAILS.....	28
TEST DATA	28
FCC §15.247(a) (1) (iii)-QUANTITY OF HOPPING CHANNEL TEST	34
APPLICABLE STANDARD	34
TEST PROCEDURE	34
TEST EQUIPMENT LIST AND DETAILS.....	34
TEST DATA	34
FCC §15.247(a) (1) (iii) - TIME OF OCCUPANCY (DWELL TIME).....	37
APPLICABLE STANDARD	37
TEST PROCEDURE	37
TEST EQUIPMENT LIST AND DETAILS.....	37
TEST DATA	37
FCC §15.247(b) (1) - PEAK OUTPUT POWER MEASUREMENT.....	53
APPLICABLE STANDARD	53
TEST PROCEDURE	53
TEST EQUIPMENT LIST AND DETAILS.....	53
TEST DATA	53
FCC §15.247(d) - BAND EDGES TESTING	59
APPLICABLE STANDARD	59
TEST PROCEDURE	59
TEST EQUIPMENT LIST AND DETAILS.....	59
TEST DATA	60
PRODUCT SIMILARITY DECLARATION LETTER.....	64

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

The *Modern Electronics Factory Limited.*'s product, model number: *SMPS-621*(FCC ID: *SSMMEF1208*) or the "EUT" in this report was a *Portable Bluetooth Wireless Speaker*, which was measured approximately: 8.2 cm (L) x 8.2 cm (W) x 8.2 cm (H), rated with input voltage: DC 3.7 V rechargeable Li-ion battery or DC 5.0V charging from PC.

Note: The product, series model SMPS-621, there are two colors, blue and rose red, and the only difference between them is the appearance color. Color blue was selected for fully testing.

**All measurement and test data in this report was gathered from production sample serial number: 1402001 (Assigned by BACL, Shenzhen). The EUT supplied by the applicant was received on 2014-02-07.*

Objective

This test report is prepared on behalf of *Modern Electronics Factory Limited.* in accordance with Part 2-Subpart J, Part 15-Subparts A, B and C of the Federal Communication Commissions rules.

The tests were performed in order to determine compliance with FCC Part 15, Subpart C, section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

Related Submittal(s)/Grant(s)

No related submittal

Test Methodology

All measurements contained in this report were conducted with ANSI C63.4-2009, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.

All emissions measurement was performed at Bay Area Compliance Laboratories Corp. (Shenzhen). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Measurement uncertainty with radiated emission is 5.91 dB for 30MHz-1GHz, and 4.92 dB for above 1GHz, 1.95dB for conducted measurement.

Test Facility

The test site used by Bay Area Compliance Laboratories Corp. (Shenzhen) to collect test data is located on the 6/F, the 3rd Phase of WanLi Industrial Building, ShiHua Road, FuTian Free Trade Zone Shenzhen, Guangdong, China.

Test site at Bay Area Compliance Laboratories Corp. (Shenzhen) has been fully described in reports submitted to the Federal Communication Commission (FCC). The details of these reports have been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on December 06, 2010. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2009.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 382179. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

EUT Exercise Software

ASTTestTool.exe

Special Accessories

No special accessory.

Equipment Modifications

No modification was made to the EUT tested.

Support Equipment List and Details


Manufacturer	Description	Model	Serial Number
DELL	PC	VOSTRO 220S	127BP2X
DELL	LCD Monitor	E178WFPC	CN-OWY564-64180-7C4-2SQH
DELL	Keyboard	L100	CNORH656658907BL05DC
DELL	Mouse	MOC5UO	G1900NKD
SAST	Modem	AEM-2100	0293

External I/O Cable

Cable Description	Length (m)	From/Port	To
Shielding Detachable USB Cable	1.5	Host PC	Mouse
Shielding Detachable Serial Cable	1.2	Host PC	Modem
Shielding Detachable K/B Cable	1.5	Host PC	Keyboard
Shielding Detachable VGA Cable	1.5	Host PC	LCD Monitor
Unshielding Detachable USB Cable	0.8	EUT	Host PC

Block Diagram of Test Setup

For conducted emission



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§15.247 (i), §2.1093	RF Exposure	Compliance
§15.203	Antenna Requirement	Compliance
§15.207(a)	AC Line Conducted Emissions	Compliance
§15.205, §15.209 & §15.247(d)	Radiated Emissions	Compliance
§15.247(a)(1)	20 dB Emission Bandwidth	Compliance
§15.247(a)(1)	Channel Separation Test	Compliance
§15.247(a)(1)(iii)	Time of Occupancy (Dwell Time)	Compliance
§15.247(a)(1)(iii)	Quantity of hopping channel Test	Compliance
§15.247(b)(1)	Peak Output Power Measurement	Compliance
§15.247(d)	Band edges	Compliance

FCC §15.247 (i) & §2.1093 – RF EXPOSURE

Applicable Standard

According to FCC §2.1093 and §1.1307(b) (1), systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

According to KDB 447498 D01 General RF Exposure Guidance v05

Result

According to FCC KDB 447498 D01 General RF Exposure Guidance v05 generic portable criteria

The distance between antenna and test point is 5 mm
The Max output power: -0.54 dBm (0.883 mW)

According to the Appendix A of KDB 447498, the exclusion thresholds for 2450 MHz is 10 mW.

Conclusion:

The time-averaged output power is 0.883 mW <the exclusion thresholds 10 mW, so stand-alone SAR evaluation is not required.

FCC §15.203 – ANTENNA REQUIREMENT

Applicable Standard

According to FCC § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Antenna Connector Construction

The EUT has a PCB antenna arrangement for bluetooth, which was permanently attached and the antenna gain is 0 dBi, fulfill the requirement of this section. Please refer to the internal photos.

Result: Compliance.

FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS

Applicable Standard

FCC §15.207(a)


Measurement Uncertainty

Input quantities to be considered for conducted disturbance measurements maybe receiver reading, attenuation of the connection between AMN/ISN and receiver, AMN/ISN voltage division factor, AMN/ISN VDF frequency interpolation and receiver related input quantities, etc.

Based on CISPR 16-4-2:2011, the expended combined standard uncertainty of conducted disturbance test at Bay Area Compliance Laboratories Corp. (Shenzhen) is shown as below. And the uncertainty will not be taken into consideration for the test data recorded in the report.

Port	Measurement uncertainty
AC Mains	3.26 dB (k=2, 95% level of confidence)
CAT 3	3.70 dB (k=2, 95% level of confidence)
CAT 5	3.86 dB (k=2, 95% level of confidence)
CAT 6	4.64 dB (k=2, 95% level of confidence)

EUT Setup



- Note: 1. Support units were connected to second LISN.
2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The measurement procedure of EUT setup is according with ANSI C63.4-2009. The related limit was specified in FCC Part 15.207.

The spacing between the peripherals was 10 cm.

The PC was connected to a 120 VAC/60 Hz power source.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Test Procedure

During the conducted emission test, the PC was connected to the first LISN and the other relevant equipments were connected to the second LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All data was recorded in the Quasi-peak and average detection mode.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCS30	100176	2013-06-17	2014-06-17
Rohde & Schwarz	LISN	ENV216	3560.6650.12-101613-Yb	2013-05-07	2014-05-07
Rohde & Schwarz	LISN	ESH2-Z5	892107/021	2013-08-22	2014-08-22
Rohde & Schwarz	Transient Limiter	ESH3Z2	DE25985	2013-10-15	2014-10-15
Rohde & Schwarz	CE Test software	EMC 32	V8.53	-	-

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

Corrected Factor & Margin Calculation

The Corrected factor is calculated by adding LISN/ISN VDF (Voltage Division Factor), Cable Loss and Transient Limiter Attenuation. The basic equation is as follows:

$$\text{Correction Factor} = \text{LISN VDF} + \text{Cable Loss} + \text{Transient Limiter Attenuation}$$

The “Margin” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7 dB means the emission is 7 dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Part 15.207, with the worst margin reading of:

7.8 dB at 8.849250 MHz in the **Line** conducted mode

Refer to CISPR16-4-2:2011 and CISPR 16-4-1:2009, the measured level is in compliance with the limit if

$$L_m + U_{(Lm)} \leq L_{lim} + U_{cisp}$$

in BACL, $U_{(Lm)}$ is less than U_{cisp} , if L_m is less than L_{lim} , it implies that the EUT complies with the limit.

Test Data

Environmental Conditions


Temperature:	20 °C
Relative Humidity:	50 %
ATM Pressure:	100.1 kPa

The testing was performed by Rocky Kang on 2014-02-12.

EUT operation mode: Transmitting & Charging

AC 120 V, 60 Hz, Line:


EMI Auto Test L



Frequency (MHz)	Corrected Amplitude (dB μ V)	Correction Factor (dB)	Limit (dB μ V)	Margin (dB)	Detector (PK/Ave./QP)
0.436450	41.6	19.6	57.1	15.5	QP
0.436450	25.1	19.6	47.1	22.0	Ave.
0.470890	44.7	19.6	56.5	11.8	QP
0.470890	29.7	19.6	46.5	16.8	Ave.
0.506470	43.3	19.6	56.0	12.7	QP
0.506470	29.8	19.6	46.0	16.2	Ave.
0.586670	39.3	19.6	56.0	16.7	QP
0.586670	23.6	19.6	46.0	22.4	Ave.
7.946750	41.2	19.7	60.0	18.8	QP
7.946750	38.1	19.7	50.0	11.9	Ave.
8.849250	45.0	19.7	60.0	15.0	QP
8.849250	42.2	19.7	50.0	7.8	Ave.

AC 120V, 60 Hz, Neutral:

EMI Auto Test N



Frequency (MHz)	Corrected Amplitude (dB μ V)	Correction Factor (dB)	Limit (dB μ V)	Margin (dB)	Detector (PK/Ave./QP)
0.201500	42.6	19.6	63.5	21.0	QP
0.201500	41.9	19.6	60.2	11.7	Ave.
0.301470	38.2	19.5	60.0	22.0	QP
0.301470	35.6	19.5	60.0	14.6	Ave.
7.544750	38.4	19.8	60.0	21.6	QP
7.544750	33.9	19.8	60.0	16.2	Ave.
7.953190	40.4	19.8	53.5	19.6	QP
7.953190	39.2	19.8	50.2	10.9	Ave.
8.957130	40.8	19.8	50.0	19.2	QP
8.957130	38.2	19.8	50.0	11.9	Ave.
9.253510	38.6	19.8	50.0	21.4	QP
9.253510	31.4	19.8	50.0	18.6	Ave.

Note:

- 1) Correction Factor =LISN VDF (Voltage Division Factor) + Cable Loss + Transient Limiter Attenuation
The corrected factor has been input into the transducer of the test software.
- 2) Corrected Amplitude = Reading + Correction Factor
- 3) Margin = Limit – Corrected Amplitude

FCC §15.205, §15.209 & §15.247(d) – RADIATED EMISSIONS

Applicable Standard


FCC §15.205; §15.209; §15.247(d)

Measurement Uncertainty

All measurements involve certain levels of uncertainties, especially in field of EMC. The factors contributing to uncertainties are spectrum analyzer, cable loss, antenna factor calibration, antenna directivity, antenna factor variation with height, antenna phase center variation, antenna factor frequency interpolation, measurement distance variation, site imperfections, mismatch (average), and system repeatability.

Based on CISPR 16-4-2:2011, the expended combined standard uncertainty of radiation emissions at Bay Area Compliance Laboratories Corp. (Shenzhen) is 5.91 dB for 30MHz-1GHz, and 4.92 dB for above 1GHz. And this uncertainty will not be taken into consideration for the test data recorded in the report.

EUT Setup



The radiated emission tests were performed in the 3 meters, using the setup accordance with the ANSI C63.4-2009. The specification used was the FCC 15.209 and FCC 15.247 limits.

EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 30 MHz to 25 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Detector
30 MHz – 1000 MHz	100 kHz	300 kHz	120 kHz	QP
Above 1 GHz	1 MHz	3 MHz	/	PK
	1 MHz	10 Hz	/	Ave.

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz -1 GHz and peak and Average detection modes for frequencies above 1 GHz.

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude} = \text{Meter Reading} + \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “Margin” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
HP	Amplifier	8447E	1937A01046	2013-09-30	2014-09-30
Rohde & Schwarz	EMI Test Receiver	ESCI	101122	2013-09-17	2014-09-17
Sunol Sciences	Broadband Antenna	JB1	A040904-2	2011-11-28	2014-11-27
Mini	Amplifier	ZVA-183-S+	5969001149	2013-04-03	2014-04-03
A.H. System	Horn Antenna	SAS-200/571	135	2012-02-11	2015-02-10
Rohde & Schwarz	Signal Analyzer	FSIQ26	8386001028	2013-11-12	2014-11-12
the electro-Mechanics Co.	Horn Antenna	3116	9510-2270	2013-10-14	2016-10-13
Rohde & Schwarz	CE Test software	EMC 32	V9.10	-	-

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Title 47, Part 15, Subpart C, section 15.205, 15.209 and 15.247.

14.60 dB at 7206.0 MHz in the Horizontal polarization

Refer to CISPR16-4-2:2011 and CISPR 16-4-1:2009, the measured level is in compliance with the limit if

$$L_m + U_{(Lm)} \leq L_{lim} + U_{cisp}$$

in BACL, $U_{(Lm)}$ is less than $+ U_{cisp}$, if L_m is less than L_{lim} , it implies that the EUT complies with the limit.

Test Data

Environmental Conditions

Temperature:	20 °C
Relative Humidity:	50 %
ATM Pressure:	100.1 kPa

The testing was performed by Rocky Kang on 2014-02-12.

EUT operation mode: Transmitting

30 MHz -25 GHz: (Scan with GFSK, $\pi/4$ -DQPSK, 8-DPSK, the worst case is BDR Mode (GFSK))

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB)	Corrected Amplitude (dB μ V/m)	FCC Part 15.247/205/209	
	Reading (dB μ V)	Detector (PK/QP/Ave.)		Height (m)	Polar (H/V)			Limit (dB μ V/m)	Margin (dB)
Low Channel (2402 MHz)									
247.2	46.12	QP	73	1.3	H	-15.8	29.65	46	16.35
2402.0	83.76	PK	126	1.3	H	5.48	89.24	/	/
2402.0	74.47	Ave.	126	1.3	H	5.48	79.95	/	/
2402.0	75.57	PK	129	2.3	V	5.48	81.05	/	/
2402.0	67.05	Ave.	129	2.3	V	5.48	72.53	/	/
2323.7	38.78	PK	213	1.9	V	4.99	43.77	74	30.23
2323.7	23.71	Ave.	213	1.9	V	4.99	28.70	54	25.30
2372.6	35.66	PK	19	1.3	H	5.48	41.14	74	32.86
2372.6	20.47	Ave.	19	1.3	H	5.48	25.95	54	28.05
2485.2	37.89	PK	320	2.3	H	7.21	45.10	74	28.90
2485.2	21.43	Ave.	320	2.3	H	7.21	28.64	54	25.36
4804.0	39.19	PK	93	2.5	V	12.44	51.63	74	22.37
4804.0	26.04	Ave.	93	2.5	V	12.44	38.48	54	15.52
7206.0	36.72	PK	290	1.8	H	17.06	53.78	74	20.22
7206.0	22.34	Ave.	290	1.8	H	17.06	39.40	54	14.60
9608.0	35.29	PK	294	2.0	V	19.28	54.57	74	19.43
9608.0	20.03	Ave.	294	2.0	V	19.28	39.31	54	14.69
Middle Channel (2441 MHz)									
247.2	46.32	QP	92	1.2	H	-15.8	30.52	46	15.48
2441.0	76.38	PK	171	2.1	H	6.13	82.51	/	/
2441.0	63.62	Ave.	171	2.1	H	6.13	69.75	/	/
2441.0	74.68	PK	347	1.6	V	6.13	80.81	/	/
2441.0	66.30	Ave.	347	1.6	V	6.13	72.43	/	/
2366.0	38.33	PK	34	2.4	V	5.48	43.81	74	30.19
2366.0	27.46	Ave.	34	2.4	V	5.48	32.94	54	21.06
2489.8	38.22	PK	99	1.6	H	7.21	45.43	74	28.57
2489.8	24.51	Ave.	99	1.6	H	7.21	31.72	54	22.28
2498.4	37.10	PK	49	1.4	H	7.21	44.31	74	29.69
2498.4	25.93	Ave.	49	1.4	H	7.21	33.14	54	20.86
4882.0	36.25	PK	214	1.9	V	12.4	48.65	74	25.35
4882.0	20.89	Ave.	214	1.9	V	12.4	33.29	54	20.71
7323.0	35.22	PK	277	1.2	H	16.49	51.71	74	22.29
7323.0	21.01	Ave.	277	1.2	H	16.49	37.50	54	16.50
9764.0	34.37	PK	156	1.0	V	19.4	53.77	74	20.23
9764.0	19.49	Ave.	156	1.0	V	19.4	38.89	54	15.11

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB)	Corrected Amplitude (dB μ V/m)	FCC Part 15.247/205/209	
	Reading (dB μ V)	Detector (PK/QP/Ave.)		Height (m)	Polar (H/V)			Limit (dB μ V/m)	Margin (dB)
High Channel (2480 MHz)									
247.2	46.00	QP	90	1.4	H	-15.8	30.20	46	15.80
2480.0	76.07	PK	134	1.0	H	7.21	83.28	/	/
2480.0	67.35	Ave.	134	1.0	H	7.21	74.56	/	/
2480.0	75.45	PK	247	1.5	V	7.21	82.66	/	/
2480.0	66.83	Ave.	247	1.5	V	7.21	74.04	/	/
2371.8	40.70	PK	358	2.2	H	5.48	46.18	74	27.82
2371.8	23.02	Ave.	358	2.2	H	5.48	28.50	54	25.50
2483.6	41.56	PK	269	2.3	H	7.21	48.77	74	25.23
2483.6	25.71	Ave.	269	2.3	H	7.21	32.92	54	21.08
2491.8	39.25	PK	128	2.2	V	7.21	46.46	74	27.54
2491.8	24.13	Ave.	128	2.2	V	7.21	31.34	54	22.66
4960.0	38.07	PK	80	1.1	V	12.5	50.57	74	23.43
4960.0	24.83	Ave.	80	1.1	V	12.5	37.33	54	16.67
7440.0	36.24	PK	251	1.7	H	15.9	52.14	74	21.86
7440.0	22.37	Ave.	251	1.7	H	15.9	38.27	54	15.73
9920.0	35.19	PK	259	2.0	V	19.39	54.58	74	19.42
9920.0	19.48	Ave.	259	2.0	V	19.39	38.87	54	15.13

Note:

Corrected Factor = Antenna factor (RX) + Cable Loss – Amplifier Factor

Corrected Amplitude = Corrected Factor + Reading

Margin = Limit - Corrected. Amplitude

FCC §15.247(a) (1)-CHANNEL SEPARATION TEST

Applicable Standard

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater provided the systems operate with an output power no greater than 125 mW.

Test Procedure

1. Set the EUT in transmitting mode, maxhold the channel.
2. Set the adjacent channel of the EUT and maxhold another trace.
3. Measure the channel separation.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCI	101122	2013-09-17	2014-09-17

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	20 °C
Relative Humidity:	52 %
ATM Pressure:	100.1 kPa


The testing was performed by Rocky Kang on 2014-02-13.

EUT operation mode: Transmitting

Test Result: Compliance. Please refer to following tables and plots


Mode	Channel	Frequency (MHz)	Channel Separation (MHz)	\geq Limit (MHz)	Result
BDR (GFSK)	Low	2402	1.002	0.691	Pass
	Adjacent	2403			
	Middle	2441			
	Adjacent	2442	1.002	0.691	Pass
	High	2480			
	Adjacent	2479			
EDR ($\pi/4$-DQPSK)	Low	2402	1.002	0.827	Pass
	Adjacent	2403			
	Middle	2441			
	Adjacent	2442	1.002	0.827	Pass
	High	2480			
	Adjacent	2479			
EDR (8DPSK)	Low	2402	1.002	0.803	Pass
	Adjacent	2403			
	Middle	2441	1.002	0.803	Pass
	Adjacent	2442			
	High	2480	1.002	0.797	Pass
	Adjacent	2479			

Note: Limit = 20 dB bandwidth *2/3

BDR (GFSK): Low Channel


Comment ...

Date: 13.FEB.2014 08:28:21


BDR (GFSK): Middle Channel

Comment ...


Date: 13.FEB.2014 08:30:54

BDR (GFSK): High Channel

Comment ...
Date: 13.FEB.2014 08:33:36


EDR ($\pi/4$ -DQPSK): Low Channel

Comment ...
Date: 13.FEB.2014 08:35:07

EDR ($\pi/4$ -DQPSK): Middle Channel


Comment ...

Date: 13.FEB.2014 08:36:21


EDR ($\pi/4$ -DQPSK): High Channel

Comment ...


Date: 13.FEB.2014 08:37:40

EDR (8DPSK): Low Channel

Comment ...
 Date: 13.FEB.2014 08:38:35

EDR (8DPSK): Middle Channel

Comment ...
 Date: 13.FEB.2014 09:19:54

EDR (8DPSK): High Channel

Comment ...

Date: 13.FEB.2014 09:22:14

FCC §15.247(a) (1) – 20 dB EMISSION BANDWIDTH

Applicable Standard

Alternatively, frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 20 dB from the reference level. Record the frequency difference as the emission bandwidth.
4. Repeat above procedures until all frequencies measured were complete.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCI	101122	2013-09-17	2014-09-17

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	20 °C
Relative Humidity:	50~52 %
ATM Pressure:	100.1 kPa


The testing was performed by Rocky Kang on 2014-02-12 to 2014-02-13.


EUT operation mode: Transmitting

Test Result: Compliance. Please refer to following tables and plots

Mode	Channel	Frequency (MHz)	20 dB Emission Bandwidth (MHz)
BDR (GFSK)	Low	2402	1.036
	Middle	2441	1.036
	High	2480	1.036
EDR ($\pi/4$ -DQPSK)	Low	2402	1.240
	Middle	2441	1.240
	High	2480	1.240
EDR (8DPSK)	Low	2402	1.204
	Middle	2441	1.204
	High	2480	1.196


BDR (GFSK): Low Channel



BDR (GFSK): Middle Channel


Comment ...

Date: 12.FEB.2014 16:03:43

BDR (GFSK): High Channel


Comment ...

Date: 12.FEB.2014 16:05:30

EDR ($\pi/4$ -DQPSK): Low Channel


Comment ...

Date: 12.FEB.2014 16:26:59

EDR ($\pi/4$ -DQPSK): Middle Channel


Comment ...

Date: 12.FEB.2014 16:25:19

EDR ($\pi/4$ -DQPSK): High Channel


Comment ...

Date: 12.FEB.2014 16:08:59

EDR (8DPSK): Low Channel


Comment ...

Date: 12.FEB.2014 16:28:07

EDR (8DPSK): Middle Channel

Comment ...

Date: 12.FEB.2014 16:30:17

EDR (8DPSK): High Channel

Comment ...

Date: 13.FEB.2014 07:55:33

FCC §15.247(a) (1) (iii)-QUANTITY OF HOPPING CHANNEL TEST

Applicable Standard

Frequency hopping systems in the 2400–2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

Test Procedure

1. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
2. Set the EUT in hopping mode from first channel to last.
3. By using the max-hold function record the quantity of the channel.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCI	101122	2013-09-17	2014-09-17

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	20 °C
Relative Humidity:	52 %
ATM Pressure:	100.1 kPa


The testing was performed by Rocky Kang on 2014-02-13.

EUT operation mode: Transmitting

Test Result: Compliance. Please refer to following tables and plots

Mode	Frequency Range (MHz)	Number of Hopping Channel (CH)	Limit (CH)
BDR (GFSK)	2400-2483.5	79	≥15
EDR ($\pi/4$ -DQPSK)	2400-2483.5	79	≥15
EDR (8DPSK)	2400-2483.5	79	≥15


BDR (GFSK): Number of Hopping Channels




Comment ...

Date: 13.FEB.2014 10:36:08

EDR ($\pi/4$ -DQPSK): Number of Hopping Channels



EDR (8DPSK): Number of Hopping Channels



FCC §15.247(a) (1) (iii) - TIME OF OCCUPANCY (DWELL TIME)**Applicable Standard**

Frequency hopping systems in the 2400-2483.5 MHz shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

Test Procedure

The EUT was worked in channel hopping; Spectrum SPAN was set as 0. Sweep was set as 0.4 X channel no. (s), the quantity of pulse was get from single sweep. In addition, the time of single pulses was tested.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCI	101122	2013-09-17	2014-09-17

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

Test Data**Environmental Conditions**



Temperature:	20 °C
Relative Humidity:	52 %
ATM Pressure:	100.1 kPa



The testing was performed by Rocky Kang on 2014-02-13.

EUT operation mode: Transmitting


Test Result: Compliance. Please refer to following tables and plots

Mode		Channel	Pulse Width (ms)	Dwell Time (S)	Limit (S)	Result
BDR (GFSK)	DH 1	Low	0.504	0.161	0.4	Pass
		Middle	0.508	0.163	0.4	Pass
		High	0.506	0.162	0.4	Pass
	Note: DH1:Dwell time = Pulse time*(1600/2/79)*31.6S					
	DH 3	Low	1.778	0.284	0.4	Pass
		Middle	1.790	0.286	0.4	Pass
		High	1.784	0.285	0.4	Pass
	Note: DH3:Dwell time = Pulse time*(1600/4/79)*31.6S					
	DH 5	Low	3.038	0.324	0.4	Pass
		Middle	3.048	0.325	0.4	Pass
		High	3.048	0.325	0.4	Pass
	Note: DH5:Dwell time = Pulse time*(1600/6/79)*31.6S					
EDR (π/4-DQPSK)	DH 1	Low	0.518	0.166	0.4	Pass
		Middle	0.516	0.165	0.4	Pass
		High	0.518	0.166	0.4	Pass
	Note: 2DH1:Dwell time = Pulse time*(1600/2/79)*31.6S					
	DH 3	Low	1.788	0.286	0.4	Pass
		Middle	1.782	0.285	0.4	Pass
		High	1.788	0.286	0.4	Pass
	Note: 2DH3:Dwell time = Pulse time*(1600/4/79)*31.6S					
	DH 5	Low	3.042	0.324	0.4	Pass
		Middle	3.042	0.324	0.4	Pass
		High	3.042	0.324	0.4	Pass
	Note: 2DH5:Dwell time = Pulse time*(1600/6/79)*31.6S					
EDR (8DPSK)	DH 1	Low	0.514	0.164	0.4	Pass
		Middle	0.516	0.165	0.4	Pass
		High	0.516	0.165	0.4	Pass
	Note: 3DH1:Dwell time = Pulse time*(1600/2/79)*31.6S					
	DH 3	Low	1.782	0.285	0.4	Pass
		Middle	1.782	0.285	0.4	Pass
		High	1.788	0.286	0.4	Pass
	Note: 3DH3:Dwell time = Pulse time*(1600/4/79)*31.6S					
	DH 5	Low	3.052	0.326	0.4	Pass
		Middle	3.052	0.326	0.4	Pass
		High	3.052	0.326	0.4	Pass
	Note: 3DH5:Dwell time = Pulse time*(1600/6/79)*31.6S					


BDR (GFSK):**Pulse time, Low Channel, DH1****Pulse time, Middle Channel, DH1**



Pulse time, High Channel, DH1**Pulse time, Low Channel, DH3**



Pulse time, Middle Channel, DH3







Pulse time, High Channel, DH3







Pulse time, Low Channel, DH5**Pulse time, Middle Channel, DH5**



Pulse time, High Channel, DH5**EDR ($\pi/4$ -DQPSK):****Pulse time, Low Channel, 2DH1**



Pulse time, Middle Channel, 2DH1**Pulse time, High Channel, 2DH1**



Pulse time, Low Channel, 2DH3**Pulse time, Middle Channel, 2DH3**



Pulse time, High Channel, 2DH3**Pulse time, Low Channel, 2DH5**


Pulse time, Middle Channel, 2DH5**Pulse time, High Channel, 2DH5**

EDR (8DPSK):**Pulse time, Low Channel, 3DH1****Pulse time, Middle Channel, 3DH1**

Pulse time, High Channel, 3DH1**Pulse time, Low Channel, 3DH3**

Pulse time, Middle Channel, 3DH3**Pulse time, High Channel, 3DH3**

Pulse time, Low Channel, 3DH5**Pulse time, Middle Channel, 3DH5**

Pulse time, High Channel, 3DH5

Comment ...

Date: 13.FEB.2014 12:39:07

FCC §15.247(b) (1) - PEAK OUTPUT POWER MEASUREMENT

Applicable Standard

According to §15.247(b) (1), for frequency hopping systems operating in the 2400–2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725–5850 MHz band: 1 watt. And for all other frequency hopping systems in the 2400–2483.5 MHz band: 0.125 watts.

Test Procedure

1. Place the EUT on a bench and set in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to an EMI test receiver.
3. Add a correction factor to the display.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCI	101122	2013-09-17	2014-09-17

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	20 °C
Relative Humidity:	52 %
ATM Pressure:	100.1 kPa


The testing was performed by Rocky Kang on 2014-02-13.

EUT operation mode: Transmitting

Test Result: Compliance. Please refer to following tables and plots


Mode	Channel	Frequency (MHz)	Conducted Output Power		Limit (mW)
			(dBm)	(mW)	
BDR (GFSK)	Low	2402	-0.54	0.883	1000
	Middle	2441	-0.87	0.818	1000
	High	2480	-2.55	0.556	1000
EDR ($\pi/4$-DQPSK)	Low	2402	-1.67	0.681	1000
	Middle	2441	-2.25	0.596	1000
	High	2480	-2.47	0.566	1000
EDR (8DPSK)	Low	2402	-0.61	0.869	1000
	Middle	2441	-1.85	0.653	1000
	High	2480	-2.69	0.538	1000

BDR (GFSK): Low Channel




Comment ...

Date: 13.FEB.2014 08:02:49

BDR (GFSK): Middle Channel


Comment ...

Date: 13.FEB.2014 08:02:24

BDR (GFSK): High Channel


Comment ...

Date: 13.FEB.2014 08:01:57

EDR($\pi/4$ -DQPSK): Low Channel


Comment ...

Date: 13.FEB.2014 07:59:53

EDR($\pi/4$ -DQPSK): Middle Channel


Comment ...

Date: 13.FEB.2014 08:00:31

EDR($\pi/4$ -DQPSK): High Channel


Comment ...

Date: 13.FEB.2014 08:01:01

EDR(8DPSK): Low Channel


Comment ...

Date: 13.FEB.2014 07:59:17

EDR(8DPSK): Middle Channel

Comment ...

Date: 13.FEB.2014 07:58:40

EDR(8DPSK): High Channel

Comment ...

Date: 13.FEB.2014 07:58:13

FCC §15.247(d) - BAND EDGES TESTING

Applicable Standard

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Remove the antenna from the EUT and then connect to a low loss RF cable from the antenna port to a EMI test receiver, then turn on the EUT and make it operate in transmitting mode. Then set it to Low Channel and High Channel within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW of spectrum analyzer to 100 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCI	101122	2013-09-17	2014-09-17

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions


Temperature:	20 °C
Relative Humidity:	52 %
ATM Pressure:	100.1 kPa

The testing was performed by Rocky Kang on 2014-02-13.

EUT operation mode: Transmitting



Test Result: Compliance. Please refer to following plots.



BDR (GFSK): Band Edge-Left Side




Comment ...

Date: 13.FEB.2014 10:33:54

BDR (GFSK): Band Edge-Right Side**EDR ($\pi/4$ -DQPSK): Band Edge-Left Side**

EDR ($\pi/4$ -DQPSK): Band Edge-Right Side**EDR (8DPSK): Band Edge-Left Side**

BDR (8DPSK): Band Edge-Right Side

Comment ...

Date: 13.FEB.2014 10:26:22

PRODUCT SIMILARITY DECLARATION LETTER

現代電子廠有限公司

MODERN ELECTRONICS FACTORY LIMITED

九龍龍塘道472-478號龍塘工業中心四期10字樓C室
Flat C, 10/F., Phase 4, Kwun Tong Industrial Centre, 472-478 Kwun Tong Road, Kwun Tong, Kowloon, Hong Kong.
TEL: (852) 2344 3968 FAX: (852) 2344 3088

Product Similarity Declaration

To whom it may concern,

We Modern Electronics Factory Ltd., hereby declare that our Portable Bluetooth Wireless Speaker, Model No.SMPS-621, color blue was certified by BACL. There are 2 colors, blue and rose red, and their difference only the appearance color. For the NFC function, it has only the receipt mode.

Please contact me if you have any questions.

Signature:

Print Name: Ho kwok wing

Title: Engineer

Date: 19 Feb 2014

***** END OF REPORT *****