

# FCC ID: SSMMEF122BT

## Portable device

According to §15.247(e)(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to KDB447498 D01 General RF Exposure Guidance V05

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:

$$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] * [\sqrt{f(\text{GHz})}] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR, where}$$

$f(\text{GHz})$  is the RF channel transmit frequency in GHz;

Power and distance are rounded to the nearest mW and mm before calculation;

The result is rounded to one decimal place for comparison;

The test exclusions are applicable only when the minimum test separation distance is  $\leq 50$  mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is  $< 5$  mm, a distance of 5 mm is applied to determine SAR test exclusion.

We use 5mm as separation distance to calculate.

Maximum measured transmitter power:

BT DSS:

| Transmit Frequency (GHz) | Mode             | Max Conducted Power (mw) | Result calculation | 1-g SAR |
|--------------------------|------------------|--------------------------|--------------------|---------|
| 2.402                    | GFSK             | 0.23                     | 0.07               | 3.0     |
| 2.441                    | GFSK             | 0.20                     | 0.06               | 3.0     |
| 2.480                    | GFSK             | 0.21                     | 0.07               | 3.0     |
| 2.402                    | 1/4 $\Pi$ -DQPSK | 0.20                     | 0.06               | 3.0     |
| 2.441                    | 1/4 $\Pi$ -DQPSK | 0.23                     | 0.07               | 3.0     |
| 2.480                    | 1/4 $\Pi$ -DQPSK | 0.20                     | 0.06               | 3.0     |
| 2.402                    | 8DPSK            | 0.20                     | 0.06               | 3.0     |
| 2.441                    | 8DPSK            | 0.19                     | 0.06               | 3.0     |
| 2.480                    | 8DPSK            | 0.20                     | 0.06               | 3.0     |

Conclusion:

For the max result :  $0.07 \leq 3.0$  for 1-g SAR extremity SAR, No SAR is required.

Sincerely,



Signature

Company Name: SHENZHEN EMTEK CO., LTD.

Address: Bldg 69, Majialong Industry Zone, Nanshan District, Shenzhen, China

David Lee/ Manager