

CERTIFICATE OF COMPLIANCE

(CLASS B)

CERTIFICATION OF COMPLIANCE is hereby issued to the named Applicant and is VALID ONLY for the equipment identified below:

Date of Tested : Jan. 03. 2005

Applicant's Name : SITECSYSTEM CO., LTD.

Applicant's Address : Diplomatic Center, 1376-10 Secho-2dong, Secho-ku,
Seoul, Korea

Manufacturer's Name : SITECSYSTEM CO., LTD.

Manufacturer's Address : Diplomatic Center, 1376-10 Secho-2dong, Secho-ku,
Seoul, Korea

Declares that the product

Product Description : Portable MPEG4 Player

Brand Name : CENTRIX

Model Number : CENTRIX MHP-100

FCC ID : STB-SITECMHP100

Conforms to FCC Rules and Regulations Part 15 Subpart B requirements.

This product herewith complies with the requirements of the FCC Rules and Regulations as listed below:

Part 15.107: Conducted Emissions.

Part 15.109: Radiated Spurious Emissions.

TESTED and CERTIFIED by:

KOREA EMC LABORATORY

210-3 Yungduck-Ri, Kihung-Eup,
Yongin-Si, Kyungki-Do,
South, Korea

Date : Jan. 04. 2005

Report No : KEL04-F12021

Authorized Signature :



M. S. CHO / President

TABLE OF CONTENTS

DESCRIPTION	Page
0. VERIFICATION OF COMPLIANCE	3
1. GENERAL INFORMATION	
1.1 Product Description	4
1.2 Related Submittal(s)/Grant(s)	4
1.3 Tested System Details	4
1.4 System Configuration	4
1.5 General Setup of the test Shield room	5
1.6 Test Facility	5
2. Measurement Procedure	
2.1 System test configuration	6
2.1.1 Video mode Justification	6
2.1.2 EUT Exercise S/W	6
2.2 Special Accessories	6
2.3 Equipment Modification	6
2.4 Connected Cable	6
2.5 System Configuration Diagram	6
2.6 Preliminary testing	7
2.7 Shielded Enclosure	7
2.8 Data Reporting Format	7
2.9 Operating Condition	7
2.10 Conditioning of the EUT	7
2.11 Power Line Conducted Emissions	8
2.12 Open field Radiated Emissions Tests	8
3. Measurement Data	
3.1 Conducted Emission Data	9
3.2 Conducted Emission Graph	10-11
3.3 Radiated Emission Data	12
3.4 Summary	13
4. Labeling Requirement	14
Appendix	
- A : Test set-up Photographs (Conducted and Radiated)	
- B : External Photographs of E.U.T	
- C : Internal Photographs of E.U.T	
- D : FCC ID label location information and sample	
- E : Block Diagram	
- F : User's Manual	

0 . VERIFICATION OF COMPLIANCE

Equipment Under Test : Portable MPEG4 Player

Model Number : CENTRIX MHP-100

Serial Number : Representative manufacturing sample

Manufacturer : SITECSYSTEM CO., LTD.
Diplomatic Center, 1376-10 Secho-2dong, Secho-ku,
Seoul, Korea

Type of Test : FCC CLASS B

Report Number : KEL04-F12021

Date Tested : Jan. 03. 2005

Tested By : S.J.LEE

The results show that the sample equipment tested as described in this reports is in compliance with the CLASS B conducted and radiated emission limits of FCC Rules Part 15, Subpart B.

1. GENERAL INFORMATION

1.1 PRODUCT DESCRIPTION

The CENTRIX MHP-100 is a Portable MPEG4 Player made by SITECSYSTEM CO., LTD. in Korea. Refer to the user's manual for more information.

ITEM	SPECIFICATION
Interface	480 Mbps USB2.0 High-Speed
HDD Type	2.5" HDD
Dimension	80 x 148 x 24 mm
* E.U.T uses 12 MHz, 27 MHz Clock.	

1.2 Related Submittal(s)/Grant(s)

N/A

1.3 Tested System Details

Type	Model Name	FCC ID	Serial NO	Manufacturer
Portable MPEG4 Player	CENTRIX MHP-100	STB-SITECMHP100	Representative manufacturing sample	SITECSYSTEM CO., LTD.
Adapter	DSA-01D1F-D5 KA	Verification	NONE	DVE
PC	DreamSys/JLC	DoC	5007403100124	Sambo
Monitor	L665	DoC	27729072 B	EIZO
Mouse	M-SBF69	DoC	HCA41302692	Suzhou Logitech
Keyboard	TRI-750(W)	DoC	147004403025654	Solid Year Co., Ltd.
Serial Mouse	M-CE15	DZLMCE15	LT292R00285	LOGITECH
USB Mouse	X08-63846	DoC	NONE	Microsoft
MIC	RM-1000	-	NONE	HANIL
Printer	2225C+	DSI6XU2225	3119S96116	HP
Adapter	PW118	Verification	KA1202F52	AULT INC.
Video Monitor	SSM-14N1U	-	6001435	Sony Corp.
Woofer	SPS-800A	-	924053	Clanx

1.4 System Configuration

Type	Model Name	Serial NO	Manufacturer	Remark
MAIN B/D	MG-25	NONE	AL Tech, Inc.	Korea
HDD	MK4019GAX	14C41348T	TOSHIBA CORP.	Philippines

1.5 General Set-up of the Test Shielded Room

The EUT was set up in accordance with the suggested configuration given in FCC measurement Procedure ANSI C63.4-2003. The measurement are performed in the shielded room which dimension is 3.0*7.0*2.5(m). The EUT was placed on a non conductive table which is 1.0*1.5(m), 80 cm above an earthed ground plane and is kept at least 1m from any other earthed ground plane except the rear of table top being removed 40 cm from a vertical conducting plane.

Power to the EUT was provided through the LISN(NSLK8128, SCHWARZBECK) which has the Impedance vs Frequency Characteristic in accordance with the conducted setup photographs in Appendix-A Impedance Characteristic of LISN. Peripheral equipment required to provide a functional system(support equipment) for EUT testing was powered through another LISN(KNW-407, KYORITSU).

Power to the LISN was filtered to eliminate ambient signal interference. A coaxial type connector which provides a 50 Ohm terminating impedance was provided for the test instrument. The excess length of the power cord was wrapped in the two non metallic pegs attached to the top of the LISN. The two pegs are 9 cm high, approximately 2.0 cm in diameter and that are spaced 6 cm on the center apart.

1.6 Test Facility

Location: Korea EMC Laboratory

210-3 Yungduck-Ri, Kihung-Eup,
Yongin-Si, Kyungki-Do,
South, Korea

Site : - 3/10m Open Fielded Radiated
- Indoor Line Conducted Room(Shielded)

The Open Field Radiated and Indoor Line Conducted sites are constructed and calibrated to meet the FCC requirements in documents ANSI C63.4-2003. Korea EMC Lab. was refilled in FCC in Dec. 19. 2003.

INSTRUMENTATION

Description	Model	Manufacturer	Serial No	Due Cal.
TEST RECEIVER	ESVS10	Rohde&Schwarz	825120/006	2005.10.15
TEST RECEIVER	ESCS30	Rohde&Schwarz	100054	2005.11.25
BILOG	VULB9160	SCHWARZBECK	3049	2005.10.14
LISN(for E.U.T)	NSLK 8128	SCHWARZBECK	8128144	2005.11.04
AMPLIFIER	87405A	Hewlett-Packard	2944A06481	2005.07.18
LISN(for Peripheral)	KNW-407	KYORITSU	8-8833-14	2005.12.11
PLOTTER	7550A	Hewlett-Packard	2407A00471	-
Attenuator	8491A	Hewlett-Packard	30907	-

The calibration of the measuring instruments, including any accessories that may effect such calibration, are checked frequently to assure their accuracy. Adjustments are made and correction factors are applied in accordance with instruments contained in the manual for the measuring instrument.

2. MEASUREMENT PROCEDURES

2.1 System Test Configuration

2.1.1 Video mode Justification

N/A

2.1.2 EUT Exercise Software

Execute media file had stored to Portable MPEG4 Player after connects Portable MPEG4 Player to PC and measure Display and Data of PC repeating Copy/Delete to Portable MPEG4 Player.

2.2 Special Accessories


2.3 Equipment Modifications

No equipment modifications were performed during testing.

2.4 Connected cable

Beginning device		Last device		Standard of cable	
Type	I/O Port	Type	I/O Port	length (m)	shielding
Portable MPEG4 Player	USB	PC	USB	1.5	Shielded
"	AV	[Video Monitor Woofers	Video in	1.5	Core Shielded(Core)
"	SV		Audio in [L	1.5	
"				R	
"			S-Video	1.5	
"	Power	Video Monitor	Audio in	1.5	Core Shielded(Core)
PC			Adapter	1.5	
"	Video		Monitor	Video	
"	Keyboard	Keyboard		1.5	
"	Mouse	Mouse		1.5	Shielded
"	Serial	Serial Mouse		1.5	Shielded
"	USB	USB Mouse		1.5	Shielded
"	MIC	MIC		1.0	
"	Line out	Monitor	Line in	1.0	
"	Parallel	Printer		1.5	Shielded(Core)
Printer	Power	Adapter		1.5	

2.5 System Configuration Diagram



2.6 PRELIMINARY TESTING

It is often valuable to performing preliminary radiated measurements at a closer distance than specified for compliance to determine the emission characteristics of the EUT. At close-in distance, it is easier to determine the spectrum signature of EUT, and if applicable, the EUT configuration that emanate the maximum level of emissions. The data may not be precisely correlatable results.

2.7 SHIELDED ENCLOSURE

To search the Radiated frequency outline of an EUT a shielded screen room may be used. If the shielded room is used for radiated data, the data page will state that the EUT was in a shielded enclosure. All data collected in a screen room for radiated emissions is for frequency outline only. If an EUT is placed in screen room for Line Conducted Data, the data page will show that a screen room was used and data frequencies and levels will be correct and used for test data.

2.8 DATA REPORTING FORMAT

The measurement results expressed in accordance with C63.4 and specified limits where applicable are presented in tabular or graphical form, or alternatively as recorder charts or photographs of a spectrum analyzer display, showing the level vs. frequency.

2.9 OPERATING CONDITIONS

The EUT was operated at the specified load conditions(mechanical and/or electrical)for which it was designed.

2.10 CONDITIONING OF THE EUT

The EUT was operated for a sufficient period of time to approximate normal operating conditions.

2 11 Power line Conducted Emissions

The EUT is set up in accordance with the suggested configuration given in FCC Measurement Procedure ANSI C63.4-2003. The measurements are performed in a 3m x 6m x 2.5m shielded room. A wooden table which height is 80 cm is located at the center of the shielded room; desktop EUTs are placed on top of this table. The rear of the EUT and table are placed 40 cm apart from the shielded room wall. All items on the table (or test-table) were placed at least 10 cm apart each other. Excess EUT power cord is folded back and forth to form a 30 cm by 40 cm bundle. Interconnecting cables which hang closer than 40 cm to the ground plane are folded back and forth to form a 30 cm by 40 cm long bundle, hanging approximately in the middle between the ground plane and table. The EUT power cord was plugged into a LISN 80 cm away, while all other devices were plugged into a second LISN, also 80 cm away.

The highest emissions were also analyzed in detail by operating the spectrum analyzer in fixed tuned mode to determine the precise amplitude of the emissions. On the other hand, the interconnecting cables were moved around the table to maximize the emissions, and the position of the peripheral devices were interchanged to check whether there is any changes in emissions.

NOTE : The resolution bandwidth and video bandwidth of test receiver is 10 kHz for Quasi-peak detection (QP) at frequency below 30 MHz. Q.P value A.V limit when do over by A.V mode conversion after measure .

2.12 Open field Radiated Emissions Tests

The EUT and support equipment are set up on the turntable in an open field site. Desktop EUTs are set up on a wooden stand (test-table), 80 cm above the ground plane. All items on the table were placed at least 10 cm apart each other. Interconnecting cables which hang closer than 40 cm to the ground plane are folded back and forth to form a 30 cm by 40 cm long bundle, hanging approximately between the ground plane and table. The highest emissions were also analyzed, in detail, with the tuned aerial to search the precise amplitude of the emissions. On the other hand, the interconnecting cables were moved around the table and if the highest amplitudes is observed, the EUT is rotated in the horizontal plane while changing the antenna polarization to the vertical plane to maximize the field strength. Once the maximum field strength is obtained, the antenna elevation and polarization will be varied between specified limits to maximize the readings. The position of the peripheral devices are interchanged to check for any changes in emissions. In rare instances, the maximum field strength may occur with the antenna polarized between vertical and horizontal.

NOTE : The resolution bandwidth and video bandwidth of test receiver is 120 kHz for Quasi-peak detection (QP) at frequency below 1 GHz

3. Measurement Data

3.1 CONDUCTED EMISSION DATA

TEST : Portable MPEG4 Player ; CENTRIX MHP-100

DATE : Jan. 03. 2005


Freq. (MHz)	EUT State	Polarity (H/N)	Level (Q.P/A.V) dB(uV)	LIMIT (Q.P/A.V) dB(uV)	Margin for(Q.P/A.V) dB
0.151	Refer to Note	L1	46.2	66.0	19.8
0.153		L1	41.9	65.9	24.0
0.171		L2	44.0	65.4	21.4
0.246		L2	30.0	63.3	33.3
0.287		L1	41.4	62.1	20.7
0.422		L2	32.4	58.2	25.8
0.661		L1	29.5	56.0	26.5
0.811		L2	3.4	56.0	52.6
1.000		L1	30.0	56.0	26.0
1.277		L2	33.8	56.0	22.2
1.540		L2	29.3	56.0	26.7
3.230		L2	32.1	56.0	23.9
5.002		L2	22.3	60.0	37.7
6.007		L2	20.0	60.0	40.0
6.504		L2	19.7	60.0	40.3
8.159		L2	16.9	60.0	43.1
12.761		L1	19.7	60.0	40.3
13.004		L2	20.2	60.0	39.8

Notes: The test is implemented in a shielded room in accordance with ANSI C63.4


L1 : HOT LINE , L2 : NEUTRAL LINE

Test Engineer.

Reviewed by.

3.2 Conducted Emission Graph




Red : PK, Blue : AV
LINE EMISSION GRAPH(L1)

Korea EMC Raboratory
Conducted Emission

Comment: L2
PK : RED AV : BLUE

Scan Settings (i Range)			Receiver Settings				
Start	Stop	Step	IF BW	Detector	M-Time	Atten	Preamp
150K	30M	0.2%	9K	PK+AV	20ms	10dB LN	OFF




Red : PK, Blue : AV
LINE EMISSION GRAPH(L2)

3.2 RADIATED EMISSION DATA

TEST : Portable MPEG4 Player : CENTRIX MHP-100

DATE : Jan. 03. 2005

[illegible]

Notes: The test is performed in a distance of 3m. Af : Antenna factor, Cl : Cable loss

The test is performed in accordance with ANSI C63.4

Test Engine~

Reviewed by.

Korea EMC Laboratory

3.3 SUMMARY

Company	: SITECSYSTEM CO., LTD.
Equipment Under Test	: Portable MPEG4 Player
Model Number	: CENTRIX MHP-100
Type of Test	: FCC CLASS B
Serial Number	: Representative manufacturing sample
Passed/Failed	: PASSED

The Equipment Under Test(EUT) was configured and operated in a manner which tends to maximize its emission characteristics in a typical application. Power and signal distribution, ground, interconnecting cabling, and physical placement of equipment were simulating the typical application and usage in so far as practicable.

LINE CONDUCTED TEST: An unshielded power cord was used to connect the EUT to a LISN Box which supplied 120 VAC/60 Hz power. The EUT was tested according to C63.4 test specifications. Line conductance scanned from 150 kHz to 30 MHz range on both Line 1(hot side) and Line 2(neutral side). ***The highest emission was observed at 0.151 MHz on Line 1 with a margin of 19.8 dB from the limit.*** All line conductance emissions were within the FCC CLASS B requirements for compliance.

RADIATED TEST: The EUT was placed on a three meter open field test site according to C63.4 test specifications. Preliminary scans ranged from 30 MHz to 1 GHz in both vertical and horizontal polarizations in all possible modes of operation. The highest six point of emission levels were recorded as data each ranges of limit. ***The highest emission was observed at 746.601 MHz(Horizontal) with margin of 7.2 dB from the limit.*** All radiated emissions were within the FCC CLASS B requirements for compliance.

4. LABELING REQUIREMENT

Section 15.19 of the Code of Federal Regulation

- 1) A CLASS B computing device subject to certification by the Commission shall be identified pursuant to par. 2.925 et Seq of this chapter. In addition, the label shall include the following statement:

This device complies with Part 15 of the FCC Rules.
Operation is subject to the following two conditions:
(1) This Device may not cause harmful interference, and
(2) This device must accept any interference received,
including interference that may cause undesired
operation.

Where a device is constructed in two or more sections connected by wires and marketed together, the statement specified in this Section is required to be affixed only to the main control unit.

The users manual or instruction manual for the EUT shall contain the following statement or equivalent.

Caution: Changes or Modifications not expressly approved by the party responsible for compliance could void the users authority to operate the equipment.

If the EUT requires accessories such as special shielded cables and/or connectors to enable compliance with emission limits, the instruction manual for the EUT shall include appropriate instructions on the first page of the text concerned with the installation of the device that these special accessories must be used with the device. It is the responsibility of the user to use the needed special accessories supplied with the equipment.

For a CLASS B digital device or peripheral, the instructions furnished the user shall include the following or similar statement placed in a prominent location in the text of the manual.

Note: This equipment has been tested and found to comply with the limits for a CLASS B digital device, pursuant to Part 15 of FCC Rules. These limits are designed to provide reasonable protection against harmful interference when the equipment is operated in a commercial environment. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.