

## FCC 47 CFR MPE REPORT

Klipsch Group, Inc.

Wireless Surrounds

Model Number: Flexus SURR 100

FCC ID: STI-XSURR100

|                          |                                                                     |
|--------------------------|---------------------------------------------------------------------|
| Applicant:               | Klipsch Group, Inc.                                                 |
| Address:                 | 3502 Woodview Trace, Suite 200, Indianapolis, IN 46268, USA         |
|                          |                                                                     |
| Prepared By:             | EST Technology Co., Ltd.                                            |
|                          | Chilingxiang, Qishantou, Santun, Houjie, Dongguan, Guangdong, China |
| Tel: 86-769-83081888-808 |                                                                     |

|                 |                       |
|-----------------|-----------------------|
| Report Number:  | ESTE-R2312068         |
| Date of Test:   | Oct. 17~Dec. 08, 2023 |
| Date of Report: | Dec .11, 2023         |

## Maximum Permissible Exposure

### 1. Applicable Standards

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 0.2m normally can be maintained between the user and the device.

#### 1.1. Limits for Maximum Permissible Exposure (MPE)

##### (a) Limits for Occupational/Controlled Exposure

| Frequency Range (MHz) | Electric Field Strength (E) (V/m) | Magnetic Field Strength (H) (A/m) | Power Density (S) (mW/cm <sup>2</sup> ) | Averaging Times   E   <sup>2</sup> ,   H   <sup>2</sup> or S (minutes) |
|-----------------------|-----------------------------------|-----------------------------------|-----------------------------------------|------------------------------------------------------------------------|
| 0.3-3.0               | 614                               | 1.63                              | (100)*                                  | 6                                                                      |
| 3.0-30                | 1842/f                            | 4.89/f                            | (900/f)*                                | 6                                                                      |
| 30-300                | 61.4                              | 0.163                             | 1.0                                     | 6                                                                      |
| 300-1500              |                                   |                                   | F/300                                   | 6                                                                      |
| 1500-10000            |                                   |                                   | 5                                       | 6                                                                      |

##### (b) Limits for General Population / Uncontrolled Exposure

| Frequency Range (MHz) | Electric Field Strength (E) (V/m) | Magnetic Field Strength (H) (A/m) | Power Density (S) (mW/cm <sup>2</sup> ) | Averaging Times   E   <sup>2</sup> ,   H   <sup>2</sup> or S (minutes) |
|-----------------------|-----------------------------------|-----------------------------------|-----------------------------------------|------------------------------------------------------------------------|
| 0.3-1.34              | 614                               | 1.63                              | (100)*                                  | 30                                                                     |
| 1.34-30               | 824/f                             | 2.19/f                            | (180/f)*                                | 30                                                                     |
| 30-300                | 27.5                              | 0.073                             | 0.2                                     | 30                                                                     |
| 300-1500              |                                   |                                   | F/1500                                  | 30                                                                     |
| 1500-10000            |                                   |                                   | 1.0                                     | 30                                                                     |

Note: f=frequency in MHz; \*Plane-wave equivalent power density

## 1.2. MPE Calculation Method

$$E \text{ (V/m)} = \frac{\sqrt{30 \times P \times G}}{d} \quad \text{Power Density: } Pd \text{ (W/m}^2\text{)} = \frac{E^2}{377}$$

E = Electric Field (V/m)

P = Peak RF output Power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30 \times P \times G}{377 \times d^2}$$

From the peak EUT RF output power, the minimum mobile separation distance, d=0.2m, as well as the gain of the used antenna, the RF power density can be obtained

## 2. Conducted Power Result

| Mode | Frequency (MHz) | Peak output power (dBm) | Peak output power (mW) |
|------|-----------------|-------------------------|------------------------|
| GFSK | 2402            | 6.90                    | 4.898                  |
|      | 2442            | 5.79                    | 3.793                  |
|      | 2481            | 4.88                    | 3.076                  |

## 3. Calculated Result and Limit

| Mode | Peak output power (dBm) | Target power (dBm) | MAX Target power (dBm) | Antenna gain |          | Power Density (S) (mW /cm <sup>2</sup> ) | Limited of Power Density (S) (mW /cm <sup>2</sup> ) | Test Result |
|------|-------------------------|--------------------|------------------------|--------------|----------|------------------------------------------|-----------------------------------------------------|-------------|
|      |                         |                    |                        | (dBi)        | (Linear) |                                          |                                                     |             |
| GFSK | 6.90                    | 6±1                | 7                      | 1.7          | 1.479    | 0.00147                                  | 1                                                   | Complies    |

**End of Test Report**