

MPE CALCULATION

FCC ID: STJ-SDMAN

RF Exposure Requirements: 47 CFR §1. 1307(b)
RF Radiation Exposure Limits: 47 CFR §1. 1310
RF Radiation Exposure Guidelines: FCC OST/OET Bulletin Number 65
EUT Frequency Band: 5180-5825MHz
Limits for General Population/Uncontrolled Exposure in the band of: 1500 - 100,000 MHz
Power Density Limit: 1 mW / cm²

Equation: $S = PG / 4\pi R^2$ or $R = \sqrt{PG / 4\pi S}$

Where, S = Power Density

P = Power Input to Antenna

G = Antenna Gain

R = distance to the center of radiated antenna

Type	CH Freq (MHz)	Conducted Power (dBm)	Antenna Gain (dBi)	Apparent Gain (dBi)	Measurement Distance (cm)	Calculated MPE (mW/cm ²)	MPE Limit (mW/cm ²)	Pass/Fail
5.2 GHz WLAN	5230	12.53	4.9	7.9	20	0.0219	1	Pass
5.3 GHz WLAN	5270	11.62	4.9	7.9	20	0.0178	1	Pass
5.5 GHz WLAN	5670	13.13	4.9	7.9	20	0.0200	1	Pass
5.8 GHz WLAN	5825	12.53	4.9	7.9	20	0.0174	1	Pass

The Above Result had shown that the device complied with MPE requirement at a prediction distance of 20cm .

Completed By: Rachana Khanduri



SIEMIC, Inc
775 Montague Expressway, Milpitas, CA 95035
Phone: (408) 526-1188
Date: October 21, 2015