



FCC ID: SVC-C388

**Statement of compliance to
Maximum Permissible Exposure (MPE)
No. 160700132SHA-003**

Applicant : Lenbrook Industries Limited

633 Granite Court, Pickering Ontario, L1W 3K1, Canada

Manufacturer : Lenbrook Industries Limited

633 Granite Court, Pickering Ontario, L1W 3K1, Canada

Product Name : HYBRID DIGITAL DAC AMPLIFIER

Type/Model : C 388

According to §2.1091, §2.1093 and §1.1307(b), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

Date of issue: October 26, 2016

Prepared by:

A handwritten signature in black ink that reads "Wade Zhang".

Wade Zhang (*Project Engineer*)

Reviewed by:

A handwritten signature in black ink that reads "Daniel Zhao".

Daniel Zhao (*Reviewer*)



Power density (S) is calculated according to the formula:

$$S = PG / (4\pi R^2)$$

Where S = power density in mW/cm²

P = transmit power in mW

G = numeric gain of transmit antenna (numeric gain=Log-1(dB antenna gain/10))

R = distance (cm)

The calculations in the table below use the highest gain of antenna for client EUT. These calculations represent worst case in terms of the exposure levels.

Frequency band	Power		Antenna Gain		R	S	Limits
(MHz)	dBm	mW	dBi	(Numeric)	(cm)	(mW/cm2)	(mW/cm2)
2402 - 2480	7.483	5.60	2.0	1.58	20	0.002	1

Note: 1 mW/cm2 from 1.310 Table 1



Appendix I

Definition below must be outlined in the User Manual:

To satisfy FCC RF exposure requirements, a separation distance of **20** cm or more should be maintained between the antenna of this device and persons during device operation. To ensure compliance, operations at closer than this distance is not recommended.