FCC/IC REPORT
(Bluetooth)

Applicant:	Shenzhen Ballet Digital Technology Co., Ltd.
Address of Applicant:	3rd Floor, Building A1, Iron Tower Industrial Park, Hedi Road, Shang Village, Gongming Town, Guangming New District, Shenzhen, China.

Equipment Under Test (EUT)

Product Name:	Bluetooth MP3 player
Model No.:	MBT0004, CMBT0004
Trade mark:	RCA
FCC ID:	SWLA1818
Canada IC:	11052A-A1818
Applicable standards:	FCC CFR Title 47 Part 15 Subpart C Section 15.247 RSS-Gen Issue 4, November 2014 RSS-247 Issue 2, February 2017
Date of sample receipt:	21 Mar., 2018
Date of Test:	21 Mar., to 08 May., 2018
Date of report issued:	09 May., 2018
Test Result:	PASS *

* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:

Bruce Zhang
Laboratory Manager

This report details the results of the testing carried out on one sample. The results contained in this test report do not relate to other samples of the same product and does not permit the use of the CCIS product certification mark. The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report.

This report may only be reproduced and distributed in full. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards.

This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

2 Version

Version No.	Date	Description
00	*09 May., 2018*	*Original*

Tested by: YT Yang ***Date:*** *09 May., 2018*

Test Engineer

Reviewed by: Winner Zhang ***Date:*** *09 May., 2018*

Project Engineer

3 Contents

Page

1 COVER PAGE 1
2 VERSION 2
3 CONTENTS 3
4 TEST SUMMARY 4
5 GENERAL INFORMATION 5
5.1 CLIENT INFORMATION 5
5.2 GENERAL DESCRIPTION OF E.U.T. 5
5.3 TEST ENVIRONMENT AND TEST MODE 6
5.4 DESCRIPTION OF SUPPORT UNITS 6
5.5 MEASUREMENT UNCERTAINTY 6
5.6 LABORATORY FACILITY 6
5.7 LABORATORY LOCATION 7
5.8 TEST INSTRUMENTS LIST 7
6 TEST RESULTS AND MEASUREMENT DATA 8
6.1 ANTENNA REQUIREMENT 8
6.2 CONDUCTED EMISSIONS 9
6.3 CONDUCTED OUTPUT POWER 14
6.4 20DB OCCUPY BANDWIDTH 17
6.5 CARRIER FREQUENCIES SEPARATION 20
6.6 HOPPING CHANNEL NUMBER 24
6.7 DWELL TIME 26
6.8 PSEUDORANDOM FREQUENCY HOPPING SEQUENCE 29
6.9 BAND EDGE 30
6.9.1 Conducted Emission Method 30
6.9.2 Radiated Emission Method 34
6.10 SPURIOUS EMISSION 59
6.10.1 Conducted Emission Method 59
6.10.2 Radiated Emission Method 62
7 TEST SETUP PHOTO 69
8 EUT CONSTRUCTIONAL DETAILS 71

4 Test Summary

Test Items	Section		Result
	FCC	IC	
Antenna Requirement	15.203/15.247 (c)	RSS-GEN Section 8.3	Pass
AC Power Line Conducted Emission	15.207	RSS-GEN Section 8.8	Pass
Conducted Peak Output Power	15.247 (b)(1)	RSS-247 Section 5.4 (b)	Pass
20dB Occupied Bandwidth	15.247 (a)(1)	RSS-247 Section 5.1 (a)	Pass
Carrier Frequencies Separation	15.247 (a)(1)	RSS-247 Section 5.1 (b)	Pass
Hopping Channel Number	15.247 (a)(1)	RSS-247 Section 5.1 (d)	Pass
Dwell Time	15.247 (a)(1)	RSS-247 Section 5.1 (d)	Pass
Spurious Emission	15.205/15.209	RSS-GEN 8.9 8.10 RSS-247 Section 5.5	Pass
Band Edge	15.247(d)	RSS-GEN 8.9 8.10 RSS-247 Section 5.5	Pass
Pass: The EUT complies with the essential requirements in the standard.			

5 General Information

5.1 Client Information

Applicant:	Shenzhen Ballet Digital Technology Co., Ltd.
Address:	3rd Floor, Building A1, Iron Tower Industrial Park, Hedi Road, Shang Village, Gongming Town, Guangming New District, Shenzhen, China.
Manufacturer/ Factory:	Shenzhen Ballet Digital Technology Co., Ltd.
Address:	3rd Floor, Building A1, Iron Tower Industrial Park, Hedi Road, Shang Village, Gongming Town, Guangming New District, Shenzhen, China.

5.2 General Description of E.U.T.

Product Name:	Bluetooth MP3 player
Model No.:	MBT0004, CMBT0004
Operation Frequency:	2402MHz~2480MHz
Transfer rate:	1/2/3 Mbits/s
Number of channel:	79
Modulation type:	GFSK, π/4-DQPSK, 8DPSK
Modulation technology:	FHSS
Antenna Type:	PCB Antenna
Antenna gain:	0 dBi
Power supply:	Rechargeable Li-ion Battery DC3.7V, 180mAh
Remark:	Model No.: MBT0004, CMBT0004 were identical inside, the electrical circuit design, layout, components used and internal wiring, with only difference being model name for different customer.

Operation Frequency each of channel for GFSK, π/4-DQPSK, 8DPSK							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
0	2402MHz	20	2422MHz	40	2442MHz	60	2462MHz
1	2403MHz	21	2423MHz	41	2443MHz	61	2463MHz
2	2404MHz	22	2424MHz	42	2444MHz	62	2464MHz
3	2405MHz	23	2425MHz	43	2445MHz	63	2465MHz
4	2406MHz	24	2426MHz	44	2446MHz	64	2466MHz
5	2407MHz	25	2427MHz	45	2447MHz	65	2467MHz
…	…	…	…	…	…	…	…
15	2417MHz	35	2437MHz	55	2457MHz	75	2477MHz
16	2418MHz	36	2438MHz	56	2458MHz	76	2478MHz
17	2419MHz	37	2439MHz	57	2459MHz	77	2479MHz
18	2420MHz	38	2440MHz	58	2460MHz	78	2480MHz
19	2421MHz	39	2441MHz	59	2461MHz		
Remark: Channel 0, 39 &78 selected for GFSK, π/4-DQPSK and 8DPSK.							

5.3 Test environment and test mode

Operating Environment:	
Temperature:	24.0 °C
Humidity:	54 % RH
Atmospheric Pressure:	1010 mbar
Test Modes:	
Non-hopping mode:	Keep the EUT in continuous transmitting mode with worst case data rate.
Hopping mode:	Keep the EUT in hopping mode.
Remark	GFSK (1 Mbps) is the worst case mode.
The sample was placed 0.8m (below 1GHz)/1.5m (above 1GHz) above the ground plane of 3m chamber*. Measurements in both horizontal and vertical polarities were performed. During the test, each emission was maximized by: having the EUT continuously working with a fresh battery, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, rotating the turntable, varying antenna height from 1m to 4m in both horizontal and vertical polarizations. The emissions worst-case are shown in Test Results of the following pages.	

5.4 Description of Support Units

The EUT has been tested as an independent unit.

5.5 Measurement Uncertainty

Parameters	Expanded Uncertainty
Conducted Emission (9kHz ~ 30MHz)	2.14 dB (k=2)
Radiated Emission (9kHz ~ 30MHz)	4.24 dB (k=2)
Radiated Emission (30MHz ~ 1000MHz)	4.35 dB (k=2)
Radiated Emission (1GHz ~ 18GHz)	4.44 dB (k=2)
Radiated Emission (18GHz ~ 26.5GHz)	4.56 dB (k=2)

5.6 Laboratory Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **FCC - Registration No.: 727551**

Shenzhen Zhongjian Nanfang Testing Co., Ltd. has been accredited as a testing laboratory by FCC (Federal Communications Commission). The Registration No. is 727551.

- **IC - Registration No.: 10106A-1**

The 3m Semi-anechoic chamber of Shenzhen Zhongjian Nanfang Testing Co., Ltd. has been Registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 10106A-1.

- **CNAS - Registration No.: CNAS L6048**

Shenzhen Zhongjian Nanfang Testing Co., Ltd. is accredited to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration laboratories for the competence of testing. The Registration No. is CNAS L6048.

- **A2LA - Registration No.: 4346.01**

This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2005 General requirements for the competence of testing and calibration laboratories. The test scope can be found as below link: https://portal.a2la.org/scopepdf/4346-01.pdf

5.7 Laboratory Location

Shenzhen Zhongjian Nanfang Testing Co., Ltd.
Address: No. B-C, 1/F., Building 2, Laodong No.2 Industrial Park, Xixiang Road,
Bao'an District, Shenzhen, Guangdong, China
Tel: +86-755-23118282, Fax: +86-755-23116366
Email: info@ccis-cb.com, Website: http://www.ccis-cb.com

5.8 Test Instruments list

Radiated Emission:

Test Equipment	Manufacturer	Model No.	Serial No.	Cal. Date (mm-dd-yy)	Cal. Due date (mm-dd-yy)
3m SAC	SAEMC	9m*6m*6m	966	07-22-2017	07-21-2020
Loop Antenna	SCHWARZBECK	FMZB1519B	00044	03-16-2018	03-15-2019
BiConiLog Antenna	SCHWARZBECK	VULB9163	497	03-16-2018	03-15-2019
Horn Antenna	SCHWARZBECK	BBHA9120D	916	03-16-2018	03-15-2019
EMI Test Software	AUDIX	E3	6.110919b	N/A	N/A
Pre-amplifier	HP	8447D	2944A09358	03-07-2018	03-06-2019
Pre-amplifier	CD	PAP-1G18	11804	03-07-2018	03-06-2019
Spectrum analyzer	Rohde & Schwarz	FSP30	101454	03-07-2018	03-06-2019
EMI Test Receiver	Rohde & Schwarz	ESRP7	101070	03-07-2018	03-06-2019
Cable	ZDECL	Z108-NJ-NJ-81	1608458	03-07-2018	03-06-2019
Cable	MICRO-COAX	MFR64639	K10742-5	03-07-2018	03-06-2019
Cable	SUHNER	SUCOFLEX100	58193/4PE	03-07-2018	03-06-2019

Conducted Emission:

Test Equipment	Manufacturer	Model No.	Serial No.	Cal. Date (mm-dd-yy)	Cal. Due date (mm-dd-yy)
EMI Test Receiver	Rohde & Schwarz	ESCI	101189	03-07-2018	03-06-2019
Pulse Limiter	SCHWARZBECK	OSRAM 2306	9731	03-07-2018	03-06-2019
LISN	CHASE	MN2050D	1447	03-19-2018	03-18-2019
LISN	Rohde & Schwarz	ESH3-Z5	8438621/010	07-21-2017	07-20-2018
Cable	HP	10503A	N/A	03-07-2018	03-06-2019
EMI Test Software	AUDIX	E3	6.110919b	N/A	N/A

6 Test results and measurement data

6.1 Antenna Requirement

Standard requirement:	FCC Part 15 C Section 15.203 /247(c)
15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. 15.247(c) (1)(i) requirement: (i) Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi.	
E.U.T Antenna:	
The Bluetooth antenna is an internal antenna which permanently attached, and the best case gain of the antenna is 0 dBi.	



6.2 Conducted Emissions

Test Requirement:	FCC Part 15 C Section 15.207 RSS-GEN Section 8.8
Test Method:	ANSI C63.10:2013
Test Frequency Range:	150 kHz to 30 MHz
Class / Severity:	Class B
Receiver setup:	RBW=9 kHz, VBW=30 kHz, Sweep time=auto
Limit:	

Frequency range (MHz)	Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50
* Decreases with the logarithm of the frequency.		

Test setup:



Remark:
E.U.T: Equipment Under Test
LISN: Line Impedence Stabilization Network
Test table height=0.8m

Test procedure:

1. The E.U.T and simulators are connected to the main power through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm/50uH coupling impedance for the measuring equipment.
2. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refer to the block diagram of the test setup and photographs).
3. Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.4: 2014 on conducted measurement.

Test Instruments:	Refer to section 5.8 for details
Test mode:	Hopping mode
Test results:	Pass

Measurement Data:
FCC
Line:



Trace: 5

Site : CCIS Shielding Room
Condition : FCC PART 15.247 QP LISN(RS) LINE
EUT : Bluetooth MP3 player
Model : MBT0004
Test Mode : BT mode
Power Rating : AC 120V/60Hz
Environment : Temp: 23 .5℃ Huni:57% Atmos:101KPa
Test Engineer: YT
Remark :

	Freq	Read Level	LISN Factor	Cable Loss	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dB	dBuV	dBuV	dB	
1	0.150	20.17	0.71	10.78	31.66	56.00	-24.34	Average
2	0.162	37.87	0.71	10.77	49.35	65.34	-15.99	QP
3	0.182	22.88	0.73	10.77	34.38	54.42	-20.04	Average
4	0.186	35.83	0.73	10.76	47.32	64.20	-16.88	QP
5	0.211	33.18	0.73	10.76	44.67	63.18	-18.51	QP
6	0.222	18.88	0.73	10.76	30.37	52.74	-22.37	Average
7	0.234	31.89	0.74	10.75	43.38	62.30	-18.92	QP
8	0.421	19.33	0.75	10.73	30.81	47.42	-16.61	Average
9	0.510	27.38	0.76	10.76	38.90	46.00	-7.10	Average
10	0.518	34.50	0.76	10.76	46.02	56.00	-9.98	QP
11	2.358	21.61	0.78	10.94	33.33	46.00	-12.67	Average
12	2.422	29.31	0.78	10.94	41.03	56.00	-14.97	QP

Notes:
1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Final Level =Receiver Read level + LISN Factor + Cable Loss.

Neutral:



Trace: 7

Site : CCIS Shielding Room
Condition : FCC PART 15.247 QP LISN(RS) NEUTRAL
EUT : Bluetooth MP3 player
Model : MBT0004
Test Mode : BT mode
Power Rating : AC 120V/60Hz
Environment : Temp: 23 .5°C Huni:57% Atmos:101KPa
Test Engineer: YT
Remark :

	Freq	Read Level	LISN Factor	Cable Loss	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dB	dBuV	dBuV	dB	
1	0.158	38.99	0.70	10.77	50.46	65.56	-15.10	QP
2	0.158	21.87	0.70	10.77	33.34	55.56	-22.22	Average
3	0.188	34.79	0.66	10.76	46.21	64.11	-17.90	QP
4	0.206	20.21	0.66	10.76	31.63	53.36	-21.73	Average
5	0.211	33.89	0.66	10.76	45.31	63.18	-17.87	QP
6	0.299	19.12	0.64	10.74	30.50	50.28	-19.78	Average
7	0.415	29.67	0.62	10.73	41.02	57.55	-16.53	QP
8	0.431	21.26	0.62	10.73	32.61	47.24	-14.63	Average
9	0.510	27.51	0.61	10.76	38.88	46.00	-7.12	Average
10	0.527	34.93	0.61	10.76	46.30	56.00	-9.70	QP
11	2.384	21.50	0.67	10.94	33.11	46.00	-12.89	Average
12	2.422	30.80	0.67	10.94	42.41	56.00	-13.59	QP

Notes:
1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Final Level =Receiver Read level + LISN Factor + Cable Loss.

IC

Line:



Site : CCIS Shielding Room
Condition : ICES-003 QP LISN(RS) LINE
EUT : Bluetooth MP3 player
Model : MBT0004
Test Mode : BT mode
Power Rating : AC 120V/60Hz
Environment : Temp: 23 .5℃ Huni:57% Atmos:101KPa
Test Engineer: YT
Remark :

	Freq	Read Level	LISN Factor	Cable Loss	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dB	dBuV	dBuV	dB	
1	0.150	20.17	0.71	10.78	31.66	56.00	-24.34	Average
2	0.162	37.87	0.71	10.77	49.35	65.34	-15.99	QP
3	0.182	22.88	0.73	10.77	34.38	54.42	-20.04	Average
4	0.186	35.83	0.73	10.76	47.32	64.20	-16.88	QP
5	0.211	33.18	0.73	10.76	44.67	63.18	-18.51	QP
6	0.222	18.88	0.73	10.76	30.37	52.74	-22.37	Average
7	0.234	31.89	0.74	10.75	43.38	62.30	-18.92	QP
8	0.421	19.33	0.75	10.73	30.81	47.42	-16.61	Average
9	0.510	27.38	0.76	10.76	38.90	46.00	-7.10	Average
10	0.518	34.50	0.76	10.76	46.02	56.00	-9.98	QP
11	2.358	21.61	0.78	10.94	33.33	46.00	-12.67	Average
12	2.422	29.31	0.78	10.94	41.03	56.00	-14.97	QP

Notes:
1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Final Level =Receiver Read level + LISN Factor + Cable Loss.

Neutral:



Trace: 7

```
Site          : CCIS Shielding Room
Condition     : ICES-003 QP LISN(RS) NEUTRAL
EUT           : Bluetooth MP3 player
Model         : MBT0004
Test Mode     : BT mode
Power Rating  : AC 120V/60Hz
Environment   : Temp: 23 .5℃ Huni:57%  Atmos:101KPa
Test Engineer: YT
Remark        :
```

	Freq	Read Level	LISN Factor	Cable Loss	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dB	dBuV	dBuV	dB	
1	0.158	38.99	0.70	10.77	50.46	65.56	-15.10	QP
2	0.158	21.87	0.70	10.77	33.34	55.56	-22.22	Average
3	0.188	34.79	0.66	10.76	46.21	64.11	-17.90	QP
4	0.206	20.21	0.66	10.76	31.63	53.36	-21.73	Average
5	0.211	33.89	0.66	10.76	45.31	63.18	-17.87	QP
6	0.299	19.12	0.64	10.74	30.50	50.28	-19.78	Average
7	0.415	29.67	0.62	10.73	41.02	57.55	-16.53	QP
8	0.431	21.26	0.62	10.73	32.61	47.24	-14.63	Average
9	0.510	27.51	0.61	10.76	38.88	46.00	-7.12	Average
10	0.527	34.93	0.61	10.76	46.30	56.00	-9.70	QP
11	2.384	21.50	0.67	10.94	33.11	46.00	-12.89	Average
12	2.422	30.80	0.67	10.94	42.41	56.00	-13.59	QP

Notes:
1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Final Level =Receiver Read level + LISN Factor + Cable Loss.

6.3 Conducted Output Power

Test Requirement:	FCC Part 15 C Section 15.247 (b)(1) RSS-247 section 5.4(b)
Test Method:	ANSI C63.10:2013 and DA00-705
Receiver setup:	RBW=1MHz, VBW=3MHz, Detector=Peak (If 20dB BW ≤1 MHz) RBW=3MHz, VBW=10MHz, Detector=Peak (If 20dB BW > 1 MHz and < 3MHz)
Limit:	FCC: For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts. IC: For FHSs operating in the band 2400-2483.5 MHz, the maximum peak conducted output power shall not exceed 1.0 W if the hopset uses 75 or more hopping channels; the maximum peak conducted output power shall not exceed 0.125 W if the hopset uses less than 75 hopping channels.
Test setup:	
Test Instruments:	Refer to section 5.8 for details
Test mode:	Non-hopping mode
Test results:	Pass

Measurement Data:

Test channel	Peak Output Power (dBm)	Limit (dBm)	Result
GFSK mode			
Lowest	3.10	30.00	Pass
Middle	2.65	30.00	Pass
Highest	2.15	30.00	Pass
π/4-DQPSK mode			
Lowest	2.95	21.00	Pass
Middle	1.21	21.00	Pass
Highest	1.97	21.00	Pass
8DPSK mode			
Lowest	1.64	21.00	Pass
Middle	1.21	21.00	Pass
Highest	1.94	21.00	Pass

Test plot as follows:

Modulation mode: GFSK	Modulation mode: π/4-DQPSK
	
Lowest channel	Lowest channel
	
Middle channel	Middle channel
	
Highest channel	Highest channel

Modulation mode: 8DPSK



Lowest channel



Middle channel



Highest channel

6.4 20dB Occupy Bandwidth

Test Requirement:	FCC Part 15 C Section 15.247 (a)(1) RSS-247 section 5.1(a)
Test Method:	ANSI C63.10:2013 and DA00-705
Receiver setup:	RBW=30 kHz, VBW=100 kHz, detector=Peak
Limit:	N/A
Test setup:	
Test Instruments:	Refer to section 5.8 for details
Test mode:	Non-hopping mode
Test results:	Pass

Measurement Data:

Test channel	20dB&99% Occupy Bandwidth (kHz)		
	GFSK	π/4-DQPSK	8DPSK
Lowest	820	1116	1158
Middle	828	1116	1152
Highest	824	1122	1158

Test plot as follows:

Modulation mode: GFSK	Modulation mode: π/4-DQPSK
	
Lowest channel	Lowest channel
	
Middle channel	Middle channel
	
Highest channel	Highest channel

Modulation mode: 8DPSK



Lowest channel



Middle channel



Highest channel

6.5 Carrier Frequencies Separation

Test Requirement:	FCC Part 15 C Section 15.247 (a)(1) RSS-247 section 5.1(b)
Test Method:	ANSI C63.10:2013 and DA00-705
Receiver setup:	RBW=100 kHz, VBW=300 kHz, detector=Peak
Limit:	0.025MHz or 2/3 of the 20dB bandwidth (whichever is greater)
Test setup:	
Test Instruments:	Refer to section 5.8 for details
Test mode:	Hopping mode
Test results:	Pass

Measurement Data:

Test channel	Carrier Frequencies Separation (kHz)	Limit (kHz)	Result
GFSK			
Lowest	1004	828.00	Pass
Middle	1004	828.00	Pass
Highest	1004	828.00	Pass
π/4-DQPSK mode			
Lowest	1004	744.00	Pass
Middle	1004	744.00	Pass
Highest	1008	744.00	Pass
8DPSK mode			
Lowest	1004	772.00	Pass
Middle	1004	772.00	Pass
Highest	1004	772.00	Pass

Note: According to section 6.4

Mode	20dB bandwidth (kHz) (worse case)	Limit (kHz) (Carrier Frequencies Separation)
GFSK	828	828.00
π/4-DQPSK	1116	744.00
8DPSK	1158	772.00

Test plot as follows:

Modulation mode: GFSK	Modulation mode: π/4-DQPSK
	
Lowest channel	Lowest channel
	
Middle channel	Middle channel
	
Highest channel	Highest channel

Modulation mode: 8DPSK



Lowest channel



Middle channel



Highest channel

6.6 Hopping Channel Number

Test Requirement:	FCC Part 15 C Section 15.247 (a)(1) RSS-247 section 5.1(d)
Test Method:	ANSI C63.10:2013 and DA00-705
Receiver setup:	RBW=100 kHz, VBW=300 kHz, Frequency range=2400MHz-2483.5MHz, Detector=Peak
Limit:	15 channels
Test setup:	
Test Instruments:	Refer to section 5.8 for details
Test mode:	Hopping mode
Test results:	Pass

Measurement Data:

Mode	Hopping channel numbers	Limit	Result
GFSK, π/4-DQPSK, 8DPSK	79	15	Pass

Test plot as follows:

GFSK



Date: 3.MAY.2018 14:44:23

π/4-DQPSK



Date: 3.MAY.2018 14:47:40

8DPSK



Date: 3.MAY.2018 14:50:23

6.7 Dwell Time

Test Requirement:	FCC Part 15 C Section 15.247 (a)(1) RSS-247 section 5.1(d)
Test Method:	ANSI C63.10:2013 and KDB DA00-705
Receiver setup:	RBW=1 MHz, VBW=1 MHz, Span=0 Hz, Detector=Peak
Limit:	0.4 Second
Test setup:	
Test Instruments:	Refer to section 5.8 for details
Test mode:	Hopping mode
Test results:	Pass

Measurement Data (Worse case):

Mode	Packet	Dwell time (second)	Limit (second)	Result
GFSK	DH1	0.13888	0.4	Pass
	DH3	0.27648		
	DH5	0.31744		
π/4-DQPSK	2-DH1	0.13824	0.4	Pass
	2-DH3	0.27552		
	2-DH5	0.31829		
8DPSK	3-DH1	0.13568	0.4	Pass
	3-DH3	0.27552		
	3-DH5	0.31744		

Note:
The test period = 0.4 Second/Channel x 79 Channel = 31.6 s
Calculation Formula: Dwell time = Ton time per hop * Hopping numbers * Period
For example:
DH1 time slot=0.434*(1600/ (2*79)) * 31.6=138.88ms
DH3 time slot=1.728*(1600/ (4*79)) * 31.6=276.48ms
DH5 time slot=2.976*(1600/ (6*79)) * 31.6=317.44ms

Test plot as follows:

Modulation mode: GFSK	Modulation mode: π/4-DQPSK
	
DH1	2-DH1
	
DH3	2-DH3
	
DH5	2-DH5

Modulation mode: 8DPSK



3-DH1



3-DH3



3-DH5

6.8 Pseudorandom Frequency Hopping Sequence

Test Requirement:	FCC Part 15 C Section 15.247 (a)(1) and RSS 247 section 5.1 requirement:

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.

Alternatively. Frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW. The system shall hop to channel frequencies that are selected at the system hopping rate from a Pseudorandom ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

EUT Pseudorandom Frequency Hopping Sequence

The pseudorandom sequence may be generated in a nine-stage shift register whose 5th and 9th stage outputs are added in a modulo-two addition stage. And the result is fed back to the input of the first stage. The sequence begins with the first ONE of 9 consecutive ONEs; i.e. the shift register is initialized with nine ones.

• Number of shift register stages: 9
• Length of pseudo-random sequence: 2^9 -1 = 511 bits
• Longest sequence of zeros: 8 (non-inverted signal)



Linear Feedback Shift Register for Generation of the PRBS sequence

An example of Pseudorandom Frequency Hopping Sequence as follow:



Each frequency used equally on the average by each transmitter.

The system receivers have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shift frequencies in synchronization with the transmitted signals.

6.9 Band Edge

6.9.1 Conducted Emission Method

Test Requirement:	FCC Part 15 C Section 15.247 (d) RSS-247 section 5.5
Test Method:	ANSI C63.10:2013 and DA00-705
Receiver setup:	RBW=100 kHz, VBW=300 kHz, Detector=Peak
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Test setup:	
Test Instruments:	Refer to section 5.8 for details
Test mode:	Non-hopping mode and hopping mode
Test results:	Pass

Test plot as follows:

GFSK	
Lowest Channel	
	
No-hopping mode	Hopping mode
Highest Channel	
	
No-hopping mode	Hopping mode

π/4-DQPSK	
Lowest Channel	
	
No-hopping mode	Hopping mode
Highest Channel	
	
No-hopping mode	Hopping mode

8DPSK	
Lowest Channel	
	
No-hopping mode	Hopping mode
Highest Channel	
	
No-hopping mode	Hopping mode

6.9.2 Radiated Emission Method

Test Requirement:	FCC Part 15 C Section 15.209 and 15.205 RSS-GEN section 8.9 8.10
Test Method:	ANSI C63.10: 2013
Test Frequency Range:	2.3GHz to 2.5GHz
Test Distance:	3m

Receiver setup:

Frequency	Detector	RBW	VBW	Remark
Above 1GHz	Peak	1MHz	3MHz	Peak Value
	RMS	1MHz	3MHz	Average Value

Limit:

Frequency	Limit (dBuV/m @3m)	Remark
Above 1GHz	54.00	Average Value
	74.00	Peak Value

Test setup:



Test Procedure:

1. The EUT was placed on the top of a rotating table 1.5meters above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation.
2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading.
5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

Test Instruments:	Refer to section 5.8 for details
Test mode:	Non-hopping mode
Test results:	Passed

FCC

GFSK mode
Test channel: Lowest channel
Horizontal:




```
Site          : 3m chamber
Condition     : FCC PART 15 (PK) 3m BBHA9120(1G18G) HORIZONTAL
EUT           : Bluetooth MP3 player
Model         : MBT0004
Test mode     : DH1-L mode
Power Rating  : DC 5V
Environment   : Temp:25.5℃  Huni:55%
Test Engineer: YT
REMARK        :
```

	Freq	ReadAntenna Level	Antenna Factor	Cable Loss	Aux Factor	Preamp Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dB	dBuV/m	dBuV/m	dB	
1	2390.000	20.17	25.45	4.69	0.00	0.00	50.31	74.00	-23.69	Peak
2	2390.000	8.73	25.45	4.69	0.00	0.00	38.87	54.00	-15.13	Average

Vertical:



Site : 3m chamber
Condition : FCC PART 15 (PK) 3m BBHA9120(1G18G) VERTICAL
EUT : Bluetooth MP3 player
Model : MBT0004
Test mode : DH1-L mode
Power Rating : DC 5V
Environment : Temp:25.5℃ Huni:55%
Test Engineer: YT
REMARK :

	Freq	ReadLevel	Antenna Factor	Cable Loss	Aux Factor	Preamp Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dB	dBuV/m	dBuV/m	dB	
1	2390.000	21.47	25.45	4.69	0.00	0.00	51.61	74.00	-22.39	Peak
2	2390.000	8.95	25.45	4.69	0.00	0.00	39.09	54.00	-14.91	Average

Test channel: Highest channel

Horizontal:



Site : 3m chamber
Condition : FCC PART 15 (PK) 3m BBHA9120(1G18G) HORIZONTAL
EUT : Bluetooth MP3 player
Model : MBT0004
Test mode : DH1-H mode
Power Rating : DC 5V
Environment : Temp:25.5°C Huni:55%
Test Engineer: YT
REMARK :

	Freq	Read Level	Antenna Factor	Cable Loss	Aux Factor	Preamp Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dB	dBuV/m	dBuV/m	dB	
1	2483.500	20.54	25.66	4.81	0.00	0.00	51.01	74.00	-22.99	Peak
2	2483.500	8.77	25.66	4.81	0.00	0.00	39.24	54.00	-14.76	Average

Vertical:



Site : 3m chamber
Condition : FCC PART 15 (PK) 3m BBHA9120(1G18G) VERTICAL
EUT : Bluetooth MP3 player
Model : MBT0004
Test mode : DH1-H mode
Power Rating : DC 5V
Environment : Temp:25.5℃ Huni:55%
Test Engineer: YT
REMARK :

	Freq	ReadAntenna Level	Factor	Cable Loss	Aux Factor	Preamp Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dB	dBuV/m	dBuV/m	dB	
1	2483.500	22.43	25.66	4.81	0.00	0.00	52.90	74.00	-21.10	Peak
2	2483.500	11.38	25.66	4.81	0.00	0.00	41.85	54.00	-12.15	Average

π/4-DQPSK mode

Test channel: Lowest channel

Horizontal:




```
Site         : 3m chamber
Condition    : FCC PART 15 (PK) 3m BBHA9120(1G18G) HORIZONTAL
EUT          : Bluetooth MP3 player
Model        : MBT0004
Test mode    : 2DH1-L mode
Power Rating : DC 5V
Environment  : Temp:25.5℃  Huni:55%
Test Engineer: YT
REMARK       :
```

	Freq	ReadLevel	Antenna Factor	Cable Loss	Aux Factor	Preamp Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dB	dBuV/m	dBuV/m	dB	
1	2390.000	20.42	25.45	4.69	0.00	0.00	50.56	74.00	-23.44	Peak
2	2390.000	9.33	25.45	4.69	0.00	0.00	39.47	54.00	-14.53	Average

Vertical:



Site : 3m chamber
Condition : FCC PART 15 (PK) 3m BBHA9120(1G18G) VERTICAL
EUT : Bluetooth MP3 player
Model : MBT0004
Test mode : 2DH1-L mode
Power Rating : DC 5V
Environment : Temp:25.5℃ Huni:55%
Test Engineer: YT
REMARK :

	Freq	Read Level	Antenna Factor	Cable Loss	Aux Factor	Preamp Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dB	dBuV/m	dBuV/m	dB	
1	2390.000	17.89	25.45	4.69	0.00	0.00	48.03	74.00	-25.97	Peak
2	2390.000	8.50	25.45	4.69	0.00	0.00	38.64	54.00	-15.36	Average

Test channel: Highest channel

Horizontal:



Site : 3m chamber
Condition : FCC PART 15 (PK) 3m BBHA9120(1G18G) HORIZONTAL
EUT : Bluetooth MP3 player
Model : MBT0004
Test mode : 2DH1-H mode
Power Rating : DC 5V
Environment : Temp:25.5℃ Huni:55%
Test Engineer: YT
REMARK :

	Freq	ReadLevel	Antenna Factor	Cable Loss	Aux Factor	Preamp Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dB	dBuV/m	dBuV/m	dB	
1	2483.500	22.36	25.66	4.81	0.00	0.00	52.83	74.00	-21.17	Peak
2	2483.500	8.76	25.66	4.81	0.00	0.00	39.23	54.00	-14.77	Average

Vertical:



Site : 3m chamber
Condition : FCC PART 15 (PK) 3m BBHA9120(1G18G) VERTICAL
EUT : Bluetooth MP3 player
Model : MBT0004
Test mode : 2DH1-H mode
Power Rating : DC 5V
Environment : Temp:25.5℃ Huni:55%
Test Engineer: YT
REMARK :

	Freq	ReadLevel	Antenna Factor	Cable Loss	Aux Factor	Preamp Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dB	dBuV/m	dBuV/m	dB	
1	2483.500	25.25	25.66	4.81	0.00	0.00	55.72	74.00	-18.28	Peak
2	2483.500	10.68	25.66	4.81	0.00	0.00	41.15	54.00	-12.85	Average

8DPSK mode

Test channel: Lowest channel

Horizontal:



Site : 3m chamber
Condition : FCC PART 15 (PK) 3m BBHA9120(1G18G) HORIZONTAL
EUT : Bluetooth MP3 player
Model : MBT0004
Test mode : 3DH1-L mode
Power Rating : DC 5V
Environment : Temp:25.5℃ Huni:55%
Test Engineer: YT
REMARK :

	Freq	ReadLevel	Antenna Factor	Cable Loss	Aux Factor	Preamp Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dB	dBuV/m	dBuV/m	dB	
1	2390.000	18.28	25.45	4.69	0.00	0.00	48.42	74.00	-25.58	Peak
2	2390.000	8.76	25.45	4.69	0.00	0.00	38.90	54.00	-15.10	Average

Vertical:



Site : 3m chamber
Condition : FCC PART 15 (PK) 3m BBHA9120(1G18G) VERTICAL
EUT : Bluetooth MP3 player
Model : MBT0004
Test mode : 3DH1-L mode
Power Rating : DC 5V
Environment : Temp:25.5°C Huni:55%
Test Engineer: YT
REMARK :

	Freq	ReadLevel	Antenna Factor	Cable Loss	Aux Factor	Preamp Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dB	dBuV/m	dBuV/m	dB	
1	2390.000	17.75	25.45	4.69	0.00	0.00	47.89	74.00	-26.11	Peak
2	2390.000	8.41	25.45	4.69	0.00	0.00	38.55	54.00	-15.45	Average

Test channel: Highest

Horizontal:



Site : 3m chamber
Condition : FCC PART 15 (PK) 3m BBHA9120(1G18G) HORIZONTAL
EUT : Bluetooth MP3 player
Model : MBT0004
Test mode : 3DH1-H mode
Power Rating : DC 5V
Environment : Temp:25.5℃ Huni:55%
Test Engineer: YT
REMARK :

	Freq	ReadLevel	Antenna Factor	Cable Loss	Aux Factor	Preamp Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dB	dBuV/m	dBuV/m	dB	
1	2483.500	21.45	25.66	4.81	0.00	0.00	51.92	74.00	-22.08	Peak
2	2483.500	8.75	25.66	4.81	0.00	0.00	39.22	54.00	-14.78	Average

Vertical:



Site : 3m chamber
Condition : FCC PART 15 (PK) 3m BBHA9120(1G18G) VERTICAL
EUT : Bluetooth MP3 player
Model : MBT0004
Test mode : 3DH1-H mode
Power Rating : DC 5V
Environment : Temp:25.5℃ Huni:55%
Test Engineer: YT
REMARK :

	Freq	ReadLevel	Antenna Factor	Cable Loss	Aux Factor	Preamp Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dB	dBuV/m	dBuV/m	dB	
1	2483.500	22.65	25.66	4.81	0.00	0.00	53.12	74.00	-20.88	Peak
2	2483.500	10.68	25.66	4.81	0.00	0.00	41.15	54.00	-12.85	Average

IC

GFSK mode
Test channel: Lowest channel
Horizontal:




```
Site          : 3m chamber
Condition     : ICES003 CLASS B (PK) 3m BBHA9120(1G18G) HORIZONTAL
EUT           : Bluetooth MP3 player
Model         : MBT0004
Test mode     : DH1-L mode
Power Rating  : DC 5V
Environment   : Temp:25.5℃  Huni:55%
Test Engineer: YT
REMARK        :
```

	Freq	ReadLevel	Antenna Factor	Cable Loss	Aux Factor	Preamp Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dB	dBuV/m	dBuV/m	dB	
1	2390.000	20.17	25.45	4.69	0.00	0.00	50.31	74.00	-23.69	Peak
2	2390.000	8.73	25.45	4.69	0.00	0.00	38.87	54.00	-15.13	Average

Vertical:



Site : 3m chamber
Condition : ICES003 CLASS B (PK) 3m BBHA9120(1G18G) VERTICAL
EUT : Bluetooth MP3 player
Model : MBT0004
Test mode : DH1-L mode
Power Rating : DC 5V
Environment : Temp:25.5℃ Huni:55%
Test Engineer: YT
REMARK :

	Freq	Read Level	Antenna Factor	Cable Loss	Aux Factor	Preamp Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dB	dBuV/m	dBuV/m	dB	
1	2390.000	21.47	25.45	4.69	0.00	0.00	51.61	74.00	-22.39	Peak
2	2390.000	8.95	25.45	4.69	0.00	0.00	39.09	54.00	-14.91	Average

Test channel: Highest channel

Horizontal:



Site : 3m chamber
Condition : ICES003 CLASS B (PK) 3m BBHA9120(1G18G) HORIZONTAL
EUT : Bluetooth MP3 player
Model : MBT0004
Test mode : DH1-H mode
Power Rating : DC 5V
Environment : Temp:25.5℃ Huni:55%
Test Engineer: YT
REMARK :

	Freq	ReadLevel	Antenna Factor	Cable Loss	Aux Factor	Preamp Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dB	dBuV/m	dBuV/m	dB	
1	2483.500	20.54	25.66	4.81	0.00	0.00	51.01	74.00	-22.99	Peak
2	2483.500	8.77	25.66	4.81	0.00	0.00	39.24	54.00	-14.76	Average

Vertical:



Site : 3m chamber
Condition : ICES003 CLASS B (PK) 3m BBHA9120(1G18G) VERTICAL
EUT : Bluetooth MP3 player
Model : MBT0004
Test mode : DH1-H mode
Power Rating : DC 5V
Environment : Temp:25.5℃ Huni:55%
Test Engineer: YT
REMARK :

	Freq	ReadLevel	Antenna Factor	Cable Loss	Aux Factor	Preamp Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dB	dBuV/m	dBuV/m	dB	
1	2483.500	22.43	25.66	4.81	0.00	0.00	52.90	74.00	-21.10	Peak
2	2483.500	11.38	25.66	4.81	0.00	0.00	41.85	54.00	-12.15	Average

π/4-DQPSK mode

Test channel: Lowest channel

Horizontal:




```
Site          : 3m chamber
Condition     : ICES003 CLASS B (PK) 3m BBHA9120(1G18G) HORIZONTAL
EUT           : Bluetooth MP3 player
Model         : MBT0004
Test mode     : 2DH1-L mode
Power Rating  : DC 5V
Environment   : Temp:25.5'C  Huni:55%
Test Engineer: YT
REMARK        :
```

	Freq	ReadAntenna Level	Antenna Factor	Cable Loss	Aux Factor	Preamp Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dB	dBuV/m	dBuV/m	dB	
1	2390.000	20.42	25.45	4.69	0.00	0.00	50.56	74.00	-23.44	Peak
2	2390.000	9.33	25.45	4.69	0.00	0.00	39.47	54.00	-14.53	Average

Vertical:



Site : 3m chamber
Condition : ICES003 CLASS B (PK) 3m BBHA9120(1G18G) VERTICAL
EUT : Bluetooth MP3 player
Model : MBT0004
Test mode : 2DH1-L mode
Power Rating : DC 5V
Environment : Temp:25.5℃ Huni:55%
Test Engineer: YT
REMARK :

	Freq	ReadLevel	Antenna Factor	Cable Loss	Aux Factor	Preamp Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dB	dBuV/m	dBuV/m	dB	
1	2390.000	17.89	25.45	4.69	0.00	0.00	48.03	74.00	-25.97	Peak
2	2390.000	8.50	25.45	4.69	0.00	0.00	38.64	54.00	-15.36	Average

Test channel: Highest channel

Horizontal:



Site : 3m chamber
Condition : ICES003 CLASS B (PK) 3m BBHA9120(1G18G) HORIZONTAL
EUT : Bluetooth MP3 player
Model : MBT0004
Test mode : 2DH1-H mode
Power Rating : DC 5V
Environment : Temp:25.5°C Huni:55%
Test Engineer: YT
REMARK :

	Freq	Read Level	Antenna Factor	Cable Loss	Aux Factor	Preamp Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dB	dBuV/m	dBuV/m	dB	
1	2483.500	22.36	25.66	4.81	0.00	0.00	52.83	74.00	-21.17	Peak
2	2483.500	8.76	25.66	4.81	0.00	0.00	39.23	54.00	-14.77	Average

Vertical:



Site : 3m chamber
Condition : ICES003 CLASS B (PK) 3m BBHA9120(1G18G) VERTICAL
EUT : Bluetooth MP3 player
Model : MBT0004
Test mode : 2DH1-H mode
Power Rating : DC 5V
Environment : Temp:25.5℃ Huni:55%
Test Engineer: YT
REMARK :

	Freq	ReadLevel	Antenna Factor	Cable Loss	Aux Factor	Preamp Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dB	dBuV/m	dBuV/m	dB	
1	2483.500	25.25	25.66	4.81	0.00	0.00	55.72	74.00	-18.28	Peak
2	2483.500	10.68	25.66	4.81	0.00	0.00	41.15	54.00	-12.85	Average

8DPSK mode

Test channel: Lowest channel

Horizontal:



Site : 3m chamber
Condition : ICES003 CLASS B (PK) 3m BBHA9120(1G18G) HORIZONTAL
EUT : Bluetooth MP3 player
Model : MBT0004
Test mode : 3DH1-L mode
Power Rating : DC 5V
Environment : Temp:25.5'C Huni:55%
Test Engineer: YT
REMARK :

	Freq	Read Level	Antenna Factor	Cable Loss	Aux Factor	Preamp Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dB	dBuV/m	dBuV/m	dB	
1	2390.000	18.28	25.45	4.69	0.00	0.00	48.42	74.00	-25.58	Peak
2	2390.000	8.76	25.45	4.69	0.00	0.00	38.90	54.00	-15.10	Average

Vertical:



Site : 3m chamber
Condition : ICES003 CLASS B (PK) 3m BBHA9120(1G18G) VERTICAL
EUT : Bluetooth MP3 player
Model : MBT0004
Test mode : 3DH1-L mode
Power Rating : DC 5V
Environment : Temp:25.5℃ Huni:55%
Test Engineer: YT
REMARK :

	Freq	ReadLevel	Antenna Factor	Cable Loss	Aux Factor	Preamp Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dB	dBuV/m	dBuV/m	dB	
1	2390.000	17.75	25.45	4.69	0.00	0.00	47.89	74.00	-26.11	Peak
2	2390.000	8.41	25.45	4.69	0.00	0.00	38.55	54.00	-15.45	Average

Test channel: Highest

Horizontal:



Site : 3m chamber
Condition : ICES003 CLASS B (PK) 3m BBHA9120(1G18G) HORIZONTAL
EUT : Bluetooth MP3 player
Model : MBT0004
Test mode : 3DH1-H mode
Power Rating : DC 5V
Environment : Temp:25.5℃ Huni:55%
Test Engineer: YT
REMARK :

	Freq	ReadLevel	Antenna Factor	Cable Loss	Aux Factor	Preamp Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dB	dBuV/m	dBuV/m	dB	
1	2483.500	21.45	25.66	4.81	0.00	0.00	51.92	74.00	-22.08	Peak
2	2483.500	8.75	25.66	4.81	0.00	0.00	39.22	54.00	-14.78	Average

Vertical:



Site : 3m chamber
Condition : ICES003 CLASS B (PK) 3m BBHA9120(1G18G) VERTICAL
EUT : Bluetooth MP3 player
Model : MBT0004
Test mode : 3DH1-H mode
Power Rating : DC 5V
Environment : Temp:25.5°C Huni:55%
Test Engineer: YT
REMARK :

	Freq	Read Level	Antenna Factor	Cable Loss	Aux Factor	Preamp Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dB	dBuV/m	dBuV/m	dB	
1	2483.500	22.65	25.66	4.81	0.00	0.00	53.12	74.00	-20.88	Peak
2	2483.500	10.68	25.66	4.81	0.00	0.00	41.15	54.00	-12.85	Average

6.10 Spurious Emission

6.10.1 Conducted Emission Method

Test Requirement:	FCC Part 15 C Section 15.247 (d) RSS-247 section 5.5
Test Method:	ANSI C63.10:2013 and DA00-705
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Test setup:	
Test Instruments:	Refer to section 5.8 for details
Test mode:	Non-hopping mode
Test results:	Pass

Test plot as follows:

GFSK	π/4-DQPSK
Lowest channel	Lowest channel
	
30MHz~25GHz	30MHz~25GHz
Middle channel	Middle channel
	
30MHz~25GHz	30MHz~25GHz
Highest channel	Highest channel
	
30MHz~25GHz	30MHz~25GHz

8DPSK
Lowest channel

30MHz~25GHz
Middle channel

30MHz~25GHz
Highest channel

30MHz~25GHz

6.10.2 Radiated Emission Method

Test Requirement:	FCC Part 15 C Section 15.209 and 15.205 RSS-Gen section 8.9 8.10				
Test Method:	ANSI C63.10: 2013				
Test Frequency Range:	9 kHz to 25 GHz				
Test Distance:	3m				
Receiver setup:	Frequency	Detector	RBW	VBW	Remark
	30MHz-1GHz	Quasi-peak	120kHz	300kHz	Quasi-peak Value
	Above 1GHz	Peak	1MHz	3MHz	Peak Value
		RMS	1MHz	3MHz	Average Value

Limit:	Frequency	Limit (dBuV/m @3m)	Remark
	30MHz-88MHz	40.0	Quasi-peak Value
	88MHz-216MHz	43.5	Quasi-peak Value
	216MHz-960MHz	46.0	Quasi-peak Value
	960MHz-1GHz	54.0	Quasi-peak Value
	Above 1GHz	54.0	Average Value
		74.0	Peak Value

Test setup:

Below 1GHz



Above 1GHz



Test Procedure:	1. The EUT was placed on the top of a rotating table 0.8m(below 1GHz) /1.5m(above 1GHz) above the ground at a 3 meter chamber. The table was rotated 360 degrees to determine the position of the highest radiation. 2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. 3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. 4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading. 5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. 6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
Test Instruments:	Refer to section 5.8 for details
Test mode:	Non-hopping mode
Test results:	Pass
Remark:	1. Pre-scan all kind of the place mode (X-axis, Y-axis, Z-axis), and found the Y-axis is the worst case. 2. 9 kHz to 30 MHz is noise floor, so only shows the data of above 30MHz in this report.

Measurement data:
FCC

Below 1GHz

Vertical:



Site : 3m chamber
Condition : FCC PART15 CLASS B 3m VULB9163(30M2G) VERTICAL
EUT : Bluetooth MP3 player
Model : MBT0004
Test mode : BT mode
Power Rating : AC 120V/60Hz
Environment : Temp:25.5℃ Huni:55%
Test Engineer: YT
REMARK :

	Freq	ReadLevel	Antenna Factor	Cable Loss	Preamp Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	30.000	47.14	11.20	0.72	29.98	29.08	40.00	-10.92	QP
2	119.856	46.14	10.30	2.17	29.39	29.22	43.50	-14.28	QP
3	155.364	48.85	8.56	2.55	29.17	30.79	43.50	-12.71	QP
4	199.986	46.25	11.30	2.87	28.83	31.59	43.50	-11.91	QP
5	287.990	42.65	13.03	2.91	28.47	30.12	46.00	-15.88	QP
6	434.065	38.65	15.60	3.16	28.84	28.57	46.00	-17.43	QP

Horizontal:



Site : 3m chamber
Condition : FCC PART15 CLASS B 3m VULB9163(30M2G) HORIZONTAL
EUT : Bluetooth MP3 player
Model : MBT0004
Test mode : BT mode
Power Rating : AC 120V/60Hz
Environment : Temp:25.5℃ Huni:55%
Test Engineer: YT
REMARK :

	Freq	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	119.856	41.07	10.30	2.17	29.39	24.15	43.50	-19.35	QP
2	147.921	44.54	8.46	2.50	29.23	26.27	43.50	-17.23	QP
3	191.745	43.13	10.58	2.81	28.89	27.63	43.50	-15.87	QP
4	336.035	41.96	14.10	3.05	28.53	30.58	46.00	-15.42	QP
5	360.448	43.77	14.64	3.10	28.61	32.90	46.00	-13.10	QP
6	564.639	31.86	17.58	3.90	29.05	24.29	46.00	-21.71	QP

IC

Below 1GHz

Vertical:



Site : 3m chamber
Condition : ICES-003 CLASS-B 3m VULB9163(30M2G) VERTICAL
EUT : Bluetooth MP3 player
Model : MBT0004
Test mode : BT mode
Power Rating : AC 120V/60Hz
Environment : Temp:25.5℃ Huni:55%
Test Engineer: YT
REMARK :

	Freq	ReadLevel	Antenna Factor	Cable Loss	Preamp Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	30.000	47.14	11.20	0.72	29.98	29.08	40.00	-10.92	QP
2	119.856	46.14	10.30	2.17	29.39	29.22	43.50	-14.28	QP
3	155.364	48.85	8.56	2.55	29.17	30.79	43.50	-12.71	QP
4	199.986	46.25	11.30	2.87	28.83	31.59	43.50	-11.91	QP
5	287.990	42.65	13.03	2.91	28.47	30.12	46.00	-15.88	QP
6	434.065	38.65	15.60	3.16	28.84	28.57	46.00	-17.43	QP

Horizontal:



Site : 3m chamber
Condition : ICES-003 CLASS-B 3m VULB9163(30M2G) HORIZONTAL
EUT : Bluetooth MP3 player
Model : MBT0004
Test mode : BT mode
Power Rating : AC 120V/60Hz
Environment : Temp:25.5℃ Huni:55%
Test Engineer: YT
REMARK :

	Freq	ReadLevel	Antenna Factor	Cable Loss	Preamp Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	119.856	41.07	10.30	2.17	29.39	24.15	43.50	-19.35	QP
2	147.921	44.54	8.46	2.50	29.23	26.27	43.50	-17.23	QP
3	191.745	43.13	10.58	2.81	28.89	27.63	43.50	-15.87	QP
4	336.035	41.96	14.10	3.05	28.53	30.58	46.00	-15.42	QP
5	360.448	43.77	14.64	3.10	28.61	32.90	46.00	-13.10	QP
6	564.639	31.86	17.58	3.90	29.05	24.29	46.00	-21.71	QP

Above 1GHz:

Test channel:			Lowest		Level:		Peak	
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4804	50.60	30.85	6.80	41.81	46.44	74.00	-27.56	Vertical
4804	53.68	30.85	6.80	41.81	49.52	74.00	-24.48	Horizontal
Test channel:			Lowest		Level:		Average	
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4804.00	48.98	30.85	6.80	41.81	44.82	54.00	-9.18	Vertical
4804.00	52.24	30.85	6.80	41.81	48.08	54.00	-5.92	Horizontal

Test channel:			Middle		Level:		Peak	
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4882.00	49.01	31.20	6.86	41.84	45.23	74.00	-28.77	Vertical
4882.00	54.58	31.20	6.86	41.84	50.80	74.00	-23.20	Horizontal
Test channel:			Middle		Level:		Average	
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4882.00	48.56	31.20	6.86	41.84	44.78	54.00	-9.22	Vertical
4882.00	52.58	31.20	6.86	41.84	48.80	54.00	-5.20	Horizontal

Test channel:			Highest		Level:		Peak	
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4960.00	50.96	31.63	6.91	41.87	47.63	74.00	-26.37	Vertical
4960.00	52.73	31.63	6.91	41.87	49.40	74.00	-24.60	Horizontal
Test channel:			Highest		Level:		Average	
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4960.00	48.51	31.63	6.91	41.87	45.18	54.00	-8.82	Vertical
4960.00	49.86	31.63	6.91	41.87	46.53	54.00	-7.47	Horizontal

Remark:

1. *Final Level =Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor*
2. *The emission levels of other frequencies are very lower than the limit and not show in test report.*