

FCC TEST REPORT

Under
FCC 15 Subpart C, Paragraph 15.247
&
(Operating in 2400 ~ 2483.5 MHz Band)

Prepared For :

Calibeur Measurements (Hong Kong) Co., Limited

B46 Bldg., 2nd Ind . Zone, TangLang, XiLi ,Shenzhen, China.

FCC ID: SWTIC-510S
EUT: Wi-Fi Video Scope
Model: IC-510S, IC-510M, IC-510R

August 31, 2015 Issue Date:
Original Report Report Type:
<i>Eric Guo</i> Test Engineer: Eric Guo
<i>Apollo Liu</i> Review By: Apollo Liu / Manager

The test report consists 61 pages in total. It may be duplicated completely for legal use with the allowance of the applicant. It shall not be reproduced except in full, without the written approval of Ke Mei Ou Laboratory Corporation. The test result in the report only applied to the tested sample.

TABLE OF CONTENTS

1. General Information	3
1. 1 Notes	3
1. 2 Testing Laboratory	3
1. 3 Details of Applicant	3
1. 4 Application Details	3
1. 5 Test Item	3
1. 6 Test Standards	3
2. Technical Test	4
2. 1 Summary of Test Results	4
2. 2 Antenna Requirement	4
3. EUT Modifications	4
4. Conducted Power Line Test	5
4. 1 Test Equipment	5
4. 2 Test Procedure	5
4. 3 Test Setup	5
4. 4 Configuration of the EUT	6
4. 5 EUT Operating Condition	8
4. 6 Conducted Power Line Emission Limits	8
4. 7 Conducted Power Line Test Result	9
5. FCC Part 15.247 Requirements for DTS Systems	10
5. 1 Test Equipment	10
5. 2 Test Procedure	10
5. 3 Test Setup	10
5. 4 Configuration of the EUT	10
5. 5 EUT Operating Condition	10
5. 6 Limit	11
5. 7 Test Result	12
6. Transmitter Spurious Radiated Emission at 3 Meters	25
6. 1 Test Equipment	31
6. 2 Test Procedure	31
6. 3 Test Setup	31
6. 4 Configuration of the EUT	32
6. 5 EUT Operating Condition	32
6. 6 Limit	33
6. 7 Test Result	34
7. RF Exposure Requirements	42
7. 1 Test Equipment	47
7. 2 Limit	47
7. 3 Test Result	47
8. Photos of Testing	48
8. 1 EUT Test Photographs	48
8. 2 EUT Detailed Photographs	49
9. FCC ID Label	60
10. Test Equipment	61

2. Technical Test

2.1 Summary of Test Results

The EUT has been tested according to the following specifications:

FCC Rule	Test Type	Limit	Result	Notes
FCC 15.247(a)(2)	6dB Bandwidth	$\geq 0.5\text{MHz}$	PASS	Complies
FCC 15.247(b)(1)	Peak Output Power	$\leq 30\text{dBm}$	PASS	Complies
FCC 15.247(e)	Power Spectral Density	$\leq 8\text{dBm}$	PASS	Complies
FCC 15.247(d)	Conducted Band Edges and Spurious Emission	$\leq 20\text{dBc}$	PASS	Complies.
FCC 15.247(d)	Radiated Band Edges and Spurious Emission	FCC 15.209(a) & 15.247(d)	PASS	Complies.
FCC 15.207	AC Conducted Emission	FCC 15.207(a)	PASS	Complies.
FCC 15.203 & 15.247(b)	Antenna Requirement	N/A	PASS	Complies

* The digital circuit porting of the EUT has been tested and verified to comply with FCC Part 15, Subpart B., Class B Digital Devices and the associated Radio Receiver has also been tested and found to comply with FCC Part 15, Subpart B – Radio Receivers.

2.2 Antenna Requirement

A. Regulation

FCC section 15.203, An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of Part 15C. The manufacturer may design the unit so that the user can replace a broken antenna, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of Sections 15.211, 15.213, 15.217, 15.219, or 15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with Section 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this Part are not exceeded.

B. Result

The antenna type used in this product is internal Antenna and fixed in the EUT and without connector. That no antenna other than furnished by the responsible party shall be used with the device. The EUT as tested meets the criteria of this rule by being antenna being permanently attached and professionally installed. The EUT is compliant with Section 15.203.

3. EUT Modifications

No modification by test lab.

4. Conducted Power Line Test

4.1 Test Equipment


Please refer to Section 10 this report.

4.2 Test Procedure

The EUT and simulators are connected to the main power through a line impedance stabilization network (L.I.S.N.). This provides a 50 ohm/50uH coupling impedance for the measuring equipment. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination.

Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission., the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10:2013 on conducted measurement. Conducted emissions were invested over the frequency range from 0.15MHz to 30MHz using a receiver bandwidth of 9kHz.

4.3 Test Setup



For the actual test configuration, Please refer to the related items – Photos of Testing.

4.4 Configuration of the EUT


The EUT was configured according to ANSI C63.10:2013 . EUT was used DC6V Battery. The operation frequency is from 2412MHz~2462MHz. Enable the signal transmitted from the EUT to Notebook PC. All interface ports were connected to the appropriate peripherals. All peripherals and cables are listed below.

A. EUT

Device	Manufacturer	Model #	FCC ID
Wi-Fi Video Scope	Same as applicant	IC-510S	SWTIC-510S

Field Antenna For 2.4GHz Band

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)	Remark
0	Bailan Electronic Technology CO.,LTD.	KABIA2425-0A	WIFI Antenna Internal	N/A	2.00	TX/RX



ANT0
TX0/RX0

Note:

The EUT provides one completed transmit and receiver.

802.11b/g/n Carrier Frequencies For 2.4GHz Band

Frequency Band	Channel No.	Frequency	Channel No.	Frequency
2400~2483.5Mhz	1	2412MHz	7	2442MHz
	2	2417MHz	8	2447MHz
	3	2422MHz	9	2452MHz
	4	2427MHz	10	2457MHz
	5	2432MHz	11	2462MHz
	6	2437MHz		

Test Modes For 2.4GHz Band

Test Items	Mode	Data Rate	Channel	Antenna
AC Power Line Conducted Emissions	Normal Link	Auto	-	-
Maximum Peak Conducted Output Power Power Spectral Density 6dB Spectrum Bandwidth	MCS0/20MHz	7.2 Mbps	1/6/11	0
	MCS0/40MHz	15 Mbps	3/6/9	-
	11b/BPSK	1 Mbps	1/6/11	0
	11g/BPSK	6 Mbps	1/6/11	0
Radiated Emissions 9kHz~1GHz	Normal Link	Auto	-	-
Radiated Emissions 1GHz~10 th Harmonic	MCS0/20MHz	7.2 Mbps	1/6/11	0
	MCS0/40MHz	15 Mbps	3/6/9	-
	11b/BPSK	1 Mbps	1/6/11	0
	11g/BPSK	6 Mbps	1/6/11	0
Band Edge Emissions	MCS0/20MHz	7.2 Mbps	1/11	0
	MCS0/40MHz	15 Mbps	3/9	-
	11b/BPSK	1 Mbps	1/11	0
	11g/BPSK	6 Mbps	1/11	0

Note: Preliminary tests were performed in different data rate to find the worst radiated emission. The data rate show in the table above is the worst-case rate with respect to the specific test item. Investigation has been done on all the possible configurations for searching the worst cases. During testing, Channel & Power Controlling Software provided by the customer was used to control the operating channel as well as the output power level, The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the find end product.

B. Internal Devices

Device	Manufacturer	Model #	FCC ID
N/A			


C. Peripherals

Device	Manufacturer	Model # Serial #	FCC ID/ DoC	Cable
Printer	HP	HP930C	DoC	1.5m unshielded power cord 1.2m unshielded data cable.
Modem	GVC	N/A	DoC	1.5m unshielded power cord 1.2m unshielded data cable.
Notebook	DELL	PP10L	DoC	1.5m unshielded power cord
PC	Dell	2400n	DoC	1.5m unshielded power cord

4. 5 EUT Operating Condition

Operating condition is according to ANSI C63.10:2013.

- A. Setup the EUT and simulators as shown on follow.
- B. Enable RF signal and confirm EUT active.
- C. Modulate output capacity of EUT up to specification.



4. 6 Conducted Power Line Emission Limits

FCC Part 15 Paragraph 15.207 (dBuV)		
Frequency Range (MHz)	Class A QP/AV	Class B QP/AV
0.15 – 0.5	79/66	66-56/56-46
0.5 – 5.0	73/60	56/46
5.0 – 30	73/60	60/50

NOTE : In the above table, the tighter limit applies at the band edges.

4. 7 Conducted Power Line Test Result

Product	: Wi-Fi Video Scope	Test Mode	: Normal Link / Auto
Test Item	: Conducted Emission Data	Temperature	: 25 °C
Test Voltage	: DC 6V (By battery)	Humidity	: 56%RH
Test Result	: N/A	Adapter Model	:

The frequency spectrum from 0.15 MHz to 30 MHz was investigated. All readings are quasi -peak values with a resolution bandwidth of 9 KHz.

- Temperature : 26 °C
- Humidity : 53 % RH

FCC Part 15 Paragraph 15.207							
Frequency (MHz)	Emission (dBuV)		LINE/ NEUTRAL	Limit (dBuV)		Margin (dB)	
	QP	AV		QP	AV	QP	AV
N/A			LINE				
			NEUTRAL				
			LINE				
			NEUTRAL				
			LINE				
			NEUTRAL				

Note: NF = No Significant Peak was Found.

Note:

- 1.Uncertainty in conducted emission measured is <+/- 2dB.
- 2.The emission levels of other frequencies were very low against the limit.
- 3.All Reading Levels are Quasi-Peak and Average value.
- 4.Emission = Meter Reading + Factor; Factor = Insertion Loss + Cable Loss.
- 5.Margin Value = Emission Level - Limit Value.

5. FCC Part 15.247 Requirements for DTS Systems


5.1 Test Equipment

Please refer to Section 10 this report.

5.2 Test Procedure

6 dB & 99% Bandwidth	Refer to FCC 15.247(a)(2), ANSI C63.10:2013
Test Method:	FCC KDB Publication No. 558074 D01 DTS Meas Guidance v03r03. - 8.1 Option 1
a) Set RBW = 100 kHz. b) Set the video bandwidth (VBW) $\geq 3 \times$ RBW. c) Detector = Peak. d) Trace mode = max hold. e) Sweep = auto couple. f) Allow the trace to stabilize.	g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission. *For 99% Bandwidth Measurement, the spectrum analyzer's resolution bandwidth (RBW) is set 30kHz and set the Video bandwidth (VBW) = 100kHz.
Peak Power:	Refer to FCC 15.247(b)(3), ANSI C63.10:2013
Test Method:	FCC KDB Publication No. 558074 D01 DTS Meas Guidance v03r03. - 9.1.2 PKPM1 Peak power meter method
The maximum peak conducted output power may be measured using a broadband peak RF power meter. The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall utilize a fast-responding diode detector.	
Peak Power Spectral Density:	Refer to FCC 15.247(e), ANSI C63.10:2013
Test Method:	FCC KDB Publication No. 558074 D01 DTS Meas Guidance v03r03. - 10.2 Method PKPSD
a) Set analyzer center frequency to DTS channel center frequency. b) Set the span to 1.5 times the DTS bandwidth. c) Set the RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$. d) Set the VBW $\geq 3 \times$ RBW. e) Detector = peak. f) Sweep time = auto couple.	g) Trace mode = max hold. h) Allow trace to fully stabilize. i) Use the peak marker function to determine the maximum amplitude level within the RBW. j) If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.
Band Edges Measurement:	Refer to FCC 15.247(d), ANSI C63.10:2013
Test Method:	FCC KDB Publication No. 558074 D01 DTS Meas Guidance v03r03.& 15.247
a. The transmitter output was connected to the spectrum analyzer via a low lose cable. b. Set both RBW and VBW of spectrum analyzer to 100kHz with suitable frequency span including 100kHz bandwidth from band edge. c. The band edges was measured and recorded.	

5.3 Test Setup



5.4 Configuration of the EUT

Same as section 4.4 of this report

5.5 EUT Operating Condition

Same as section 4.5 of this report.

5.6 Limit

According to §15.247(a)(2), systems using digital modulation techniques may operate in the 902 ~ 928 MHz, 2400 ~ 2483.5 MHz, and 5725 ~ 5850 MHz bands. The minimum 6dB bandwidth shall be at least 500 kHz.

According to §15.247(b)(3), for systems using digital modulation in the bands of 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz: 1 Watt.

According to §15.247(b)(4), the conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be

reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

According to §15.247(d), in any 100 kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power

limits. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in 15.209(a) (see Section 15.205(c)).

According to §15.247(e), for digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

According to §15.247(f), the digital modulation operation of the hybrid system, with the frequency hopping turned off, shall comply with the power density requirements of paragraph (d) of this section.

5. 7 Test Result

A. 6 dB & 99% Occupied Bandwidth

Product : Wi-Fi Video Scope
 Test Item : 6 dB BW
 Test Voltage : DC 6V (Power by battery)
 Test Result : **PASS**

Test Mode : IEEE 802.11b/g/n
 Temperature : 25 °C
 Humidity : 56%RH

IEEE 802.11b

Channel	Frequency (MHz)	Bandwidth (MHz)	FCC Limit (kHz)	Result
Low	2412	10.00	>500 kHz	PASS
Mid	2437	9.84		PASS
High	2462	10.12		PASS

IEEE 802.11g

Channel	Frequency (MHz)	Bandwidth (MHz)	FCC Limit (kHz)	Result
Low	2412	15.04	>500 kHz	PASS
Mid	2437	15.12		PASS
High	2462	13.84		PASS

Draft n MCS0 20MHz Ant.0


Channel	Frequency (MHz)	Bandwidth (MHz)	FCC Limit (kHz)	Result
Low	2412	15.40	>500 kHz	PASS
Mid	2437	15.36		PASS
High	2462	15.52		PASS

Draft n MCS0 40MHz Ant.0

Channel	Frequency (MHz)	Bandwidth (MHz)	FCC Limit (kHz)	Result
Low	2422	33.84	>500 kHz	PASS
Mid	2437	33.88		PASS
High	2452	33.84		PASS


IEEE 802.11b

6dB Bandwidth (CH Low)




Date: 2.JUL.2015 11:53:15

6dB Bandwidth (CH Mid)



Date: 2.JUL.2015 11:57:06


6dB Bandwidth (CH High)



Date: 2.JUL.2015 12:00:45


IEEE 802.11g

6dB Bandwidth (CH Low)




Date: 20.JUL.2015 16:54:48

6dB Bandwidth (CH Mid)



Date: 20.JUL.2015 16:57:36


6dB Bandwidth (CH High)



Date: 20.JUL.2015 17:05:11


Draft n MCS0 20MHz Ant.0

6dB Bandwidth (CH Low)




Date: 2.JUL.2015 14:01:47

6dB Bandwidth (CH Mid)



Date: 6.JUL.2015 10:57:06


6dB Bandwidth (CH High)



Date: 6.JUL.2015 11:01:55


Draft n MCS0 40MHz Ant.0

6dB Bandwidth (CH Low)




Date: 6.JUL.2015 11:15:54

6dB Bandwidth (CH Mid)



Date: 6.JUL.2015 11:22:27

6dB Bandwidth (CH High)



Date: 20.JUL.2015 16:10:49

B. Peak Power

Product	: Wi-Fi Video Scope	Test Mode	: 802.11b/g/n
Test Item	: Peak Power	Temperature	: 25 °C
Test Voltage	: DC 6V (Power by battery)	Humidity	: 56%RH
Test Result	: PASS		

IEEE 802.11b

Channel	Frequency (MHz)	Output Power (dBm)	FCC Limit (W/dBm)	Result
Low	2412	2.04	1.00/30.00	PASS
Mid	2437	2.23		PASS
High	2462	6.44		PASS

IEEE 802.11g

Channel	Frequency (MHz)	Output Power (dBm)	FCC Limit (W/dBm)	Result
Low	2412	2.43	1.00/30.00	PASS
Mid	2437	3.40		PASS
High	2462	6.21		PASS

Draft n MCS8 20MHz Ant.0

Channel	Frequency (MHz)	Output Power (dBm)	FCC Limit (W/dBm)	Result
Low	2412	2.01	1.00/30.00	PASS
Mid	2437	4.09		PASS
High	2462	6.87		PASS


Draft n MCS8 40MHz Ant.0

Channel	Frequency (MHz)	Output Power (dBm)	FCC Limit (W/dBm)	Result
Low	2422	4.37	1.00/30.00	PASS
Mid	2437	4.89		PASS
High	2452	5.13		PASS

C. Band Edges Measurement


Product	: Wi-Fi Video Scope	Test Mode	: 802.11b/g/n
Test Item	: Band Edges Measurement	Temperature	: 25 °C
Test Voltage	: DC 6V (Power by battery)	Humidity	: 56%RH
Test Result	: PASS		

IEEE 802.11b Channel: Low




Date: 7.JUL.2015 15:52:52

IEEE 802.11b Channel: High




Date: 7.JUL.2015 15:59:23

IEEE 802.11g Channel: Low




Date: 7.JUL.2015 16:13:48

IEEE 802.11g Channel: High




Date: 7.JUL.2015 16:08:26

IEEE 802.11n MCS8 20MHz Ant.0
Channel: Low




Date: 20.JUL.2015 18:11:51

IEEE 802.11n MCS8 20MHz Ant.0
Channel: High




Date: 20.JUL.2015 18:20:42

IEEE 802.11n MCS8 40MHz Ant.0
Channel: Low



Date: 7.JUL.2015 16:36:04

IEEE 802.11n MCS8 40MHz Ant.0
Channel: High



Date: 20.JUL.2015 16:18:50

D. Peak Power Spectral Density

Product	: Wi-Fi Video Scope	Test Mode	: 802.11b/g/n
Test Item	: Peak Power Spectral Density	Temperature	: 25 °C
Test Voltage	: DC 6V (Power by battery)	Humidity	: 56%RH
Test Result	: PASS		

IEEE 802.11b

Channel	Frequency (MHz)	3kHz PPSD (dBm)	FCC Limit (dBm)	Result
Low	2412	-20.96	8.00	PASS
Mid	2437	-17.47		PASS
High	2462	-13.75		PASS

IEEE 802.11g

Channel	Frequency (MHz)	3kHz PPSD (dBm)	FCC Limit (dBm)	Result
Low	2412	-22.04	8.00	PASS
Mid	2437	-17.63		PASS
High	2462	-14.05		PASS


Draft n MCS0 20MHz Ant.0

Channel	Frequency (MHz)	3kHz PPSD (dBm)	FCC Limit (dBm)	Result
Low	2412	-20.34	8.00	PASS
Mid	2437	-18.17		PASS
High	2462	-13.05		PASS

Draft n MCS8 40MHz Ant.0


Channel	Frequency (MHz)	3kHz PPSD (dBm)	FCC Limit (dBm)	Result
Low	2422	-17.76	8.00	PASS
Mid	2437	-15.91		PASS
High	2452	-15.00		PASS

IEEE 802.11b Channel: Low




Date: 7.JUL.2015 16:51:17

IEEE 802.11b Channel: Mid




Date: 7.JUL.2015 16:56:40

IEEE 802.11b Channel: High




Date: 7.JUL.2015 17:02:38

IEEE 802.11g Channel: Low




Date: 7.JUL.2015 17:05:53

IEEE 802.11g Channel: Mid




Date: 7.JUL.2015 17:28:23

IEEE 802.11g Channel: High




Date: 7.JUL.2015 17:22:15

Draft n MCS0 20MHz Ant.0/2412MHZ
(Channel: Low)




Date: 21.JUL.2015 09:41:48

Draft n MCS0 20MHz Ant.0/2437MHZ
(Channel: Mid)




Date: 21.JUL.2015 09:48:08

Draft n MCS0 20MHz Ant.0/2462MHZ
(Channel: High)




Date: 21.JUL.2015 09:54:03

Draft n MCS0 40MHz Ant.0/2422MHZ
(Channel: Low)




Date: 7.JUL.2015 17:44:06

Draft n MCS0 40MHz Ant.0/2437MHZ
(Channel: Mid)



Date: 7.JUL.2015 17:56:07

Draft n MCS0 40MHz Ant.0/2452MHZ
(Channel: High)



Date: 20.JUL.2015 16:33:32

6. Transmitter Spurious Radiated Emission at 3 Meters

6.1 Test Equipment


Please refer to Section 10 this report.

6.2 Test Procedure


1. The EUT was tested according to ANSI C63.10:2013.
2. The EUT, peripherals were put on the turntable which table size is 1m x 1.5 m, table high 0.8 m, and which is 1.5 m high for above 1 GHz. All set up is according to ANSI C63.10:2013 .
3. The frequency spectrum from 9 kHz to 25 GHz was investigated. All readings from 9 kHz to 150 kHz are quasi-peak values with a resolution bandwidth of 200 Hz. All readings from 150 kHz to 30 MHz are quasi-peak values with a resolution bandwidth of 9 KHz. All readings from 30 MHz to 1 GHz are quasi-peak values with a resolution bandwidth of 120 KHz. All readings are above 1 GHz , peak values with a resolution bandwidth of 1 MHz . Measurements were made at 3 meters.
4. The emissions from the EUT were measured continuously at every azimuth by rotating the turntable. The Receiving antenna high is varied from 1 m to 4 m high to find the maximum emission for each frequency. Emissions below 30MHz were measured with a loop antenna while emission above 30MHz were measured using a broadband E-field antenna.
5. Maximizing procedure was performed on the six (6) highest emissions to ensure EUT compliance is with all installation combinations. All data was recorded in the peak detection mode. Quasi-peak readings was performed only when an emission was found to be marginal (within -4 dB of specification limit), and are distinguished with a "QP" in the data table.
6. Each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the max. emission, the relative positions of this transmitter(EUT) was rotated through three orthogonal axes according to the requirements in Section 8 and 13 of ANSI C63.10:2013

6.3 Test Setup

For Frequencies below 30 MHz



For the actual test configuration , please refer to the related items – Photos of Testing

For Frequencies above 30 MHz

For the actual test configuration , please refer to the related items – Photos of Testing

6. 4 Configuration of the EUT

Same as section 4.4 of this report

6. 5 EUT Operating Condition

Same as section 4.5 of this report.

6.6 Limit

In any 100 KHz bandwidth outside the operating frequency band, the radio frequency power that is produced by modulation products of the spreading sequence, the information sequence and the carrier frequency shall be either at least 20 dB below that in any 100 KHz bandwidth within the band that contains the highest level of the desired power or shall not exceed the general levels specified in section 15.209(a), which lesser attenuation.

All other emissions inside restricted bands specified in section 15.205(a) shall not exceed the general radiated emission limits specified in section 15.209(a)

Note:

Applies to harmonics/spurious emissions that fall in the restricted bands listed in section 15.205. The maximum permitted average field strength is listed in section 15.209.

47 CFR § 15.237(c): The emission limits as specified above are based on measurement instrument employing an average detector. The provisions in section 15.35 for limiting peak emissions apply.

FCC CFR 47, Part 15, Subpart C, Para. 15.205(a) – Restricted Frequency Bands

MHz	MHz	MHz	GHz
0.090–0.110	16.42–16.423	399.9–410	4.5–5.15
¹ 0.495–0.505	16.69475–16.69525	608–614	5.35–5.46
2.1735–2.1905	16.80425–16.80475	960–1240	7.25–7.75
4.125–4.128	25.5–25.67	1300–1427	8.025–8.5
4.17725–4.17775	37.5–38.25	1435–1626.5	9.0–9.2
4.20725–4.20775	73–74.6	1645.5–1646.5	9.3–9.5
6.215–6.218	74.8–75.2	1660–1710	10.6–12.7
6.26775–6.26825	108–121.94	1718.8–1722.2	13.25–13.4
6.31175–6.31225	123–138	2200–2300	14.47–14.5
8.291–8.294	149.9–150.05	2310–2390	15.35–16.2
8.362–8.366	156.52475–156.52525	2483.5–2500	17.7–21.4
8.37625–8.38675	156.7–156.9	2655–2900	22.01–23.12
8.41425–8.41475	162.0125–167.17	3260–3267	23.6–24.0
12.29–12.293	167.72–173.2	3332–3339	31.2–31.8
12.51975–12.52025	240–285	3345.8–3358	36.43–36.5
12.57675–12.57725	322–335.4	3600–4400	(²)
13.36–13.41			

¹ Until February 1, 1999, this restricted band shall be 0.490–0.510 MHz.

² Above 38.6


FCC 47 CFR, Part 15.209(a) – Field Strength Limits within Restricted Frequency Bands

Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009–0.490	2400/F(kHz)	300
0.490–1.705	24000/F(kHz)	30
1.705–30.0	30	30
30–88	100**	3
88–216	150**	3
216–960	200**	3
Above 960	500	3

6.7 Test Result

Transmitter Radiated Bandedge Emissions

802.11b CH Low



Date: 31.AUG.2015 10:06:27

Transmitter Radiated Bandedge Emissions Result								
Modulation	802.11b		Non-restricted Band Emissions					
Non-restricted Band (MHz)	Channel (MHz)	In-band PSD [a] (dBuV/100kHz)	Freq. (MHz)	Out-band PSD [b] (dBuV/100kHz)	[a] – [b] (dB)	Limit (dB)	Level Type	Pol. note 1
2390-2400	2412	96.62	2395.200	50.57	46.05	20	PK	H


Note 1: Measurement at the “worst case” settings emissions of receive antenna polarization: H (Horizontal) or V (Vertical)

Modulation	802.11b		Restricted Band Emissions					
Restricted Band (MHz)	Channel (MHz)	In-band PSD (dBuV/100kHz)	Freq. (MHz)	Measure Distance (m)	Out-Band Level (dBuV/m)	Limit (dB)	Level Type	Pol. note 1
2310-2390	2412	96.36	2375.200	3	47.48	74	PK	H
2310-2390	2412	/	2375.200	3	/	54	AV	H

Note 1: Measurement at the “worst case” settings emissions of receive antenna polarization: H (Horizontal) or V (Vertical)

Note 2: Average emission setting: RBW=1MHz; VBW $\geq 1/T$, where T is “Pulse On Time”, e.g., LE VBW $\geq 1/625\mu s$, VBW=3kHz.

802.11b CH High




Date: 31.AUG.2015 10:13:38

Transmitter Radiated Bandedge Emissions Result								
Modulation	802.11b		Non-restricted Band Emissions					
Non-restricted Band (MHz)	Channel (MHz)	In-band PSD [a] (dBuV/100kHz)	Freq. (MHz)	Out-band PSD [b] (dBuV/100kHz)	[a] – [b] (dB)	Limit (dB)	Level Type	Pol. note 1
2500-2690	2462	97.60	2500.000	49.41	48.19	20	PK	H
Note 1: Measurement at the “worst case” settings emissions of receive antenna polarization: H (Horizontal) or V (Vertical)								

Modulation	802.11b		Restricted Band Emissions					
Restricted Band (MHz)	Channel (MHz)	In-band PSD (dBuV/100kHz)	Freq. (MHz)	Measure Distance (m)	Out-Band Level (dBuV/m)	Limit (dB)	Level Type	Pol. note 1
2483.5-2500	2462	97.41	2490.000	3	45.15	74	PK	H
2483.5-2500	2462	/	2490.000	3	/	54	AV	H
Note 1: Measurement at the “worst case” settings emissions of receive antenna polarization: H (Horizontal) or V (Vertical)								
Note 2: Average emission setting: RBW=1MHz; VBW ≥ 1/T, where T is “Pulse On Time” , e.g., LE VBW≥1/625us, VBW=3kHz.								

802.11g CH Low



Date: 28.AUG.2015 17:42:51

Transmitter Radiated Bandedge Emissions Result								
Modulation	802.11g		Non-restricted Band Emissions					
Non-restricted Band (MHz)	Channel (MHz)	In-band PSD [a] (dBuV/100kHz)	Freq. (MHz)	Out-band PSD [b] (dBuV/100kHz)	[a] – [b] (dB)	Limit (dB)	Level Type	Pol. note 1
2390-2400	2412	96.71	2399.200	69.37	27.34	20	PK	H


Note 1: Measurement at the “worst case” settings emissions of receive antenna polarization: H (Horizontal) or V (Vertical)

Modulation	802.11g		Restricted Band Emissions					
Restricted Band (MHz)	Channel (MHz)	In-band PSD (dBuV/100kHz)	Freq. (MHz)	Measure Distance (m)	Out-Band Level (dBuV/m)	Limit (dB)	Level Type	Pol. note 1
2310-2390	2412	96.65	2388.000	3	52.07	74	PK	H
2310-2390	2412	/	2388.000	3	/	54	AV	H

Note 1: Measurement at the “worst case” settings emissions of receive antenna polarization: H (Horizontal) or V (Vertical)

Note 2: Average emission setting: RBW=1MHz; VBW $\geq 1/T$, where T is “Pulse On Time”, e.g., LE VBW $\geq 1/625\mu s$, VBW=3kHz.

802.11g CH High



Date: 31.AUG.2015 11:12:53

Transmitter Radiated Bandedge Emissions Result								
Modulation	802.11g		Non-restricted Band Emissions					
Non-restricted Band (MHz)	Channel (MHz)	In-band PSD [a] (dBuV/100kHz)	Freq. (MHz)	Out-band PSD [b] (dBuV/100kHz)	[a] – [b] (dB)	Limit (dB)	Level Type	Pol. note 1
2500-2690	2462	99.70	2546.000	49.67	50.03	20	PK	H


Note 1: Measurement at the “worst case” settings emissions of receive antenna polarization: H (Horizontal) or V (Vertical)

Modulation	802.11g		Restricted Band Emissions					
Restricted Band (MHz)	Channel (MHz)	In-band PSD (dBuV/100kHz)	Freq. (MHz)	Measure Distance (m)	Out-Band Level (dBuV/m)	Limit (dB)	Level Type	Pol. note 1
2483.5-2500	2462	99.62	2484.800	3	69.99	74	PK	H
2483.5-2500	2462	/	2484.800	3	42.94	54	AV	H

Note 1: Measurement at the “worst case” settings emissions of receive antenna polarization: H (Horizontal) or V (Vertical)

Note 2: Average emission setting: RBW=1MHz; VBW $\geq 1/T$, where T is “Pulse On Time”, e.g., LE VBW $\geq 1/625\mu s$, VBW=3kHz.

802.11n HT20



Transmitter Radiated Bandedge Emissions Result								
Modulation	802.11n HT20		Non-restricted Band Emissions					
Non-restricted Band (MHz)	Channel (MHz)	In-band PSD [a] (dBuV/100kHz)	Freq. (MHz)	Out-band PSD [b] (dBuV/100kHz)	[a] – [b] (dB)	Limit (dB)	Level Type	Pol. note 1
2390-2400	2412	96.72	2399.600	69.37	27.35	20	PK	H


Note 1: Measurement at the “worst case” settings emissions of receive antenna polarization: H (Horizontal) or V (Vertical)

Modulation	802.11n HT20		Restricted Band Emissions					
Restricted Band (MHz)	Channel (MHz)	In-band PSD (dBuV/100kHz)	Freq. (MHz)	Measure Distance (m)	Out-Band Level (dBuV/m)	Limit (dB)	Level Type	Pol. note 1
2310-2390	2412	96.55	2389.600	3	56.10	74	PK	H
2310-2390	2412	/	2389.600	3	39.64	54	AV	H

Note 1: Measurement at the “worst case” settings emissions of receive antenna polarization: H (Horizontal) or V (Vertical)

Note 2: Average emission setting: RBW=1MHz; VBW $\geq 1/T$, where T is “Pulse On Time”, e.g., LE VBW $\geq 1/625\mu s$, VBW=3kHz.

802.11HT20 CH High



Date: 31.AUG.2015 10:47:28

Transmitter Radiated Bandedge Emissions Result								
Modulation	802.11n HT20		Non-restricted Band Emissions					
Non-restricted Band (MHz)	Channel (MHz)	In-band PSD [a] (dBuV/100kHz)	Freq. (MHz)	Out-band PSD [b] (dBuV/100kHz)	[a] – [b] (dB)	Limit (dB)	Level Type	Pol. note 1
2500-2690	2462	99.68	2544.000	49.27	50.41	20	PK	H
Note 1: Measurement at the “worst case” settings emissions of receive antenna polarization: H (Horizontal) or V (Vertical)								

Modulation	802.11n HT20		Restricted Band Emissions					
Restricted Band (MHz)	Channel (MHz)	In-band PSD (dBuV/100kHz)	Freq. (MHz)	Measure Distance (m)	Out-Band Level (dBuV/m)	Limit (dB)	Level Type	Pol. note 1
2483.5-2500	2462	99.61	2483.600	3	60.57	74	PK	H
2483.5-2500	2462	/	2483.600	3	43.02	54	AV	H
Note 1: Measurement at the “worst case” settings emissions of receive antenna polarization: H (Horizontal) or V (Vertical)								
Note 2: Average emission setting: RBW=1MHz; VBW ≥ 1/T, where T is “Pulse On Time” , e.g., LE VBW≥1/625us, VBW=3kHz.								

Date: 28.AUG.2015 18:05:58

Transmitter Radiated Bandedge Emissions Result								
Modulation	802.11n HT40		Non-restricted Band Emissions					
Non-restricted Band (MHz)	Channel (MHz)	In-band PSD [a] (dBuV/100kHz)	Freq. (MHz)	Out-band PSD [b] (dBuV/100kHz)	[a] – [b] (dB)	Limit (dB)	Level Type	Pol. note 1
2390-2400	2422	96.41	2398.800	69.56	26.85	20	PK	H
Note 1: Measurement at the “worst case” settings emissions of receive antenna polarization: H (Horizontal) or V (Vertical)								

Modulation	802.11n HT40		Restricted Band Emissions					
Restricted Band (MHz)	Channel (MHz)	In-band PSD (dBuV/100kHz)	Freq. (MHz)	Measure Distance (m)	Out-Band Level (dBuV/m)	Limit (dB)	Level Type	Pol. note 1
2310-2390	2422	96.38	2389.200	3	56.59	74	PK	H
2310-2390	2422	/	2389.200	3	33.47	54	AV	H

Note 1: Measurement at the “worst case” settings emissions of receive antenna polarization: H (Horizontal) or V (Vertical)

Note 2: Average emission setting: RBW=1MHz; VBW $\geq 1/T$, where T is “Pulse On Time”, e.g., LE VBW $\geq 1/625\mu s$, VBW=3kHz.



Note 1: Measurement at the “worst case” settings emissions of receive antenna polarization: H (Horizontal) or V (Vertical)

Note 1: Measurement at the “worst case” settings emissions of receive antenna polarization: H (Horizontal) or V (Vertical)

Note 2: Average emission setting: RBW=1MHz; VBW $\geq 1/T$, where T is “Pulse On Time”, e.g., LE VBW $\geq 1/625\mu s$, VBW=3kHz.

Harmonics Radiated Emission Data**IEEE 802.11b Channel: Low**

Freq. (MHz)	Emission (dBuV/m) Peak Detector	HORIZ / VERT	Limits (dBuV/m) Peak / Average	Margin (dB)
4824.00	48.76	HORZ	74.0 / 54.0	-25.24
4824.00	47.68	VERT	74.0 / 54.0	-26.32
7236.00	47.17	HORZ	74.0 / 54.0	-26.83
7236.08	47.04	VERT	74.0 / 54.0	-26.96
9648.02	47.11	HORZ	74.0 / 54.0	-26.89
9648.10	47.02	VERT	74.0 / 54.0	-26.98
24120.04	-	HORZ	74.0 / 54.0	-
24120.20	-	VERT	74.0 / 54.0	-

IEEE 802.11b Channel: Mid

Freq. (MHz)	Emission (dBuV/m) Peak Detector	HORIZ / VERT	Limits (dBuV/m) Peak / Average	Margin (dB)
4874.00	48.49	HORZ	74.0 / 54.0	-25.51
4874.00	47.96	VERT	74.0 / 54.0	-26.04
7311.00	48.24	HORZ	74.0 / 54.0	-25.76
7311.02	47.68	VERT	74.0 / 54.0	-26.32
9748.10	48.01	HORZ	74.0 / 54.0	-25.99
9748.00	47.39	VERT	74.0 / 54.0	-26.61
24370.10	-	HORZ	74.0 / 54.0	-
24370.00	-	VERT	74.0 / 54.0	-

IEEE 802.11b Channel: High

Freq. (MHz)	Emission (dBuV/m) Peak Detector	HORIZ / VERT	Limits (dBuV/m) Peak / Average	Margin (dB)
4924.00	48.85	HORZ	74.0 / 54.0	-25.15
4924.00	48.11	VERT	74.0 / 54.0	-25.89
7386.12	48.33	HORZ	74.0 / 54.0	-25.67
7368.00	47.89	VERT	74.0 / 54.0	-26.11
9848.00	48.23	HORZ	74.0 / 54.0	-25.77
9848.00	47.66	VERT	74.0 / 54.0	-26.34
24620.11	-	HORZ	74.0 / 54.0	-
24620.00	-	VERT	74.0 / 54.0	-

- Note:**
- (1) All Reading Levels below 1GHz are Quasi-Peak, above are peak and average value.
 - (2) Emission Level = Reading Level + Probe Factor + Cable Loss.
 - (3) Receiver setting (Peak Detector) : RBW=1MHz; VBW=1MHz; Span=100MHz
 - (4) Receiver setting (AVG Detector): RBW=1MHz; VBW=30Hz; Span=20MHz
 - (5) The average measurement was not performed when the peak measured data under the limit of average detection. If the readings given are average, peak measurement should also be supplied.
 - (6) Where an emission level is indicated by a -, levels had a margin greater than 20 dB when compared to the limit.

IEEE 802.11g Channel: Low

Freq. (MHz)	Emission (dBuV/m) Peak	HORIZ / VERT	Limits (dBuV/m) Peak / Average	Margin (dB)
4824.00	48.56	HORZ	74.0 / 54.0	-25.44
4824.00	48.22	VERT	74.0 / 54.0	-25.78
7236.00	48.15	HORZ	74.0 / 54.0	-25.85
7236.08	47.89	VERT	74.0 / 54.0	-26.11
9648.02	48.03	HORZ	74.0 / 54.0	-25.97
9648.10	47.67	VERT	74.0 / 54.0	-26.33
24120.04	-	HORZ	74.0 / 54.0	-
24120.20	-	VERT	74.0 / 54.0	-

IEEE 802.11g Channel: Mid

Freq. (MHz)	Emission (dBuV/m) Peak	HORIZ / VERT	Limits (dBuV/m) Peak / Average	Margin (dB)
4874.00	48.95	HORZ	74.0 / 54.0	-25.05
4874.00	48.44	VERT	74.0 / 54.0	-25.56
7311.00	48.79	HORZ	74.0 / 54.0	-25.21
7311.02	48.26	VERT	74.0 / 54.0	-25.74
9748.10	48.18	HORZ	74.0 / 54.0	-25.82
9748.00	47.94	VERT	74.0 / 54.0	-26.06
24370.10	-	HORZ	74.0 / 54.0	-
24370.00	-	VERT	74.0 / 54.0	-

IEEE 802.11g Channel: High

Freq. (MHz)	Emission (dBuV/m) Peak	HORIZ / VERT	Limits (dBuV/m) Peak / Average	Margin (dB)
4924.00	48.99	HORZ	74.0 / 54.0	-25.01
4924.00	48.46	VERT	74.0 / 54.0	-25.54
7386.12	48.73	HORZ	74.0 / 54.0	-25.27
7368.00	48.32	VERT	74.0 / 54.0	-25.68
9848.00	48.12	HORZ	74.0 / 54.0	-25.88
9848.00	47.88	VERT	74.0 / 54.0	-26.12
24620.11	-	HORZ	74.0 / 54.0	-
24620.00	-	VERT	74.0 / 54.0	-

- Note:**
- (1) All Reading Levels below 1GHz are Quasi-Peak, above are peak and average value.
 - (2) Emission Level = Reading Level + Probe Factor + Cable Loss.
 - (3) Receiver setting (Peak Detector) : RBW=1MHz; VBW=1MHz; Span=100MHz
 - (4) Receiver setting (AVG Detector): RBW=1MHz; VBW=30Hz; Span=20MHz
 - (5) The average measurement was not performed when the peak measured data under the limit of average detection. If the readings given are average, peak measurement should also be supplied.
 - (6) Where an emission level is indicated by a -, levels had a margin greater than 20 dB when compared to the limit.

802.11n MCS8 20MHz Ant.0 Channel: Low

Freq. (MHz)	Emission (dBuV/m) Peak /Av	HORIZ / VERT	Limits (dBuV/m) Peak / Average	Margin (dB)
4824.00	48.88	HORZ	74.0 / 54.0	-25.12
4824.00	48.25	VERT	74.0 / 54.0	-25.75
7236.00	48.36	HORZ	74.0 / 54.0	-25.64
7236.08	48.12	VERT	74.0 / 54.0	-25.88
9648.02	47.98	HORZ	74.0 / 54.0	-26.02
9648.10	47.55	VERT	74.0 / 54.0	-26.45
24120.04	-	HORZ	74.0 / 54.0	-
24120.20	-	VERT	74.0 / 54.0	-

802.11n MCS8 20MHz Ant.0 Channel: Mid

Freq. (MHz)	Emission (dBuV/m) Peak	HORIZ / VERT	Limits (dBuV/m) Peak / Average	Margin (dB)
4874.00	48.79	HORZ	74.0 / 54.0	-25.21
4874.00	48.32	VERT	74.0 / 54.0	-25.68
7311.00	48.45	HORZ	74.0 / 54.0	-25.55
7311.02	48.13	VERT	74.0 / 54.0	-25.87
9748.10	47.67	HORZ	74.0 / 54.0	-26.33
9748.00	47.25	VERT	74.0 / 54.0	-26.75
24370.10	-	HORZ	74.0 / 54.0	-
24370.00	-	VERT	74.0 / 54.0	-

802.11n MCS8 20MHz Ant.0 Channel: High

Freq. (MHz)	Emission (dBuV/m) Peak /Av	HORIZ / VERT	Limits (dBuV/m) Peak / Average	Margin (dB)
4924.00	49.12	HORZ	74.0 / 54.0	-24.88
4924.00	48.76	VERT	74.0 / 54.0	-25.24
7386.12	48.87	HORZ	74.0 / 54.0	-25.13
7368.00	48.55	VERT	74.0 / 54.0	-25.45
9848.00	48.45	HORZ	74.0 / 54.0	-25.55
9848.00	48.22	VERT	74.0 / 54.0	-25.78
24620.11	-	HORZ	74.0 / 54.0	-
24620.00	-	VERT	74.0 / 54.0	-

- Note:**
- (1) All Reading Levels below 1GHz are Quasi-Peak, above are peak and average value.
 - (2) Emission Level = Reading Level + Probe Factor + Cable Loss.
 - (3) Receiver setting (Peak Detector) : RBW=1MHz; VBW=1MHz; Span=100MHz
 - (4) Receiver setting (AVG Detector): RBW=1MHz; VBW=30Hz; Span=20MHz
 - (5) The average measurement was not performed when the peak measured data under the limit of average detection. If the readings given are average, peak measurement should also be supplied.
 - (6) Where an emission level is indicated by a -, levels had a margin greater than 20 dB when compared to the limit.

802.11n MCS8 40MHz Ant.0 Channel: Low

Freq. (MHz)	Emission (dBuV/m) Peak /Av	HORIZ / VERT	Limits (dBuV/m) Peak / Average	Margin (dB)
4844.00	48.57	HORZ	74.0 / 54.0	-25.43
4844.00	48.36	VERT	74.0 / 54.0	-25.64
7266.00	48.12	HORZ	74.0 / 54.0	-25.88
7266.08	47.86	VERT	74.0 / 54.0	-26.14
9688.02	47.89	HORZ	74.0 / 54.0	-26.11
9688.10	47.33	VERT	74.0 / 54.0	-26.67
24220.04	-	HORZ	74.0 / 54.0	-
24220.20	-	VERT	74.0 / 54.0	-

802.11n MCS8 40MHz Ant.0 Channel: Mid

Freq. (MHz)	Emission (dBuV/m) Peak	HORIZ / VERT	Limits (dBuV/m) Peak / Average	Margin (dB)
4874.00	48.58	HORZ	74.0 / 54.0	-25.42
4874.00	48.36	VERT	74.0 / 54.0	-25.64
7311.00	48.24	HORZ	74.0 / 54.0	-25.76
7311.02	48.11	VERT	74.0 / 54.0	-25.89
9748.10	47.85	HORZ	74.0 / 54.0	-26.15
9748.00	47.43	VERT	74.0 / 54.0	-26.57
24370.10	-	HORZ	74.0 / 54.0	-
24370.00	-	VERT	74.0 / 54.0	-

802.11n MCS8 40MHz Ant.0 Channel: High

Freq. (MHz)	Emission (dBuV/m) Peak /Av	HORIZ / VERT	Limits (dBuV/m) Peak / Average	Margin (dB)
4904.00	48.88	HORZ	74.0 / 54.0	-25.12
4904.00	48.54	VERT	74.0 / 54.0	-25.46
7356.12	48.27	HORZ	74.0 / 54.0	-25.73
7356.00	48.01	VERT	74.0 / 54.0	-25.99
9808.00	47.69	HORZ	74.0 / 54.0	-26.31
9808.00	47.32	VERT	74.0 / 54.0	-26.68
24520.11	-	HORZ	74.0 / 54.0	-
24520.00	-	VERT	74.0 / 54.0	-

- Note:**
- (1) All Reading Levels below 1GHz are Quasi-Peak, above are peak and average value.
 - (2) Emission Level = Reading Level + Probe Factor + Cable Loss.
 - (3) Receiver setting (Peak Detector) : RBW=1MHz; VBW=1MHz; Span=100MHz
 - (4) Receiver setting (AVG Detector): RBW=1MHz; VBW=30Hz; Span=20MHz
 - (5) The average measurement was not performed when the peak measured data under the limit of average detection. If the readings given are average, peak measurement should also be supplied.
 - (6) Where an emission level is indicated by a -, levels had a margin greater than 20 dB when compared to the limit.

General Radiated Emission Data

Product	: Wi-Fi Video Scope	Test Mode	: IEEE 802.11b/g/n
Test Item	: Spurious Radiated Emissions	Temperature	: 25 °C
Test Voltage	: DC 6V (Power by battery)	Humidity	: 56%RH
Test Result	: PASS		

For Frequency below 30MHz

Freq. (MHz)	Emission (dBuV/m) QP Detector	HORIZ / VERT	Limits (dBuV/m)	Margin (dB)
N/A				
N/A				
N/A				
N/A				
N/A				
N/A				

- Note:**
- (1) All Readings below 1GHz are Quasi-Peak, above are performed with peak and/or average measurements as necessary.
 - (2) "N/A" remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
 - (3) Emission Level = Reading Level + Probe Factor + Cable Loss.


For Frequency from 30MHz to 1GHz

Freq. (MHz)	Emission (dBuV/m) QP Detector	HORIZ / VERT	Limits (dBuV/m)	Margin (dB)
324.040	42.83	HORZ	46.0	-3.17
72.000	27.31	VERT	40.0	-12.69
480.040	41.55	HORZ	46.0	-4.45
165.400	26.35	VERT	43.5	-17.15
960.120	41.64	HORZ	54.0	-12.36
480.000	34.79	VERT	46.0	-11.21

- Note:**
- (1) All Readings below 1GHz are Quasi-Peak, above are performed with peak and/or average measurements as necessary.
 - (2) "N/A" remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
 - (3) Emission Level = Reading Level + Probe Factor + Cable Loss.

Radiated Emission

FCC 15.209



Date: 25 JUN 2015 15:49:03

7. RF Exposure Requirements

7.1 Test Equipment

Please refer to Section 10 this report.

7.2 Limit

According to FCC 15.247(e)(i) and FCC 1.1307(b)(1), Systems operating under provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the Commissions guidelines.

According to KDB 447498 D01 General RF Exposure v05, section 4.3.1

SAR Test Exclusion Thresholds for 100 MHz-6GHz and ≤ 50 mm

Frequency Range		Maximum measured transmitter power frequency(MHz)	SAR Limitation (mW)
Low Frequency(MHz)	High Frequency(MHz)		
2402	2480	2402	10

7.3 Test Result

Product : Wi-Fi Video Scope
 Test Item : RF Exposure
 Test Voltage : DC 6V (Power by battery)
 Test Result : **PASS**

Test Mode : IEEE 802.11b/g/n
 Temperature : 25 °C
 Humidity : 56%RH

RF Exposure Requirements	Compliance with FCC Rules
EIRP= $P \times G$ Where: P=Power input to antenna G=Power gain of the antenna relative to an isotropic radiator	Maximum output power at antenna input terminal: 6.44 dBm = 4.41 mW (802.11b, 2462MHz) 6.21 dBm = 4.18 mW (802.11g, 2462MHz) 6.87 dBm = 4.86 mW (802.11n/20MHz, 2462MHz) 5.13 dBm = 3.26 mW (802.11n/40MHz, 2452MHz) Prediction distance: ≤ 50 mm Antenna gain : 2.0 dBi SAR Test Exclusion Threshold is 10 mW (802.11b, 2462MHz):6.98 mW (802.11g, 2462MHz):6.62 mW (802.11n/20MHz, 2462MHz):7.71 mW (802.11n/40MHz, 2452MHz):5.16 mW The max. output power E.I.R.P < 10 mW Conclusion: No SAR is required.


8. Photos of Testing

8.1 EUT Test Photographs


Radiated Emission test view(Frequency from 30MHz to 1GHz)



Radiated Emission test view(Frequency above 1GHz)




8. 2 EUT Detailed Photographs





EUT bottom view







EUT inside whole view



Main board component side



Main board solder side



IC-510M

EUT top view






EUT bottom view





IC-510R

EUT top view





EUT bottom view






9. FCC&IC ID Label

FCC ID: SWTIC-510S

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

The Label must not be a stick-on paper label. The Label on these products must be permanently affixed to the product and readily visible at the time of purchase and must last the expected lifetime of the equipment not be readily detachable.

Proposed Label Location on EUT



10. Test Equipment

The following test equipments were used during the radiated & conducted emission test:

Equipment/ Facilities	Manufacturer	Model #	Serial No.	Due Date
Turntable	Innco systems GmbH	CT-0801	KMO-SZ114	NCR
Antenna Tower	Innco systems GmbH	MM4000-PP	KMO-SZ115	NCR
Controller	Innco systems GmbH	CO2000	KMO-SZ116	NCR
Pre-Amplifier	Agilent	87405C	KMO-SZ155	Dec.6, 2015
Pre-Amplifier	Com-Power	PAM-840	KMO-SZ156	Dec.6, 2015
Horn Antenna	Com-Power	AH-840	KMO-SZ157	Dec.6, 2015
EMI Test Receiver	Rohde & Schwarz	ESPI7	KMO-SZ002	June 27, 2016
Spectrum Analyzer	Rohde & Schwarz	FSP40	KMO-SZ003	June 27, 2016
Signal Generator	FLUKE	PM5418+Y/C	KMO-SZ020	May 27, 2016
Loop Antenna	Rohde & Schwarz	HFH2-Z2	KMO-SZ004	Jan. 30, 2016
Trilog-Super Broadband Antenna	SCHWARZBECK	VULB9161	KMO-SZ005	Sep.18, 2015
Trilog-Super Broadband Antenna	SCHWARZBECK	VULB9161	KMO-SZ006	Sep.18, 2015
Broad-Band Horn Antenna	SCHWARZBECK	BBHA 9120D	KMO-SZ007	Sep.18, 2015
Broad-Band Horn Antenna	SCHWARZBECK	BBHA 9120D	KMO-SZ008	Sep.18, 2015
AMN	Rohde & Schwarz	ESH3-Z5	KMO-SZ009	June 27, 2016
Pulse Limiter	SCHWARZBECK	VTSD 9561-F	KMO-SZ077	Nov.29, 2015
ISN	SCHWARZBECK	NTFM 8158 CAT3	KMO-SZ070	Nov.19, 2015
ISN	SCHWARZBECK	NTFM 8158 CAT5	KMO-SZ071	Nov.19, 2015
ISN	SCHWARZBECK	NTFM 8158 CAT6	KMO-SZ072	Nov.19, 2015
KMO Shielded Room	KMO	KMO-001	KMO-SZ036	NCR
Coaxial Cable with N-Connectors	SCHWARZBECK	AK9515H	KMO-SZ037	Sep.18, 2015
AC Power Source / Analyzer	Agilent	6813B	KMO-SZ166	July 22, 2016
Digital Radio Communication Tester	Rohde & Schwarz	CMD60	KMO-SZ169	April 10, 2016
Universal Radio Communication Tester	Rohde & Schwarz	CMU200	KMO-SZ170	April 10, 2016
Regulatory Test System 30 MHz to 40 GHz	Rohde & Schwarz	TS8997	KMO-HK015	Nov.6, 2015
Program Control Telephone Exchanger	Excelltel	CDX8000-M	KMO-SZ221	NCR
3m Anechoic Chamber	KMO	KMO-3AC	KMO-3AC-1	Nov.12, 2016
Temperature Chamber	TABAI	PSL-4GTW	N/A	Feb.10, 2016