

FCC RF Test Report

APPLICANT : Ubiquiti Networks, Inc.
EQUIPMENT : airCube Loco
BRAND NAME : UBIQUITI
MODEL NAME : ACB-LOCO
FCC ID : SWX-ACBLOCO
STANDARD : FCC Part 15 Subpart C §15.247
CLASSIFICATION : (DTS) Digital Transmission System

The product was received on Oct. 06, 2017 and testing was completed on Nov. 15, 2017. We, SPORTON INTERNATIONAL INC., would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC., the test report shall not be reproduced except in full.



Reviewed by: Joseph Lin / Supervisor



Approved by: Jones Tsai / Manager



SPORTON INTERNATIONAL INC.

No. 52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan District, Tao Yuan City, Taiwan, R.O.C.

SPORTON INTERNATIONAL INC.

TEL : 886-3-327-3456

FAX : 886-3-328-4978

FCC ID : SWX-ACBLOCO

Page Number : 1 of 52

Report Issued Date : Nov. 20, 2017

Report Version : Rev. 01

Report Template No.: BU5-FR15CWL MA Version 2.0



TABLE OF CONTENTS

REVISION HISTORY.....	3
SUMMARY OF TEST RESULT	4
1 GENERAL DESCRIPTION	5
1.1 Applicant	5
1.2 Manufacturer	5
1.3 Product Feature of Equipment Under Test.....	5
1.4 Modification of EUT	5
1.5 Testing Location	6
1.6 Applicable Standards.....	7
2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST	8
2.1 Carrier Frequency and Channel	8
2.2 Test Mode.....	9
2.3 Connection Diagram of Test System.....	10
2.4 Support Unit used in test configuration and system	11
2.5 EUT Operation Test Setup	11
2.6 Measurement Results Explanation Example.....	12
3 TEST RESULT	13
3.1 6dB and 99% Bandwidth Measurement	13
3.2 Peak Output Power Measurement	15
3.3 Power Spectral Density Measurement	16
3.4 Conducted Band Edges and Spurious Emission Measurement	19
3.5 Radiated Band Edges and Spurious Emission Measurement	44
3.6 AC Conducted Emission Measurement.....	48
3.7 Antenna Requirements.....	50
4 LIST OF MEASURING EQUIPMENT	51
5 UNCERTAINTY OF EVALUATION	52
APPENDIX A. CONDUCTED TEST RESULTS	
APPENDIX B. AC CONDUCTED EMISSION TEST RESULT	
APPENDIX C. RADIATED SPURIOUS EMISSION	
APPENDIX D. RADIATED SPURIOUS EMISSION PLOTS	
APPENDIX E. DUTY CYCLE PLOTS	
APPENDIX F. SETUP PHOTOGRAPHS	



REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR741927-02	Rev. 01	Initial issue of report	Nov. 20, 2017

SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	15.247(a)(2)	6dB Bandwidth	$\geq 0.5\text{MHz}$	Pass	-
3.1	-	99% Bandwidth	-	Pass	-
3.2	15.247(b)	Power Output Measurement	$\leq 30\text{dBm}$	Pass	-
3.3	15.247(e)	Power Spectral Density	$\leq 8\text{dBm}/3\text{kHz}$	Pass	-
3.4	15.247(d)	Conducted Band Edges	$\leq 20\text{dBc}$	Pass	-
		Conducted Spurious Emission		Pass	-
3.5	15.247(d)	Radiated Band Edges and Radiated Spurious Emission	15.209(a) & 15.247(d)	Pass	Under limit 0.49 dB at 2390.000 MHz
3.6	15.207	AC Conducted Emission	15.207(a)	Pass	Under limit 9.9 dB at 0.470 MHz
3.7	15.203 & 15.247(b)	Antenna Requirement	N/A	Pass	-



1 General Description

1.1 Applicant

Ubiquiti Networks, Inc.

685 Third Avenue, 27th Floor New York, New York 10017 USA

1.2 Manufacturer

Ubiquiti Networks, Inc.

685 Third Avenue, 27th Floor New York, New York 10017 USA

1.3 Product Feature of Equipment Under Test

Wi-Fi 2.4GHz 802.11b/g/n

Product Specification subjective to this standard	
Antenna Type	WLAN: Internal Antenna

1.4 Modification of EUT

No modifications are made to the EUT during all test items.

1.5 Testing Location

Sporton Lab is accredited to ISO 17025 by Taiwan Accreditation Foundation (TAF code : 1190) and the FCC designation No. TW1190 and TW0007 under the FCC 2.948(e) by Mutual Recognition Agreement (MRA) in FCC Test.

Test Site	SPORTON INTERNATIONAL INC.	
Test Site Location	No. 52, Hwa Ya 1 st Rd., Hwa Ya Technology Park, Kwei-Shan District, Tao Yuan City, Taiwan, R.O.C. TEL: +886-3-327-3456 FAX: +886-3-328-4978	
Test Site No.	Sporton Site No.	
	TH05-HY	CO05-HY

Note: The test site complies with ANSI C63.4 2014 requirement.

Test Site	SPORTON INTERNATIONAL INC.	
Test Site Location	No.58, Aly. 75, Ln. 564, Wenhua 3rd Rd. Guishan Dist, Taoyuan City, Taiwan (R.O.C.) TEL: +886-3-327-0868 FAX: +886-3-327-0855	
Test Site No.	Sporton Site No.	
	03CH13-HY	

Note: The test site complies with ANSI C63.4 2014 requirement.



1.6 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC Part 15 Subpart C §15.247
- ♦ FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v04
- ♦ FCC KDB 662911 D01 Multiple Transmitter Output v02r01.
- ♦ ANSI C63.10-2013

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

2 Test Configuration of Equipment Under Test

- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases (Y plane) were recorded in this report.
- b. AC power line Conducted Emission was tested under maximum output power.

2.1 Carrier Frequency and Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
2400-2483.5 MHz	1	2412	7	2442
	2	2417	8	2447
	3	2422	9	2452
	4	2427	10	2457
	5	2432	11	2462
	6	2437		



2.2 Test Mode


Final test mode of conducted test items and radiated spurious emissions are considering the modulation and worse data rates as below table.

MIMO Antenna

Modulation	Data Rate
802.11b	1 Mbps
802.11g	6 Mbps
802.11n HT20	MCS0
802.11n HT40	MCS0

Test Cases	
AC Conducted Emission	Mode 1 : WLAN Link + WAN Link + Lan Link + Adapter

2.3 Connection Diagram of Test System



2.4 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	LCD MONITOR	Dell	P2715Qt	FCC DoC	Shielded, 1.6m	Unshielded,1.8m
2.	iPod	Apple	A1285	FCC DoC	Shielded, 1.0 m	N/A
3.	Notebook	DELL	P20G	FCC DoC/ Contains FCC ID: QDS-BRCM1051	N/A	AC I/P: Unshielded, 1.2 m DC O/P: Shielded, 1.8 m
4.	Notebook	DELL	Latitude E6320	FCC DoC/ Contains FCC ID: QDS-BRCM1054	N/A	AC I/P: Unshielded, 1.2 m DC O/P: Shielded, 1.8 m
5.	Notebook	DELL	Latitude E3340	FCC DoC/ Contains FCC ID: PD97260NGU	N/A	AC I/P: Unshielded, 1.2 m DC O/P: Shielded, 1.8 m
6.	Adapter	HUAWEI	HW-059200UHQ	N/A	N/A	N/A
7.	HUB	D-Link	DES-1005A	FCC DoC	N/A	Unshielded, 1.4m

2.5 EUT Operation Test Setup

The RF test items, programmed RF utility, "cmd" installed in the notebook make the EUT provide functions like channel selection and power level for continuous transmitting signals.



2.6 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example:

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 4.2 dB and 10dB attenuator.

$$\begin{aligned}\text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)} \\ &= 4.2 + 10 = 14.2 \text{ (dB)}\end{aligned}$$

3 Test Result

3.1 6dB and 99% Bandwidth Measurement

3.1.1 Limit of 6dB and 99% Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.


3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.1.3 Test Procedures

1. The testing follows FCC KDB Publication No. 558074 DTS D01 Meas. Guidance v04.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6 dB bandwidth must be greater than 500 kHz.
5. For 99% Bandwidth Measurement, the spectrum analyzer's resolution bandwidth (RBW) = 1MHz and set the Video bandwidth (VBW) = 3MHz.
6. Measure and record the results in the test report.


3.1.4 Test Setup





3.1.5 Test Result of 6dB and 99% Occupied Bandwidth

Please refer to Appendix A.



Note : The occupied channel bandwidth is maintained within the band of operation for all of the modulations.

3.2 Peak Output Power Measurement

3.2.1 Limit of Peak Output Power

For systems using digital modulation in the 2400-2483.5MHz, the limit for peak output power is 30dBm. If transmitting antenna with directional gain greater than 6dBi is used, the peak output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.


3.2.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.2.3 Test Procedures

1. The testing follows the Measurement Procedure of FCC KDB No. 558074 DTS D01 Meas. Guidance v04 section 9.1.2 PKPM1 Peak power meter method.
2. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Measure the conducted output power and record the results in the test report.
5. For MIMO mode, calculation method follows FCC KDB 662911 D01 Multiple Transmitter Output v02r01.

3.2.4 Test Setup



3.2.5 Test Result of Peak Output Power

Please refer to Appendix A.

3.2.6 Test Result of Average output Power (Reporting Only)

Please refer to Appendix A

3.3 Power Spectral Density Measurement

3.3.1 Limit of Power Spectral Density

The peak power spectral density shall not be greater than 8dBm in any 3kHz band at any time interval of continuous transmission.

3.3.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.3.3 Test Procedures

1. The testing follows Measurement Procedure 10.2 Method PKPSD of FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v04.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 3 kHz. Video bandwidth VBW = 10 kHz In order to make an accurate measurement, set the span to 1.5 times DTS Channel Bandwidth. (6dB BW)
5. Detector = peak, Sweep time = auto couple, Trace mode = max hold, Allow trace to fully stabilize. Use the peak marker function to determine the maximum power level.
6. Measure and record the results in the test report.
7. For MIMO mode, calculation method follows FCC KDB 662911 D01 Multiple Transmitter Output v02r01.


If measurements performed using method (2) plus $10 \log(N)$ exceeds the emission limit, the test should choose method (1) before declaring that the device fails the emission limit.

Method (1): Measure and sum the spectra across the outputs.

The total final Power Spectral Density is from a device with 2 transmitter outputs. The spectrum measurements of the individual outputs are all performed with the same span and number of points, the spectrum value in the first spectral bin of output 1 is summed with that in the first spectral bin of output 2 to obtain the value for the first frequency bin of the summed spectrum.

Method (2): Measure and add $10 \log(N)$ dB, where N is the number of outputs. (N=2)



3.3.4 Test Setup





3.3.5 Test Result of Power Spectral Density

Please refer to Appendix A.



3.4 Conducted Band Edges and Spurious Emission Measurement

3.4.1 Limit of Conducted Band Edges and Spurious Emission Measurement

In any 100 kHz bandwidth outside of the authorized frequency band, the emissions which fall in the non-restricted bands shall be attenuated at least 20 dB / 30dB relative to the maximum PSD level in 100 kHz by RF conducted measurement.


3.4.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.4.3 Test Procedures

1. The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v04.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Set RBW = 100 kHz, VBW=300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB per 15.247(d).
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

3.4.4 Test Setup






3.4.5 Test Result of Conducted Band Edges and Spurious Emission

Number of TX = 2, Ant. 1 (Measured)

Number of TX	2	Ant. :	1
Test Mode :	802.11b	Temperature :	21~25℃
Test Band :	2.4GHz Low	Relative Humidity :	51~54%
Test Channel :	01	Test Engineer :	Shiming Liu and Allen Lin






Number of TX :	2	Ant. :	1
Test Mode :	802.11b	Temperature :	21~25°C
Test Band :	2.4GHz Mid	Relative Humidity :	51~54%
Test Channel :	06	Test Engineer :	Shiming Liu and Allen Lin


WLAN 802.11b Channel 06

100kHz PSD reference Level




Date: 9.NOV.2017 19:24:38

Spurious Emission 30MHz~3GHz



Date: 9.NOV.2017 19:30:57

Spurious Emission 2GHz~25GHz




Date: 9.NOV.2017 19:31:05



Number of TX :	2	Ant. :	1
Test Mode :	802.11b	Temperature :	21~25°C
Test Band :	2.4GHz High	Relative Humidity :	51~54%
Test Channel :	11	Test Engineer :	Shiming Liu and Allen Lin


WLAN 802.11b Channel 11

100kHz PSD reference Level




Date: 14.NOV.2017 14:16:03

High Channel Plot




Date: 14.NOV.2017 14:16:13

Spurious Emission 30MHz~3GHz



Date: 14.NOV.2017 14:16:26

Spurious Emission 2GHz~25GHz




Date: 14.NOV.2017 14:16:34



Number of TX :	2	Ant. :	1
Test Mode :	802.11g	Temperature :	21~25°C
Test Band :	2.4GHz Low	Relative Humidity :	51~54%
Test Channel :	01	Test Engineer :	Shiming Liu and Allen Lin


WLAN 802.11g Channel 01

100kHz PSD reference Level




Date: 14.NOV.2017 13:17:18

Low Channel Plot




Date: 14.NOV.2017 13:18:24

Spurious Emission 30MHz~3GHz



Date: 14.NOV.2017 13:18:39

Spurious Emission 2GHz~25GHz




Date: 14.NOV.2017 13:18:47

Number of TX :	2	Ant. :	1
Test Mode :	802.11g	Temperature :	21~25℃
Test Band :	2.4GHz Mid	Relative Humidity :	51~54%
Test Channel :	06	Test Engineer :	Shiming Liu and Allen Lin


WLAN 802.11g Channel 06

100kHz PSD reference Level




Date: 15.NOV.2017 13:59:52

Spurious Emission 30MHz~3GHz



Date: 15.NOV.2017 14:00:06


Spurious Emission 2GHz~25GHz




Date: 15.NOV.2017 14:00:15




Number of TX :	2	Ant. :	1
Test Mode :	802.11g	Temperature :	21~25°C
Test Band :	2.4GHz High	Relative Humidity :	51~54%
Test Channel :	11	Test Engineer :	Shiming Liu and Allen Lin

WLAN 802.11g Channel 11**100kHz PSD reference Level**


Date: 14.NOV.2017 13:29:41

High Channel Plot

Date: 14.NOV.2017 13:30:03

Spurious Emission 30MHz~3GHz

Date: 14.NOV.2017 13:30:16

Spurious Emission 2GHz~25GHz


Date: 14.NOV.2017 13:30:25



Number of TX :	2	Ant. :	1
Test Mode :	802.11n HT20	Temperature :	21~25°C
Test Band :	2.4GHz Low	Relative Humidity :	51~54%
Test Channel :	01	Test Engineer :	Shiming Liu and Allen Lin


WLAN 802.11n HT20 Channel 01

100kHz PSD reference Level




Date: 14.NOV.2017 13:40:30

Low Channel Plot




Date: 14.NOV.2017 13:40:39

Spurious Emission 30MHz~3GHz



Date: 14.NOV.2017 13:40:50

Spurious Emission 2GHz~25GHz




Date: 14.NOV.2017 13:40:59



Number of TX :	2	Ant. :	1
Test Mode :	802.11n HT20	Temperature :	21~25°C
Test Band :	2.4GHz Mid	Relative Humidity :	51~54%
Test Channel :	06	Test Engineer :	Shiming Liu and Allen Lin


WLAN 802.11n HT20 Channel 06

100kHz PSD reference Level




Date: 15.NOV.2017 14:11:09

Spurious Emission 30MHz~3GHz



Date: 15.NOV.2017 14:11:20


Spurious Emission 2GHz~25GHz




Date: 15.NOV.2017 14:11:29




Number of TX :	2	Ant. :	1
Test Mode :	802.11n HT20	Temperature :	21~25°C
Test Band :	2.4GHz High	Relative Humidity :	51~54%
Test Channel :	11	Test Engineer :	Shiming Liu and Allen Lin

WLAN 802.11n HT20 Channel 11**100kHz PSD reference Level**


Date: 14.NOV.2017 13:54:55

High Channel Plot

Date: 14.NOV.2017 13:55:05

Spurious Emission 30MHz~3GHz


Date: 14.NOV.2017 13:55:20

Spurious Emission 2GHz~25GHz


Date: 14.NOV.2017 13:55:29




Number of TX :	2	Ant. :	1
Test Mode :	802.11n HT40	Temperature :	21~25°C
Test Band :	2.4GHz Low	Relative Humidity :	51~54%
Test Channel :	03	Test Engineer :	Shiming Liu and Allen Lin

WLAN 802.11n HT40 Channel 03**100kHz PSD reference Level**


Date: 9.NOV.2017 20:38:26

Low Channel Plot

Date: 9.NOV.2017 20:39:02

Spurious Emission 30MHz~3GHz

Date: 9.NOV.2017 20:40:00

Spurious Emission 2GHz~25GHz


Date: 9.NOV.2017 20:40:08



Number of TX :	2	Ant. :	1
Test Mode :	802.11n HT40	Temperature :	21~25°C
Test Band :	2.4GHz Mid	Relative Humidity :	51~54%
Test Channel :	06	Test Engineer :	Shiming Liu and Allen Lin


WLAN 802.11n HT40 Channel 06

100kHz PSD reference Level




Date: 9.NOV.2017 21:00:28

Spurious Emission 30MHz~3GHz



Date: 9.NOV.2017 21:00:50

Spurious Emission 2GHz~25GHz




Date: 9.NOV.2017 21:00:58



Number of TX :	2	Ant. :	1
Test Mode :	802.11n HT40	Temperature :	21~25°C
Test Band :	2.4GHz High	Relative Humidity :	51~54%
Test Channel :	09	Test Engineer :	Shiming Liu and Allen Lin


WLAN 802.11n HT40 Channel 09

100kHz PSD reference Level




Date: 9.NOV.2017 21:14:42

High Channel Plot




Date: 9.NOV.2017 21:14:55

Spurious Emission 30MHz~3GHz



Date: 9.NOV.2017 21:15:07

Spurious Emission 2GHz~25GHz



Date: 9.NOV.2017 21:15:16




Number of TX = 2, Ant. 2 (Measured)

Number of TX :	2	Ant. :	2
Test Mode :	802.11b	Temperature :	21~25°C
Test Band :	2.4GHz Low	Relative Humidity :	51~54%
Test Channel :	01	Test Engineer :	Shiming Liu and Allen Lin


WLAN 802.11b Channel 01

100kHz PSD reference Level




Date: 14.NOV.2017 10:45:54

Low Channel Plot




Date: 14.NOV.2017 10:47:28

Spurious Emission 30MHz~3GHz



Date: 14.NOV.2017 10:47:40

Spurious Emission 2GHz~25GHz




Date: 14.NOV.2017 10:47:49



Number of TX :	2	Ant. :	2
Test Mode :	802.11b	Temperature :	21~25°C
Test Band :	2.4GHz Mid	Relative Humidity :	51~54%
Test Channel :	06	Test Engineer :	Shiming Liu and Allen Lin


WLAN 802.11b Channel 06

100kHz PSD reference Level




Date: 9.NOV.2017 19:36:06

Spurious Emission 30MHz~3GHz



Date: 9.NOV.2017 19:36:26

Spurious Emission 2GHz~25GHz




Date: 9.NOV.2017 19:36:34



Number of TX :	2	Ant. :	2
Test Mode :	802.11b	Temperature :	21~25°C
Test Band :	2.4GHz High	Relative Humidity :	51~54%
Test Channel :	11	Test Engineer :	Shiming Liu and Allen Lin


WLAN 802.11b Channel 11

100kHz PSD reference Level




Date: 14.NOV.2017 10:58:49

High Channel Plot




Date: 14.NOV.2017 10:59:00

Spurious Emission 30MHz~3GHz



Date: 14.NOV.2017 10:59:12

Spurious Emission 2GHz~25GHz




Date: 14.NOV.2017 10:59:21



Number of TX :	2	Ant. :	2
Test Mode :	802.11g	Temperature :	21~25°C
Test Band :	2.4GHz Low	Relative Humidity :	51~54%
Test Channel :	01	Test Engineer :	Shiming Liu and Allen Lin


WLAN 802.11g Channel 01

100kHz PSD reference Level




Date: 14.NOV.2017 13:22:00

Low Channel Plot




Date: 14.NOV.2017 13:22:22

Spurious Emission 30MHz~3GHz



Date: 14.NOV.2017 13:22:36

Spurious Emission 2GHz~25GHz




Date: 14.NOV.2017 13:22:44



Number of TX :	2	Ant. :	2
Test Mode :	802.11g	Temperature :	21~25°C
Test Band :	2.4GHz Mid	Relative Humidity :	51~54%
Test Channel :	06	Test Engineer :	Shiming Liu and Allen Lin


WLAN 802.11g Channel 06

100kHz PSD reference Level




Date: 15.NOV.2017 14:02:42

Spurious Emission 30MHz~3GHz



Date: 15.NOV.2017 14:02:53


Spurious Emission 2GHz~25GHz




Date: 15.NOV.2017 14:03:02




Number of TX :	2	Ant. :	2
Test Mode :	802.11g	Temperature :	21~25°C
Test Band :	2.4GHz High	Relative Humidity :	51~54%
Test Channel :	11	Test Engineer :	Shiming Liu and Allen Lin

WLAN 802.11g Channel 11**100kHz PSD reference Level**


Date: 14.NOV.2017 13:34:40

High Channel Plot

Date: 14.NOV.2017 13:34:52

Spurious Emission 30MHz~3GHz

Date: 14.NOV.2017 13:35:04

Spurious Emission 2GHz~25GHz


Date: 14.NOV.2017 13:35:12



Number of TX :	2	Ant. :	2
Test Mode :	802.11n HT20	Temperature :	21~25°C
Test Band :	2.4GHz Low	Relative Humidity :	51~54%
Test Channel :	01	Test Engineer :	Shiming Liu and Allen Lin


WLAN 802.11n HT20 Channel 01

100kHz PSD reference Level




Date: 14.NOV.2017 13:42:35

Low Channel Plot




Date: 14.NOV.2017 13:42:45

Spurious Emission 30MHz~3GHz



Date: 14.NOV.2017 13:43:18

Spurious Emission 2GHz~25GHz




Date: 14.NOV.2017 13:43:27



Number of TX :	2	Ant. :	2
Test Mode :	802.11n HT20	Temperature :	21~25°C
Test Band :	2.4GHz Mid	Relative Humidity :	51~54%
Test Channel :	06	Test Engineer :	Shiming Liu and Allen Lin


WLAN 802.11n HT20 Channel 06

100kHz PSD reference Level




Date: 15.NOV.2017 14:13:14

Spurious Emission 30MHz~3GHz



Date: 15.NOV.2017 14:13:26

Spurious Emission 2GHz~25GHz




Date: 15.NOV.2017 14:13:34



Number of TX :	2	Ant. :	2
Test Mode :	802.11n HT20	Temperature :	21~25°C
Test Band :	2.4GHz High	Relative Humidity :	51~54%
Test Channel :	11	Test Engineer :	Shiming Liu and Allen Lin


WLAN 802.11n HT20 Channel 11

100kHz PSD reference Level




Date: 14.NOV.2017 13:57:13

High Channel Plot




Date: 14.NOV.2017 13:57:32

Spurious Emission 30MHz~3GHz



Date: 14.NOV.2017 13:57:46


Spurious Emission 2GHz~25GHz




Date: 14.NOV.2017 13:57:55




Number of TX :	2	Ant. :	2
Test Mode :	802.11n HT40	Temperature :	21~25°C
Test Band :	2.4GHz Low	Relative Humidity :	51~54%
Test Channel :	03	Test Engineer :	Shiming Liu and Allen Lin

WLAN 802.11n HT40 Channel 03**100kHz PSD reference Level**


Date: 9.NOV.2017 20:44:54

Low Channel Plot

Date: 9.NOV.2017 20:45:18

Spurious Emission 30MHz~3GHz

Date: 9.NOV.2017 20:45:51

Spurious Emission 2GHz~25GHz


Date: 9.NOV.2017 20:46:00



Number of TX :	2	Ant. :	2
Test Mode :	802.11n HT40	Temperature :	21~25°C
Test Band :	2.4GHz Mid	Relative Humidity :	51~54%
Test Channel :	06	Test Engineer :	Shiming Liu and Allen Lin


WLAN 802.11n HT40 Channel 06

100kHz PSD reference Level




Date: 9.NOV.2017 21:05:04

Spurious Emission 30MHz~3GHz



Date: 9.NOV.2017 21:05:54

Spurious Emission 2GHz~25GHz




Date: 9.NOV.2017 21:06:02



Number of TX :	2	Ant. :	2
Test Mode :	802.11n HT40	Temperature :	21~25°C
Test Band :	2.4GHz High	Relative Humidity :	51~54%
Test Channel :	09	Test Engineer :	Shiming Liu and Allen Lin


WLAN 802.11n HT40 Channel 09

100kHz PSD reference Level




Date: 9.NOV.2017 21:18:41

High Channel Plot




Date: 9.NOV.2017 21:19:02

Spurious Emission 30MHz~3GHz



Date: 9.NOV.2017 21:19:14

Spurious Emission 2GHz~25GHz



Date: 9.NOV.2017 21:19:23



3.5 Radiated Band Edges and Spurious Emission Measurement

3.5.1 Limit of Radiated band edge and Spurious Emission Measurement

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. If the output power of this device was measured by spectrum analyzer, the attenuation under this paragraph shall be 30 dB instead of 20 dB. In addition, radiated emissions which fall in the restricted bands must also comply with the limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.5.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.



3.5.3 Test Procedures


1. The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v04.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.
3. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
6. For measurement below 1GHz, If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.
7. Use the following spectrum analyzer settings:
 - (1) Span shall wide enough to fully capture the emission being measured;
 - (2) Set RBW=100 kHz for $f < 1$ GHz; VBW $\geq$ RBW; Sweep = auto; Detector function = peak; Trace = max hold;
 - (3) Set RBW = 1 MHz, VBW= 3MHz for $f \geq 1$ GHz for peak measurement.

For average measurement:


 - VBW = 10 Hz, when duty cycle is no less than 98 percent.
 - VBW $\geq 1/T$, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.

3.5.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



3.5.5 Test Results of Radiated Spurious Emissions (9kHz ~ 30MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

3.5.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix C and D.

3.5.7 Duty Cycle

Please refer to Appendix E.

3.5.8 Test Result of Radiated Spurious Emission (30MHz ~ 10th Harmonic)

Please refer to Appendix C and D.

3.6 AC Conducted Emission Measurement

3.6.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of Emission (MHz)	Conducted Limit (dB μ V)	
	Quasi-Peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.6.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.6.3 Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room, and it was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF bandwidth = 9kHz) with Maximum Hold Mode.

3.6.4 Test Setup



3.6.5 Test Result of AC Conducted Emission

Please refer to Appendix B.

3.7 Antenna Requirements

3.7.1 Standard Applicable

If directional gain of transmitting Antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. The use of a permanently attached Antenna or of an Antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the rule.

3.7.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

3.7.3 Antenna Gain

FCC KDB 662911 D01 Multiple Transmitter Output v02r01

For CDD transmissions, directional gain is calculated as

Directional gain = G_{ANT} + Array Gain, where Array Gain is as follows.

For power spectral density (PSD) measurements on all devices,

Array Gain = $10 \log(N_{ANT}/N_{SS}=1)$ dB.

For power measurements on IEEE 802.11 devices,

Array Gain = 0 dB (i.e., no array gain) for $N_{ANT} \leq 4$.

Directional gain may be calculated by using the formulas applicable to equal gain antennas with G_{ANT} set equal to the gain of the antenna having the highest gain;

The EUT supports CDD mode.

For power, the directional gain G_{ANT} is set equal to the antenna having the highest gain, i.e., F)2)f)i).

For PSD, the directional gain calculation is following F)2)f)ii) of KDB 662911 D01 v02r01.

The power and PSD limit should be modified if the directional gain of EUT is over 6 dBi,

The directional gain "DG" is calculated as following table.

	Chain Port 0	Chain Port 1	DG for Power	DG for PSD	Power Limit Reduction	PSD Limit Reduction
	Ant 1 (dBi)	Ant 2 (dBi)	(dBi)	(dBi)	(dB)	(dB)
2.4 GHz	4.00	4.00	4.00	7.01	0.00	1.01

$Power\ Limit\ Reduction = DG(Power) - 6dBi, (min = 0)$

$PSD\ Limit\ Reduction = DG(PSD) - 6dBi, (min = 0)$



4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Power Meter	Anritsu	ML2495A	1240001	N/A	Sep. 07, 2017	Nov. 09, 2017~ Nov. 15, 2017	Sep. 06, 2018	Conducted (TH05-HY)
Power Sensor	Anritsu	MA2411B	1207349	300MHz~40GHz z	Sep. 07, 2017	Nov. 09, 2017~ Nov. 15, 2017	Sep. 06, 2018	Conducted (TH05-HY)
Spectrum Analyzer	Rohde & Schwarz	FSP40	100055	9kHz~40GHz	Jun. 20, 2017	Nov. 09, 2017~ Nov. 15, 2017	Jun. 19, 2018	Conducted (TH02-HY)
AC Power Source	ChainTek	APC-1000W	N/A	N/A	N/A	Oct. 12, 2017	N/A	Conduction (CO05-HY)
EMI Test Receiver	Rohde & Schwarz	ESCI 7	100724	9kHz~7GHz	Sep. 20, 2017	Oct. 12, 2017	Sep. 19, 2018	Conduction (CO05-HY)
LISN	Rohde & Schwarz	ENV216	100080	9kHz~30MHz	Nov. 29, 2016	Oct. 12, 2017	Nov. 28, 2017	Conduction (CO05-HY)
LISN	Rohde & Schwarz	ENV216	100081	9kHz~30MHz	Dec. 06, 2016	Oct. 12, 2017	Dec. 05, 2017	Conduction (CO05-HY)
Amplifier	MITEQ	TTA1840-35-HG	1871923	18GHz~40GHz, VSWR : 2.5:1 max	Jul. 18, 2017	Nov. 08, 2017~ Nov. 14, 2017	Jul. 17, 2018	Radiation (03CH13-HY)
Loop Antenna	Rohde & Schwarz	HFH2-Z2	100488	9 kHz~30 MHz	Oct. 20, 2016	Nov. 08, 2017~ Nov. 14, 2017	Oct. 19, 2018	Radiation (03CH13-HY)
EMI Test Receiver	Keysight	N9038A(MXE)	MY55420170	N/A	Mar. 03, 2017	Nov. 08, 2017~ Nov. 14, 2017	Mar. 02, 2018	Radiation (03CH13-HY)
Amplifier	Sonoma-Instrument	310 N	187282	9KHz~1GHz	Dec. 21, 2016	Nov. 08, 2017~ Nov. 14, 2017	Dec. 20, 2017	Radiation (03CH13-HY)
Bilog Antenna	TESEQ	CBL 6111D&00800 N1D01N-06	40103&04	30MHz to 1GHz	Jan. 07, 2017	Nov. 08, 2017~ Nov. 14, 2017	Jan. 06, 2018	Radiation (03CH13-HY)
Horn Antenna	SCHWARZBECK	BBHA 9120 D	9120D-1241	1GHz ~ 18GHz	Jun. 15, 2017	Nov. 08, 2017~ Nov. 14, 2017	Jun. 14, 2018	Radiation (03CH13-HY)
Preamplifier	MITEQ	AMF-7D-0010 1800-30-10P	1590074	1GHz~18GHz	May 22, 2017	Nov. 08, 2017~ Nov. 14, 2017	May 21, 2018	Radiation (03CH13-HY)
Preamplifier	Keysight	83017A	MY53270147	1GHz~26.5GHz	Jan. 09, 2017	Nov. 08, 2017~ Nov. 14, 2017	Jan. 08, 2018	Radiation (03CH13-HY)
Spectrum Analyzer	Keysight	N9010A	MY55370526	N/A	Mar. 15, 2017	Nov. 08, 2017~ Nov. 14, 2017	Mar. 14, 2018	Radiation (03CH13-HY)
Filter	Wainwright	WHKX12-270 0-3000-18000 -60SS	SN2	3G High Pass	Sep. 18, 2017	Nov. 08, 2017~ Nov. 14, 2017	Sep. 17, 2018	Radiation (03CH13-HY)
Antenna Mast	EMEC	AM-BS-4500-B	N/A	1m~4m	N/A	Nov. 08, 2017~ Nov. 14, 2017	N/A	Radiation (03CH13-HY)
Turn Table	EMEC	TT2000	N/A	0~360 Degree	N/A	Nov. 08, 2017~ Nov. 14, 2017	N/A	Radiation (03CH13-HY)
SHF-EHF Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA9170576	18GHz ~ 40GHz	Apr. 27, 2017	Nov. 08, 2017~ Nov. 14, 2017	Apr. 26, 2018	Radiation (03CH13-HY)

5 Uncertainty of Evaluation

Uncertainty of Conducted Emission Measurement (150kHz ~ 30MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	2.70
--	------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	4.90
--	------

Uncertainty of Radiated Emission Measurement (1000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.40
--	------

Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	4.30
--	------

Appendix A. Test Result of Conducted Test Items

Test Engineer:	Shiming Liu / Allen Lin	Temperature:	21~25	°C
Test Date:	2017/11/9~2017/11/15	Relative Humidity:	51~54	%

TEST RESULTS DATA
6dB and 99% Occupied Bandwidth

2.4GHz Band										
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	99% Occupied BW (MHz)		6dB BW (MHz)		6dB BW Limit (MHz)	Pass/Fail
					Ant 1	Ant 2	Ant 1	Ant 2		
11b	1Mbps	2	1	2412	13.65	13.70	10.02	10.04	0.50	Pass
11b	1Mbps	2	6	2437	13.60	13.65	10.00	10.00	0.50	Pass
11b	1Mbps	2	11	2462	13.75	13.75	10.02	10.02	0.50	Pass
11g	6Mbps	2	1	2412	16.60	16.60	15.68	15.42	0.50	Pass
11g	6Mbps	2	6	2437	16.70	16.75	16.02	14.74	0.50	Pass
11g	6Mbps	2	11	2462	16.70	16.75	15.66	15.32	0.50	Pass
HT20	MCS0	2	1	2412	17.60	17.75	16.24	16.32	0.50	Pass
HT20	MCS0	2	6	2437	17.60	17.70	15.54	15.62	0.50	Pass
HT20	MCS0	2	11	2462	17.65	17.75	15.90	16.50	0.50	Pass
HT40	MCS0	2	3	2422	35.90	36.00	34.80	34.64	0.50	Pass
HT40	MCS0	2	6	2437	36.10	36.10	34.64	35.04	0.50	Pass
HT40	MCS0	2	9	2452	36.00	36.00	34.91	35.32	0.50	Pass

TEST RESULTS DATA
Peak Output Power

2.4GHz Band																
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Peak Conducted Power (dBm)			Conducted Power Limit (dBm)		DG (dBi)		EIRP Power (dBm)		EIRP Power Limit (dBm)		Pass /Fail
					Ant 1	Ant 2	SUM	Ant 1	Ant 2	Ant 1	Ant 2	Ant 1	Ant 2	Ant 1	Ant 2	
11b	1Mbps	2	1	2412	12.44	12.78	15.62	30.00		4.00		19.62		36.00		Pass
11b	1Mbps	2	6	2437	14.03	14.75	17.42	30.00		4.00		21.42		36.00		Pass
11b	1Mbps	2	11	2462	15.66	16.13	18.91	30.00		4.00		22.91		36.00		Pass
11g	6Mbps	2	1	2412	21.32	21.60	24.47	30.00		4.00		28.47		36.00		Pass
11g	6Mbps	2	6	2437	22.97	23.55	26.28	30.00		4.00		30.28		36.00		Pass
11g	6Mbps	2	11	2462	23.17	23.37	26.28	30.00		4.00		30.28		36.00		Pass
HT20	MCS0	2	1	2412	22.24	22.67	25.47	30.00		4.00		29.47		36.00		Pass
HT20	MCS0	2	6	2437	23.22	23.74	26.50	30.00		4.00		30.50		36.00		Pass
HT20	MCS0	2	11	2462	23.01	23.25	26.14	30.00		4.00		30.14		36.00		Pass
HT40	MCS0	2	3	2422	16.95	17.97	20.50	30.00		4.00		24.50		36.00		Pass
HT40	MCS0	2	6	2437	21.30	21.88	24.61	30.00		4.00		28.61		36.00		Pass
HT40	MCS0	2	9	2452	19.85	20.50	23.20	30.00		4.00		27.20		36.00		Pass

Note: Measured power (dBm) has offset with cable loss.

TEST RESULTS DATA
Average Output Power

2.4GHz Band									
Mod.	Data Rate	N _{TX}	CH.	Freq. (MHz)	Duty Factor (dB)		Average Conducted Power (dBm)		
					Ant 1	Ant 2	Ant 1	Ant 2	SUM
11b	1Mbps	2	1	2412	0.00	0.00	9.75	10.12	12.95
11b	1Mbps	2	6	2437	0.00	0.00	11.54	12.24	14.91
11b	1Mbps	2	11	2462	0.00	0.00	13.16	13.64	16.42
11g	6Mbps	2	1	2412	0.00	0.00	14.54	14.92	17.74
11g	6Mbps	2	6	2437	0.00	0.00	16.76	17.72	20.28
11g	6Mbps	2	11	2462	0.00	0.00	17.04	17.42	20.24
HT20	MCS0	2	1	2412	0.00	0.00	15.40	16.17	18.81
HT20	MCS0	2	6	2437	0.00	0.00	17.00	17.84	20.45
HT20	MCS0	2	11	2462	0.00	0.00	16.68	17.03	19.87
HT40	MCS0	2	3	2422	0.00	0.00	12.05	12.95	15.53
HT40	MCS0	2	6	2437	0.00	0.00	16.56	17.20	19.90
HT40	MCS0	2	9	2452	0.00	0.00	14.95	15.60	18.30

Note: Measured power (dBm) has offset with cable loss.

TEST RESULTS DATA
Peak Power Spectral Density

2.4GHz Band												
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Peak PSD (dBm/3kHz)			DG (dBi)		Peak PSD Limit (dBm/3kHz)		Pass/Fail
					Ant 1	Ant 2	Worse + 3.01	Ant 1	Ant 2	Ant 1	Ant 2	
11b	1Mbps	2	1	2412	-14.03	-13.79	-10.78	7.01		6.99		Pass
11b	1Mbps	2	6	2437	-11.69	-11.21	-8.20	7.01		6.99		Pass
11b	1Mbps	2	11	2462	-10.03	-10.27	-7.02	7.01		6.99		Pass
11g	6Mbps	2	1	2412	-10.16	-10.50	-7.15	7.01		6.99		Pass
11g	6Mbps	2	6	2437	-7.94	-8.31	-4.93	7.01		6.99		Pass
11g	6Mbps	2	11	2462	-6.57	-7.67	-3.56	7.01		6.99		Pass
HT20	MCS0	2	1	2412	-9.56	-8.40	-5.39	7.01		6.99		Pass
HT20	MCS0	2	6	2437	-8.88	-6.35	-3.34	7.01		6.99		Pass
HT20	MCS0	2	11	2462	-7.83	-7.91	-4.82	7.01		6.99		Pass
HT40	MCS0	2	3	2422	-15.88	-14.14	-11.13	7.01		6.99		Pass
HT40	MCS0	2	6	2437	-12.03	-11.61	-8.60	7.01		6.99		Pass
HT40	MCS0	2	9	2452	-13.25	-11.95	-8.94	7.01		6.99		Pass

Measured power density (dBm) has offset with cable loss.




Appendix B. AC Conducted Emission Test Results

Test Engineer :	Blue Lan	Temperature :	26~27°C
		Relative Humidity :	46~47%

EUT Information

Report NO : 741927-02
Test Mode : Mode 1
Test Voltage : 120Vac/60Hz
Phase : Line

ENV216 Auto Test FCC Power Bar - L



Final Result 1

Frequency (MHz)	QuasiPeak (dBµV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.150000	43.7	Off	L1	19.6	22.3	66.0
0.198000	37.3	Off	L1	19.6	26.4	63.7
0.470000	46.6	Off	L1	19.6	9.9	56.5
0.518000	45.7	Off	L1	19.6	10.3	56.0
0.974000	39.8	Off	L1	19.6	16.2	56.0
1.894000	32.1	Off	L1	19.6	23.9	56.0
2.302000	29.9	Off	L1	18.9	26.1	56.0
3.774000	30.5	Off	L1	19.7	25.5	56.0


Final Result 2

Frequency (MHz)	Average (dBµV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.150000	30.7	Off	L1	19.6	25.3	56.0
0.198000	25.5	Off	L1	19.6	28.2	53.7
0.470000	32.7	Off	L1	19.6	13.8	46.5
0.518000	34.2	Off	L1	19.6	11.8	46.0
0.974000	32.0	Off	L1	19.6	14.0	46.0
1.894000	23.5	Off	L1	19.6	22.5	46.0
2.302000	21.5	Off	L1	18.9	24.5	46.0
3.774000	23.0	Off	L1	19.7	23.0	46.0

EUT Information

Report NO : 741927-02
Test Mode : Mode 1
Test Voltage : 120Vac/60Hz
Phase : Neutral

ENV216 Auto Test FCC Power Bar - N



Final Result 1

Frequency (MHz)	QuasiPeak (dBμV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.150000	47.8	Off	N	19.5	18.2	66.0
0.486000	41.9	Off	N	19.5	14.3	56.2
0.534000	39.4	Off	N	19.5	16.6	56.0
0.798000	33.4	Off	N	19.5	22.6	56.0
0.982000	36.3	Off	N	19.6	19.7	56.0
1.230000	31.1	Off	N	19.6	24.9	56.0
1.950000	28.5	Off	N	19.6	27.5	56.0

Final Result 2

Frequency (MHz)	Average (dBμV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.150000	30.3	Off	N	19.5	25.7	56.0
0.486000	27.7	Off	N	19.5	18.5	46.2
0.534000	26.1	Off	N	19.5	19.9	46.0
0.798000	23.0	Off	N	19.5	23.0	46.0
0.982000	26.9	Off	N	19.6	19.1	46.0
1.230000	21.4	Off	N	19.6	24.6	46.0
1.950000	21.7	Off	N	19.6	24.3	46.0



Appendix C. Radiated Spurious Emission

Test Engineer :	Alex Jeng ,Bill Chang and Wilson Wu	Temperature :	24.7~25.2°C
		Relative Humidity :	47~52%



2.4GHz 2400~2483.5MHz

WIFI 802.11b (Band Edge @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1+2		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11b CH 01 2412MHz		2363.235	53.2	-20.8	74	42.67	26.79	4.8	30.99	124	306	P	H
		2386.335	41.18	-12.82	54	30.52	26.89	4.83	30.99	124	306	A	H
	*	2412	100.63	-	-	89.88	26.94	4.87	30.99	124	306	P	H
	*	2412	97.64	-	-	86.89	26.94	4.87	30.99	124	306	A	H
													H
													H
		2373.735	51	-23	74	40.42	26.84	4.8	30.99	100	79	P	V
		2385.285	40.91	-13.09	54	30.3	26.84	4.83	30.99	100	79	A	V
	*	2412	100.68	-	-	89.93	26.94	4.87	30.99	100	79	P	V
	*	2412	97.58	-	-	86.83	26.94	4.87	30.99	100	79	A	V
													V
													V
802.11b CH 06 2437MHz		2326.8	51.06	-22.94	74	40.7	26.68	4.76	31.01	295	288	P	H
		2388.82	40.59	-13.41	54	29.93	26.89	4.83	30.99	295	288	A	H
	*	2437	102.84	-	-	91.97	27.04	4.88	30.98	295	288	P	H
	*	2437	99.85	-	-	88.98	27.04	4.88	30.98	295	288	A	H
		2496.92	52.23	-21.77	74	41.13	27.2	4.93	30.96	295	288	P	H
		2484.95	41.04	-12.96	54	30	27.15	4.93	30.97	295	288	A	H
		2389.24	51.47	-22.53	74	40.81	26.89	4.83	30.99	151	77	P	V
		2388.82	40.83	-13.17	54	30.17	26.89	4.83	30.99	151	77	A	V
	*	2437	104.06	-	-	93.19	27.04	4.88	30.98	151	77	P	V
	*	2437	100.92	-	-	90.05	27.04	4.88	30.98	151	77	A	V
		2487.19	52.29	-21.71	74	41.25	27.15	4.93	30.97	151	77	P	V
		2483.69	41.48	-12.52	54	30.44	27.15	4.93	30.97	151	77	A	V



802.11b CH 11 2462MHz	*	2462	105.8	-	-	94.84	27.1	4.9	30.97	115	306	P	H
	*	2462	102.81	-	-	91.85	27.1	4.9	30.97	115	306	A	H
		2486.48	53.5	-20.5	74	42.46	27.15	4.93	30.97	115	306	P	H
		2487.68	44.06	-9.94	54	32.96	27.2	4.93	30.96	115	306	A	H
													H
													H
	*	2462	104.84	-	-	93.88	27.1	4.9	30.97	100	55	P	V
	*	2462	101.88	-	-	90.92	27.1	4.9	30.97	100	55	A	V
		2498.96	53.2	-20.8	74	42.1	27.2	4.93	30.96	100	55	P	V
		2487.56	43.26	-10.74	54	32.16	27.2	4.93	30.96	100	55	A	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz

WIFI 802.11b (Harmonic @ 3m)

WIFI Ant. 1+2	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11b CH 01 2412MHz		4824	51.47	-22.53	74	69.31	31.56	7.33	57.24	102	224	P	H
		4824	49.32	-4.68	54	67.16	31.56	7.33	57.24	102	224	A	H
													H
													H
		4824	54.89	-19.11	74	72.73	31.56	7.33	57.24	100	157	P	V
		4824	52.92	-1.08	54	70.76	31.56	7.33	57.24	100	157	A	V
													V
													V
802.11b CH 06 2437MHz		4874	50.55	-23.45	74	68.15	31.63	7.44	57.17	100	288	P	H
		4874	48.7	-5.3	54	66.3	31.63	7.44	57.17	100	288	A	H
		7311	44.74	-29.26	74	56.26	36.16	9.13	57.27	100	0	P	H
													H
		4874	54.43	-19.57	74	72.03	31.63	7.44	57.17	100	161	P	V
		4874	52.8	-1.2	54	70.4	31.63	7.44	57.17	100	161	A	V
		7311	45.92	-28.08	74	57.44	36.16	9.13	57.27	100	0	P	V
													V
802.11b CH 11 2462MHz		4924	54.3	-19.7	74	71.68	31.7	7.52	57.1	100	294	P	H
		4924	52.88	-1.12	54	70.26	31.7	7.52	57.1	100	294	A	H
		7386	46.12	-27.88	74	57.57	36.31	9.18	57.38	100	0	P	H
													H
		4924	54.45	-19.55	74	71.83	31.7	7.52	57.1	100	237	P	V
		4924	52.99	-1.01	54	70.37	31.7	7.52	57.1	100	237	A	V
		7386	49.21	-24.79	74	60.66	36.31	9.18	57.38	100	0	P	V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz
WIFI 802.11g (Band Edge @ 3m)

WIFI Ant. 1+2	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11g CH 01 2412MHz		2389.59	62.18	-11.82	74	51.52	26.89	4.83	30.99	125	305	P	H
		2390	48.81	-5.19	54	38.15	26.89	4.83	30.99	125	305	A	H
	*	2412	108.31	-	-	97.56	26.94	4.87	30.99	125	305	P	H
	*	2412	100.33	-	-	89.58	26.94	4.87	30.99	125	305	A	H
													H
													H
		2390	61.81	-12.19	74	51.15	26.89	4.83	30.99	100	79	P	V
		2390	48.42	-5.58	54	37.76	26.89	4.83	30.99	100	79	A	V
	*	2412	107.74	-	-	96.99	26.94	4.87	30.99	100	79	P	V
	*	2412	99.95	-	-	89.2	26.94	4.87	30.99	100	79	A	V
													V
													V
802.11g CH 06 2437MHz		2336.6	52.2	-21.8	74	41.79	26.73	4.76	31.01	333	285	P	H
		2389.66	41.51	-12.49	54	30.85	26.89	4.83	30.99	333	285	A	H
	*	2437	113.1	-	-	102.23	27.04	4.88	30.98	333	285	P	H
	*	2437	106.15	-	-	95.28	27.04	4.88	30.98	333	285	A	H
		2498.25	51.42	-22.58	74	40.32	27.2	4.93	30.96	333	285	P	H
		2483.5	41.78	-12.22	54	30.74	27.15	4.93	30.97	333	285	A	H
		2389.38	52.88	-21.12	74	42.22	26.89	4.83	30.99	149	77	P	V
		2389.94	43.28	-10.72	54	32.62	26.89	4.83	30.99	149	77	A	V
	*	2437	115.65	-	-	104.78	27.04	4.88	30.98	149	77	P	V
	*	2437	107.48	-	-	96.61	27.04	4.88	30.98	149	77	A	V
		2483.69	55.18	-18.82	74	44.14	27.15	4.93	30.97	149	77	P	V
		2483.5	43.93	-10.07	54	32.89	27.15	4.93	30.97	149	77	A	V



802.11g CH 11 2462MHz	*	2462	112.34	-	-	101.38	27.1	4.9	30.97	115	307	P	H
	*	2462	104.34	-	-	93.38	27.1	4.9	30.97	115	307	A	H
		2483.52	64.8	-9.2	74	53.76	27.15	4.93	30.97	115	307	P	H
		2483.52	52.28	-1.72	54	41.24	27.15	4.93	30.97	115	307	A	H
													H
													H
	*	2462	110.49	-	-	99.53	27.1	4.9	30.97	100	55	P	V
	*	2462	103	-	-	92.04	27.1	4.9	30.97	100	55	A	V
		2483.52	63	-11	74	51.96	27.15	4.93	30.97	100	55	P	V
		2483.52	50.95	-3.05	54	39.91	27.15	4.93	30.97	100	55	A	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz

WIFI 802.11g (Harmonic @ 3m)

WIFI Ant. 1+2	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11g CH 01 2412MHz		4824	57.69	-16.31	74	75.53	31.56	7.33	57.24	100	220	P	H
		4824	47.93	-6.07	54	65.77	31.56	7.33	57.24	100	220	A	H
													H
													H
		4824	62.2	-11.8	74	80.04	31.56	7.33	57.24	105	159	P	V
		4824	52.31	-1.69	54	70.15	31.56	7.33	57.24	105	159	A	V
													V
													V
802.11g CH 06 2437MHz		4874	62.36	-11.64	74	79.96	31.63	7.44	57.17	100	294	P	H
		4874	52.63	-1.37	54	70.23	31.63	7.44	57.17	100	294	A	H
		7311	69.48	-4.52	74	81	36.16	9.13	57.27	100	127	P	H
		7311	52.92	-1.08	54	64.44	36.16	9.13	57.27	100	127	A	H
		4874	58.14	-15.86	74	75.74	31.63	7.44	57.17	100	168	P	V
		4874	49.87	-4.13	54	67.47	31.63	7.44	57.17	100	168	A	V
		7311	71.65	-2.35	74	83.17	36.16	9.13	57.27	396	171	P	V
		7311	52.85	-1.15	54	64.37	36.16	9.13	57.27	396	171	A	V
802.11g CH 11 2462MHz		4924	59.68	-14.32	74	77.06	31.7	7.52	57.1	101	291	P	H
		4924	48.59	-5.41	54	65.97	31.7	7.52	57.1	101	291	A	H
		7386	55.16	-18.84	74	66.61	36.31	9.18	57.38	101	40	P	H
		7386	43.86	-10.14	54	55.31	36.31	9.18	57.38	101	40	A	H
		4924	59.62	-14.38	74	77	31.7	7.52	57.1	125	164	P	V
		4924	48.9	-5.1	54	66.28	31.7	7.52	57.1	125	164	A	V
		7386	59.4	-14.6	74	70.85	36.31	9.18	57.38	101	351	P	V
		7386	47.63	-6.37	54	59.08	36.31	9.18	57.38	101	351	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz

WIFI 802.11n HT20 (Band Edge @ 3m)

WIFI Ant. 1+2	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT20 CH 01 2412MHz		2390	64.92	-9.08	74	54.26	26.89	4.83	30.99	126	307	P	H
		2390	53.51	-0.49	54	42.85	26.89	4.83	30.99	126	307	A	H
	*	2412	109.52	-	-	98.77	26.94	4.87	30.99	126	307	P	H
	*	2412	101.75	-	-	91	26.94	4.87	30.99	126	307	A	H
													H
													H
		2389.59	62.68	-11.32	74	52.02	26.89	4.83	30.99	100	78	P	V
		2390	51.67	-2.33	54	41.01	26.89	4.83	30.99	100	78	A	V
	*	2412	109.45	-	-	98.7	26.94	4.87	30.99	100	78	P	V
	*	2412	101.42	-	-	90.67	26.94	4.87	30.99	100	78	A	V
													V
													V
802.11n HT20 CH 06 2437MHz		2389.94	54.32	-19.68	74	43.66	26.89	4.83	30.99	121	286	P	H
		2389.94	43.78	-10.22	54	33.12	26.89	4.83	30.99	121	286	A	H
	*	2437	113.51	-	-	102.64	27.04	4.88	30.98	121	286	P	H
	*	2437	105.45	-	-	94.58	27.04	4.88	30.98	121	286	A	H
		2483.76	54.04	-19.96	74	43	27.15	4.93	30.97	121	286	P	H
		2483.5	43.98	-10.02	54	32.94	27.15	4.93	30.97	121	286	A	H
		2389.94	53.36	-20.64	74	42.7	26.89	4.83	30.99	100	83	P	V
		2389.94	42.66	-11.34	54	32	26.89	4.83	30.99	100	83	A	V
	*	2437	112.41	-	-	101.54	27.04	4.88	30.98	100	83	P	V
	*	2437	104.52	-	-	93.65	27.04	4.88	30.98	100	83	A	V
		2483.76	55.82	-18.18	74	44.78	27.15	4.93	30.97	100	83	P	V
		2483.5	45.04	-8.96	54	34	27.15	4.93	30.97	100	83	A	V



802.11n HT20 CH 11 2462MHz	*	2462	110.27	-	-	99.31	27.1	4.9	30.97	119	307	P	H
	*	2462	102.38	-	-	91.42	27.1	4.9	30.97	119	307	A	H
		2483.52	65.19	-8.81	74	54.15	27.15	4.93	30.97	119	307	P	H
		2483.52	52.38	-1.62	54	41.34	27.15	4.93	30.97	119	307	A	H
													H
													H
	*	2462	108.57	-	-	97.61	27.1	4.9	30.97	100	56	P	V
	*	2462	100.75	-	-	89.79	27.1	4.9	30.97	100	56	A	V
		2484.28	63.92	-10.08	74	52.88	27.15	4.93	30.97	100	56	P	V
		2483.52	52.28	-1.72	54	41.24	27.15	4.93	30.97	100	56	A	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz
WIFI 802.11n HT20 (Harmonic @ 3m)

WIFI Ant. 1+2	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT20 CH 01 2412MHz		4824	60.6	-13.4	74	78.44	31.56	7.33	57.24	101	218	P	H
		4824	48.84	-5.16	54	66.68	31.56	7.33	57.24	101	218	A	H
													H
													H
		4824	64.87	-9.13	74	82.71	31.56	7.33	57.24	103	153	P	V
		4824	53.23	-0.77	54	71.07	31.56	7.33	57.24	103	153	A	V
													V
													V
802.11n HT20 CH 06 2437MHz		4874	59.59	-14.41	74	77.19	31.63	7.44	57.17	100	293	P	H
		4874	48.81	-5.19	54	66.41	31.63	7.44	57.17	100	293	A	H
		7311	72.86	-1.14	74	84.38	36.16	9.13	57.27	100	132	P	H
		7311	49.95	-4.05	54	61.47	36.16	9.13	57.27	100	132	A	H
		4874	62.33	-11.67	74	79.93	31.63	7.44	57.17	100	161	P	V
		4874	51.31	-2.69	54	68.91	31.63	7.44	57.17	100	161	A	V
		7311	67.1	-6.9	74	78.62	36.16	9.13	57.27	100	101	P	V
		7311	46.9	-7.1	54	58.42	36.16	9.13	57.27	100	101	A	V
802.11n HT20 CH 11 2462MHz		4924	59.33	-14.67	74	76.71	31.7	7.52	57.1	100	299	P	H
		4924	47.99	-6.01	54	65.37	31.7	7.52	57.1	100	299	A	H
		7386	52.82	-21.18	74	64.27	36.31	9.18	57.38	101	40	P	H
		7386	41.67	-12.33	54	53.12	36.31	9.18	57.38	101	40	A	H
		4924	59.62	-14.38	74	77	31.7	7.52	57.1	100	170	P	V
		4924	48.51	-5.49	54	65.89	31.7	7.52	57.1	100	170	A	V
		7386	57.94	-16.06	74	69.39	36.31	9.18	57.38	101	348	P	V
		7386	46.08	-7.92	54	57.53	36.31	9.18	57.38	101	348	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz

WIFI 802.11n HT40 (Band Edge @ 3m)

WIFI Ant. 1+2	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT40 CH 03 2422MHz		2389.94	64.94	-9.06	74	54.28	26.89	4.83	30.99	122	307	P	H
		2389.94	52.96	-1.04	54	42.3	26.89	4.83	30.99	122	307	A	H
	*	2422	103.23	-	-	92.42	26.99	4.87	30.98	122	307	P	H
	*	2422	94.96	-	-	84.15	26.99	4.87	30.98	122	307	A	H
		2484.6	52.56	-21.44	74	41.52	27.15	4.93	30.97	122	307	P	H
		2484.32	40.9	-13.1	54	29.86	27.15	4.93	30.97	122	307	A	H
		2389.8	62.78	-11.22	74	52.12	26.89	4.83	30.99	149	78	P	V
		2389.94	52.67	-1.33	54	42.01	26.89	4.83	30.99	149	78	A	V
	*	2422	103.67	-	-	92.86	26.99	4.87	30.98	149	78	P	V
	*	2422	95.82	-	-	85.01	26.99	4.87	30.98	149	78	A	V
		2486.35	52.43	-21.57	74	41.39	27.15	4.93	30.97	149	78	P	V
		2488.73	40.97	-13.03	54	29.87	27.2	4.93	30.96	149	78	A	V
802.11n HT40 CH 06 2437MHz		2388.4	63.67	-10.33	74	53.01	26.89	4.83	30.99	111	314	P	H
		2389.94	51.48	-2.52	54	40.82	26.89	4.83	30.99	111	314	A	H
	*	2437	107.92	-	-	97.05	27.04	4.88	30.98	111	314	P	H
	*	2437	100.24	-	-	89.37	27.04	4.88	30.98	111	314	A	H
		2484.11	57.39	-16.61	74	46.35	27.15	4.93	30.97	111	314	P	H
		2483.5	47.19	-6.81	54	36.15	27.15	4.93	30.97	111	314	A	H
		2388.68	64.16	-9.84	74	53.5	26.89	4.83	30.99	100	62	P	V
		2389.94	52.64	-1.36	54	41.98	26.89	4.83	30.99	100	62	A	V
	*	2437	108.33	-	-	97.46	27.04	4.88	30.98	100	62	P	V
	*	2437	100.05	-	-	89.18	27.04	4.88	30.98	100	62	A	V
		2483.76	58.86	-15.14	74	47.82	27.15	4.93	30.97	100	62	P	V
		2483.5	47.6	-6.4	54	36.56	27.15	4.93	30.97	100	62	A	V



802.11n HT40 CH 09 2452MHz		2382.38	51.88	-22.12	74	41.27	26.84	4.83	30.99	115	310	P	H
		2389.8	40.64	-13.36	54	29.98	26.89	4.83	30.99	115	310	A	H
	*	2452	105.82	-	-	94.92	27.04	4.9	30.97	115	310	P	H
	*	2452	97.97	-	-	87.07	27.04	4.9	30.97	115	310	A	H
		2484.32	64.56	-9.44	74	53.52	27.15	4.93	30.97	115	310	P	H
		2483.5	52.97	-1.03	54	41.93	27.15	4.93	30.97	115	310	A	H
		2383.5	52.01	-21.99	74	41.4	26.84	4.83	30.99	100	27	P	V
		2389.94	40.68	-13.32	54	30.02	26.89	4.83	30.99	100	27	A	V
	*	2452	106.55	-	-	95.65	27.04	4.9	30.97	100	27	P	V
	*	2452	98.01	-	-	87.11	27.04	4.9	30.97	100	27	A	V
		2484.88	63.26	-10.74	74	52.22	27.15	4.93	30.97	100	27	P	V
		2483.5	52.86	-1.14	54	41.82	27.15	4.93	30.97	100	27	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz
WIFI 802.11n HT40 (Harmonic @ 3m)

WIFI Ant. 1+2	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT40 CH 03 2422MHz		4844	47.34	-26.66	74	65.1	31.58	7.37	57.22	100	0	P	H
		7266	43.9	-30.1	74	55.45	36.1	9.11	57.23	100	0	P	H
													H
													H
		4844	53	-21	74	70.76	31.58	7.37	57.22	100	158	P	V
		4844	42.18	-11.82	54	59.94	31.58	7.37	57.22	100	158	A	V
		7266	44.64	-29.36	74	56.19	36.1	9.11	57.23	100	0	P	V
													V
802.11n HT40 CH 06 2437MHz		4874	54.9	-19.1	74	72.5	31.63	7.44	57.17	100	285	P	H
		4874	42.27	-11.73	54	59.87	31.63	7.44	57.17	100	285	A	H
		7311	47.43	-26.57	74	58.95	36.16	9.13	57.27	100	0	P	H
													H
		4874	57.76	-16.24	74	75.36	31.63	7.44	57.17	100	151	P	V
		4874	45.82	-8.18	54	63.42	31.63	7.44	57.17	100	151	A	V
		7311	48.79	-25.21	74	60.31	36.16	9.13	57.27	100	0	P	V
													V
802.11n HT40 CH 09 2452MHz		4904	49.45	-24.55	74	66.91	31.68	7.48	57.12	100	0	P	H
		7356	45.05	-28.95	74	56.51	36.25	9.17	57.33	100	0	P	H
													H
													H
		4904	54.18	-19.82	74	71.64	31.68	7.48	57.12	100	158	P	V
		4904	43.45	-10.55	54	60.91	31.68	7.48	57.12	100	158	A	V
		7356	47.5	-26.5	74	58.96	36.25	9.17	57.33	100	0	P	V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz

Emission below 1GHz

2.4GHz WIFI 802.11n HT20 (LF)

WIFI Ant.	Note	Frequency	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Ant Pos	Table Pos	Peak Avg.	Pol.
1+2		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
2.4GHz 802.11n HT20 LF		153.39	29.76	-13.74	43.5	46.97	13.75	1.27	32.28	-	-		H
		238.71	33.06	-12.94	46	50.3	13.31	1.59	32.22	-	-		H
		285.69	31.02	-14.98	46	45.93	15.49	1.68	32.15	-	-		H
		465.9	34.09	-11.91	46	43.79	20.27	2.13	32.18	100	0		H
		804.7	31.99	-14.01	46	36.03	25.03	2.78	31.97	-	-		H
		959.4	31.26	-14.74	46	30.5	28.52	3.07	30.97	-	-		H
													H
													H
													H
													H
													H
													H
		39.99	32.34	-7.66	40	49.51	14.41	0.74	32.33	-	-		V
		51.87	31.28	-8.72	40	52.29	10.55	0.74	32.32	-	-		V
		59.97	34.32	-5.68	40	57.25	8.56	0.84	32.31	100	0		V
		885.9	32.68	-13.32	46	35	26.21	2.94	31.58	-	-		V
		894.3	33.39	-12.61	46	35.51	26.37	2.94	31.54	-	-		V
		948.9	31.39	-14.61	46	31.42	27.83	3.06	31.06	-	-		V
													V
													V
													V
													V
													V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against limit line.												



Note symbol

*	Fundamental Frequency which can be ignored. However, the level of any unwanted emissions shall not exceed the level of the fundamental frequency.
!	Test result is over limit line.
P/A	P eak or A verage
H/V	H orizontal or V ertical



A calculation example for radiated spurious emission is shown as below:

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1+2		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11b		2390	55.45	-18.55	74	54.51	32.22	4.58	35.86	103	308	P	H
CH 01													
2412MHz		2390	43.54	-10.46	54	42.6	32.22	4.58	35.86	103	308	A	H

1. Level(dBμV/m) =

Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

2. Over Limit(dB) = Level(dBμV/m) – Limit Line(dBμV/m)

For Peak Limit @ 2390MHz:

1. Level(dBμV/m)

= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 54.51(dBμV) – 35.86 (dB)

= 55.45 (dBμV/m)

2. Over Limit(dB)

= Level(dBμV/m) – Limit Line(dBμV/m)

= 55.45(dBμV/m) – 74(dBμV/m)

= -18.55(dB)

For Average Limit @ 2390MHz:

1. Level(dBμV/m)

= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 42.6(dBμV) – 35.86 (dB)

= 43.54 (dBμV/m)

2. Over Limit(dB)

= Level(dBμV/m) – Limit Line(dBμV/m)

= 43.54(dBμV/m) – 54(dBμV/m)

= -10.46(dB)

Both peak and average measured complies with the limit line, so test result is “PASS”.



Appendix D. Radiated Spurious Emission Plots

Test Engineer :	Alex Jeng ,Bill Chang and Wilson Wu	Temperature :	24.7~25.2°C
		Relative Humidity :	47~52%





Note symbol





-L	Low channel location
-R	High channel location









2.4GHz 2400~2483.5MHz





WIFI 802.11b (Band Edge @ 3m)

WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11b CH01 2412MHz	
1+2	Horizontal	Fundamental
Peak	 Site : 03CH13-HY Condition : PEAK_BE_74 3m HORN_91200_1241 HORIZONTAL Detector : Peak Project : 741927-02 Mode : 1 Power : 11	 Site : 03CH13-HY Condition : PEAK_74 3m HORN_91200_1241 HORIZONTAL Detector : Peak Project : 741927-02 Mode : 1 Power : 11
Avg.	 Site : 03CH13-HY Condition : AVG_BE_54 3m HORN_91200_1241 HORIZONTAL Detector : Peak Project : 741927-02 Mode : 1 Power : 11	 Site : 03CH13-HY Condition : AVG_54 3m HORN_91200_1241 HORIZONTAL Detector : Peak Project : 741927-02 Mode : 1 Power : 11



WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11b CH01 2412MHz	
1+2	Vertical	Fundamental
Peak	 Site : 03CH13-HY Condition : PEAK_BE_74 3m HORN_91200_1241 VERTICAL Detector : Peak Project : 741927-02 Mode : 1 Power : 11	 Site : 03CH13-HY Condition : PEAK_74 3m HORN_91200_1241 VERTICAL Detector : Peak Project : 741927-02 Mode : 1 Power : 11
Avg.	 Site : 03CH13-HY Condition : AVG_BE_54 3m HORN_91200_1241 VERTICAL Detector : Peak Project : 741927-02 Mode : 1 Power : 11	 Site : 03CH13-HY Condition : AVG_54 3m HORN_91200_1241 VERTICAL Detector : Peak Project : 741927-02 Mode : 1 Power : 11

WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11b CH06 2437MHz - L	
1+2	Horizontal	Fundamental
Peak	 Site : 03CH13-HV Condition : PEAK_BE_74 3m HORN_91200_1241 HORIZONTAL Detector : Peak Project : 741927-02 Mode : 2 Power : 12.5	 Site : 03CH13-HV Condition : PEAK_74 3m HORN_91200_1241 HORIZONTAL Detector : Peak Project : 741927-02 Mode : 2 Power : 12.5
Avg.	 Site : 03CH13-HV Condition : AVG_BE_54 3m HORN_91200_1241 HORIZONTAL Detector : Peak Project : 741927-02 Mode : 2 Power : 12.5	 Site : 03CH13-HV Condition : AVG_54 3m HORN_91200_1241 HORIZONTAL Detector : Peak Project : 741927-02 Mode : 2 Power : 12.5





WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11b CH06 2437MHz - R	
1+2	Horizontal	Fundamental
Peak	 Site : 03CH13-HV Condition : PEAK_BE_74 3m HORN_91200_1241 HORIZONTAL Detector : Peak Project : 741927-02 Mode : 2 Power : 12.5	Left blank
Avg.	 Site : 03CH13-HV Condition : AVG_BE_54 3m HORN_91200_1241 HORIZONTAL Detector : Peak Project : 741927-02 Mode : 2 Power : 12.5	Left blank

WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11b CH06 2437MHz - L	
1+2	Vertical	Fundamental
Peak	 Site : 03CH13-HY Condition : PEAK_BE_74 3m HORN_91200_1241 VERTICAL Detector : Peak Project : 741927-02 Mode : 2 Power : 12.5	 Site : 03CH13-HY Condition : PEAK_74 3m HORN_91200_1241 VERTICAL Detector : Peak Project : 741927-02 Mode : 2 Power : 12.5
Avg.	 Site : 03CH13-HY Condition : AVG_BE_54 3m HORN_91200_1241 VERTICAL Detector : Peak Project : 741927-02 Mode : 2 Power : 12.5	 Site : 03CH13-HY Condition : AVG_54 3m HORN_91200_1241 VERTICAL Detector : Peak Project : 741927-02 Mode : 2 Power : 12.5







WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11b CH06 2437MHz - R	
1+2	Vertical	Fundamental
Peak	 Site : 03CH13-HV Condition : PEAK_BE_74 3m HORN_91200_1241 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 741927-02 Mode : 2 Power : 12.5	Left blank
Avg.	 Site : 03CH13-HV Condition : AVG_BE_54 3m HORN_91200_1241 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 741927-02 Mode : 2 Power : 12.5	Left blank



WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11b CH11 2462MHz	
1+2	Horizontal	Fundamental
Peak	 Site : 03CH13-HV Condition : PEAK_BE_74 3m HORN_91200_1241 HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 741927-02 Mode : 3 Power : 13.5	 Site : 03CH13-HV Condition : PEAK_74 3m HORN_91200_1241 HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 741927-02 Mode : 3 Power : 13.5
Avg.	 Site : 03CH13-HV Condition : AVG_BE_54 3m HORN_91200_1241 HORIZONTAL RBW:1000.000KHz VBW:0.010KHz SWT:Auto Detector : Peak Project : 741927-02 Mode : 3 Power : 13.5	 Site : 03CH13-HV Condition : AVG_54 3m HORN_91200_1241 HORIZONTAL RBW:1000.000KHz VBW:0.010KHz SWT:Auto Detector : Peak Project : 741927-02 Mode : 3 Power : 13.5











WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11b CH11 2462MHz	
1+2	Vertical	Fundamental
Peak	 Site : 03CH13-HV Condition : PEAK_BE_74 3m HORN_91200_1241 VERTICAL Detector : Peak Project : 741927-02 Mode : 3 Power : 13.5	 Site : 03CH13-HV Condition : PEAK_74 3m HORN_91200_1241 VERTICAL Detector : Peak Project : 741927-02 Mode : 3 Power : 13.5
Avg.	 Site : 03CH13-HV Condition : AVG_BE_54 3m HORN_91200_1241 VERTICAL Detector : Peak Project : 741927-02 Mode : 3 Power : 13.5	 Site : 03CH13-HV Condition : AVG_54 3m HORN_91200_1241 VERTICAL Detector : Peak Project : 741927-02 Mode : 3 Power : 13.5









2.4GHz 2400~2483.5MHz





WIFI 802.11g (Band Edge @ 3m)

WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11g CH01 2412MHz	
1+2	Horizontal	Fundamental
Peak	 Site : 03CH13-HY Condition : PEAK_BE_74 3m HORN_91200_1241 HORIZONTAL Detector : Peak Project : 741927-02 Mode : 4 Power : 15.5	 Site : 03CH13-HY Condition : PEAK_74 3m HORN_91200_1241 HORIZONTAL Detector : Peak Project : 741927-02 Mode : 4 Power : 15.5
Avg.	 Site : 03CH13-HY Condition : AVG_BE_54 3m HORN_91200_1241 HORIZONTAL Detector : Peak Project : 741927-02 Mode : 4 Power : 15.5	 Site : 03CH13-HY Condition : AVG_54 3m HORN_91200_1241 HORIZONTAL Detector : Peak Project : 741927-02 Mode : 4 Power : 15.5



WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11g CH01 2412MHz	
1+2	Vertical	Fundamental
Peak	 Site : 03CH13-HY Condition : PEAK_BE_74 3m HORN_91200_1241 VERTICAL Detector : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Project : Peak Mode : 741927-02 Power : 4 : 15.5	 Site : 03CH13-HY Condition : PEAK_74 3m HORN_91200_1241 VERTICAL Detector : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Project : Peak Mode : 741927-02 Power : 4 : 15.5
Avg.	 Site : 03CH13-HY Condition : AVG_BE_54 3m HORN_91200_1241 VERTICAL Detector : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Project : Peak Mode : 741927-02 Power : 4 : 15.5	 Site : 03CH13-HY Condition : AVG_54 3m HORN_91200_1241 VERTICAL Detector : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Project : Peak Mode : 741927-02 Power : 4 : 15.5

WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11g CH06 2437MHz - L	
1+2	Horizontal	Fundamental
Peak	 Site : 03CH13-HY Condition : PEAK_BE_74 3m HORN_91200_1241 HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 741927-02 Mode : 5 Power : 22	 Site : 03CH13-HY Condition : PEAK_74 3m HORN_91200_1241 HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 741927-02 Mode : 5 Power : 22
Avg.	 Site : 03CH13-HY Condition : AVG_BE_54 3m HORN_91200_1241 HORIZONTAL RBW:1000.000KHz VBW:0.010KHz SWT:Auto Detector : Peak Project : 741927-02 Mode : 5 Power : 22	 Site : 03CH13-HY Condition : AVG_54 3m HORN_91200_1241 HORIZONTAL RBW:1000.000KHz VBW:0.010KHz SWT:Auto Detector : Peak Project : 741927-02 Mode : 5 Power : 22

WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11g CH06 2437MHz - R	
1+2	Horizontal	Fundamental
Peak		Left blank
Avg.		Left blank





WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11g CH06 2437MHz - L	
1+2	Vertical	Fundamental
Peak	 Site : 03CH13-HY Condition : PEAK_BE_74 3m HORN_91200_1241 VERTICAL Detector : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Project : Peak 741927-02 Mode : 5 Power : Z2	 Site : 03CH13-HY Condition : PEAK_74 3m HORN_91200_1241 VERTICAL Detector : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Project : Peak 741927-02 Mode : 5 Power : Z2
Avg.	 Site : 03CH13-HY Condition : AVG_BE_54 3m HORN_91200_1241 VERTICAL Detector : RBW:1000.000KHz VBW:0.010KHz SWT:Auto Project : Peak 741927-02 Mode : 5 Power : Z2	 Site : 03CH13-HY Condition : AVG_54 3m HORN_91200_1241 VERTICAL Detector : RBW:1000.000KHz VBW:0.010KHz SWT:Auto Project : Peak 741927-02 Mode : 5 Power : Z2







WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11g CH06 2437MHz - R	
1+2	Vertical	Fundamental
Peak	 Site : 03CH13-HY Condition : PEAK_BE_74 3m HORN_91200_1241 VERTICAL Detector : Peak Project : 741927-02 Mode : 5 Power : Z2	Left Blank
Avg.	 Site : 03CH13-HY Condition : AVG_BE_54 3m HORN_91200_1241 VERTICAL Detector : Peak Project : 741927-02 Mode : 5 Power : Z2	Left Blank











WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11g CH11 2462MHz	
1+2	Horizontal	Fundamental
Peak	Site : 03CH13-HV Condition : PEAK_BE_74 3m HORN_91200_1241 HORIZONTAL Detector : Peak Project : 741927-02 Mode : 6 Power : 17.5	Site : 03CH13-HV Condition : PEAK_74 3m HORN_91200_1241 HORIZONTAL Detector : Peak Project : 741927-02 Mode : 6 Power : 17.5
Avg.	Site : 03CH13-HV Condition : AVG_BE_54 3m HORN_91200_1241 HORIZONTAL Detector : Peak Project : 741927-02 Mode : 6 Power : 17.5	Site : 03CH13-HV Condition : AVG_54 3m HORN_91200_1241 HORIZONTAL Detector : Peak Project : 741927-02 Mode : 6 Power : 17.5

WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11g CH11 2462MHz	
1+2	Vertical	Fundamental
Peak	 Site : 03CH13-HY Condition : PEAK_BE_74 3m HORN_91200_1241 VERTICAL Detector : Peak Project : 741927-02 Mode : 6 Power : 17.5	 Site : 03CH13-HY Condition : PEAK_74 3m HORN_91200_1241 VERTICAL Detector : Peak Project : 741927-02 Mode : 6 Power : 17.5
Avg.	 Site : 03CH13-HY Condition : AVG_BE_54 3m HORN_91200_1241 VERTICAL Detector : Peak Project : 741927-02 Mode : 6 Power : 17.5	 Site : 03CH13-HY Condition : AVG_54 3m HORN_91200_1241 VERTICAL Detector : Peak Project : 741927-02 Mode : 6 Power : 17.5



2.4GHz 2400~2483.5MHz
WIFI 802.11n HT20 (Band Edge @ 3m)





WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11n HT20 CH01 2412MHz	
1+2	Horizontal	Fundamental
Peak	 Site : 03CH13-HY Condition : PEAK_BE_74 3m HORN_91200_1241 HORIZONTAL Detector : Peak Project : 741927-02 Mode : 7 Power : 17	 Site : 03CH13-HY Condition : PEAK_74 3m HORN_91200_1241 HORIZONTAL Detector : Peak Project : 741927-02 Mode : 7 Power : 17
	 Site : 03CH13-HY Condition : AVG_BE_54 3m HORN_91200_1241 HORIZONTAL Detector : Peak Project : 741927-02 Mode : 7 Power : 17	 Site : 03CH13-HY Condition : AVG_54 3m HORN_91200_1241 HORIZONTAL Detector : Peak Project : 741927-02 Mode : 7 Power : 17

WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11n HT20 CH01 2412MHz	
1+2	Vertical	Fundamental
Peak	 Site : 03CH13-HY Condition : PEAK_BE_74 3m HORN_91200_1241 VERTICAL Detector : Peak Project : 741927-02 Mode : 7 Power : 17	 Site : 03CH13-HY Condition : PEAK_74 3m HORN_91200_1241 VERTICAL Detector : Peak Project : 741927-02 Mode : 7 Power : 17
Avg.	 Site : 03CH13-HY Condition : AVG_BE_54 3m HORN_91200_1241 VERTICAL Detector : Peak Project : 741927-02 Mode : 7 Power : 17	 Site : 03CH13-HY Condition : AVG_54 3m HORN_91200_1241 VERTICAL Detector : Peak Project : 741927-02 Mode : 7 Power : 17



WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11n HT20 CH06 2437MHz - L	
1+2	Horizontal	Fundamental
Peak	 Site : 03CH13-HV Condition : PEAK_BE_74 3m HORN_91200_1241 HORIZONTAL Detector : Peak Project : 741927-02 Mode : 8 Power : 21	 Site : 03CH13-HV Condition : PEAK_74 3m HORN_91200_1241 HORIZONTAL Detector : Peak Project : 741927-02 Mode : 8 Power : 21
Avg.	 Site : 03CH13-HV Condition : AVG_BE_54 3m HORN_91200_1241 HORIZONTAL Detector : Peak Project : 741927-02 Mode : 8 Power : 21	 Site : 03CH13-HV Condition : AVG_54 3m HORN_91200_1241 HORIZONTAL Detector : Peak Project : 741927-02 Mode : 8 Power : 21







WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11n HT20 CH06 2437MHz - R	
1+2	Horizontal	Fundamental
Peak	 Site : 03CH13-HV Condition : PEAK_BE_74 3m HORN_91200_1241 HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 741927-02 Mode : 8 Power : Z1	Left blank
Avg.	 Site : 03CH13-HV Condition : AVG_BE_54 3m HORN_91200_1241 HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 741927-02 Mode : 8 Power : Z1	Left blank

WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11n HT20 CH06 2437MHz - L	
1+2	Vertical	Fundamental
Peak	 Site : 03CH13-HY Condition : PEAK_BE_74 3m HORN_91200_1241 VERTICAL Detector : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Project : Peak Mode : 741927-02 Power : 8 : Z1	 Site : 03CH13-HY Condition : PEAK_74 3m HORN_91200_1241 VERTICAL Detector : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Project : Peak Mode : 741927-02 Power : 8 : Z1
Avg.	 Site : 03CH13-HY Condition : AVG_BE_54 3m HORN_91200_1241 VERTICAL Detector : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Project : Peak Mode : 741927-02 Power : 8 : Z1	 Site : 03CH13-HY Condition : AVG_54 3m HORN_91200_1241 VERTICAL Detector : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Project : Peak Mode : 741927-02 Power : 8 : Z1







WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11n HT20 CH06 2437MHz - R	
1+2	Vertical	Fundamental
Peak	 Site : 03CH13-HV Condition : PEAK_BE_74 3m HORN_91200_1241 VERTICAL Detector : Peak Project : 741927-02 Mode : 8 Power : Z1	Left Blank
Avg.	 Site : 03CH13-HV Condition : AVG_BE_54 3m HORN_91200_1241 VERTICAL Detector : Peak Project : 741927-02 Mode : 8 Power : Z1	Left Blank



WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11n HT20 CH11 2462MHz	
1+2	Horizontal	Fundamental
Peak	 Site : 03CH13-HV Condition : PEAK_BE_74 3m HORN_91200_1241 HORIZONTAL Detector : Peak Project : 741927-02 Mode : 9 Power : 17.5	 Site : 03CH13-HV Condition : PEAK_74 3m HORN_91200_1241 HORIZONTAL Detector : Peak Project : 741927-02 Mode : 9 Power : 17.5
Avg.	 Site : 03CH13-HV Condition : AVG_BE_54 3m HORN_91200_1241 HORIZONTAL Detector : Peak Project : 741927-02 Mode : 9 Power : 17.5	 Site : 03CH13-HV Condition : AVG_54 3m HORN_91200_1241 HORIZONTAL Detector : Peak Project : 741927-02 Mode : 9 Power : 17.5



WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11n HT20 CH11 2462MHz	
1+2	Vertical	Fundamental
Peak	 Site : 03CH13-HY Condition : PEAK_BE_74 3m HORN_91200_1241 VERTICAL Detector : Peak Project : 741927-02 Mode : 9 Power : 17.5	 Site : 03CH13-HY Condition : PEAK_74 3m HORN_91200_1241 VERTICAL Detector : Peak Project : 741927-02 Mode : 9 Power : 17.5
Avg.	 Site : 03CH13-HY Condition : AVG_BE_54 3m HORN_91200_1241 VERTICAL Detector : Peak Project : 741927-02 Mode : 9 Power : 17.5	 Site : 03CH13-HY Condition : AVG_54 3m HORN_91200_1241 VERTICAL Detector : Peak Project : 741927-02 Mode : 9 Power : 17.5









2.4GHz 2400~2483.5MHz



WIFI 802.11n HT40 (Band Edge @ 3m)

WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11n HT40 CH03 2422MHz - L	
1+2	Horizontal	Fundamental
Peak	Site : 03CH13-HY Condition : PEAK_BE_74 3m HORN_91200_1241 HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 741927-02 Mode : 10 Power : 13.5	Site : 03CH13-HY Condition : PEAK_74 3m HORN_91200_1241 HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 741927-02 Mode : 10 Power : 13.5
Avg.	Site : 03CH13-HY Condition : AVG_BE_54 3m HORN_91200_1241 HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 741927-02 Mode : 10 Power : 13.5	Site : 03CH13-HY Condition : AVG_54 3m HORN_91200_1241 HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 741927-02 Mode : 10 Power : 13.5







WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11n HT40 CH03 2422MHz - R	
1+2	Horizontal	Fundamental
Peak	 Site : 03CH13-HV Condition : PEAK_BE_74 3m HORN_91200_1241 HORIZONTAL Detector : Peak Project : 741927-02 Mode : 10 Power : 13.5	Left Blank
Avg.	 Site : 03CH13-HV Condition : AVG_BE_54 3m HORN_91200_1241 HORIZONTAL Detector : Peak Project : 741927-02 Mode : 10 Power : 13.5	Left Blank



WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11n HT40 CH03 2422MHz - L	
1+2	Vertical	Fundamental
Peak	 Site : 03CH13-HY Condition : PEAK_BE_74 3m HORN_91200_1241 VERTICAL Detector : Peak Project : 741927-02 Mode : 10 Power : 13.5	 Site : 03CH13-HY Condition : PEAK_74 3m HORN_91200_1241 VERTICAL Detector : Peak Project : 741927-02 Mode : 10 Power : 13.5
Avg.	 Site : 03CH13-HY Condition : AVG_BE_54 3m HORN_91200_1241 VERTICAL Detector : Peak Project : 741927-02 Mode : 10 Power : 13.5	 Site : 03CH13-HY Condition : AVG_54 3m HORN_91200_1241 VERTICAL Detector : Peak Project : 741927-02 Mode : 10 Power : 13.5

WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11n HT40 CH03 2422MHz - R	
1+2	Vertical	Fundamental
Peak	 Site : 03CH13-HV Condition : PEAK_BE_74 3m HORN_91200_1241 VERTICAL Detector : Peak Project : 741927-02 Mode : 10 Power : 13.5	Left blank
Avg.	 Site : 03CH13-HV Condition : AVG_BE_54 3m HORN_91200_1241 VERTICAL Detector : Peak Project : 741927-02 Mode : 10 Power : 13.5	Left blank









WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11n HT40 CH06 2437MHz - L	
1+2	Horizontal	Fundamental
Peak	 Site : 03CH13-HY Condition : PEAK_BE_74 3m HORN_91200_1241 HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 741927-02 Mode : 11 Power : 18	 Site : 03CH13-HY Condition : PEAK_74 3m HORN_91200_1241 HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 741927-02 Mode : 11 Power : 18
Avg.	 Site : 03CH13-HY Condition : AVG_BE_54 3m HORN_91200_1241 HORIZONTAL RBW:1000.000KHz VBW:0.010KHz SWT:Auto Detector : Peak Project : 741927-02 Mode : 11 Power : 18	 Site : 03CH13-HY Condition : AVG_54 3m HORN_91200_1241 HORIZONTAL RBW:1000.000KHz VBW:0.010KHz SWT:Auto Detector : Peak Project : 741927-02 Mode : 11 Power : 18









WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11n HT40 CH06 2437MHz - R	
1+2	Horizontal	Fundamental
Peak	 Site : 03CH13-HV Condition : PEAK_BE_74 3m HORN_91200_1241 HORIZONTAL Detector : Peak Project : 741927-02 Mode : 11 Power : 18	Left blank
Avg.	 Site : 03CH13-HV Condition : AVG_BE_54 3m HORN_91200_1241 HORIZONTAL Detector : Peak Project : 741927-02 Mode : 11 Power : 18	Left blank







WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11n HT40 CH06 2437MHz - L	
1+2	Vertical	Fundamental
Peak	 Site : 03CH13-HY Condition : PEAK_BE_74 3m HORN_91200_1241 VERTICAL Detector : Peak Project : 741927-02 Mode : 11 Power : 18	 Site : 03CH13-HY Condition : PEAK_74 3m HORN_91200_1241 VERTICAL Detector : Peak Project : 741927-02 Mode : 11 Power : 18
Avg.	 Site : 03CH13-HY Condition : AVG_BE_54 3m HORN_91200_1241 VERTICAL Detector : Peak Project : 741927-02 Mode : 11 Power : 18	 Site : 03CH13-HY Condition : AVG_54 3m HORN_91200_1241 VERTICAL Detector : Peak Project : 741927-02 Mode : 11 Power : 18



WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11n HT40 CH06 2437MHz - R	
1+2	Horizontal	Fundamental
Peak	 Site : 03CH13-HV Condition : PEAK_BE_74 3m HORN_91200_1241 VERTICAL Detector : Peak Project : 741927-02 Mode : 11 Power : 18	Left blank
Avg.	 Site : 03CH13-HV Condition : AVG_BE_54 3m HORN_91200_1241 VERTICAL Detector : Peak Project : 741927-02 Mode : 11 Power : 18	Left blank

WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11n HT40 CH09 2452MHz - L	
1+2	Horizontal	Fundamental
Peak	 Site : 03CH13-HV Condition : PEAK_BE_74 3m HORN_91200_1241 HORIZONTAL Detector : Peak Project : 741927-02 Mode : 12 Power : 16.5	 Site : 03CH13-HV Condition : PEAK_74 3m HORN_91200_1241 HORIZONTAL Detector : Peak Project : 741927-02 Mode : 12 Power : 16.5
Avg.	 Site : 03CH13-HV Condition : AVG_BE_54 3m HORN_91200_1241 HORIZONTAL Detector : Peak Project : 741927-02 Mode : 12 Power : 16.5	 Site : 03CH13-HV Condition : AVG_54 3m HORN_91200_1241 HORIZONTAL Detector : Peak Project : 741927-02 Mode : 12 Power : 16.5



WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11n HT40 CH09 2452MHz - R	
1+2	Horizontal	Fundamental
Peak	 Site : 03CH13-HV Condition : PEAK_BE_74 3m HORN_91200_1241 HORIZONTAL Detector : Peak Project : 741927-02 Mode : 12 Power : 16.5	Left blank
Avg.	 Site : 03CH13-HV Condition : AVG_BE_54 3m HORN_91200_1241 HORIZONTAL Detector : Peak Project : 741927-02 Mode : 12 Power : 16.5	Left blank





WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11n HT40 CH09 2452MHz - L	
1+2	Vertical	Fundamental
Peak	 Site : 03CH13-HY Condition : PEAK_BE_74 3m HORN_91200_1241 VERTICAL Detector : Peak Project : 741927-02 Mode : 12 Power : 16.5	 Site : 03CH13-HY Condition : PEAK_74 3m HORN_91200_1241 VERTICAL Detector : Peak Project : 741927-02 Mode : 12 Power : 16.5
Avg.	 Site : 03CH13-HY Condition : AVG_BE_54 3m HORN_91200_1241 VERTICAL Detector : Peak Project : 741927-02 Mode : 12 Power : 16.5	 Site : 03CH13-HY Condition : AVG_54 3m HORN_91200_1241 VERTICAL Detector : Peak Project : 741927-02 Mode : 12 Power : 16.5



WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11n HT40 CH09 2452MHz - R	
1+2	Vertical	Fundamental
Peak	 Site : 03CH13-HY Condition : PEAK_BE_74 3m HORN_91200_1241 VERTICAL Detector : Peak Project : 741927-02 Mode : 12 Power : 16.5	Left blank
Avg.	 Site : 03CH13-HY Condition : AVG_BE_54 3m HORN_91200_1241 VERTICAL Detector : Peak Project : 741927-02 Mode : 12 Power : 16.5	Left blank

2.4GHz 2400~2483.5MHz
WIFI 802.11b (Harmonic @ 3m)



WIFI	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	802.11b CH01 2412MHz	
1+2	Horizontal	Vertical
Peak Avg.	 Site : 03CH13-HY Condition : PEAK_74 3m SHF_HORN_584 HORIZONTAL Detector : Peak Project : 741927-02 Mode : 1 Plane : Y With Accessory Power : 11	 Site : 03CH13-HY Condition : PEAK_74 3m SHF_HORN_584 VERTICAL Detector : Peak Project : 741927-02 Mode : 1 Plane : Y With Accessory Power : 11

WIFI	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	802.11b CH06 2437MHz	
1+2	Horizontal	Vertical
Peak Avg.	 Site : 03CH13-4V Condition : PEAK_74 3m SHF_HORN_584 HORIZONTAL Detector : Peak Project : 741927-02 Mode : 2 Plane : Y With Accessory Power : 12.5	 Site : 03CH13-4V Condition : PEAK_74 3m SHF_HORN_584 VERTICAL Detector : Peak Project : 741927-02 Mode : 2 Plane : Y With Accessory Power : 12.5





WIFI	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	802.11b CH11 2462MHz	
1+2	Horizontal	Vertical
Peak Avg.	 Site : 03CH13-HV Condition : PEAK_74 3m SHF_HORN_584 HORIZONTAL Detector : Peak Project : 741927-02 Mode : 3 Plane : Y With Accessory Power : 13.5	 Site : 03CH13-HV Condition : PEAK_74 3m SHF_HORN_584 VERTICAL Detector : Peak Project : 741927-02 Mode : 3 Plane : Y With Accessory Power : 13.5



2.4GHz 2400~2483.5MHz
WIFI 802.11g (Harmonic @ 3m)

WIFI	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	802.11g CH01 2412MHz	
1+2	Horizontal	Vertical
Peak Avg.	 Site : 03CH13-HY Condition : PEAK_74 3m SHF_HORN_584 HORIZONTAL Detector : Peak Project : 741927-02 Mode : 4 Plane : Y With Accessory Power : 15.5	 Site : 03CH13-HY Condition : PEAK_74 3m SHF_HORN_584 VERTICAL Detector : Peak Project : 741927-02 Mode : 4 Plane : Y With Accessory Power : 15.5





WIFI	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	802.11g CH06 2437MHz	
1+2	Horizontal	Vertical
Peak Avg.	 Site : 03CH13-4V Condition : PEAK_74 3m SHF_HORN_584 HORIZONTAL Detector : Peak Project : 741927-02 Mode : S Plane : Y With Accessory Power : Z2	 Site : 03CH13-4V Condition : PEAK_74 3m SHF_HORN_584 VERTICAL Detector : Peak Project : 741927-02 Mode : S Plane : Y With Accessory Power : Z2





WIFI	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	802.11g CH11 2462MHz	
1+2	Horizontal	Vertical
Peak Avg.	 Site : 03CH13-4V Condition : PEAK_74 3m SHF_HORN_584 HORIZONTAL Detector : Peak Project : 741927-02 Mode : 6 Power : 17.5	 Site : 03CH13-4V Condition : PEAK_74 3m SHF_HORN_584 VERTICAL Detector : Peak Project : 741927-02 Mode : 6 Power : 17.5



2.4GHz 2400~2483.5MHz
WIFI 802.11n HT20 (Harmonic @ 3m)

WIFI	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	802.11n HT20 CH01 2412MHz	
1+2	Horizontal	Vertical
Peak Avg.	 Site : 03CH13-HY Condition : PEAK_74 3m SHF_HORN_584 HORIZONTAL Detector : Peak Project : 741927-02 Mode : 7 Power : 17	 Site : 03CH13-HY Condition : PEAK_74 3m SHF_HORN_584 VERTICAL Detector : Peak Project : 741927-02 Mode : 7 Power : 17







WIFI	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	802.11n HT20 CH06 2437MHz	
1+2	Horizontal	Vertical
Peak Avg.	 Site : 03CH13-4V Condition : PEAK_74 3m SHF_HORN_584 HORIZONTAL Detector : Peak Project : 741927-02 Mode : 8 Power : 21	 Site : 03CH13-4V Condition : PEAK_74 3m SHF_HORN_584 VERTICAL Detector : Peak Project : 741927-02 Mode : 8 Power : 21





WIFI	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	802.11n HT20 CH11 2462MHz	
1+2	Horizontal	Vertical
Peak Avg.	 Site : 03CH13-4V Condition : PEAK_74 3m SHF_HORN_584 HORIZONTAL Detector : Peak Project : 741927-02 Mode : 9 Power : 17.5	 Site : 03CH13-4V Condition : PEAK_74 3m SHF_HORN_584 VERTICAL Detector : Peak Project : 741927-02 Mode : 9 Power : 17.5



2.4GHz 2400~2483.5MHz
WIFI 802.11n HT40 (Harmonic @ 3m)

WIFI	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	802.11n HT40 CH03 2422MHz	
1+2	Horizontal	Vertical
Peak Avg.	 Site : 03CH13-HY Condition : PEAK_74 3m SHF_HORN_584 HORIZONTAL Detector : Peak Project : 741927-02 Mode : 10 Power : 13.5	 Site : 03CH13-HY Condition : PEAK_74 3m SHF_HORN_584 VERTICAL Detector : Peak Project : 741927-02 Mode : 10 Power : 13.5

WIFI	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	802.11n HT40 CH06 2437MHz	
1+2	Horizontal	Vertical
Peak Avg.	 Site : 03CH13-4V Condition : PEAK_74 3m SHF_HORN_584 HORIZONTAL Detector : Peak Project : 741927-02 Mode : 11 Power : 18	 Site : 03CH13-4V Condition : PEAK_74 3m SHF_HORN_584 VERTICAL Detector : Peak Project : 741927-02 Mode : 11 Power : 18

WIFI	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	802.11n HT40 CH09 2452MHz	
1+2	Horizontal	Vertical
Peak Avg.	 Site : 03CH13-4V Condition : PEAK_74 3m SHF_HORN_584 HORIZONTAL Detector : Peak Project : 741927-02 Mode : 12 Power : 16.5	 Site : 03CH13-4V Condition : PEAK_74 3m SHF_HORN_584 VERTICAL Detector : Peak Project : 741927-02 Mode : 12 Power : 16.5

Emission below 1GHz
2.4GHz WIFI 802.11n HT20 (LF)

WIFI	2.4GHz 2400~2483.5MHz	
ANT	802.11n HT20 LF	
1+2	Horizontal	Vertical
QP / Peak	 Site : 03CH13-HY Condition : QP 3m B1LOG_40103 HORIZONTAL Detector : Peak Project : 741927-02 Mode : 13	 Site : 03CH13-HY Condition : QP 3m B1LOG_40103 VERTICAL Detector : Peak Project : 741927-02 Mode : 13


Appendix E. Duty Cycle Plots

Antenna	Band	Duty Cycle(%)	T(us)	1/T(kHz)	VBW Setting
1+2	2.4GHz 802.11b for Ant 1	100	-	-	10Hz
1+2	2.4GHz 802.11b for Ant 2	100	-	-	
1+2	2.4GHz 802.11g for Ant 1	100	-	-	
1+2	2.4GHz 802.11g for Ant 2	100	-	-	
1+2	2.4GHz 802.11n HT20 for Ant 1	100	-	-	
1+2	2.4GHz 802.11n HT20 for Ant 2	100	-	-	
1+2	2.4GHz 802.11ac VHT20 for Ant 1	100	-	-	
1+2	2.4GHz 802.11ac VHT20 for Ant 2	100	-	-	




MIMO<Ant. 1+2(1)>

802.11b



Date: 9.NOV.2017 19:01:00

802.11g




Date: 9.NOV.2017 19:40:11




802.11n HT40



MIMO<Ant. 1+2(2)>
802.11b


Date: 9.NOV.2017 19:02:08

802.11g


Date: 9.NOV.2017 19:41:02



802.11n HT40

