



427 West 12800 South
Draper, UT 84020

Test Report Certification

FCC ID	SWX-E7ADI
ISED ID	6545A-E7ADI
Equipment Under Test	E7-Audience-Indoor
Test Report Serial Number	TR10362_01
Date of Test(s)	16 - 18 July; 14 August 2024 28 January; 24 - 26 February; 11 - 13 March 2025
Report Issue Date	17 September 2025

Test Specification	Applicant
47 CFR FCC Part 15, Subpart E RSS-248, Issue 3 (October 2024)	Ubiquiti Inc. 685 Third Avenue New York, NY 10017 U.S.A.



Certification of Engineering Report


This report has been prepared by Unified Compliance Laboratory (UCL) to document compliance of the device described below with the requirement of Federal Communication Commissions (FCC) Part 15, Subpart E. This report may be reproduced in full. Partial reproduction of this report may only be made with the written consent of the laboratory. The results in this report apply only to the sample tested with the specifications provided by the manufacturer.

Applicant	Ubiquiti Inc.
Manufacturer	Ubiquiti Inc.
Brand Name	UBIQUITI
Model Number	E7-Audience-Indoor
FCC ID	SWX-E7ADI
ISED ID	6545A-E7ADI

On this 17th day of September 2025, I individually and for Unified Compliance Laboratory certify that the statements made in this engineering report are true, complete, and correct to the best of my knowledge and are made in good faith. Unified Compliance laboratory is not responsible for incorrect information provided by the manufacturer.

Although NVLAP has accredited the Unified Compliance Laboratory testing facilities, this report must not be used to claim product certification, approval, or endorsement by NVLAP, NIST or any agency of the U.S. federal government.

Unified Compliance Laboratory



Written By: Kimberly DeBole



Reviewed By: Joseph W. Jackson

Revision History		
Revision	Description	Date
01	Original Report Release	17 September 2025

Table of Contents

1	Client Information.....	5
1.1	Applicant.....	5
1.2	Manufacturer.....	5
2	Equipment Under Test (EUT).....	6
2.1	Identification of EUT	6
2.2	Description of EUT	6
2.3	EUT and Support Equipment	7
2.4	Interface Ports on EUT	8
2.5	Operating Environment.....	8
2.6	Operating Modes.....	8
2.7	EUT Exercise Software.....	8
2.8	Block Diagram of Test Configuration	9
2.9	Modification Incorporated/Special Accessories on EUT.....	9
2.10	Deviation, Opinions Additional Information or Interpretations from Test Standard.....	9
3	Test Specification, Method and Procedures.....	10
3.1	Test Specification.....	10
3.2	Methods & Procedures.....	10
3.3	FCC Part 15, Subpart E.....	10
3.4	Results.....	10
3.5	Test Location	11
4	Test Equipment	12
4.1	Conducted Emissions at Mains Ports.....	12
4.2	Direct Connect at the Antenna Port Tests.....	12
4.3	Radiated Emissions	13
4.4	Equipment Calibration	14
4.5	Measurement Uncertainty.....	14
5	Test Results.....	15
5.1	§15.203 Antenna Requirements.....	15
5.2	Conducted Emissions at Mains Ports Data	16
5.3	§15.407(a) 26 dB Emissions Bandwidth.....	18
5.4	§15.407(a)(4) Maximum Output Power.....	20
5.5	§15.407(b)(7) Spurious Emissions.....	26
5.6	§15.407(a)(4) Maximum Power Spectral Density	32

1 Client Information

1.1 Applicant

Company	Ubiquiti Inc. 685 Third Avenue New York, NY 10017 U.S.A.
Contact Name	Alex Macon
Title	Compliance

1.2 Manufacturer

Company	Ubiquiti Inc. 685 Third Avenue New York, NY 10017 U.S.A.
Contact Name	Alex Macon
Title	Compliance

2 Equipment Under Test (EUT)

2.1 Identification of EUT

Brand Name	UBIQUITI
Model Number	E7-Audience-Indoor
Serial Number	FE60A0
Dimensions (cm)	47.4 x 26.5 x 9.4

2.2 Description of EUT

The E7-Audience-Indoor is a WiFi 7 access point designed for high-density environments with (1) 10GbE PoE port and (1) 1GbE PoE port. The E7-Audience-Indoor transmits in the 5 GHz, and 6 GHz frequency bands using integral antennas and is powered by an 802.3at PoE power adapter.

The E7-Audience-Indoor has a low gain mode with the antenna gain of 11 dBi and a high gain mode with the antenna gain of 15 dBi. For Output Power (Section 5.4) and PSD (Section 5.6) both low gain and high gain antenna modes are documented. For the remaining test, the high gain mode is characterized as worst-case scenario.

The E7-Audience-Indoor uses Transmit Power (TP) Control protocol and is included in the power tables of Section 5.4.

This device does not support channel puncturing.

For CDD transmission, direction gain is calculated as follows.

Array Gain = $10 \log(\text{NANT}/\text{NSS})$ dB

NANT = number of transmit antennas and NSS = number of spatial streams. NSS = 1 considered worst case. For power measurements on IEEE 802.11 devices, Array Gain = 0 dB for $\text{NANT} \leq 4$;

Low Gain Mode

For PSD measurements when $\text{Nss}=1$: Array Gain = $10 \log(\text{NANT}/\text{NSS})$ dB + Antenna Gain (dBi). Or $6.02 \text{ dB} + 11 \text{ dBi} = 17.02 \text{ dBi}$.

High Gain Mode

For PSD measurements when $\text{Nss}=1$: Array Gain = $10 \log(\text{NANT}/\text{NSS})$ dB + Antenna Gain (dBi). Or $6.02 \text{ dB} + 15 \text{ dBi} = 21.02 \text{ dBi}$.

This report covers the circuitry of the device subject to FCC Part 15, Subpart E. The circuitry of the device subject to FCC Part 15 Subpart B was found to be compliant and is covered under a separate Unified Compliance Laboratory test report.

The table below show the channels used within the different modulation bandwidths.

Band	Modulation Bandwidth	Frequency (MHz)	Maximum Power Setting
UNII-5	be (EHT20)	5955, 5975, 5995, 6015, 6035, 6055, 6075, 6095, 6115, 6135, 6155, 6175, 6195, 6215, 6235, 6255, 6275, 6295, 6315, 6335, 6355, 6375, 6395	TP11
		6415	TP10
	be (EHT40)	5965, 6005, 6045, 6085, 6125, 6165, 6205, 6245, 6285, 6325, 6385	TP11
		6405	TP10
	be (EHT80)	5985, 6065, 6145	TP10
		6225, 6305	TP11
		6385	TP10
	be (EHT160)	6025	TP11
		6185, 6325	TP10
	be (EHT320)	6265	TP10

2.3 EUT and Support Equipment

The EUT and support equipment used during the test are listed below.

Brand Name Model Number Serial Number	Description	Name of Interface Ports / Interface Cables
BN: UBIQUITI MN: E7-Audience-Indoor (Note 1) SN: FE60A0	Wireless Access Point	See Section 2.4
BN: UBIQUITI MN: U-POE-at SN: N/A	PoE Injector Power Supply	Shielded or Un-shielded Cat 5e cable (Note 2)
BN: Dell MN: XPS 13 SN: N/A	Laptop Computer	Shielded or Un-shielded Cat 5e cable (Note 2)

Notes: (1) EUT

(2) Interface port connected to EUT (See Section 2.4)

The support equipment listed above was not modified in order to achieve compliance with this standard.

2.4 Interface Ports on EUT

Name of Ports	No. of Ports Fitted to EUT	Cable Description/Length
PoE Input	1	7m Shielded Cat 5E
PoE Output (PoE Injector)	1	7m Shielded Cat 5E to E7-Audience-Indoor PoE Input
LAN (PoE Injector)	1	unshielded Cat 5E to Laptop PC
AC (PoE Injector)	1	3 Conductor power cord to AC mains/80cm

2.5 Operating Environment

Power Supply	120 Volts AC Mains to 48 Volts PoE
AC Mains Frequency	60 Hz
Temperature	21.5 – 23.3 °C
Humidity	21.4 – 27.8 %
Barometric Pressure	1013 mBar

2.6 Operating Modes

The E7-Audience-Indoor was tested using test software in order to enable to constant transmission. The measurements within this report are corrected to reference a 100% duty cycle. All emission modes of 802.11 be were investigated. All measurements are reported with the worst-case mode (802.11be) unless otherwise stated.

2.7 EUT Exercise Software

EUT firmware version 1.0 was used to operate the transmitter using a constant transmit mode.

2.8 Block Diagram of Test Configuration




Diagram 1: Test Configuration Block Diagram

2.9 Modification Incorporated/Special Accessories on EUT

There were no modifications made to the EUT during testing to comply with the specification.

2.10 Deviation, Opinions Additional Information or Interpretations from Test Standard

There were no deviations, opinions, additional information or interpretations from the test specification.

3 Test Specification, Method and Procedures

3.1 Test Specification

Title	47 CFR FCC Part 15, Subpart E, Section 15.407 Limits and methods of measurement of radio interference characteristics of Unlicensed National Information Infrastructure Devices
Purpose of Test	The tests were performed to demonstrate initial compliance

3.2 Methods & Procedures

3.2.1 47 CFR FCC Part 15 Section 15.407

See test standard for details.

3.3 FCC Part 15, Subpart E

3.3.1 Summary of Tests

FCC Section	ISED Section	Environmental Phenomena	Frequency Range (MHZ)	Result
15.203	N/A	Antenna requirements	Structural Requirement	Compliant
15.207	RSS-Gen	Conducted Disturbance at Mains Port	0.15 to 30	Compliant
15.407(a)	RSS-247 §6.2.2	Bandwidth Requirement	5955 to 6415	Compliant
15.407(a)	RSS-247 §6.2.2, §6.2.3	Peak Output Power ¹	5955 to 6415	Compliant
15.407(b)	RSS-247 §6.2.2, §6.2.3	Antenna Conducted Spurious Emissions ¹	0.009 to 40000	N/A Note ²
15.209	RSS-247 §6.2.2, §6.2.3	Radiated Spurious Emissions	0.009 to 40000	Compliant
15.407(a)	RSS-247 §6.2.2, §6.2.3	Peak Power Spectral Density ¹	5955 to 6415	Compliant

The testing was performed according to the procedures in ANSI C63.10-2013, KDB 789033, KDB 987594 and 47 CFR Part 15. Where applicable, KDB 662911 was followed to sum required measurements.

Note ¹: Various RU modes were considered for RF Power, PSD, and Spurious Emissions, and the "single client" RU mode is the worst case - the results herein are "single client" RU mode.

Note ²: Radiated Spurious was performed per 15.209 with the antenna unterminated.

3.4 Results

In the configuration tested, the EUT complied with the requirements of the specification.

3.5 Test Location

Testing was performed at the Unified Compliance Laboratory 3-Meter and 10-Meter chambers located at 427 West 12800 South, Draper, UT 84020. Unified Compliance Laboratory is accredited by National Voluntary Laboratory Accreditation Program (NVLAP); NVLAP Code 600241-0 which is effective until 30 June 2026. This site has also been registered with Innovations, Science and Economic Development (ISED) department as was accepted under Appendix B, Phase 1 procedures of the APEC Tel MRA for Canadian recognition. ISED No.: 25346, effective until 30 June 2026.

Unified Compliance Laboratory has been assigned Designation Number US5037 by the FCC and Conformity Assessment Number US0223 by ISED.

4 Test Equipment

4.1 Conducted Emissions at Mains Ports

Type of Equipment	Manufacturer	Model Number	Asset Number	Date of Last Calibration	Due Date of Calibration
EMI Receiver	AFJ	FFT3010	UCL-6754	2/27/2025	2/27/2026
LISN	AFJ	LS16C/10	UCL-6749	3/3/2025	3/3/2026
ISN	Teseq	ISN T800	UCL-2971	3/31/2025	3/31/2026
AC Power Source	Laplace Instruments	AC1000A	UCL-2857	N/A	N/A
Test Software	AFJ	AFJ FFT3010	UCL-3107	N/A	N/A

Table 1: List of equipment used for Conducted Emissions Testing at Mains Port




Figure 1: Conducted Emissions Test

4.2 Direct Connect at the Antenna Port Tests

Type of Equipment	Manufacturer	Model Number	Asset Number	Date of Last Calibration	Due Date of Calibration
Spectrum Analyzer	R&S	FSV40	UCL-2861	1/16/2025	1/16/2026
Signal Generator	R&S	SMB100A	UCL-2864	N/A	N/A
Vector Signal Generator	R&S	SMBV100A	UCL-2873	N/A	N/A
Switch Extension	R&S	OSP-B157WX	UCL-2867	4/28/2025	1/16/2026
Switch Extension	R&S	OSP-150W	UCL-2870	4/28/2025	1/16/2026
Test Software	R&S	EMC32	UCL-9442	--	--

Table 2: List of equipment used for Direct Connect at the Antenna Port




Figure 2: Direct Connect at the Antenna Port Test

4.3 Radiated Emissions

Type of Equipment	Manufacturer	Model Number	Asset Number	Date of Last Calibration	Due Date of Calibration
EMI Receiver	Keysight	N9038A	UCL-2778	12/27/2024	12/27/2025
Pre-Amplifier 9 kHz – 1 GHz	Sonoma Instruments	310N	UCL-2889	1/19/2024	1/19/2026
Broadband Antenna	ETS-Lindgren	3142E	UCL-9782	2/6/2025	2/6/2026
Double Ridge Horn Antenna	Scwarzbeck	BBHA 9120D	UCL-3065	4/2/2025	4/2/2027
Log Periodic	Scwarzbeck	STLP 9129	UCL-3068	2/11/2025	2/4/2027
10 - 40 GHz Horn Antenna	ETS-Lindgren	3116C	UCL-7209	6/6/2024	6/6/2026
1 – 18 GHz Amplifier	Com-Power	PAM 118A	UCL-3833	7/22/2025	7/22/2026
Test Software	Nexio	BatEMC	UCL-5253 & UCL-5249	N/A	N/A

Table 3: List of equipment used for Radiated Emissions




Figure 3: Radiated Emissions Test

4.4 Equipment Calibration

All applicable equipment is calibrated using either an independent calibration laboratory or Unified Compliance Laboratory personnel at intervals defined in ANSI C63.4:2014 following outlined calibration procedures. All measurement instrumentation is traceable to the National Institute of Standards and Technology (NIST). Supporting documentation relative to traceability is on file and is available for examination upon request.

4.5 Measurement Uncertainty

Test	Uncertainty ($\pm$ dB)	Confidence (%)
Conducted Emissions	1.44	95
Radiated Emissions (9 kHz to 30 MHz)	2.50	95
Radiated Emissions (30 MHz to 1 GHz)	4.38	95
Radiated Emissions (1 GHz to 18 GHz)	4.37	95
Radiated Emissions (18 GHz to 40 GHz)	3.93	95
Direct Connect Tests	K Factor	Value
Emissions Bandwidth	2	2.0%
Output Power	2	1.0 dB
Peak Power Spectral Density	2	1.3 dB
Band Edge	2	0.8 dB
Transmitter Spurious Emissions	2	1.8 dB

5 Test Results

5.1 §15.203 Antenna Requirements


The EUT uses an internal integrated antenna. Per the manufacturer, the Maximum gain of the antenna per chain is 15 dBi. This is an 802.11 device and utilizes CDD as described in KDB 662911 D01. The antenna is not user replaceable. For CDD transmissions, directional gain is calculated as follows.

Results

The EUT complied with the specification


5.2 Conducted Emissions at Mains Ports Data

5.2.1 Line



ID	Frequency	Probe	Cable	Atten.	Detector	Meter Read	Meas Level	Limit 1	Limit 1 Dist.	Limit 2	Limit 2 Dist.	P/F
MU	MHz	dB	dB	dB	Type	dBμV	dBμV	dBμV	dB	dBμV	dB	P/F
3	513,000kHz	12.35	0.00		QPeak	38.11	50.46	56.00	-5.54			
1	192,000kHz	12.37	0.00		QPeak	45.29	57.66	63.95	-6.29			
2	312,000kHz	12.38	0.00		QPeak	39.84	52.22	59.92	-7.69			
4	192,000kHz	12.37	0.00		C_AVG	37.40	49.77			53.95	-4.18	
5	318,000kHz	12.38	0.00		C_AVG	32.40	44.78			49.76	-4.98	
6	513,000kHz	12.35	0.00		C_AVG	29.83	42.18			46.00	-3.82	

5.2.2 Neutral



ID	Frequency	Probe	Cable	Atten.	Detector	Meter Read	Meas Level	Limit 1	Limit 1 Dist.	Limit 2	Limit 2 Dist.	P/F
MU	MHz	dB	dB	dB	Type	dBμV	dBμV	dBμV	dB	dBμV	dB	P/F
1	192,000kHz	12.36	0.00		QPeak	44.82	57.18	63.95	-6.77			
3	513,000kHz	12.37	0.00		QPeak	35.73	48.10	56.00	-7.90			
2	315,000kHz	12.39	0.00		QPeak	38.49	50.88	59.84	-8.96			
4	192,000kHz	12.36	0.00		C_AVG	35.92	48.28			53.95	-5.67	
5	318,000kHz	12.39	0.00		C_AVG	31.03	43.42			49.76	-6.34	
6	516,000kHz	12.37	0.00		C_AVG	27.08	39.45			46.00	-6.55	

Result

The EUT complied with the specification limit.

5.3 §15.407(a) 26 dB Emissions Bandwidth

All chains were measured under the guidance of KDB 789033 Section II.C. and KDB 662911 D01.
Please see associated annex for details on instrument settings.

5.3.1 Low Gain Mode

Nominal BW (MHz)	Frequency (MHz)	99% Bandwidth (MHz)	26 dB Bandwidth (MHz)
EHT 20	5955	19.3	25.8
EHT 20	6195	19.3	23.1
EHT 20	6415	19.3	28.7
EHT 40	5965	38.5	45.5
EHT 40	6205	38.5	43.3
EHT 40	6405	39.0	53.5
EHT 80	5985	79.0	84.5
EHT 80	6225	80.0	88.5
EHT 80	6385	79.0	85.5
EHT 160	6025	160.0	172.0
EHT 160	6185	162.5	175.0
EHT 160	6325	160.0	171.0
EHT 320	6265	315.0	340.0

5.3.2 High Gain Mode

Nominal BW (MHz)	Frequency (MHz)	99% Bandwidth (MHz)	26 dB Bandwidth (MHz)
EHT 20	5955	19.3	22.7
EHT 20	6195	19.5	22.2
EHT 20	6415	19.3	22.8
EHT 40	5965	38.5	44.3
EHT 40	6205	38.5	43.0
EHT 40	6405	38.5	42.8
EHT 80	5985	78.0	84.5
EHT 80	6225	79.0	91.0
EHT 80	6385	79.0	85.5
EHT 160	6025	160.0	174.0
EHT 160	6185	162.5	172.0
EHT 160	6325	162.5	174.0
EHT 320	6265	317.5	345.0

Result

All chains were tested and the highest bandwidth per chain is reported above. For the 320 MHz emissions bandwidth the 99% bandwidth was used. Please see Annex for all bandwidth measurements.

5.4 §15.407(a)(4) Maximum Output Power

All chains were measured and summed under the guidance of KDB 789033 Section II. E.2. and KDB 662911 D01. Please see associated annex for details on instrument settings.

See Section 2.2 of this report for the directional gain calculation.

The maximum average RF conducted output power measured for this device was 35.93 dBm or 3917.42 mW (Low Gain Mode). The limit is 36 dBm EIRP, or 4 watt EIRP. The antenna has a gain of 11 dBi (Low Gain Mode) and 15 dBi (High Gain Mode).

5.4.1 Low Gain Mode

Output Power Per Chain

Modulation (BW)	Frequency (MHz)	Chain0 (dBm)	Chain1 (dBm)	Chain2 (dBm)	Chain3 (dBm)	Total Summed Output Power* (dBm)
EHT 20	5955	18.66	17.11	18.82	19.69	24.69
EHT 20	6195	18.01	18.08	17.00	19.02	24.10
EHT 20	6415	18.47	17.48	18.47	18.63	24.31
EHT 40	5965	18.95	17.48	19.25	19.67	24.93
EHT 40	6205	18.82	19.25	17.71	19.52	24.90
EHT 40	6405	18.52	18.63	17.87	18.24	24.35
EHT 80	5985	18.41	19.23	17.74	19.28	24.83
EHT 80	6225	18.63	19.03	17.19	18.88	24.51
EHT 80	6385	18.44	18.91	17.80	18.27	24.40
EHT 160	6025	17.89	19.17	17.28	19.02	24.43
EHT 160	6185	17.64	18.36	17.16	18.78	24.05
EHT 160	6325	18.28	18.94	16.72	18.13	24.11
EHT 320	6265	18.57	19.29	16.80	19.08	24.56

Nss>1

Modulation (BW)	Frequency (MHz)	Data Rate	TP Setting	Total Summed Output Power* (dBm)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Margin (dBm)
EHT 20	5955	Mcs0_Nss4	22	24.69	11	35.69	36	-0.31
EHT 20	6195	Mcs0_Nss4	20	24.10	11	35.10	36	-0.90
EHT 20	6415	Mcs0_Nss4	21	24.31	11	35.31	36	-0.69
EHT 40	5965	Mcs0_Nss4	22	24.93	11	35.93	36	-0.07
EHT 40	6205	Mcs0_Nss4	21	24.90	11	35.90	36	-0.10
EHT 40	6405	Mcs0_Nss4	21	24.35	11	35.35	36	-0.65
EHT 80	5985	Mcs0_Nss4	21	24.83	11	35.73	36	-0.27
EHT 80	6225	Mcs0_Nss4	21	24.51	11	35.51	36	-0.49
EHT 80	6385	Mcs0_Nss4	21	24.40	11	35.40	36	-0.60
EHT 160	6025	Mcs0_Nss4	21	24.43	11	35.43	36	-0.57
EHT 160	6185	Mcs0_Nss4	20	24.05	11	35.05	36	-0.95
EHT 160	6325	Mcs0_Nss4	21	24.11	11	35.11	36	-0.89
EHT 320	6265	Mcs0_Nss4	21	24.56	11	35.56	36	-0.44

Nss=1

Modulation (BW)	Frequency (MHz)	Data Rate	TP Setting	Total Summed Output Power* (dBm)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Margin (dBm)
EHT 20	5955	Mcs0_Nss1	14	17.51	11	28.51	36	-7.49
EHT 20	6195	Mcs0_Nss1	14	18.45	11	29.45	36	-6.55
EHT 20	6415	Mcs0_Nss1	15	18.89	11	29.89	36	-6.11
EHT 40	5965	Mcs0_Nss1	17	20.58	11	31.58	36	-4.42
EHT 40	6205	Mcs0_Nss1	17	21.13	11	32.13	36	-3.87
EHT 40	6405	Mcs0_Nss1	18	21.31	11	32.31	36	-3.69
EHT 80	5985	Mcs0_Nss1	20	23.66	11	34.66	36	-1.34
EHT 80	6225	Mcs0_Nss1	21	24.51	11	35.51	36	-0.49
EHT 80	6385	Mcs0_Nss1	21	24.40	11	35.40	36	-0.60
EHT 160	6025	Mcs0_Nss1	21	24.43	11	35.43	36	-0.57
EHT 160	6185	Mcs0_Nss1	20	24.05	11	35.05	36	-0.95
EHT 160	6325	Mcs0_Nss1	21	24.11	11	35.11	36	-0.89
EHT 320	6265	Mcs0_Nss1	21	24.56	11	35.56	36	-0.44

5.4.2 High Gain Mode

Output Power Per Chain

Modulation (BW)	Frequency (MHz)	Chain0 (dBm)	Chain1 (dBm)	Chain2 (dBm)	Chain3 (dBm)	Total Summed Output Power* (dBm)
EHT 20	5955	13.60	15.09	13.70	14.58	20.31
EHT 20	6195	14.10	14.48	13.61	15.07	20.37
EHT 20	6415	14.03	13.88	13.98	13.96	19.98
EHT 40	5965	14.06	15.24	14.21	14.54	20.56
EHT 40	6205	13.81	14.32	13.56	14.62	20.12
EHT 40	6405	14.74	14.89	14.50	14.83	20.76
EHT 80	5985	14.48	14.93	14.45	14.96	20.73
EHT 80	6225	14.68	15.09	14.00	15.27	20.81
EHT 80	6385	14.87	15.05	14.35	14.74	20.78
EHT 160	6025	14.22	14.89	14.46	14.72	20.60
EHT 160	6185	13.69	14.44	13.40	14.73	20.12
EHT 160	6325	14.79	15.18	13.87	14.70	20.68
EHT 320	6265	14.76	15.22	14.36	15.09	20.89

Nss>1

Modulation (BW)	Frequency (MHz)	Data Rate	TP Setting	Total Summed Output Power* (dBm)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Margin (dBm)
EHT 20	5955	Mcs0_Nss4	17	20.31	15	35.31	36	-0.69
EHT 20	6195	Mcs0_Nss4	16	20.37	15	35.37	36	-0.63
EHT 20	6415	Mcs0_Nss4	16	19.98	15	34.98	36	-1.02
EHT 40	5965	Mcs0_Nss4	17	20.56	15	35.56	36	-0.44
EHT 40	6205	Mcs0_Nss4	16	20.12	15	35.12	36	-0.88
EHT 40	6405	Mcs0_Nss4	17	20.76	15	35.76	36	-0.24
EHT 80	5985	Mcs0_Nss4	18	20.73	15	35.73	36	-0.27
EHT 80	6225	Mcs0_Nss4	17	20.81	15	35.81	36	-0.19
EHT 80	6385	Mcs0_Nss4	17	20.78	15	35.78	36	-0.22
EHT 160	6025	Mcs0_Nss4	17	20.60	15	35.60	36	-0.40
EHT 160	6185	Mcs0_Nss4	16	20.12	15	35.12	36	-0.88
EHT 160	6325	Mcs0_Nss4	17	20.68	15	35.68	36	-0.32
EHT 320	6265	Mcs0_Nss4	17	20.89	15	35.89	36	-0.11

Nss=1

Modulation (BW)	Frequency (MHz)	Data Rate	TP Setting	Total Summed Output Power* (dBm)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Margin (dBm)
EHT 20	5955	Mcs0_Nss1	10	13.60	15	28.60	36	-7.40
EHT 20	6195	Mcs0_Nss1	10	14.27	15	29.27	36	-6.73
EHT 20	6415	Mcs0_Nss1	10	15.23	15	30.23	36	-5.77
EHT 40	5965	Mcs0_Nss1	13	16.81	15	31.81	36	-4.19
EHT 40	6205	Mcs0_Nss1	13	17.30	15	32.30	36	-3.70
EHT 40	6405	Mcs0_Nss1	13	17.09	15	32.09	36	-3.91
EHT 80	5985	Mcs0_Nss1	16	19.89	15	34.89	36	-1.11
EHT 80	6225	Mcs0_Nss1	17	20.81	15	35.81	36	-0.19
EHT 80	6385	Mcs0_Nss1	17	20.78	15	35.78	36	-0.22
EHT 160	6025	Mcs0_Nss1	17	20.60	15	35.60	36	-0.40
EHT 160	6185	Mcs0_Nss1	16	20.12	15	35.12	36	-0.88
EHT 160	6325	Mcs0_Nss1	17	20.68	15	35.69	36	-0.31
EHT 320	6265	Mcs0_Nss1	17	20.89	15	35.89	36	-0.11

Result

In the configuration tested, the maximum average RF outpower was less than 4 watt EIRP; therefore, the EUT complied with the requirements of the specification (see spectrum analyzer plots in attached Annex).

* Gated EIRP shown in the Annex is the conducted measurement.

5.5 §15.407(b)(7) Spurious Emissions


5.5.1 Radiated Spurious Emissions in the Restricted Bands of § 15.205

The EUT uses various power settings based on the channel in use. In order to reduce test time, the radiated spurious emissions at the lowest, middle, and highest channel were measured at the maximum power of TP31.

Correction Factor = Antenna Factor (dBi) + Cable Loss (dB) - Pre-Amplifier Gain (dB), and is added to the Receiver reading.

Result


All emissions in the restricted bands of § 15.205 met the limits specified in § 15.209; therefore, the EUT complies with the specification. See Annex for Conducted Band edge plots.



QuasiPeak

Frequency	Level (dBμV/m)	Limit (dBμV/m)	Margin	Azimuth (°)	Height	Pol.	Correction (dB)
36.35 MHz	37.33	40.0	-2.67	43	1.129	Vertical	-9.91
37.85 MHz	36.35	40.0	-3.65	88	1.306	Vertical	-9.42
39.99 MHz	36.33	40.0	-3.67	80	1.126	Vertical	-8.84
519.77 MHz	37.74	47.0	-9.26	117	1.489	Vertical	-2.52
42.81 MHz	21.48	40.0	-18.52	143	1.897	Horizontal	-8.30
310.01 MHz	41.31	47.0	-5.69	334	1.131	Horizontal	-7.04

Table 4: Radiated Emissions 30 – 1000 MHz




Peak

Frequency	Level (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Azimuth (°)	Height (m)	Pol.	Correction (dB)
9.00 GHz	54.78	74.0	-19.22	208	1.5	Vertical	9.43
11.91 GHz	51.07	74.0	-22.93	126	1.5	Vertical	12.11
14.85 GHz	50.89	74.0	-23.11	0	3.497	Vertical	14.38
9.00 GHz	49.71	74.0	-24.29	106	3.199	Horizontal	9.43
11.91 GHz	54.46	74.0	-19.54	155	1.5	Horizontal	12.11
16.57 GHz	50.09	74.0	-23.91	0	3.493	Horizontal	16.10

Avg

Frequency	Level (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Azimuth (°)	Height (m)	Pol.	Correction (dB)
9.00 GHz	51.40	54.0	-2.60	208	1.5	Vertical	9.43
11.91 GHz	41.88	54.0	-12.12	126	1.5	Vertical	12.11
14.85 GHz	37.58	54.0	-16.42	0	3.497	Vertical	14.38
9.00 GHz	42.01	54.0	-11.99	106	3.199	Horizontal	9.43
11.91 GHz	43.08	54.0	-10.92	155	1.5	Horizontal	12.11
16.57 GHz	37.02	54.0	-16.98	0	3.493	Horizontal	16.10

Table 5: Radiated Emissions 1 – 17 GHz at the Lowest Frequency




Peak

Frequency	Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Azimuth (°)	Height (m)	Pol.	Correction (dB)
9.00 GHz	54.81	74.0	-19.19	208	1.5	Vertical	9.43
12.40 GHz	51.51	74.0	-22.49	205	4	Vertical	11.17
6.19 GHz	63.07	74.0	-10.93	211	1.5	Horizontal	3.27
11.38 GHz	48.16	74.0	-25.84	342	3.953	Horizontal	12.41
12.39 GHz	50.94	74.0	-23.06	126	1.5	Horizontal	11.19
14.62 GHz	51.16	74.0	-22.84	234	1.5	Horizontal	14.87

Avg

Frequency	Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Azimuth (°)	Height (m)	Pol.	Correction (dB)
9.00 GHz	51.29	54.0	-2.71	208	1.5	Vertical	9.43
12.40 GHz	37.83	54.0	-16.17	205	4	Vertical	11.17
6.19 GHz	49.90	54.0	-4.10	211	1.5	Horizontal	3.27
11.38 GHz	34.85	54.0	-19.15	342	3.953	Horizontal	12.41
12.39 GHz	38.63	54.0	-15.37	126	1.5	Horizontal	11.19
14.62 GHz	37.35	54.0	-16.65	234	1.5	Horizontal	14.87

Table 6: Radiated Emissions 1 – 17 GHz at the Middle Frequency




Peak

Frequency	Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Azimuth (°)	Height (m)	Pol.	Correction (dB)
9.00 GHz	56.15	74.0	-17.85	211	1.695	Vertical	9.43
12.83 GHz	49.76	74.0	-24.24	205	3.495	Vertical	11.50
14.69 GHz	51.61	74.0	-22.39	0	1.991	Vertical	14.85
9.00 GHz	48.42	74.0	-25.58	193	2.258	Horizontal	9.43
12.83 GHz	49.56	74.0	-24.44	126	3.496	Horizontal	11.50

Avg

Frequency	Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Azimuth (°)	Height (m)	Pol.	Correction (dB)
9.00 GHz	53.57	54.0	-0.43	211	1.695	Vertical	9.43
12.83 GHz	39.35	54.0	-14.65	205	3.495	Vertical	11.50
14.69 GHz	37.59	54.0	-16.41	0	1.991	Vertical	14.85
9.00 GHz	39.41	54.0	-14.59	193	2.258	Horizontal	9.43
12.83 GHz	35.75	54.0	-18.25	126	3.496	Horizontal	11.50

Table 7: Radiated Emissions 1 – 17 GHz at the Highest Frequency



Peak

Frequency	Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Azimuth (°)	Pol.	Correction (dB)
15.58 GHz	65.25	74.0	-8.75	116	Vertical	-0.55
24.78 GHz	55.16	74.0	-18.84	74	Vertical	1.71
18.59 GHz	65.42	74.0	-8.58	90	Horizontal	-0.57

Avg

Frequency	Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Azimuth (°)	Pol.	Correction (dB)
15.58 GHz	51.55	54.0	-3.45	116	Vertical	-0.55
24.78 GHz	47.66	54.0	-6.34	74	Vertical	1.71
18.59 GHz	50.91	54.0	-3.09	90	Horizontal	-0.57

Table 8: Radiated Emissions 17 – 40 GHz at the Lowest Frequency (worse case)

5.6 §15.407(a)(4) Maximum Power Spectral Density

The maximum average power spectral density conducted from the intentional radiator of the antenna shall not be greater than 23 dBm EIRP in any 1 MHz band during any time interval of continuous transmission. Results of this testing are summarized.

The maximum average power spectral density conducted from the intentional radiator of the antenna shall not be greater than 30 dBm in any 500 kHz band during any time interval of continuous transmission.

As per KDB 662911, When the EUT is using spatial-multiplexing in HE modes, there is not additional array gain to accommodate.

See Section 2.2 of this report for the directional gain calculation.

Results of this testing are summarized.

5.6.1 Low Gain Mode (Indoor Operation)

Nss>1

Modulation (BW)	Freq. (MHz)	Data Rate	TP Setting	Total Sum PSD EIRP (dBm)	Antenna Gain (dBi)	Limit (dBm)	Margin (dBm)
EHT20	5955	Mcs0_Nss4	22	12.30	11	23	-10.7
EHT20	6195	Mcs0_Nss4	20	11.02	11	23	-11.98
EHT20	6415	Mcs0_Nss4	21	11.21	11	23	-11.79
EHT40	5965	Mcs0_Nss4	22	9.67	11	23	-13.33
EHT40	6205	Mcs0_Nss4	21	8.83	11	23	-14.17
EHT40	6405	Mcs0_Nss4	21	8.53	11	23	-14.47
EHT80	5985	Mcs0_Nss4	21	6.33	11	23	-16.67
EHT80	6225	Mcs0_Nss4	21	5.60	11	23	-17.4
EHT80	6385	Mcs0_Nss4	21	5.28	11	23	-17.72
EHT160	6025	Mcs0_Nss4	21	3.32	11	23	-19.68
EHT160	6185	Mcs0_Nss4	20	2.26	11	23	-20.74
EHT160	6325	Mcs0_Nss4	21	2.10	11	23	-20.9
EHT 320	6265	Mcs0_Nss4	21	0.20	11	23	-22.8

Nss=1

Modulation (BW)	Freq. (MHz)	Data Rate	TP Setting	Total Sum PSD EIRP (dBm)	Antenna Gain (dBi)	Limit (dBm)	Margin (dBm)
EHT20	5955	Mcs0_Nss1	14	5.22	11	5.98	-0.76
EHT20	6195	Mcs0_Nss1	14	5.38	11	5.98	-0.6
EHT20	6415	Mcs0_Nss1	15	5.77	11	5.98	-0.21
EHT40	5965	Mcs0_Nss1	17	5.29	11	5.98	-0.69
EHT40	6205	Mcs0_Nss1	17	5.25	11	5.98	-0.73
EHT40	6405	Mcs0_Nss1	18	5.59	11	5.98	-0.39
EHT80	5985	Mcs0_Nss1	20	5.28	11	5.98	-0.7
EHT80	6225	Mcs0_Nss1	21	5.60	11	5.98	-0.38
EHT80	6385	Mcs0_Nss1	21	5.28	11	5.98	-0.7
EHT160	6025	Mcs0_Nss1	21	3.32	11	5.98	-2.66
EHT160	6185	Mcs0_Nss1	20	2.26	11	5.98	-3.72
EHT160	6325	Mcs0_Nss1	21	2.10	11	5.98	-3.88
EHT 320	6265	Mcs0_Nss1	21	0.20	11	5.98	-5.78

RU PSD

Modulation (BW)	Freq. (MHz)	TP Setting	RU PSD Edge EIRP (dBm)	RU PSD Center EIRP (dBm)	Antenna Gain (dBi)	Limit (dBm)	Margin Edge (dBm)	Margin Center (dBm)
EHT20	6195	20	13.73	14.76	11	23	-9.27	-8.24
EHT40	6205	21	10.48	11.26	11	23	-12.52	-11.74
EHT80	6225	21	10.42	11.48	11	23	-12.58	-11.52
EHT160	6185	20	9.58	10.27	11	23	-13.42	-12.73
EHT 320	6265	21	9.74	9.56	11	23	-13.26	-13.44

5.6.2 High Gain Mode

Nss>1

Modulation (BW)	Freq. (MHz)	Data Rate	TP Setting	Total Sum PSD EIRP (dBm)	Antenna Gain (dBi)	Limit (dBm)	Margin (dBm)
EHT20	5955	Mcs0_Nss4	17	7.75	15	23	-15.25
EHT20	6195	Mcs0_Nss4	16	7.07	15	23	-15.93
EHT20	6415	Mcs0_Nss4	16	6.75	15	23	-16.25
EHT40	5965	Mcs0_Nss4	17	5.10	15	23	-17.9
EHT40	6205	Mcs0_Nss4	16	4.08	15	23	-18.92
EHT40	6405	Mcs0_Nss4	17	4.85	15	23	-18.15
EHT80	5985	Mcs0_Nss4	18	2.19	15	23	-20.81
EHT80	6225	Mcs0_Nss4	17	1.83	15	23	-21.17
EHT80	6385	Mcs0_Nss4	17	1.49	15	23	-21.51
EHT160	6025	Mcs0_Nss4	17	-0.52	15	23	-23.52
EHT160	6185	Mcs0_Nss4	16	-1.63	15	23	-24.63
EHT160	6325	Mcs0_Nss4	17	-1.36	15	23	-24.36
EHT 320	6265	Mcs0_Nss4	17	-3.67	15	23	-26.67

Nss=1

Modulation (BW)	Freq. (MHz)	Data Rate	TP Setting	Total Sum PSD EIRP (dBm)	Antenna Gain (dBi)	Limit (dBm)	Margin (dBm)
EHT20	5955	Mcs0_Nss1	17	1.23	15	1.98	-0.75
EHT20	6195	Mcs0_Nss1	16	1.15	15	1.98	-0.83
EHT20	6415	Mcs0_Nss1	16	1.15	15	1.98	-0.83
EHT40	5965	Mcs0_Nss1	17	1.55	15	1.98	-0.43
EHT40	6205	Mcs0_Nss1	16	1.36	15	1.98	-0.62
EHT40	6405	Mcs0_Nss1	17	1.35	15	1.98	-0.63
EHT80	5985	Mcs0_Nss1	18	1.43	15	1.98	-0.55
EHT80	6225	Mcs0_Nss1	17	1.83	15	1.98	-0.15
EHT80	6385	Mcs0_Nss1	17	1.49	15	1.98	-0.49
EHT160	6025	Mcs0_Nss1	17	-0.52	15	1.98	-2.50
EHT160	6185	Mcs0_Nss1	16	-1.63	15	1.98	-3.61
EHT160	6325	Mcs0_Nss1	17	-1.36	15	1.98	-3.34
EHT 320	6265	Mcs0_Nss1	17	-3.67	15	1.98	-5.65

RU PSD

Modulation (BW)	Freq. (MHz)	TP Setting	RU PSD Edge EIRP (dBm)	RU PSD Center EIRP (dBm)	Antenna Gain (dBi)	Limit (dBm)	Margin Edge (dBm)	Margin Center (dBm)
EHT20	6195	16	11.68	12.63	15	23	-11.32	-10.37
EHT40	6205	16	7.44	8.09	15	23	-15.56	-14.91
EHT80	6225	17	8.01	8.94	15	23	-14.99	-14.06
EHT160	6185	16	7.24	8.41	15	23	-15.76	-14.59
EHT 320	6265	17	6.86	6.68	15	23	-16.14	-16.32

Result

The maximum average power spectral density was less than the limit of 23 dBm EIRP; therefore, the EUT complies with the specification.

5.6.3 OFDMA RU Check

If EUT supports OFDMA multiple partial Resource Unit (RU) configurations were verified and the worst case mode was tested.




Figure 4: 6195 20MHz RU Vérification - Center




Figure 5: 6195 20MHz RU Vérification - Edge

Measurement 1

Setting	Instrument Value	Target Value
Start Frequency	6.14500 GHz	6.14500 GHz
Stop Frequency	6.24500 GHz	6.24500 GHz
Span	100.000 MHz	100.000 MHz
RBW	300.000 kHz	~ 300.000 kHz
VBW	1.000 MHz	>= 900.000 kHz
SweepPoints	667	~ 667
SweepTime	1.100 ms	AUTO
Reference Level	10.000 dBm	10.000 dBm
Attenuation	20.000 dB	20.000 dB
Detector	RMS	RMS
SweepCount	100	100
Filter	3 dB	3 dB
Trace Mode	Average Power	Average Power
SweepType	Sweep	Sweep
Preamp	off	off

Table 9: 6195 20MHz RU Vérification

In Band




Figure 6: 6205 40MHz RU Vérification - Center




Figure 7: 6205 40MHz RU Vérification – Edge

Measurement 1

Setting	Instrument Value	Target Value
Start Frequency	6.10500 GHz	6.10500 GHz
Stop Frequency	6.30500 GHz	6.30500 GHz
Span	200.000 MHz	200.000 MHz
RBW	500.000 kHz	~ 500.000 kHz
VBW	2.000 MHz	>= 1.500 MHz
SweepPoints	800	~ 800
SweepTime	1.000 ms	AUTO
Reference Level	10.000 dBm	10.000 dBm
Attenuation	20.000 dB	20.000 dB
Detector	RMS	RMS
SweepCount	100	100
Filter	3 dB	3 dB
Trace Mode	Average Power	Average Power
Sweeptype	Sweep	Sweep
Preamp	off	off

Table 10: 6205 40MHz RU Vérification




Figure 8: 6225 80MHz RU Vérification - Center




Figure 9: 6225 80MHz RU Vérification – Edge

Measurement 1

Setting	Instrument Value	Target Value
Start Frequency	6.02500 GHz	6.02500 GHz
Stop Frequency	6.42500 GHz	6.42500 GHz
Span	400.000 MHz	400.000 MHz
RBW	1.000 MHz	~ 1.000 MHz
VBW	3.000 MHz	>= 3.000 MHz
SweepPoints	800	~ 800
SweepTime	1.000 ms	AUTO
Reference Level	10.000 dBm	10.000 dBm
Attenuation	20.000 dB	20.000 dB
Detector	RMS	RMS
SweepCount	100	100
Filter	3 dB	3 dB
Trace Mode	Average Power	Average Power
SweepType	Sweep	Sweep
Preamp	off	off

Table 11: 6225 80MHz RU Vérification

In Band





Figure 10: 6185 160MHz RU Vérification - Center



**Figure 11: 6185 160MHz RU Vérification - Edge
Measurement 1**

Setting	Instrument Value	Target Value
Start Frequency	5.78500 GHz	5.78500 GHz
Stop Frequency	6.58500 GHz	6.58500 GHz
Span	800.000 MHz	800.000 MHz
RBW	2.000 MHz	~ 2.000 MHz
VBW	10.000 MHz	>= 6.000 MHz
SweepPoints	800	~ 800
SweepTime	1.000 ms	AUTO
Reference Level	0.000 dBm	0.000 dBm
Attenuation	20.000 dB	20.000 dB
Detector	RMS	RMS
SweepCount	100	100
Filter	3 dB	3 dB
Trace Mode	Average Power	Average Power
SweepType	Sweep	Sweep
Preamp	off	off

Table 12: 6185 160MHz RU Vérification




Figure 12: 6265 320MHz RU Vérification - Center




Figure 13: 6265 320MHz RU Vérification - Edge

Measurement 1

Setting	Instrument Value	Target Value
Start Frequency	5.46500 GHz	5.46500 GHz
Stop Frequency	7.06500 GHz	7.06500 GHz
Span	1.600 GHz	1.600 GHz
RBW	5.000 MHz	~ 5.000 MHz
VBW	10.000 MHz	~ 15.000 MHz
SweepPoints	640	~ 640
SweepTime	6.400 ms	AUTO
Reference Level	0.000 dBm	0.000 dBm
Attenuation	20.000 dB	20.000 dB
Detector	RMS	RMS
SweepCount	100	100
Filter	3 dB	3 dB
Trace Mode	Average Power	Average Power
SweepType	Sweep	Sweep
Preamp	off	off

Table 13: 320MHz RU Vérification

-- End of Test Report --