



Compliance Testing, LLC

Previously Flom Test Lab

EMI, EMC, RF Testing Experts Since 1963

toll-free: (866) 311-3268

fax: (480) 926-3598

<http://www.ComplianceTesting.com>

info@ComplianceTesting.com

Test Report

Prepared for: Ubiquiti Networks, Inc

Model: NBE-M5-16

Description: NanoBeam M5 16

Serial Number: N/A

FCC ID: SWX-NBE5M16

To

FCC Part 1.1310

Date of Issue: August 4, 2015

On the behalf of the applicant:

**Ubiquiti Networks, Inc
91 E. Tasman Drive
San Jose, CA 95134**

Attention of:

**Michael Taylor, Compliance Manager
Ph: (408) 942-3085
E-Mail: compliance@ubnt.com**

**Prepared By
Compliance Testing, LLC
1724 S. Nevada Way
Mesa, AZ 85204
(480) 926-3100 phone / (480) 926-3598 fax
www.compliancetesting.com
Project No: p14a0021**

**Alex Macon
Project Test Engineer**

This report may not be reproduced, except in full, without written permission from Compliance Testing
All results contained herein relate only to the sample tested



Test Report Revision History

Revision	Date	Revised By	Reason for Revision
1.0	June 26, 2015	Alex Macon	Original Document



ILAC / A2LA

Compliance Testing, LLC, has been accredited in accordance with the recognized International Standard ISO/IEC 17025:2005. This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (refer joint ISO-ILAC-IAF Communiqué dated January 2009)

The tests results contained within this test report all fall within our scope of accreditation, unless below

Please refer to <http://www.compliancetesting.com/labscope.html> for current scope of accreditation.

Testing Certificate Number: **2152.01**



FCC Site Reg. #349717

IC Site Reg. #2044A-2

Non-accredited tests contained in this report:

N/A

EUT Description

Model: NBE-M5-16

Description: NanoBeam M5 16

Firmware: N/A

Software: N/A

Serial Number: N/A

Additional Information: The EUT is a 2x2 MIMO 802.11n radio



MPE Limit Calculations

Exposure Limit $1\text{mW}/\text{cm}^2$

Source Based Time Averaged Power Calculation

Average Power Calculations

Average Power = Peak Power * duty-cycle%

Tuned Frequency (MHz)	Conducted Peak Output Power (mW)	Duty Cycle (%)	Average Power (mW)
5265	24.0	100	24.0



MPE Evaluation

This is a **fixed/mobile** device used in uncontrolled /general population exposure environment.

Limits Uncontrolled Exposure 47 CFR 1.1310 Table 1, (B)

0.3-1.234 MHz
1.34-30 MHz
30-300 MHz
300-1500 MHz
1500-100,000 MHz

Limit [mW/cm²] = 100
Limit [mW/cm²] = (180/f²)
Limit [mW/cm²] = 0.2
Limit [mW/cm²] = f/1500
Limit [mW/cm²] = 1.0

Test Data

Test Frequency, MHz	5265
Power, Conducted, mW (P)	24.0
Antenna Gain Isotropic	16
Antenna Gain Numeric (G)	39.81
Antenna Type	Point to point
Distance (R)	20

$S = \frac{P * G}{4\pi r^2}$			
Power Density (S) mw/cm ²	Power mW (P)	Numeric Gain (G)	Distance (r ²) cm
0.1900843546	24	39.81	20

Power Density (S) =	0.19
Limit =(from above table) =	1.0



MPE Limit Calculations

Exposure Limit $1\text{mW}/\text{cm}^2$

Source Based Time Averaged Power Calculation

Average Power Calculations

Average Power = Peak Power * duty-cycle%

Tuned Frequency (MHz)	Conducted Peak Output Power (mW)	Duty Cycle (%)	Average Power (mW)
5600	25.1	100	25.1



MPE Evaluation

This is a **fixed/mobile** device used in uncontrolled /general population exposure environment.

Limits Uncontrolled Exposure 47 CFR 1.1310 Table 1, (B)

0.3-1.234 MHz
1.34-30 MHz
30-300 MHz
300-1500 MHz
1500-100,000 MHz

Limit [mW/cm²] = 100
Limit [mW/cm²] = (180/f²)
Limit [mW/cm²] = 0.2
Limit [mW/cm²] = f/1500
Limit [mW/cm²] = 1.0

Test Data

Test Frequency, MHz	5600
Power, Conducted, mW (P)	25.1
Antenna Gain Isotropic	16
Antenna Gain Numeric (G)	39.81
Antenna Type	Point to point
Distance (R)	20

$S = \frac{P * G}{4\pi r^2}$			
Power Density (S) mw/cm ²	Power mW (P)	Numeric Gain (G)	Distance (r ²) cm
0.1987965542	25.1	39.81	20

Power Density (S) =	0.2
Limit =(from above table) =	1.0

END OF TEST REPORT