



11. Radio Frequency Exposure

11.1 Applicable Standards

The measurements shown in this test report were made in accordance with the procedures given in FCC Part 2 (Section 2.1091)
KDB 447498

11.2 EUT Specification

Frequency band (Operating)	☒ WLAN: 2412MHz ~ 2462MHz ☐ WLAN: 5150MHz ~ 5250MHz ☐ WLAN: 5250MHz ~ 5350MHz ☐ WLAN: 5470MHz ~ 5725MHz ☒ WLAN: 5725MHz ~ 5850MHz ☐ Bluetooth: 2402MHz ~ 2480MHz
Device category	☐ Portable (<20cm separation) ☒ Mobile (>20cm separation)
Exposure classification	☐ Occupational/Controlled exposure ($S = 5\text{mW}/\text{cm}^2$) ☒ General Population/Uncontrolled exposure ($S=1\text{mW}/\text{cm}^2$)
Antenna diversity	☐ Single antenna ☒ Multiple antennas ☐ Tx diversity ☐ Rx diversity ☒ Tx/Rx diversity
Evaluation applied	☒ MPE Evaluation* ☐ SAR Evaluation ☐ N/A
Remark: 1. The maximum output power is <u>19.06dBm (80.47mW)</u> at <u>2437MHz</u> (with <u>numeric 18 antenna gain.</u>) 2. DTS device is not subject to routine RF evaluation; MPE estimate is used to justify the compliance. 3. For mobile or fixed location transmitters, no SAR consideration applied. The maximum power density is $1.0\text{ mW}/\text{cm}^2$ even if the calculation indicates that the power density would be larger.	



11.3 Test Results

No non-compliance noted.

11.4 Calculation

$$\text{Given } E = \frac{\sqrt{30 \times P \times G}}{d} \quad \& \quad S = \frac{E^2}{3770}$$

Where E = Field strength in Volts / meter

P = Power in Watts

G = Numeric antenna gain

d = Distance in meters

S = Power density in milliwatts / square centimeter

Combining equations and re-arranging the terms to express the distance as a function of the remaining variables yields:

$$S = \frac{30 \times P \times G}{3770d^2}$$

Changing to units of mW and cm, using:

$P \text{ (mW)} = P \text{ (W)} / 1000$ and

$d \text{ (cm)} = d \text{ (m)} / 100$

Yields

$$S = \frac{30 \times (P / 1000) \times G}{3770 \times (d / 100)^2} = 0.0796 \times \frac{P \times G}{d^2} \quad \text{Equation 1}$$

Where d = Distance in cm

P = Power in mW

G = Numeric antenna gain

S = Power density in mW / cm²



11.5 Maximum Permissible Exposure

P to P

Modulation Type	Frequency band (MHz)	Max. Conducted output power(dBm)	Antenna Gain(dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
11n HT10	2412-2462	19.01	18	28	0.5097	1
11n HT20	2412-2462	15.27	18	28	0.2157	1
11n HT40	2412-2462	10.48	18	28	0.0716	1
11ac VHT10	2422-2452	19.06	18	28	0.5154	1
11ac VHT20	2412-2462	15.29	18	28	0.2167	1
11ac VHT40	2422-2452	10.52	18	28	0.0722	1

P to MP

Modulation Type	Frequency band (MHz)	Max. Conducted output power(dBm)	Antenna Gain(dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
11n HT10	2412-2462	17.61	18	28	0.3695	1
11n HT20	2412-2462	15.27	18	28	0.2157	1
11n HT40	2412-2462	10.48	18	28	0.0716	1
11ac VHT10	2422-2452	17.64	18	28	0.3717	1
11ac VHT20	2412-2462	15.29	18	28	0.2167	1
11ac VHT40	2422-2452	10.52	18	28	0.0722	1