



Compliance Testing, LLC

Previously Flom Test Lab

EMI, EMC, RF Testing Experts Since 1963

toll-free: (866) 311-3268

fax: (480) 926-3598

<http://www.ComplianceTesting.com>

info@ComplianceTesting.com

Test Report

Prepared for: Ubiquiti Networks, Inc

Model: PBE-5AC

Description: PowerBeam 5AC

FCC ID: SWX-PBE5AC

To

FCC Part 1.1310

Date of Issue: June 25, 2015

On the behalf of the applicant:

Ubiquiti Networks, Inc
91 E. Tasman Drive
San Jose, CA 95134

Attention of:

Michael Taylor, Compliance Manager
Ph: (408) 942-3085
E-Mail: compliance@ubnt.com

Prepared By
Compliance Testing, LLC
1724 S. Nevada Way
Mesa, AZ 85204
(480) 926-3100 phone / (480) 926-3598 fax
www.compliancetesting.com
Project No: p14a0019

Greg Corbin
Project Test Engineer

This report may not be reproduced, except in full, without written permission from Compliance Testing
All results contained herein relate only to the sample tested



Test Report Revision History

Revision	Date	Revised By	Reason for Revision
1.0	June 19, 2015	Greg Corbin	Original Document



ILAC / A2LA

Compliance Testing, LLC, has been accredited in accordance with the recognized International Standard ISO/IEC 17025:2005. This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (refer joint ISO-ILAC-IAF Communiqué dated January 2009)

The tests results contained within this test report all fall within our scope of accreditation, unless below

Please refer to <http://www.compliancetesting.com/labscope.html> for current scope of accreditation.

Testing Certificate Number: **2152.01**



FCC Site Reg. #349717

IC Site Reg. #2044A-2

Non-accredited tests contained in this report:

N/A

EUT Description

Model: PBE-5AC

Description: PowerBeam 5AC

Firmware: N/A

Software: N/A

Serial Number: N/A

Additional Information:

The EUT is a 2x2 MIMO 802.11ac radio.



Source Based Time Averaged Power Calculation

Average Power calculations

Average Power = Peak Power * duty-cycle%

Band	Tuned Frequency (MHz)	Peak Conducted Output Power (mW)	Duty Cycle (%)	Average Power (mW)
UNII-2A	5265	128.8	100	128.8
UNII-2C	5600	195.0	100	195.0



MPE Evaluation

This is a **fixed** device used in uncontrolled /general population exposure environment.

Limits Uncontrolled Exposure 47 CFR 1.1310 Table 1, (B)

0.3-1.234 MHz:	Limit [mW/cm ²] = 100
1.34-30 MHz:	Limit [mW/cm ²] = (180/f ²)
30-300 MHz:	Limit [mW/cm ²] = 0.2
300-1500 MHz:	Limit [mW/cm ²] = f/1500
1500-100,000 MHz	Limit [mW/cm ²] = 1.0

UNII-2A Test Data

Test Frequency, MHz	5265
Power, Conducted, mW (P)	128.8
Antenna Gain Isotropic	6
Antenna Gain Numeric (G)	3.98
Antenna Type	Omni
Distance (R)	20

$S = \frac{P * G}{4\pi r^2}$			
Power Density (S) mw/cm ²	Power mW (P)	Numeric Gain (G)	Distance (r ²) cm
0.102	128.8	3.98	20

Power Density (S) = 0.102 mw/cm ²
Limit =(from above table) = 1.0 mw/cm ²

Note: Due to out of band emission limitations the highest EIRP occurs with the 6 dBi Omni antenna. Therefore the power density cannot exceed 0.102 mW/cm²



UNII-2C Test Data

Test Frequency, MHz	5600
Power, Conducted, mW (P)	195.0
Antenna Gain Isotropic	6
Antenna Gain Numeric (G)	3.98
Antenna Type	Omni
Distance (R)	20

$S = \frac{P * G}{4\pi r^2}$			
Power Density (S) mw/cm ²	Power mW (P)	Numeric Gain (G)	Distance (r ²) cm
0.154	195.0	3.98	20

Power Density (S) = 0.154 mw/cm ²
Limit =(from above table) = 1.0 mw/cm ²

Note: Due to out of band emission limitations the highest EIRP occurs with the 6 dBi Omni antenna. Therefore the power density cannot exceed 0.154 mW/cm²

END OF TEST REPORT