



Compliance Testing, LLC

Previously Flom Test Lab

EMI, EMC, RF Testing Experts Since 1963

toll-free: (866) 311-3268

fax: (480) 926-3598

<http://www.ComplianceTesting.com>

info@ComplianceTesting.com

Test Report

Prepared for: Ubiquiti Networks, Inc.

Model: RM5-AC-PTP-Lite

Description: Access Point

Serial Number: N/A

FCC ID: SWX-RM5ACL

To

FCC Part 1.1310

Date of Issue: September 21, 2016

On the behalf of the applicant:

**Ubiquiti Networks, Inc
2580 Orchard Parkway
San Jose, CA 95131**

Attention of:

**Kevin Forbey
Ph: (408) 942-3085
E-mail: kevin.forbey@ubnt.com**

**Prepared By
Compliance Testing, LLC
1724 S. Nevada Way
Mesa, AZ 85204
(480) 926-3100 phone / (480) 926-3598 fax
www.compliancetesting.com
Project No: p1630028**

Poona Saber

This report may not be reproduced, except in full, without written permission from Compliance Testing
All results contained herein relate only to the sample tested



Test Report Revision History

Revision	Date	Revised By	Reason for Revision
1.0	September 21, 2016	Poona Saber	Original Document

ILAC / A2LA

Compliance Testing, LLC, has been accredited in accordance with the recognized International Standard ISO/IEC 17025:2005. This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (refer joint ISO-ILAC-IAF Communiqué dated January 2009)

The tests results contained within this test report all fall within our scope of accreditation, unless below

Please refer to <http://www.compliancetesting.com/labscope.html> for current scope of accreditation.

Testing Certificate Number: **2152.01**



FCC Site Reg. #349717

IC Site Reg. #2044A-2

Non-accredited tests contained in this report:

N/A

EUT Description

Model: RM5-AC-PTP-Lite

Description: Access Point

Firmware: N/A

Software: N/A

S/N: N/A



Source Based Time Averaged Power Calculation

Average Power calculations

Average Power = Peak Power * duty-cycle%

Tuned Frequency (MHz)	Conducted Peak Output Power (mW)	Duty Cycle (%)	Average Power (mW)
5785 (HT-20)	977.2	98.51	962.3
5755 (HT-40)	977.2	94.73	925.2



MPE Evaluation

This is a portable device used in Uncontrolled Exposure environment.

Limits Controlled Exposure 47 CFR 1.1310 Table 1, (A)

0.3-3.0 MHz:	Limit [mW/cm ²] = 100
3.0-30 MHz:	Limit [mW/cm ²] = (900/f ²)
30-300 MHz:	Limit [mW/cm ²] = 1.0
300-1500 MHz:	Limit [mW/cm ²] = f/300
1500-100,000 MHz	Limit [mW/cm ²] = 5

Limits Uncontrolled Exposure 47 CFR 1.1310 Table 1, (B)

0.3-1.234 MHz:	Limit [mW/cm ²] = 100
1.34-30 MHz:	Limit [mW/cm ²] = (180/f ²)
30-300 MHz:	Limit [mW/cm ²] = 0.2
300-1500 MHz:	Limit [mW/cm ²] = f/1500
1500-100,000 MHz	Limit [mW/cm ²] = 1.0

Test Data

Test Frequency, MHz	5785
Power, Conducted, mW (P)	962.3
Antenna Gain Isotropic	34 dBi
Antenna Gain Numeric (G)	2511.8
Antenna Type	Dish
Distance (R)	20 cm

$S = \frac{P * G}{4\pi r^2}$
Power Density (S) mw/cm ²

Power Density (S) = 481.1
Limit =(from above table) = 1



Minimum Safe Distance Evaluation

This is a mobile device used in Uncontrolled Exposure environment.

Limits Controlled Exposure 47 CFR 1.1310 Table 1, (A)

0.3-3.0 MHz:	Limit [mW/cm ²] = 100
3.0-30 MHz:	Limit [mW/cm ²] = (900/f ²)
30-300 MHz:	Limit [mW/cm ²] = 1.0
300-1500 MHz:	Limit [mW/cm ²] = f/300
1500-100,000 MHz	Limit [mW/cm ²] = 5

Limits Uncontrolled Exposure 47 CFR 1.1310 Table 1, (B)

0.3-1.234 MHz:	Limit [mW/cm ²] = 100
1.34-30 MHz:	Limit [mW/cm ²] = (180/f ²)
30-300 MHz:	Limit [mW/cm ²] = 0.2
300-1500 MHz:	Limit [mW/cm ²] = f/1500
1500-100,000 MHz	Limit [mW/cm ²] = 1.0

Test Data

Test Frequency, MHz	5795
Power, Conducted, mW (P)	962.3
Antenna Gain Isotropic	34 dBi
Antenna Gain Numeric (G)	2511.8
Antenna Type	Dish
Limit (L)	1

$R = \sqrt{(PG/4\pi L)}$			
Distance (R) cm	Power mW (P)	Numeric Gain (G)	Limit (L)
438.6	962.3	2511.8	1

END OF TEST REPORT