



Radio Exposure Evaluation Report

FCC ID : SWX-UAPIWHD
Equipment : UniFi HD IN-WALL
Brand Name : UBIQUITI
Model Name : UAP-IW-HD
Applicant / Manufacturer : Ubiquiti Networks, Inc.
685 Third Avenue, 27th Floor New York, New York
10017 USA
Standard : 47 CFR Part 2.1091

The product was received on Oct. 30, 2017, and testing was started from Nov. 07, 2017 and completed on Mar. 24, 2018. We, SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, would like to declare that the tested sample has been evaluated in accordance with the procedures given in 47 CFR Part 2.1091 and shown compliance with the applicable technical standards.

The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any agency of United States government.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, the test report shall not be reproduced except in full.



Approved by: Allen Lin

SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory

No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.)



Table of Contents

HISTORY OF THIS TEST REPORT	3
1 GENERAL DESCRIPTION	4
1.1 EUT General Information	4
1.2 Testing Location	4
1.3 Table for Permissive Change	4
2 MAXIMUM PERMISSIBLE EXPOSURE	5
2.1 Limit of Maximum Permissible Exposure	5
2.2 MPE Calculation Method	5
2.3 Calculated Result and Limit	6
Photographs of EUT V01	

History of this test report

[illegible]

Reviewed by: Sam Tsai

Report Producer: Debby Hung

1 General Description

1.1 EUT General Information

RF General Information			
Evaluation Mode	Frequency Range (MHz)	Operating Frequency (MHz)	Modulation Type
2.4GHz WLAN	2400-2483.5	2412-2462	802.11b: DSSS (DBPSK, DQPSK, CCK) 802.11g/n: OFDM (BPSK, QPSK, 16QAM, 64QAM)
5GHz WLAN	5150-5250 5725-5850	5180-5240 5745-5825	802.11a/n: OFDM (BPSK, QPSK, 16QAM, 64QAM) 802.11ac: OFDM (BPSK, QPSK, 16QAM, 64QAM, 256QAM)
Bluetooth	2400-2483.5	2402-2480	BR / EDR: FHSS (GFSK / $\pi/4$ -DQPSK / 8DPSK) LE: DSSS (GFSK)

1.2 Testing Location

Testing Location			
☒	HWA YA	ADD : No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.)	
		TEL : 886-3-327-3456	FAX : 886-3-327-0973
Test site Designation No. TW1190 with FCC.			
☐	JHUBEI	ADD : No.8, Ln. 724, Bo'ai St., Zhubei City, Hsinchu County, Taiwan (R.O.C.)	
		TEL : 886-3-656-9065	FAX : 886-3-656-9085
Test site Designation No. TW0006 with FCC.			

1.3 Table for Permissive Change

This product is an extension of original one reported under Sporton project number: FA7O2609-03

Below is the table for the change of the product with respect to the original one.

Modifications	Performance Checking
1. Adding DFS bands of operation (5250MHz~5350MHz and 5470MHz~5725MHz) by software. 2. Enable 802.11ac VHT80+VHT80 bandwidth. 3. Enable outdoor operation 4. Enable 5GHz transmit beamforming operation in UNII-2A and UNII-2C by software.	N/A

2 Maximum Permissible Exposure

2.1 Limit of Maximum Permissible Exposure

(A) Limits for Occupational / Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842 / f	4.89 / f	(900 / f ²)*	6
30-300	61.4	0.163	1.0	6
300-1500	-	-	F/300	6
1500-100,000	-	-	5	6

(B) Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f ²)*	30
30-300	27.5	0.073	0.2	30
300-1500	-	-	F/1500	30
1500-100,000	-	-	1.0	30

Note: f = frequency in MHz ; *Plane-wave equivalent power density

2.2 MPE Calculation Method

The MPE was calculated at 20 cm to show compliance with the power density limit.

The following formula was used to calculate the Power Density:

$$E \text{ (V/m)} = \frac{\sqrt{30 \times P \times G}}{d} \quad \text{Power Density: } Pd \text{ (W/m}^2\text{)} = \frac{E^2}{377}$$

E = Electric field (V/m)

P = RF output power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30 \times P \times G}{377 \times d^2}$$

2.3 Calculated Result and Limit

Exposure Environment: General Population / Uncontrolled Exposure

For Bluetooth function:

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	Tolerance (dB)	Tune-up EIRP (dBm)	Tune-up EIRP (W)	Distance (cm)	S (mW/cm ²)	S Limit (mW/cm ²)
2.4G;BT-LE	1.80	7.30	9.10	0.50	9.60	0.00912	20	0.00181	1.00000

For Wi-Fi 2.4G/5GHz function:

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	Tolerance (dB)	T-EIRP (dBm)	T-EIRP (W)	Distance (cm)	S (mW/cm ²)	S Limit (mW/cm ²)	Ratio (S/Limit)
2.4G;D1D	1.80	22.98	24.78	0.50	25.28	0.33729	20	0.06710	1.00000	0.06710
5.2G;D1D	10.02	25.77	35.79	0.50	36.29	4.25598	20	0.84670	1.00000	0.84670
									Sum Ratio	0.91380
									Ratio Limit	1

—————THE END—————