



427 West 12800 South
Draper, UT 84020

Test Report Certification

FCC ID	SWX-UAW
ISED ID	6545A-UAW
Equipment Under Test	U-AirWire
Test Report Serial Number	TR10698_02
Date of Test(s)	5 November; 12, 18 December 2025; 2, 5, 20 January 2026
Report Issue Date	3 February 2026

Test Specification	Applicant
47 CFR FCC Part 15, Subpart E RSS-248, Issue 3 (October 2024)	Ubiquiti Inc. 685 Third Avenue New York, NY 10017 U.S.A.



NVLAP LAB CODE 600241-0

Certification of Engineering Report

This report has been prepared by Unified Compliance Laboratory (UCL) to document compliance of the device described below with the requirement of Federal Communication Commissions (FCC) Part 15, Subpart E and RSS-248, Issue 3 (October 2024). This report may be reproduced in full. Partial reproduction of this report may only be made with the written consent of the laboratory. The results in this report apply only to the sample tested with the specifications provided by the manufacturer.

Applicant	Ubiquiti Inc.
Manufacturer	Ubiquiti Inc.
Brand Name	UBIQUITI
Model Number	U-AirWire
FCC ID	SWX-UAW
ISED ID	6545A-UAW

On this 3rd day of February 2026, I individually and for Unified Compliance Laboratory certify that the statements made in this engineering report are true, complete and correct to the best of my knowledge and are made in good faith. Unified Compliance laboratory is not responsible for incorrect information provided by the manufacturer.

Although NVLAP has accredited the Unified Compliance Laboratory testing facilities, this report must not be used to claim product certification, approval, or endorsement by NVLAP, NIST or any agency of the U.S. federal government.

Unified Compliance Laboratory


Written By: Joseph W. Jackson
Reviewed By: Kimberly DeBole

Revision History		
Revision	Description	Date
01	Original Report Release	3 February 2026
02	Amended Standard Reference in Section 3.3.1 and Corrected Table on Page 2	19 February 2026

Table of Contents

1	Client Information.....	5
1.1	Applicant.....	5
1.2	Manufacturer.....	5
2	Equipment Under Test (EUT).....	6
2.1	Identification of EUT	6
2.2	Description of EUT	6
2.3	EUT and Support Equipment	7
2.4	Interface Ports on EUT	7
2.5	Operating Environment.....	7
2.6	Operating Modes.....	8
2.7	EUT Exercise Software.....	8
2.8	Block Diagram of Test Configuration	8
2.9	Modification Incorporated/Special Accessories on EUT.....	8
2.10	Deviation, Opinions Additional Information or Interpretations from Test Standard.....	8
3	Test Specification, Method and Procedures.....	9
3.1	Test Specification.....	9
3.2	Methods & Procedures.....	9
3.3	FCC Part 15, Subpart E.....	9
3.4	Results.....	9
3.5	Test Location	10
4	Test Equipment	11
4.1	Conducted Emissions at Mains Ports.....	11
4.2	Direct Connect at the Antenna Port Tests.....	11
4.3	Radiated Emissions	12
4.4	Contention Base Protocol Tests	13
4.5	Equipment Calibration	13
4.6	Measurement Uncertainty	14
5	Test Results	15
5.1	§15.203 Antenna Requirements.....	15
5.2	§15.207 Conducted Emissions at Mains Ports Data	16
5.3	§15.407(a) 26 dB Emissions Bandwidth.....	18
5.4	§15.407(a)(3) Maximum Average Output Power	19
5.5	§15.407(b)(7) Spurious Emissions.....	21
5.6	§15.407(a) Maximum Power Spectral Density	24
5.7	§15.407(d) Contention Based Protocol.....	26

1 Client Information

1.1 Applicant

Company	Ubiquiti Inc. 685 Third Avenue New York, NY 10017 U.S.A.
Contact Name	Alex Macon
Title	Compliance

1.2 Manufacturer

Company	Ubiquiti Inc. 685 Third Avenue New York, NY 10017 U.S.A.
Contact Name	Alex Macon
Title	Compliance

2 Equipment Under Test (EUT)

2.1 Identification of EUT

Brand Name	UBIQUITI
Model Number	U-AirWire
Serial Number	25E
Dimensions (cm)	11.7 x 11.7 x 4.3

2.2 Description of EUT

The U-AirWire is a wireless USB adapter which supports WiFi 7. The U-AirWire transmits in the 2.4 GHz, 5 GHz and 6 GHz WiFi frequency bands. The U-AirWire has a rotatable directional 2x2 mountable antenna for optimal wireless performance. The U-AirWire also has a Bluetooth transmitter for system management. The U-AirWire has one main USB-C port for data and power, which powers the U-AirWire, and a second USB-C auxiliary power port.

This device does not support channel puncturing.

For CDD transmission, directional gain is calculated as follows.

Array Gain = $10 \log(\text{NANT}/\text{NSS})$ dB

NANT = number of transmit antennas and NSS = number of spatial streams. NSS = 1 considered worst case. For power measurements on IEEE 802.11 devices, Array Gain = 0 dB for $\text{NANT} \leq 4$;

For PSD measurements when $\text{Nss}=1$: Array Gain = $10 \log(\text{NANT}/\text{NSS})$ dB + Antenna Gain (dBi). Or $3.01 \text{ dB} + 11 \text{ dBi} = 14.01 \text{ dBi}$.

This report covers the circuitry of the device subject to FCC Part 15, Subpart E. The circuitry of the device subject to FCC Part 15 Subpart B was found to be compliant and is covered under a separate Unified Compliance Laboratory test report.

The table below show the channels used within the different modulation bandwidths.

Band	Modulation Bandwidth	Frequency (MHz)	Maximum Power Setting
UNII-7	be (EHT20)	6535, 6555, 6575, 6595, 6615, 6635, 6655, 6675	TP6
		6695, 6715, 6735, 6755, 6775, 6795, 6815, 6835, 6855, 6875	TP5
	be (EHT40)	6525, 6565, 6605, 6645,	TP9
		6685, 6725, 6765, 6805, 6845	TP8
		6885	TP9

	be (EHT80)	6545, 6625	TP12
		6705, 6785, 6865	TP11
	be (EHT160)	6505, 6665, 6825	TP14
	be (EHT320)	6585	TP14

2.3 EUT and Support Equipment

The EUT and support equipment used during the test are listed below.

Brand Name Model Number Serial Number	Description	Name of Interface Ports / Interface Cables
BN: UBIQUITI MN: U-AirWire SN: 25E	Wireless WiFi USB Adapter	See Section 2.4
BN: UBIQUITI MN: GP-M015-QC SN: N/A	USB-C Power Supply	USB-C/1 Meter
BN: Dell MN: XPS 13 SN: N/A	Laptop Personal Computer (For Testing Only)	USB-C/2 meters (Note 2)

Notes: (1) EUT

(2) Interface port connected to EUT (See Section 2.4)

The support equipment listed above was not modified in order to achieve compliance with this standard.

2.4 Interface Ports on EUT

Name of Ports	No. of Ports Fitted to EUT	Cable Description/Length
USB-C Data/Power	1	USB-C/1 Meter
USB-C Auxiliary/Power	1	USB-C/2 Meters

2.5 Operating Environment

Power Supply	120 Vac to USB-C Power
AC Mains Frequency	60 Hz
Temperature	21.1 - 23.4 °C
Humidity	22.8 - 29.9 %
Barometric Pressure	1011 mBar

2.6 Operating Modes

The U-AirWire was tested using test software in order to enable to constant transmission. The measurements within this report are corrected to reference a 100% duty cycle. All emission modes of 802.11be were investigated. All measurements are reported with the worst-case mode (802.11be maximum conducted output power and maximum power spectral density) unless otherwise stated.

2.7 EUT Exercise Software

EUT firmware version 1.0 was used to operate the transmitter using a constant transmit mode.

2.8 Block Diagram of Test Configuration




Diagram 1: Test Configuration Block Diagram

2.9 Modification Incorporated/Special Accessories on EUT

There were no modifications made to the EUT during testing to comply with the specification.

2.10 Deviation, Opinions Additional Information or Interpretations from Test Standard

There were no deviations, opinions, additional information or interpretations from the test specification.

3 Test Specification, Method and Procedures

3.1 Test Specification

Title	47 CFR FCC Part 15, Subpart E, Section 15.407 Limits and methods of measurement of radio interference characteristics of Unlicensed National Information Infrastructure Devices
Purpose of Test	The tests were performed to demonstrate initial compliance

3.2 Methods & Procedures

3.2.1 47 CFR FCC Part 15 Section 15.407

See test standard for details.

3.3 FCC Part 15, Subpart E

3.3.1 Summary of Tests

FCC Section	ISED Section	Environmental Phenomena	Frequency Range (MHZ)	Result
15.203	N/A	Antenna requirements	Structural Requirement	Compliant
15.207	RSS-Gen	Conducted Disturbance at Mains Port	0.15 to 30	Compliant
15.407(a)	RSS-248 §4.4	Bandwidth Requirement	6535 to 6865	Compliant
15.407(a)	RSS-248 §4.5	Peak Output Power ¹	6535 to 6865	Compliant
15.407(b)	RSS-248 §4.6	Antenna Conducted Spurious Emissions ¹	0.009 to 40000	N/A Note ²
15.209	RSS-248 §4.6	Radiated Spurious Emissions	0.009 to 40000	Compliant
15.407(a)	RSS-248 §4.5	Peak Power Spectral Density ¹	6535 to 6865	Compliant
15.407(d)	RSS-248 §4.7	Contention Based Protocol	6535 to 6865	Compliant

The testing was performed according to the procedures in ANSI C63.10-2020/Cor 1-2021, KDB 789033, KDB 987594 and 47 CFR Part 15. Where applicable, KDB 662911 was followed to sum required measurements.

Note ¹: Various RU modes were considered for RF Power, PSD, and Spurious Emissions, and the "single client" RU mode is the worst case - the results herein are "single client" RU mode.

Note ²: Radiated Spurious was performed per 15.209 with the antenna unterminated.

3.4 Results

In the configuration tested, the EUT complied with the requirements of the specification.

3.5 Test Location

Testing was performed at the Unified Compliance Laboratory 3-Meter and 10-Meter chambers located at 427 West 12800 South, Draper, UT 84020. Unified Compliance Laboratory is accredited by National Voluntary Laboratory Accreditation Program (NVLAP); NVLAP Code 600241-0 which is effective until 30 June 2026. This site has also been registered with Innovations, Science and Economic Development (ISED) department as was accepted under Appendix B, Phase 1 procedures of the APEC Tel MRA for Canadian recognition. ISED No.: 25346, effective until 30 June 2026.

Unified Compliance Laboratory has been assigned Registration Number 376708 by the FCC, MRA Designation Number US5037 and Conformity Assessment Number US0223 by ISED.

4 Test Equipment

4.1 Conducted Emissions at Mains Ports

Type of Equipment	Manufacturer	Model Number	Asset Number	Date of Last Calibration	Due Date of Calibration
EMI Receiver	AFJ	FFT3010	UCL-2500	11/18/2025	11/18/2026
LISN	AFJ	LS16C/10	UCL-2512	8/12/2025	8/12/2026
ISN	Teseq	ISN T800	UCL-2971	3/31/2025	3/31/2026
AC Power Source	Laplace Instruments	AC1000A	UCL-2857	N/A	N/A
Test Software	UCL	Revision 1	UCL-3107	N/A	N/A

Table 1: List of equipment used for Conducted Emissions Testing at Mains Port




Figure 1: Conducted Emissions Test

4.2 Direct Connect at the Antenna Port Tests

Type of Equipment	Manufacturer	Model Number	Asset Number	Date of Last Calibration	Due Date of Calibration
Spectrum Analyzer	R&S	FSV40	UCL-2861	1/16/2025	4/16/2026
Signal Generator	R&S	SMB100A	UCL-2864	N/A	N/A
Vector Signal Generator	R&S	SMBV100A	UCL-2873	N/A	N/A
Switch Extension	R&S	OSP-B157WX	UCL-2867	4/28/2025	4/16/2026
Switch Extension	R&S	OSP-150W	UCL-2870	4/28/2025	4/16/2026
Test Software	R&S	EMC32	UCL-9442	--	--

Table 2: List of equipment used for Direct Connect at the Antenna Port




Figure 2: Direct Connect at the Antenna Port Test

4.3 Radiated Emissions

Type of Equipment	Manufacturer	Model Number	Asset Number	Date of Last Calibration	Due Date of Calibration
EMI Receiver	Keysight	N9038A	UCL-2778	12/18/2025	12/18/2026
Pre-Amplifier 9 kHz – 1 GHz	Sonoma Instruments	310N	UCL-2889	7/22/2025	7/22/2026
Broadband Antenna	ETS-Lindgren	3142E	UCL-9782	2/6/2025	2/6/2026
Double Ridge Horn Antenna	Scwarzbeck	BBHA 9120D	UCL-3065	4/2/2025	4/2/2027
Log Periodic	Scwarzbeck	STLP 9129	UCL-3068	2/11/2025	2/4/2027
10 - 40 GHz Horn Antenna	ETS-Lindgren	3116C	UCL-7209	6/6/2024	6/6/2026
1 – 18 GHz Amplifier	Com-Power	PAM 118A	UCL-3833	7/22/2025	7/22/2026
Test Software	Nexio	BatEMC	UCL-5253 & UCL-5249	N/A	N/A

Table 3: List of equipment used for Radiated Emissions




Figure 3: Radiated Emissions Test

4.4 Contention Base Protocol Tests

Type of Equipment	Manufacturer	Model Number	Asset Number	Date of Last Calibration	Due Date of Calibration
Spectrum Analyzer	Keysight	N9010B EXA	UCL-7069	5/20/2025	5/20/2026
Signal Generator	Keysight	MXG-B	UCL-6291	6/28/2024	6/22/2026
MIMO Test Set	Keysight	X8750A	UCL-7372	9/24/2024	10/07/2025

Table 4: List of equipment used for Direct Connect at the Antenna Port




Figure 1. CBP conducted test setup diagram. Source: KDB 987594 D02 V01r01

Figure 4: Contention Base Protocol Test

4.5 Equipment Calibration

All applicable equipment is calibrated using either an independent calibration laboratory or Unified Compliance Laboratory personnel at intervals defined in ANSI C63.4:2014 following outlined calibration procedures. All measurement instrumentation is traceable to the National Institute of Standards and Technology (NIST). Supporting documentation relative to traceability is on file and is available for examination upon request.

4.6 Measurement Uncertainty

Test	Uncertainty ($\pm$ dB)	Confidence (%)
Conducted Emissions	1.44	95
Radiated Emissions (9 kHz to 30 MHz)	2.50	95
Radiated Emissions (30 MHz to 1 GHz)	4.38	95
Radiated Emissions (1 GHz to 18 GHz)	4.37	95
Radiated Emissions (18 GHz to 40 GHz)	3.93	95
Direct Connect Tests	K Factor	Value
Emissions Bandwidth	2	2.0%
Output Power	2	1.0 dB
Peak Power Spectral Density	2	1.3 dB
Band Edge	2	0.8 dB
Transmitter Spurious Emissions	2	1.8 dB

5 Test Results

5.1 §15.203 Antenna Requirements

The EUT uses an integral internal patch antenna. Per the manufacturer, the Maximum gain of the antenna per chain is 11 dBi. This is an 802.11 device and utilizes CDD as described in KDB 662911 D01. The antenna is not user replaceable.


See Section 2.2 for directional gain calculation.

Results

The EUT complied with the specification


5.2 §15.207 Conducted Emissions at Mains Ports Data

5.2.1 Line



ID	Frequency	Probe	Cable	Atten.	Detector	Meter Read	Meas Level	Limit 1	Limit 1 Dist.	Limit 2	Limit 2 Dist.	P/F
MU	MHz	dB	dB	dB	Type	dBμV	dBμV	dBμV	dB	dBμV	dB	P/F
3	153,000kHz	9.49			QPeak	46.94	56.43	65.84	-9.41			
1	279,000kHz	9.48			QPeak	40.23	49.71	60.85	-11.13			
4	348,000kHz	9.48			QPeak	31.52	41.00	59.01	-18.01			
2	282,000kHz	9.48			C_AVG	26.42	35.90			50.76	-14.86	
5	153,000kHz	9.49			C_AVG	30.72	40.21			55.84	-15.63	

5.2.2 Neutral



ID	Frequency	Probe	Cable	Atten.	Detector	Meter Read	Meas Level	Limit 1	Limit 1 Dist.	Limit 2	Limit 2 Dist.	P/F
MU	MHz	dB	dB	dB	Type	dBμV	dBμV	dBμV	dB	dBμV	dB	P/F
1	282,000kHz	9.63			QPeak	42.18	51.81	60.76	-8.95			
4	153,000kHz	9.62			QPeak	47.18	56.80	65.84	-9.04			
3	348,000kHz	9.63			QPeak	33.03	42.66	59.01	-16.35			
2	285,000kHz	9.63			C_AVG	32.19	41.82			50.67	-8.85	
5	150,000kHz	9.62			C_AVG	32.45	42.07			56.00	-13.93	
6	351,000kHz	9.63			C_AVG	20.86	30.49			48.94	-18.45	

Result

The EUT complied with the specification limit.

5.3 §15.407(a) 26 dB Emissions Bandwidth

All chains were measured under the guidance of KDB 789033 Section II.C. and KDB 662911 D01. Please see associated annex for details on instrument settings.

Nominal BW (MHz)	Frequency (MHz)	99% Bandwidth (MHz)	26 dB Bandwidth (MHz)
EHT 20	6535	19.2	22.5
EHT 20	6695	19.2	22.8
EHT 20	6875	19.2	23.1
EHT 40	6525	38.3	42.8
EHT 40	6685	38.3	42.5
EHT 40	6885	38.3	43.8
EHT 80	6545	78.5	84.5
EHT 80	6705	77.5	86.5
EHT 80	6865	77.5	86.5
EHT 160	6505	159.0	167.0
EHT 160	6665	157.0	169.0
EHT 160	6825	157.0	169.0
EHT 320	6585	317.5	347.5

Result

All chains were tested and the highest bandwidth per chain is reported above. For the 320 MHz emissions bandwidth the 99% bandwidth was used. Please see Annex for all bandwidth measurements.

5.4 §15.407(a)(3) Maximum Average Output Power

All chains were measured and summed under the guidance of KDB 789033 Section II. E.2. and KDB 662911 D01. Please see associated annex for details on instrument settings.

See Section 2.2 of this report for the directional gain calculation.

The maximum average RF conducted output power measured for this device was 18.55 dBm or 71.61 mW. The limit is 30 dBm EIRP, or 1 Watt EIRP. The antenna has a gain of 11 dBi.

Nss>1

Modulation (BW)	Frequency (MHz)	Data Rate	TP Setting	Total Summed Output Power* (dBm)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Margin (dBm)
EHT 20	6535	Mcs0_Nss2	6	7.39	11	18.39	30	-11.61
EHT 20	6695	Mcs0_Nss2	5	6.59	11	17.59	30	-12.41
EHT 20	6875	Mcs0_Nss2	5	6.54	11	17.54	30	-12.46
EHT 40	6525	Mcs0_Nss2	9	9.83	11	20.83	30	-9.17
EHT 40	6685	Mcs0_Nss2	8	9.50	11	20.50	30	-9.50
EHT 40	6885	Mcs0_Nss2	9	10.58	11	21.58	30	-8.42
EHT 80	6545	Mcs0_Nss2	12	13.01	11	24.01	30	-5.99
EHT 80	6705	Mcs0_Nss2	11	12.92	11	23.92	30	-6.08
EHT 80	6865	Mcs0_Nss2	11	12.71	11	23.71	30	-6.29
EHT 160	6505	Mcs0_Nss2	14	15.81	11	26.81	30	-3.19
EHT 160	6665	Mcs0_Nss2	14	15.80	11	26.80	30	-3.20
EHT 160	6825	Mcs0_Nss2	14	15.98	11	26.98	30	-3.02
EHT 320	6585	Mcs0_Nss2	17	18.55	11	29.55	30	-0.45

Nss=1

Modulation (BW)	Frequency (MHz)	Data Rate	TP Setting	Total Summed Output Power* (dBm)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Margin (dBm)
EHT 20	6535	Mcs0_Nss1	2	3.84	11	14.84	30	-15.16
EHT 20	6695	Mcs0_Nss1	3	4.22	11	15.22	30	-14.78
EHT 20	6875	Mcs0_Nss1	2	3.63	11	14.63	30	-15.37
EHT 40	6525	Mcs0_Nss1	6	6.96	11	17.96	30	-12.04
EHT 40	6685	Mcs0_Nss1	5	6.44	11	17.44	30	-12.56
EHT 40	6885	Mcs0_Nss1	5	6.48	11	17.48	30	-12.52
EHT 80	6545	Mcs0_Nss1	9	9.68	11	20.68	30	-9.32
EHT 80	6705	Mcs0_Nss1	8	9.72	11	20.72	30	-9.28
EHT 80	6865	Mcs0_Nss1	9	10.49	11	21.49	30	-8.51
EHT 160	6505	Mcs0_Nss1	11	12.68	11	23.68	30	-6.32
EHT 160	6665	Mcs0_Nss1	11	12.61	11	23.61	30	-6.39
EHT 160	6825	Mcs0_Nss1	11	13.00	11	24.00	30	-6.00
EHT 320	6585	Mcs0_Nss1	14	15.69	11	26.69	30	-3.31

Result

In the configuration tested, the maximum average RF outpower was less than 1 watt EIRP; therefore, the EUT complied with the requirements of the specification (see spectrum analyzer plots in attached Annex).

* Gated EIRP shown in the Annex is the conducted measurement.

5.5 §15.407(b)(7) Spurious Emissions

5.5.1 Radiated Spurious Emissions in the Restricted Bands of § 15.205

The EUT uses various power settings based on the channel in use. In order to reduce test time, the radiated spurious emissions at the lowest, middle, and highest channel were measured at the maximum power of TP26.

Correction Factor = Antenna Factor (dBi) + Cable Loss (dB) - Pre-Amplifier Gain (dB), and is added to the Receiver reading.

Result

All emissions in the restricted bands of § 15.205 met the limits specified in § 15.209; therefore, the EUT complies with the specification. See Annex for Conducted Band edge plots.

QuasiPeak

Frequency	Level (dBμV/m)	Limit (dBμV/m)	Margin	Azimuth (°)	Height	Pol.	Correction (dB)
62.86 MHz	27.17	30.0	-2.83	277	3.22	Vertical	-14.01
148.26 MHz	12.23	30.0	-17.77	229	2.93	Vertical	-17.34
149.42 MHz	24.98	30.0	-5.02	261	1.02	Vertical	-17.34
156.84 MHz	23.68	30.0	-6.32	351	1.02	Vertical	-17.02
179.27 MHz	23.58	30.0	-6.42	21	1.11	Vertical	-15.92
63.05 MHz	20.57	30.0	-9.43	22	4	Horizontal	-14.07
149.12 MHz	25.73	30.0	-4.27	346	3.46	Horizontal	-17.34
156.18 MHz	25.07	30.0	-4.93	335	3.95	Horizontal	-17.02

Table 5: Radiated Emissions 30 – 1000 MHz

Peak

Frequency	Level (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Azimuth (°)	Height (m)	Pol.	Correction (dB)
No significant emissions were observed in the vertical orientation of the antenna.							
No significant emissions were observed in the horizontal orientation of the antenna.							

Avg

Frequency	Level (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Azimuth (°)	Height (m)	Pol.	Correction (dB)
No significant emissions were observed in the vertical orientation of the antenna.							
No significant emissions were observed in the horizontal orientation of the antenna.							

Table 6: Radiated Emissions 1 – 17 GHz at the Lowest Frequency

Peak

Frequency	Level (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Azimuth (°)	Height (m)	Pol.	Correction (dB)
14.66 GHz	55.07	74.0	-18.93	296	2.291	Vertical	16.10
No significant emissions were observed in the horizontal orientation of the antenna.							

Avg

Frequency	Level (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Azimuth (°)	Height (m)	Pol.	Correction (dB)
14.66 GHz	36.95	54.0	-17.05	296	2.291	Vertical	16.10
No significant emissions were observed in the horizontal orientation of the antenna.							

Table 7: Radiated Emissions 1 – 17 GHz at the Middle Frequency

Peak

Frequency	Level (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Azimuth (°)	Height (m)	Pol.	Correction (dB)
No significant emissions were observed in the vertical orientation of the antenna.							
No significant emissions were observed in the horizontal orientation of the antenna.							

Avg

Frequency	Level (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Azimuth (°)	Height (m)	Pol.	Correction (dB)
No significant emissions were observed in the vertical orientation of the antenna.							
No significant emissions were observed in the horizontal orientation of the antenna.							

Table 8: Radiated Emissions 1 – 17 GHz at the Highest Frequency

Peak

Frequency	Level (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Azimuth (°)	Pol.	Correction (dB)
16.58 GHz	54.63	74.0	-19.37	352	Vertical	3.32
20.63 GHz	56.17	74.0	-17.83	115	Vertical	0.25
20.72 GHz	55.09	74.0	-18.91	97	Vertical	0.92
27.49 GHz	54.45	74.0	-19.55	112	Vertical	2.59
34.35 GHz	56.37	74.0	-17.63	82	Vertical	3.96
39.61 GHz	59.91	74.0	-14.09	265	Vertical	6.41
16.51 GHz	53.65	74.0	-20.35	358	Horizontal	3.03
20.63 GHz	51.95	74.0	-22.05	136	Horizontal	0.29
27.49 GHz	59.05	74.0	-14.95	2	Horizontal	2.50
35.04 GHz	57.21	74.0	-16.79	203	Horizontal	5.65

Avg

Frequency	Level (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Azimuth (°)	Pol.	Correction (dB)
16.58 GHz	43.11	54.0	-10.89	352	Vertical	3.32
20.63 GHz	42.52	54.0	-11.48	115	Vertical	0.25
20.72 GHz	48.00	54.0	-6.00	97	Vertical	0.92
27.49 GHz	40.54	54.0	-13.46	112	Vertical	2.59
34.35 GHz	41.89	54.0	-12.11	82	Vertical	3.96
39.61 GHz	43.66	54.0	-10.34	265	Vertical	6.41
16.51 GHz	40.09	54.0	-13.91	358	Horizontal	3.03
20.63 GHz	38.35	54.0	-15.65	136	Horizontal	0.29
27.49 GHz	44.40	54.0	-9.60	2	Horizontal	2.50
35.04 GHz	41.33	54.0	-12.67	203	Horizontal	5.65

Table 9: Radiated Emissions 17 – 40 GHz at the Highest Frequency (worse case)

5.6 §15.407(a) Maximum Power Spectral Density

All chains were measured and summed under the guidance of KDB 789033 Section II. F. and KDB 662911 D01. Please see associated annex for details on instrument settings.

The maximum average power spectral density conducted from the intentional radiator of the antenna shall not be greater than 5 dBm EIRP in any 1 MHz band during any time interval of continuous transmission.

See Section 2.2 of this report for the directional gain calculation.

Results of this testing are summarized.

Nss>1

Modulation (BW)	Freq. (MHz)	Data Rate	TP Setting	Total Sum PSD EIRP (dBm)	Antenna Gain (dBi)	Limit (dBm)	Margin (dBm)
EHT 20	6535	Mcs0_Nss2	2	-6.36	11	-6	-0.36
EHT 20	6695	Mcs0_Nss2	3	-6.79	11	-6	-0.79
EHT 20	6875	Mcs0_Nss2	2	-7.06	11	-6	-1.06
EHT 40	6525	Mcs0_Nss2	6	-6.69	11	-6	-0.69
EHT 40	6685	Mcs0_Nss2	5	-6.73	11	-6	-0.73
EHT 40	6885	Mcs0_Nss2	5	-6.04	11	-6	-0.04
EHT 80	6545	Mcs0_Nss2	9	-6.45	11	-6	-0.45
EHT 80	6705	Mcs0_Nss2	8	-6.43	11	-6	-0.43
EHT 80	6865	Mcs0_Nss2	9	-6.87	11	-6	-0.87
EHT 160	6505	Mcs0_Nss2	11	-6.71	11	-6	-0.71
EHT 160	6665	Mcs0_Nss2	11	-6.50	11	-6	-0.50
EHT 160	6825	Mcs0_Nss2	11	-6.34	11	-6	-0.34
EHT 320	6585	Mcs0_Nss2	14	-6.54	11	-6	-0.54

Nss=1

Modulation (BW)	Freq. (MHz)	Data Rate	TP Setting	Total Sum PSD EIRP (dBm)	Antenna Gain (dBi)	Limit (dBm)	Margin (dBm)
EHT 20	6535	Mcs0_Nss1	2	-9.99	11	-9.01	-0.98
EHT 20	6695	Mcs0_Nss1	3	-9.17	11	-9.01	-0.16
EHT 20	6875	Mcs0_Nss1	2	-9.85	11	-9.01	-0.84
EHT 40	6525	Mcs0_Nss1	6	-9.54	11	-9.01	-0.53
EHT 40	6685	Mcs0_Nss1	5	-9.82	11	-9.01	-0.81
EHT 40	6885	Mcs0_Nss1	5	-10.00	11	-9.01	-0.99
EHT 80	6545	Mcs0_Nss1	9	-9.60	11	-9.01	-0.59
EHT 80	6705	Mcs0_Nss1	8	-9.57	11	-9.01	-0.56
EHT 80	6865	Mcs0_Nss1	9	-9.04	11	-9.01	-0.03
EHT 160	6505	Mcs0_Nss1	11	-9.74	11	-9.01	-0.73
EHT 160	6665	Mcs0_Nss1	11	-9.49	11	-9.01	-0.48
EHT 160	6825	Mcs0_Nss1	11	-9.36	11	-9.01	-0.35
EHT 320	6585	Mcs0_Nss1	14	-9.43	11	-9.01	-0.42

Result

The maximum average power spectral density was less than the limit of 5 dBm EIRP; therefore, the EUT complies with the specification.

5.7 §15.407(d) Contention Based Protocol

This product was tested and found to be compliant with the requirements of Contention-based Protocol as specified in FCC Part 15.407 and KDB 987594 D02.


Initially the test setup was connected directly to the signal source with all splitters (splitters terminated with a 50-ohm loads on unused ports) and cables in place to verify the AWGN signal is 10MHz wide at a signal level of less than or equal to -62dBm and for conducted measurements the threshold was adjusted for an antenna gain of 11 dBi. The level at the signal generator required to achieve the required signal level at the DUT was recorded for use during testing.

The DUT was connected as shown in figure 4 above and set to transmit at a constant duty cycle at each frequency and bandwidth noted in the table below and verified to be communicating with the companion device as intended.


Starting at the levels established above, the AWGN signal was introduced to the DUT and increased to determine a threshold level at where the DUT will terminate with at least a 90% detection rate. The level at the DUT, which the 90% detection rate was achieved was recorded as the “Sensitivity Level” below.

Any measurement below the sensitivity level will result in the Tx minimal and any further measurement below the sensitivity level will result in Tx on.


Testing shall be repeated at each applicable channel and bandwidth as noted in Table 1 of KDB 987594 D02.




Plot 1: AWGN Signal BW/Power Details




Plot 2: AWGN Signal Detection 20MHz




Plot 3: EUT 160MHz Bandwidth




Plot 4: EUT 160MHz Bandwidth Reduction




Plot 5: AWGN Signal Detection 160MHz




Plot 6: AWGN Signal Detection 160MHz




Plot 7: AWGN Signal Detection 160MHz




Plot 8: EUT 320MHz Bandwidth




Plot 9: EUT 320MHz Bandwidth Reduction



Plot 10: AWGN Signal Detection 320MHz



Plot 11: AWGN Signal Detection 320MHz



Plot 12: AWGN Signal Detection 320MHz

Contention Based Protocol 987594 D02 U-NNI 6 GHz EMC Measurement

Band	BW _{EUT} (MHz)	F _{c1}	F _{c2}	AWGN Power (dBm)	Adjusted Power (dBm)	Limit (dBm)	Margin (dB)	Detection >90%
UNII-5 5.925 - 6.425GHz	20	6135	6135	-42	-53.082	-52	-1.082	Pass
	160	6185	6110	-42	-53.082	-52	-1.082	Pass
			6185	-53	-64.082	-52	-12.082	Pass
			6260	-42	-53.082	-52	-1.082	Pass
	320	6265	6110	-48	-59.082	-52	-7.082	Pass
			6265	-55	-66.082	-52	-14.082	Pass
			6410	-53	-64.082	-52	-12.082	Pass
UNII-6 6.425 - 6.525GHz	20	6455	6455	-49	-60.082	-52	-8.082	Pass
	160	6505	6430	-51	-62.082	-52	-10.082	Pass
			6505	-51	-62.082	-52	-10.082	Pass
			6580	-53	-64.082	-52	-12.082	Pass
UNII-7 6.525 - 6.875GHz	20	6695	6695	-55	-66.082	-52	-14.082	Pass
	160	6665	6595	-55	-66.082	-52	-14.082	Pass
			6665	-48	-59.082	-52	-7.082	Pass
			6740	-41	-52.082	-52	-0.082	Pass
	320	6745	6590	-48	-59.082	-52	-7.082	Pass
			6745	-45	-56.082	-52	-4.082	Pass
UNII-8 6.875 - 7.125GHz	160	6985	6890	-45	-56.082	-52	-4.082	Pass
			6910	-53	-64.082	-52	-12.082	Pass
			6985	-53	-64.082	-52	-12.082	Pass
	20	7015	7015	-55	-66.082	-52	-14.082	Pass
UNII-8 6.875 - 7.125GHz	160	6985	6910	-53	-64.082	-52	-12.082	Pass
			6985	-53	-64.082	-52	-12.082	Pass
			7060	-53	-64.082	-52	-12.082	Pass

Min. Antenna Gain (dBi)	10	Ports	Path Loss (dBm)	AWGN Clock
Max Threshold Level (TL)	-52	FJ3,FJ4	-11.082	23

Table 10: Trial Table

CBP Path Loss is – 11.082 dB

Detection Level = Injected AWGN Power (dBm) – Antenna Gain (dBi) + Path Loss (dB)

Result

The EUT complies with the specification.

-- End of Test Report --

