


FCC C2PC Test Report

FCC ID : SWX-UDR
Equipment : UniFi Dream Router
Model No. : UDR
Brand Name : UBIQUITI
Applicant : Ubiquiti Inc.
Address : 685 Third Avenue, (27th Floor) New York, New York 10017 USA
Standard : 47 CFR FCC Part 15.247
Received Date : Jun. 08, 2021
Tested Date : Oct. 08, 2021

We, International Certification Corporation, would like to declare that the tested sample has been evaluated and in compliance with the requirement of the above standards. The test results contained in this report refer exclusively to the product. It may be duplicated completely for legal use with the approval of the applicant. It shall not be reproduced except in full without the written approval of our laboratory.

Reviewed by:



Along Chen / Assistant Manager

Approved by:



Gary Chang / Manager



Table of Contents

1	GENERAL DESCRIPTION	5
1.1	Information.....	5
1.2	Local Support Equipment List	7
1.3	Test Setup Chart	7
1.4	The Equipment List	8
1.5	Test Standards	9
1.6	Reference Guidance	9
1.7	Deviation from Test Standard and Measurement Procedure.....	9
1.8	Measurement Uncertainty	9
2	TEST CONFIGURATION	10
2.1	Testing Facility.....	10
2.2	The Worst Test Modes and Channel Details	10
3	TRANSMITTER TEST RESULTS.....	11
3.1	Conducted Emissions.....	11
3.2	Unwanted Emissions into Restricted Frequency Bands	14
4	TEST LABORATORY INFORMATION	18

Release Record

Report No.	Version	Description	Issued Date
FR160801-02AC	Rev. 01	Initial issue	Nov. 11, 2021

Summary of Test Results

FCC Rules	Test Items	Measured	Result
15.207	Conducted Emissions	[dBuV]: 0.564MHz 42.99(Margin -3.01dB) - AV	Pass
15.247(d) 15.209	Radiated Emissions	[dBuV/m at 3m]: 36.79MHz 36.95 (Margin -3.05dB) – QP [dBuV/m at 3m]: 45.52MHz 36.95 (Margin -3.05dB) - QP	Pass

Declaration of Conformity:

The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

Comments and Explanations:

The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

1 General Description

1.1 Information

This is a Class II Permissive Change report (C2PC).

This report is issued as a supplementary report to original ICC report no. FR160801AC. The difference is concerned with following item:

- ✧ LCM spi clk pin R8421 change to 33 ohm
- ✧ LED DIN pin R8408 change to 47 ohm
- ✧ Vendor of power transformer is changed.
- ✧ Conductive fabric is added on RJ45 port

Conducted Emissions & Radiated emission below 1GHz tests have been performed and are recorded in the following sections.

1.1.1 Specification of the Equipment under Test (EUT)

RF General Information					
Frequency Range (MHz)	IEEE Std. 802.11	Ch. Freq. (MHz)	Channel Number	Transmit Chains (N _{TX})	Data Rate / MCS
2400-2483.5	b	2412-2462	1-11 [11]	4	1-11 Mbps
2400-2483.5	g	2412-2462	1-11 [11]	4	6-54 Mbps
2400-2483.5	n (HT20)	2412-2462	1-11 [11]	4	MCS 0-31
2400-2483.5	n (HT40)	2422-2452	3-9 [7]	4	MCS 0-31
Note 1: RF output power specifies that Maximum Conducted (Average) Output Power. Note 2: 802.11b uses a combination of DSSS-DBPSK, DQPSK, CCK modulation. Note 3: 802.11g/n uses a combination of OFDM-BPSK, QPSK, 16QAM, 64QAM modulation.					

1.1.2 Antenna Details

Ant. No.	Brand	Model	Type	Connector	Gain (dBi)
1	UBIQUITI	ANT 0	Short-circuited Monopole	I-PEX	3.4
2	UBIQUITI	ANT 1	Short-circuited Monopole	I-PEX	3.4
3	UBIQUITI	ANT 2	Short-circuited Monopole	I-PEX	3.4
4	UBIQUITI	ANT 3	Short-circuited Monopole	I-PEX	3.4

1.1.3 Power Supply Type of Equipment under Test (EUT)

Power Supply Type	100-240V~1.1A Max, 50/60Hz
--------------------------	----------------------------

1.1.4 Accessories

Accessories		
No.	Equipment	Description
1	Power cord	2m, non-shielded without core


1.1.5 Channel List

Frequency band (MHz)		2400~2483.5	
802.11 b / g / n HT20		802.11n HT40	
Channel	Frequency(MHz)	Channel	Frequency(MHz)
1	2412	3	2422
2	2417	4	2427
3	2422	5	2432
4	2427	6	2437
5	2432	7	2442
6	2437	8	2447
7	2442	9	2452
8	2447	---	---
9	2452	---	---
10	2457	---	---
11	2462	---	---

1.2 Local Support Equipment List

Support Equipment List					
No.	Equipment	Brand	Model	FCC ID	Remarks
1	RJ45	ICC	RJ45-10m	---	---
2	RJ45	ICC	RJ45-10m	---	---
3	RJ45	ICC	RJ45-1m	---	---
4	RJ45	ICC	RJ45-1m	---	---
5	RJ45	ICC	RJ45-1m	---	---
6	RJ45 Load	ICC	--	---	---
7	Notebook	DELL	Latitude 5400	DoC	---
8	Notebook	DELL	Latitude E5470	DoC	---

1.3 Test Setup Chart



1.4 The Equipment List

Test Item	Conducted Emission				
Test Site	Conduction room 1 / (CO01-WS)				
Test Date	Oct. 08, 2021				
Instrument	Brand	Model No.	Serial No.	Calibration Date	Calibration Until
Receiver	R&S	ESR3	101658	Feb. 08, 2021	Feb. 07, 2022
LISN	R&S	ENV216	101579	Mar. 17, 2021	Mar. 16, 2022
LISN (Support Unit)	SCHWARZBECK	Schwarzbeck 8127	8127-666	Dec. 29, 2020	Dec. 28, 2021
RF Cable-CON	Woken	CFD200-NL	CFD200-NL-001	Oct. 21, 2020	Oct. 20, 2021
50 ohm terminal (Support Unit)	NA	50	04	May 25, 2021	May 24, 2022
Measurement Software	AUDIX	e3	6.120210k	NA	NA
Note: Calibration Interval of instruments listed above is one year.					

Test Item	Radiated Emission below 1GHz				
Test Site	966 chamber1 / (03CH01-WS)				
Test Date	Oct. 08, 2021				
Instrument	Brand	Model No.	Serial No.	Calibration Date	Calibration Until
Receiver	R&S	ESR3	101657	Mar. 12, 2021	Mar. 11, 2022
Loop Antenna	R&S	HFH2-Z2	100330	Nov. 17, 2020	Nov. 16, 2021
Bilog Antenna	SCHWARZBECK	VULB9168	VULB9168-522	Jun. 30, 2021	Jun. 29, 2022
Preamplifier	EMC	EMC02325	980225	Jun. 29, 2021	Jun. 28, 2022
Loop Antenna Cable	KOAX KABEL	101354-BW	101354-BW	Oct. 05, 2021	Oct. 04, 2022
LF cable 3M	Woken	CFD400NL-LW	CFD400NL-001	Oct. 05, 2021	Oct. 04, 2022
LF cable 11M	EMC	EMCCFD400-NW-N W-11000	200801	Oct. 05, 2021	Oct. 04, 2022
LF cable 1M	EMC	EMCCFD400-NM-N M-1000	160502	Oct. 05, 2021	Oct. 04, 2022
Measurement Software	AUDIX	e3	6.120210g	NA	NA
Note: Calibration Interval of instruments listed above is one year.					

1.5 Test Standards

47 CFR FCC Part 15.247

ANSI C63.10-2013

1.6 Reference Guidance

FCC KDB 558074 D01 15.247 Meas Guidance v05r02

FCC KDB 662911 D01 Multiple Transmitter Output v02r01

1.7 Deviation from Test Standard and Measurement Procedure

None

1.8 Measurement Uncertainty

The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor ($k=2$)).

Measurement Uncertainty	
Parameters	Uncertainty
AC conducted emission	± 2.92 dB
Radiated emission ≤ 1 GHz	± 3.41 dB

2 Test Configuration

2.1 Testing Facility

Test Laboratory	International Certification Corporation
Test Site	CO01-WS, 03CH01-WS
Address of Test Site	No.3-1, Lane 6, Wen San 3rd St., Kwei Shan Dist., Tao Yuan City 33381, Taiwan (R.O.C.)

- FCC Designation No.: TW2732
- FCC site registration No.: 181692
- ISSED#: 10807A
- CAB identifier: TW2732

2.2 The Worst Test Modes and Channel Details

Test item	Modulation Mode	Test Frequency (MHz)	Data Rate	Test Configuration
Conducted Emissions	11b	2462	1 Mbps	---
Radiated Emissions ≤ 1 GHz	11b	2462	1 Mbps	---

3 Transmitter Test Results

3.1 Conducted Emissions

3.1.1 Limit of Conducted Emissions


Conducted Emissions Limit		
Frequency Emission (MHz)	Quasi-Peak	Average
0.15-0.5	66 - 56 *	56 - 46 *
0.5-5	56	46
5-30	60	50

Note 1: * Decreases with the logarithm of the frequency.

3.1.2 Test Procedures


1. The device is placed on a test table, raised 80 cm above the reference ground plane. The vertical conducting plane is located 40 cm to the rear of the device.
2. The device is connected to line impedance stabilization network (LISN) and other accessories are connected to other LISN. Measured levels of AC power line conducted emission are across the 50 Ω LISN port.
3. AC conducted emission measurements is made over frequency range from 150 kHz to 30 MHz.
4. This measurement was performed with AC 120V / 60Hz.


3.1.3 Test Setup



- Note: 1. Support units were connected to second LISN.
2. Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes

3.1.4 Test Result of Conducted Emissions

Modulation	11b	Test Freq. (MHz)	2462																																																																																																																					
Power Phase	Line																																																																																																																							
Test by : Joe Liao Temperature: 22°C Humidity: 68%																																																																																																																								
Level (dBUV)  Frequency (MHz) <table><thead><tr><th></th><th>Freq MHz</th><th>Level dBUV</th><th>Limit Line dBUV</th><th>Over Limit dB</th><th>Read Level dBUV</th><th>Factor dB</th><th>Cable loss dB</th><th>Remark</th></tr></thead><tbody><tr><td>1</td><td>0.393</td><td>37.33</td><td>47.99</td><td>-10.66</td><td>27.61</td><td>9.64</td><td>0.08</td><td>Average</td></tr><tr><td>2</td><td>0.393</td><td>42.20</td><td>57.99</td><td>-15.79</td><td>32.48</td><td>9.64</td><td>0.08</td><td>QP</td></tr><tr><td>3</td><td>0.502</td><td>42.45</td><td>46.00</td><td>-3.55</td><td>32.72</td><td>9.64</td><td>0.09</td><td>Average</td></tr><tr><td>4</td><td>0.502</td><td>44.40</td><td>56.00</td><td>-11.60</td><td>34.67</td><td>9.64</td><td>0.09</td><td>QP</td></tr><tr><td>5*</td><td>0.564</td><td>42.99</td><td>46.00</td><td>-3.01</td><td>33.25</td><td>9.64</td><td>0.10</td><td>Average</td></tr><tr><td>6</td><td>0.564</td><td>47.39</td><td>56.00</td><td>-8.61</td><td>37.65</td><td>9.64</td><td>0.10</td><td>QP</td></tr><tr><td>7</td><td>1.552</td><td>33.95</td><td>46.00</td><td>-12.05</td><td>24.13</td><td>9.66</td><td>0.16</td><td>Average</td></tr><tr><td>8</td><td>1.552</td><td>39.94</td><td>56.00</td><td>-16.06</td><td>30.12</td><td>9.66</td><td>0.16</td><td>QP</td></tr><tr><td>9</td><td>2.334</td><td>37.10</td><td>46.00</td><td>-8.90</td><td>27.24</td><td>9.66</td><td>0.20</td><td>Average</td></tr><tr><td>10</td><td>2.334</td><td>39.57</td><td>56.00</td><td>-16.43</td><td>29.71</td><td>9.66</td><td>0.20</td><td>QP</td></tr><tr><td>11</td><td>2.721</td><td>32.92</td><td>46.00</td><td>-13.08</td><td>23.03</td><td>9.66</td><td>0.23</td><td>Average</td></tr><tr><td>12</td><td>2.721</td><td>36.57</td><td>56.00</td><td>-19.43</td><td>26.68</td><td>9.66</td><td>0.23</td><td>QP</td></tr></tbody></table>					Freq MHz	Level dBUV	Limit Line dBUV	Over Limit dB	Read Level dBUV	Factor dB	Cable loss dB	Remark	1	0.393	37.33	47.99	-10.66	27.61	9.64	0.08	Average	2	0.393	42.20	57.99	-15.79	32.48	9.64	0.08	QP	3	0.502	42.45	46.00	-3.55	32.72	9.64	0.09	Average	4	0.502	44.40	56.00	-11.60	34.67	9.64	0.09	QP	5*	0.564	42.99	46.00	-3.01	33.25	9.64	0.10	Average	6	0.564	47.39	56.00	-8.61	37.65	9.64	0.10	QP	7	1.552	33.95	46.00	-12.05	24.13	9.66	0.16	Average	8	1.552	39.94	56.00	-16.06	30.12	9.66	0.16	QP	9	2.334	37.10	46.00	-8.90	27.24	9.66	0.20	Average	10	2.334	39.57	56.00	-16.43	29.71	9.66	0.20	QP	11	2.721	32.92	46.00	-13.08	23.03	9.66	0.23	Average	12	2.721	36.57	56.00	-19.43	26.68	9.66	0.23	QP
	Freq MHz	Level dBUV	Limit Line dBUV	Over Limit dB	Read Level dBUV	Factor dB	Cable loss dB	Remark																																																																																																																
1	0.393	37.33	47.99	-10.66	27.61	9.64	0.08	Average																																																																																																																
2	0.393	42.20	57.99	-15.79	32.48	9.64	0.08	QP																																																																																																																
3	0.502	42.45	46.00	-3.55	32.72	9.64	0.09	Average																																																																																																																
4	0.502	44.40	56.00	-11.60	34.67	9.64	0.09	QP																																																																																																																
5*	0.564	42.99	46.00	-3.01	33.25	9.64	0.10	Average																																																																																																																
6	0.564	47.39	56.00	-8.61	37.65	9.64	0.10	QP																																																																																																																
7	1.552	33.95	46.00	-12.05	24.13	9.66	0.16	Average																																																																																																																
8	1.552	39.94	56.00	-16.06	30.12	9.66	0.16	QP																																																																																																																
9	2.334	37.10	46.00	-8.90	27.24	9.66	0.20	Average																																																																																																																
10	2.334	39.57	56.00	-16.43	29.71	9.66	0.20	QP																																																																																																																
11	2.721	32.92	46.00	-13.08	23.03	9.66	0.23	Average																																																																																																																
12	2.721	36.57	56.00	-19.43	26.68	9.66	0.23	QP																																																																																																																
Note 1: Level (dBUV) = Read Level (dBUV) + LISN Factor (dB) + Cable Loss (dB). 2: Over Limit (dB) = Level (dBUV) – Limit Line (dBUV).																																																																																																																								

Modulation	11b	Test Freq. (MHz)	2462																																																																																																																																							
Power Phase	Neutral																																																																																																																																									
Test by : Joe Liao Temperature: 22°C Humidity: 68%																																																																																																																																										
Level (dBuV)  Frequency (MHz) <table><thead><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Over</th><th>Read</th><th>Factor</th><th>Cable</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV</th><th>Line</th><th>Limit</th><th>Level</th><th>dB</th><th>loss</th><th>Remark</th></tr><tr><th></th><th></th><th></th><th>dBuV</th><th>dB</th><th>dBuV</th><th></th><th>dB</th><th></th></tr></thead><tbody><tr><td>1</td><td>0.393</td><td>38.90</td><td>47.99</td><td>-9.09</td><td>29.15</td><td>9.67</td><td>0.08</td><td>Average</td></tr><tr><td>2</td><td>0.393</td><td>43.39</td><td>57.99</td><td>-14.60</td><td>33.64</td><td>9.67</td><td>0.08</td><td>QP</td></tr><tr><td>3</td><td>0.518</td><td>41.67</td><td>46.00</td><td>-4.33</td><td>31.91</td><td>9.67</td><td>0.09</td><td>Average</td></tr><tr><td>4</td><td>0.518</td><td>45.44</td><td>56.00</td><td>-10.56</td><td>35.68</td><td>9.67</td><td>0.09</td><td>QP</td></tr><tr><td>5*</td><td>0.567</td><td>42.66</td><td>46.00</td><td>-3.34</td><td>32.89</td><td>9.67</td><td>0.10</td><td>Average</td></tr><tr><td>6</td><td>0.567</td><td>46.00</td><td>56.00</td><td>-10.00</td><td>36.23</td><td>9.67</td><td>0.10</td><td>QP</td></tr><tr><td>7</td><td>1.560</td><td>39.90</td><td>46.00</td><td>-6.10</td><td>30.05</td><td>9.69</td><td>0.16</td><td>Average</td></tr><tr><td>8</td><td>1.560</td><td>41.60</td><td>56.00</td><td>-14.40</td><td>31.75</td><td>9.69</td><td>0.16</td><td>QP</td></tr><tr><td>9</td><td>1.949</td><td>39.87</td><td>46.00</td><td>-6.13</td><td>30.00</td><td>9.69</td><td>0.18</td><td>Average</td></tr><tr><td>10</td><td>1.949</td><td>41.15</td><td>56.00</td><td>-14.85</td><td>31.28</td><td>9.69</td><td>0.18</td><td>QP</td></tr><tr><td>11</td><td>2.334</td><td>31.73</td><td>46.00</td><td>-14.27</td><td>21.84</td><td>9.69</td><td>0.20</td><td>Average</td></tr><tr><td>12</td><td>2.334</td><td>36.81</td><td>56.00</td><td>-19.19</td><td>26.92</td><td>9.69</td><td>0.20</td><td>QP</td></tr></tbody></table>					Freq	Level	Limit	Over	Read	Factor	Cable			MHz	dBuV	Line	Limit	Level	dB	loss	Remark				dBuV	dB	dBuV		dB		1	0.393	38.90	47.99	-9.09	29.15	9.67	0.08	Average	2	0.393	43.39	57.99	-14.60	33.64	9.67	0.08	QP	3	0.518	41.67	46.00	-4.33	31.91	9.67	0.09	Average	4	0.518	45.44	56.00	-10.56	35.68	9.67	0.09	QP	5*	0.567	42.66	46.00	-3.34	32.89	9.67	0.10	Average	6	0.567	46.00	56.00	-10.00	36.23	9.67	0.10	QP	7	1.560	39.90	46.00	-6.10	30.05	9.69	0.16	Average	8	1.560	41.60	56.00	-14.40	31.75	9.69	0.16	QP	9	1.949	39.87	46.00	-6.13	30.00	9.69	0.18	Average	10	1.949	41.15	56.00	-14.85	31.28	9.69	0.18	QP	11	2.334	31.73	46.00	-14.27	21.84	9.69	0.20	Average	12	2.334	36.81	56.00	-19.19	26.92	9.69	0.20	QP
	Freq	Level	Limit	Over	Read	Factor	Cable																																																																																																																																			
	MHz	dBuV	Line	Limit	Level	dB	loss	Remark																																																																																																																																		
			dBuV	dB	dBuV		dB																																																																																																																																			
1	0.393	38.90	47.99	-9.09	29.15	9.67	0.08	Average																																																																																																																																		
2	0.393	43.39	57.99	-14.60	33.64	9.67	0.08	QP																																																																																																																																		
3	0.518	41.67	46.00	-4.33	31.91	9.67	0.09	Average																																																																																																																																		
4	0.518	45.44	56.00	-10.56	35.68	9.67	0.09	QP																																																																																																																																		
5*	0.567	42.66	46.00	-3.34	32.89	9.67	0.10	Average																																																																																																																																		
6	0.567	46.00	56.00	-10.00	36.23	9.67	0.10	QP																																																																																																																																		
7	1.560	39.90	46.00	-6.10	30.05	9.69	0.16	Average																																																																																																																																		
8	1.560	41.60	56.00	-14.40	31.75	9.69	0.16	QP																																																																																																																																		
9	1.949	39.87	46.00	-6.13	30.00	9.69	0.18	Average																																																																																																																																		
10	1.949	41.15	56.00	-14.85	31.28	9.69	0.18	QP																																																																																																																																		
11	2.334	31.73	46.00	-14.27	21.84	9.69	0.20	Average																																																																																																																																		
12	2.334	36.81	56.00	-19.19	26.92	9.69	0.20	QP																																																																																																																																		
Note 1: Level (dBuV) = Read Level (dBuV) + LISN Factor (dB) + Cable Loss (dB). 2: Over Limit (dB) = Level (dBuV) – Limit Line (dBuV).																																																																																																																																										

3.2 Unwanted Emissions into Restricted Frequency Bands

3.2.1 Limit of Unwanted Emissions into Restricted Frequency Bands

Restricted Band Emissions Limit			
Frequency Range (MHz)	Field Strength (uV/m)	Field Strength (dBuV/m)	Measure Distance (m)
0.009~0.490	2400/F(kHz)	48.5 - 13.8	300
0.490~1.705	24000/F(kHz)	33.8 - 23	30
1.705~30.0	30	29	30
30~88	100	40	3
88~216	150	43.5	3
216~960	200	46	3
Above 960	500	54	3

Note 1:
Qusai-Peak value is measured for frequency below 1GHz except for 9–90 kHz, 110–490 kHz frequency band. Peak and average value are measured for frequency above 1GHz. The limit on average radio frequency emission is as above table. The limit on peak radio frequency emissions is 20 dB above the maximum permitted average emission limit

Note 2:
Measurements may be performed at a distance other than what is specified provided. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor as below, Frequency at or above 30 MHz: 20 dB/decade Frequency below 30 MHz: 40 dB/decade.

3.2.2 Test Procedures


1. Measurement is made at a semi-anechoic chamber that incorporates a turntable allowing a EUT rotation of 360°. A continuously-rotating, remotely-controlled turntable is installed at the test site to support the EUT and facilitate determination of the direction of maximum radiation for each EUT emission frequency. The EUT is placed at test table. For emissions testing at or below 1 GHz, the table height is 80 cm above the reference ground plane. For emission measurements above 1 GHz, the table height is 1.5 m
2. Measurement is made with the antenna positioned in both the horizontal and vertical planes of polarization. The measurement antenna is varied in height (1m ~ 4m) above the reference ground plane to obtain the maximum signal strength. Distance between EUT and antenna is 3 m.
3. This investigation is performed with the EUT rotated 360°, the antenna height scanned between 1 m and 4 m, and the antenna rotated to repeat the measurements for both the horizontal and vertical antenna polarizations.

Note:


1. 120kHz measurement bandwidth of test receiver and Quasi-peak detector is for radiated emission below 1GHz.
2. RBW=1MHz, VBW=3MHz and Peak detector is for peak measured value of radiated emission above 1GHz.
3. RBW=1MHz, VBW=1/T and Peak detector is for average measured value of radiated emission above 1GHz.

3.2.3 Test Setup

Radiated Emissions below 1 GHz



Radiated Emissions above 1 GHz



3.2.4 Transmitter Radiated Unwanted Emissions (Below 1GHz)

Modulation	11b	Test Freq. (MHz)	2462
Polarization	Horizontal		
Test By :Akun Chung Temperature(°C):24 Humidity(%):67			
Level (dBUV/m) <			

Modulation	11b	Test Freq. (MHz)	2462
Polarization	Vertical		
Test By :Akun Chung Temperature(°C):24 Humidity(%):67			
Level (dBuV/m) </			

4 Test laboratory information

Established in 2012, ICC provides foremost EMC & RF Testing and advisory consultation services by our skilled engineers and technicians. Our services employ a wide variety of advanced edge test equipment and one of the widest certification extents in the business.

International Certification Corporation (EMC and Wireless Communication Laboratory), it is our definitive objective is to institute long term, trust-based associations with our clients. The expectation we set up with our clients is based on outstanding service, practical expertise and devotion to a certified value structure. Our passion is to grant our clients with best EMC / RF services by oriented knowledgeable and accommodating staff.

Our Test sites are located at Linkou District and Kwei Shan District. Location map can be found on our website <http://www.icertifi.com.tw>.

Linkou

Tel: 886-2-2601-1640

No.30-2, Ding Fwu Tsuen, Lin Kou
District, New Taipei City, Taiwan
(R.O.C.)

Kwei Shan

Tel: 886-3-271-8666

No.3-1, Lane 6, Wen San 3rd
St., Kwei Shan Dist., Tao Yuan
City 33381, Taiwan (R.O.C.)
No.2-1, Lane 6, Wen San 3rd
St., Kwei Shan Dist., Tao Yuan
City 33381, Taiwan (R.O.C.)

Kwei Shan Site II

Tel: 886-3-271-8640

No.14-1, Lane 19, Wen San 3rd
St., Kwei Shan Dist., Tao Yuan
City 333, Taiwan (R.O.C.)

If you have any suggestion, please feel free to contact us as below information.

Tel: 886-3-271-8666

Fax: 886-3-318-0345

Email: ICC_Service@icertifi.com.tw

==END==