

Phone G3 Touch Pro



Mechanical

Dimensions	165 x 140 x 185 mm (6.5 x 5.5 x 7.3")
Weight	1 kg (2.2 lb)
Enclosure materials	Enclosure: plastic Base: aluminum

Display

Display size	127 mm (5") diagonal
Resolution	720 x 1280 HD (16:9)
Screen technology	GFF multi-touch

Video

Camera sensor	5 MP
Resolution	2592 x 1944

Audio

Handset dynamic receiver	32 ohm Sensitivity: 121dB/10mW at BK4195
Handset microphone	Omnidirectional electret microphone SNR 70 dB Sensitivity -38 ± 3 dB
Codec	WCD9326: Standalone Hi-Fi audio codec IC WSA8815: Smart speaker amplifier
Hands-free speaker	Mono, 4 ohm Nominal power: 2W Max. power: 3W SPL 80 dB at 1W, 0.5 m
Hands-free microphone	Dual omnidirectional MEMS microphones SNR 64 dB Sensitivity -26 dBFS Digital microphone

Hardware

Processor	Octa-Core ARM® Cortex® A53, 1.8 GHz
Memory	Storage: 32 GB RAM: 2 GB
WiFi standards	802.11 a/b/g/n/ac
Power input	PoE+
Connectivity	(1) GbE RJ45 port Bluetooth® 4.2 WiFi 2.4 GHz b/g/n, 20/40 MHz WiFi 5 GHz a/n/ac, 20/40/80 MHz, Slave DFS
Headset support	3.5 mm (0.14") Audio Jack
Operating temperature	0 to 40° C (32 to 104° F)



Operating humidity	10 to 90% noncondensing
Certifications	FCC, IC, CE

Software

LED	Glowing white: power status
Audio DSP algorithm	Active echo cancellation, noise suppression, blind source separation
Protocol	SIP/SDP/RTP/RTCP/VLAN/DHCP
Number of supported phone lines	Multiple
UniFi OS application	UniFi Talk
Minimum software requirements	Web browser (Chrome™ recommended)

FCC/IC - Required Statement:
https://dl.ui.com/compliance/FCC_IC_required_statement_2023-01-10.pdf



Specifications are subject to change. Ubiquiti products are sold with a limited warranty described at www.ui.com/support/warranty

©2023 Ubiquiti Inc. All rights reserved. Ubiquiti, the Ubiquiti U logo, UniFi, UniFi Talk and UniFi Protect are trademarks or registered trademarks of Ubiquiti, Inc. in the United States and in other countries. All other trademarks are the property of their respective owners.