FCC RADIO TEST REPORT

Applicant	:	Ubiquiti Inc.
Address	:	685 Third Avenue, 27th Floor New York, New York 10017, USA
Equipment	:	UNAS Pro 4
Model No.	:	UNAS-Pro-4
Trade Name	:	UBIQUITI
FCC ID	:	SWX-UNASP4

I HEREBY CERTIFY THAT :

The sample was received on Sep. 06, 2025 and the testing was completed on Sep. 12, 2025 at Cerpass Technology Corp. The test result refers exclusively to the test presented test model / sample. Without written approval of Cerpass Technology Corp., the test report shall not be reproduced except in full.

Approved by:

Mark Liao / Supervisor

Laboratory Accreditation:

Cerpass Technology Corporation Test Laboratory

CONTENTS

1. Summary of Test Procedure and Test Results 5
1.1 Applicable Standards 5
2. Test Configuration of Equipment under Test 6
2.1 Feature of Equipment under Test 6
2.2 Carrier Frequency of Channels 6
2.3 Test Mode and Test Software 7
2.4 Description of Test System 8
2.5 General Information of Test 9
2.6 Measurement Uncertainty 9
3. Test Equipment and Ancillaries Used for Tests 10
4. Antenna Requirements 11
4.1 Standard Applicable 11
4.2 Antenna Construction and Directional Gain 11
5. Test of AC Power Line Conducted Emission 12
5.1 Test Limit 12
5.2 Test Procedures 12
5.3 Typical Test Setup 13
5.4 Test Result and Data 14
5.5 Test Photographs 16
6. Test of Spurious Emission (Radiated) 17
6.1 Test Limit 17
6.2 Test Procedures 18
6.3 Typical Test Setup 19
6.4 Test Result and Data (9kHz ~ 30MHz) 21
6.5 Test Result and Data (30MHz ~ 1GHz) 21
6.6 Test Result and Data (1GHz ~ 25GHz) 23
6.7 Restricted Bands of Operation 29
6.8 Test Photographs (30MHz ~ 1GHz) 30
6.9 Test Photographs (1GHz ~ 25GHz) 31
7. Test of Spurious Emission (Conducted) 33
7.1 Test Limit 33
7.2 Test Procedure 33
7.3 Test Setup Layout 33
7.4 Test Result and Data 33
8. On Time, Duty Cycle and Measurement methods 36
8.1 Test Limit 36
8.2 Test Procedure 36
8.3 Test Setup Layout 36
8.4 Test Result and Data 36
9. 6dB Bandwidth Measurement Data 38
9.1 Test Limit 38

9.2 Test Procedures 38
9.3 Test Setup Layout 38
9.4 Test Result and Data 38
10. Maximum Average Output Power 40
10.1 Test Limit 40
10.2 Test Procedures 40
10.3 Test Setup Layout 40
10.4 Test Result and Data 41
11. Power Spectral Density 43
11.1 Test Limit 43
11.2 Test Procedures 43
11.3 Test Setup Layout 43
11.4 Test Result and Data 43

History of this test report

Report No.	Issued Date	Description
25090087-TRFCC01	Sep. 30, 2025	Original

1. Summary of Test Procedure and Test Results

1.1 Applicable Standards

ANSI C63.10-2020+Cor.1-2023+C63.10a-2024+Errata to C63.10a-2024

FCC Rules and Regulations Part 15 Subpart C §15.247

FCC Rule	. Description of Test	Result
15.203	. Antenna Requirement	PASS
15.207	. AC Power Line Conducted Emission	PASS
15.209 15.205	. Radiated Spurious Emission	PASS
15.247(d)	. Conducted Spurious Emission	PASS
15.247(a)(2)	. 6dB Bandwidth	PASS
15.247(b)	. Maximum Output Power	PASS
15.247(e)	. Power Spectral Density	PASS

*The lab has reduced the uncertainty risk factor from test equipment, environment and staff technicians which according to the standard on contract. Therefore, the test result will only be determined by standard requirement,measurement uncertainty evaluation is not considered.

*This EUT has been also tested and compiled with the requirement of FCC Part 15, Subpart B, recorded in a separate test report(25090087-TEFV01).

2. Test Configuration of Equipment under Test

2.1 Feature of Equipment under Test

Operation Frequency Range	2400-2483.5MHz
Center Frequency Range	2402-2480MHz
Modulation Type	GFSK
Modulation Technology	DTS
Data Rate	1Mbps
Antenna Type	Dipole Antenna
Antenna Gain	-2 dBi
Firmware Number	V0.0.2
Serial Number	2532AZ A89C6C02B37D

Note: For more details, please refer to the User's manual of the EUT.

2.2 Carrier Frequency of Channels

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
***00**	**2402**	14	2430	28	2458
01	2404	15	2432	29	2460
02	2406	16	2434	30	2462
03	2408	17	2436	31	2464
04	2410	18	2438	32	2466
05	2412	***19**	**2440**	33	2468
06	2414	20	2442	34	2470
07	2416	21	2444	35	2472
08	2418	22	2446	36	2474
09	2420	23	2448	37	2476
10	2422	24	2450	38	2478
11	2424	25	2452	***39**	**2480**
12	2426	26	2454	--	--
13	2428	27	2456	--	--

Note: Channels remarked * are selected to perform test.

2.3 Test Mode and Test Software

a. During testing, the interface cables and equipment positions were varied according to ANSI C63.10.
b. The complete test system included Notebook and EUT for RF test.
c. An executive program, ”hcitool -i hci0 command” under Windows OS system was executed to transmit and receive data via Bluetooth.
d. The following test modes were performed for the test:

Conducted Emissions from the AC mains power ports	
Test Mode	Operating Description
1	GFSK(1Mbps), TX Mode, From PoE (AC 120V/60Hz)
2	GFSK(1Mbps), TX Mode, From PoE (AC 240V/60Hz)
caused “Test Mode 1” generated the worst case, it was reported as the final data.	
Radiation Emissions (30MHz ~ 1GHz)	
Test Mode	Operating Description
1	GFSK(1Mbps), TX Mode, From PoE (AC 120V/60Hz)
2	GFSK(1Mbps), TX Mode, From PoE (AC 240V/60Hz)
caused “Test Mode 2” generated the worst case, it was reported as the final data.	
Radiation Emissions (1GHz ~ 25GHz)	
Test Mode	Operating Description
1	GFSK(1Mbps), TX Mode, From PoE (AC 120V/60Hz)
2	GFSK(1Mbps), TX Mode, From PoE (AC 240V/60Hz)
caused “Test Mode 1” generated the worst case, it was reported as the final data.	

The EUT incorporates a MIMO function

Modulation Type	TX CONFIGURATION
GFSK (1Mbps)	1TX

2.4 Description of Test System

RF Conducted				
Equipment	Brand	Model	Length/Type	Power cord/Length/Type
Notebook	DELL	Latitude 7490	N/A	Adapter / 1.8m / NS
RJ45 Cable	N/A	N/A	1.2m / NS	N/A
Radiated Emissions				
Equipment	Brand	Model	Length/Type	Power cord/Length/Type
Notebook	DELL	Latitude E5270	N/A	Adapter / 1.8m / NS
RJ45 Cable	TE CONNECTIVITY	CAT5E	1.2m / NS	N/A
Power Cord	KING-CORD	KC-003	1m / NS	N/A
AC Power Line Conducted Emission				
Equipment	Brand	Model	Length/Type	Power cord/Length/Type
Notebook	DELL	Latitude E5270	N/A	Adapter / 1.8m / NS
RJ45 Cable	TE CONNECTIVITY	CAT5E	1.2m / NS	N/A
Power Cord	KING-CORD	KC-003	1m / NS	N/A

2.5 General Information of Test

Organization	Cerpass Technology Corp.	
☒ Test Site	Cerpass Technology Corporation Test Laboratory Address: No.10, Ln. 2, Lianfu St., Luzhu Dist., Taoyuan City 33848, Taiwan (R.O.C.) Tel: +886-3-3226-888 Fax: +886-3-3226-881	
	FCC	TW1439, TW1079
	IC	4934E-1, 4934E-2
Frequency Range Investigated	Conducted: from 150kHz to 30 MHz Radiation: from 30 MHz to 25,000MHz	
Test Distance	The test distance of radiated emission from antenna to EUT is 3 M.	

Test Item	Test Site	Test Period	Environmental Conditions	Tested By
RF Conducted	RFCON01-NK	2025/09/11	25℃/51%	Leon Huang
RF Conducted	RFCON01-NK	2025/09/12	25.3℃/48%	Leon Huang
Radiated Emissions	3M02-NK	2025/09/09	18.6℃/ 67%	Leon Huang
AC Power Line Conducted Emission	CON02-NK	2025/09/09	25.5℃/ 58%	Leon Huang

2.6 Measurement Uncertainty

ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor (k=2)

Measurement Item	Uncertainty
AC Power Line Conduction(150K~30MHz)	±3.2dB
Radiated Spurious Emission(9KHz~30MHz)	±3.5dB
Radiated Spurious Emission(30MHz~1GHz)	±5.1dB
Radiated Spurious Emission(1GHz~40GHz)	±5.2dB
Conducted Spurious Emission	±2.1dB
6dB Bandwidth	±5.4%
20dB Bandwidth	±4.4%
Occupied Bandwidth	±4.5%
Peak Output Power(Conducted Power Meter)	±1.1dB
Dwell Time / Deactivation Time	±7.6%
Power Spectral Density	±2.0dB
Duty Cycle	±3.5%

3. Test Equipment and Ancillaries Used for Tests

Test Item	Radiated Emissions				
Test Site	Semi Anechoic Room(3M02-NK)				
Instrument	Manufacturer	Model No	Serial No	Calibration Date	Valid Date
Bilog Antenna	Schwarzbeck	VULB9168	VULB 9168-369	2025/02/17	2026/02/16
Active Loop Antenna	Schwarzbeck	FMZB 1513	00414	2025/02/18	2026/02/17
Horn Anrenna	EMCO	3116	31974	2025/02/20	2026/02/19
Horn Antenna	EMCO	3115	31589	2025/02/20	2026/02/19
Spectrum Analyzer 44GHz	ROHDE & SCHWARZ	FSV3044	101744	2025/04/23	2026/04/22
EMI Receiver	ROHDE & SCHWARZ	ESR 7	101906	2025/05/19	2026/05/18
Preamplifier	Agilent	8449B	3008A01954	2025/02/12	2026/02/11
Preamplifier	EMC INSTRUMENTS	EMC184045	980065	2024/10/15	2025/10/14
Preamplifier	EM Electronics corp.	EM330	60659	2024/12/16	2025/12/15
Cable-4m(9k-3G)	EMEC	RG-223	18274M	2025/07/02	2026/07/01
Cable-3in1(30M-1G)	HARBOUR INDUSTRIES	LL142	CCE1315	2025/02/21	2026/02/20
Cable-0.5m(1G-40G)	HUBER SUHNER	SUCOFLEX 104	805443/4	2025/02/26	2026/02/25
Cable-3m(1G-40G)	HUBER SUHNER	SUCOFLEX 104	805796/4	2025/02/26	2026/02/25
Cable-8m(1G-26.5G)	WOKEN	WCBA-WCA203SM	CCE1374	2025/02/26	2026/02/25
Cable-3m(10M-40G)	HUBER SUHNER	SF102	804619/2	2024/10/14	2025/10/13
Cable-1m(10M-40G)	HUBER SUHNER	SF102	804398/2	2024/10/14	2025/10/13
Highpass Filter	Warison	WFIL-H7500-18000F	WRQ4BFWC2J1	2025/02/21	2026/02/20
Notch Filter	Warison	WFIL-N5925-7125F-04	WRQ4BFWC4M1	2025/02/11	2026/02/10
Highpass Filter	WOKEN	WFIL-H3000-18000F-03	WR377WC2B1	2024/10/15	2025/10/14
E3	AUDIX	v8.2014-8-6	RK-000529	NA	NA

Test Item	RF Conducted				
Test Site	RFCON02-NK				
Instrument	Manufacturer	Model No	Serial No	Calibration Date	Valid Date
CAX Signal Analyzer	KEYSIGHT	N9000B	MY57100339	2024/10/23	2025/10/22
Power Meter	Anritsu	ML2495A	1224005	2025/02/12	2026/02/11
Power Sensor	Anritsu	MA2411B	1207295	2025/02/12	2026/02/11
Attenuator	KEYSIGHT	8491B	MY39250703	2025/02/12	2026/02/11

Test Item	AC Power Line Conducted Emission				
Test Site	CON02-NK				
Instrument	Manufacturer	Model No	Serial No	Calibration Date	Valid Date
EMI Receiver	ROHDE & SCHWARZ	ESR 7	101906	2025/05/19	2026/05/18
Cable-4m(9k-3G)	EMEC	RG-223	18274M	2025/07/02	2026/07/01
Two-Line V-Network	Schwarzbeck	ENV216	101584	2025/02/26	2026/02/25
Line Impedance Stabilization Network	Schwarzbeck	NSLK 8127	01197	2025/02/26	2026/02/25
E3	AUDIX	v8.2014-8-6	RK-000531	NA	NA

4. Antenna Requirements

4.1 Standard Applicable

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

4.2 Antenna Construction and Directional Gain

Antenna Type	Dipole Antenna
Antenna Gain	-2 dBi

5. Test of AC Power Line Conducted Emission

5.1 Test Limit

Conducted Emissions were measured from 150 kHz to 30 MHz with a bandwidth of 9 KHz, according to the methods defined in ANSI C63.10-2020+Cor.1-2023 and ANSI C63.10a-2024. The EUT was placed on a nonmetallic stand in a shielded room 0.8 meters above the ground plane. The interface cables and equipment positioning were varied within limits of reasonable applications to determine the position produced maximum conducted emissions.

Frequency (MHz)	Quasi Peak (dB μ V)	Average (dB μ V)
0.15 – 0.5	66-56*	56-46*
0.5 – 5.0	56	46
5.0 – 30.0	60	50

*Decreases with the logarithm of the frequency.

5.2 Test Procedures

a. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
b. Connect EUT to the power mains through a line impedance stabilization network (LISN).
c. All the support units are connecting to the other LISN.
d. The LISN provides 50 ohm coupling impedance for the measuring instrument.
e. The FCC states that a 50 ohm, 50 micro-Henry LISN should be used.
f. Both sides of AC line were checked for maximum conducted interference.
g. The frequency range from 150 kHz to 30 MHz was searched.
h. Set the test-receiver system to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

5.3 Typical Test Setup



5.4 Test Result and Data

Test Mode : BLE 1TX CH00 1Mbps
Voltage : AC 120V/60Hz
Phase : Line



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F
1	0.2222	9.53	15.54	25.07	52.74	-27.67	Average	P
2	0.2222	9.53	37.85	47.38	62.74	-15.36	QP	P
3	0.2387	9.54	20.76	30.30	52.14	-21.84	Average	P
4	0.2387	9.54	40.40	49.94	62.14	-12.20	QP	P
5	0.2558	9.54	28.69	38.23	51.57	-13.34	Average	P
6	0.2558	9.54	42.29	51.83	61.57	-9.74	QP	P
7	0.6445	9.57	15.87	25.44	46.00	-20.56	Average	P
8	0.6445	9.57	31.75	41.32	56.00	-14.68	QP	P
9	0.7852	9.57	21.30	30.87	46.00	-15.13	Average	P
10	0.7852	9.57	33.29	42.86	56.00	-13.14	QP	P
11	16.8226	9.98	20.70	30.68	50.00	-19.32	Average	P
12	16.8226	9.98	27.75	37.73	60.00	-22.27	QP	P

Note: Level=Reading+Factor
Margin=Level-Limit
Factor=(LISN or ISN or Current Probe)Factor + Cable Loss

Test Mode : BLE 1TX CH00 1Mbps
Voltage : AC 120V/60Hz
Phase : Neutral



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F
1	0.2015	9.55	17.36	26.91	53.55	-26.64	Average	P
2	0.2015	9.55	29.99	39.54	63.55	-24.01	QP	P
3	0.2502	9.56	17.47	27.03	51.75	-24.72	Average	P
4	0.2502	9.56	36.83	46.39	61.75	-15.36	QP	P
5	0.2971	9.57	12.91	22.48	50.32	-27.84	Average	P
6	0.2971	9.57	27.86	37.43	60.32	-22.89	QP	P
7	0.6369	9.62	15.43	25.05	46.00	-20.95	Average	P
8	0.6369	9.62	32.61	42.23	56.00	-13.77	QP	P
9	0.7848	9.62	22.18	31.80	46.00	-14.20	Average	P
10	0.7848	9.62	34.77	44.39	56.00	-11.61	QP	P
11	16.7181	10.11	18.20	28.31	50.00	-21.69	Average	P
12	16.7181	10.11	25.82	35.93	60.00	-24.07	QP	P

Note: Level=Reading+Factor
Margin=Level-Limit
Factor=(LISN or ISN or Current Probe)Factor + Cable Loss

6. Test of Spurious Emission (Radiated)

6.1 Test Limit

In any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. If the transmitter measurement is based on the maximum conducted output power, the attenuation required under this paragraph shall be 30dB instead of 20dB. In addition, radiated emissions which fall in section 15.205(a) the restricted bands must also comply with the radiated emission limit specified in section 15.209(a).

Frequency (MHz)	Field Strength (microvolt/meter)	Measurement Distance (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

6.2 Test Procedures

a. The EUT was placed on a rotatable table top 0.8 meter above ground.
b. The EUT was set 3 meters from the interference receiving antenna which was mounted on the top of a variable height antenna tower.
c. The table was rotated 360 degrees to determine the position of the highest radiation.
d. The antenna is a broadband antenna and its height is varied between one meter and four meters above ground to find the maximum value of the field strength both horizontal polarization and vertical polarization of the antenna are set to make the measurement.
e. For each suspected emission the EUT was arranged to its worst case and then tune the antenna tower (from 1 M to 4 M) and turn table (from 0 degree to 360 degrees) to find the maximum reading.
f. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function and specified bandwidth with Maximum Hold Mode.
g. If the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method and reported.
h. For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than average limit (that means the emission level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
i. “Cone of radiation” has been considered to be 3dB bandwidth of the measurement antenna.

Note:

1.The supporting fixture shall permit orientation of the EUT in each of three orthogonal axis positions such that emissions from the EUT are maximized.
(Z-AXIS is the worst.)

2.Due to the test software function limit the operation band setting(200dBuV/m).
There's no corresponding limitation in the actual test item.

6.3 Typical Test Setup

Below 30MHz test setup



30MHz- 1GHz Test Setup



Above 1GHz Test Setup



6.4 Test Result and Data (9kHz ~ 30MHz)

The 9kHz - 30MHz spurious emission is under limit 20dB more.

6.5 Test Result and Data (30MHz ~ 1GHz)

Test Mode : BLE 1TX CH00 1Mbps
Voltage : AC 240V/60Hz
Pol : Vertical



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	30.00	-10.28	41.75	31.47	40.00	-8.53	Peak	400	0	P
2	57.16	-9.45	33.95	24.50	40.00	-15.50	Peak	400	0	P
3	72.68	-12.77	37.72	24.95	40.00	-15.05	Peak	400	0	P
4	119.24	-12.62	45.29	32.67	43.50	-10.83	Peak	400	0	P
5	466.50	-3.59	32.67	29.08	46.00	-16.92	Peak	400	0	P
6	701.24	1.20	29.52	30.72	46.00	-15.28	Peak	400	0	P

Note: Level=Reading+Factor
Margin=Level-Limit
Factor=Antenna Factor + cable loss - Amplifier Factor

Test Mode : BLE 1TX CH00 1Mbps
Voltage : AC 240V/60Hz
Pol : Horizontal



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	30.00	-10.28	37.87	27.59	40.00	-12.41	Peak	400	0	P
2	64.92	-10.64	34.54	23.90	40.00	-16.10	Peak	400	0	P
3	90.14	-15.89	41.95	26.06	43.50	-17.44	Peak	400	0	P
4	105.66	-13.63	39.79	26.16	43.50	-17.34	Peak	400	0	P
5	125.06	-12.02	34.89	22.87	43.50	-20.63	Peak	400	0	P
6	466.50	-3.59	33.30	29.71	46.00	-16.29	Peak	400	0	P

Note: Level=Reading+Factor
Margin=Level-Limit
Factor=Antenna Factor + cable loss - Amplifier Factor

6.6 Test Result and Data (1GHz ~ 25GHz)

Test Mode : BLE 1TX CH00 1Mbps
Voltage : AC 120V/60Hz
Pol : Vertical



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	2390.00	-4.52	41.12	36.60	54.00	-17.40	Average	100	8	P
2	2390.00	-4.52	53.44	48.92	74.00	-25.08	Peak	100	8	P
3	2402.00	-4.65	93.44	88.79	200.00	-111.21	Average	100	8	P
4	2402.00	-4.65	94.56	89.91	200.00	-110.09	Peak	100	8	P
5	4804.00	6.59	29.67	36.26	54.00	-17.74	Average	100	123	P
6	4804.00	6.59	41.77	48.36	74.00	-25.64	Peak	100	123	P

Note: Level=Reading+Factor
Margin=Level-Limit
Factor=Antenna Factor + cable loss - Amplifier Factor

Test Mode : BLE 1TX CH00 1Mbps
Voltage : AC 120V/60Hz
Pol : Horizontal



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	2390.00	-4.52	41.14	36.62	54.00	-17.38	Average	100	54	P
2	2390.00	-4.52	53.75	49.23	74.00	-24.77	Peak	100	54	P
3	2402.00	-4.65	93.93	89.28	200.00	-110.72	Average	100	54	P
4	2402.00	-4.65	95.09	90.44	200.00	-109.56	Peak	100	54	P
5	4804.00	6.59	29.45	36.04	54.00	-17.96	Average	100	131	P
6	4804.00	6.59	41.50	48.09	74.00	-25.91	Peak	100	131	P

Note: Level=Reading+Factor
Margin=Level-Limit
Factor=Antenna Factor + cable loss - Amplifier Factor

Test Mode : BLE 1TX CH19 1Mbps
Voltage : AC 120V/60Hz
Pol : Vertical



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	2390.00	-4.52	41.08	36.56	54.00	-17.44	Average	100	25	P
2	2390.00	-4.52	53.45	48.93	74.00	-25.07	Peak	100	25	P
3	2440.00	-4.75	93.85	89.10	200.00	-110.90	Average	100	25	P
4	2440.00	-4.75	94.62	89.87	200.00	-110.13	Peak	100	25	P
5	2483.50	-4.75	41.33	36.58	54.00	-17.42	Average	100	25	P
6	2483.50	-4.75	53.22	48.47	74.00	-25.53	Peak	100	25	P
7	4880.00	6.86	29.94	36.80	54.00	-17.20	Average	100	115	P
8	4880.00	6.86	41.76	48.62	74.00	-25.38	Peak	100	115	P
9	7320.00	13.02	32.95	45.97	54.00	-8.03	Average	100	62	P
10	7320.00	13.02	43.94	56.96	74.00	-17.04	Peak	100	62	P

Note: Level=Reading+Factor
Margin=Level-Limit
Factor=Antenna Factor + cable loss - Amplifier Factor

Test Mode : BLE 1TX CH19 1Mbps
Voltage : AC 120V/60Hz
Pol : Horizontal



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	2390.00	-4.52	41.03	36.51	54.00	-17.49	Average	219	311	P
2	2390.00	-4.52	53.31	48.79	74.00	-25.21	Peak	219	311	P
3	2440.00	-4.75	86.91	82.16	200.00	-117.84	Average	219	311	P
4	2440.00	-4.75	87.94	83.19	200.00	-116.81	Peak	219	311	P
5	2483.50	-4.75	41.22	36.47	54.00	-17.53	Average	219	311	P
6	2483.50	-4.75	53.81	49.06	74.00	-24.94	Peak	219	311	P
7	4880.00	6.86	29.41	36.27	54.00	-17.73	Average	100	199	P
8	4880.00	6.86	41.96	48.82	74.00	-25.18	Peak	100	199	P
9	7320.00	13.02	33.15	46.17	54.00	-7.83	Average	100	52	P
10	7320.00	13.02	43.94	56.96	74.00	-17.04	Peak	100	52	P

Note: Level=Reading+Factor
Margin=Level-Limit
Factor=Antenna Factor + cable loss - Amplifier Factor

Test Mode : BLE 1TX CH39 1Mbps
Voltage : AC 120V/60Hz
Pol : Vertical



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	2480.00	-4.74	93.19	88.45	200.00	-111.55	Average	100	27	P
2	2480.00	-4.74	93.71	88.97	200.00	-111.03	Peak	100	27	P
3	2483.50	-4.75	41.10	36.35	54.00	-17.65	Average	100	27	P
4	2483.50	-4.75	53.76	49.01	74.00	-24.99	Peak	100	27	P
5	4960.00	7.21	28.34	35.55	54.00	-18.45	Average	100	119	P
6	4960.00	7.21	41.95	49.16	74.00	-24.84	Peak	100	119	P
7	7440.00	13.34	33.96	47.30	54.00	-6.70	Average	100	218	P
8	7440.00	13.34	43.39	56.73	74.00	-17.27	Peak	100	218	P

Note: Level=Reading+Factor
Margin=Level-Limit
Factor=Antenna Factor + cable loss - Amplifier Factor

Test Mode : BLE 1TX CH39 1Mbps
Voltage : AC 120V/60Hz
Pol : Horizontal



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	2480.00	-4.74	89.21	84.47	200.00	-115.53	Average	100	51	P
2	2480.00	-4.74	90.11	85.37	200.00	-114.63	Peak	100	51	P
3	2483.50	-4.75	41.12	36.37	54.00	-17.63	Average	100	51	P
4	2483.50	-4.75	90.11	85.36	74.00	11.36	Peak	100	51	F
5	4960.00	7.21	26.22	33.43	54.00	-20.57	Average	100	114	P
6	4960.00	7.21	41.96	49.17	74.00	-24.83	Peak	100	114	P
7	7440.00	13.34	33.29	46.63	54.00	-7.37	Average	100	158	P
8	7440.00	13.34	43.38	56.72	74.00	-17.28	Peak	100	158	P

Note: Level=Reading+Factor
Margin=Level-Limit
Factor=Antenna Factor + cable loss - Amplifier Factor

6.7 Restricted Bands of Operation

Only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.09000 – 0.11000	16.42000 – 16.42300	399.9 – 410.0	4.500 – 5.250
0.49500 – 0.505**	16.69475 – 16.69525	608.0 – 614.0	5.350 – 5.460
2.17350 – 2.19050	16.80425 – 16.80475	960.0 – 1240.0	7.250 – 7.750
4.12500 – 4.12800	25.50000 – 25.67000	1300.0 – 1427.0	8.025 – 8.500
4.17725 – 4.17775	37.50000 – 38.25000	1435.0 – 1626.5	9.000 – 9.200
4.20725 – 4.20775	73.00000 – 74.60000	1645.5 – 1646.5	9.300 – 9.500
6.21500 – 6.21800	74.80000 – 75.20000	1660.0 – 1710.0	10.600 – 12.700
6.26775 – 6.26825	108.00000 – 121.94000	1718.8 – 1722.2	13.250 – 13.400
6.31175 – 6.31225	123.00000 – 138.00000	2200.0 – 2300.0	14.470 – 14.500
8.29100 – 8.29400	149.90000 – 150.05000	2310.0 – 2390.0	15.350 – 16.200
8.36200 – 8.36600	156.52475 – 156.52525	2483.5 – 2500.0	17.700 – 21.400
8.37625 – 8.38675	156.70000 – 156.90000	2655.0 – 2900.0	22.010 – 23.120
8.41425 – 8.41475	162.01250 – 167.17000	3260.0 – 3267.0	23.600 – 24.000
12.29000 – 12.29300	167.72000 – 173.20000	3332.0 – 3339.0	31.200 – 31.800
12.51975 – 12.52025	240.00000 – 285.00000	3345.8 – 3358.0	36.430 – 36.500
12.57675 – 12.57725	322.00000 – 335.40000	3600.0 – 4400.0	Above 38.6
13.36000 – 13.41000			

**: Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz

7. Test of Spurious Emission (Conducted)

7.1 Test Limit

According to the methods defined in ANSI C63.10-2020 Section 11.11.1
Below –30dB of the highest emission level of operating band (In 100 kHz Resolution Bandwidth)

7.2 Test Procedure

According to the methods defined in ANSI C63.10-2020 Section 11.11.2 & 11.11.3

a. The transmitter output was connected to the spectrum analyzer via a low loss cable.
b. Set RBW of spectrum analyzer to 100 KHz and VBW of spectrum analyzer to 300 KHz with convenient frequency span including 100 KHz bandwidth from band edge.
c. Peak conducted output power measured within any 100 kHz outside the authorized frequency band shall be attenuated by at least 30dB relative to the maximum measured in-band peak PSD level.
d. The band edges was measured and recorded.

7.3 Test Setup Layout



7.4 Test Result and Data

Note: Test plots refer to the following pages.

Modulation Type: GFSK(1Mbps)
CH00



Modulation Type: GFSK(1Mbps)
CH19







Modulation Type: GFSK(1Mbps)
CH39





8. On Time, Duty Cycle and Measurement methods

8.1 Test Limit

None; for reporting purposes only.

8.2 Test Procedure

According to the methods defined in ANSI C63.10-2020 Section 11.6 Zero-Span Spectrum Analyzer Method.

8.3 Test Setup Layout



8.4 Test Result and Data

Modulation Type	On Time (ms)	Period Time (ms)	Duty Cycle (%)
GFSK(1MBps)	0.41	0.65	63.29%

Modulation Type: GFSK(1Mbps)



9. 6dB Bandwidth Measurement Data

9.1 Test Limit

The minimum of 6dB Bandwidth Measurement is 0.5 MHz.

9.2 Test Procedures

According to the methods defined in ANSI C63.10-2020 Section 11.8

a. The transmitter output was connected to the spectrum analyzer.
b. Set RBW of spectrum analyzer to 100 KHz and VBW to 300 KHz.
c. The 6 dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 6 dB.
d. The 6dB Bandwidth was measured and recorded.

9.3 Test Setup Layout



9.4 Test Result and Data

Modulation Type	Channel	Frequency (MHz)	6dB Bandwidth (KHz)	Limit (KHz)
GFSK(1Mbps)	0	2402	693.10	500
	19	2440	700.30	500
	39	2480	702.40	500

Modulation Type: GFSK(1Mbps)
CH00

Modulation Type: GFSK(1Mbps)
CH19

Modulation Type: GFSK(1Mbps)
CH39



10. Maximum Average Output Power

10.1 Test Limit

The Maximum Output Power Measurement is 30dBm.

10.2 Test Procedures

According to the methods defined in ANSI C63.10-2020 Section 11.9.2.3.2
The antenna port (RF output) of the EUT was connected to the input (RF input) of a power meter. Power was read directly from the meter and cable loss connection was added to the reading to obtain power at the EUT antenna terminal. The EUT Output Power was set to maximum to produce the worse case test result.

10.3 Test Setup Layout



10.4 Test Result and Data

BT-LE(1M bps)

Conducted Setting	Modulation Type	Channel	Frequency (MHz)	Power Output (dBm)	Power Output (mW)
				Average	Average
8	GFSK	0	2402	5.43	3.491
8		19	2440	7.15	5.188
8		39	2480	8.46	7.015

Gate setup plot:



11. Power Spectral Density

11.1 Test Limit

The Maximum of Power Spectral Density Measurement is 8dBm.

If transmitting antennas of directional gain greater than 6 dBi are used, the power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi

11.2 Test Procedures

According to the methods defined in ANSI C63.10-2020 Section 11.10.1

11.3 Test Setup Layout



11.4 Test Result and Data

Modulation Type	Channel	Frequency (MHz)	Maximum Power Density of 10KHz Bandwidth(dBm)	Duty Cycle CF(dB)	Total PSD (dBm)	Limit
GFSK(1Mbps)	0	2402	-24.736	1.99	-22.75	8.00
	19	2440	-22.175	1.99	-20.19	8.00
	39	2480	-20.875	1.99	-18.89	8.00

Modulation Type: GFSK(1Mbps)
CH00



Modulation Type: GFSK(1Mbps)
CH19



Modulation Type: GFSK(1Mbps)
CH39



----------THE END OF REPORT----------