



FCC RADIO TEST REPORT

FCC ID : SWX-USLGGH
Equipment : SuperLink Gateway HA
Brand Name : UBIQUITI
Model Name : USL-G2-Gateway-HA
Applicant : Ubiquiti Inc.
685 Third Avenue, New York, New York 10017, USA
Manufacturer : Ubiquiti Inc.
685 Third Avenue, New York, New York 10017, USA
Standard : FCC Part 15 Subpart C §15.247

The product was received on Sep. 04, 2025 and testing was performed from Sep. 09, 2025 to Oct. 29, 2025. We, Sporton International Inc. EMC & Wireless Communications Laboratory, would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval from Sporton International Inc. EMC & Wireless Communications Laboratory, the test report shall not be reproduced except in full.

Approved by: Louis Wu

Sporton International Inc. EMC & Wireless Communications Laboratory
No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City 333, Taiwan (R.O.C.)



Table of Contents

History of this test report.....	3
Summary of Test Result.....	4
1 General Description.....	5
1.1 Product Feature of Equipment Under Test.....	5
1.2 Modification of EUT	5
1.3 Testing Location	5
1.4 Applicable Standards.....	6
2 Test Configuration of Equipment Under Test.....	7
2.1 Carrier Frequency Channel	7
2.2 Test Mode.....	8
2.3 Connection Diagram of Test System.....	9
2.4 Support Unit used in test configuration and system	9
2.5 EUT Operation Test Setup	10
2.6 Measurement Results Explanation Example.....	10
3 Test Result.....	11
3.1 6dB and 99% Bandwidth Measurement	11
3.2 Output Power Measurement.....	12
3.3 Power Spectral Density Measurement	13
3.4 Conducted Band Edges and Spurious Emission Measurement	14
3.5 Radiated Band Edges and Spurious Emission Measurement	15
3.6 AC Conducted Emission Measurement.....	19
3.7 Antenna Requirements.....	21
4 List of Measuring Equipment	22
5 Measurement Uncertainty	24
Appendix A. Conducted Test Results	
Appendix B. AC Conducted Emission Test Result	
Appendix C. Radiated Spurious Emission Test Result	
Appendix D. Duty Cycle Plots	
Appendix E. Setup Photographs	



History of this test report

Report No.	Version	Description	Issue Date
FR581203C	01	Initial issue of report	Jul. 01, 2026

Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
3.1	15.247(a)(2)	6dB Bandwidth	Pass	-
3.1	2.1049	99% Occupied Bandwidth	Pass	-
3.2	15.247(b)(3) 15.247(b)(4)	Output Power	Pass	-
3.3	15.247(e)	Power Spectral Density	Pass	-
3.4	15.247(d)	Conducted Band Edges and Spurious Emission	Pass	-
3.5	15.247(d)	Radiated Band Edges and Spurious Emission	Pass	-
3.6	15.207	AC Conducted Emission	Pass	-
3.7	15.203	Antenna Requirement	Pass	-

Conformity Assessment Condition:

1. The test results (PASS/FAIL) with all measurement uncertainty excluded are presented against the regulation limits or in accordance with the requirements stipulated by the applicant/manufacture who shall bear all the risks of non-compliance that may potentially occur if measurement uncertainty is taken into account.
2. The measurement uncertainty please refer to each test result in the section "Measurement Uncertainty".

Disclaimer:

The product specifications of the EUT presented in the test report that may affect the test assessments are declared by the manufacturer who shall take full responsibility for the authenticity.

Reviewed by: Danny Lee

Report Producer: Shannon Huang

1 General Description

1.1 Product Feature of Equipment Under Test

Product Feature
General Specs LTE, Bluetooth LE, LoRa, and Thread.
Antenna Type Bluetooth: Monopole Antenna

Antenna information
2400 MHz ~ 2483.5 MHz
Peak Gain (dBi) 4.0

Remark: The EUT's information above is declared by manufacturer. Please refer to Disclaimer in report summary.

Specification of Accessory
Battery
Brand Name Mic-power
Model Name MT24J01

1.2 Modification of EUT

No modifications made to the EUT during the testing.

1.3 Testing Location

The test location is accredited based on TAF code 1190 and 3786 designated by NCC (National Communication Commission).

Test Site	Sporton International Inc. EMC & Wireless Communications Laboratory
Test Site Location	No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City 333, Taiwan (R.O.C.)
Test Site No.	Sporton Site No. CO05-HY, 03CH07-HY

Test Site	Sporton International Inc. Wensan Laboratory
Test Site Location	No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City 333010, Taiwan (R.O.C.)
Test Site No.	Sporton Site No. TH05-HY (TAF Code: 3786)

Remark: The Conducted test item subcontracted to Sporton International Inc. Wensan Laboratory.

FCC designation No.: TW1190 and TW3786

Note: The test site complies with ANSI C63.4 2014 requirement.



1.4 Applicable Standards

According to the specifications declared by the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC KDB Publication No. 558074 D01 15.247 Meas Guidance v05r02
- ♦ FCC KDB 414788 D01 Radiated Test Site v01r01
- ♦ FCC Part 15 Subpart C §15.247
- ♦ ANSI C63.10-2020 + Cor.1-2023

Remark:

1. All the test items were validated and recorded in accordance with the standards without any modification during the testing.
2. The TAF code is not including all the FCC KDB listed without accreditation.
3. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.



2 Test Configuration of Equipment Under Test

2.1 Carrier Frequency Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
2400-2483.5 MHz	0	2402	21	2444
	1	2404	22	2446
	2	2406	23	2448
	3	2408	24	2450
	4	2410	25	2452
	5	2412	26	2454
	6	2414	27	2456
	7	2416	28	2458
	8	2418	29	2460
	9	2420	30	2462
	10	2422	31	2464
	11	2424	32	2466
	12	2426	33	2468
	13	2428	34	2470
	14	2430	35	2472
	15	2432	36	2474
	16	2434	37	2476
	17	2436	38	2478
	18	2438	39	2480
	19	2440	-	-
	20	2442	-	-


2.2 Test Mode

- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, the measured emission level of the EUT was maximized by rotating the EUT on a turntable, adjusting the orientation of the EUT and EUT antenna in three orthogonal axis (X: flat, Y: portrait, Z: landscape), and adjusting the measurement antenna orientation, following C63.10 exploratory test procedures and only the worst case emissions were reported in this report.
- b. AC power line Conducted Emission was tested under maximum output power.

The following summary table is showing all test modes to demonstrate in compliance with the standard.

Summary table of Test Cases	
Test Item	Data Rate / Modulation
Conducted Test Cases	Bluetooth – LE / GFSK
	Mode 1: Bluetooth Tx CH00_2402 MHz_1Mbps
	Mode 2: Bluetooth Tx CH19_2440 MHz_1Mbps
	Mode 3: Bluetooth Tx CH39_2480 MHz_1Mbps
AC Conducted Emission	Mode 1: Bluetooth-LE TX + LAN Link + AC Adapter
Remark: - For radiation spurious emission, the modulation and the data rate picked for testing are determined by the Max. RF conducted power. - The detailed Radiated test modes are shown in Appendix C.	

2.3 Connection Diagram of Test System



2.4 Support Unit used in test configuration and system

Item	Equipment	Brand Name	Model Name	FCC ID	Data Cable	Power Cord
1.	AC Adapter	UBIQUITI	E005-1I050100VU	FCC DoC	N/A	Shielded, 1.5m
2.	Notebook	Dell	Latitude 3420	FCC DoC	N/A	AC I/P : Unshielded, 1.2m DC O/P : Shielded, 1.8m



2.5 EUT Operation Test Setup

The RF test items, utility "SimplicityStudio-5 v6.0.1" was installed in Notebook which was programmed in order to make the EUT get into the engineering modes to provide channel selection, power level, data rate and the application type and for continuous transmitting signals.

2.6 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example :

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 4.2 dB and 10 dB attenuator.

$$\begin{aligned}\text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)} \\ &= 4.2 + 10 = 14.2 \text{ (dB)}\end{aligned}$$

3 Test Result

3.1 6dB and 99% Bandwidth Measurement

3.1.1 Limit of 6dB and 99% Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.


3.1.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.1.3 Test Procedures

1. The testing follows the ANSI C63.10 Section 6.9.3 (OBW) and 11.8.1 (6dB BW).
2. The RF output of EUT is connected to the spectrum analyzer by RF cable and attenuator. The path loss is compensated to the results for each measurement.
3. Set the maximum power setting and enable the EUT to transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 1% to 5% of the OBW but not less than 100 kHz. Set the Video bandwidth VBW $\geq 3 * RBW$. In order to make an accurate measurement. The 6dB bandwidth must be greater than 500 kHz.
5. For 99% Bandwidth Measurement, the spectrum analyzer's resolution bandwidth (RBW) is set 1-5% of the emission bandwidth, and set the Video bandwidth (VBW) $\geq 3 * RBW$.
6. Measure and record the results in the test report.

3.1.4 Test Setup



3.1.5 Test Result of 6dB Bandwidth

Please refer to Appendix A.

3.1.6 Test Result of 99% Occupied Bandwidth

Please refer to Appendix A.

3.2 Output Power Measurement

3.2.1 Limit of Output Power

For systems using digital modulation in the 2400-2483.5 MHz, the limit for output power is 30 dBm. If transmitting antenna of directional gain greater than 6 dBi is used, the peak output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.


3.2.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.2.3 Test Procedures

1. For Peak Power, the testing follows ANSI C63.10 Section 11.9.1.2 PKPM1.
2. For Average Power, the testing follows ANSI C63.10 Section 11.9.2.3.2 Method AVGPM-G
3. The RF output of EUT is connected to the power meter by RF cable and attenuator.
4. The path loss is compensated to the results for each measurement.
5. Set the maximum power setting and enable the EUT to transmit continuously.
6. Measure the conducted output power and record the results in the test report.

3.2.4 Test Setup



3.2.5 Test Result of Peak Output Power

Please refer to Appendix A.

3.2.6 Test Result of Average Output Power (Reporting Only)

Please refer to Appendix A.

3.3 Power Spectral Density Measurement

3.3.1 Limit of Power Spectral Density

The peak power spectral density shall not be greater than 8 dBm in any 3 kHz band at any time interval of continuous transmission.


3.3.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.3.3 Test Procedures

1. The testing follows the ANSI C63.10 Section 11.10.2 Method PKPSD.
2. The RF output of EUT is connected to the spectrum analyzer by RF cable and attenuator. The path loss is compensated to the results for each measurement.
3. Set the maximum power setting and enable the EUT to transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 3 kHz. Video bandwidth (VBW) = 10 kHz. In order to make an accurate measurement, set the span to 1.5 times DTS Channel Bandwidth. (6 dB BW)
5. Detector = peak, Sweep time = No faster than coupled (auto) time, Trace mode = max hold, Allow trace to fully stabilize. Use the peak marker function to determine the maximum power level.
6. Measure and record the results in the test report.
7. The Measured power density (dBm)/ 100 kHz is a reference level and is used as 20 dBc down limit line for Conducted Band Edges and Conducted Spurious Emission.

3.3.4 Test Setup



3.3.5 Test Result of Power Spectral Density

Please refer to Appendix A.

3.4 Conducted Band Edges and Spurious Emission Measurement

3.4.1 Limit of Conducted Band Edges and Spurious Emission

All harmonics/spurious must be at least 30 dB down from the highest emission level within the authorized band.


3.4.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.4.3 Test Procedure

1. The testing follows the ANSI C63.10 Section 11.11.3 Emission level measurement.
2. The RF output of EUT is connected to the spectrum analyzer by RF cable and attenuator. The path loss is compensated to the results for each measurement.
3. Set the maximum power setting and enable the EUT to transmit continuously.
4. Set RBW = 100 kHz, VBW = 300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

3.4.4 Test Setup



3.4.5 Test Result of Conducted Band Edges Plots

Please refer to Appendix A.

3.4.6 Test Result of Conducted Spurious Emission Plots

Please refer to Appendix A.

3.5 Radiated Band Edges and Spurious Emission Measurement

3.5.1 Limit of Radiated Band Edges and Spurious Emission

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required shall be 30 dB instead of 20 dB. In addition, radiated emissions which fall in the restricted bands must also comply with the limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.5.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.




3.5.3 Test Procedures


1. The testing follows the ANSI C63.10 Section 11.12.1 Radiated emission measurements.
2. The EUT is arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.
3. The EUT is placed on a turntable with 0.8 meter for frequency below 1 GHz and 1.5 meter for frequency above 1 GHz respectively above ground.
4. The EUT is set 3 meters away from the receiving antenna, which is mounted on the top of a variable height antenna tower.
5. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
6. Radiated testing below 1 GHz is performed by adjusting the antenna tower from 1 m to 4 m and by rotating the turn table from 0 degree to 360 degrees to find the peak maximum hold reading. When there is no suspected emission found and the emission level is with at least 6 dB margin against QP limit line, the position is marked as “-”.
7. Radiated testing above 1 GHz is performed by adjusting the antenna tower from 1 m to 4 m and by rotating the turn table from 0 degree to 360 degrees to find the peak maximum hold reading for scanning all frequencies. When there is no suspected emission found and the harmonic emission level is with at least 6 dB margin against average limit line, the position is marked as “-”.
8. Use the following spectrum analyzer settings:
 - (1) Span shall wide enough to fully capture the emission being measured;
 - (2) Set RBW = 100 kHz for $f < 1$ GHz; VBW $\geq$ RBW; Sweep = auto; Detector function = peak; Trace = max hold;
 - (3) Set RBW = 1 MHz, VBW = 3 MHz for $f \geq 1$ GHz for peak measurement.
For average measurement:
 - VBW = 10 Hz, when duty cycle is no less than 98 percent.
 - VBW $\geq 1/T$, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.

3.5.4 Test Setup


For radiated test below 30MHz




For radiated test from 30MHz to 1GHz



For radiated test from 1GHz to 18GHz



For radiated test above 18GHz



3.5.5 Test Results of Radiated Spurious Emissions (9 kHz ~ 30 MHz)

There is adequate comparison measurement of both open-field test site and alternative test site - semi-Anechoic chamber according to 414788 D01 Radiated Test Site v01r01, and the result comes out very similar.

3.5.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix C.

3.5.7 Duty Cycle

Please refer to Appendix D.

3.5.8 Test Result of Radiated Spurious Emission (30 MHz ~ 10th Harmonic)

Please refer to Appendix C.

3.6 AC Conducted Emission Measurement

3.6.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.6.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.6.3 Test Procedures

1. The EUT is placed 0.4 meter away from the conducting wall of the shielding room, and is kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. Both Line and Neutral shall be tested in order to find out the maximum conducted emission.
6. The frequency range from 150 kHz to 30 MHz is scanned.
7. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9 kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.

3.6.4 Test Setup



3.6.5 Test Result of AC Conducted Emission

Please refer to Appendix B.



3.7 Antenna Requirements

3.7.1 Standard Applicable

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of § 15.211, 15.213, 15.217, 15.219, 15.221, or § 15.236. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with § 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

3.7.2 Antenna Anti-Replacement Construction

Unique (non-standard) antenna connector.



4 List of Measuring Equipment

Instrument	Brand Name	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Bilog Antenna	TESEQ	CBL 6111D & 00800N1D01N-06	35419 & 03	30MHz~1GHz	Apr. 21, 2025	Oct. 20, 2025~ Oct. 21, 2025	Apr. 20, 2026	Radiation (03CH07-HY)
Double Ridge Horn Antenna	ETS-Lindgren	3117	00075962	1GHz ~ 18GHz	Nov. 28, 2024	Oct. 20, 2025~ Oct. 21, 2025	Nov. 27, 2025	Radiation (03CH07-HY)
Loop Antenna	Rohde & Schwarz	HFH2-Z2	100315	9 kHz~30 MHz	Mar. 06, 2025	Oct. 20, 2025~ Oct. 21, 2025	Mar. 05, 2026	Radiation (03CH07-HY)
Preamplifier	MITEQ	AMF-7D-00101800-30-10P	1590075	1GHz~18GHz	Apr. 18, 2025	Oct. 20, 2025~ Oct. 21, 2025	Apr. 17, 2026	Radiation (03CH07-HY)
Preamplifier	COM-POWER	PA-103A	161241	10MHz~1GHz	Sep. 30, 2025	Oct. 20, 2025~ Oct. 21, 2025	Sep. 29, 2026	Radiation (03CH07-HY)
Spectrum Analyzer	Agilent	N9030A	MY52350276	3Hz~44GHz	Mar. 28, 2025	Oct. 20, 2025~ Oct. 21, 2025	Mar. 27, 2026	Radiation (03CH07-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY28655/4 MY24971/4 MY15682/4	30MHz to 18GHz	Feb. 20, 2025	Oct. 20, 2025~ Oct. 21, 2025	Feb. 19, 2026	Radiation (03CH07-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY28655/4 MY24971/4	9kHz to 30MHz	Feb. 20, 2025	Oct. 20, 2025~ Oct. 21, 2025	Feb. 19, 2026	Radiation (03CH07-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 126	532078/126E	30MHz~18GHz	Sep. 13, 2025	Oct. 20, 2025~ Oct. 21, 2025	Sep. 12, 2026	Radiation (03CH07-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	801606/2	9KHz ~ 40GHz	Apr. 23, 2025	Oct. 20, 2025~ Oct. 21, 2025	Apr. 22, 2026	Radiation (03CH07-HY)
Controller	EMEC	EM1000	N/A	Control Ant Mast	N/A	Oct. 20, 2025~ Oct. 21, 2025	N/A	Radiation (03CH07-HY)
Controller	MF	MF-7802	N/A	Control Turn table	N/A	Oct. 20, 2025~ Oct. 21, 2025	N/A	Radiation (03CH07-HY)
Antenna Mast	EMEC	AM-BS-4500E	N/A	Boresight mast 1M~4M	N/A	Oct. 20, 2025~ Oct. 21, 2025	N/A	Radiation (03CH07-HY)
Turn Table	ChainTek	Chaintek 3000	N/A	0~360 Degree	N/A	Oct. 20, 2025~ Oct. 21, 2025	N/A	Radiation (03CH07-HY)
Software	Audix	E3	N/A	N/A	N/A	Oct. 20, 2025~ Oct. 21, 2025	N/A	Radiation (03CH07-HY)
USB Data Logger	TECPEL	TR-32	HE17XB2495	N/A	Feb. 24, 2025	Oct. 20, 2025~ Oct. 21, 2025	Feb. 23, 2026	Radiation (03CH07-HY)
Hygrometer	TECPEL	DTM-303A	TP201996	N/A	Nov. 01, 2024	Sep. 09, 2025~ Oct. 29, 2025	Oct. 31, 2025	Conducted (TH05-HY)
Power Sensor	DARE	RPR3006W	13100030SNO 31 (NO:182)	9kHz~6GHz	Jan. 09, 2025	Sep. 09, 2025~ Oct. 29, 2025	Jan. 08, 2026	Conducted (TH05-HY)
Signal Analyzer	Rohde & Schwarz	FSV3044	101467	10HZ~44GHZ	Jan. 14, 2025	Sep. 09, 2025~ Oct. 29, 2025	Jan. 13, 2026	Conducted (TH05-HY)
Switch Control Mainframe	E-Instrument	ETF-1405-0	EC1900157 (BOX6)	N/A	Feb. 10, 2025	Sep. 09, 2025~ Oct. 29, 2025	Feb. 09, 2026	Conducted (TH05-HY)
Software	Sporton	BTWIFI_Final_version_240513	N/A	Conducted Other Test Item	N/A	Sep. 09, 2025~ Oct. 29, 2025	N/A	Conducted (TH05-HY)



Instrument	Brand Name	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
AC Power Source	ChainTek	APC-1000W	N/A	N/A	N/A	Oct. 02, 2025	N/A	Conduction (CO05-HY)
EMI Test Receiver	Rohde & Schwarz	ESR3	102388	N/A	Dec. 10, 2024	Oct. 02, 2025	Dec. 09, 2025	Conduction (CO05-HY)
Hygrometer	TECPEL	DTM-303A	TP210031	N/A	Jun. 26, 2025	Oct. 02, 2025	Jun. 25, 2026	Conduction (CO05-HY)
LISN	Rohde & Schwarz	ENV216	100081	N/A	Jul. 25, 2025	Oct. 02, 2025	Jul. 24, 2026	Conduction (CO05-HY)
Software	Rohde & Schwarz	EMC32	N/A	N/A	N/A	Oct. 02, 2025	N/A	Conduction (CO05-HY)
Pulse Limiter	SCHWARZBECK	VTSD 9561-FN	00691	N/A	Jul. 29, 2025	Oct. 02, 2025	Jul. 28, 2026	Conduction (CO05-HY)
LISN Cable	MVE	RG-400	MQT24082501	N/A	Oct. 15, 2024	Oct. 02, 2025	Oct. 14, 2025	Conduction (CO05-HY)

5 Measurement Uncertainty

Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	3.7 dB
--	--------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	6.3 dB
--	--------

Uncertainty of Radiated Emission Measurement (1000 MHz ~ 6000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	4.7 dB
--	--------

Uncertainty of Radiated Emission Measurement (6000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.5 dB
--	--------

Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	4.9 dB
--	--------

Appendix A. Test Result of Conducted Test Items

Test Engineer:	Jay Chen	Temperature:	21~25	°C
Test Date:	2025/9/9~2025/10/29	Relative Humidity:	51~54	%

TEST RESULTS DATA 6dB and 99% Occupied Bandwidth								
Mod.	Data Rate	NTx	CH.	Freq. (MHz)	99% Occupied BW (MHz)	6dB BW (MHz)	6dB BW Limit (MHz)	Pass/Fail
BLE	1Mbps	1	0	2402	1.028	0.673	0.50	Pass
BLE	1Mbps	1	19	2440	1.028	0.672	0.50	Pass
BLE	1Mbps	1	39	2480	1.028	0.669	0.50	Pass

TEST RESULTS DATA Peak Power Table										
Mod.	Data Rate	NTx	CH.	Freq. (MHz)	Peak Conducted Power (dBm)	Conducted Power Limit (dBm)	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass /Fail
BLE	1Mbps	1	0	2402	19.77	30.00	4.00	23.77	36.00	Pass
BLE	1Mbps	1	19	2440	19.73	30.00	4.00	23.73	36.00	Pass
BLE	1Mbps	1	39	2480	14.55	30.00	4.00	18.55	36.00	Pass

TEST RESULTS DATA Average Power Table (Reporting Only)										
Mod.	Data Rate	NTx	CH.	Freq. (MHz)	Average Conducted Power (dBm)	Conducted Power Limit (dBm)	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass /Fail
BLE	1Mbps	1	0	2402	17.97	30.00	4.00	21.97	36.00	Pass
BLE	1Mbps	1	19	2440	17.82	30.00	4.00	21.82	36.00	Pass
BLE	1Mbps	1	39	2480	12.55	30.00	4.00	16.55	36.00	Pass

TEST RESULTS DATA Peak Power Density									
Mod.	Data Rate	NTx	CH.	Freq. (MHz)	Peak PSD (dBm /100kHz)	Peak PSD (dBm /3kHz)	DG (dBi)	Peak PSD Limit (dBm /3kHz)	Pass/Fail
BLE	1Mbps	1	0	2402	17.94	2.17	4.00	8.00	Pass
BLE	1Mbps	1	19	2440	17.69	1.95	4.00	8.00	Pass
BLE	1Mbps	1	39	2480	12.56	-2.97	4.00	8.00	Pass

Note: PSD (dBm/ 100kHz) is a reference level used for Conducted Band Edges and Conducted Spurious Emission 20dBc limit.




Number of TX = 1, Ant. 1 (Measured)


6dB Bandwidth

<1Mbps>


6 dB Bandwidth Plot on Channel 00



6 dB Bandwidth Plot on Channel 19






6 dB Bandwidth Plot on Channel 39






**99% Occupied Bandwidth**

<1Mbps>

99% Occupied Bandwidth Plot on Channel 00**99% Occupied Bandwidth Plot on Channel 19****99% Occupied Bandwidth Plot on Channel 39**





**Power Spectral Density (dBm/3kHz)**

<1Mbps>

Power Density (dBm/3kHz) Plot Channel 00**Power Density (dBm/3kHz) Plot Channel 19****Power Density (dBm/3kHz) Plot Channel 39**

**Band Edge and Conducted Spurious Emission**


<1Mbps>

Channel 00**100kHz PSD reference Level Plot****Plot on Channel 00****Spurious Emission 30MHz~1GHz Plot****Spurious Emission 1GHz~26.5GHz Plot**




Channel 19


100kHz PSD reference Level Plot



Spurious Emission 30MHz~1GHz Plot




Spurious Emission 1GHz~26.5GHz Plot






Channel 39


100kHz PSD reference Level Plot




Plot on Channel 39



Spurious Emission 30MHz~1GHz Plot



Spurious Emission 1GHz~26.5GHz Plot






Appendix B. AC Conducted Emission Test Results

Test Engineer :	Brian Chen	Temperature :	23 ~ 26°C
		Relative Humidity :	45 ~ 55%

EUT Information

Report NO : 581203
 Test Mode : Mode 1
 Test Voltage : 120Vac/60Hz
 Phase : Line

Full Spectrum



Final_Result


Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.289500	---	27.13	50.54	23.41	L1	OFF	19.8
0.289500	32.95	---	60.54	27.59	L1	OFF	19.8
0.485250	---	34.51	46.25	11.74	L1	OFF	19.8
0.485250	40.46	---	56.25	15.79	L1	OFF	19.8
0.503250	---	35.19	46.00	10.81	L1	OFF	19.8
0.503250	41.38	---	56.00	14.62	L1	OFF	19.8
0.555000	---	39.55	46.00	6.45	L1	OFF	19.8
0.555000	46.04	---	56.00	9.96	L1	OFF	19.8
0.784500	---	39.24	46.00	6.76	L1	OFF	19.9
0.784500	44.91	---	56.00	11.09	L1	OFF	19.9
1.160250	---	30.15	46.00	15.85	L1	OFF	19.9
1.160250	37.32	---	56.00	18.68	L1	OFF	19.9
1.450500	---	29.31	46.00	16.69	L1	OFF	19.9
1.450500	36.24	---	56.00	19.76	L1	OFF	19.9
1.684500	---	27.58	46.00	18.42	L1	OFF	19.9
1.684500	34.26	---	56.00	21.74	L1	OFF	19.9
3.405750	---	27.23	46.00	18.77	L1	OFF	20.0
3.405750	31.77	---	56.00	24.23	L1	OFF	20.0
4.668000	---	26.52	46.00	19.48	L1	OFF	20.1
4.668000	29.38	---	56.00	26.62	L1	OFF	20.1
4.956000	---	26.22	46.00	19.78	L1	OFF	20.1

4.956000	32.24	---	56.00	23.76	L1	OFF	20.1
6.513000	---	26.67	50.00	23.33	L1	OFF	20.3
6.513000	30.89	---	60.00	29.11	L1	OFF	20.3
16.228500	---	32.08	50.00	17.92	L1	OFF	20.6
16.228500	37.98	---	60.00	22.02	L1	OFF	20.6
23.129250	---	35.03	50.00	14.97	L1	OFF	20.6
23.129250	43.71	---	60.00	16.29	L1	OFF	20.6

EUT Information

Report NO : 581203
Test Mode : Mode 1
Test Voltage : 120Vac/60Hz
Phase : Neutral

Full Spectrum



Final_Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.152250	---	29.93	55.88	25.95	N	OFF	19.8
0.152250	37.61	---	65.88	28.27	N	OFF	19.8
0.505500	---	28.57	46.00	17.43	N	OFF	19.8
0.505500	35.27	---	56.00	20.73	N	OFF	19.8
0.555000	---	31.77	46.00	14.23	N	OFF	19.8
0.555000	36.71	---	56.00	19.29	N	OFF	19.8
0.782250	---	30.18	46.00	15.82	N	OFF	19.9
0.782250	39.23	---	56.00	16.77	N	OFF	19.9
3.405750	---	25.31	46.00	20.69	N	OFF	20.0
3.405750	27.41	---	56.00	28.59	N	OFF	20.0
6.438750	---	26.26	50.00	23.74	N	OFF	20.3
6.438750	28.15	---	60.00	31.85	N	OFF	20.3
26.610000	---	32.92	50.00	17.08	N	OFF	20.8
26.610000	37.12	---	60.00	22.88	N	OFF	20.8

Appendix C. Radiated Spurious Emission Test Data

Test Engineer :	Jesse Wang, Stan Hsieh, and Ken Wu	Temperature :	20.4 ~ 23.8°C
		Relative Humidity :	56.1 ~ 71.4%

Note symbol

-L	Low channel location
-R	High channel location

C1. Radiated Spurious Emission Test Modes

Mode	Band (MHz)	Antenna	Modulation	Channel	Frequency	Data Rate	RU	Remark
Mode 1	2400-2483.5	1	Bluetooth-LE GFSK	00	2402	1Mbps	-	-
Mode 2	2400-2483.5	1	Bluetooth-LE GFSK	19	2440	1Mbps	-	-
Mode 3	2400-2483.5	1	Bluetooth-LE GFSK	39	2480	1Mbps	-	-
Mode 4	2400-2483.5	1	Bluetooth-LE GFSK	39	2480	1Mbps	-	LF

C2. Summary of each worse mode

Mode	Modulation	Ch.	Freq. (MHz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Pol.	Peak Avg.	Result	RU	Remark
1	Bluetooth-LE GFSK	00	2389.76	46.80	54.00	-7.20	H	Avg.	Pass	-	Band Edge
	Bluetooth-LE GFSK	00	4804.00	47.47	54.00	-6.53	H	Avg.	Pass	-	Harmonic
2	Bluetooth-LE GFSK	19	2495.80	46.55	54.00	-7.45	V	Avg.	Pass	-	Band Edge
	Bluetooth-LE GFSK	19	7320.00	52.64	54.00	-1.36	H	Avg.	Pass	-	Harmonic
3	Bluetooth-LE GFSK	39	2483.52	53.68	54.00	-0.32	H	Avg.	Pass	-	Band Edge
	Bluetooth-LE GFSK	39	4960.00	46.03	54.00	-7.97	H	Avg.	Pass	-	Harmonic
4	LF	39	31.94	33.23	40.00	-6.77	V	Peak	Pass	-	LF





Mode	1																																																																																		
	Band Edge																																																																																		
	2400-2483.5_Bluetooth-LE GFSK_CH00_2402MHz																																																																																		
ANT	1																																																																																		
Pol.	Horizontal						Fundamental																																																																												
Peak	Level (dBuV/m) Date: 2025-10-20 Site : 03CH07-HY Condition: PEAK_BE_74 3m HF_ANT_00075962 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level</th><th>Ant Factor</th><th>Cable Loss</th><th>Preamp Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1 2387.28</td><td>55.86</td><td>74.00</td><td>-18.14</td><td>40.17</td><td>32.10</td><td>8.36</td><td>34.67</td><td>9.90</td><td>106</td><td>180</td><td>Peak</td></tr></table>						Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1 2387.28	55.86	74.00	-18.14	40.17	32.10	8.36	34.67	9.90	106	180	Peak	Level (dBuV/m) Date: 2025-10-20 Site : 03CH07-HY Condition: PEAK_74 3m HF_ANT_00075962 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level</th><th>Ant Factor</th><th>Cable Loss</th><th>Preamp Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1 2402.00</td><td>115.87</td><td>-----</td><td>-----</td><td>100.16</td><td>32.10</td><td>8.38</td><td>34.67</td><td>9.90</td><td>106</td><td>180</td><td>Peak</td></tr></table>					Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1 2402.00	115.87	-----	-----	100.16	32.10	8.38	34.67	9.90	106	180	Peak
	Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark																																																																							
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																									
1 2387.28	55.86	74.00	-18.14	40.17	32.10	8.36	34.67	9.90	106	180	Peak																																																																								
Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark																																																																								
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																									
1 2402.00	115.87	-----	-----	100.16	32.10	8.38	34.67	9.90	106	180	Peak																																																																								
Avg	Level (dBuV/m) Date: 2025-10-20 Site : 03CH07-HY Condition: AVG_BE_54 3m HF_ANT_00075962 HORIZONTAL : RBW:1000.000kHz VBW:2.700kHz SMT:Auto <table><tr><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level</th><th>Ant Factor</th><th>Cable Loss</th><th>Preamp Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1 2389.76</td><td>46.80</td><td>54.00</td><td>-7.20</td><td>31.11</td><td>32.10</td><td>8.36</td><td>34.67</td><td>9.90</td><td>106</td><td>180</td><td>Average</td></tr></table>						Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1 2389.76	46.80	54.00	-7.20	31.11	32.10	8.36	34.67	9.90	106	180	Average	Level (dBuV/m) Date: 2025-10-20 Site : 03CH07-HY Condition: AVG_54 3m HF_ANT_00075962 HORIZONTAL : RBW:1000.000kHz VBW:2.700kHz SMT:Auto <table><tr><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level</th><th>Ant Factor</th><th>Cable Loss</th><th>Preamp Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1 2402.00</td><td>115.35</td><td>-----</td><td>-----</td><td>99.64</td><td>32.10</td><td>8.38</td><td>34.67</td><td>9.90</td><td>106</td><td>180</td><td>Average</td></tr></table>					Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1 2402.00	115.35	-----	-----	99.64	32.10	8.38	34.67	9.90	106	180	Average
Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark																																																																								
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																									
1 2389.76	46.80	54.00	-7.20	31.11	32.10	8.36	34.67	9.90	106	180	Average																																																																								
Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark																																																																								
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																									
1 2402.00	115.35	-----	-----	99.64	32.10	8.38	34.67	9.90	106	180	Average																																																																								



Mode	1																																																																																									
	Band Edge																																																																																									
	2400-2483.5_Bluetooth-LE GFSK_CH00_2402MHz																																																																																									
ANT	1																																																																																									
Pol.	Vertical						Fundamental																																																																																			
Peak	Level (dBuV/m) Date: 2025-10-20 Site : 03CH07-HY Condition: PEAK_BE_74 3m HF_ANT_00075962 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level</th><th>Ant Factor</th><th>Cable Loss</th><th>Preamp Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>2386.45</td><td>54.95</td><td>74.00</td><td>-19.05</td><td>39.27</td><td>32.10</td><td>8.35</td><td>34.67</td><td>9.90</td><td>142</td><td>243</td><td>Peak</td></tr></table>							Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	2386.45	54.95	74.00	-19.05	39.27	32.10	8.35	34.67	9.90	142	243	Peak	Level (dBuV/m) Date: 2025-10-20 Site : 03CH07-HY Condition: PEAK_74 3m HF_ANT_00075962 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level</th><th>Ant Factor</th><th>Cable Loss</th><th>Preamp Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>2402.00</td><td>113.73</td><td>74.00</td><td>39.73</td><td>98.02</td><td>32.10</td><td>8.38</td><td>34.67</td><td>9.90</td><td>142</td><td>243</td><td>Peak</td></tr></table>							Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	2402.00	113.73	74.00	39.73	98.02	32.10	8.38	34.67	9.90	142	243	Peak
		Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark																																																																													
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																															
1	2386.45	54.95	74.00	-19.05	39.27	32.10	8.35	34.67	9.90	142	243	Peak																																																																														
	Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark																																																																														
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																															
1	2402.00	113.73	74.00	39.73	98.02	32.10	8.38	34.67	9.90	142	243	Peak																																																																														
Avg	Level (dBuV/m) Date: 2025-10-20 Site : 03CH07-HY Condition: AVG_BE_54 3m HF_ANT_00075962 VERTICAL : RBW:1000.000kHz VBW:2.700kHz SMT:Auto <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level</th><th>Ant Factor</th><th>Cable Loss</th><th>Preamp Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>2325.18</td><td>45.91</td><td>54.00</td><td>-8.09</td><td>30.48</td><td>31.95</td><td>8.24</td><td>34.66</td><td>9.90</td><td>142</td><td>243</td><td>Average</td></tr></table>							Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	2325.18	45.91	54.00	-8.09	30.48	31.95	8.24	34.66	9.90	142	243	Average	Level (dBuV/m) Date: 2025-10-20 Site : 03CH07-HY Condition: AVG_54 3m HF_ANT_00075962 VERTICAL : RBW:1000.000kHz VBW:2.700kHz SMT:Auto <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level</th><th>Ant Factor</th><th>Cable Loss</th><th>Preamp Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>2402.00</td><td>113.21</td><td>54.00</td><td>59.21</td><td>97.50</td><td>32.10</td><td>8.38</td><td>34.67</td><td>9.90</td><td>142</td><td>243</td><td>Average</td></tr></table>							Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	2402.00	113.21	54.00	59.21	97.50	32.10	8.38	34.67	9.90	142	243	Average
		Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark																																																																													
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																															
1	2325.18	45.91	54.00	-8.09	30.48	31.95	8.24	34.66	9.90	142	243	Average																																																																														
	Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark																																																																														
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																															
1	2402.00	113.21	54.00	59.21	97.50	32.10	8.38	34.67	9.90	142	243	Average																																																																														



Mode	1																																																																																																																																												
	Harmonic																																																																																																																																												
	2400-2483.5_Bluetooth-LE GFSK _CH00_2402MHz																																																																																																																																												
ANT	1																																																																																																																																												
Pol.	Horizontal						Vertical																																																																																																																																						
Peak Avg	 Level (dBuV/m) Date: 2025-10-20 PEAK_74 AVG_54						 Level (dBuV/m) Date: 2025-10-20 PEAK_74 AVG_54																																																																																																																																						
	Site : 03CH07-HY Condition: PEAK_74 3m HF_ANT_00075962 HORIZONTAL						Site : 03CH07-HY Condition: PEAK_74 3m HF_ANT_00075962 VERTICAL																																																																																																																																						
	<table><thead><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr></thead><tbody><tr><td>1</td><td>4804.00</td><td>51.97</td><td>74.00</td><td>-22.03</td><td>63.10</td><td>34.29</td><td>11.93</td><td>58.41</td><td>1.06</td><td>105</td><td>302</td><td>Peak</td></tr><tr><td>2</td><td>4804.00</td><td>47.47</td><td>54.00</td><td>-6.53</td><td>58.60</td><td>34.29</td><td>11.93</td><td>58.41</td><td>1.06</td><td>105</td><td>302</td><td>Average</td></tr><tr><td>3</td><td>7206.00</td><td>57.93</td><td>-----</td><td>-----</td><td>63.95</td><td>35.80</td><td>14.50</td><td>57.50</td><td>1.18</td><td>--</td><td>--</td><td>Peak</td></tr></tbody></table>							Freq	Level	Limit	Line Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	4804.00	51.97	74.00	-22.03	63.10	34.29	11.93	58.41	1.06	105	302	Peak	2	4804.00	47.47	54.00	-6.53	58.60	34.29	11.93	58.41	1.06	105	302	Average	3	7206.00	57.93	-----	-----	63.95	35.80	14.50	57.50	1.18	--	--	Peak	<table><thead><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr></thead><tbody><tr><td>1</td><td>4804.00</td><td>50.97</td><td>74.00</td><td>-23.03</td><td>62.10</td><td>34.29</td><td>11.93</td><td>58.41</td><td>1.06</td><td>100</td><td>293</td><td>Peak</td></tr><tr><td>2</td><td>4804.00</td><td>46.47</td><td>54.00</td><td>-7.53</td><td>57.60</td><td>34.29</td><td>11.93</td><td>58.41</td><td>1.06</td><td>100</td><td>293</td><td>Average</td></tr><tr><td>3</td><td>7206.00</td><td>55.89</td><td>-----</td><td>-----</td><td>61.91</td><td>35.80</td><td>14.50</td><td>57.50</td><td>1.18</td><td>--</td><td>--</td><td>Peak</td></tr></tbody></table>							Freq	Level	Limit	Line Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	4804.00	50.97	74.00	-23.03	62.10	34.29	11.93	58.41	1.06	100	293	Peak	2	4804.00	46.47	54.00	-7.53	57.60	34.29	11.93	58.41	1.06	100	293	Average	3	7206.00	55.89	-----	-----	61.91	35.80	14.50	57.50	1.18	--	--
	Freq	Level	Limit	Line Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																	
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																																																		
1	4804.00	51.97	74.00	-22.03	63.10	34.29	11.93	58.41	1.06	105	302	Peak																																																																																																																																	
2	4804.00	47.47	54.00	-6.53	58.60	34.29	11.93	58.41	1.06	105	302	Average																																																																																																																																	
3	7206.00	57.93	-----	-----	63.95	35.80	14.50	57.50	1.18	--	--	Peak																																																																																																																																	
	Freq	Level	Limit	Line Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																	
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																																																		
1	4804.00	50.97	74.00	-23.03	62.10	34.29	11.93	58.41	1.06	100	293	Peak																																																																																																																																	
2	4804.00	46.47	54.00	-7.53	57.60	34.29	11.93	58.41	1.06	100	293	Average																																																																																																																																	
3	7206.00	55.89	-----	-----	61.91	35.80	14.50	57.50	1.18	--	--	Peak																																																																																																																																	

Remark: The unwanted signal at 7206.00 MHz can be ignored since it falls within the non-restricted band and meets the requirements of 15.247(d), and RSS-247 Section 6.6.



FCC RADIO TEST REPORT

Report No. : FR581203C

Mode	2																																																																																																	
	Band Edge - L																																																																																																	
	2400-2483.5_Bluetooth-LE GFSK_CH19_2440MHz																																																																																																	
ANT	1																																																																																																	
Pol.	Horizontal						Fundamental																																																																																											
Peak	Level (dBuV/m) Date: 2025-10-20 Site : 03CH07-HY Condition: PEAK_BE_74 3m HF_ANT_00075962 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2380.59</td><td>54.84</td><td>74.00</td><td>-19.16</td><td>39.17</td><td>32.10</td><td>8.34</td><td>34.67</td><td>9.90</td><td>100</td><td>224 Peak</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2380.59	54.84	74.00	-19.16	39.17	32.10	8.34	34.67	9.90	100	224 Peak	Level (dBuV/m) Date: 2025-10-20 Site : 03CH07-HY Condition: PEAK_74 3m HF_ANT_00075962 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2440.00</td><td>116.17</td><td>-----</td><td>-----</td><td>100.27</td><td>32.20</td><td>8.45</td><td>34.67</td><td>9.92</td><td>100</td><td>224 Peak</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2440.00	116.17	-----	-----	100.27	32.20	8.45	34.67	9.92	100	224 Peak
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																								
Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor																																																																																											
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																								
1	2380.59	54.84	74.00	-19.16	39.17	32.10	8.34	34.67	9.90	100	224 Peak																																																																																							
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																									
Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor																																																																																											
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																								
1	2440.00	116.17	-----	-----	100.27	32.20	8.45	34.67	9.92	100	224 Peak																																																																																							
Avg	Level (dBuV/m) Date: 2025-10-20 Site : 03CH07-HY Condition: AVG_BE_54 3m HF_ANT_00075962 HORIZONTAL : RBW:1000.000kHz VBW:2.700kHz SMT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2362.91</td><td>46.47</td><td>54.00</td><td>-7.53</td><td>30.92</td><td>32.00</td><td>8.31</td><td>34.66</td><td>9.90</td><td>100</td><td>224 Average</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2362.91	46.47	54.00	-7.53	30.92	32.00	8.31	34.66	9.90	100	224 Average	Level (dBuV/m) Date: 2025-10-20 Site : 03CH07-HY Condition: AVG_54 3m HF_ANT_00075962 HORIZONTAL : RBW:1000.000kHz VBW:2.700kHz SMT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2440.00</td><td>115.66</td><td>-----</td><td>-----</td><td>99.76</td><td>32.20</td><td>8.45</td><td>34.67</td><td>9.92</td><td>100</td><td>224 Average</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2440.00	115.66	-----	-----	99.76	32.20	8.45	34.67	9.92	100	224 Average
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																								
Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor																																																																																											
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																								
1	2362.91	46.47	54.00	-7.53	30.92	32.00	8.31	34.66	9.90	100	224 Average																																																																																							
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																									
Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor																																																																																											
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																								
1	2440.00	115.66	-----	-----	99.76	32.20	8.45	34.67	9.92	100	224 Average																																																																																							



Mode	2	
	Band Edge - R	
	2400-2483.5_Bluetooth-LE GFSK _CH19_2440MHz	
ANT	1	
Pol.	Horizontal	Fundamental
Peak		



Mode	2																																																																																																			
	Band Edge - L																																																																																																			
	2400-2483.5_Bluetooth-LE GFSK_CH19_2440MHz																																																																																																			
ANT	1																																																																																																			
Pol.	Vertical						Fundamental																																																																																													
Peak	Level (dBuV/m) Date: 2025-10-20 Site : 03CH07-HY Condition: PEAK_BE_74 3m HF_ANT_00075962 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2388.72</td><td>55.42</td><td>74.00</td><td>-18.58</td><td>39.75</td><td>32.10</td><td>8.34</td><td>34.67</td><td>9.90</td><td>100</td><td>300</td><td>Peak</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2388.72	55.42	74.00	-18.58	39.75	32.10	8.34	34.67	9.90	100	300	Peak	Level (dBuV/m) Date: 2025-10-20 Site : 03CH07-HY Condition: PEAK_74 3m HF_ANT_00075962 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2440.00</td><td>112.28</td><td>-----</td><td>-----</td><td>96.38</td><td>32.20</td><td>8.45</td><td>34.67</td><td>9.92</td><td>100</td><td>300</td><td>Peak</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2440.00	112.28	-----	-----	96.38	32.20	8.45	34.67	9.92	100	300	Peak
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																										
Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor																																																																																													
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																										
1	2388.72	55.42	74.00	-18.58	39.75	32.10	8.34	34.67	9.90	100	300	Peak																																																																																								
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																											
Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor																																																																																													
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																										
1	2440.00	112.28	-----	-----	96.38	32.20	8.45	34.67	9.92	100	300	Peak																																																																																								
Avg	Level (dBuV/m) Date: 2025-10-20 Site : 03CH07-HY Condition: AVG_BE_54 3m HF_ANT_00075962 VERTICAL : RBW:1000.000kHz VBW:2.700kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2383.17</td><td>46.28</td><td>54.00</td><td>-7.72</td><td>30.73</td><td>32.00</td><td>8.31</td><td>34.66</td><td>9.90</td><td>100</td><td>300</td><td>Average</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2383.17	46.28	54.00	-7.72	30.73	32.00	8.31	34.66	9.90	100	300	Average	Level (dBuV/m) Date: 2025-10-20 Site : 03CH07-HY Condition: AVG_54 3m HF_ANT_00075962 VERTICAL : RBW:1000.000kHz VBW:2.700kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2440.00</td><td>111.78</td><td>-----</td><td>-----</td><td>95.88</td><td>32.20</td><td>8.45</td><td>34.67</td><td>9.92</td><td>100</td><td>300</td><td>Average</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2440.00	111.78	-----	-----	95.88	32.20	8.45	34.67	9.92	100	300	Average
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																										
Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor																																																																																													
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																										
1	2383.17	46.28	54.00	-7.72	30.73	32.00	8.31	34.66	9.90	100	300	Average																																																																																								
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																											
Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor																																																																																													
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																										
1	2440.00	111.78	-----	-----	95.88	32.20	8.45	34.67	9.92	100	300	Average																																																																																								







Mode	2	
	Band Edge - R	
	2400-2483.5_Bluetooth-LE GFSK _CH19_2440MHz	
ANT	1	
Pol.	Vertical	Fundamental
Peak		



Mode	2																																																																																																																																																																																					
	Harmonic																																																																																																																																																																																					
	2400-2483.5_Bluetooth-LE GFSK _CH19_2440MHz																																																																																																																																																																																					
ANT	1																																																																																																																																																																																					
Pol.	Horizontal							Vertical																																																																																																																																																																														
Peak Avg	Level (dBuV/m) Date: 2025-10-20 Site : 03CH07-HY Condition: PEAK_74 3m HF_ANT_00075962 HORIZONTAL <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>4880.00</td><td>50.32</td><td>74.00</td><td>-23.68</td><td>61.35</td><td>34.20</td><td>12.03</td><td>58.25</td><td>0.99</td><td>100</td><td>304</td><td>Peak</td><td></td></tr><tr><td>2</td><td>4880.00</td><td>46.10</td><td>54.00</td><td>-7.90</td><td>57.13</td><td>34.20</td><td>12.03</td><td>58.25</td><td>0.99</td><td>100</td><td>304</td><td>Average</td><td></td></tr><tr><td>3</td><td>7320.00</td><td>56.52</td><td>74.00</td><td>-17.48</td><td>62.66</td><td>35.70</td><td>14.70</td><td>57.70</td><td>1.16</td><td>100</td><td>255</td><td>Peak</td><td></td></tr><tr><td>4</td><td>7320.00</td><td>52.64</td><td>54.00</td><td>-1.36</td><td>58.78</td><td>35.70</td><td>14.70</td><td>57.70</td><td>1.16</td><td>100</td><td>255</td><td>Average</td><td></td></tr></table>								Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	4880.00	50.32	74.00	-23.68	61.35	34.20	12.03	58.25	0.99	100	304	Peak		2	4880.00	46.10	54.00	-7.90	57.13	34.20	12.03	58.25	0.99	100	304	Average		3	7320.00	56.52	74.00	-17.48	62.66	35.70	14.70	57.70	1.16	100	255	Peak		4	7320.00	52.64	54.00	-1.36	58.78	35.70	14.70	57.70	1.16	100	255	Average		Level (dBuV/m) Date: 2025-10-20 Site : 03CH07-HY Condition: PEAK_74 3m HF_ANT_00075962 VERTICAL <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>4880.00</td><td>48.10</td><td>74.00</td><td>-25.90</td><td>59.13</td><td>34.20</td><td>12.03</td><td>58.25</td><td>0.99</td><td>100</td><td>282</td><td>Peak</td><td></td></tr><tr><td>2</td><td>4880.00</td><td>43.85</td><td>54.00</td><td>-10.15</td><td>54.88</td><td>34.20</td><td>12.03</td><td>58.25</td><td>0.99</td><td>100</td><td>282</td><td>Average</td><td></td></tr><tr><td>3</td><td>7320.00</td><td>56.17</td><td>74.00</td><td>-17.83</td><td>62.31</td><td>35.70</td><td>14.70</td><td>57.70</td><td>1.16</td><td>325</td><td>95</td><td>Peak</td><td></td></tr><tr><td>4</td><td>7320.00</td><td>52.09</td><td>54.00</td><td>-1.91</td><td>58.23</td><td>35.70</td><td>14.70</td><td>57.70</td><td>1.16</td><td>325</td><td>95</td><td>Average</td><td></td></tr></table>								Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	4880.00	48.10	74.00	-25.90	59.13	34.20	12.03	58.25	0.99	100	282	Peak		2	4880.00	43.85	54.00	-10.15	54.88	34.20	12.03	58.25	0.99	100	282	Average		3	7320.00	56.17	74.00	-17.83	62.31	35.70	14.70	57.70	1.16	325	95	Peak		4	7320.00	52.09	54.00	-1.91	58.23	35.70	14.70	57.70	1.16	325	95	Average	
		Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																																																								
	MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																																																																																										
1	4880.00	50.32	74.00	-23.68	61.35	34.20	12.03	58.25	0.99	100	304	Peak																																																																																																																																																																										
2	4880.00	46.10	54.00	-7.90	57.13	34.20	12.03	58.25	0.99	100	304	Average																																																																																																																																																																										
3	7320.00	56.52	74.00	-17.48	62.66	35.70	14.70	57.70	1.16	100	255	Peak																																																																																																																																																																										
4	7320.00	52.64	54.00	-1.36	58.78	35.70	14.70	57.70	1.16	100	255	Average																																																																																																																																																																										
	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																																																									
	MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																																																																																										
1	4880.00	48.10	74.00	-25.90	59.13	34.20	12.03	58.25	0.99	100	282	Peak																																																																																																																																																																										
2	4880.00	43.85	54.00	-10.15	54.88	34.20	12.03	58.25	0.99	100	282	Average																																																																																																																																																																										
3	7320.00	56.17	74.00	-17.83	62.31	35.70	14.70	57.70	1.16	325	95	Peak																																																																																																																																																																										
4	7320.00	52.09	54.00	-1.91	58.23	35.70	14.70	57.70	1.16	325	95	Average																																																																																																																																																																										



Mode	3																																																																																											
	Band Edge																																																																																											
	2400-2483.5_Bluetooth-LE GFSK_CH39_2480MHz																																																																																											
ANT	1																																																																																											
Pol.	Horizontal												Fundamental																																																																															
Peak	Level (dBuV/m) Date: 2025-10-20  PEAK_BE_74 Site : 03CH07-HY Condition: PEAK_BE_74 3m HF_ANT_00075962 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level</th><th>Ant Factor</th><th>Cable Loss</th><th>Preamp Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>2483.66</td><td>61.52</td><td>74.00</td><td>-12.48</td><td>45.31</td><td>32.44</td><td>8.52</td><td>34.68</td><td>9.93</td><td>219</td><td>355</td><td>Peak</td></tr></table>														Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	2483.66	61.52	74.00	-12.48	45.31	32.44	8.52	34.68	9.93	219	355	Peak	Level (dBuV/m) Date: 2025-10-20  PEAK_74 Site : 03CH07-HY Condition: PEAK_74 3m HF_ANT_00075962 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level</th><th>Ant Factor</th><th>Cable Loss</th><th>Preamp Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>2480.00</td><td>111.14</td><td>-----</td><td>-----</td><td>94.98</td><td>32.40</td><td>8.51</td><td>34.68</td><td>9.93</td><td>219</td><td>355</td><td>Peak</td></tr></table>		Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	2480.00	111.14	-----	-----	94.98	32.40	8.51	34.68	9.93	219	355	Peak
		Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark																																																																															
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																	
1	2483.66	61.52	74.00	-12.48	45.31	32.44	8.52	34.68	9.93	219	355	Peak																																																																																
	Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark																																																																																
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																	
1	2480.00	111.14	-----	-----	94.98	32.40	8.51	34.68	9.93	219	355	Peak																																																																																
Avg	Level (dBuV/m) Date: 2025-10-20  AVG_BE_54 Site : 03CH07-HY Condition: AVG_BE_54 3m HF_ANT_00075962 HORIZONTAL : RBW:1000.000kHz VBW:2.700kHz SMT:Auto <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level</th><th>Ant Factor</th><th>Cable Loss</th><th>Preamp Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>2483.52</td><td>53.68</td><td>54.00</td><td>-0.32</td><td>37.47</td><td>32.44</td><td>8.52</td><td>34.68</td><td>9.93</td><td>219</td><td>355</td><td>Average</td></tr></table>														Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	2483.52	53.68	54.00	-0.32	37.47	32.44	8.52	34.68	9.93	219	355	Average	Level (dBuV/m) Date: 2025-10-20  AVG_54 Site : 03CH07-HY Condition: AVG_54 3m HF_ANT_00075962 HORIZONTAL : RBW:1000.000kHz VBW:2.700kHz SMT:Auto <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level</th><th>Ant Factor</th><th>Cable Loss</th><th>Preamp Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>2480.00</td><td>110.66</td><td>-----</td><td>-----</td><td>94.50</td><td>32.40</td><td>8.51</td><td>34.68</td><td>9.93</td><td>219</td><td>355</td><td>Average</td></tr></table>		Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	2480.00	110.66	-----	-----	94.50	32.40	8.51	34.68	9.93	219	355	Average
		Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark																																																																															
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																	
1	2483.52	53.68	54.00	-0.32	37.47	32.44	8.52	34.68	9.93	219	355	Average																																																																																
	Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark																																																																																
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																	
1	2480.00	110.66	-----	-----	94.50	32.40	8.51	34.68	9.93	219	355	Average																																																																																



Mode	3																																																																																		
	Band Edge																																																																																		
	2400-2483.5_Bluetooth-LE GFSK_CH39_2480MHz																																																																																		
ANT	1																																																																																		
Pol.	Vertical						Fundamental																																																																												
Peak	Level (dBuV/m) Date: 2025-10-20 Site : 03CH07-HY Condition: PEAK_BE_74 3m HF_ANT_00075962 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level</th><th>Ant Factor</th><th>Cable Loss</th><th>Preamp Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1 2484.16</td><td>58.10</td><td>74.00</td><td>-15.90</td><td>41.89</td><td>32.44</td><td>8.52</td><td>34.68</td><td>9.93</td><td>100</td><td>297</td><td>Peak</td></tr></table>						Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1 2484.16	58.10	74.00	-15.90	41.89	32.44	8.52	34.68	9.93	100	297	Peak	Level (dBuV/m) Date: 2025-10-20 Site : 03CH07-HY Condition: PEAK_74 3m HF_ANT_00075962 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level</th><th>Ant Factor</th><th>Cable Loss</th><th>Preamp Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1 2480.00</td><td>106.09</td><td>-----</td><td>-----</td><td>90.73</td><td>32.40</td><td>8.51</td><td>34.68</td><td>9.93</td><td>100</td><td>297</td><td>Peak</td></tr></table>					Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1 2480.00	106.09	-----	-----	90.73	32.40	8.51	34.68	9.93	100	297	Peak
	Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark																																																																							
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																									
1 2484.16	58.10	74.00	-15.90	41.89	32.44	8.52	34.68	9.93	100	297	Peak																																																																								
Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark																																																																								
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																									
1 2480.00	106.09	-----	-----	90.73	32.40	8.51	34.68	9.93	100	297	Peak																																																																								
Avg	Level (dBuV/m) Date: 2025-10-20 Site : 03CH07-HY Condition: AVG_BE_54 3m HF_ANT_00075962 VERTICAL : RBW:1000.000kHz VBW:2.700kHz SMT:Auto <table><tr><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level</th><th>Ant Factor</th><th>Cable Loss</th><th>Preamp Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1 2483.58</td><td>50.07</td><td>54.00</td><td>-3.93</td><td>33.06</td><td>32.44</td><td>8.52</td><td>34.68</td><td>9.93</td><td>100</td><td>297</td><td>Average</td></tr></table>						Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1 2483.58	50.07	54.00	-3.93	33.06	32.44	8.52	34.68	9.93	100	297	Average	Level (dBuV/m) Date: 2025-10-20 Site : 03CH07-HY Condition: AVG_54 3m HF_ANT_00075962 VERTICAL : RBW:1000.000kHz VBW:2.700kHz SMT:Auto <table><tr><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level</th><th>Ant Factor</th><th>Cable Loss</th><th>Preamp Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1 2480.00</td><td>106.42</td><td>-----</td><td>-----</td><td>90.26</td><td>32.40</td><td>8.51</td><td>34.68</td><td>9.93</td><td>100</td><td>297</td><td>Average</td></tr></table>					Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1 2480.00	106.42	-----	-----	90.26	32.40	8.51	34.68	9.93	100	297	Average
Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark																																																																								
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																									
1 2483.58	50.07	54.00	-3.93	33.06	32.44	8.52	34.68	9.93	100	297	Average																																																																								
Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark																																																																								
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																									
1 2480.00	106.42	-----	-----	90.26	32.40	8.51	34.68	9.93	100	297	Average																																																																								



Mode	3																																																																																																																																																																							
	Harmonic																																																																																																																																																																							
	2400-2483.5_Bluetooth-LE GFSK _CH39_2480MHz																																																																																																																																																																							
ANT	1																																																																																																																																																																							
Pol.	Horizontal							Vertical																																																																																																																																																																
Peak Avg	Level (dBuV/m) Date: 2025-10-20 Site : 03CH07-HY Condition: PEAK_74 3m HF_ANT_00075962 HORIZONTAL <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>4960.00</td><td>50.43</td><td>74.00</td><td>-23.57</td><td>61.13</td><td>34.32</td><td>12.14</td><td>58.08</td><td>0.92</td><td>300</td><td>144</td><td></td><td>Peak</td></tr><tr><td>2</td><td>4960.00</td><td>46.03</td><td>54.00</td><td>-7.97</td><td>56.73</td><td>34.32</td><td>12.14</td><td>58.08</td><td>0.92</td><td>300</td><td>144</td><td></td><td>Average</td></tr><tr><td>3</td><td>7440.00</td><td>49.49</td><td>74.00</td><td>-24.51</td><td>55.72</td><td>35.70</td><td>14.87</td><td>57.91</td><td>1.11</td><td>100</td><td>253</td><td></td><td>Peak</td></tr><tr><td>4</td><td>7440.00</td><td>44.35</td><td>54.00</td><td>-9.65</td><td>50.58</td><td>35.70</td><td>14.87</td><td>57.91</td><td>1.11</td><td>100</td><td>253</td><td></td><td>Average</td></tr></table>								Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	4960.00	50.43	74.00	-23.57	61.13	34.32	12.14	58.08	0.92	300	144		Peak	2	4960.00	46.03	54.00	-7.97	56.73	34.32	12.14	58.08	0.92	300	144		Average	3	7440.00	49.49	74.00	-24.51	55.72	35.70	14.87	57.91	1.11	100	253		Peak	4	7440.00	44.35	54.00	-9.65	50.58	35.70	14.87	57.91	1.11	100	253		Average	Level (dBuV/m) Date: 2025-10-20 Site : 03CH07-HY Condition: PEAK_74 3m HF_ANT_00075962 VERTICAL <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>4960.00</td><td>48.95</td><td>74.00</td><td>-25.05</td><td>59.65</td><td>34.32</td><td>12.14</td><td>58.08</td><td>0.92</td><td>100</td><td>269</td><td></td><td>Peak</td></tr><tr><td>2</td><td>4960.00</td><td>44.11</td><td>54.00</td><td>-9.89</td><td>54.81</td><td>34.32</td><td>12.14</td><td>58.08</td><td>0.92</td><td>100</td><td>269</td><td></td><td>Average</td></tr><tr><td>3</td><td>7440.00</td><td>44.13</td><td>74.00</td><td>-29.87</td><td>50.36</td><td>35.70</td><td>14.87</td><td>57.91</td><td>1.11</td><td>--</td><td>--</td><td></td><td>Peak</td></tr></table>								Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	4960.00	48.95	74.00	-25.05	59.65	34.32	12.14	58.08	0.92	100	269		Peak	2	4960.00	44.11	54.00	-9.89	54.81	34.32	12.14	58.08	0.92	100	269		Average	3	7440.00	44.13	74.00	-29.87	50.36	35.70	14.87	57.91	1.11	--	--		Peak
		Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																																										
		MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																																																																											
1	4960.00	50.43	74.00	-23.57	61.13	34.32	12.14	58.08	0.92	300	144		Peak																																																																																																																																																											
2	4960.00	46.03	54.00	-7.97	56.73	34.32	12.14	58.08	0.92	300	144		Average																																																																																																																																																											
3	7440.00	49.49	74.00	-24.51	55.72	35.70	14.87	57.91	1.11	100	253		Peak																																																																																																																																																											
4	7440.00	44.35	54.00	-9.65	50.58	35.70	14.87	57.91	1.11	100	253		Average																																																																																																																																																											
	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																																											
	MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																																																																												
1	4960.00	48.95	74.00	-25.05	59.65	34.32	12.14	58.08	0.92	100	269		Peak																																																																																																																																																											
2	4960.00	44.11	54.00	-9.89	54.81	34.32	12.14	58.08	0.92	100	269		Average																																																																																																																																																											
3	7440.00	44.13	74.00	-29.87	50.36	35.70	14.87	57.91	1.11	--	--		Peak																																																																																																																																																											



Mode	4																																																																																																																																																																																																																																													
	LF																																																																																																																																																																																																																																													
	2400-2483.5_Bluetooth-LE GFSK _CH39_2480MHz																																																																																																																																																																																																																																													
ANT	1																																																																																																																																																																																																																																													
Pol.	Horizontal							Vertical																																																																																																																																																																																																																																						
QPI Peak	Level (dBuV/m) Date: 2025-10-21 Site : 03CH07-HY Condition: QP 3m Bilog_35419 HORIZONTAL <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th></th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>31.94</td><td>21.86</td><td>40.00</td><td>-18.14</td><td></td><td>27.73</td><td>23.07</td><td>1.05</td><td>29.99</td><td>0.00</td><td>--</td><td>--</td><td>Peak</td></tr><tr><td>2</td><td>91.11</td><td>26.28</td><td>43.50</td><td>-17.22</td><td></td><td>39.57</td><td>14.94</td><td>1.71</td><td>29.94</td><td>0.00</td><td>--</td><td>--</td><td>Peak</td></tr><tr><td>3</td><td>278.56</td><td>35.93</td><td>46.00</td><td>-10.07</td><td></td><td>43.92</td><td>18.96</td><td>2.88</td><td>29.83</td><td>0.00</td><td>--</td><td>--</td><td>Peak</td></tr><tr><td>4</td><td>323.91</td><td>32.01</td><td>46.00</td><td>-13.99</td><td></td><td>39.22</td><td>19.51</td><td>3.14</td><td>29.86</td><td>0.00</td><td>--</td><td>--</td><td>Peak</td></tr><tr><td>5</td><td>378.23</td><td>30.69</td><td>46.00</td><td>-15.31</td><td></td><td>36.24</td><td>21.00</td><td>3.34</td><td>29.89</td><td>0.00</td><td>--</td><td>--</td><td>Peak</td></tr><tr><td>6</td><td>941.80</td><td>29.07</td><td>46.00</td><td>-16.93</td><td></td><td>22.55</td><td>30.05</td><td>5.29</td><td>28.82</td><td>0.00</td><td>--</td><td>--</td><td>Peak</td></tr></table>								Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB		dBuV	dB/m	dB	dB	dB	dB	cm	deg	1	31.94	21.86	40.00	-18.14		27.73	23.07	1.05	29.99	0.00	--	--	Peak	2	91.11	26.28	43.50	-17.22		39.57	14.94	1.71	29.94	0.00	--	--	Peak	3	278.56	35.93	46.00	-10.07		43.92	18.96	2.88	29.83	0.00	--	--	Peak	4	323.91	32.01	46.00	-13.99		39.22	19.51	3.14	29.86	0.00	--	--	Peak	5	378.23	30.69	46.00	-15.31		36.24	21.00	3.34	29.89	0.00	--	--	Peak	6	941.80	29.07	46.00	-16.93		22.55	30.05	5.29	28.82	0.00	--	--	Peak	Level (dBuV/m) Date: 2025-10-21 Site : 03CH07-HY Condition: QP 3m Bilog_35419 VERTICAL <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th></th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>31.94</td><td>33.23</td><td>40.00</td><td>-6.77</td><td></td><td>39.10</td><td>23.07</td><td>1.05</td><td>29.99</td><td>0.00</td><td>--</td><td>--</td><td>Peak</td></tr><tr><td>2</td><td>40.67</td><td>30.48</td><td>40.00</td><td>-9.52</td><td></td><td>40.09</td><td>19.23</td><td>1.18</td><td>30.02</td><td>0.00</td><td>--</td><td>--</td><td>Peak</td></tr><tr><td>3</td><td>100.81</td><td>24.72</td><td>43.50</td><td>-18.78</td><td></td><td>36.66</td><td>16.19</td><td>1.80</td><td>29.93</td><td>0.00</td><td>--</td><td>--</td><td>Peak</td></tr><tr><td>4</td><td>269.59</td><td>32.48</td><td>46.00</td><td>-13.52</td><td></td><td>40.38</td><td>19.06</td><td>2.87</td><td>29.83</td><td>0.00</td><td>--</td><td>--</td><td>Peak</td></tr><tr><td>5</td><td>323.91</td><td>30.07</td><td>46.00</td><td>-15.93</td><td></td><td>37.28</td><td>19.51</td><td>3.14</td><td>29.86</td><td>0.00</td><td>--</td><td>--</td><td>Peak</td></tr><tr><td>6</td><td>959.26</td><td>30.37</td><td>46.00</td><td>-15.63</td><td></td><td>22.82</td><td>30.90</td><td>5.35</td><td>28.70</td><td>0.00</td><td>--</td><td>--</td><td>Peak</td></tr></table>								Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB		dBuV	dB/m	dB	dB	dB	dB	cm	deg	1	31.94	33.23	40.00	-6.77		39.10	23.07	1.05	29.99	0.00	--	--	Peak	2	40.67	30.48	40.00	-9.52		40.09	19.23	1.18	30.02	0.00	--	--	Peak	3	100.81	24.72	43.50	-18.78		36.66	16.19	1.80	29.93	0.00	--	--	Peak	4	269.59	32.48	46.00	-13.52		40.38	19.06	2.87	29.83	0.00	--	--	Peak	5	323.91	30.07	46.00	-15.93		37.28	19.51	3.14	29.86	0.00	--	--	Peak	6	959.26	30.37	46.00	-15.63		22.82	30.90	5.35	28.70	0.00	--	--	Peak
		Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																																																																																																																
		MHz	dBuV/m	dBuV/m	dB		dBuV	dB/m	dB	dB	dB	dB	cm	deg																																																																																																																																																																																																																																
1	31.94	21.86	40.00	-18.14		27.73	23.07	1.05	29.99	0.00	--	--	Peak																																																																																																																																																																																																																																	
2	91.11	26.28	43.50	-17.22		39.57	14.94	1.71	29.94	0.00	--	--	Peak																																																																																																																																																																																																																																	
3	278.56	35.93	46.00	-10.07		43.92	18.96	2.88	29.83	0.00	--	--	Peak																																																																																																																																																																																																																																	
4	323.91	32.01	46.00	-13.99		39.22	19.51	3.14	29.86	0.00	--	--	Peak																																																																																																																																																																																																																																	
5	378.23	30.69	46.00	-15.31		36.24	21.00	3.34	29.89	0.00	--	--	Peak																																																																																																																																																																																																																																	
6	941.80	29.07	46.00	-16.93		22.55	30.05	5.29	28.82	0.00	--	--	Peak																																																																																																																																																																																																																																	
	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																																																																																																																	
	MHz	dBuV/m	dBuV/m	dB		dBuV	dB/m	dB	dB	dB	dB	cm	deg																																																																																																																																																																																																																																	
1	31.94	33.23	40.00	-6.77		39.10	23.07	1.05	29.99	0.00	--	--	Peak																																																																																																																																																																																																																																	
2	40.67	30.48	40.00	-9.52		40.09	19.23	1.18	30.02	0.00	--	--	Peak																																																																																																																																																																																																																																	
3	100.81	24.72	43.50	-18.78		36.66	16.19	1.80	29.93	0.00	--	--	Peak																																																																																																																																																																																																																																	
4	269.59	32.48	46.00	-13.52		40.38	19.06	2.87	29.83	0.00	--	--	Peak																																																																																																																																																																																																																																	
5	323.91	30.07	46.00	-15.93		37.28	19.51	3.14	29.86	0.00	--	--	Peak																																																																																																																																																																																																																																	
6	959.26	30.37	46.00	-15.63		22.82	30.90	5.35	28.70	0.00	--	--	Peak																																																																																																																																																																																																																																	



Appendix D. Duty Cycle Plots

Band	Duty Cycle (%)	T(us)	1/T(kHz)	VBW Setting
Bluetooth - LE for 1Mbps	31.85	400	2.50	2.7kHz

