



427 West 12800 South
Draper, UT 84020

Test Report Certification

FCC ID	SWX-UTR
ISED ID	6545A-UTR
Equipment Under Test	UTR
Test Report Serial Number	TR10557_01
Date of Test(s)	14, 21, 24, 27 October; 4 December 2025
Report Issue Date	5 December 2025

Test Specification	Applicant
47 CFR FCC Part 15, Subpart E RSS-247, Issue 3 (August 2023)	Ubiquiti Inc. 685 Third Avenue New York, NY 10017 U.S.A.



NVLAP LAB CODE 600241-0

Certification of Engineering Report


This report has been prepared by Unified Compliance Laboratory (UCL) to document compliance of the device described below with the requirement of Federal Communication Commissions (FCC) Part 15, Subpart E. This report may be reproduced in full. Partial reproduction of this report may only be made with the written consent of the laboratory. The results in this report apply only to the sample tested with the specifications provided by the manufacturer.

Applicant	Ubiquiti Inc.
Manufacturer	Ubiquiti Inc.
Brand Name	UBIQUITI
Model Number	UTR
FCC ID	SWX-UTR
ISED ID	6545A-UTR

On this 5th day of December 2025, I individually and for Unified Compliance Laboratory certify that the statements made in this engineering report are true, complete, and correct to the best of my knowledge and are made in good faith. Unified Compliance laboratory is not responsible for incorrect information provided by the manufacturer.

Although NVLAP has accredited the Unified Compliance Laboratory testing facilities, this report must not be used to claim product certification, approval, or endorsement by NVLAP, NIST or any agency of the U.S. federal government.

Unified Compliance Laboratory


Written By: Joseph W. Jackson
Reviewed By: Kimberly DeBole

Revision History		
Revision	Description	Date
01	Original Report Release	12/05/2025

Table of Contents

1	Client Information.....	5
1.1	Applicant.....	5
1.2	Manufacturer.....	5
2	Equipment Under Test (EUT).....	6
2.1	Identification of EUT	6
2.2	Description of EUT	6
2.3	EUT and Support Equipment	7
2.4	Interface Ports on EUT	7
2.5	Operating Environment.....	7
2.6	Operating Modes.....	8
2.7	EUT Exercise Software.....	8
2.8	Block Diagram of Test Configuration	8
2.9	Modification Incorporated/Special Accessories on EUT.....	8
2.10	Deviation, Opinions Additional Information or Interpretations from Test Standard.....	8
3	Test Specification, Method and Procedures.....	9
3.1	Test Specification.....	9
3.2	Methods & Procedures.....	9
3.3	FCC Part 15, Subpart E.....	9
3.4	Results.....	9
3.5	Test Location	10
4	Test Equipment	11
4.1	Conducted Emissions at Mains Ports.....	11
4.2	Direct Connect at the Antenna Port Tests.....	11
4.3	Radiated Emissions	12
4.4	Equipment Calibration	13
4.5	Measurement Uncertainty	13
5	Test Results.....	14
5.1	§15.203 Antenna Requirements.....	14
5.2	§15.207 Conducted Emissions at Mains Ports Data	15
5.3	§15.407(a) 26 dB Emissions Bandwidth.....	17
5.4	§15.407(a) Maximum Average Output Power	18
5.5	§15.209 Spurious Emissions	20
5.6	§15.407(a) Maximum Power Spectral Density	31

1 Client Information

1.1 Applicant

Company	Ubiquiti Inc. 685 Third Avenue New York, NY 10017 U.S.A.
Contact Name	Alex Macon
Title	Compliance

1.2 Manufacturer

Company	Ubiquiti Inc. 685 Third Avenue New York, NY 10017 U.S.A.
Contact Name	Alex Macon
Title	Compliance

2 Equipment Under Test (EUT)

2.1 Identification of EUT

Brand Name	UBIQUITI
Model Number	UTR
Serial Number	DA9F92
Dimensions (cm)	6.5 x 9.6 x 1.3

2.2 Description of EUT

The UniFi Travel Router (UTR) is a compact travel router and VPN functionality for secure connections on the go. The UTR has 2x2 2.4 GHz and 2x2 5GHz dual-band wireless transmitters. The UTR has a Bluetooth transmitter for management control. The UTR is an indoor device and is powered from a USB-C power port.

For CDD transmission, direction gain is calculated as follows.

Array Gain = $10 \log(\text{NANT}/\text{NSS})$ dB

NANT = number of transmit antennas and NSS = number of spatial streams. NSS = 1 considered worst case. For power measurements on IEEE 802.11 devices, Array Gain = 0 dB for $\text{NANT} \leq 4$;

For PSD measurements when $\text{Nss}=1$: Array Gain = $10 \log(\text{NANT}/\text{NSS})$ dB + Antenna Gain (dBi). Or 3.01 dB + 5 dBi = 8.01 dBi.

This report covers the circuitry of the device subject to FCC Part 15, Subpart E. The circuitry of the device subject to FCC Part 15 Subpart B was found to be compliant and is covered under a separate Unified Compliance Laboratory test report.

Band	WiFi Mode	Modulation Bandwidth	Modulation Type	Frequency (MHz)
UNII-1	a	20 MHz	OFDM	5180, 5200, 5210, 5240
	ac	20 MHz	VHT	5180, 5200, 5210, 5240
	ac	40 MHz	VHT	5190, 5230
	ac	80 MHz	VHT	5210

2.3 EUT and Support Equipment

The EUT and support equipment used during the test are listed below.

Brand Name Model Number Serial Number	Description	Name of Interface Ports / Interface Cables
BN: UBIQUITI MN: UTR (Note 1) SN: DA9F92	Wireless Router	See Section 2.4
BN: UBIQUITI MN: E005-1I050100VU SN: N/A	USB Power Adapter	2 Conductor power cord to AC mains/80cm
BN: Dell MN: XPS 13 SN: N/A	Laptop Personal Computer	Unshielded Cat 5e cable/3 meters

Notes: (1) EUT

(2) Interface port connected to EUT (See Section 2.4)

The support equipment listed above was not modified in order to achieve compliance with this standard.

2.4 Interface Ports on EUT

Name of Ports	No. of Ports Fitted to EUT	Cable Description/Length
USB-C Power	1	2 conductor power to AC mains/80cm
USB-C Passthrough	1	USB-C cable/3 meters
Ethernet	2	Unshielded Cat 5e cable/3 meters

2.5 Operating Environment

Power Supply	120 Volts AC Main to USB-C
AC Mains Frequency	60 Hz
Temperature	21.3 - 23.2 °C
Humidity	25.3 - 30.7 %
Barometric Pressure	1014 mBar

2.6 Operating Modes

The UTR was tested using test software in order to enable a constant transmission. The measurements within this report are corrected to reference a 100% duty cycle. All emission modes of 802.11 a/ac were investigated. All measurements are reported with the worst-case mode (802.11ac maximum conducted output power and maximum power spectral density) unless otherwise stated.

2.7 EUT Exercise Software

EUT firmware version 1.0 was used to operate the transmitter using a constant transmit mode.

2.8 Block Diagram of Test Configuration




Diagram 1: Test Configuration Block Diagram

2.9 Modification Incorporated/Special Accessories on EUT

There were no modifications made to the EUT during testing to comply with the specification.

2.10 Deviation, Opinions Additional Information or Interpretations from Test Standard

There were no deviations, opinions, additional information or interpretations from the test specification.

3 Test Specification, Method and Procedures

3.1 Test Specification

Title	47 CFR FCC Part 15, Subpart E, Section 15.407 Limits and methods of measurement of radio interference characteristics of Unlicensed National Information Infrastructure Devices
Purpose of Test	The tests were performed to demonstrate initial compliance

3.2 Methods & Procedures

3.2.1 47 CFR FCC Part 15 Section 15.407

See test standard for details.

3.3 FCC Part 15, Subpart E

3.3.1 Summary of Tests

FCC Section	ISED Section	Environmental Phenomena	Frequency Range (MHZ)	Result
15.203	N/A	Antenna requirements	Structural Requirement	Compliant
15.207	RSS-Gen	Conducted Disturbance at Mains Port	0.15 to 30	Compliant
15.407(a)	RSS-247 §6.2.2	Bandwidth Requirement	5180 to 5210	Compliant
15.407(a)	RSS-247 §6.2.2, §6.2.3	Peak Output Power	5180 to 5210	Compliant
15.407(b)	RSS-247 §6.2.2, §6.2.3	Antenna Conducted Spurious Emissions	0.009 to 40000	N/A Note ¹
15.209	RSS-247 §6.2.2, §6.2.3	Radiated Spurious Emissions	0.009 to 40000	Compliant
15.407(a)	RSS-247 §6.2.2, §6.2.3	Peak Power Spectral Density	5180 to 5210	Compliant
The testing was performed according to the procedures in ANSI C63.10-2013, KDB 789033 and 47 CFR Part 15. Where applicable, KDB 662911 was followed to sum required measurements. Note ¹ : Radiated Spurious was performed per 15.209 with the antenna unterminated.				

3.4 Results

In the configuration tested, the EUT complied with the requirements of the specification.

3.5 Test Location

Testing was performed at the Unified Compliance Laboratory 3-Meter and 10-Meter chambers located at 427 West 12800 South, Draper, UT 84020. Unified Compliance Laboratory is accredited by National Voluntary Laboratory Accreditation Program (NVLAP); NVLAP Code 600241-0 which is effective until 30 June 2026. This site has also been registered with Innovations, Science and Economic Development (ISED) department as was accepted under Appendix B, Phase 1 procedures of the APEC Tel MRA for Canadian recognition. ISED No.: 25346, effective until 30 June 2026.

Unified Compliance Laboratory has been assigned Registration Number 376708 by the FCC, MRA Designation Number US5037 and Conformity Assessment Number US0223 by ISED.

4 Test Equipment

4.1 Conducted Emissions at Mains Ports

Type of Equipment	Manufacturer	Model Number	Asset Number	Date of Last Calibration	Due Date of Calibration
EMI Receiver	AFJ	FFT3010	UCL-6754	2/27/2025	2/27/2026
LISN	AFJ	LS16C/10	UCL-6749	3/3/2025	3/3/2026
ISN	Teseq	ISN T800	UCL-2971	3/31/2025	3/31/2026
AC Power Source	Laplace Instruments	AC1000A	UCL-2857	N/A	N/A
Test Software	AFJ	AFJ FFT3010	UCL-3107	N/A	N/A

Table 1: List of equipment used for Conducted Emissions Testing at Mains Port




Figure 1: Conducted Emissions Test

4.2 Direct Connect at the Antenna Port Tests

Type of Equipment	Manufacturer	Model Number	Asset Number	Date of Last Calibration	Due Date of Calibration
Spectrum Analyzer	R&S	FSV40	UCL-2861	1/16/2025	1/16/2026
Signal Generator	R&S	SMB100A	UCL-2864	N/A	N/A
Vector Signal Generator	R&S	SMBV100A	UCL-2873	N/A	N/A
Switch Extension	R&S	OSP-B157WX	UCL-2867	4/28/2025	1/16/2026
Switch Extension	R&S	OSP-150W	UCL-2870	4/28/2025	1/16/2026
Test Software	R&S	EMC32	UCL-9442	--	--

Table 2: List of equipment used for Direct Connect at the Antenna Port




Figure 2: Direct Connect at the Antenna Port Test



Figure 3: Output Power Measurement

4.3 Radiated Emissions

Type of Equipment	Manufacturer	Model Number	Asset Number	Date of Last Calibration	Due Date of Calibration
EMI Receiver	Keysight	N9038A	UCL-2778	12/27/2024	12/27/2025
Pre-Amplifier 9 kHz – 1 GHz	Sonoma Instruments	310N	UCL-2889	1/19/2024	1/19/2026
Broadband Antenna	ETS-Lindgren	3142E	UCL-9782	2/6/2025	2/6/2026
Double Ridge Horn Antenna	Scwarzbeck	BBHA 9120D	UCL-3065	4/2/2025	4/2/2027
Log Periodic	Scwarzbeck	STLP 9129	UCL-3068	2/11/2025	2/4/2027
10 - 40 GHz Horn Antenna	ETS-Lindgren	3116C	UCL-7209	6/6/2024	6/6/2026
1 – 18 GHz Amplifier	Com-Power	PAM 118A	UCL-3833	7/22/2025	7/22/2026
Test Software	Nexio	BatEMC	UCL-5253 & UCL- 5249	N/A	N/A

Table 3: List of equipment used for Radiated Emissions




Figure 4: Radiated Emissions Test

4.4 Equipment Calibration

All applicable equipment is calibrated using either an independent calibration laboratory or Unified Compliance Laboratory personnel at intervals defined in ANSI C63.4:2014 following outlined calibration procedures. All measurement instrumentation is traceable to the National Institute of Standards and Technology (NIST). Supporting documentation relative to traceability is on file and is available for examination upon request.

4.5 Measurement Uncertainty

Test	Uncertainty ($\pm$ dB)	Confidence (%)
Conducted Emissions	1.44	95
Radiated Emissions (9 kHz to 30 MHz)	2.50	95
Radiated Emissions (30 MHz to 1 GHz)	4.38	95
Radiated Emissions (1 GHz to 18 GHz)	4.37	95
Radiated Emissions (18 GHz to 40 GHz)	3.93	95
Direct Connect Tests	K Factor	Value
Emissions Bandwidth	2	2.0%
Output Power	2	1.0 dB
Peak Power Spectral Density	2	1.3 dB
Band Edge	2	0.8 dB
Transmitter Spurious Emissions	2	1.8 dB

5 Test Results

5.1 §15.203 Antenna Requirements

The EUT uses an integrated internal antenna. Per the manufacturer, the Maximum gain of the antenna per chain is 5 dBi. This is an 802.11 device and utilizes CDD as described in KDB 662911 D01. The antenna is not user replaceable.


See Section 2.2 for directional gain calculation.

Results

The EUT complied with the specification


5.2 §15.207 Conducted Emissions at Mains Ports Data

5.2.1 Line



ID	Frequency	Probe	Cable	Atten.	Detector	Meter Read	Meas Level	Limit 1	Limit 1 Dist.	Limit 2	Limit 2 Dist.	P/F
MU	MHz	dB	dB	dB	Type	dBμV	dBμV	dBμV	dB	dBμV	dB	P/F
1	465,000kHz	9.49			QPeak	34.87	44.36	56.60	-12.25			
3	876,000kHz	9.54			QPeak	33.26	42.80	56.00	-13.20			
5	1.068	9.58			QPeak	32.98	42.56	56.00	-13.44			
2	468,000kHz	9.49			C_AVG	29.83	39.32			46.55	-7.23	
4	909,000kHz	9.55			C_AVG	23.71	33.26			46.00	-12.74	
6	1.098	9.58			C_AVG	23.62	33.20			46.00	-12.80	

5.2.2 Neutral



ID	Frequency	Probe	Cable	Atten.	Detector	Meter Read	Meas Level	Limit 1	Limit 1 Dist.	Limit 2	Limit 2 Dist.	P/F
MU	MHz	dB	dB	dB	Type	dBμV	dBμV	dBμV	dB	dBμV	dB	P/F
1	498,000kHz	9.64			QPeak	34.36	44.00	56.03	-12.03			
3	1.041	9.56			QPeak	33.75	43.31	56.00	-12.69			
5	876,000kHz	9.52			QPeak	33.67	43.19	56.00	-12.81			
2	495,000kHz	9.64			C_AVG	26.79	36.43			46.08	-9.66	
4	1.071	9.56			C_AVG	24.17	33.73			46.00	-12.27	
6	909,000kHz	9.53			C_AVG	24.44	33.97			46.00	-12.03	

Result

The EUT complied with the specification limit.

5.3 §15.407(a) 26 dB Emissions Bandwidth

All chains were measured under the guidance of KDB 789033 Section II.C. and KDB 662911 D01. Please see associated annex for details on instrument settings.

Nominal BW (MHz)	Frequency (MHz)	99% Bandwidth (MHz)	Emissions 26 dB Bandwidth (MHz)
OFDM 20	5180	17.2	30.8
OFDM 20	5210	28.3	42.9
OFDM 20	5240	28.3	42.2
VHT 20	5180	35.8	68.5
VHT 20	5210	31.0	49.0
VHT 20	5240	29.0	48.0
VHT 40	5190	66.0	110.0
VHT 40	5230	60.0	107.0
VHT 80	5210	95.0	198.0

Result

All chains were tested and the highest bandwidth per chain is reported above. Please see Annex for all bandwidth measurements.

5.4 §15.407(a) Maximum Average Output Power

All chains were measured and summed under the guidance of KDB 789033 Section II. E.2. and KDB 662911 D01. Please see associated annex for details on instrument settings.

The maximum average RF conducted output power measured for this device was 24.16 dBm or 260.62 mW. The limit is 30 dBm, or 1 Watt when using an antenna with 6 dBi (indoor/outdoor access point) or less gain. The antenna has a gain of 5 dBi.

See Section 2.2 for directional gain calculation.

Nss>1

Modulation (BW)	Frequency (MHz)	Data Rate	TP Setting	Total Summed Output Power* (dBm)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Margin (dBm)
OFDM 20	5180	Mcs0_Nss2	36	19.55	5	24.55	36	-11.45
OFDM 20	5210	Mcs0_Nss2	45	24.16	5	29.16	36	-6.84
OFDM 20	5240	Mcs0_Nss2	45	23.86	5	28.86	36	-7.14
VHT 20	5180	Mcs0_Nss2	45	24.09	5	29.09	36	-6.91
VHT 20	5210	Mcs0_Nss2	45	24.08	5	29.08	36	-6.92
VHT 20	5240	Mcs0_Nss2	45	23.66	5	28.66	36	-7.34
VHT 40	5190	Mcs0_Nss2	45	24.29	5	29.29	36	-6.71
VHT 40	5230	Mcs0_Nss2	45	24.43	5	29.43	36	-6.57
VHT 80	5210	Mcs0_Nss2	45	23.54	5	28.54	36	-7.46

Nss=1

Modulation (BW)	Frequency (MHz)	Data Rate	TP Setting	Total Summed Output Power* (dBm)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Margin (dBm)
OFDM 20	5180	Mcs0_Nss1	36	19.55	5	24.55	36	-11.45
OFDM 20	5210	Mcs0_Nss1	45	24.16	5	29.16	36	-6.84
OFDM 20	5240	Mcs0_Nss1	45	23.86	5	28.86	36	-7.14
VHT 20	5180	Mcs0_Nss1	45	24.09	5	29.09	36	-6.91
VHT 20	5210	Mcs0_Nss1	45	24.08	5	29.08	36	-6.92
VHT 20	5240	Mcs0_Nss1	45	23.66	5	28.66	36	-7.34
VHT 40	5190	Mcs0_Nss1	45	24.29	5	29.29	36	-6.71
VHT 40	5230	Mcs0_Nss1	45	24.43	5	29.43	36	-6.57
VHT 80	5210	Mcs0_Nss1	45	23.54	5	28.54	36	-7.46

Canada (Indoor Use Only)

Modulation (BW)	Frequency (MHz)	Data Rate	TP Setting	Total Summed Output Power* (dBm)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Margin (dBm)
OFDM 20	5180	Mcs0_Nss2	30	17.09	5	22.09	23	-0.91
OFDM 20	5210	Mcs0_Nss2	31	17.47	5	22.47	23	-0.53
OFDM 20	5240	Mcs0_Nss2	31	16.96	5	21.96	23	-1.04
VHT 20	5180	Mcs0_Nss2	31	17.55	5	22.55	23	-0.45
VHT 20	5210	Mcs0_Nss2	31	17.50	5	22.50	23	-0.50
VHT 20	5240	Mcs0_Nss2	32	17.86	5	22.86	23	-0.14
VHT 40	5190	Mcs0_Nss2	31	17.77	5	22.77	23	-0.23
VHT 40	5230	Mcs0_Nss2	31	17.54	5	22.54	23	-0.46
VHT 80	5210	Mcs0_Nss2	32	17.65	5	22.65	23	-0.35

Result

In the configuration tested, the maximum summed average RF output power was less than 1 watt; therefore, the EUT complied with the requirements of the specification (see spectrum analyzer plots in attached Annex).

* Gated EIRP shown in the Annex is the conducted measurement.

5.5 §15.209 Spurious Emissions


5.5.1 Radiated Spurious Emissions in the Restricted Bands of § 15.205

The EUT uses various power settings based on the channel in use. In order to reduce test time, the radiated spurious emissions at the lowest, middle, and highest channel were measured at the maximum power of TP45, as this setting was found to be worst case for spurious emissions. Power was subsequently reduced during in-band and band edge testing. The band edge at the restricted band ending at 5180 MHz was measured using radiated measurement or conducted at the antenna port methods. [For radiated] All emissions modes were tested, and the worst-case measurement are shown below. For frequencies above 1 GHz, a measurement of 3 meters was used. For frequencies below 1 GHz, a measurement distance of 10 meters was used.

Correction Factor = Antenna Factor (dBi) + Cable Loss (dB) - Pre-Amplifier Gain (dB), and is added to the Receiver reading.

Result

All emissions in the restricted bands of § 15.205 met the limits specified in § 15.209; therefore, the EUT complies with the specification. All emissions met the limits specified in § 15.407(b). Representative band edge plots are included in this report.




QuasiPeak

Frequency	Level (dBµV/m)	Limit (dBµV/m)	Margin	Azimuth (°)	Height	Pol.	Correction (dB)
37.86 MHz	25.08	30.0	-4.92	76	4	Vertical	-14.08
43.39 MHz	25.24	30.0	-4.76	177	1.76	Vertical	-12.10
46.20 MHz	24.16	30.0	-5.84	357	2.02	Vertical	-11.85
55.03 MHz	20.51	30.0	-9.49	2783	3.88	Vertical	-12.01
80.94 MHz	23.44	30.0	-6.56	197	4	Vertical	-18.40
90.06 MHz	21.63	30.0	-8.37	2	2.32	Vertical	-15.55

Note: No significant emissions were observed in the Horizontal orientation of the antenna

Table 4: Radiated Emissions 30 – 1000 MHz




Peak

Frequency	Level (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Azimuth (°)	Height (m)	Pol.	Correction (dB)
14.30 GHz	54.81	74.0	-19.19	348	3.861	Vertical	11.09
16.74 GHz	53.83	74.0	-20.17	89	3.857	Vertical	11.61
Note: No significant emissions were observed in the Horizontal orientation of the antenna							

Avg

Frequency	Level (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Azimuth (°)	Height (m)	Pol.	Correction (dB)
14.30 GHz	41.15	54.0	-12.85	348	3.861	Vertical	11.09
16.74 GHz	40.56	54.0	-13.44	89	3.857	Vertical	11.61
Note: No significant emissions were observed in the Horizontal orientation of the antenna							

Table 5: Radiated Emissions 1 – 17 GHz at the Lowest Frequency




Peak

Frequency	Level (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Azimuth (°)	Height (m)	Pol.	Correction (dB)
14.82 GHz	54.86	74.0	-19.14	248	1.5	Vertical	11.79
16.81 GHz	54.53	74.0	-19.47	226	2.65	Vertical	11.57
Note: No significant emissions were observed in the Horizontal orientation of the antenna							

Avg

Frequency	Level (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Azimuth (°)	Height (m)	Pol.	Correction (dB)
14.82 GHz	41.96	54.0	-12.04	248	1.5	Vertical	11.79
16.81 GHz	40.82	54.0	-13.18	226	2.65	Vertical	11.57
Note: No significant emissions were observed in the Horizontal orientation of the antenna							

Table 6: Radiated Emissions 1 – 17 GHz at the Middle Frequency




Peak

Frequency	Level (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Azimuth (°)	Height (m)	Pol.	Correction (dB)
14.84 GHz	54.65	74.0	-19.35	180	2.142	Vertical	11.75
16.87 GHz	54.10	74.0	-19.90	17	1.847	Vertical	11.81
Note: No significant emissions were observed in the Horizontal orientation of the antenna							

Avg

Frequency	Level (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Azimuth (°)	Height (m)	Pol.	Correction (dB)
14.84 GHz	41.86	54.0	-12.14	180	2.142	Vertical	11.75
16.87 GHz	41.08	54.0	-12.92	17	1.847	Vertical	11.81
Note: No significant emissions were observed in the Horizontal orientation of the antenna							

Table 7: Radiated Emissions 1 – 17 GHz at the Highest Frequency



Peak


Frequency	Level (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Azimuth (°)	Pol.	Correction (dB)
16.54 GHz	53.42	74.0	-20.58	8	Vertical	3.18
20.85 GHz	54.81	74.0	-19.19	51	Vertical	1.27
27.61 GHz	55.55	74.0	-18.45	355	Vertical	3.59
33.44 GHz	55.60	74.0	-18.40	28	Vertical	4.76
36.35 GHz	59.09	74.0	-14.91	296	Vertical	6.97
39.51 GHz	60.17	74.0	-13.83	248	Vertical	6.93
16.52 GHz	54.31	74.0	-19.69	133	Horizontal	3.07
18.84 GHz	52.75	74.0	-21.25	191	Horizontal	1.42
20.84 GHz	57.30	74.0	-16.70	260	Horizontal	1.44
27.62 GHz	55.54	74.0	-18.46	258	Horizontal	3.59

Avg


Frequency	Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Azimuth (°)	Pol.	Correction (dB)
16.54 GHz	40.22	54.0	-13.78	8	Vertical	3.18
20.85 GHz	38.55	54.0	-15.45	51	Vertical	1.27
27.61 GHz	41.35	54.0	-12.65	355	Vertical	3.59
33.44 GHz	41.52	54.0	-12.48	28	Vertical	4.76
36.35 GHz	41.97	74.0	-12.03	296	Vertical	6.97
39.51 GHz	44.76	74.0	-9.24	248	Vertical	6.93
16.52 GHz	40.16	54.0	-13.84	133	Horizontal	3.07
18.84 GHz	39.15	54.0	-14.85	191	Horizontal	1.42
20.84 GHz	39.46	54.0	-14.54	260	Horizontal	1.44
27.62 GHz	40.94	54.0	-13.06	258	Horizontal	3.59

Table 8: Radiated Emissions 17 – 26 GHz at the Middle Frequency (worse case)


5.5.2 Band Edge




Graph 1: Band Edge Low a Mode 20 MHz




Graph 2: Band Edge High a Mode 20 MHz




Graph 3: Band Edge Low ac Mode 20 MHz




Graph 4: Band Edge High ac Mode 20 MHz



Graph 5: Band Edge Low ac Mode 40 MHz



Graph 6: Band Edge High ac Mode 40 MHz



Graph 7: Band Edge ac Mode 80 MHz

5.6 §15.407(a) Maximum Power Spectral Density

All chains were measured and summed under the guidance of KDB 789033 Section II. F. and KDB 662911 D01. Please see associated annex for details on instrument settings.

The maximum average power spectral density conducted from the intentional radiator of the antenna shall not be greater than 17 dBm in any 1 MHz band during any time interval of continuous transmission.

See Section 2.2 for directional gain calculation.

Results of this testing are summarized.

Nss>1

Modulation (BW)	Freq. (MHz)	Data Rate	TP Setting	Total Sum PSD EIRP (dBm)	Antenna Gain (dBi)	Limit (dBm)	Margin (dBm)
OFDM 20	5180	Mcs0_Nss2	36	7.35	5	17	-9.65
OFDM 20	5210	Mcs0_Nss2	45	11.98	5	17	-5.02
OFDM 20	5240	Mcs0_Nss2	45	11.57	5	17	-5.43
VHT 20	5180	Mcs0_Nss2	45	11.04	5	17	-5.96
VHT 20	5210	Mcs0_Nss2	45	11.14	5	17	-5.86
VHT 20	5240	Mcs0_Nss2	45	10.29	5	17	-6.71
VHT 40	5190	Mcs0_Nss2	45	8.45	5	17	-8.55
VHT 40	5230	Mcs0_Nss2	45	9.12	5	17	-7.88
VHT 80	5210	Mcs0_Nss2	45	4.88	5	17	-12.12

Nss=1

Modulation (BW)	Freq. (MHz)	Data Rate	TP Setting	Total Sum PSD EIRP (dBm)	Antenna Gain (dBi)	Limit (dBm)	Margin (dBm)
OFDM 20	5180	Mcs0_Nss1	36	7.35	5	14.99	-7.64
OFDM 20	5210	Mcs0_Nss1	45	11.98	5	14.99	-3.01
OFDM 20	5240	Mcs0_Nss1	45	11.57	5	14.99	-3.42
VHT 20	5180	Mcs0_Nss1	45	11.04	5	14.99	-5.96
VHT 20	5210	Mcs0_Nss1	45	11.14	5	14.99	-5.86
VHT 20	5240	Mcs0_Nss1	45	10.29	5	14.99	-6.71
VHT 40	5190	Mcs0_Nss1	45	8.45	5	14.99	-8.55
VHT 40	5230	Mcs0_Nss1	45	9.12	5	14.99	-7.88
VHT 80	5210	Mcs0_Nss1	45	4.88	5	14.99	-12.12

Result

The maximum summed average power spectral density was less than the limit of 17 dBm; therefore, the EUT complies with the specification.

-- End of Test Report --