



**SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch**

No. 1 Workshop, M-10, Middle section, Science & Technology Park,
Shenzhen, Guangdong, China 518057

Telephone: +86 (0) 755 2601 2053
Fax: +86 (0) 755 2671 0594
Email: ee.shenzhen@sgs.com

Report No.: SZEM170800807501
Page: 1 of 151

TEST REPORT

Application No.: SZEM1708008075CR
Applicant: DLP Design, Inc.
Address of Applicant: 1605 Roma Lane Allen. Texas (TX) 75013 USA
Manufacturer: DLP Design, Inc.
Address of Manufacturer: 1605 Roma Lane Allen Texas(TX) 75013 USA
Factory: DLP Design, Inc.
Address of Factory: 1605 Roma Lane Allen Texas(TX) 75013 USA
Equipment Under Test (EUT):
EUT Name: 2.4GHz RF Transceiver Module
Model No.: DLP-RFS1280
FCC ID: SX9RFS2
Standard(s) : 47 CFR Part 15, Subpart C 15.247
Date of Receipt: 2017-08-02
Date of Test: 2017-08-09 to 2017-09-05
Date of Issue: 2017-09-08

Test Result:	Pass*
---------------------	--------------

* In the configuration tested, the EUT complied with the standards specified above.



Jack Zhang
EMC Laboratory Manager

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.



Revision Record				
Version	Chapter	Date	Modifier	Remark
01		2017-09-08		Original

Authorized for issue by:				
				
		Jacky Li /Project Engineer		
				
		Eric Fu /Reviewer		



2 Test Summary

Radio Spectrum Technical Requirement				
Item	Standard	Method	Requirement	Result
Antenna Requirement	47 CFR Part 15, Subpart C 15.247	N/A	47 CFR Part 15, Subpart C 15.203 & 15.247(c)	Pass

Radio Spectrum Matter Part				
Item	Standard	Method	Requirement	Result
Conducted Emissions at AC Power Line (150kHz-30MHz)	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 6.2	47 CFR Part 15, Subpart C 15.207	Pass
Minimum 6dB Bandwidth	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 11.8.1	47 CFR Part 15, Subpart C 15.247a(2)	Pass
Conducted Peak Output Power	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 11.9.1.2	47 CFR Part 15, Subpart C 15.247(b)(3)	Pass
Power Spectrum Density	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 11.10.2	47 CFR Part 15, Subpart C 15.247(e)	Pass
Conducted Band Edges Measurement	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 11.13.3.2	47 CFR Part 15, Subpart C 15.247(d)	Pass
Conducted Spurious Emissions	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 11.11	47 CFR Part 15, Subpart C 15.247(d)	Pass
Radiated Emissions which fall in the restricted bands	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 6.10.5	47 CFR Part 15, Subpart C 15.209 & 15.247(d)	Pass
Radiated Spurious Emissions	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 6.10.4	47 CFR Part 15, Subpart C 15.209 & 15.247(d)	Pass



3 Contents

	Page
1 COVER PAGE	1
2 TEST SUMMARY	3
3 CONTENTS	4
4 GENERAL INFORMATION.....	6
4.1 DETAILS OF E.U.T.	6
4.2 DESCRIPTION OF SUPPORT UNITS	6
4.3 MEASUREMENT UNCERTAINTY	6
4.4 TEST LOCATION	7
4.5 TEST FACILITY	7
4.6 DEVIATION FROM STANDARDS.....	7
4.7 ABNORMALITIES FROM STANDARD CONDITIONS	7
5 EQUIPMENT LIST	8
6 RADIO SPECTRUM TECHNICAL REQUIREMENT.....	12
6.1 ANTENNA REQUIREMENT	12
6.1.1 Test Requirement:	12
6.1.2 Conclusion	12
7 RADIO SPECTRUM MATTER TEST RESULTS	14
7.1 CONDUCTED EMISSIONS AT AC POWER LINE (150kHz-30MHz)	14
7.1.1 E.U.T. Operation.....	15
7.1.2 Test Setup Diagram.....	15
7.1.3 Measurement Procedure and Data.....	15
7.2 MINIMUM 6DB BANDWIDTH	18
7.2.1 E.U.T. Operation.....	18
7.2.2 Test Setup Diagram.....	18
7.2.3 Measurement Procedure and Data.....	18
7.3 CONDUCTED PEAK OUTPUT POWER.....	19
7.3.1 E.U.T. Operation.....	20
7.3.2 Test Setup Diagram.....	20
7.3.3 Measurement Procedure and Data.....	20
7.4 POWER SPECTRUM DENSITY	21
7.4.1 E.U.T. Operation.....	21
7.4.2 Test Setup Diagram.....	21
7.4.3 Measurement Procedure and Data.....	21
7.5 CONDUCTED BAND EDGES MEASUREMENT	22
7.5.1 E.U.T. Operation.....	23
7.5.2 Test Setup Diagram.....	23
7.5.3 Measurement Procedure and Data.....	23
7.6 CONDUCTED SPURIOUS EMISSIONS.....	24
7.6.1 E.U.T. Operation.....	25
7.6.2 Test Setup Diagram.....	25
7.6.3 Measurement Procedure and Data.....	25
7.7 RADIATED EMISSIONS WHICH FALL IN THE RESTRICTED BANDS	26
7.7.1 E.U.T. Operation.....	27
7.7.2 Test Setup Diagram.....	27



7.7.3	Measurement Procedure and Data.....	27
7.8	RADIATED SPURIOUS EMISSIONS.....	41
7.8.1	E.U.T. Operation.....	42
7.8.2	Test Setup Diagram.....	42
7.8.3	Measurement Procedure and Data.....	43
8	PHOTOGRAPHS.....	65
8.1	CONDUCTED EMISSIONS AT AC POWER LINE (150kHz-30MHz) TEST SETUP.....	65
8.2	RADIATED SPURIOUS EMISSIONS TEST SETUP.....	66
8.3	EUT CONSTRUCTIONAL DETAILS	67
9	APPENDIX.....	68
9.1	APPENDIX -FLRC.....	68
9.2	APPENDIX -GFSK	96
9.3	APPENDIX - LORA.....	124-151



4 General Information

4.1 Details of E.U.T.

Power supply:	DC 3.3V for the module
Type of Modulation:	LORA, FLRC, GFSK
Operating Frequency:	2402~2480MHz
Channel Number:	40
Channels Step:	Channels with 2MHz step
Sample Type:	Mobile production
Antenna Type:	Antenna 1: Integral Antenna, Antenna 2: Chip Antenna
Antenna Gain:	0.5dBi for antenna 1 and antenna 2 (Two antennas can't transmit simultaneously)

4.2 Description of Support Units

Description	Manufacturer	Model No.	Serial No.
Laptop	Lenovo	T430u	REF. No.SEA1800
Router	NETGEAR	DGN2200	REF. No.SEA2200
Mouse	Lenovo	M-U0025-O	REF. No.:SEA2400
Test board	DLP Design, Inc.	TestLabInstructions ACT Board P2	/

4.3 Measurement Uncertainty

No.	Item	Measurement Uncertainty
1	Radio Frequency	7.25×10^{-8}
2	Duty cycle	0.37%
3	Occupied Bandwidth	3%
4	RF conducted power	0.75dB
5	RF power density	2.84dB
6	Conducted Spurious emissions	0.75dB
7	RF Radiated power	4.5dB (below 1GHz)
		4.8dB (above 1GHz)
8	Radiated Spurious emission test	4.5dB (30MHz-1GHz)
		4.8dB (1GHz-18GHz)
9	Temperature test	1 °C
10	Humidity test	3%
11	Supply voltages	1.5%
12	Time	3%

4.4 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen Branch

No. 1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, Guangdong, China.
518057.

Tel: +86 755 2601 2053 Fax: +86 755 2671 0594

No tests were sub-contracted.

4.5 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **CNAS (No. CNAS L2929)**

CNAS has accredited SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

- **A2LA (Certificate No. 3816.01)**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 3816.01.

- **VCCI**

The 10m Semi-anechoic chamber and Shielded Room of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-823, R-4188, T-1153 and C-2383 respectively.

- **FCC –Designation Number: CN1178**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized as an accredited testing laboratory.

Designation Number: CN1178. Test Firm Registration Number: 406779.

- **Industry Canada (IC)**

Two 3m Semi-anechoic chambers and the 10m Semi-anechoic chamber of SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab have been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 4620C-1, 4620C-2, 4620C-3.

4.6 Deviation from Standards

None

4.7 Abnormalities from Standard Conditions

None



5 Equipment List

Conducted Emissions at AC Power Line (150kHz-30MHz)					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
Shielding Room	ZhongYu Electron	GB-88	SEM001-06	2017-05-10	2018-05-10
Measurement Software	AUDIX	e3 V5.4.1221d	N/A	N/A	N/A
LISN	Rohde & Schwarz	ENV216	SEM007-01	2016-10-09	2017-10-09
LISN	ETS-LINDGREN	3816/2	SEM007-02	2017-04-14	2018-04-13
8 Line ISN	Fischer Custom Communications Inc.	FCC-TLISN-T8-02	EMC0120	2016-09-28	2017-09-28
4 Line ISN	Fischer Custom Communications Inc.	FCC-TLISN-T4-02	EMC0121	2016-09-28	2017-09-28
2 Line ISN	Fischer Custom	FCC-TLISN-T2-02	EMC0122	2016-09-28	2017-09-28

Minimum 6dB Bandwidth					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
DC Power Supply	ZhaoXin	RXN-305D	SEM011-02	2016-10-09	2017-10-09
Spectrum Analyzer	Rohde & Schwarz	FSP	SEM004-06	2016-10-09	2017-10-09
Measurement Software	JS Tonscend	JS1120-2 BT/WIFI V2.	N/A	N/A	N/A
Signal Generator	Rohde & Schwarz	SML03	SEM006-02	2017-04-14	2018-04-13
Power Meter	Rohde & Schwarz	NRVS	SEM014-02	2016-10-09	2017-10-09

Conducted Peak Output Power					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
DC Power Supply	ZhaoXin	RXN-305D	SEM011-02	2016-10-09	2017-10-09
Spectrum Analyzer	Rohde & Schwarz	FSP	SEM004-06	2016-10-09	2017-10-09
Measurement Software	JS Tonscend	JS1120-2 BT/WIFI V2.	N/A	N/A	N/A
Signal Generator	Rohde & Schwarz	SML03	SEM006-02	2017-04-14	2018-04-13
Power Meter	Rohde & Schwarz	NRVS	SEM014-02	2016-10-09	2017-10-09



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

Report No.: SZEM170800807501

Page: 9 of 151

Power Spectrum Density					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
DC Power Supply	ZhaoXin	RXN-305D	SEM011-02	2016-10-09	2017-10-09
Spectrum Analyzer	Rohde & Schwarz	FSP	SEM004-06	2016-10-09	2017-10-09
Measurement Software	JS Tonscend	JS1120-2 BT/WIFI V2.	N/A	N/A	N/A
Signal Generator	Rohde & Schwarz	SML03	SEM006-02	2017-04-14	2018-04-13
Power Meter	Rohde & Schwarz	NRVS	SEM014-02	2016-10-09	2017-10-09

Conducted Band Edges Measurement					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
DC Power Supply	ZhaoXin	RXN-305D	SEM011-02	2016-10-09	2017-10-09
Spectrum Analyzer	Rohde & Schwarz	FSP	SEM004-06	2016-10-09	2017-10-09
Measurement Software	JS Tonscend	JS1120-2 BT/WIFI V2.	N/A	N/A	N/A
Signal Generator	Rohde & Schwarz	SML03	SEM006-02	2017-04-14	2018-04-13
Power Meter	Rohde & Schwarz	NRVS	SEM014-02	2016-10-09	2017-10-09

Conducted Spurious Emissions					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
DC Power Supply	ZhaoXin	RXN-305D	SEM011-02	2016-10-09	2017-10-09
Spectrum Analyzer	Rohde & Schwarz	FSP	SEM004-06	2016-10-09	2017-10-09
Measurement Software	JS Tonscend	JS1120-2 BT/WIFI V2.	N/A	N/A	N/A
Signal Generator	Rohde & Schwarz	SML03	SEM006-02	2017-04-14	2018-04-13
Power Meter	Rohde & Schwarz	NRVS	SEM014-02	2016-10-09	2017-10-09



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

Report No.: SZEM170800807501

Page: 10 of 151

RE in Chamber					
Test Equipment	Manufacturer	Model No.	Inventory No.	Cal. Date (yyyy-mm-dd)	Cal. Due date (yyyy-mm-dd)
3m Semi-Anechoic Chamber	ETS-LINDGREN	N/A	SEM001-01	2017-08-05	2020-08-04
MXE EMI Receiver (20Hz-8.4GHz)	Agilent Technologies	N9038A	SEM004-05	2016-10-09	2017-10-09
BiConiLog Antenna (26-3000MHz)	ETS-LINDGREN	3142C	SEM003-02	2017-03-05	2020-03-05
Pre-amplifier (0.1-1300MHz)	Agilent Technologies	8447D	SEM005-01	2017-04-14	2018-04-13
Measurement Software	AUDIX	e3 V8.2014-6-27	N/A	N/A	N/A

Radiated Emissions which fall in the restricted bands					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
3m Semi-Anechoic Chamber	AUDIX	N/A	SEM001-02	2017-05-02	2020-05-01
Measurement Software	AUDIX	e3 V8.2014-6-27	N/A	N/A	N/A
Spectrum Analyzer	Rohde & Schwarz	FSU43	SEM004-08	2017-04-14	2018-04-13
BiConiLog Antenna (26-3000MHz)	ETS-Lindgren	3142C	SEM003-02	2017-03-05	2020-03-05
Horn Antenna (1-18GHz)	Rohde & Schwarz	HF907	SEM003-07	2015-06-14	2018-06-14
Horn Antenna (15GHz-40GHz)	Schwarzbeck	BBHA 9170	SEM003-14	2017-06-16	2020-06-15
Pre-amplifier (0.1-1300MHz)	HP	8447D	SEM005-02	2016-10-09	2017-10-09
Low Noise Amplifier (100MHz-18GHz)	Black Diamond Series	BDLNA-0118-352810	SEM005-05	2016-10-09	2017-10-09
Pre-amplifier (0.1-26.5GHz)	Compliance Directions Systems Inc.	PAP-0126	SEM004-10	2016-10-17	2017-10-17
Pre-amplifier (26GHz-40GHz)	Compliance Directions Systems Inc.	PAP-2640-50	SEM005-08	2017-04-14	2018-04-13
DC Power Supply	Zhao Xin	RXN-305D	SEM011-02	2016-10-09	2017-10-09
Active Loop Antenna	ETS-Lindgren	6502	SEM003-08	2017-08-22	2020-08-21
Band filter	N/A	N/A	SEM023-01	N/A	N/A

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

Report No.: SZEM170800807501

Page: 11 of 151

Radiated Spurious Emissions					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
3m Semi-Anechoic Chamber	AUDIX	N/A	SEM001-02	2017-05-02	2020-05-01
Measurement Software	AUDIX	e3 V8.2014-6-27	N/A	N/A	N/A
Spectrum Analyzer	Rohde & Schwarz	FSU43	SEM004-08	2017-04-14	2018-04-13
BiConiLog Antenna (26-3000MHz)	ETS-Lindgren	3142C	SEM003-02	2017-03-05	2020-03-05
Horn Antenna (1-18GHz)	Rohde & Schwarz	HF907	SEM003-07	2015-06-14	2018-06-14
Horn Antenna (15GHz-40GHz)	Schwarzbeck	BBHA 9170	SEM003-14	2017-06-16	2020-06-15
Pre-amplifier (0.1-1300MHz)	HP	8447D	SEM005-02	2016-10-09	2017-10-09
Low Noise Amplifier (100MHz-18GHz)	Black Diamond Series	BDLNA-0118-352810	SEM005-05	2016-10-09	2017-10-09
Pre-amplifier (0.1-26.5GHz)	Compliance Directions Systems Inc.	PAP-0126	SEM004-10	2016-10-17	2017-10-17
Pre-amplifier (26GHz-40GHz)	Compliance Directions Systems Inc.	PAP-2640-50	SEM005-08	2017-04-14	2018-04-13
DC Power Supply	Zhao Xin	RXN-305D	SEM011-02	2016-10-09	2017-10-09
Active Loop Antenna	ETS-Lindgren	6502	SEM003-08	2017-08-22	2020-08-21
Band filter	N/A	N/A	SEM023-01	N/A	N/A

General used equipment					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
Humidity/ Temperature Indicator	Shanghai Meteorological Industry Factory	ZJ1-2B	SEM002-03	2016-10-12	2017-10-12
Humidity/ Temperature Indicator	Shanghai Meteorological Industry Factory	ZJ1-2B	SEM002-04	2016-10-12	2017-10-12
Humidity/ Temperature Indicator	Mingle	N/A	SEM002-08	2016-10-12	2017-10-12
Barometer	Changchun Meteorological Industry Factory	DYM3	SEM002-01	2017-04-18	2018-04-18

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

6 Radio Spectrum Technical Requirement

6.1 Antenna Requirement

6.1.1 Test Requirement:

47 CFR Part 15, Subpart C 15.203 & 15.247(c)

6.1.2 Conclusion


Standard Requirement:


An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

15.247(b) (4) requirement:

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

EUT Antenna:





**Antenna 1
Connector**

The antenna is integrated on the main PCB and no consideration of replacement. The best case gain of the antenna is 0.5dBi.



7 Radio Spectrum Matter Test Results

7.1 Conducted Emissions at AC Power Line (150kHz-30MHz)

Test Requirement 47 CFR Part 15, Subpart C 15.207

Test Method: ANSI C63.10 (2013) Section 6.2

Limit:

Frequency of emission(MHz)	Conducted limit(dBμV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50
*Decreases with the logarithm of the frequency.		


7.1.1 E.U.T. Operation

Operating Environment:

Temperature: 25 °C Humidity: 51 % RH Atmospheric Pressure: 1005 mbar

Test mode a:TX mode_Keep the EUT in continuously transmitting mode with all modulation types. Only the data of worst case is recorded in the report.

7.1.2 Test Setup Diagram




7.1.3 Measurement Procedure and Data

- 1) The mains terminal disturbance voltage test was conducted in a shielded room.
- 2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a 50ohm/50μH + 5ohm linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded.
- 3) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane,
- 4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2.
- 5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10 on conducted measurement.

Remark: LISN=Read Level+ Cable Loss+ LISN Factor

Note: All antennas have been tested and we find antenna 1 owns the worst test result. We only record the worst test result of antenna 1.


Mode:a; Line:Live Line; Modulation: LORA



Site : Shielding Room
Condition: Line
Job No. : 08075CR
Test mode: a

	Freq	Cable Loss	LISN Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB	dBuV	dBuV	dBuV	dB	
1	0.15	0.02	9.64	36.43	46.09	56.00	-9.91	Peak
2	0.21	0.02	9.63	32.38	42.03	53.18	-11.15	Peak
3	0.24	0.01	9.63	31.42	41.06	52.22	-11.16	Peak
4	1.37	0.02	9.65	16.10	25.77	46.00	-20.23	Peak
5	4.93	0.01	9.72	13.52	23.25	46.00	-22.75	Peak
6	17.75	0.02	10.10	22.13	32.25	50.00	-17.75	Peak

Mode:a; Line:Neutral Line; Modulation: LORA



Site : Shielding Room
 Condition: Neutral
 Job No. : 08075CR
 Test mode: a

	Freq	Cable Loss	LISN Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB	dBuV	dBuV	dBuV	dB	
1	0.17	0.02	9.63	40.00	49.65	55.08	-5.43	Peak
2	0.19	0.02	9.63	36.40	46.05	54.02	-7.97	Peak
3	0.28	0.01	9.63	27.86	37.50	50.81	-13.31	Peak
4	1.40	0.02	9.65	15.61	25.28	46.00	-20.72	Peak
5	5.06	0.01	9.72	12.21	21.94	50.00	-28.06	Peak
6	18.04	0.02	10.12	23.70	33.84	50.00	-16.16	Peak

7.2 Minimum 6dB Bandwidth


Test Requirement	47 CFR Part 15, Subpart C 15.247a(2)
Test Method:	ANSI C63.10 (2013) Section 11.8.1
Limit:	≥500 kHz

7.2.1 E.U.T. Operation

Operating Environment:

Temperature:	25 °C	Humidity:	55 % RH	Atmospheric Pressure:	1005 mbar
Test mode	a:TX mode_Keep the EUT in continuously transmitting mode with all modulation types. Only the data of worst case is recorded in the report.				

7.2.2 Test Setup Diagram



7.2.3 Measurement Procedure and Data

The detailed test data see: Appendix 15.247



7.3 Conducted Peak Output Power

Test Requirement 47 CFR Part 15, Subpart C 15.247(b)(3)

Test Method: ANSI C63.10 (2013) Section 11.9.1.2

Limit:

Frequency range(MHz)	Output power of the intentional radiator(watt)
902-928	1 for ≥ 50 hopping channels
	0.25 for $25 \leq$ hopping channels < 50
	1 for digital modulation
2400-2483.5	1 for ≥ 75 non-overlapping hopping channels
	0.125 for all other frequency hopping systems
	1 for digital modulation
5725-5850	1 for frequency hopping systems and digital modulation


7.3.1 E.U.T. Operation

Operating Environment:

Temperature: 25 °C Humidity: 55 % RH Atmospheric Pressure: 1005 mbar

Test mode a:TX mode_Keep the EUT in continuously transmitting mode with all modulation types. Only the data of worst case is recorded in the report.

7.3.2 Test Setup Diagram



7.3.3 Measurement Procedure and Data

The detailed test data see: Appendix 15.247

7.4 Power Spectrum Density

Test Requirement: 47 CFR Part 15, Subpart C 15.247(e)
 Test Method: ANSI C63.10 (2013) Section 11.10.2
 Limit: $\leq 8\text{dBm}$ in any 3 kHz band during any time interval of continuous transmission


7.4.1 E.U.T. Operation

Operating Environment:

Temperature: 25 °C Humidity: 55 % RH Atmospheric Pressure: 1005 mbar

Test mode: a:TX mode_Keep the EUT in continuously transmitting mode with all modulation types. Only the data of worst case is recorded in the report.

7.4.2 Test Setup Diagram



7.4.3 Measurement Procedure and Data

The detailed test data see: Appendix 15.247



7.5 Conducted Band Edges Measurement

Test Requirement	47 CFR Part 15, Subpart C 15.247(d)
Test Method:	ANSI C63.10 (2013) Section 11.13.3.2
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c))


7.5.1 E.U.T. Operation

Operating Environment:

Temperature: 25 °C Humidity: 55 % RH Atmospheric Pressure: 1005 mbar

Test mode a:TX mode_Keep the EUT in continuously transmitting mode with all modulation types. Only the data of worst case is recorded in the report.

7.5.2 Test Setup Diagram



7.5.3 Measurement Procedure and Data

The detailed test data see: Appendix 15.247



7.6 Conducted Spurious Emissions

Test Requirement	47 CFR Part 15, Subpart C 15.247(d)
Test Method:	ANSI C63.10 (2013) Section 11.11
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c))


7.6.1 E.U.T. Operation

Operating Environment:

Temperature: 25 °C Humidity: 55 % RH Atmospheric Pressure: 1005 mbar

Test mode a:TX mode_Keep the EUT in continuously transmitting mode with all modulation types. Only the data of worst case is recorded in the report.

7.6.2 Test Setup Diagram



7.6.3 Measurement Procedure and Data

The detailed test data see: Appendix 15.247



7.7 Radiated Emissions which fall in the restricted bands

Test Requirement 47 CFR Part 15, Subpart C 15.209 & 15.247(d)

Test Method: ANSI C63.10 (2013) Section 6.10.5

Measurement Distance: 3m

Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.


7.7.1 E.U.T. Operation

Operating Environment:

Temperature: 23 °C Humidity: 54 % RH Atmospheric Pressure: 1000 mbar

Test mode a:TX mode_Keep the EUT in continuously transmitting mode with all modulation types. Only the data of worst case is recorded in the report.

7.7.2 Test Setup Diagram



7.7.3 Measurement Procedure and Data


- a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- d. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- f. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- g. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- h. Test the EUT in the lowest channel,the middle channel,the Highest channel.
- i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- j. Repeat above procedures until all frequencies measured was complete.

Remark: Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor



Note: All antennas have been tested and we find antenna 1 owns the worst test result. We only record the worst test result of antenna 1.

Mode:a; Polarization:Horizontal; Modulation Type: FLRC; Channel:Low



Condition: 3m HORIZONTAL

Job No : 08075CR/08076CR


Mode : 2402 Band edge

: FLRC

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2386.320	5.47	29.07	37.96	48.45	45.03	74.00	-28.97	peak
2	2390.000	5.47	29.08	37.96	45.10	41.69	74.00	-32.31	peak
3 pp	2402.000	5.49	29.11	37.95	106.83	103.48	74.00	29.48	peak



Mode:a; Polarization:Vertical; Modulation Type: FLRC; Channel:Low



Condition: 3m VERTICAL


Job No : 08075CR/08076CR

Mode : 2402 Band edge

: FLRC

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2369.792	5.45	29.02	37.96	47.23	43.74	74.00	-30.26	peak
2	2390.000	5.47	29.08	37.96	44.27	40.86	74.00	-33.14	peak
3 pp	2402.000	5.49	29.11	37.95	102.77	99.42	74.00	25.42	peak

Mode:a; Polarization:Horizontal; Modulation Type: FLRC; Channel:High



Condition: 3m HORIZONTAL


Job No : 08075CR/08076CR

Mode : 2480 Band edge

: FLRC

	Freq	Cable Loss	Ant Factor	Preamplifier Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 pp	2480.000	5.59	29.34	37.95	105.72	102.70	74.00	28.70	peak
2	2483.500	5.60	29.35	37.95	49.16	46.16	74.00	-27.84	peak
3	2496.033	5.61	29.39	37.95	49.55	46.60	74.00	-27.40	peak

Mode:a; Polarization:Vertical; Modulation Type: FLRC; Channel:High



Condition: 3m VERTICAL

Job No : 08075CR/08076CR


Mode : 2480 Band edge

: FLRC

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 pp	2480.000	5.59	29.34	37.95	103.30	100.28	74.00	26.28 peak
2	2483.500	5.60	29.35	37.95	46.30	43.30	74.00	-30.70 peak
3	2495.808	5.61	29.39	37.95	48.06	45.11	74.00	-28.89 peak



Mode:a; Polarization:Horizontal; Modulation Type: GFSK; Channel:Low




Condition: 3m HORIZONTAL
Job No : 08075CR/08076CR
Mode : 2402 Band edge
: GFSK

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2317.157	5.37	28.86	37.96	53.69	49.96	74.00	-24.04	peak
2	2390.000	5.47	29.08	37.96	44.59	41.18	74.00	-32.82	peak
3 pp	2402.000	5.49	29.11	37.95	105.90	102.55	74.00	28.55	peak



Mode:a; Polarization:Vertical; Modulation Type: GFSK; Channel:Low



Condition: 3m VERTICAL


Job No : 08075CR/08076CR

Mode : 2402 Band edge

: GFSK

	Freq	Cable Loss	Ant Factor	Preamplifier Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2333.417	5.40	28.91	37.96	51.72	48.07	74.00	-25.93	peak
2	2390.000	5.47	29.08	37.96	44.40	40.99	74.00	-33.01	peak
3 pp	2402.000	5.49	29.11	37.95	103.05	99.70	74.00	25.70	peak

Mode:a; Polarization:Horizontal; Modulation Type: GFSK; Channel:High



Condition: 3m HORIZONTAL


Job No : 08075CR/08076CR

Mode : 2480 Band edge

: GFSK

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 pp	2480.000	5.59	29.34	37.95	107.04	104.02	74.00	30.02 peak
2	2483.500	5.60	29.35	37.95	54.04	51.04	74.00	-22.96 peak
3	2483.821	5.60	29.35	37.95	55.58	52.58	74.00	-21.42 peak

Mode:a; Polarization:Vertical; Modulation Type: GFSK; Channel:High



Condition: 3m VERTICAL


Job No : 08075CR/08076CR

Mode : 2480 Band edge

: GFSK

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 pp	2480.000	5.59	29.34	37.95	104.31	101.29	74.00	27.29	peak
2	2483.500	5.60	29.35	37.95	52.30	49.30	74.00	-24.70	peak
3	2484.321	5.60	29.35	37.95	52.33	49.33	74.00	-24.67	peak

Mode:a; Polarization:Horizontal; Modulation Type: LORA; Channel:Low



Condition: 3m HORIZONTAL


Job No : 08075CR/08076CR

Mode : 2402 Band edge

Note : LORA

	Freq	Cable Loss	Ant Factor	Preamplifier Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2390.000	5.47	29.08	37.96	52.37	48.96	74.00	-25.04	peak
2 pp	2401.334	5.49	29.11	37.95	105.41	102.06	74.00	28.06	peak

Mode:a; Polarization:Vertical; Modulation Type: LORA; Channel:Low



Condition: 3m VERTICAL


Job No : 08075CR/08076CR

Mode : 2402 Band edge

Note : LORA

	Freq	Cable Loss	Ant Factor	Preamplifier Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2322.466	5.38	28.87	37.96	53.92	50.21	74.00	-23.79	peak
2	2390.000	5.47	29.08	37.96	49.50	46.09	74.00	-27.91	peak
3 pp	2402.759	5.49	29.12	37.95	101.38	98.04	74.00	24.04	peak

Mode:a; Polarization:Horizontal; Modulation Type: LORA; Channel:Low



Condition: 3m HORIZONTAL


Job No : 08075CR/08076CR

Mode : 2480 Band edge

Note : LORA

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 pp	2479.232	5.59	29.34	37.95	105.36	102.34	74.00	28.34 peak
2 av	2483.500	5.60	29.35	37.95	44.20	41.20	54.00	-12.80 Average
3	2483.500	5.60	29.35	37.95	74.32	71.32	74.00	-2.68 peak

Mode:a; Polarization:Vertical; Modulation Type: LORA; Channel:Low



Condition: 3m VERTICAL

Job No : 08075CR/08076CR

Mode : 2480 Band edge

Note : LORA

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 pp	2479.432	5.59	29.34	37.95	101.88	98.86	74.00	24.86 peak
2 av	2483.500	5.60	29.35	37.95	41.47	38.47	54.00	-15.53 Average
3	2483.500	5.60	29.35	37.95	71.11	68.11	74.00	-5.89 peak



Remark:

1) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Final Test Level = Receiver Reading + Antenna Factor + Cable Factor – Preamplifier Factor

2) As shown in this section, for frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. So, only the peak measurements were shown in the report.



7.8 Radiated Spurious Emissions

Test Requirement 47 CFR Part 15, Subpart C 15.209 & 15.247(d)

Test Method: ANSI C63.10 (2013) Section 6.10.4

Measurement Distance: 3m

Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.


7.8.1 E.U.T. Operation

Operating Environment:

Temperature: 24 °C Humidity: 54 % RH Atmospheric Pressure: 1000 mbar

Test mode a:TX mode_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); data rate @ 13.5Mbps is the worst case of IEEE 802.11n(HT40). Only the data of worst case is recorded in the report.

7.8.2 Test Setup Diagram





7.8.3 Measurement Procedure and Data

- a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- d. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- f. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- g. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- h. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- j. Repeat above procedures until all frequencies measured was complete.

Remark: Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor




Note: All antennas have been tested and we find antenna 1 owns the worst test result. We only record the worst test result of antenna 1.

30MHz~1GHz

QP value

Mode:a; Polarization:Horizontal




Condition: 3m HORIZONTAL

Job No. : 08075CR

Test mode: a

	Freq	Cable Loss	Ant Factor	Preamplifier Factor	Read Level	Level	Limit Line	Over Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	43.51	0.68	11.56	27.31	25.69	10.62	40.00	-29.38
2	144.33	1.31	8.49	26.94	32.68	15.54	43.50	-27.96
3	166.65	1.35	9.53	26.83	35.88	19.93	43.50	-23.57
4	238.31	1.62	11.93	26.57	32.36	19.34	46.00	-26.66
5 pp	287.99	1.85	13.37	26.43	44.82	33.61	46.00	-12.39
6	431.03	2.33	16.52	27.33	31.50	23.02	46.00	-22.98

Mode:a; Polarization:Vertical



Condition: 3m VERTICAL


Job No. : 08075CR

Test mode: a

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	30.96	0.60	18.16	27.35	22.15	13.56	40.00	-26.44
2	144.33	1.31	8.49	26.94	31.22	14.08	43.50	-29.42
3	166.65	1.35	9.53	26.83	35.97	20.02	43.50	-23.48
4	238.31	1.62	11.93	26.57	32.45	19.43	46.00	-26.57
5 pp	287.99	1.85	13.37	26.43	45.31	34.10	46.00	-11.90
6	431.03	2.33	16.52	27.33	31.32	22.84	46.00	-23.16

Above 1GHz

Mode:a; Polarization:Horizontal; Modulation Type: FLRC; Channel:Low



Condition: 3m HORIZONTAL

Job No : 08075CR/08076CR


Mode : 2402 TX RSE

: FLRC

	Freq	Cable Loss	Ant Factor	Preamplifier Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1335.141	4.93	25.11	38.06	46.53	38.51	74.00	-35.49	peak
2	4157.664	7.17	33.60	38.09	44.89	47.57	74.00	-26.43	peak
3	4804.000	7.89	34.16	38.41	44.14	47.78	74.00	-26.22	peak
4	6914.763	10.36	36.27	37.38	43.77	53.02	74.00	-20.98	peak
5	7206.000	10.08	36.42	37.10	43.42	52.82	74.00	-21.18	peak
6 pp	9608.000	10.75	37.52	35.09	40.28	53.46	74.00	-20.54	peak




Mode:a; Polarization:Vertical; Modulation Type: FLRC; Channel:Low



Condition: 3m VERTICAL
Job No : 08075CR/08076CR
Mode : 2402 TX RSE
: FLRC

	Freq	Cable Loss	Ant Factor	Preamplifier Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1663.137	5.27	26.52	38.03	47.91	41.67	74.00	-32.33	peak
2	4027.554	7.01	33.60	38.02	44.51	47.10	74.00	-26.90	peak
3	4804.000	7.89	34.16	38.41	44.55	48.19	74.00	-25.81	peak
4	6894.806	10.42	36.21	37.40	43.64	52.87	74.00	-21.13	peak
5	7206.000	10.08	36.42	37.10	44.05	53.45	74.00	-20.55	peak
6 pp	9608.000	10.75	37.52	35.09	40.31	53.49	74.00	-20.51	peak

Mode:a; Polarization: Horizontal; Modulation Type: FLRC; Channel:Middle



Condition: 3m HORIZONTAL

Job No : 08075CR/08076CR


Mode : 2440 TX RSE

: FLRC

	Freq	Cable Loss	Ant Factor	Preamplifier Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1672.779	5.26	26.56	38.03	43.68	37.47	74.00	-36.53	peak
2	4367.058	7.41	33.60	38.20	43.83	46.64	74.00	-27.36	peak
3	4880.000	7.97	34.29	38.45	43.63	47.44	74.00	-26.56	peak
4 pp	6659.763	11.08	35.56	37.62	43.92	52.94	74.00	-21.06	peak
5	7320.000	10.05	36.37	37.00	41.03	50.45	74.00	-23.55	peak
6	9760.000	10.82	37.55	35.02	39.28	52.63	74.00	-21.37	peak



Mode:a; Polarization:Vertical; Modulation Type: FLRC; Channel:Middle



Condition: 3m VERTICAL


Job No : 08075CR/08076CR

Mode : 2440 TX RSE

: FLRC

	Freq	Cable Loss	Ant Factor	Preamplifier Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1335.141	4.93	25.11	38.06	47.73	39.71	74.00	-34.29	peak
2	4169.698	7.18	33.60	38.09	44.73	47.42	74.00	-26.58	peak
3	4880.000	7.97	34.29	38.45	45.48	49.29	74.00	-24.71	peak
4	6414.167	11.38	35.03	37.87	44.96	53.50	74.00	-20.50	peak
5 pp	7320.000	10.05	36.37	37.00	41.08	50.50	54.00	-3.50	Average
6 pk	7320.000	10.05	36.37	37.00	47.30	56.72	74.00	-17.28	peak
7	9760.000	10.82	37.55	35.02	40.37	53.72	74.00	-20.28	peak

Mode:a; Polarization: Horizontal; Modulation Type: FLRC; Channel:High



Condition: 3m HORIZONTAL

Job No : 08075CR/08076CR


Mode : 2480 TX RSE

: FLRC

	Freq	Cable Loss	Ant Factor	Preamplifier Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1597.181	5.35	26.24	38.03	43.63	37.19	74.00	-36.81	peak
2	3946.885	6.93	33.46	38.00	44.34	46.73	74.00	-27.27	peak
3	4960.000	8.05	34.43	38.48	42.94	46.94	74.00	-27.06	peak
4	6659.763	11.08	35.56	37.62	43.18	52.20	74.00	-21.80	peak
5	7440.000	10.02	36.32	36.89	41.79	51.24	74.00	-22.76	peak
6 pp	9920.000	10.90	37.58	34.94	38.98	52.52	74.00	-21.48	peak



Mode:a; Polarization:Vertical; Modulation Type: FLRC; Channel:High



Condition: 3m VERTICAL


Job No : 08075CR/08076CR

Mode : 2480 TX RSE

: FLRC

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1335.141	4.93	25.11	38.06	46.76	38.74	74.00	-35.26	peak
2	4354.454	7.40	33.60	38.19	44.70	47.51	74.00	-26.49	peak
3	4960.000	8.05	34.43	38.48	43.82	47.82	74.00	-26.18	peak
4	6894.806	10.42	36.21	37.40	43.50	52.73	74.00	-21.27	peak
5 pp	7440.000	10.02	36.32	36.89	41.07	50.52	54.00	-3.48	Average
6 pk	7440.000	10.02	36.32	36.89	48.41	57.86	74.00	-16.14	peak
7	9920.000	10.90	37.58	34.94	38.66	52.20	74.00	-21.80	peak

Mode:a; Polarization: Horizontal; Modulation Type: GFSK; Channel:Low



Condition: 3m HORIZONTAL


Job No : 08075CR/08076CR

Mode : 2402 TX RSE

: GFSK

	Freq	Cable Loss	Ant Factor	Preamplifier Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1335.141	4.93	25.11	38.06	45.89	37.87	74.00	-36.13	peak
2	4392.376	7.44	33.60	38.21	44.81	47.64	74.00	-26.36	peak
3	4804.000	7.89	34.16	38.41	44.12	47.76	74.00	-26.24	peak
4 pp	6894.806	10.42	36.21	37.40	44.17	53.40	74.00	-20.60	peak
5	7206.000	10.08	36.42	37.10	43.08	52.48	74.00	-21.52	peak
6	9608.000	10.75	37.52	35.09	39.75	52.93	74.00	-21.07	peak

Mode:a; Polarization:Vertical; Modulation Type: GFSK; Channel:Low



Condition: 3m VERTICAL


Job No : 08075CR/08076CR

Mode : 2402 TX RSE

: GFSK

	Freq	Cable Loss	Ant Factor	Preamplifier Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1335.141	4.93	25.11	38.06	47.66	39.64	74.00	-34.36	peak
2	4367.058	7.41	33.60	38.20	44.98	47.79	74.00	-26.21	peak
3	4804.000	7.89	34.16	38.41	46.09	49.73	74.00	-24.27	peak
4	6395.654	11.34	35.02	37.89	44.07	52.54	74.00	-21.46	peak
5 pp	7206.000	10.08	36.42	37.10	43.70	53.10	74.00	-20.90	peak
6	9608.000	10.75	37.52	35.09	39.85	53.03	74.00	-20.97	peak

Mode:a; Polarization: Horizontal; Modulation Type: GFSK; Channel:Middle



Condition: 3m HORIZONTAL


Job No : 08075CR/08076CR

Mode : 2440 TX RSE

: GFSK

	Freq	Cable Loss	Ant Factor	Preamplifier Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1335.141	4.93	25.11	38.06	46.67	38.65	74.00	-35.35	peak
2	4133.699	7.14	33.60	38.07	44.64	47.31	74.00	-26.69	peak
3	4880.000	7.97	34.29	38.45	44.75	48.56	74.00	-25.44	peak
4	6894.806	10.42	36.21	37.40	43.65	52.88	74.00	-21.12	peak
5	7320.000	10.05	36.37	37.00	44.03	53.45	74.00	-20.55	peak
6 pp	9760.000	10.82	37.55	35.02	40.49	53.84	74.00	-20.16	peak

Mode:a; Polarization:Vertical; Modulation Type: GFSK; Channel:Middle



Condition: 3m VERTICAL


Job No : 08075CR/08076CR

Mode : 2440 TX RSE

: GFSK

	Freq	Cable Loss	Ant Factor	Preamplifier Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1335.141	4.93	25.11	38.06	47.26	39.24	74.00	-34.76	peak
2	4145.664	7.16	33.60	38.08	44.94	47.62	74.00	-26.38	peak
3	4880.000	7.97	34.29	38.45	46.24	50.05	74.00	-23.95	peak
4	6698.373	10.97	35.67	37.59	43.18	52.23	74.00	-21.77	peak
5 pp	7320.000	10.05	36.37	37.00	41.23	50.65	54.00	-3.35	Average
6 pk	7320.000	10.05	36.37	37.00	50.56	59.98	74.00	-14.02	peak
7	9760.000	10.82	37.55	35.02	39.22	52.57	74.00	-21.43	peak

Mode:a; Polarization: Horizontal; Modulation Type: GFSK; Channel:High



Condition: 3m HORIZONTAL


Job No : 08075CR/08076CR

Mode : 2480 TX RSE

: GFSK

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1335.141	4.93	25.11	38.06	47.50	39.48	74.00	-34.52	peak
2	4367.058	7.41	33.60	38.20	45.06	47.87	74.00	-26.13	peak
3	4960.000	8.05	34.43	38.48	43.13	47.13	74.00	-26.87	peak
4 pp	6815.551	10.64	36.00	37.47	44.45	53.62	74.00	-20.38	peak
5	7440.000	10.02	36.32	36.89	43.74	53.19	74.00	-20.81	peak
6	9920.000	10.90	37.58	34.94	39.48	53.02	74.00	-20.98	peak

Mode:a; Polarization:Vertical; Modulation Type: GFSK; Channel:High



Condition: 3m VERTICAL


Job No : 08075CR/08076CR

Mode : 2402 TX RSE

: GFSK

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1335.141	4.93	25.11	38.06	47.66	39.64	74.00	-34.36	peak
2	4367.058	7.41	33.60	38.20	44.98	47.79	74.00	-26.21	peak
3	4804.000	7.89	34.16	38.41	46.09	49.73	74.00	-24.27	peak
4	6395.654	11.34	35.02	37.89	44.07	52.54	74.00	-21.46	peak
5 pp	7206.000	10.08	36.42	37.10	43.70	53.10	74.00	-20.90	peak
6	9608.000	10.75	37.52	35.09	39.85	53.03	74.00	-20.97	peak

Mode:a; Polarization: Horizontal; Modulation Type: LORA; Channel:Low



Condition: 3m HORIZONTAL


Job No : 08075CR/08076CR

Mode : 2402 TX RSE

Note : LORA

	Freq	Cable Loss	Ant Factor	Preamplifier Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1620.431	5.32	26.34	38.03	44.92	38.55	74.00	-35.45	peak
2	4392.376	7.44	33.60	38.21	45.73	48.56	74.00	-25.44	peak
3	4804.000	7.89	34.16	38.41	44.38	48.02	74.00	-25.98	peak
4	6659.763	11.08	35.56	37.62	44.05	53.07	74.00	-20.93	peak
5 pp	7206.000	10.08	36.42	37.10	43.94	53.34	74.00	-20.66	peak
6	9608.000	10.75	37.52	35.09	39.78	52.96	74.00	-21.04	peak

Mode:a; Polarization:Vertical; Modulation Type: LORA; Channel:Low



Condition: 3m VERTICAL


Job No : 08075CR/08076CR

Mode : 2402 TX RSE

Note : LORA

	Freq	Cable Loss	Ant Factor	Preamplifier Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1677.621	5.25	26.58	38.03	43.99	37.79	74.00	-36.21	peak
2	3969.767	6.95	33.52	38.00	45.51	47.98	74.00	-26.02	peak
3	4804.000	7.89	34.16	38.41	44.92	48.56	74.00	-25.44	peak
4	6815.551	10.64	36.00	37.47	44.04	53.21	74.00	-20.79	peak
5 pp	7206.000	10.08	36.42	37.10	44.24	53.64	74.00	-20.36	peak
6	9608.000	10.75	37.52	35.09	40.06	53.24	74.00	-20.76	peak

Mode:a; Polarization: Horizontal; Modulation Type: LORA; Channel:Middle



Condition: 3m HORIZONTAL


Job No : 08075CR/08076CR

Mode : 2440 TX RSE

Note : LORA

	Freq	Cable Loss	Ant Factor	Preamplifier	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1473.013	5.39	25.69	38.04	53.68	46.72	74.00	-27.28	peak
2	4354.454	7.40	33.60	38.19	44.67	47.48	74.00	-26.52	peak
3	4880.000	7.97	34.29	38.45	43.54	47.35	74.00	-26.65	peak
4	6894.806	10.42	36.21	37.40	44.36	53.59	74.00	-20.41	peak
5	pp 7320.000	10.05	36.37	37.00	44.50	53.92	74.00	-20.08	peak
6	9760.000	10.82	37.55	35.02	39.80	53.15	74.00	-20.85	peak

Mode:a; Polarization:Vertical; Modulation Type: LORA; Channel:Middle



Condition: 3m VERTICAL


Job No : 08075CR/08076CR

Mode : 2440 TX RSE

Note : LORA

	Freq	Cable Loss	Ant Factor	Preamplifier Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1370.328	5.05	25.26	38.05	54.54	46.80	74.00	-27.20	peak
2	4157.664	7.17	33.60	38.09	50.66	53.34	74.00	-20.66	peak
3	4880.000	7.97	34.29	38.45	47.11	50.92	74.00	-23.08	peak
4	6679.040	11.02	35.61	37.60	44.01	53.04	74.00	-20.96	peak
5 pp	7320.000	10.05	36.37	37.00	34.51	43.93	54.00	-10.07	Average
6 pk	7320.000	10.05	36.37	37.00	47.45	56.87	74.00	-17.13	peak
7	9760.000	10.82	37.55	35.02	40.66	54.01	74.00	-19.99	peak

Mode:a; Polarization: Horizontal; Modulation Type: LORA; Channel:High



Condition: 3m HORIZONTAL


Job No : 08075CR/08076CR

Mode : 2480 TX RSE

Note : LORA

	Freq	Cable Loss	Ant Factor	Preamplifier Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1587.975	5.37	26.20	38.03	43.56	37.10	74.00	-36.90	peak
2	4157.664	7.17	33.60	38.09	44.98	47.66	74.00	-26.34	peak
3	4960.000	8.05	34.43	38.48	43.91	47.91	74.00	-26.09	peak
4	6640.542	11.13	35.50	37.64	42.34	51.33	74.00	-22.67	peak
5 pp	7440.000	10.02	36.32	36.89	44.02	53.47	74.00	-20.53	peak
6	9920.000	10.90	37.58	34.94	38.96	52.50	74.00	-21.50	peak

Mode:a; Polarization:Vertical; Modulation Type: LORA; Channel:High



Condition: 3m VERTICAL

Job No : 08075CR/08076CR

Mode : 2480 TX RSE

Note : LORA

	Freq	Cable Loss	Ant Factor	Preamplifier Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1625.121	5.32	26.36	38.03	45.71	39.36	74.00	-34.64	peak
2	4145.664	7.16	33.60	38.08	45.83	48.51	74.00	-25.49	peak
3	4960.000	8.05	34.43	38.48	46.04	50.04	74.00	-23.96	peak
4	6776.265	10.75	35.89	37.51	45.29	54.42	74.00	-19.58	peak
5 pp	7440.000	10.02	36.32	36.89	34.98	44.43	54.00	-9.57	Average
6 pk	7440.000	10.02	36.32	36.89	47.99	57.44	74.00	-16.56	peak
7	9920.000	10.90	37.58	34.94	40.30	53.84	74.00	-20.16	peak



Remark:


1) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Final Test Level = Receiver Reading + Antenna Factor + Cable Factor – Preamplifier Factor



2) Scan from 9kHz to 25GHz, the disturbance above 13GHz and below 30MHz was very low, and the above harmonics were the highest point could be found when testing, so only the above harmonics had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.

8 Photographs

8.1 Conducted Emissions at AC Power Line (150kHz-30MHz) Test Setup



8.2 Radiated Spurious Emissions Test Setup





8.3 EUT Constructional Details

Refer to Appendix A - Photographs of EUT Constructional Details for SZEM1708008075CR.





9 Appendix


9.1 Appendix -FLRC

1.6dB Bandwidth

Test Mode	Test Channel	Ant	EBW[MHz]	Limit[MHz]	Verdict
FLRC	2402	Ant1	0.501	≥ 0.5	PASS
FLRC	2402	Ant2	0.501	≥ 0.5	PASS
FLRC	2440	Ant1	0.504	≥ 0.5	PASS
FLRC	2440	Ant2	0.501	≥ 0.5	PASS
FLRC	2480	Ant1	0.501	≥ 0.5	PASS
FLRC	2480	Ant2	0.504	≥ 0.5	PASS












2.Maximum peak conducted output power

Test Mode	Test Channel	Ant	Power[dBm]	Limit[dBm]	Verdict
FLRC	2402	Ant1	9.13	<30	PASS
FLRC	2402	Ant2	9.02	<30	PASS
FLRC	2440	Ant1	9.84	<30	PASS
FLRC	2440	Ant2	9.52	<30	PASS
FLRC	2480	Ant1	10.34	<30	PASS
FLRC	2480	Ant2	9.98	<30	PASS













3.Maximum Peak power spectral density

Test Mode	Test Channel	Ant	PSD[dBm/3kHz]	Limit[dBm/3kHz]	Verdict
FLRC	2402	Ant1	-2.67	<8.00	PASS
FLRC	2402	Ant2	-2.76	<8.00	PASS
FLRC	2440	Ant1	-1.9	<8.00	PASS
FLRC	2440	Ant2	-1.83	<8.00	PASS
FLRC	2480	Ant1	-1.49	<8.00	PASS
FLRC	2480	Ant2	-1.4	<8.00	PASS











4. Band-edge for RF Conducted Emissions

Test Mode	Test Channel	Ant	Carrier Power[dBm]	Max. Spurious Level [dBm]	Limit [dBm]	Verdict
FLRC	2402	Ant1	8.710	-53.581	<-11.29	PASS
FLRC	2402	Ant2	8.560	-53.086	<-11.44	PASS
FLRC	2480	Ant1	9.970	-51.161	<-10.03	PASS
FLRC	2480	Ant2	9.610	-50.344	<-10.39	PASS











5.RF Conducted Spurious Emissions


Test Mode	Test Channel	StartFre [MHz]	StopFre [MHz]	RBW [kHz]	VBW [kHz]	Pref[dBm]	Max. Level [dBm]	Limit [dBm]	Verdict
FLRC(Ant.1)	2402	30	10000	1000	3000	8.67	-34.720	<-11.33	PASS
FLRC(Ant.1)	2402	10000	25000	1000	3000	8.67	-64.900	<-11.33	PASS
FLRC(Ant.2)	2402	30	10000	1000	3000	8.63	-34.830	<-11.37	PASS
FLRC(Ant.2)	2402	10000	25000	1000	3000	8.63	-64.990	<-11.37	PASS
FLRC(Ant.1)	2440	30	10000	1000	3000	9.52	-33.750	<-10.48	PASS
FLRC(Ant.1)	2440	10000	25000	1000	3000	9.52	-64.920	<-10.48	PASS
FLRC(Ant.2)	2440	30	10000	1000	3000	9.13	-34.360	<-10.87	PASS
FLRC(Ant.2)	2440	10000	25000	1000	3000	9.13	-65.260	<-10.87	PASS
FLRC(Ant.1)	2480	30	10000	1000	3000	10.12	-32.040	<-9.88	PASS
FLRC(Ant.1)	2480	10000	25000	1000	3000	10.12	-65.290	<-9.88	PASS
FLRC(Ant.2)	2480	30	10000	1000	3000	9.69	-32.740	<-10.31	PASS
FLRC(Ant.2)	2480	10000	25000	1000	3000	9.69	-65.160	<-10.31	PASS





































9.2 Appendix -GFSK

1.6dB Bandwidth

Test Mode	Test Channel	Ant	EBW[MHz]	Limit[MHz]	Verdict
GFSK	2402	Ant1	0.945	≥ 0.5	PASS
GFSK	2402	Ant2	0.942	≥ 0.5	PASS
GFSK	2440	Ant1	0.948	≥ 0.5	PASS
GFSK	2440	Ant2	0.942	≥ 0.5	PASS
GFSK	2480	Ant1	0.942	≥ 0.5	PASS
GFSK	2480	Ant2	0.945	≥ 0.5	PASS












2.Maximum peak conducted output power

Test Mode	Test Channel	Ant	Power[dBm]	Limit[dBm]	Verdict
GFSK	2402	Ant1	9.1	<30	PASS
GFSK	2402	Ant2	8.97	<30	PASS
GFSK	2440	Ant1	9.84	<30	PASS
GFSK	2440	Ant2	9.49	<30	PASS
GFSK	2480	Ant1	10.39	<30	PASS
GFSK	2480	Ant2	10.01	<30	PASS










3.Maximum Peak power spectral density


Test Mode	Test Channel	Ant	PSD[dBm/3kHz]	Limit[dBm/3kHz]	Verdict
GFSK	2402	Ant1	0.31	<8.00	PASS
GFSK	2402	Ant2	0.18	<8.00	PASS
GFSK	2440	Ant1	0.96	<8.00	PASS
GFSK	2440	Ant2	0.65	<8.00	PASS
GFSK	2480	Ant1	1.3	<8.00	PASS
GFSK	2480	Ant2	1.14	<8.00	PASS







Maximum Peak power spectral density_ GFSK _2402_Ant1



Maximum Peak power spectral density_ GFSK _2402_Ant2












4.Band-edge for RF Conducted Emissions

Test Mode	Test Channel	Ant	Carrier Power[dBm]	Max. Spurious Level [dBm]	Limit [dBm]	Verdict
GFSK	2402	Ant1	8.530	-52.363	<-11.47	PASS
GFSK	2402	Ant2	8.630	-53.966	<-11.37	PASS
GFSK	2480	Ant1	9.950	-49.805	<-10.05	PASS
GFSK	2480	Ant2	9.600	-48.982	<-10.4	PASS











5.RF Conducted Spurious Emissions


Test Mode	Test Channel	StartFre [MHz]	StopFre [MHz]	RBW [kHz]	VBW [kHz]	Pref[dBm]	Max. Level [dBm]	Limit [dBm]	Verdict
GFSK(Ant.1)	2402	30	10000	1000	3000	8.42	-34.710	<-11.58	PASS
GFSK(Ant.1)	2402	10000	25000	1000	3000	8.42	-65.230	<-11.58	PASS
GFSK(Ant.2)	2402	30	10000	1000	3000	8.54	-34.840	<-11.46	PASS
GFSK(Ant.2)	2402	10000	25000	1000	3000	8.54	-64.980	<-11.46	PASS
GFSK(Ant.1)	2440	30	10000	1000	3000	9.55	-33.700	<-10.45	PASS
GFSK(Ant.1)	2440	10000	25000	1000	3000	9.55	-64.770	<-10.45	PASS
GFSK(Ant.2)	2440	30	10000	1000	3000	9.27	-34.410	<-10.73	PASS
GFSK(Ant.2)	2440	10000	25000	1000	3000	9.27	-65.040	<-10.73	PASS
GFSK(Ant.1)	2480	30	10000	1000	3000	10.13	-31.980	<-9.87	PASS
GFSK(Ant.1)	2480	10000	25000	1000	3000	10.13	-65.180	<-9.87	PASS
GFSK(Ant.2)	2480	30	10000	1000	3000	9.66	-32.690	<-10.34	PASS
GFSK(Ant.2)	2480	10000	25000	1000	3000	9.66	-64.530	<-10.34	PASS





































9.3 Appendix - LORA

1.6dB Bandwidth

Test Mode	Test	Ant	EBW[MHz]	Limit[MHz]	Verdict
LORA	2402	Ant1	1.515	≥ 0.5	PASS
LORA	2402	Ant2	1.521	≥ 0.5	PASS
LORA	2440	Ant1	1.515	≥ 0.5	PASS
LORA	2440	Ant2	1.515	≥ 0.5	PASS
LORA	2480	Ant1	1.515	≥ 0.5	PASS
LORA	2480	Ant2	1.521	≥ 0.5	PASS












2.Maximum peak conducted output power

Test Mode	Test Channel	Ant	Power[dBm]	Limit[dBm]	Verdict
LORA	2402	Ant1	11.32	<30	PASS
LORA	2402	Ant2	9.05	<30	PASS
LORA	2440	Ant1	11.36	<30	PASS
LORA	2440	Ant2	9.61	<30	PASS
LORA	2480	Ant1	11.42	<30	PASS
LORA	2480	Ant2	10.08	<30	PASS










3.Maximum Peak power spectral density


Test Mode	Test Channel	Ant	PSD[dBm/3kHz]	Limit[dBm/3kHz]	Verdict
LORA	2402	Ant1	-5.07	<8.00	PASS
LORA	2402	Ant2	-5.21	<8.00	PASS
LORA	2440	Ant1	-4.52	<8.00	PASS
LORA	2440	Ant2	-4.71	<8.00	PASS
LORA	2480	Ant1	-4.25	<8.00	PASS
LORA	2480	Ant2	-4.47	<8.00	PASS



Maximum Peak power spectral density_ LORA _2402_Ant1




Maximum Peak power spectral density_ LORA _2402_Ant2








Maximum Peak power spectral density_ LORA _2440_Ant1



Maximum Peak power spectral density_ LORA _2440_Ant2









4.Band-edge for RF Conducted Emissions

Test Mode	Test Channel	Ant	Carrier Power[dBm]	Max. Spurious Level [dBm]	Limit [dBm]	Verdict
LORA	2402	Ant1	7.720	-50.662	<-12.28	PASS
LORA	2402	Ant2	7.800	-50.269	<-12.2	PASS
LORA	2480	Ant1	8.990	-34.835	<-11.01	PASS
LORA	2480	Ant2	9.180	-35.274	<-10.82	PASS







5.RF Conducted Spurious Emissions

Test Mode	Test Channel	StartFre [MHz]	StopFre [MHz]	RBW [kHz]	VBW [kHz]	Pref[dBm]	Max. Level [dBm]	Limit [dBm]	Verdict
LORA(Ant.1)	2402	30	10000	1000	3000	8.01	-34.670	<-11.99	PASS
LORA(Ant.1)	2402	10000	25000	1000	3000	8.01	-65.130	<-11.99	PASS
LORA(Ant.2)	2402	30	10000	1000	3000	7.83	-34.770	<-12.17	PASS
LORA(Ant.2)	2402	10000	25000	1000	3000	7.83	-64.610	<-12.17	PASS
LORA(Ant.1)	2440	30	10000	1000	3000	7.31	-33.870	<-12.69	PASS
LORA(Ant.1)	2440	10000	25000	1000	3000	7.31	-65.060	<-12.69	PASS
LORA(Ant.2)	2440	30	10000	1000	3000	8.43	-34.120	<-11.57	PASS
LORA(Ant.2)	2440	10000	25000	1000	3000	8.43	-64.160	<-11.57	PASS
LORA(Ant.1)	2480	30	10000	1000	3000	9.18	-32.140	<-10.82	PASS
LORA(Ant.1)	2480	10000	25000	1000	3000	9.18	-65.490	<-10.82	PASS
LORA(Ant.2)	2480	30	10000	1000	3000	8.7	-32.560	<-11.3	PASS
LORA(Ant.2)	2480	10000	25000	1000	3000	8.7	-65.040	<-11.3	PASS

