FCC Test Report (Bluetooth)

FCC ID	:	**SXXKTS-86**
Applicant	:	**Shenzhen KingBoard Technology Co., Ltd.** Bldg. A, Dakanglong Industry Zone Dabuxiang, Guanlan, Shenzhen, China
Sample Description		
Product Name	:	**Bluetooth Speaker**
Model No.	:	KTS-86
Serial No.	:	N/A
Trademark	:	N/A
Receipt Date	:	2015-06-03
Test Date	:	2015-06-04 to 2015-06-06
Issue Date	:	2015-06-08
Test Standard(s)	:	**FCC CFR Title 47 Part 15 Subpart C Section 15.247**
Conclusions	:	**PASSED***

*In the configuration tested, the EUT complied with the standards specified above.

Test/Witness Engineer : Jason Deng

Approved & Authorized : Frank Zhang

This report details the results of the testing carried out on one sample. The results contained in this test report do not relate to other samples of the same product. The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in the report.

Contents

CONTENTS 2
1. GENERAL INFORMATION 4
1.1. Client Information 4
1.2. General Description of EUT (Equipment Under Test) 4
1.3. Block Diagram Showing The Configuration of System Tested 5
1.4. Description of Support Units 6
1.5. External I/O Cable 6
1.6. Description of Test Mode 6
1.7. Test Instruments List 6
1.8. Laboratory Location 7
2. TEST SUMMARY 8
3. ANTENNA REQUIREMENT 9
3.1. Standard Requirement 9
3.2. Antenna Connected Construction 9
4. CONDUCTED EMISSION TEST 10
4.1. Test Standard and Limit 10
4.2. Test Setup 10
4.3. Test Procedure 10
4.4. Test Data 11
5. CONDUCTED PEAK OUTPUT POWER TEST 14
5.1. Test Standard and Limit 14
5.2. Test Setup 14
5.3. Test Procedure 14
5.4. Test Data 14
6. 20DB OCCUPY BANDWIDTH TEST 21
6.1. Test Standard and Limit 21
6.2. Test Setup 21
6.3. Test Procedure 21
6.4. Test Data 21
7. CARRIER FREQUENCY SEPARATION TEST 28
7.1. Test Standard and Limit 28
7.2. Test Setup 28
7.3. Test Procedure 28
7.4. Test Data 28
8. NUMBER OF HOPPING CHANNEL 32
8.1. Test Standard and Limit 32
8.2. Test Setup 32

8.3. Test Procedure 32
8.4. Test Data 32
9. DWELL TIME TEST 35
9.1. Test Standard and Limit 35
9.2. Test Setup 35
9.3. Test Procedure 35
9.4. Test Data 35
10. PSEUDORANDOM FREQUENCY HOPPING SEQUENCE 42
10.1. Standard Requirement 42
10.2. EUT Pseudorandom Frequency Hopping Sequence 42
11. BAND EDGE REQUIREMENT (CONDUCTED EMISSION METHOD) 43
11.1. Test Standard and Limit 43
11.2. Test Setup 43
11.3. Test Procedure 43
11.4. Test Data 43
12. BAND EDGE REQUIREMENT (RADIATED EMISSION METHOD) 47
12.1. Test Standard and Limit 47
12.2. Test Setup 47
12.3. Test Procedure 47
12.4. Test Data 48
13. SPURIOUS EMISSION (RADIATED EMISSION METHOD) 50
13.1. Test Standard and Limit 50
13.2. Test Setup 50
13.3. Test Procedure 50
13.4. Test Data 51

1. General Information

1.1. Client Information

Applicant	:	Shenzhen KingBoard Technology Co., Ltd.
Address	:	Bldg. A, Dakanglong Industry Zone Dabuxiang, Guanlan, Shenzhen, China
Manufacturer	:	Shenzhen KingBoard Technology Co., Ltd.
Address	:	Bldg. A, Dakanglong Industry Zone Dabuxiang, Guanlan, Shenzhen, China

1.2. General Description of EUT (Equipment Under Test)

Product Name	:	Bluetooth Speaker	
Models No.	:	KTS-86	
Difference	:	N/A	
Product Description	:	Operation Frequency:	2402MHz~2480MHz
		Transfer Rate:	1/2/3 Mbits/s
		Number of Channel:	79 Channels
		Modulation Type:	GFSK, π/4-DQPSK, 8-DPSK
		Modulation Technology:	FHSS
		Antenna Type:	Integral PCB Antenna
		Antenna Gain:	0 dBi
Power Supply	:	USB DC 5V from USB Port, DC 3.7V from Li-ion battery	

Note:

(1) For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.

(2) Channel List:

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
00	2402	27	2429	54	2456
01	2403	28	2430	55	2457
02	2404	29	2431	56	2458
03	2405	30	2432	57	2459
04	2406	31	2433	58	2460
05	2407	32	2434	59	2461
06	2408	33	2435	60	2462
07	2409	34	2436	61	2463

08	2410	35	2437	62	2464
09	2411	36	2438	63	2465
10	2412	37	2439	64	2466
11	2413	38	2440	65	2467
12	2414	39	2441	66	2468
13	2415	40	2442	67	2469
14	2416	41	2443	68	2470
15	2417	42	2444	69	2471
16	2418	43	2445	70	2472
17	2419	44	2446	71	2473
18	2420	45	2447	72	2474
19	2421	46	2448	73	2475
20	2422	47	2449	74	2476
21	2423	48	2450	75	2477
22	2424	49	2451	76	2478
23	2425	50	2452	77	2479
24	2426	51	2453	78	2480
25	2427	52	2454		
26	2428	53	2455		
Remark: Channel 0, 39 &78 selected for GFSK, π/4-DQPSK and 8DPSK.					

1.3. Block Diagram Showing The Configuration of System Tested





1.4. Description of Support Units

Name	Model	Serial Number	Manufacturer
Notebook	/	/	ASUS

1.5. External I/O Cable

N/A

1.6. Description of Test Mode

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned follow was evaluated respectively.

Test Mode	Description
Charging & Working mode	Keep the EUT in Charging& working mode
Transmitting mode	Keep the EUT in Transmitting mode with worst case data rate
Remark	GFSK(1Mbps) is the worst case mode

Remark: The sample was placed 0.8m above the ground plane of 3m chamber. Measurements in both horizontal and vertical polarities were performed. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, rotating the turntable, varying antenna height from 1m to 4m in both horizontal and vertical polarizations. The emissions worst-case are shown in Test Results of the following pages.

1.7. Test Instruments List

Item	Test Equipment	Manufacturer	Model No.	Cal. Date	Cal. Due date
1	Bilog Antenna	SCHWARZBECK MESS-ELEKTRONIK	VULB9163	May 23, 2015	May 22, 2016
2	Double -ridged waveguide horn	SCHWARZBECK MESS-ELEKTRONIK	BBHA9120D	May 28, 2015	May 27, 2016
3	Coaxial Cable	N/A	N/A	Mar. 30, 2015	Mar. 29, 2016
4	Coaxial Cable	N/A	N/A	Mar. 30, 2015	Mar. 29, 2016
5	Coaxial cable	N/A	N/A	Mar. 30, 2015	Mar. 29, 2016
6	Coaxial Cable	N/A	N/A	Mar. 30, 2015	Mar. 29, 2016
7	Coaxial Cable	N/A	N/A	Mar. 30, 2015	Mar. 29, 2016

8	Amplifier (10kHz-1.3GHz)	HP	8447D	Mar. 30, 2015	Mar. 29, 2016
9	Amplifier (1GHz-18GHz)	Compliance Direction Systems Inc.	PAP-1G18	Jun. 07, 2015	Jun. 06, 2016
10	Pre-amplifier (18-26GHz)	Rohde & Schwarz	AFS33-18002 650-30-8P-44	Mar. 30, 2015	Mar. 29, 2016
11	Horn Antenna	ETS-LINDGREN	3160	Mar. 28, 2015	Mar. 27, 2016
12	Positioning Controller	UC	UC3000	N/A	N/A
13	Spectrum analyzer 9kHz-30GHz	Rohde & Schwarz	FSP	May 27, 2015	May 26, 2016
14	EMI Test Receiver	Rohde & Schwarz	ESPI	Mar. 30, 2015	Mar. 29, 2016
15	Loop antenna	Laplace instrument	RF300	May 23, 2015	May 22, 2016
16	Universal radio communication tester	Rhode & Schwarz	CMU200	May 27, 2015	May 26, 2016
17	Signal Analyzer	Rohde & Schwarz	FSIQ3	May 27, 2015	May 26, 2016
18	L.I.S.N.#1	Rohde & Schwarz	NSLK8126	May 27, 2015	May 26, 2016
19	L.I.S.N.#2	Rohde & Schwarz	ENV216	May 27, 2015	May 26, 2016

1.8. Laboratory Location

Shenzhen TOBY technology Co., Ltd

Address: 1 A/F., Bldg.6, Yusheng Industrial Zone The National Road No.107 Xixiang Section 467, Xixiang, Bao'an, Shenzhen, Guangdong, 518057, China

At the time of testing, the Laboratory is accredited. It is listed in the United States of American Federal Communications Commission (FCC), and the registration number is 811562 7.

Tel:0086-755-26509301 Fax: 0086-755-26509195

2. Test Summary

Standard Section	Test Item	Judgment
15.203/15.247(c)	Antenna Requirement	PASSED
15.207	Conducted Emission	PASSED
15.247(b)(1)	Conducted Peak Output Power	PASSED
15.247(a)(1)	20dB Occupied Bandwidth	PASSED
15.247(a)(1)	Carrier Frequencies Separation	PASSED
15.247(a)(1)	Hopping Channel Number	PASSED
15.247(a)(1)	Dwell Time	PASSED
15.247(b)(4)&TCB Exclusion List (7 July 2002)	Pseudorandom Frequency Hopping Sequence	PASSED
15.205/15.209	Spurious Emission	PASSED
15.247(d)	Band Edge	PASSED
Remark: “N/A” is an abbreviation for Not Applicable.		

3. Antenna Requirement

3.1. Standard Requirement

3.1.1 Test standard

FCC Part15 Section 15.203 /247(c)

3.1.2 Requirement

1) 15.203 requirement:
An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

2) 15.247(c) (1)(i) requirement:
Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.

3.2. Antenna Connected Construction

The bluetooth antenna is an integral antenna which permanently attached, and the best case gain of the antenna is 0dBi. It complies with the standard requirement.

4. Conducted Emission Test

4.1. Test Standard and Limit

4.1.1 Test Standard

FCC Part15 Section 15.207

4.1.2 Test Limit

Conducted Emission Test Limit

Frequency	Maximum RF Line Voltage (dBμV)	
	Quasi-peak Level	Average Level
150kHz~500kHz	66 ~ 56 *	56 ~ 46 *
500kHz~5MHz	56	46
5MHz~30MHz	60	50
Remark: (1) *Decreasing linearly with logarithm of the frequency. (2) The lower limit shall apply at the transition frequencies.		

4.2. Test Setup



4.3. Test Procedure

1) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a 50Ω/50μH + 5Ω linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded.

2) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane.

The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal

ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2.

The Test Receiver setup: RBW=9kHz, VBW=30kHz, Sweep time= auto

4.4. Test Data

Please to see the following pages

Conducted Emission Test Data

EUT:	Bluetooth Speaker	M/N: KTS-86
Operating Condition:	Charging & Working mode	
Test Site:	Shielded room	
Operator:	Jason	
Test Specification:	AC120V/60Hz	
Polarization:	Line	
Note	Tem:25℃ Hum:50%	



Condition : FCC PART 15 B QP POL: LINE Temp:20.1 ℃ Hum:45 %

Item	Freq MHz	Read dBuV	LISN Factor dB	Preamp Factor dB	Cable Lose dB	Level dBuV	Limit dBuV	Margin dBuV	Remark
1	0.206	27.56	0.03	-9.72	0.10	37.43	63.36	-25.93	Peak
2	0.541	25.57	0.03	-9.72	0.10	35.42	56.00	-20.58	Peak
3	0.914	23.45	0.04	-9.71	0.10	33.30	56.00	-22.70	Peak
4	1.418	21.90	0.05	-9.71	0.10	31.76	56.00	-24.24	Peak
5	3.328	12.54	0.08	-9.69	0.12	22.43	56.00	-33.57	Peak
6	12.384	8.79	0.25	-9.45	0.22	18.71	60.00	-41.29	Peak

Remarks: Level = Read + LISN Factor - Preamp Factor + Cable loss

Conducted Emission Test Data

EUT:	Bluetooth Speaker	M/N: KTS-86
Operating Condition:	Charging & Working mode	
Test Site:	Shielded room	
Operator:	Jason	
Test Specification:	AC 120V/60Hz	
Polarization:	Neutral	
Note	Tem:25℃ Hum:50%	



Condition : FCC PART 15 B QP POL: NEUTRAL Temp:20.1 ℃ Hum:45 %

Item	Freq MHz	Read dBuV	LISN Factor dB	Preamp Factor dB	Cable Loss dB	Level dBuV	Limit dBuV	Margin dBuV	Remark
1	0.161	27.53	0.03	-9.72	0.10	37.38	65.43	-28.05	Peak
2	0.343	25.72	0.03	-9.72	0.10	35.57	59.13	-23.56	Peak
3	0.775	23.92	0.00	-9.71	0.10	33.73	56.00	-22.27	Peak
4	6.186	8.69	0.11	-9.60	0.14	18.54	60.00	-41.46	Peak
5	18.232	9.31	0.29	-9.45	0.32	19.37	60.00	-40.63	Peak

Remarks: Level = Read + LISN Factor - Preamp Factor + Cable loss

5. Conducted Peak Output Power Test

5.1. Test Standard and Limit

5.1.1 Test Standard

FCC Part15 C Section 15.247 (b)(3)

5.1.2 Test Limit

FCC Part 15 Subpart C(15.247)		
Test Item	Limit	Frequency Range (MHz)
Peak Output Power	Hopping Channels>75 Power<1W(30dBm) Other <125 mW(21dBm)	2400~2483.5

5.2. Test Setup



5.3. Test Procedure

(1) The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above.

(2) Spectrum Setting:

RBW=1MHz, VBW=3MHz, Detector=Peak (If 20dB BW ≤1 MHz)

RBW=3MHz, VBW=10MHz, Detector=Peak (If 20dB BW > 1 MHz)

(3) The EUT was set to continuously transmitting in the max power during the test.

5.4. Test Data

GFSK mode				
Channel Number	**Channel Frequency (MHz)**	**Test Result (dBm)**	**Limit (30dBm)**	**Judgment**
CH 00	2402	-0.528	21	PASSED
CH 39	2441	0.633	21	PASSED
CH 78	2480	0.903	21	PASSED
π/4-DQPSK mode				
Channel Number	**Channel Frequency (MHz)**	**Test Result (dBm)**	**Limit (30dBm)**	**Judgment**
CH 00	2402	-1.356	21	PASSED
CH 39	2441	-0.106	21	PASSED
CH 78	2480	0.197	21	PASSED
8DPSK mode				
Channel Number	**Channel Frequency (MHz)**	**Test Result (dBm)**	**Limit (30dBm)**	**Judgment**
CH 00	2402	-1.370	21	PASSED
CH 39	2441	-0.131	21	PASSED
CH 78	2480	0.128	21	PASSED
Remark: Test plot as follows				

Modulation mode		GFSK mode
2402MHz		
2441MHz		

2480MHz		

Modulation mode	π/4-DQPSK
2402MHz	

2441MHz		
2480MHz		

Modulation mode		8DPSK	
2402MHz			
2441MHz			

2480MHz		RF 50 Ω AC SENSE:INT ALIGN AUTO 02:19:45 PM Jun 06, 2015 arker 1 2.479850000000 GHz PNO: Fast IFGain:Low Trig: Free Run #Atten: 20 dB Avg Type: Log-Pwr Avg|Hold:>100/100 TRACE 1 2 3 4 5 6 TYPE M DET P N N N N N Mkr1 2.479 850 GHz 0.126 dBm dB/div Ref 10.00 dBm enter 2.480000 GHz tes BW 1.0 MHz #VBW 1.0 MHz Span 5.000 MHz Sweep 1.000 ms (1001 pts) STATUS Peak Search Next Peak Next Pk Right Next Pk Left Marker Delta Mkr→CF Mkr→Ref Lvl More 1 of 2

6. 20dB Occupy Bandwidth Test

6.1. Test Standard and Limit

6.1.1 Test Standard

FCC Part15 C Section 15.247 (a)(1)

6.1.2 Test Limit

FCC Part 15 Subpart C(15.247)		
Test Item	Limit	Frequency Range (MHz)
Bandwidth	20dB bandwidth	2400~2483.5

6.2. Test Setup



6.3. Test Procedure

(1) The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above.

(2) Spectrum Setting:
Bandwidth: RBW=30 kHz, VBW=100 kHz, detector= Peak

6.4. Test Data

Channel Number	Channel Frequency	20dB Bandwidth (kHz)		
		GFSK	π/4-DQPSK	8DPSK
CH 00	2402(MHz)	832.5	1180	1165
CH 39	2441(MHz)	829.3	1150	1160
CH 78	2480(MHz)	833.7	1150	1162
Remark: Test plot as follows				

Modulation mode		GFSK mode
2402MHz		
2441MHz		

2480MHz		Agilent Spectrum Analyzer - Occupied BW Center Freq 2.480000000 GHz Center Freq: 2.480000000 GHz Trig: Free Run #Atten: 20 dB Avg|Hold:>10/10 Radio Std: None Radio Device: BTS 11:02:37 AM Jun 06, 2015 Trace/Detector Clear Write Average Max Hold Min Hold Detector Peak Auto Man 10 dB/div Ref 10.00 dBm Log Center 2.48 GHz #Res BW 30 kHz #VBW 100 kHz Span 3 MHz #Sweep 3.2 ms Occupied Bandwidth 836.99 kHz Transmit Freq Error -3.271 kHz OBW Power 99.00 % x dB Bandwidth 833.7 kHz x dB -20.00 dB MSG STATUS

Modulation mode	π/4-DQPSK
2402MHz	
2441MHz	

2480MHz		Agilent Spectrum Analyzer - Occupied BW Center Freq 2.480000000 GHz Center Freq: 2.480000000 GHz Trig: Free Run #Atten: 20 dB Avg|Hold:>10/10 Radio Std: None Radio Device: BTS 11:03:23 AM Jun 06, 2015 Trace/Detector 10 dB/div Ref 10.00 dBm Log Clear Write Average Max Hold Min Hold Center 2.48 GHz #Res BW 30 kHz #VBW 100 kHz Span 3 MHz #Sweep 3.2 ms Occupied Bandwidth 1.0623 MHz Transmit Freq Error -1.814 kHz OBW Power 99.00 % x dB Bandwidth 1.115 MHz x dB -20.00 dB Detector Peak Auto Man MSG STATUS

Modulation mode		8DPSK
2402MHz		
2441MHz		

2480MHz		

Agilent Spectrum Analyzer - Occupied BW
RF 50 Ω AC
SENSE:INT
ALIGN AUTO
11:05:50 AM Jun 06, 2015
Center Freq 2.480000000 GHz
IFGain:Low
Center Freq: 2.480000000 GHz
Trig: Free Run
Avg|Hold:>10/10
#Atten: 20 dB
Radio Std: None
Radio Device: BTS
Trace/Detector
10 dB/div
Ref 10.00 dBm
Log
0.00
-10.0
-20.0
-30.0
-40.0
-50.0
-60.0
-70.0
-80.0
Clear Write
Average
Max Hold
Min Hold
Center 2.48 GHz
#Res BW 30 kHz
#VBW 100 kHz
Span 3 MHz
#Sweep 3.2 ms
Occupied Bandwidth
1.1029 MHz
Transmit Freq Error -1.782 kHz
OBW Power 99.00 %
x dB Bandwidth 1.162 MHz
x dB -20.00 dB
Detector
Peak
Auto
Man
MSG
STATUS

7. Carrier Frequency Separation Test

7.1. Test Standard and Limit

7.1.1 Test Standard

FCC Part15 C Section 15.247 (a)(1)

7.1.2 Test Limit

FCC Part 15 Subpart C(15.247)		
Test Item	Limit	Frequency Range (MHz)
Channel Separation	>25KHz or >two-thirds of the 20 dB bandwidth (Which is greater)	2400~2483.5

7.2. Test Setup



7.3. Test Procedure

(1) The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above.

(2) Spectrum Setting:
RBW=100 kHz, VBW=300 kHz, detector= Peak, Sweep Time =auto.

(3) The EUT was set to the Hopping Mode for Channel Separation Test and continuously transmitting for the Test.

7.4. Test Data

GFSK mode				
Channel Number	**Channel Frequency (MHz)**	**Test Result (KHz)**	**Limit (KHz)**	**Judgment**
CH 39	2441	1002	552.867	PASSED
π/4-DQPSK mode				
Channel Number	**Channel Frequency (MHz)**	**Test Result (KHz)**	**Limit (KHz)**	**Judgment**
CH 39	2441	1002	766.667	PASSED
8DPSK mode				
Channel Number	**Channel Frequency (MHz)**	**Test Result (KHz)**	**Limit (KHz)**	**Judgment**
CH 39	2441	1017	773.333	PASSED
Remark: Test plot as follows				

According to section 6.4

Test Mode	20dB bandwidth (kHz)	Limit (kHz) (Carrier Frequency Separation)
GFSK	829.3	552.867
π/4-DQPSK	1150	766.667
8DPSK	1160	773.333

Modulation mode	GFSK mode
2441MHz	

Modulation mode	π/4-DQPSK
2441MHz	