

Nemko Korea CO., Ltd.

300-2, Osan-Ri, Mohyun-Myun, Yongin-City, Gyunggi-Do, KOREA

TEL:+82 31 322 2333

FAX:+82 31 322 2332

FCC EVALUATION REPORT FOR CERTIFICATION

Applicant :

Bellwave Co.,Ltd.

23rd~24th FL. Construction Finance Center Bldg,395-70

Shindaebang-dong,Dongjak-gu,Seoul,156-714,Korea

Dates of Issue : September, 19, 2006

Test Report No. : NK2GR180

Test Site : Nemko Korea Co., Ltd.

FCC ID**SY6BPP-UP500****Brand Name**

Bellwave

Bellwave Co., Ltd.

CONTACT PERSON23rd~24th FL, Construction Finance Center Bldg.395-70

Shindaebang-dong,Dongjak-gu,Seoul,156-714,Korea

Mr. Ju-Won Seol

Telephone No. : +82 2 829-7415

Applied Standard:

FCC 47 CFR Part 15 & 2

FCC 47 CFR Part 22H & Part 24E

Classification:

FCC Class B Device

Equipment Class:

Public Mobile Services

EUT Type:

Dual-Band GSM Mobile Phone

The device bearing the brand name and FCC ID specified above has been shown to comply with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in ANSI C63.4-2003.

I attest to the accuracy of data and all measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.



Tested By : S. Lee
Engineer



Reviewed By : H.H. Kim
Manager & Chief Engineer

TABLE OF CONTENTS

1. Scope	4
2. Introduction (Site Description)	5
3. Test Conditions & EUT Information	6
4. Measuring Instrument Calibration	8
5. Summary of Test Results	9
6. Recommendation / Conclusion	10
7. Test Equipment	11
8. Description of Test	12
8.1 Conducted Emission	12
8.2 Radiated Emission	13
8.3 Effective Radiated Power / Equivalent Isotropic Radiated Power	14
8.4 Radiated Spurious & Harmonic Emission	15
8.5 Occupied Bandwidth / 26dB Emission Bandwidth	17
8.6 Spurious and Harmonic Emissions at Antenna Terminal	18
8.7 Frequency Stability / Temperature Variation	21
9. Test Data	22
9.1 Effective Radiated Power (ERP)	22
9.2 Equivalent Isotropic Radiated Power (EIRP)	23
9.3 Conducted Output Power	24
9.4 Occupied Bandwidth / 26dB Emission Bandwidth	25
9.5 Radiated Spurious & Harmonic Emission (GSM850)	26
9.6 Radiated Spurious & Harmonic Emission (PCS1900)	28
9.7 Frequency Stability / Temperature Variation (GSM850)	30
9.8 Frequency Stability / Temperature Variation (PCS1900)	32
9.9 AC Power LINE Conducted Emission	34

10. Emission Designator	42
11. Test Plots (GSM850)	43
12. Test Plots (PCS1900)	49
Appendix A: Labelling Requirement	55
Appendix B: Photographs of Test Set-up	56
Appendix C: EUT Photographs	58
Appendix D: Schematic Diagram	72
Appendix E: Block Diagram	73
Appendix F: USER'S Manual	74
Appendix G: Operational Description	75
Appendix H: Turn up Procedure	76

1. Scope

Measurement and determination of electromagnetic emissions (EME) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission under FCC Part 15 & Part 22 & 24.

Responsible Party:	Bellwave Co.,Ltd.
Contact Person:	Mr. Ju-Won Seol Tel : +82 2 829-7415
Manufacturer:	Bellwave Co.,Ltd. 23 rd ~24th FL. Construction Finance Center Bldg,395-70 Shindaebang-dong,Dongjak-gu,Seoul,156-714,Korea

- | | |
|----------------------|--|
| ● FCC ID: | SY6BPP-UP500 |
| ● Model: | BPP-UP500 |
| ● Brand Name: | Bellwave |
| ● EUT Type: | Dual-Band GSM Mobile Phone |
| ● Electric Rating: | DC3.7V, 650mA |
| ● Equipment Class: | Public Mobile Services |
| ● Classification: | Licensed Portable Transmitter Held to Ear (PCE) |
| ● Applied Standard: | FCC 47 CFR Part 15 & 2
FCC 47 CFR Part 22H &24E |
| ● Test Procedure(s): | ANSI C63.4 (2003), TIA/EIA603 |
| ● Dates of Test: | September 04, 2006 to September 18, 2006 |
| ● Place of Tests: | Nemko Korea Co., Ltd. |
| ● Test Report No.: | NK2GR180 |

2. Introduction (Site Description)

The measurement procedure described in American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9kHz to 40GHz (ANSI C63.4-2003) was used in determining radiated and conducted emissions emanating from **Bellwave Co.,Ltd.**

FCC ID : **SY6BPP-UP500**

These measurement tests were conducted at **Nemko Korea Co., Ltd.**

The site address is 300-2, Osan-Ri, Mohyun-Myun, Yongin-City, GyungGi-Do, KOREA
The area of Nemko Korea Corporation Ltd. Test Site is located in a mountain area at 80 kilometers (48 miles) southeast and Incheon International Airport (Incheon Airport), 30 kilometers (18miles) south-southeast from central Seoul.

It is located in the valley surrounded by mountains in all directions where ambient radio signal conditions are quiet and a favorable area to measure the radio frequency interference on open field test site for the computing and ISM devices manufactures.

The detailed description of the measurement facility was found to be in compliance with the requirements of § 2.948 according to ANSI C63.4 2003.



Nemko Korea Co., Ltd.
300-2, Osan-Ri, Mohyun-Myun,
Yongin-City GyungGi-Do, KOREA
449-852
Tel)+82-31-322-2333
Fax)+82-31-322-2332

Fig. 1. The map above shows the Seoul in Korea vicinity area.
The map also shows Nemko Korea Corporation Ltd. and Incheon Airport.

3. Test Conditions & EUT Information

Operating During Test

The EUT was tested at the lowest channel, middle channel and the highest channel with the maximum RF Power and all data recorded in the report.

Environmental Conditions

Temperature	22℃ ~ 25℃
Relative Humidity	35% ~ 75%

Description of EUT

Frequency Range	GSM850	Tx : 824.2MHz ~ 848.8MHz Rx : 869.2MHz ~ 893.8MHz
	PCS1900	Tx : 1850.2MHz ~ 1909.8MHz Rx : 1930.2MHz ~ 1989.8MHz
Output Power	GSM850	2.009W ERP (33.03dBm)
	PCS1900	1.380W EIRP (31.40dBm)
Emission Designator	250KGXW	
Modulation(s)	GSM	
Frequency Tolerances	±0.00025%(2.5ppm)	
Antenna Type	Internal	
Dimensions (L X W X H)	132 X 40 X 20mm (80 X 40 X 20mm)	
Weight	63g(with Battery)	
Operating Conditions	Storage : -30℃ ~ +60℃	
DC Input Voltage	+3.7Vdc, 650mA	

Support Equipment

Dual Band GSM Mobile Phone (EUT)	Bellwave Co., Ltd. FCC ID: SY6BPP-UP500	S/N: N/A
Travel Adaptor	Bellwave Co., Ltd. Model : TA-11E 1.5m shielded dc power cable	S/N: N/A
Headset	Bellwave Co., Ltd. Model : N/A 1.2m unshielded mono jack cable	S/N: N/A
Wireless Communications Test set	Agilent Model: E5515C 1.8m shielded power cable	S/N: GB43193659

4. Measuring Instrument Calibration

All measurements were made with instruments calibrated according to the recommendation by manufacturer. Measurement of radiated emissions and conducted emissions were made with instruments conforming to American National Standards Institute, ANSI C63.4-2003.

The calibration of measuring instrument, including any accessories that may affect test results, were performed according to the recommendation by manufacturer.

- End of page -

5. Summary of Test Results

The EUT has been tested according to the following specification:

Description of Test	FCC Rule	Result
Modulation Characteristics	§2.1047	Complies
ERP / EIRP Measurement	§2.1046 §22.913(a) §24.232(b)	Complies
Conducted Output Power	§2.1046(a) §22.913(a) §24.232(a)	Complies
Occupied Bandwidth / 26dB Bandwidth	§2.1049(h)	Complies
Spurious Emission at antenna Terminals	§2.1051 §22.917(a) §24.238(a)	Complies
Field Strength of spurious Radiation	§2.1053 §22.917(a) §24.238(a)	Complies
Frequency Stability / Temperature Variation	§2.1055 §22.355 §24.235	Complies
Band Edge	§22.917(a) §24.238(a)	Complies
AC Power Line Conducted Emission	§15.207	Complies

6. Recommendation / Conclusion

The data collected shows that the Bellwave Dual-Band GSM Mobile Phone.
FCC ID : SY6BPP-UP500 complies with all the requirements of Parts 2 & 22 & 24
of the FCC Rules.

The highest emission observed was at **0.51MHz** for conducted emissions with a
Q.P margin of **6.6dB**.

7. Test Equipment List

No.	Instrument	Manufacturer	Model	Serial No.	Calibration Date	Calibration Interval
1	Test Receiver	R & S	ESCS 30	833364/020	Aug. 17 2006	1year
2	*Test Receiver	R & S	ESCS 30	100302	Dec. 06 2005	1year
3	Amplifier	Agilent	8447F	3113A04549	Aug. 17 2006	1year
4	Amplifier	HP	8447F	2944A03956	Aug. 17 2006	1year
5	*Amplifier	HP	8447F	2805A03351	Oct. 25 2005	1year
6	*Amplifier	HP	8449B	3008A00107	Mar. 12 2006	1year
7	*Spectrum Analyzer	HP	8566B	267A03469	Mar.10 2006	1year
8	Spectrum Analyzer	Advantest	R3265A	45060401	Dec.06 2005	1year
9	Spectrum Analyzer	HP	8568B	1912A00573	Oct.25 2005	1year
10	*Biconical Log-Perio. Antenna	ARA	LBP-2520/A	1203	May. 06 2006	1year
11	*Double Ridged Broadband Horn Antenna	Schwarzbeck	BBHA 9120 D	9120D-474	Apr. 05 2006	1year
12	*Biconical Log Antenn	ARA	LPB-2520/A	1180	Mar. 06 2006	1year
13	Signal Generater	R & S	SMP02	833286/003	Aug. 17 2006	1year
14	*LISN	R & S	ESH3-Z5	833874/006	Oct. 25 2005	1year
15	*Position Controller	DAEIL EMC	N/A	N/A	N/A	N/A
16	*Turn Table	DAEIL EMC	N/A	N/A	N/A	N/A
17	*Antenna Mast	DAEIL EMC	N/A	N/A	N/A	N/A
18	*Anechoic Chamber	EM Eng.	N/A	N/A	N/A	N/A
19	*Shielded Room	EM Eng.	N/A	N/A	N/A	N/A
20	*Position Controller	Inn-co	CO2000	N/A	N/A	N/A
21	*Turn Table	Inn-co	DS1200S	N/A	N/A	N/A
22	*Antenna Mast	Inn-co	AS2000P	N/A	N/A	N/A
23	*Anechoic Chamber	Seo-Young EMC	N/A	N/A	N/A	N/A
24	*Double Ridged Broadband Horn Antenna	Schwarzbeck	BBHA 9120 D	9120D-508	Oct. 12 2005	1year
25	*Communications Test Set	Agilent	E5515C	GB43193659	Jun.09 2006	1year
26	*Spectrum Analyzer	Agilent	E4440A	MY44022567	Dec.31 2005	1year
27	*Signal Generator	Anritsu	68245B	983206	Jan.06 2006	1year

*) Test equipment used during the test

8. Description of Tests

8.1 Conducted Emissions

The Line conducted emission test facility is located inside a 4 X 7 X 2.5 meter shielded enclosure.

It is manufactured by EM engineering. The shielding effectiveness of the shielded room is in accordance with MIL-STD-285 or NSA 65-6.

A 1m X 1.5m wooden table 0.8m height is placed 0.4m away from the vertical wall and 1.5m away from the side of wall of the shielded room

Rohde & Schwarz (ESH3-Z5) and Kyoritsu (KNW-407) of the 50ohm/50uH Line Impedance Stabilization Network(LISN) are bonded to the shielded room.

The EUT is powered from the Rohde & Schwarz LISN and the support equipment is powered from the Kyoritsu LISN. Power to the LISN s are filtered by high-current high insertion loss Power line filters. The purpose of filter is to attenuate ambient signal interference and this filter is also bonded to shielded enclosure. All electrical cables are shielded by tinned copper zipper tubing with inner diameter of 1/2".

If DC power device, power will be derived from the source power supply it normally will be powered from and this supply lines will be connected to the LISNs,

All interconnecting cables more than 1 meter were shortened by non inductive bundling (serpentine fashion) to a 1 meter length.

Sufficient time for EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The RF output of the LISN was connected to the spectrum analyzer to determine the frequency producing the maximum EME from the EUT. The spectrum was scanned from 150kHz to 30MHz with 20msec sweep time.

The frequency producing the maximum level was re-examined using the EMI test receiver. (Rohde & Schwarz ESCS30).

The detector function were set to CISPR quasi-peak mode & average mode.

The bandwidth of receiver was set to 9KHz. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each EME emission.

Each emission was maximized by; switching power lines; varying the mode of operation or resolution; clock or data exchange speed; scrolling H pattern to the EUT and of support equipment, and powering the monitor from the floor mounted outlet box and computer aux AC outlet, if applicable; which ever determined the worst case emission.

Each EME reported was calibrated using the R&S signal generator.




Fig. 2. LISN Schematic Diagram

8.2 Radiated Emissions

Preliminary measurement were made indoors at 3 meter using broad band antennas, broadband amplifier, and spectrum analyzer to determine the frequency producing the maximum EME. Appropriate precaution was taken to ensure that all EME from the EUT were maximized and investigated. The Technology configuration, clock speed, mode of operation or video resolution, turntable azimuth with respect to the antenna was note for each frequency found. The spectrum was scanned from 30 to 1000MHz using Biconical log Antenna (ARA, LPB-2520/A).

Final Measurements were made outdoors at 3 or 10m test range using Logbicon Super Antenna (Schwarzbeck, VULB 9166).

The test equipment was placed on a wooden table.

Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition.

Each frequency found during pre-scan measurements was reexamined and investigated using EMI test receiver.(ESCS30)

The detector function were set to CISPR quasi-peak and peak mode and the bandwidth of the receiver were set to 120KHz and 1MHz depending on the frequency or type of signal. The half wave dipole antenna was tuned to the frequency found during preliminary radiated measurements.

The EUT support equipment and interconnecting cables were re configured to the setup producing the maximum emission for the frequency and were placed on top of a 0.8m high non- metallic 1.0X 1.5 meter table.

The EUT, support equipment and interconnecting cables were re-arranged and manipulated to maximize each EME emission.

The turn table containing the Technology was rotated; the antenna height was varied 1 to 4meter and stopped at the azimuth or height producing the maximum emission. Each emission was maximized by : switching power lines; varying the mode of operation or resolution; clock or data exchange speed; scrolling H pattern to the EUT and of support equipment, and powering the monitor from the floor mounted outlet box and computer aux AC outlet, if applicable; which ever determined the worst case emission.

Each EME reported was calibrated using the R/S signal generator.




Fig. 3. Dimensions of Outdoor Test Site

8.3 Effective Radiated Power / Equivalent Isotropic Radiated Power

Test Set-up

Effective Radiated Power Output and Equivalent Isotropic Radiated Power output Measurements by Substitution Method according to ANSI/TIA/EIA-603-A-2003.




Figure 4. Diagram of ERP/EIRP test Set-up

The EUT was set on a non-conductive turntable in a semi anechoic chamber. In the corner of the chamber there was a communication antenna, which was connected to the BS simulator located outside the chamber. The radiated power from the EUT was measured with an antenna fixed to a antenna tower. The tower and turn table were remotely controlled to turn the EUT and change the antenna polarization. The measured signal was routed from the measuring antenna to the spectrum analyzer. The BS simulator was used to set the TX channel and power level and modulate the TX signal with different bit patterns.

Test Method

- The maximum power level was searched by moving the turn table and measuring antenna and manipulating the EUT. This level (P_{EUT}) was recorded.
- The EUT was replaced with a substituting antenna.
- The substituting antenna was fed with the power (P_{Subst_TX}) giving a convenient reading on the spectrum analyzer. That reading (P_{Subst_RX}) on spectrum analyzer was recorded.

8.4 Radiated Spurious & Harmonic Emission

Test Set-up

Effective Radiated Power Output and Equivalent Isotropic Radiated Power output Measurements by Substitution Method according to ANSI/TIA/EIA-603-A-2003.




Figure 5. Diagram of Radiated Spurious & Harmonic test Set-up

The EUT was set on a non-conductive turntable in a semi anechoic chamber. In the corner of the chamber there was a communication antenna, which was connected to the BS simulator located outside the chamber. The radiated power from the EUT was measured with an antenna fixed to a antenna tower. The tower and turn table were remotely controlled to turn the EUT and change the antenna polarization. The measured signal was routed from the measuring antenna to the spectrum analyzer. The BS simulator was used to set the TX channel and power level and modulate the TX signal with different bit patterns.

Test Method

- The maximum power level was searched by moving the turn table and measuring antenna and manipulating the EUT. This level (P_{EUT}) was recorded.
- The EUT was replaced with a substituting antenna.
- The substituting antenna was fed with the power (P_{Subst_TX}) giving a convenient reading on the spectrum analyzer. That reading (P_{Subst_RX}) on spectrum analyzer was recorded.

CALCULATION

The formula below was used to calculate the ERP/EIRP of the EUT.

$P_{\text{subst_TX[dBm]}}$, $P_{\text{subst_RX[dBm]}}$, $L_{\text{Cable[dB]}}$ and $G_{\text{substitute_antenna[dBd]}}$ factors are combined in one correction factor.

$$P_{\text{ERP[W]}} = \frac{10^{(P_{\text{sust_Tx[dBm]}} + P_{\text{EUT[dBm]}} - P_{\text{subst_Rx[dBm]}} + G_{\text{subst_antenna[dBd]}} - L_{\text{cable[dB]}}) / 10}}{1000}$$

where the variables are as follows:

$P_{\text{EUT [dBm]}}$	Measured power level from the EUT
$P_{\text{Subst_TX [dBm]}}$	Power fed to the substituting antenna
$P_{\text{Subst_RX [dBm]}}$	Power received with the spectrum analyzer
$G_{\text{Substitute_antenna [dBd]}}$	Gain of the substitutive antenna over dipole (dBi – 2.15dB)
$L_{\text{Cable [dB]}}$	Loss of the cable between signal generator and the substituting antenna

8.5 Occupied Bandwidth / 26dB Emission Bandwidth

Occupied Bandwidth

The EUT was setup to maximum output power at its lowest channel.
The occupied bandwidth was measured using a spectrum analyzer.
The measurements are repeated for the highest and a middle channel.
The EUT's occupied bandwidth is measured as the width of the signal between two points, one below the carrier center frequency and one above the carrier frequency, outside of which all emissions are attenuated at least 26dB below the transmitter power.
Plots of the EUT's occupied bandwidth are shown.

26dB Emission Bandwidth

The transmitter output is connected to the spectrum analyzer.
The RBW of spectrum analyzer is set to approximately 1% of the emission bandwidth
And peak detection is used.
The emission bandwidth is defined as the total spectrum over which the power is higher than the peak power minus 26dB.

8.6 Spurious and Harmonic Emissions at Antenna Terminal

8.6.1 Occupied Bandwidth Emission Limits

- (a) On any frequency outside a license's frequency block, the power of any emission shall be attenuated below the transmitter power (P) by at least $43 + 10 \log(P)$ dB.
- (b) Compliance with these provisions is based on the use of measurement instrumentation employing a resolution bandwidth of 1 MHz or greater.
However, in the 1MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least 1% of the emission bandwidth of the fundamental emission of the transmitter may be employed.
The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emission are attenuated at least 26 dB below the transmitter power.
- (c) When measuring the emission limits, the nominal carrier frequency shall be adjusted as close to the licensee's frequency block edges, both upper and lower, as the design permits.
- (d) The measurement of emission power can be expressed in peak or average values, provided they are expressed in the same parameters as the transmitter power.

BLOCK	Frequency Range (MHz) Transmitter (Tx)	Frequency Range (MHz) Receiver (Rx)
A* Low +A	824 ~ 835	869 ~ 880
B	835 ~ 845	880 ~ 890
A* High	845 ~ 846.5	890 ~ 891.5
B*	846.5 ~ 849	891.5 ~ 894

Table 1. Cellular Service Frequency Blocks

BLOCK	Frequency Range (MHz) Transmitter (Tx)	Frequency Range (MHz) Receiver (Rx)
A	1850 ~ 1865	1930 ~ 1745
B	1870 ~ 1885	1950 ~ 1965
C	1895 ~ 1910	1975 ~ 1990
D	1865 ~ 1870	1945 ~ 1950
E	1885 ~ 1890	1965 ~ 1970
F	1890 ~ 1895	1970 ~ 1975

Table 2. Broadband PCS Service Frequency Blocks

8.6.2 Conducted Spurious Emission

Minimum standard:

On any frequency outside a license frequency block, the power of any emission shall be attenuated below the transmitter power (P) by at least $43+10\log(P)$ dB. Limit equivalent to -13dBm, calculation shown below.

$$43 + 10\log(2.009 \text{ W}) = 46.03 \text{ dB}$$

$$33.03\text{dBm} - 46.03 \text{ dB} = -13 \text{ dBm}$$

Compliance with the out-of-band emissions requirement is based on test being performed with an analyzer resolution bandwidth of 1MHz. However in the 1MHz band immediately outside and adjacent to the frequency block a resolution bandwidth of at least 1% of the fundamental emissions bandwidth may be employed.

Test Procedure:

The EUT was setup to maximum output power at its lowest channel.

The Resolution BW of the analyzer is set to 1% of the emission bandwidth to show compliance with the -13dBm limit, in the 1MHz bands immediately outside and adjacent to the edge of the frequency block.

The measurements are repeated for the EUT's highest channel. For the Out-of-Band measurements a 1MHz RBW was used to scan from 10MHz to 20GHz.

A display line was placed at -13dBm to show compliance. The high, lowest and a middle channel were tested for out of band measurements.

Plots are shown.

8.7 Frequency Stability / Temperature Variation

The frequency stability of the transmitter is measured by:

- a.) Temperature: The temperature is carried from -30°C to +60°C using an environmental chamber.
- b.) Primary Supply Voltage: The primary supply voltage is varied from 85% to 115% of the voltage normally at the input to the device or at the power supply terminals if cables are not normally supplied.

Specification: The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within $\pm 0.00025\%$ ($\pm 2.5\text{ppm}$) of the center frequency.

Time Period and Procedure:

1. The carrier frequency of the transmitter and the individual oscillators is measured at room temperature (20°C to 25°C to provide a reference).
2. The equipment is subjected to an overnight "soak" at -30°C without any power applied.
3. After the overnight "soak" at -30°C (Usually 14~16 hours), the equipment is turned on in a "standby" condition for one minute before applying power to the transmitter. Measurement of the carrier frequency of the transmitter and the individual oscillators is made within a three minute interval after applying to the transmitter.
4. Frequency measurements are made at 10°C interval up to room temperature. At least a period of one and one half-hour is provided to allow stabilization of the equipment at each temperature level.
5. Again the transmitter carrier frequency and the individual oscillators is measured at room temperature to begin measurement of the upper temperature levels.
6. Frequency measurements are at 10 intervals starting at -30°C up to +60°C allowing at least two hours at each temperature for stabilization. In all measurements the frequency is measured within three minutes after re-applying power to the transmitter.
7. The artificial load is mounted external to the temperature chamber.

Note : The EUT is tested down to the battery endpoint.

9. Test Data

9.1 Effective Radiated Power (ERP)

EUT Mode : GSM850

Measurement Result :

Frequency (MHz)	*EUT Pol.	Ant. Pol.	P _{EUT} (dBm)	P _{TX} (dBm)	P _{RX} (dBm)	G _{antenna} (dBd)	L _{Cable} (dBm)	ERP (dBm)	Limit (dBm)
824.2	H	H	-23.42	0.00	-39.99	0.99	1.55	16.01	38.45
		V	-10.51	0.00	-44.10	0.99	1.55	33.03	
	E1	H	-11.47	0.00	-39.99	0.99	1.55	27.96	
		V	-19.97	0.00	-44.10	0.99	1.55	23.57	
	E2	H	-11.84	0.00	-39.99	0.99	1.55	27.59	
		V	-25.41	0.00	-44.10	0.99	1.55	18.13	
836.6	H	H	-23.04	0.00	-39.46	1.31	1.54	16.19	38.45
		V	-10.19	0.00	-43.45	1.31	1.54	33.03	
	E1	H	-11.23	0.00	-39.46	1.31	1.54	28.00	
		V	-20.60	0.00	-43.45	1.31	1.54	22.62	
	E2	H	-11.65	0.00	-39.46	1.31	1.54	27.58	
		V	-25.80	0.00	-43.45	1.31	1.54	17.42	
848.8	H	H	-22.68	0.00	-38.37	1.63	1.48	15.84	38.45
		V	-9.87	0.00	-40.78	1.63	1.48	31.06	
	E1	H	-11.13	0.00	-38.37	1.63	1.48	27.39	
		V	-20.14	0.00	-40.78	1.63	1.48	20.79	
	E2	H	-11.79	0.00	-38.37	1.63	1.48	26.73	
		V	-25.67	0.00	-40.78	1.63	1.48	15.26	

Table 8. Radiated Measurements at 3meters

9.2 Equivalent Isotropic Radiated Power (EIRP)

EUT Mode : PCS1900

Measurement Result:

Frequency (MHz)	*EUT Pol.	Ant. Pol.	P _{EUT} (dBm)	P _{TX} (dBm)	P _{RX} (dBm)	G _{antenna} (dBi)	L _{Cable} (dBm)	ERP (dBm)	Limit (dBm)
1850.2	H	H	-23.11	0.00	-34.65	10.40	2.57	19.37	33
		V	-12.14	0.00	-35.43	10.40	2.57	31.12	
	E1	H	-17.04	0.00	-34.65	10.40	2.57	25.44	
		V	-15.68	0.00	-35.43	10.40	2.57	27.58	
	E2	H	-16.93	0.00	-34.65	10.40	2.57	25.55	
		V	-18.33	0.00	-35.43	10.40	2.57	24.93	
1880.0	H	H	-23.79	0.00	-34.85	10.43	2.58	18.91	33
		V	-12.14	0.00	-35.67	10.43	2.58	31.38	
	E1	H	-15.88	0.00	-34.85	10.43	2.58	26.82	
		V	-16.01	0.00	-35.67	10.43	2.58	27.51	
	E2	H	-16.49	0.00	-34.85	10.43	2.58	26.21	
		V	-17.08	0.00	-35.67	10.43	2.58	26.44	
1909.8	H	H	-24.05	0.00	-35.29	10.44	2.58	19.10	33
		V	-12.49	0.00	-36.03	10.44	2.58	31.40	
	E1	H	-16.84	0.00	-35.29	10.44	2.58	26.31	
		V	-16.79	0.00	-36.03	10.44	2.58	27.10	
	E2	H	-18.01	0.00	-35.29	10.44	2.58	25.14	
		V	-18.07	0.00	-36.03	10.44	2.58	25.82	

Table 8. Radiated Measurements at 3meters

9.3 Conducted Output Power

Measurement Result:

EUT Mode	Channel	Frequency (MHz)	Measurement Power (dBm)
GSM850	128	824.2	32.14
	190	836.6	32.30
	251	848.8	32.42

Measurement Result:

EUT Mode	Channel	Frequency (MHz)	Measurement Power (dBm)
PCS1900`	512	1850.2	28.83
	661	1880.0	28.78
	810	1909.8	28.70

9.4 Occupied Bandwidth / 26dB Emission Bandwidth

Measurement Result:

EUT Mode	Channel	Frequency (MHz)	Occupied BW (KHz)	26dB Emission BW (KHz)
GSM850	128	824.2	247	313
	190	836.6	244	313
	251	848.8	243	304

Measurement Result:

EUT Mode	Channel	Frequency (MHz)	Occupied BW (KHz)	26dB Emission BW (KHz)
PCS1900	512	1850.2	246	308
	661	1880.0	243	316
	810	1909.8	247	313

- End of page -

9.5 Radiated Spurious & Harmonic Emission (GSM850)

Measurement Result:

CH128 (824.2MHz)

Freq. (MHz)	*EUT Pol.	Ant. Pol.	P _{EUT} (dBm)	P _{TX} (dBm)	P _{RX} (dBm)	G _{antenna} (dBd)	L _{Cable} (dB)	ERP (dBm)	Limit (dBm)	Margin (dB)
1648.4	E1	H	-36.16	0.00	-1.15	7.62	2.28	-29.67	-13	16.67
1648.4	E1	V	-45.06	0.00	-1.11	7.62	2.28	-38.61	-13	25.61
2472.6	E2	H	-58.26	0.00	-3.56	8.34	3.03	-49.39	-13	36.39
2472.6	E2	V	-61.85	0.00	-3.69	8.34	3.03	-52.85	-13	39.85
3296.8	E1	H	-62.12	0.00	-5.24	10.61	3.62	-49.89	-13	36.89
3296.8	E2	V	-63.97	0.00	-5.07	10.61	3.62	-51.91	-13	38.91

CH190 (836.6MHz)

Freq. (MHz)	*EUT Pol.	Ant. Pol.	P _{EUT} (dBm)	P _{TX} (dBm)	P _{RX} (dBm)	G _{antenna} (dBd)	L _{Cable} (dB)	ERP (dBm)	Limit (dBm)	Margin (dB)
1673.2	E1	H	-38.35	0.00	-1.23	7.80	2.30	-31.62	-13	18.62
1673.2	H	V	-34.62	0.00	-1.15	7.80	2.30	-27.97	-13	14.97
2509.8	E2	H	-57.93	0.00	-3.75	8.47	3.04	-48.75	-13	35.75
2509.8	H	V	-57.07	0.00	-3.78	8.47	3.04	-47.86	-13	34.86
3346.4	H	H	-65.61	0.00	-5.00	10.71	3.63	-53.53	-13	40.53
3346.4	H	V	-65.73	0.00	-4.86	10.71	3.63	-53.79	-13	40.79

CH251 (848.8MHz)

Freq. (MHz)	*EUT Pol.	Ant. Pol.	P _{EUT} (dBm)	P _{TX} (dBm)	P _{RX} (dBm)	G _{antenna} (dBd)	L _{Cable} (dB)	ERP (dBm)	Limit (dBm)	Margin (dB)
1697.6	E1	H	-46.06	0.00	-1.24	7.96	2.31	-39.17	-13	26.17
1697.6	E1	V	-50.72	0.00	-1.16	7.96	2.31	-43.91	-13	30.91
2546.4	H	H	-61.25	0.00	-3.93	8.53	3.04	-51.83	-13	38.83
2546.4	H	V	-56.48	0.00	-3.88	8.53	3.04	-47.11	-13	34.11
3395.2			---					---		
3395.2			---					---		

Note: 1. All modes of operation were investigated and the worst -case emission are reported.

2. “---“ means that the emission level is too low to be measured

- End of page -

9.6 Radiated Spurious & Harmonic Emission (PCS1900)

Measurement Result :

CH512 (1850.2MHz)

Freq. (MHz)	*EUT Pol.	Ant. Pol.	P _{EUT} (dBm)	P _{TX} (dBm)	P _{RX} (dBm)	G _{antenna} (dBi)	L _{Cable} (dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)
3700.4	H	H	-57.63	0.00	-10.79	12.69	3.77	-37.92	-13	24.92
3700.4	E2	V	-55.87	0.00	-10.91	12.69	3.77	-36.04	-13	23.04
5550.6	H	H	-49.26	0.00	-10.23	13.15	4.92	-30.80	-13	17.80
5550.6	E1	V	-51.74	0.00	-10.18	13.15	4.92	-33.33	-13	20.33
7400.8	E2	H	-52.48	0.00	-20.53	11.70	6.54	-26.79	-13	13.79
7400.8	E2	V	-54.98	0.00	-20.49	11.70	6.54	-29.33	-13	16.33
9251.0			---					---		
9251.0			---					---		

CH661 (1880.0MHz)

Freq. (MHz)	*EUT Pol.	Ant. Pol.	P _{EUT} (dBm)	P _{TX} (dBm)	P _{RX} (dBm)	G _{antenna} (dBi)	L _{Cable} (dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)
3760.0	E2	H	-54.82	0.00	-10.74	12.73	3.85	-35.20	-13	22.20
3760.0	E2	V	-61.25	0.00	-10.89	12.73	3.85	-41.48	-13	28.48
5640.0	H	H	-50.80	0.00	-10.28	13.14	4.95	-32.33	-13	19.33
5640.0	H	V	-51.68	0.00	-10.45	13.14	4.95	-33.04	-13	20.04
7520.0	H	H	-64.19	0.00	-18.90	11.28	5.94	-39.95	-13	26.95
7520.0	H	V	-65.86	0.00	-18.82	11.28	5.94	-41.70	-13	28.70
9400.0	E2	H	-53.38	0.00	-21.66	11.59	6.75	-26.88	-13	13.88
9400.0	E2	V	-58.06	0.00	-21.53	11.59	6.75	-31.69	-13	18.69

CH810 (1909.8MHz)

Freq. (MHz)	*EUT Pol.	Ant. Pol.	P _{EUT} (dBm)	P _{TX} (dBm)	P _{RX} (dBm)	G _{antenna} (dBi)	L _{Cable} (dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)
3819.6	H	H	-58.39	0.00	-10.55	12.73	3.93	-39.04	-13	26.04
3819.6	E1	V	-58.03	0.00	-10.71	12.73	3.93	-38.52	-13	25.52
5729.4	H	H	-48.26	0.00	-10.46	13.11	5.10	-29.79	-13	16.79
5729.4	H	V	-54.94	0.00	-11.14	13.11	5.10	-35.79	-13	22.79
7639.2	E2	H	-63.69	0.00	-19.10	11.46	5.97	-39.10	-13	26.10
7639.2			---					---		
9549.0	E2	H	-56.89	0.00	-21.27	11.85	6.62	-30.39	-13	17.39
9549.0	E2	V	-61.93	0.00	-20.99	11.85	6.62	-35.71	-13	22.71

Note: 1. All modes of operation were investigated and the worst -case emission are reported.

2. “---“ means that the emission level is too low to be measured

- End of page -

9.7 Frequency Stability / Temperature Variation (GSM850)

Test Mode : Set to Middle channel (836.6MHz)


Deviation Limit : $\pm 2.5\text{ppm}$

Measurement Result :


Voltage (%)	Power (Vdc)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	PPM
100%	3.7	+23(Ref.)	836,599,981	-19	-0.023
100%		-30	836,599,988	-12	-0.014
100%		-20	836,599,989	-11	-0.013
100%		-10	836,599,991	-9	-0.011
100%		0	836,599,989	-11	-0.013
100%		10	836,599,995	-5	-0.006
100%		20	836,599,989	-11	-0.013
100%		30	836,599,982	-18	-0.022
100%		40	836,599,985	-15	-0.018
100%		50	836,599,979	-21	-0.025
100%		60	836,599,983	-17	-0.020
85%	3.145	23	836,599,991	-9	-0.011
115%	4.255	23	836,599,972	-28	-0.033
Battery End point	3.07	23	836599967	-33	-0.039

*The temperature is varied from -30°C to +60°C using an environmental chamber.

9.7.1 Frequency Stability Graph (GSM850)



Zoom In



9.8 Frequency Stability / Temperature Variation (PCS1900)

Test Mode : Set to Middle channel (1880.0MHz)


Deviation Limit : $\pm 2.5\text{ppm}$

Measurement Result :


Voltage (%)	Power (Vdc)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	PPM
100%	3.7	+23(Ref.)	1,879,999,989	-11	-0.006
100%		-30	1,879,999,990	-10	-0.005
100%		-20	1,879,999,986	-14	-0.007
100%		-10	1,879,999,985	-15	-0.008
100%		0	1,880,000,005	5	0.003
100%		10	1,879,999,984	-16	-0.009
100%		20	1,879,999,987	-13	-0.007
100%		30	1,879,999,993	-7	-0.004
100%		40	1,879,999,991	-9	-0.005
100%		50	1,879,999,985	-15	-0.008
100%		60	1,879,999,983	-17	-0.009
85%	3.145	23	1,879,999,983	-17	-0.009
115%	4.255	23	1,879,999,977	-23	-0.012
Battery End point	3.07	23	1879999971	-29	-0.015

*The temperature is varied from -30°C to +60°C using an environmental chamber.

9.8.1 Frequency Stability Graph (PCS1900)



Zoom In



9.9 AC Power LINE Conducted Emission

Measurement Result :

► Idle mode

Frequency (MHz)	Level(dB μ V)		Line	Limit(dB μ V)		Margin(dB)	
	Q-Peak	Average		Q-Peak	Average	Q-Peak	Average
0.26	47.8	38.9	N	61.4	51.4	13.6	12.5
0.51	49.4	38.2	N	56.0	46.0	6.6	7.8
0.64	48.5	36.9	N	56.0	46.0	7.5	9.1
0.77	44.8	30.6	N	56.0	46.0	11.2	15.4
0.89	48.4	34.8	N	56.0	46.0	7.6	11.2
1.02	48.4	34.2	N	56.0	46.0	7.6	11.8

Table 1. Line Conducted Emissions Tabulated Data

► GSM 850MHz TCH mode

Frequency (MHz)	Level(dB μ V)		Line	Limit(dB μ V)		Margin(dB)	
	Q-Peak	Average		Q-Peak	Average	Q-Peak	Average
0.25	47.9	39.5	N	61.8	51.8	13.9	12.3
0.38	41.3	31.3	N	58.3	48.3	17.0	17.0
0.51	49.4	38.1	N	56.0	46.0	6.6	7.9
0.63	48.3	36.4	N	56.0	46.0	7.7	9.6
0.89	48.0	35.0	N	56.0	46.0	8.0	11.0
2.67	45.0	31.5	N	56.0	46.0	11.0	14.5

Table 2. Line Conducted Emissions Tabulated Data

► PCS TCH mode


Frequency (MHz)	Level(dB μ V)		Line	Limit(dB μ V)		Margin(dB)	
	Q-Peak	Average		Q-Peak	Average	Q-Peak	Average
0.25	47.7	38.9	N	61.8	51.8	14.1	12.9
0.38	42.1	32.0	N	58.3	48.3	16.2	16.3
0.51	48.9	38.5	N	56.0	46.0	7.1	7.5
0.63	47.8	36.7	N	56.0	46.0	8.2	9.3
0.89	47.8	34.7	N	56.0	46.0	8.2	11.3
2.67	44.7	32.0	N	56.0	46.0	11.3	14.0

Table 3. Line Conducted Emissions Tabulated Data


NOTES:

1. Measurements using CISPR quasi-peak mode & average mode.
2. All modes of operation were investigated and the worst -case emission are reported. See attached Plots.
3. LINE : L =Line , N = Neutral
4. The limit is on the FCC Part section 15.207(a).


Conducted Disturbance at the mains ports Spectrum (Idle Mode, Line)




Conducted Disturbance at the mains ports Spectrum (Idle Mode, Neutral)




Conducted Disturbance at the mains ports Spectrum (GSM850 Mode, Line)




Conducted Disturbance at the mains ports Spectrum (GSM850 Mode, Neutral)



Conducted Disturbance at the mains ports Spectrum (PCS1900 Mode, Line)



Conducted Disturbance at the mains ports Spectrum (PCS1900 Mode, Neutral)



10. Emission Designator

Emission Designator

Emission Designator = 250KGXW

GSM Bandwidth = 250KHz

G = Phase Modulation

X = Cases not otherwise covered


W = Combination (Audio/Data)

- End of page -


11. Test Plots (GSM850)

● Occupied Bandwidth / 26dB Bandwidth


Channel 128



Channel 190





Channel 251





- End of page -

● Spurious Emission at antenna Terminals



Channel 128



Channel 190




Channel 251




● **Band Edge**

Channel 128




Channel 251




12. Test Plots (PCS1900)

● Occupied Bandwidth / 26dB Bandwidth


Channel 512



Channel 661





Channel 810





- End of page -

● Spurious Emission at antenna Terminals



Channel 512



Channel 661




Channel 810



● **Band Edge**

Channel 512



Channel 810

