

TEST REPORT

Applicant Name : Feit Electric Company
Address : 4901 Gregg Road, Pico Rivera, California, United States 90660
Report Number : SZNS220106-00692E-RF-00
FCC ID: SYW-GLASSBREAKWF

Test Standard (s)

FCC PART 15.247

Sample Description

Product Type: Smart Glass Break Sensor
Model No.: GLASSBREAK/WIFI
Multiple Model(s) No.: N/A
Trade Mark: FEIT
Date Received: 2022/01/06
Date of Test: 2022/01/17~2022/01/24
Report Date: 2022/01/28

Test Result:	Pass*
--------------	-------

* In the configuration tested, the EUT complied with the standards above.

Prepared and Checked By:



Fan Yang
EMC Engineer

Approved By:



Robert Li
EMC Engineer

Note: This report may contain data that are not covered by the A2LA accreditation and are marked with an asterisk "★".

Shenzhen Accurate Technology Co., Ltd. is not responsible for the authenticity of any test data provided by the applicant. Data included from the applicant that may affect test results are marked with an asterisk "★". Customer model name, addresses, names, trademarks etc. are not considered data.

This report cannot be reproduced except in full, without prior written approval of the Company. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

Shenzhen Accurate Technology Co., Ltd.

1/F., Building A, Changyuan New Material Port, Science & Industry Park, Nanshan District, Shenzhen, Guangdong, P.R. China
Tel: +86 755-26503290 Fax: +86 755-26503396 Web: www.atc-lab.com

TABLE OF CONTENTS

GENERAL INFORMATION.....	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	4
OBJECTIVE	4
TEST METHODOLOGY	4
MEASUREMENT UNCERTAINTY	5
SYSTEM TEST CONFIGURATION.....	6
DESCRIPTION OF TEST CONFIGURATION	6
EQUIPMENT MODIFICATIONS	6
EUT EXERCISE SOFTWARE	6
DUTY CYCLE	6
SUPPORT EQUIPMENT LIST AND DETAILS	6
EXTERNAL I/O CABLE.....	7
BLOCK DIAGRAM OF TEST SETUP	7
SUMMARY OF TEST RESULTS	8
TEST EQUIPMENT LIST	9
FCC §15.247 (I) & §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE).....	10
FCC §15.203 - ANTENNA REQUIREMENT.....	11
APPLICABLE STANDARD	11
ANTENNA CONNECTOR CONSTRUCTION	11
FCC §15.209, §15.205 & §15.247(D) - SPURIOUS EMISSIONS.....	12
APPLICABLE STANDARD	12
EUT SETUP	12
EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP	13
TEST PROCEDURE	13
FACTOR & MARGIN CALCULATION	13
TEST DATA	13
FCC §15.247(A) (2) – 6 DB EMISSION BANDWIDTH & OCCUPIED BANDWIDTH	21
APPLICABLE STANDARD	21
TEST PROCEDURE	21
TEST DATA	21
FCC §15.247(B) (3) - MAXIMUM CONDUCTED OUTPUT POWER	22
APPLICABLE STANDARD	22
TEST PROCEDURE	22
TEST DATA	22
FCC §15.247(D) – 100 KHZ BANDWIDTH OF FREQUENCY BAND EDGE	23
APPLICABLE STANDARD	23
TEST PROCEDURE	23
TEST DATA	23
FCC §15.247(E) - POWER SPECTRAL DENSITY.....	24
APPLICABLE STANDARD	24
TEST PROCEDURE	24
TEST DATA	24

APPENDIX	25
APPENDIX A: DTS BANDWIDTH	25
APPENDIX B: OCCUPIED CHANNEL BANDWIDTH	29
APPENDIX C: MAXIMUM CONDUCTED OUTPUT POWER	33
APPENDIX D: MAXIMUM POWER SPECTRAL DENSITY	34
APPENDIX E: BAND EDGE MEASUREMENTS	38
APPENDIX F: DUTY CYCLE	40

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

Frequency Range	Wi-Fi: 2412-2462MHz
Maximum Conducted Peak Output Power	Wi-Fi: 802.11b: 18.43dBm, 802.11g: 21.90dBm, 802.11n-HT20: 21.94dBm
Modulation Technique	Wi-Fi: DSSS, OFDM
Antenna Specification*	Internal Antenna: 3.0dBi(provided by the applicant)
Voltage Range	DC 3.0V from battery
Sample serial number	SZNS220106-00692E-RF-S1 (Assigned by ATC)
Sample/EUT Status	Good condition

Objective

This test report is in accordance with Part 2-Subpart J, Part 15-Subparts A and C of the Federal Communication Commission's rules.

The tests were performed in order to determine compliance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.209 and 15.247 rules.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

And KDB 558074 D01 15.247 Meas Guidance v05r02.

All emissions measurement was performed at Shenzhen Accurate Technology Co., Ltd. The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Measurement Uncertainty

Parameter		Uncertainty
Occupied Channel Bandwidth		5%
RF Frequency		0.082×10^{-7}
RF output power, conducted		0.73dB
Unwanted Emission, conducted		1.6dB
AC Power Lines Conducted Emissions		2.72dB
Emissions, Radiated	9kHz - 30MHz	2.66dB
	30MHz - 1GHz	4.28dB
	1GHz - 18GHz	4.98dB
	18GHz - 26.5GHz	5.06dB
	26.5GHz - 40GHz	4.72dB
Temperature		1 °C
Humidity		6%
Supply voltages		0.4%

Note: The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval. Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.

Test Facility

The test site used by Shenzhen Accurate Technology Co., Ltd. to collect test data is located on the 1/F., Building A, Changyuan New Material Port, Science & Industry Park, Nanshan District, Shenzhen, Guangdong, P.R. China.

The test site has been approved by the FCC under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No.: 708358, the FCC Designation No.: CN1189. Accredited by American Association for Laboratory Accreditation (A2LA) The Certificate Number is 429 7.01.

Listed by Innovation, Science and Economic Development Canada (ISED), the Registration Number is 5077A.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

For 802.11b, 802.11g and 802.11n-HT20 mode, total 11 channels are provided to testing:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	7	2442
2	2417	8	2447
3	2422	9	2452
4	2427	10	2457
5	2432	11	2462
6	2437	/	/

802.11b, 802.11g and 802.11n-HT20 mode was tested with Channel 1, 6 and 11.

Equipment Modifications

No modification was made to the EUT tested.

EUT Exercise Software

“esp rf test tool.exe” software was used to test and power level as below:

Mode	Data rate	Power Level*		
		Low Channel	Middle Channel	High Channel
802.11b	1Mbps	32	32	32
802.11g	6Mbps	0	0	0
802.11n-HT20	MCS0	4	4	4

The software and power level was provided by the applicant.

Duty cycle

Test Result: Compliant. Please refer to the Appendix Wi-Fi.


Support Equipment List and Details

Manufacturer	Description	Model	Serial Number
/	/	/	/

External I/O Cable

Cable Description	Length (m)	From Port	To
/	/	/	/

Block Diagram of Test Setup



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§15.247 (i), §2.1091	MAXIMUM PERMISSIBLE EXPOSURE (MPE)	Compliant
§15.203	Antenna Requirement	Compliant
§15.207 (a)	AC Line Conducted Emissions	Not Applicable
§15.205, §15.209, §15.247(d)	Spurious Emissions	Compliant
§15.247 (a)(2)	6 dB Emission Bandwidth & Occupied Bandwidth	Compliant
§15.247(b)(3)	Maximum Conducted Output Power	Compliant
§15.247(d)	100 kHz Bandwidth of Frequency Band Edge	Compliant
§15.247(e)	Power Spectral Density	Compliant

Not Applicable: The EUT is only powered by battery.

TEST EQUIPMENT LIST

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Radiated Emissions Test					
Rohde& Schwarz	Test Receiver	ESR	102725	2021/12/13	2022/12/12
Rohde&Schwarz	Spectrum Analyzer	FSV40	101949	2021/12/13	2022/12/12
SONOMA INSTRUMENT	Amplifier	310 N	186131	2021/11/09	2022/11/08
A.H. Systems, inc.	Preamplifier	PAM-0118P	135	2021/11/09	2022/11/08
Quinstar	Amplifier	QLW-18405536-J0	15964001002	2021/11/11	2022/11/10
Schwarzbeck	Bilog Antenna	VULB9163	9163-323	2021/07/06	2024/07/05
Schwarzbeck	Horn Antenna	BBHA9120D	9120D-1067	2020/01/05	2023/01/04
Schwarzbeck	HORN ANTENNA	BBHA9170	9170-359	2020/01/05	2023/01/04
Radiated Emission Test Software: e3 19821b (V9)					
Unknown	RF Coaxial Cable	No.10	N050	2021/12/14	2022/12/13
Unknown	RF Coaxial Cable	No.11	N1000	2021/12/14	2022/12/13
Unknown	RF Coaxial Cable	No.12	N040	2021/12/14	2022/12/13
Unknown	RF Coaxial Cable	No.13	N300	2021/12/14	2022/12/13
Unknown	RF Coaxial Cable	No.14	N800	2021/12/14	2022/12/13
Unknown	RF Coaxial Cable	No.15	N600	2021/12/14	2022/12/13
Unknown	RF Coaxial Cable	No.16	N650	2021/12/14	2022/12/13
Wainwright	High Pass Filter	WHKX3.6/18 G-10SS	5	2021/12/14	2022/12/13
RF Conducted Test					
Rohde & Schwarz	Spectrum Analyzer	FSV-40	101495	2021/12/13	2022/12/12
Tonscend	RF Control Unit	JS0806-2	19G8060182	2021/07/06	2022/07/05
Unknown	RF Cable	Unknown	Unknown	Each time	/

* **Statement of Traceability:** Shenzhen Accurate Technology Co., Ltd. attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

FCC §15.247 (i) & §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Applicable Standard

According to subpart 15.247 (i) and subpart 2.1091 systems operating under the provisions of this section shall be operated in a manner that ensures the public is not exposed to RF energy level in excess of the communication guidelines.

Limits for General Population/Uncontrolled Exposure

Limits for General Population/Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Averaging Time (Minutes)
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30

f = frequency in MHz

* = Plane-wave equivalent power density

a)

Result

Calculated Formulary:

Predication of MPE limit at a given distance

$$S = \frac{PG}{4\pi R^2}$$

S = power density (in appropriate units, e.g. mW/cm²)

P = power input to the antenna (in appropriate units, e.g., mW).

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain.

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

Frequency (MHz)	Antenna Gain		Tune up conducted power		Evaluation Distance (cm)	Power Density (mW/cm ²)	MPE Limit (mW/cm ²)
	(dBi)	(numeric)	(dBm)	(mW)			
2412-2462	3.0	2.00	22.0	158.49	20	0.063	1

To maintain compliance with the FCC's RF exposure guidelines, place the equipment at least 20cm from nearby persons.

Result: Compliant

FCC §15.203 - ANTENNA REQUIREMENT

Applicable Standard

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- b. Antenna must be permanently attached to the unit.
 - c. Antenna must use a unique type of connector to attach to the EUT.
- Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

And according to FCC 47 CFR section 15.247 (b), if the transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Antenna Connector Construction

The EUT has one internal antenna arrangement, which was permanently attached and the antenna gain is 3.0dBi, fulfill the requirement of this section. Please refer to the EUT photos.

Result: Compliance.


FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS

Applicable Standard


FCC §15.247 (d); §15.209; §15.205;

EUT Setup

Below 1 GHz:



Above 1GHz:



The radiated emission tests were performed in the 3 meters test site, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209, and FCC 15.247 limits.

EMI Test Receiver & Spectrum Analyzer Setup

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Measurement
30 MHz – 1000 MHz	100 kHz	300 kHz	120 kHz	QP
Above 1 GHz	1MHz	3 MHz	/	PK
	1MHz	10 Hz ^{Note 1}	/	Average
	1MHz	> 1/T ^{Note 2}	/	Average

Note 1: when duty cycle is no less than 98%

Note 2: when duty cycle is less than 98%

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz-1 GHz, peak and Average detection modes for frequencies above 1 GHz.

Factor & Margin Calculation

The Factor is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain. The basic equation is as follows:

$$\text{Factor} = \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Over Limit or Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a over limit/margin of -7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\begin{aligned} \text{Margin/Over Limit} &= \text{Corrected Amplitude/Level-Limit} \\ \text{Corrected Amplitude/Level} &= \text{Reading} + \text{Factor} \end{aligned}$$

Test Data

Environmental Conditions

Temperature:	23~25.1 °C
Relative Humidity:	44~61 %
ATM Pressure:	101.0 kPa


The testing was performed by Chao Mo on 2022-01-24 for below 1GHz, Chao Mo and Caro Hu on 2022-01-17 and 2022-01-24 for above 1GHz.

EUT operation mode: Transmitting (Pre-scan in the X,Y and Z axes of orientation, the worst case of X orientation was recorded)

30MHz-1GHz: (Worst case is 802.11G mode, low Channel)

Note: When the test result of peak was less than the limit of QP more than 6dB, just peak value were recorded


Horizontal



Site : chamber
Condition: 3m HORIZONTAL
Job No. : SZNS220106-00692E-RF
Test Mode: Transmitting

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	57.695	-9.94	27.26	17.32	40.00	-22.68	Peak
2	101.067	-11.67	28.54	16.87	43.50	-26.63	Peak
3	191.493	-11.34	28.92	17.58	43.50	-25.92	Peak
4	298.661	-9.24	29.78	20.54	46.00	-25.46	Peak
5	399.030	-6.75	29.69	22.94	46.00	-23.06	Peak
6	724.896	-1.28	32.00	30.72	46.00	-15.28	Peak

Vertical



Site : chamber
 Condition: 3m VERTICAL
 Job No. : SZNS220106-00692E-RF
 Test Mode: Transmitting

	Freq	Factor	Read Level	Level	Limit	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	46.605	-10.00	30.21	20.21	40.00	-19.79	Peak
2	100.625	-11.73	30.63	18.90	43.50	-24.60	Peak
3	190.906	-11.43	30.83	19.40	43.50	-24.10	Peak
4	328.175	-8.09	31.73	23.64	46.00	-22.36	Peak
5	415.450	-6.22	32.27	26.05	46.00	-19.95	Peak
6	715.740	-1.32	32.58	31.26	46.00	-14.74	Peak

1-25 GHz:

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB/m)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	PK/QP/AV		Height (m)	Polar (H/V)				
802.11B, Low Channel									
2310	67.65	PK	205	1.8	H	-7.24	60.41	74	-13.59
2310	53.33	AV	205	1.8	H	-7.24	46.09	54	-7.91
2390	67.91	PK	75	1.4	H	-7.22	60.69	74	-13.31
2390	54.56	AV	75	1.4	H	-7.22	47.34	54	-6.66
2310	67.56	PK	263	1.5	V	-7.24	60.32	74	-13.68
2310	53.35	AV	263	1.5	V	-7.24	46.11	54	-7.89
2390	68.21	PK	42	1.5	V	-7.22	60.99	74	-13.01
2390	54.39	AV	42	1.5	V	-7.22	47.17	54	-6.83
4824	58.91	PK	96	2.1	H	-3.52	55.39	74	-18.61
4824	53.99	AV	96	2.1	H	-3.52	50.47	54	-3.53
4824	56.91	PK	153	1.6	V	-3.52	53.39	74	-20.61
4824	49.81	AV	153	1.6	V	-3.52	46.29	54	-7.71
802.11B, Middle Channel									
4874	57.87	PK	78	1.2	H	-3.42	54.45	74	-19.55
4874	52.49	AV	78	1.2	H	-3.42	49.07	54	-4.93
4874	57.25	PK	269	1.8	V	-3.42	53.83	74	-20.17
4874	51.4	AV	269	1.8	V	-3.42	47.98	54	-6.02
11B, High Channel									
2483.5	69.56	PK	71	1.4	H	-7.2	62.36	74	-11.64
2483.5	55.31	AV	71	1.4	H	-7.2	48.11	54	-5.89
2500	68.62	PK	2	1	H	-7.18	61.44	74	-12.56
2500	55.27	AV	2	1	H	-7.18	48.09	54	-5.91
2483.5	68.83	PK	49	1.8	V	-7.2	61.63	74	-12.37
2483.5	55.22	AV	49	1.8	V	-7.2	48.02	54	-5.98
2500	69.8	PK	77	1.8	V	-7.18	62.62	74	-11.38
2500	54.83	AV	77	1.8	V	-7.18	47.65	54	-6.35
4924	57.46	PK	171	1.6	H	-3.16	54.3	74	-19.7
4924	51.87	AV	171	1.6	H	-3.16	48.71	54	-5.29
4924	55.7	PK	343	1.6	V	-3.16	52.54	74	-21.46
4924	49.55	AV	343	1.6	V	-3.16	46.39	54	-7.61

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB/m)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	PK/QP/AV		Height (m)	Polar (H/V)				
802.11G, Low Channel									
2310	67.37	PK	141	1.1	H	-7.24	60.13	74	-13.87
2310	54.38	AV	141	1.1	H	-7.24	47.14	54	-6.86
2390	68.39	PK	177	1.8	H	-7.22	61.17	74	-12.83
2390	55.41	AV	177	1.8	H	-7.22	48.19	54	-5.81
2310	67.42	PK	262	1.3	V	-7.24	60.18	74	-13.82
2310	54.44	AV	262	1.3	V	-7.24	47.2	54	-6.8
2390	68.1	PK	265	1.2	V	-7.22	60.88	74	-13.12
2390	55.42	AV	265	1.2	V	-7.22	48.2	54	-5.8
4824	64.63	PK	118	2	H	-3.52	61.11	74	-12.89
4824	51.93	AV	118	2	H	-3.52	48.41	54	-5.59
4824	62.94	PK	291	1.7	V	-3.52	59.42	74	-14.58
4824	49.81	AV	291	1.7	V	-3.52	46.29	54	-7.71
802.11G, Middle Channel									
4874	62.91	PK	116	1.8	H	-3.42	59.49	74	-14.51
4874	48.89	AV	116	1.8	H	-3.42	45.47	54	-8.53
4874	60.46	PK	170	2.5	V	-3.42	57.04	74	-16.96
4874	47.42	AV	170	2.5	V	-3.42	44	54	-10
802.11G, High Channel									
2483.5	72.05	PK	149	1.9	H	-7.2	64.85	74	-9.15
2483.5	57.16	AV	149	1.9	H	-7.2	49.96	54	-4.04
2500	69.08	PK	243	2	H	-7.18	61.9	74	-12.1
2500	55.59	AV	243	2	H	-7.18	48.41	54	-5.59
2483.5	70.15	PK	207	2.2	V	-7.2	62.95	74	-11.05
2483.5	56.43	AV	207	2.2	V	-7.2	49.23	54	-4.77
2500	68.67	PK	127	2.4	V	-7.18	61.49	74	-12.51
2500	55.5	AV	127	2.4	V	-7.18	48.32	54	-5.68
4924	60.29	PK	139	1.1	H	-3.16	57.13	74	-16.87
4924	47.49	AV	139	1.1	H	-3.16	44.33	54	-9.67
4924	57.93	PK	112	1.1	V	-3.16	54.77	74	-19.23
4924	46.17	AV	112	1.1	V	-3.16	43.01	54	-10.99

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB/m)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	PK/QP/AV		Height (m)	Polar (H/V)				
802.11N20, Low Channel									
2310	66.9	PK	52	2.3	H	-7.24	59.66	74	-14.34
2310	54.41	AV	52	2.3	H	-7.24	47.17	54	-6.83
2390	70.09	PK	149	1	H	-7.22	62.87	74	-11.13
2390	55.76	AV	149	1	H	-7.22	48.54	54	-5.46
2310	67.29	PK	30	1.7	V	-7.24	60.05	74	-13.95
2310	54.66	AV	30	1.7	V	-7.24	47.42	54	-6.58
2390	69.94	PK	116	2.3	V	-7.22	62.72	74	-11.28
2390	55.78	AV	116	2.3	V	-7.22	48.56	54	-5.44
4824	60.06	PK	82	2	H	-3.52	56.54	74	-17.46
4824	48.56	AV	82	2	H	-3.52	45.04	54	-8.96
4824	59.95	PK	229	1.9	V	-3.52	56.43	74	-17.57
4824	48.51	AV	229	1.9	V	-3.52	44.99	54	-9.01
802.11N20, Middle Channel									
4874	62.3	PK	135	1.6	H	-3.42	58.88	74	-15.12
4874	48.7	AV	135	1.6	H	-3.42	45.28	54	-8.72
4874	61.18	PK	217	2.4	V	-3.42	57.76	74	-16.24
4874	47.8	AV	217	2.4	V	-3.42	44.38	54	-9.62
802.11N20, High Channel									
2483.5	71.5	PK	21	1.2	H	-7.2	64.3	74	-9.7
2483.5	57.15	AV	21	1.2	H	-7.2	49.95	54	-4.05
2500	68.35	PK	204	1.6	H	-7.18	61.17	74	-12.83
2500	55.39	AV	204	1.6	H	-7.18	48.21	54	-5.79
2483.5	69.41	PK	26	2.2	V	-7.2	62.21	74	-11.79
2483.5	56.52	AV	26	2.2	V	-7.2	49.32	54	-4.68
2500	69.25	PK	236	2	V	-7.18	62.07	74	-11.93
2500	55.4	AV	236	2	V	-7.18	48.22	54	-5.78
4924	62.12	PK	170	1.8	H	-3.16	58.96	74	-15.04
4924	48.66	AV	170	1.8	H	-3.16	45.5	54	-8.5
4924	60.96	PK	235	2	V	-3.16	57.8	74	-16.2
4924	47.66	AV	235	2	V	-3.16	44.5	54	-9.5

Note:

Factor = Antenna factor (RX) + Cable Loss – Amplifier Factor

Absolute Level (Corrected Amplitude) = Factor + Reading

Margin = Absolute Level - Limit


The other spurious emission which is 20dB below to the limit was not recorded.

The test result of peak was less than the limit of average, so just peak values were recorded.


1-18 GHz:

Pre-scan Plots:

802.11 b Low Channel
Horizontal




Vertical




18 -25GHz:

Pre-scan Plots:

802.11 b Low Channel
Horizontal



Vertical




FCC §15.247(a) (2) – 6 dB EMISSION BANDWIDTH & OCCUPIED BANDWIDTH

Applicable Standard

Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 6 dB from the reference level. Record the frequency difference as the emission bandwidth.
4. Repeat above procedures until all frequencies measured were complete.



Test Data

Environmental Conditions

Temperature:	27 °C
Relative Humidity:	57 %
ATM Pressure:	101.0 kPa

The testing was performed by Paul Liu on 2022-01-19.

EUT operation mode: Transmitting

Test Result: Compliant. Please refer to the Appendix.


FCC §15.247(b) (3) - MAXIMUM CONDUCTED OUTPUT POWER

Applicable Standard

According to FCC §15.247(b) (3), for systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

Test Procedure

- d. Place the EUT on a bench and set it in transmitting mode.
- e. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to one test equipment.
- f. Add a correction factor to the display.



Note: the RF control unit has a built-in power sensor.

Test Data

Environmental Conditions

Temperature:	27 °C
Relative Humidity:	57 %
ATM Pressure:	101.0 kPa

The testing was performed by Paul Liu on 2022-01-19.

EUT operation mode: Transmitting

Test Result: Compliant. Please refer to the Appendix.


FCC §15.247(d) – 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE

Applicable Standard

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test Procedure

- g. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- h. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
- i. Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
- j. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
- k. Repeat above procedures until all measured frequencies were complete.



Test Data

Environmental Conditions

Temperature:	27 °C
Relative Humidity:	57 %
ATM Pressure:	101.0 kPa

The testing was performed by Paul Liu on 2022-01-19.

EUT operation mode: Transmitting

Test Result: Compliant.

Conducted Band Edge Result:

Please refer to the Appendix.


FCC §15.247(e) - POWER SPECTRAL DENSITY

Applicable Standard

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

Test Procedure

- l. Use this procedure when the maximum peak conducted output power in the fundamental emission is used to demonstrate compliance.
- m. Set the RBW to: $3\text{kHz} \leq \text{RBW} \leq 100\text{ kHz}$.
- n. Set the VBW $\geq 3 \times \text{RBW}$.
- o. Set the span to 1.5 times the DTS bandwidth.
- p. Detector = peak.
- q. Sweep time = auto couple.
- r. Trace mode = max hold.
- s. Allow trace to fully stabilize.
- t. Use the peak marker function to determine the maximum amplitude level within the RBW.
- u. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.



Test Data

Environmental Conditions

Temperature:	27 °C
Relative Humidity:	57 %
ATM Pressure:	101.0 kPa

The testing was performed by Paul Liu on 2022-01-19.

EUT operation mode: Transmitting


Test Result: Compliant. Please refer to the Appendix.

APPENDIX


Appendix A: DTS Bandwidth Test Result

Test Mode	Antenna	Channel	DTS BW [MHz]	Limit[MHz]	Verdict
11B	Ant1	2412	7.640	0.5	PASS
		2437	7.160	0.5	PASS
		2462	9.120	0.5	PASS
11G	Ant1	2412	15.200	0.5	PASS
		2437	15.240	0.5	PASS
		2462	15.240	0.5	PASS
11N20SISO	Ant1	2412	15.240	0.5	PASS
		2437	15.240	0.5	PASS
		2462	15.240	0.5	PASS

Test Graphs




11G Ant1_2412




Date: 19.JAN.2022 14:08:36

11G Ant1_2437




Date: 19.JAN.2022 14:10:06

11G Ant1_2462




Date: 19.JAN.2022 14:11:06

11N20SISO_Ant1_2412




Date: 19.JAN.2022 14:14:47

11N20SISO_Ant1_2437



Date: 19.JAN.2022 14:16:03

11N20SISO_Ant1_2462




Date: 19.JAN.2022 14:17:01


**Appendix B: Occupied Channel Bandwidth
Test Result**

Test Mode	Antenna	Channel	OCB [MHz]	Limit[MHz]	Verdict
11B	Ant1	2412	11.109	---	PASS
		2437	11.149	---	PASS
		2462	11.149	---	PASS
11G	Ant1	2412	24.935	---	PASS
		2437	22.418	---	PASS
		2462	18.541	---	PASS
11N20SISO	Ant1	2412	21.499	---	PASS
		2437	20.100	---	PASS
		2462	18.062	---	PASS

Test Graphs




11G Ant1_2412



Date: 19.JAN.2022 14:08:46

11G Ant1_2437




Date: 19.JAN.2022 14:10:16

11G Ant1_2462




Date: 19.JAN.2022 14:11:16

11N20SISO_Ant1_2412



Date: 19.JAN.2022 14:14:57

11N20SISO_Ant1_2437



Date: 19.JAN.2022 14:16:13

11N20SISO_Ant1_2462



Date: 19.JAN.2022 14:17:11


**Appendix C: Maximum conducted output power
Test Result**

Test Mode	Antenna	Channel	Result[dBm]	Limit[dBm]	Verdict
11B	Ant1	2412	18.43	≤30	PASS
		2437	17.40	≤30	PASS
		2462	15.72	≤30	PASS
11G	Ant1	2412	21.90	≤30	PASS
		2437	21.86	≤30	PASS
		2462	21.78	≤30	PASS
11N20SISO	Ant1	2412	21.87	≤30	PASS
		2437	21.94	≤30	PASS
		2462	21.59	≤30	PASS


**Appendix D: Maximum power spectral density
Test Result**

Test Mode	Antenna	Channel	Result[dBm/3kHz]	Limit[dBm/3kHz]	Verdict
11B	Ant1	2412	-7.5	≤8	PASS
		2437	-8.79	≤8	PASS
		2462	-10.46	≤8	PASS
11G	Ant1	2412	-5.68	≤8	PASS
		2437	-6.34	≤8	PASS
		2462	-7.12	≤8	PASS
11N20SISO	Ant1	2412	-5.84	≤8	PASS
		2437	-6.72	≤8	PASS
		2462	-7.78	≤8	PASS

Test Graphs




11G_Ant1_2412




Date: 19.JAN.2022 14:09:05

11G_Ant1_2437




Date: 19.JAN.2022 14:10:35

11G_Ant1_2462




Date: 19.JAN.2022 14:11:35


11N20SISO_Ant1_2412




11N20SISO_Ant1_2437




11N20SISO_Ant1_2462



Appendix E: Band edge measurements Test Graphs




11G Ant1_High_2462




Date: 19.JAN.2022 14:11:44

11N20SISO Ant1_Low_2412



Date: 19.JAN.2022 14:14:22

11N20SISO Ant1_High_2462



Date: 19.JAN.2022 14:17:38

**Appendix F: Duty Cycle
Test Result**

Test Mode	Antenna	Channel	Transmission Duration [ms]	Transmission Period [ms]	Duty Cycle [%]
11B	Ant1	2437	4.18	4.70	88.94
11G	Ant1	2437	0.69	0.80	86.25
11N20SISO	Ant1	2437	0.65	0.76	85.53

Test Graphs



***** END OF REPORT *****