

**BEST VERIFICATION LLC**

1st FLR, 7# BLD, Erix Industrial Park, Huihuan, Huizhou, 516106 P.R.C
Tel: +86-18927465912; E-mail: service@bestcert.cn

FCC ID: SYW-NFCHASEREM

1. Limit for Portable Equipment Exposure

Frequency	1-g SAR
100MHz-6GHz	3

According to KDB 447498 D01 General RF Exposure Guidance v06 and part 2.1093
For 100 MHz to 6 GHz and test separation distances ≤ 50 mm, the 1-g and 10-g SAR test exclusion thresholds are determined by the following:
$$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0 \text{ for 1-g SAR, and } \leq 7.5 \text{ for 10-g extremity SAR, where } \sqrt{f(\text{GHz})} \text{ is the RF channel transmit frequency in GHz}$$

2. CALCULATION

Frequency (MHz)	Measured Field Strength (dBuV/m)	Output Power (mW)	Separation Distance (mm)	Result (mw/mm ²)	1-g SAR (mw/mm ²)
433.941	71.65	0.0044	5	0.0006	3
Result:	PASS				