

FCC PART 15.227
EMI MEASUREMENT AND TEST REPORT


For

Planet Toys (HK) Ltd

1107 Chinachem Golden Plaza, 77 Mody RD, TsimShaTsui East, Kowloon, Hong Kong

FCC ID: SZ23701T27

July 22, 2005

This Report Concerns: ☒ Original Report	Equipment Type: Transmitter, 1:5 scale RC
Test Engineer: Louise Lu 	
Report No.: RSZ05071401	
Test Date: July 15, 2005	
Reviewed By: Chris Zeng 	
Prepared By: Bay Area Compliance Lab Corp. (ShenZhen) 6/F, the 3rd Phase of WanLi Industrial Building, ShiHua Road, FuTian Free Trade Zone, ShenZhen, Guangdong 518038, P.R.China Tel: 86-755-33320018 Fax: 86-755-33320008	

Note: The test report is specially limited to the above company and this particular sample only.
It may not be duplicated without prior written consent of Bay Area Compliance Lab
Corp. (ShenZhen). This report **must not** be used by the client to claim product certification,
approval, or endorsement by NVLAP, NIST or any agency of the US Government.

TABLE OF CONTENTS

GENERAL INFORMATION.....	3
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	3
OBJECTIVE	3
RELATED SUBMITTAL(S)/GRANT(S).....	3
TEST METHODOLOGY	3
TEST FACILITY	3
SYSTEM TEST CONFIGURATION.....	4
JUSTIFICATION	4
EUT EXERCISE SOFTWARE	4
SPECIAL ACCESSORIES	4
EQUIPMENT MODIFICATIONS	4
CONFIGURATION OF TEST SETUP	5
BLOCK DIAGRAM OF TEST SETUP	5
SUMMARY OF TEST RESULTS.....	6
§15.203 - ANTENNA REQUIREMENT.....	7
STANDARD APPLICABLE	7
§15.205, §15.209, §15.227(A) - RADIATED EMISSIONS TEST	8
MEASUREMENT UNCERTAINTY	8
EUT SETUP.....	8
EMI TEST RECEIVER SETUP	8
TEST EQUIPMENT LIST AND DETAILS.....	8
TEST PROCEDURE	8
CORRECTED AMPLITUDE & MARGIN CALCULATION	9
TEST RESULTS SUMMARY	9
TEST DATA	10
PLOT(S) OF TEST DATA	10
§15.227(B) - OUT OF BAND EMISSION	13

GENERAL INFORMATION

Product Description for Equipment Under Test (EUT)

The Planet Toys (HK) Ltd 's product, model number: 3701 or the "EUT" as referred to in this report is a transmitter, the product name is 1:5 scale RC. The EUT is measured approximately 19.2cm L x 15.0cm W x 7.7cm H, rated input voltage: DC 9 V battery, with permanently Antenna 76 cm.

** The test data gathered are from production sample, serial number: 0507022, provided by the manufacturer.*

Objective

This Type approval report is prepared on behalf of *Planet Toys (HK) Ltd* in accordance with Part 2, Subpart J, and Part 15, Subparts A , B and C of the Federal Communication Commissions rules.

The objective is to determine compliance with FCC rules, sec 15.203, 15.205, 15.209 and sec 15.227.

Related Submittal(s)/Grant(s)

No Related Submittals.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.4-2003, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.

All radiated and conducted emissions measurement was performed at Bay Area Compliance Laboratory Corp. The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Test Facility

The Test site used by Bay Area Compliance Lab Corp. (ShenZhen) to collect test data is located in the 6/F, the 3rd Phase of WanLi Industrial Building, ShiHua Road, FuTian Free Trade Zone, ShenZhen, Guangdong 518038, P.R.China.

Test site at Bay Area Compliance Lab Corp. (ShenZhen) has been fully described in reports submitted to the Federal Communication Commission (FCC). The details of these reports have been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on November 04, 2004. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2003.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 382179. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

Additionally, Bay Area Compliance Lab Corp. (ShenZhen) is a National Institute of Standards and Technology (NIST) accredited laboratory, under the National Voluntary Laboratory Accredited Program (Lab Code 200707-0). The current scope of accreditations can be found at <http://ts.nist.gov/ts/htdocs/210/214/scopes/2007070.htm>.

SYSTEM TEST CONFIGURATION

Justification

The system was configured for testing in a typical fashion (as normally used by a typical user).

EUT Exercise Software

N/A.


Special Accessories

N/A.


Equipment Modifications

Bay Area Compliance Lab Corp. (ShenZhen) has not done any modification on the EUT.

Configuration of Test Setup



Stand View




Side View



Lie View

Note: We tested Lie orientation, side orientation and stand orientation, the stand orientation is the worst mode, so we select the stand orientation to test.

Block Diagram of Test Setup



SUMMARY OF TEST RESULTS

FCC RULES	DESCRIPTION OF TEST	RESULT
§15.203	Antenna requirement	Compliant
§15.205	Restricted Band of operation	Compliant
§15.209	Radiated Emission Test	Compliant
§15.227(a)	Field Strength	Compliant
§15.227(b)	Out of Band Emission	Compliant

Note: The highest clocks of the EUT was 27.145 MHz.

§15.203 - ANTENNA REQUIREMENT

Standard Applicable

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

This product has a permanent antenna, fulfill the requirement of this section.

Test Result: Pass

§15.205, §15.209, §15.227(a) - RADIATED EMISSIONS TEST

Measurement Uncertainty

All measurements involve certain levels of uncertainties, especially in field of EMC. The factors contributing to uncertainties are spectrum analyzer, cable loss, antenna factor calibration, antenna directivity, antenna factor variation with height, antenna phase center variation, antenna factor frequency interpolation, measurement distance variation, site imperfections, mismatch (average), and system repeatability.

Based on NIS 81, The Treatment of Uncertainty in EMC Measurements, the best estimate of the uncertainty of a radiation emissions measurement at Bay Area Compliance Lab Corp. (ShenZhen) is ± 4.0 dB.

The fundamental data was recorded in average detection mode: set the VBW AVE on, then record the data.

EUT Setup

The radiated emission tests were performed in the chamber B test site, using the setup accordance with the ANSI C63.4-2003. The specification used was the FCC Part 15 Subpart C section 15.227 limits.

EMI Test Receiver Setup

According to FCC Rules, 47 CFR 15.33, the EUT emissions were investigated from 27 to 1000 MHz.

During the radiated emission test, the EMI test receiver was set with the following configurations:

<i>Frequency</i>	<i>RB/W</i>	<i>VB/W</i>	<i>IF B/W</i>
9 kHz-30 MHz	10 kHz	10 kHz	9 kHz
30 MHz-1 GHz	100 kHz	100 kHz	120 kHz

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
HP	Amplifier	8447D	2994A09795	2004-9-1	2005-8-31
Rohde & Schwarz	EMI Test Receiver	ESCI	100028	2004-9-15	2005-9-15
Sunol Sciences	Broadband Antenna	JB1	A040904-1	2005-4-28	2006-4-28

*** Statement of Traceability:** Bay Area Compliance Lab Corp. (ShenZhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

All data was recorded in the Quasi-peak detection mode.

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Loss and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corr. Ampl.} = \text{Meter Reading} + \text{Antenna Loss} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -7dB means the emission is 7dB below the maximum limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Corr. Ampl.} - \text{Limit}$$

Test Results Summary

According to the data in the following table, the EUT complied with the FCC Part 15.227&15.209, with the worst margin reading of:

-1.4 dB at 129.556 MHz in the Vertical polarization.

Test Data**Environmental Conditions**

Temperature:	26 °C
Relative Humidity:	56 %
ATM Pressure:	1000mbar

The testing was performed by Louise Lu on 2005-7-15.

Test Mode: Transmitting

Meter					Antenna	Cable	Amplifier	Corr.	FCC Part 15.227&15.209		
Frequency	Reading	Direction	Height	Polar	Loss	loss	Gain	Ampl.			
MHz	dBuV/m	Degree	Meter	H / V	dB	dB	dB	dBuV/m	Limit dBuV/m	Margin dB	Remark
129.556	52.3	180	1.2	V	14.4	1.5	25.98	42.1	43.5	-1.4	Spurious (PK)
141.549	51.5	45	1.0	V	13.8	1.5	25.91	40.8	43.5	-2.7	Spurious (PK)
153.510	45.5	45	1.0	V	13.1	1.6	25.93	34.3	43.5	-9.2	Spurious (PK)
58.830	45.9	60	1.0	V	7.9	1.5	26.32	29.0	40.0	-11.0	Spurious (PK)
81.435	43.4	45	1.2	V	8.4	1.4	26.22	27.0	40.0	-13.0	Harmonic (PK)
141.540	39.4	0	1.0	H	13.8	1.5	25.91	28.7	43.5	-14.8	Spurious (PK)
129.556	37.8	180	1.2	H	14.4	1.5	25.98	27.7	43.5	-15.8	Spurious (PK)
58.830	39.1	35	3.8	H	7.9	1.5	26.32	22.1	40.0	-17.9	Spurious (PK)
153.520	36.9	0	1.0	H	13.1	1.6	25.93	25.6	43.5	-17.9	Spurious (PK)
70.749	38.2	45	1.2	H	8.6	1.3	26.29	21.9	40.0	-18.1	Spurious (PK)
81.435	36.8	90	1.2	H	8.4	1.4	26.22	20.4	40.0	-19.6	Harmonic (PK)
27.145	73.6	289	1.0	V	24.1	1.4	26.44	73.3	100.0	-26.7	Fundamental (PK)
27.145	52.2	289	1.0	V	24.1	1.4	26.44	51.2	80.0	-28.8	Fundamental (AV)
27.145	56.4	60	1.2	H	24.1	1.4	26.44	55.4	100.0	-44.6	Fundamental (PK)
27.145	34.0	35	3.8	H	24.1	1.4	26.44	34.2	80.0	-45.8	Fundamental (AV)

Plot(s) of Test Data

Plot(s) of Test Data is presented hereinafter as reference.



15.Jul 05 15:44

Ref 102 dBμV

* Att 10 dB


* RBW 100 kHz Marker 1 [T1]

* VBW 100 kHz

55.41 dBμV

* SWT 300 ms

27.113484112 MHz

1 PK
VIEW



15.Jul 05 15:25

Ref 92 dBμV

* Att 10 dB


* RBW 100 kHz Marker 1 [T1]

* VBW 100 kHz

73.34 dBμV

* SWT 300 ms

27.113484112 MHz


1 PK
MAXH

§15.227(b) - Out of Band Emission

The result has been complied with the 15.227(b), see the following plot:

Frequency MHz	Emission dB μ V/m	Limit dB μ V/m
26.96	30.83	40
27.28	37.78	40

Test Result: Pass






* RBW 10 kHz Marker 1 [T1]
* VBW 10 kHz 37.78 dBμV
* SWT 300 ms 27.280000000 MHz

Ref 102 dBμV

* Att 10 dB

1 PK
VIEW



Start 26.9 MHz

40 kHz/

Stop 27.3 MHz