
Appendix B. Highest Measurement Data

Test Laboratory: DEKRA

Date: 2026/05/06

1_SRD 2.4GHz_SRD_CH19_Front_5mm_ANT 1**DUT: Wireless Adapter; Type: CFI-ZWA3**

Communication System: UID 0, WLAN 2.4G; Frequency: 2440.3958 MHz

Communication System PAR: 0 dB

Medium parameters used: $f = 2440.3958$ MHz; $\sigma = 1.79$ S/m; $\epsilon_r = 39.07$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2011)

DASY Configuration:

- Probe: EX3DV4 - SN3698; ConvF(6.64, 6.51, 6.41) @ 2440.3958 MHz; Calibrated: 2025/11/27
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1207; Calibrated: 2025/11/13
- Phantom: ELI 5.0; Type: QDOVA002AA; Serial: 1199
- Measurement SW: DASYS2, Version 52.10 (4);

Configuration/Flat/Area Scan (6x10x1): Measurement grid: dx=12mm, dy=12mm

Maximum value of SAR (measured) = 0.104 W/kg

Configuration/Flat/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 7.876 V/m; Power Drift = 0.13 dB

Peak SAR (extrapolated) = 0.158 W/kg

SAR(1 g) = 0.073 W/kg; SAR(10 g) = 0.032 W/kg

Smallest distance from peaks to all points 3 dB below = 5.7 mm

Ratio of SAR at M2 to SAR at M1 = 47.7%

Maximum value of SAR (measured) = 0.129 W/kg

