Test Report

FCC Part15 Subpart C & ISED RSS-247 Issue 2

Product Name	:	Bluetooth Headset
Model No.	:	G015B
FCC ID	:	SZGG015B
IC	:	7702A-G015B

Applicant	:	Weifang Goertek Electronics Co., Ltd
Address	:	Gaoxin 2 Road,Free Trade Zone, Weifang, Shandong,261205,P.R.China

Date of Receipt	:	Aug. 18th, 2017
Test Date	:	Aug. 18th, 2017~ Sep. 18th, 2017
Issued Date	:	Sep. 21st, 2017
Report No.	:	1782091R-RF-US-P06V02
Report Version	:	V 2.0

The test results relate only to the samples tested.
The test results shown in the test report are traceable to the national/international standard through the calibration of the equipment and evaluated measurement uncertainty herein.
This report must not be used to claim product endorsement by TAF, A2LA or any agency of the government.
The test report shall not be reproduced without the written approval of DEKRA Testing & Certification (Suzhou) Co., Ltd.

Test Report Certification

Issued Date : Sep. 21st, 2017
Report No. : 1782091R-RF-US-P06V02

Product Name	:	Bluetooth Headset
Applicant	:	Weifang Goertek Electronics Co., Ltd
Address	:	Gaoxin 2 Road,Free Trade Zone,Weifang,Shandong,261205,P.R.China
Manufacturer	:	Weifang Goertek Electronics Co., Ltd
Address	:	Gaoxin 2 Road,Free Trade Zone,Weifang,Shandong,261205,P.R.China
Factory	:	Goertek Inc
Address	:	No.999 Liyuan Street, High-Tech Industrial Development District, Weifang, Shandong, 261031, P.R. China
Model No.	:	G015B
FCC ID	:	SZGG015B
IC	:	7702A-G015B
EUT Voltage	:	DC 3.3V
Test Voltage	:	AC 120V/60Hz
Applicable Standard	:	FCC CFR Title 47 Part 15 Subpart C: 2017 ANSI C63.4:2014; ANSI C63.10:2013; KDB 558074 D01v03r05 ISED RSS-Gen Issue 4 / RSS-247 Issue 2
Test Result	:	Complied
Performed Location	:	DEKRA Testing & Certification (Suzhou) Co., Ltd. No.99 Hongye Rd., Suzhou Industrial Park, Suzhou, 215006, Jiangsu, China TEL: +86-512-6251-5088 / FAX: +86-512-6251-5098 FCC Registration Number: CN1155; IC Lab Code: 4075B

Documented By : Kathy Feng

(Project Assistant: Kathy Feng)

Reviewed By : Frank he

(Senior Engineer: Frank He)

Approved By : Harry zhao

(Engineering Manager: Harry Zhao)

TABLE OF CONTENTS

Description		Page
1.	General Information	6
1.1.	EUT Description	6
1.2.	Working Frequency of Each Channel:	7
1.3.	Antenna information	7
1.4.	Mode of Operation	8
1.5.	Tested System Details	8
1.6.	Configuration of Tested System	9
1.7.	EUT Exercise Software	10
2.	Technical Test	11
2.1.	Summary of Test Result	11
2.2.	Test Frequency configuration:	13
2.3.	Test Environment	14
2.4.	Measurement Uncertainty	14
3.	AC Power Line Conducted Emission	15
3.1.	Test Equipment	15
3.2.	Test Setup	15
3.3.	Limit	16
3.4.	Test Procedure	16
3.5.	Test Result	17
4.	Emissions in restricted frequency bands	19
4.1.	Test Equipment	19
4.2.	Test Setup	20
4.3.	Limit	21
4.4.	Test Procedure	24
4.5.	EUT test Axis definition	25
4.6.	Test Result	26
5.	Emissions in non-restricted frequency bands	34
5.1.	Test Equipment	34
5.2.	Test Setup	34
5.3.	Limit	35
5.4.	Test Procedure	36
5.5.	EUT test Axis definition	37
5.6.	Test Result	38
6.	Radiated Emission Band Edge	39
6.1.	Test Equipment	39
6.2.	Test Setup	40
6.3.	Limit	40

6.4. Test Procedure 41
6.5. EUT test definition 42
6.6. Duty Cycle 43
6.7 Test Result 44
7. Occupied Bandwidth 56
7.1. Test Equipment 56
7.2. Test Setup 56
7.3. Limit 57
7.4. Test Procedure 57
7.5. EUT test definition 58
7.6. Test Result 59
8. Fundamental emission output power 60
8.1. Test Equipment 60
8.2. Test Setup 60
8.3. Limit 61
8.4. Test Procedure 62
8.5. EUT test definition 63
8.6. Test Result 64
9. Power Spectral Density 65
9.1. Test Equipment 65
9.2. Test Setup 65
9.3. Limit 65
9.4. Test Procedure 66
9.5. EUT test definition 67
9.6. Test Result 68

History of This Test Report

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
1782091R-RF-US-P06V02	V1.0	Initial Issued Report	Sep. 19th, 2017
1782091R-RF-US-P06V02	V2.0	Delete model G015C as accessory showed in the report	Sep. 21st, 2017

1. General Information

1.1. EUT Description

Product Name	Bluetooth Headset
Model No.	G015B
EUT Voltage	DC 3.3V
Test Voltage	AC 120V/60Hz
Bluetooth Specification	V4.0
Frequency Range	2402- 2480 MHz
Channel Number	V4.0: 40
Channel Separation	V4.0: 2MHz
Type of Modulation	V4.0: GFSK
Data Rate	V4.0: 1Mbps(GFSK)
Antenna Type	Reference to Antenna List
Peak Antenna Gain	Reference to Antenna List
Accessory	
Product Name	Charging Case
Model No.	G015C
Manufacturer	Weifang Goertek Electronics Co., Ltd

1.2. Working Frequency of Each Channel:

Bluetooth Working Frequency of Each Channel: (For V4.0)							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
00	2402 MHz	01	2404 MHz	02	2406 MHz	03	2408 MHz
04	2410 MHz	05	2412 MHz	06	2414 MHz	07	2416 MHz
08	2418 MHz	09	2420 MHz	10	2422 MHz	11	2424 MHz
12	2426 MHz	13	2428 MHz	14	2430 MHz	15	2432 MHz
16	2434 MHz	17	2436 MHz	18	2438 MHz	19	2440 MHz
20	2442 MHz	21	2444 MHz	22	2446 MHz	23	2448 MHz
24	2450 MHz	25	2452 MHz	26	2454 MHz	27	2456 MHz
28	2458 MHz	29	2460 MHz	30	2462 MHz	31	2464 MHz
32	2466 MHz	33	2468 MHz	34	2470 MHz	35	2472 MHz
36	2474 MHz	37	2476 MHz	38	2478 MHz	39	2480 MHz

1.3. Antenna information

Model No.	N/A			
Antenna manufacturer	N/A			
Antenna Delivery	☒	1*TX+1*RX	☐ 2*TX+2*RX	☐ 3*TX+3*RX
Antenna technology	☒	SISO		
	☐	MIMO	☐	Basic
			☐	CDD
			☐	Sectorized
			☐	Beam-forming
Antenna Type	☐	External	☐	Dipole
			☐	Sectorized
	☒	Internal	☐	PIFA
			☐	PCB
			☐	Ceramic Chip Antenna
			☒	Monopole Antenna

Antenna Technology	Ant Gain (dBi)
☒ SISO	-4.04

1.4. Mode of Operation

Test Mode
Mode 1: Transmit-1Mbps(GFSK_BLE)

1.5. Tested System Details

The types for all equipment, plus descriptions of all cables used in the tested system (including inserted cards) are:

No.	Product	Manufacturer	Model No.	Serial No.	Power Cord
1	Notebook	Think Pad	2526	LV-A3285	Power by adapter
A	USB cable	N/A	N/A	N/A	Shielded,0.5m
B	USB cable	N/A	N/A	N/A	Shielded,10m

1.6. Configuration of Tested System

Test setup Diagram- Radiated Emission


1.7. EUT Exercise Software

1	Setup the EUT and simulators as shown on above.
2	Turn on the power of all equipment.
3	Run the Bluetest3 software, and set the test mode and channel, then press OK to start continue receive.

2. Technical Test

2.1. Summary of Test Result

Performed Test Item	Normative References	Worst case mode	Limit	Result
AC Power Line Conducted Emission	FCC CFR Title 47 Part 15 Subpart C: 2015 Section 15.207	Mode 1	FCC 15.207	PASS
Emissions in restricted frequency bands	FCC CFR Title 47 Part 15 Subpart C: 2015 Section 15.209	Mode 1	FCC 15.209	PASS
Emissions in non-restricted frequency bands	FCC CFR Title 47 Part 15 Subpart C: 2015 Section 15.247(d)	Mode 1	≥20dBc	PASS
Radiated Emission Band Edge	FCC CFR Title 47 Part 15 Subpart C: 2015 15.247(d)	Mode 1	FCC 15.209	PASS
Occupied Bandwidth	FCC CFR Title 47 Part 15 Subpart C: 2015 Section 15.247(a)(2)	Mode 1	≥500kHz	PASS
Fundamental emission output power	FCC CFR Title 47 Part 15 Subpart C: 2015 Section 15.247(b)(3)	Mode 1	≤30dBm	PASS
Power Spectral Density	FCC CFR Title 47 Part 15 Subpart C: 2015 Section 15.247(e)	Mode 1	≤8dBm/3kHz	PASS
Antenna Requirement	FCC CFR Title 47 Part 15 Subpart C: 2015 Section 15.203	N/A	FCC 15.203	PASS

Performed Test Item	Normative References	Worst case mode	Limit	Result
AC Power Line Conducted Emission	RSS-Gen Issue 4 Section 8.8	N/A	RSS-Gen	PASS
Emissions in restricted frequency bands	RSS-Gen Issue 4 Section 8.9	Mode 1	RSS-Gen	PASS
Emissions in non-restricted frequency bands	RSS-247 Issue 2 Section A5.5	Mode 1	≥20dBc	PASS
Radiated Emission Band Edge	RSS-247 Issue 2 Section A5.5	Mode 1	RSS-247	PASS
Occupied Bandwidth	RSS-Gen Issue 4 Section 6.6 RSS-247 Issue 2 Section A5.2(1)	Mode 1	≥500kHz	PASS
Fundamental emission output power	RSS-247 Issue 2 Section A5.4(4)	Mode 1	≤30dBm	PASS

Power Spectral Density	RSS-247 Issue 2 Section A5.2(2)	Mode 1	≤8dBm/3kHz	PASS
Antenna Requirement	RSS-Gen Issue 4 Section 8.3	N/A	RSS-Gen Issue 4	PASS

2.2. Test Frequency configuration:

Modulation Mode	Channel	Frequency	Channel	Frequency	Channel	Frequency
BLE	00	2402 MHz	19	2440 MHz	39	2480MHz

2.3. Test Environment

Items	Required (IEC 68-1)	Actual
Temperature (°C)	15-35	21
Humidity (%RH)	25-75	50
Barometric pressure (mbar)	860-1060	950-1000

2.4. Measurement Uncertainty

Test Items	Uncertainty
AC Power Line Conducted Emission	±2.02dB
Radiated Emission	Below 1GHz ±3.8 dB
	Above 1GHz ±3.9 dB
RF Antenna Port Conducted Emission	±1.27dB
Radiated Emission Band Edge	±3.9dB
Occupied Bandwidth	±1kHz
Power Spectral Density	±1.27dB

3. AC Power Line Conducted Emission

3.1. Test Equipment

AC Power Line Conducted Emission / TR-1					
Instrument	Manufacturer	Type No.	Serial No.	Cal. Date	Cal. Due Date
EMI Test Receiver	R&S	ESCI	100906	2017.03.05	2018.03.04
Two-Line V-Network	R&S	ENV 216	101189	2017.07.16	2018.07.15
Two-Line V-Network	R&S	ENV 216	101044	2017.09.16	2018.09.15
50ohm Coaxial Switch	Anritsu	MP59B	6200464462	N/A	N/A
50ohm Termination	SHX	TF2	07081402	2017.09.16	2018.09.15
Temperature/Humidity Meter	Zhichen	ZC1-2	TR1-TH	2017.01.04	2018.01.03
Note: All equipment are calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.					

3.2. Test Setup

AC Power Line Conducted Emission test setup



3.3. Limit

Frequency of Emission (MHz)	Conducted Limit	
	Quasi-peak (dB μ V)	Average(dB μ V)
0.15-0.5	66 to 56	56 to 46
0.5-5	56	46
5-30	60	50
Note 1: The lower limit shall apply at the transition frequencies. Note 2: The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.5 MHz.		

3.4. Test Procedure

Test Method			
	References Rule	Chapter	Item
☒	ANSI C63.10-2013	6.2	Standard test method for ac power-line conducted emissions from unlicensed wireless devices
☒	ANSI C63.4-2014	7	AC power-line conducted emission measurements

3.5. Test Result

Engineer: Leon	
Site: TR1	Time: 2017/08/26
Limit: FCC_Part15.107_CE_AC Power_ClassB	Margin: 0
Probe: ENV216_101190(0.009-30MHz)	Polarity: Line
EUT: Bluetooth Headset	Power: AC 120V/60Hz
Mode 1: Transmit at 2402MHz by DH5 by normal mode	



No	Mark	Frequency (MHz)	Measure Level (dBuV)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV)	Probe (dB)	Cable (dB)	Amp (dB)	Type
1		0.150	36.998	27.364	-29.002	66.000	9.610	0.025	0.000	QP
2		0.150	18.702	9.067	-37.298	56.000	9.610	0.025	0.000	AV
3		0.214	27.445	17.815	-35.604	63.049	9.600	0.029	0.000	QP
4		0.214	14.395	4.766	-38.654	53.049	9.600	0.029	0.000	AV
5		0.270	21.538	11.905	-39.580	61.118	9.600	0.033	0.000	QP
6		0.270	13.776	4.143	-37.342	51.118	9.600	0.033	0.000	AV
7		0.522	20.750	11.107	-35.250	56.000	9.600	0.043	0.000	QP
8		0.522	14.538	4.895	-31.462	46.000	9.600	0.043	0.000	AV
9		1.594	20.689	11.003	-35.311	56.000	9.610	0.076	0.000	QP
10		1.594	13.431	3.745	-32.569	46.000	9.610	0.076	0.000	AV
11		16.066	35.649	25.440	-24.351	60.000	9.951	0.257	0.000	QP
12	*	16.066	28.835	18.626	-21.165	50.000	9.951	0.257	0.000	AV

Note:1." * ", means this data is the worst emission level.

2. Measurement Level = Reading Level + Factor(Probe+Cable-Amp).

3. Both charging case mode and normal mode had been tested. And only show the worst case data.

Engineer: Leon	
Site: TR1	Time: 2017/08/26
Limit: FCC_Part15.107_CE_AC Power_ClassB	Margin: 0
Probe: ENV216_101190(0.009-30MHz)	Polarity: Neutral
EUT: Bluetooth Headset	Power: AC 120V/60Hz
Mode 1: Transmit at 2402MHz by DH5 by normal mode	



No	Mark	Frequency (MHz)	Measure Level (dBuV)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV)	Probe (dB)	Cable (dB)	Amp (dB)	Type
1		0.170	36.308	26.675	-28.652	64.960	9.606	0.027	0.000	QP
2		0.170	22.132	12.500	-32.828	54.960	9.606	0.027	0.000	AV
3		0.222	29.042	19.412	-33.702	62.744	9.600	0.029	0.000	QP
4		0.222	16.771	7.142	-35.973	52.744	9.600	0.029	0.000	AV
5		0.514	22.467	12.823	-33.533	56.000	9.600	0.043	0.000	QP
6		0.514	16.181	6.537	-29.819	46.000	9.600	0.043	0.000	AV
7		1.578	22.040	12.354	-33.960	56.000	9.610	0.076	0.000	QP
8		1.578	14.130	4.444	-31.870	46.000	9.610	0.076	0.000	AV
9		3.530	13.019	3.264	-42.981	56.000	9.635	0.119	0.000	QP
10		3.530	4.505	-5.250	-41.495	46.000	9.635	0.119	0.000	AV
11		16.266	36.775	26.555	-23.225	60.000	9.961	0.259	0.000	QP
12	*	16.266	29.953	19.733	-20.047	50.000	9.961	0.259	0.000	AV

Note:1." * ", means this data is the worst emission level.

2. Measurement Level = Reading Level + Factor(Probe+Cable-Amp).

3. Both charging case mode and normal mode had been tested. And only show the worst case data.

4. Emissions in restricted frequency bands

4.1. Test Equipment

Radiated Emission(Below 1GHz) / AC-2					
Instrument	Manufacturer	Type No.	Serial No.	Cal. Date	Cal. Due Date
EMI Test Receiver	R&S	ESCI	100573	2017.03.29	2018.03.28
Loop Antenna	R&S	HFH2-Z2	833799/003	2016.11.16	2017.11.15
Bilog Antenna	Teseq GmbH	CBL6112D	27611	2016.10.16	2017.10.15
Coaxial Cable	Huber+Suhner	SUCOFLEX 106	AC2-C	2016.03.02	2018.03.01
Temperature/Humidity Meter	Zhichen	ZC1-2	AC2-TH	2017.01.03	2018.01.02
Note: All equipment are calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.					

Radiated Emission(Above 1GHz) / AC-5					
Instrument	Manufacturer	Type No.	Serial No.	Cal. Date	Cal. Due Date
Spectrum Analyzer	Agilent	E4446A	MY45300103	2017.01.04	2018.01.03
Preamplifier	Miteq	NSP1800-25	1364185	2017.05.06	2018.05.05
Preamplifier	QuieTek	AP-040G	CHM-0906001	2017.05.06	2018.05.05
DRG Horn	ETS-Lindgren	3117	00123988	2017.01.22	2018.01.21
Broad-Band Horn Antenna	Schwarzbeck	BBHA9170	294	2016.11.25	2017.11.24
Coaxial Cable	Huber+Suhner	SUCOFLEX 106	AC5-C1	2016.03.02	2018.03.01
Coaxial Cable	Huber+Suhner	SUCOFLEX 106	AC5-C2	2016.03.02	2018.03.01
Coaxial Cable	Huber+Suhner	SUCOFLEX 102	AC5-C3	2016.03.02	2018.03.01
EMI Receiver	Agilent	N9038A	MY51210196	2017.06.10	2018.06.09
Temperature/Humidity Meter	Zhichen	ZC1-2	AC5-TH	2017.01.04	2018.01.03
Note: All equipment are calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.					

4.2. Test Setup

Below 30MHz Test Setup:



30MHz-1GHz Test Setup:



Above 1GHz Test Setup:



4.3. Limit

For FCC

Restricted Bands of operation			
Frequency (MHz)	Frequency (MHz)	Frequency (MHz)	Frequency (GHz)
0.090 – 0.110	16.42 – 16.423	399.9 – 410	4.5 – 5.15
0.495 – 0.505	16.69475 –16.69525	608 – 614	5.35 – 5.46
2.1735 – 2.1905	16.80425 – 16.80475	960 – 1240	7.25 – 7.75
4.125 – 4.128	25.5 – 25.67	1300 – 1427	8.025 – 8.5
4.17725 – 4.17775	37.5 – 38.25	1435 – 1626.5	9.0 – 9.2
4.20725 – 4.20775	73 – 74.6	1645.5 – 1646.5	9.3 – 9.5
6.215 – 6.218	74.8 – 75.2	1660 – 1710	10.6 – 12.7
6.26775 – 6.26825	108 – 121.94	1718.8 – 1722.2	13.25 – 13.4
6.31175 – 6.31225	123 – 138	2200 – 2300	14.47 – 14.5
8.291 – 8.294	149.9 – 150.05	2310 – 2390	15.35 – 16.2
8.362 – 8.366	156.52475 – 156.52525	2483.5 – 2500	17.7 – 21.4
8.37625 – 8.38675	156.7 – 156.9	2690 – 2900	22.01 – 23.12
8.81425 – 8.81475	162.0125 – 167.17	3260 – 3267	23.6 – 24.0
12.29 – 12.293	167.72 – 173.2	3332 – 3339	31.2 – 31.8
12.51975–12.52025	240 – 285	3345.8 – 3358	36.43 – 36.5
12.57675–12.57725	322 – 335.4	3600 – 4400	
13.36 – 13.41			

For IC:

Restricted Bands of operation			
Frequency (MHz)	Frequency (MHz)	Frequency (MHz)	Frequency (GHz)
0.090-0.110	13.36-13.41	1645.5-1646.5	9.0-9.2
2.1735-2.1905	16.42-16.423	1660-1710	9.3-9.5
3.020-3.026	16.69475-16.69525	1718.8-1722.2	10.6-12.7
4.125-4.128	16.80425-16.80475	2200-2300	13.25-13.4
4.17725-4.17775	25.5-25.67	2310-2390	14.47-14.5
4.20725-4.20775	37.5-38.25	2655-2900	15.35-16.2
5.677-5.683	73-74.6	3260-3267	17.7-21.4
6.215-6.218	74.8-75.2	3332-3339	22.01-23.12
6.26775-6.26825	108-138	3345.8-3358	23.6-24.0
6.31175-6.31225	156.52475-156.52525	3500-4400	31.2-31.8
8.291-8.294	156.7-156.9	4500-5150	36.43-36.5
8.362-8.366	240-285	5350-5460	Above 38.6
8.37625-8.38675	322-335.4	7250-7750	
8.41425-8.41475	399.9-410	8025-8500	
12.29-12.293	608-614		
12.51975-12.52025	960-1427		
12.57675-12.57725	1435-1626.5		

Restricted Band Emissions Limit			
Frequency (MHz)	Field strength (μ V/m)	Field strength (dB μ V/m)	Measurement distance (m)
0.009 - 0.49	2400/F(kHz)	48.5 – 13.8	300(Note 1)
0.49 - 1.705	24000/F(kHz)	33.8 - 23	30(Note 1)
1.705 - 30	30	29.5	30(Note 1)
30 - 88	100	40	3(Note 2)
88 - 216	150	43.5	3(Note 2)
216 - 960	200	46	3(Note 2)
Above 960	500	54	3(Note 2)

Note 1: At frequencies below 30 MHz, measurements may be performed at a distance closer than that specified in the regulations; however, an attempt should be made to avoid making measurements in the near field. Pending the development of an appropriate measurement procedure for measurements performed below 30 MHz, when performing measurements at a closer distance than specified, the results shall be extrapolated to the specified distance by either making measurements at a minimum of two distances on at least one radial to determine the proper extrapolation factor or by using the square of an inverse linear distance extrapolation factor (40 dB/decade).

Note 2: At frequencies at or above 30 MHz, measurements may be performed at a distance other than what is specified provided: measurements are not made in the near field except where it can be shown that near field measurements are appropriate due to the characteristics of the device; and it can be demonstrated that the signal levels needed to be measured at the distance employed can be detected by the measurement equipment. Measurements shall not be performed at a distance greater than 30 meters unless it can be further demonstrated that measurements at a distance of 30 meters or less are impractical. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade (inverse linear-distance for field strength measurements; inverse-linear-distance-squared for power density measurements).

4.4. Test Procedure

Test Method						
	References Rule				Chapter	Description
☐	ANSI C63.10				11.11	Emissions in non-restricted frequency bands
	☐	ANSI C63.10			11.11.2	Reference level measurement
	☐	ANSI C63.10			11.11.3	Emission level measurement
☒	ANSI C63.10				11.12	Emissions in restricted frequency bands
	☒	ANSI C63.10			11.12.1	Radiated emission measurements
	☒	ANSI C63.10			11.12.2.7	Radiated spurious emission test
		☒	ANSI C63.10		6.4	Radiated emissions from unlicensed wireless devices below 30 MHz
		☒	ANSI C63.10		6.5	Radiated emissions from unlicensed wireless devices in the frequency range of 30 MHz to 1000 MHz
		☒	ANSI C63.10		6.6	Radiated emissions from unlicensed wireless devices above 1 GHz
		☐	ANSI C63.10		11.12.2.3	Quasi-peak measurement procedure
		☒	ANSI C63.10		11.12.2.4	Peak power measurement procedure
		☒	ANSI C63.10		11.12.2.5	Average power measurement procedures
			☐	ANSI C63.10	11.12.2.5.1	Trace averaging with continuous EUT transmission at full power
			☐	ANSI C63.10	11.12.2.5.2	Trace averaging across ON and OFF times of the EUT transmissions followed by duty cycle correction
			☒	ANSI C63.10	11.12.2.5.3	Reduced VBW averaging across ON and OFF times of the EUT transmissions with max hold

4.5. EUT test Axis definition

Item	Emissions in restricted frequency bands			
Device Category	☐	Fixed point-to-point		
	☐	Emit multiple directional beams, simultaneously or sequentially		
	☒	Other cases		
Test mode	Mode 1			
Test method	☒	Radiated		
		X Axis	Y Axis	Z Axis
				
		Worst Axis ☒	Worst Axis ☐	Worst Axis ☐
	☐	Conducted		
	☐	Chain 0		
				
	☐	Chain 0	Chain 1	
				
	☐	Chain 0	Chain 1	Chain 2

4.6. Test Result

Engineer: Slark	
Site: AC5	Time: 2017/09/19 - 16:50
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Bluetooth Headset	Power: AC 120V/60Hz
Note: Mode 1:Transmit at 2402MHz by BLE	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		4808.000	49.332	49.848	-24.668	74.000	-0.516	PK
2	*	4810.250	42.732	43.247	-11.268	54.000	-0.515	AV

Engineer: Slark	
Site: AC5	Time: 2017/09/19 - 16:50
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Bluetooth Headset	Power: AC 120V/60Hz
Note: Mode 1:Transmit at 2402MHz by BLE	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		4808.000	52.657	53.173	-21.343	74.000	-0.516	PK
2	*	4810.500	47.066	47.580	-6.934	54.000	-0.515	AV

Engineer: Slark	
Site: AC5	Time: 2017/09/19 - 16:50
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Bluetooth Headset	Power: AC 120V/60Hz
Note: Mode 1:Transmit at 2440MHz by BLE	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		4876.000	46.352	46.762	-27.648	74.000	-0.410	PK
2	*	4878.230	40.402	40.850	-13.598	54.000	-0.448	AV
3		7320.000	45.129	41.215	-28.871	74.000	3.914	PK
4		7322.478	38.514	34.589	-15.486	54.000	3.926	AV

Engineer: Slark	
Site: AC5	Time: 2017/09/19 - 16:50
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Bluetooth Headset	Power: AC 120V/60Hz
Note: Mode 1:Transmit at 2440MHz by BLE	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		4876.000	44.156	44.566	-29.844	74.000	-0.410	PK
2		4878.450	38.338	38.790	-15.662	54.000	-0.452	AV
3		7324.000	47.056	43.124	-26.944	74.000	3.932	PK
4	*	7324.860	40.527	36.610	-13.473	54.000	3.917	AV

Engineer: Slark	
Site: AC5	Time: 2017/09/19 - 16:50
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Bluetooth Headset	Power: AC 120V/60Hz
Note: Mode 1:Transmit at 2480MHz by BLE	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		4961.000	44.907	45.822	-29.093	74.000	-0.915	PK
2	*	4963.450	38.674	39.540	-15.326	54.000	-0.865	AV
3		7440.000	43.558	39.919	-30.442	74.000	3.638	PK
4		7442.600	36.047	32.450	-17.953	54.000	3.597	AV

Engineer: Slark	
Site: AC5	Time: 2017/09/19 - 16:50
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Bluetooth Headset	Power: AC 120V/60Hz
Note: Mode 1:Transmit at 2480MHz by BLE	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		4961.000	47.123	48.038	-26.877	74.000	-0.915	PK
2	*	4962.450	41.434	42.320	-12.566	54.000	-0.886	AV
3		7440.000	45.013	41.374	-28.987	74.000	3.638	PK
4		7440.600	38.139	34.510	-15.861	54.000	3.629	AV

The worst case of Radiated Emission below 1GHz:

Engineer: Samuel	
Site: AC3	Time: 2017/08/22
Limit: FCC_Part15.109_RE(3m)_ClassB	Margin: 0
Probe: AC3_3m (30-1000MHz)	Polarity: Horizontal
EUT: Bluetooth Headset	Power: AC 120V/60Hz
Note: Mode 1:Transmit at 2402MHz by DH5	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Probe (dB/m)	Cable (dB)	Amp (dB)	Ant Pos (cm)	Table Pos (deg)	Type
1		32.789	27.768	1.330	-12.232	40.000	19.968	6.470	0.000	100	164	QP
2		160.706	28.892	11.550	-14.608	43.500	10.215	7.128	0.000	200	39	QP
3		421.165	30.509	3.330	-15.491	46.000	19.219	7.960	0.000	100	326	QP
4		619.770	30.873	1.360	-15.127	46.000	21.032	8.482	0.000	100	326	QP
5		761.746	31.631	2.160	-14.369	46.000	20.675	8.797	0.000	100	159	QP
6	*	958.360	38.877	6.130	-7.123	46.000	23.531	9.216	0.000	100	313	QP

Note:1." * ", means this data is the worst emission level.

2. Measurement Level = Reading Level + Factor(Probe+Cable-Amp).

3. Both charging case mode and normal mode had been tested. And only show the worst case data.

Engineer: Samuel	
Site: AC3	Time: 2017/08/22
Limit: FCC_Part15.109_RE(3m)_ClassB	Margin: 0
Probe: AC3_3m (30-1000MHz)	Polarity: Vertical
EUT: Bluetooth Headset	Power: AC 120V/60Hz
Note: Mode 1:Transmit at 2402MHz by DH5	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Probe (dB/m)	Cable (dB)	Amp (dB)	Ant Pos (cm)	Table Pos (deg)	Type
1		36.305	24.214	2.360	-15.786	40.000	15.353	6.501	0.000	100	22	QP
2		66.374	21.930	6.430	-18.070	40.000	8.817	6.682	0.000	100	22	QP
3		104.326	24.183	2.150	-19.317	43.500	15.164	6.869	0.000	195	360	QP
4		155.096	27.318	8.630	-16.182	43.500	11.588	7.100	0.000	200	16	QP
5		207.032	27.313	4.110	-16.187	43.500	15.897	7.306	0.000	100	36	QP
6	*	882.745	33.339	0.360	-12.661	46.000	23.915	9.065	0.000	200	135	QP

Note:1." * ", means this data is the worst emission level.

2. Measurement Level = Reading Level + Factor(Probe+Cable-Amp).

3. Both charging case mode and normal mode had been tested. And only show the worst case data.

5. Emissions in non-restricted frequency bands

5.1. Test Equipment

Emissions in non-restricted frequency bands / TR-8					
Instrument	Manufacturer	Type No.	Serial No.	Cal. Date	Cal. Due Date
Spectrum Analyzer	Agilent	N9010A	MY48030494	2017.02.04	2018.02.03
EXA Spectrum Analyzer	Keysight	N9010A	MY55370495	2017.04.09	2018.04.08
MXA Signal Anlyzer	Keysight	N9020A	MY56060147	2017.04.09	2018.04.08
Temperature/Humidity Meter	zhichen	ZC1-2	TR8-TH	2017.04.10	2018.04.09
Note: All equipment are calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.					

5.2. Test Setup

Emissions in non-restricted frequency bands test setup:



5.3. Limit

Un-Restricted Band Emissions Limit	
RF Output power (Detection methods)	Limit(dB)
RF Output power(Average detector)	30c(Note1)
RF Output power(PK detector)	20c(Note2)

Note 1: If maximum conducted (average) output power was used to demonstrate compliance as described in 9.2, then the peak power in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 30 dB relative to the maximum in-band peak PSD level in 100 kHz (i.e., 30 dBc).

Note 2: If the maximum peak conducted output power procedure was used, then the peak output power measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz (i.e., 20 dBc).

5.4. Test Procedure

Test Method						
	References Rule				Chapter	Description
☒	ANSI C63.10				11.11	Emissions in non-restricted frequency bands
	☒	ANSI C63.10			11.11.2	Reference level measurement
	☒	ANSI C63.10			11.11.3	Emission level measurement
☐	ANSI C63.10				11.12	Emissions in restricted frequency bands
	☐	ANSI C63.10			11.12.1	Radiated emission measurements
	☐	ANSI C63.10			11.12.2.7	Radiated spurious emission test
☐	ANSI C63.10				6.4	Radiated emissions from unlicensed wireless devices below 30 MHz
☐	ANSI C63.10				6.5	Radiated emissions from unlicensed wireless devices in the frequency range of 30 MHz to 1000 MHz
☐	ANSI C63.10				6.6	Radiated emissions from unlicensed wireless devices above 1 GHz
	☒	ANSI C63.10			11.12.2	Antenna-port conducted measurements
		☐	ANSI C63.10		11.12.2.3	Quasi-peak measurement procedure
		☒	ANSI C63.10		11.12.2.4	Peak power measurement procedure
		☐	ANSI C63.10		11.12.2.5	Average power measurement procedures
			☐	ANSI C63.10	11.12.2.5.1	Trace averaging with continuous EUT transmission at full power
			☐	ANSI C63.10	11.12.2.5.2	Trace averaging across ON and OFF times of the EUT transmissions followed by duty cycle correction
			☐	ANSI C63.10	11.12.2.5.3	Reduced VBW averaging across ON and OFF times of the EUT transmissions with max hold

5.5. EUT test Axis definition

Item	Emissions in non-restricted frequency bands			
Device Category	☐	Fixed point-to-point		
	☐	Emit multiple directional beams, simultaneously or sequentially		
	☒	Other cases		
Test mode	Mode 1			
Test method	☐	Radiated		
		X Axis	Y Axis	Z Axis
				
		Worst Axis ☐	Worst Axis ☐	Worst Axis ☐
	☒	Conducted		
	☒	Chain 0		
				
	☐	Chain 0	Chain 1	
				
	☐	Chain 0	Chain 1	Chain 2

5.6. Test Result

Product Name	:	Bluetooth Headset	Power	:	AC 120V/60Hz
Test Mode	:	Mode 1	Test Site	:	TR-8
Test Date	:	2017.09.15			

Mode	Channel	Test Frequency (MHz)	In-Band PSD[a] (dBm/100kHz)	Frequency (MHz)	Out-Band PSD[b] (dBm/100kHz)	[a]-[b] (dB)	Limit (dB)	Result
1	00	2402	8.253	2400.00	-36.660	44.913	>20	Pass
1	39	2480	9.266	2500.00	-48.114	57.38	>20	Pass

Note: The worst case of Emissions in non-restricted frequency bands as below:

Mode 1 CH00 (2402MHz)



6. Radiated Emission Band Edge

6.1. Test Equipment

Radiated Emission(Above 1GHz) / AC-5					
Instrument	Manufacturer	Type No.	Serial No.	Cal. Date	Cal. Due Date
EMI Receiver	Agilent	N9038A	MY51210196	2017.07.16	2018.07.15
Pre-Amplifier	Miteq	NSP1800-25	1364185	2017.05.03	2018.05.02
DRG Horn Antenna	ETS-Lindgren	3117	00167055	2017.07.12	2018.07.11
Broad-Band Horn Antenna	Schwarzbeck	BBHA9170	294	2017.09.18	2018.09.17
Coaxial Cable	Huber+Suhner	SUCOFLEX 106	AC5-C1	2017.02.28	2018.02.27
Coaxial Cable	Huber+Suhner	SUCOFLEX 106	AC5-C2	2017.02.28	2018.02.27
Temperature/Humidity Meter	Zhichen	ZC1-2	AC5-TH	2017.01.05	2018.01.04

6.2. Test Setup

Above 1GHz Test Setup:



6.3. Limit

Band edge Limit				
Frequency bands (MHz)	Detector	Limit (dB μ V/m)	RBW (MHz)	Distance (m)
2310-2390 2483.5-2500	PK	74	1	3
	AV	54	1	3
Note: The field strength of emissions appearing within these frequency bands shall not exceed the limits.				

6.4. Test Procedure

Test Method						
	References Rule				Chapter	Description
☒	ANSI C63.10				6.10	Band-edge testing
	☒	ANSI C63.10			6.10.5	Restricted-band band-edge measurements
	☐	ANSI C63.10			6.10.6	Marker-delta method
☒	ANSI C63.10				11.12	Emissions in restricted frequency bands
	☒	ANSI C63.10			11.12.1	Radiated emission measurements
	☒	ANSI C63.10			11.12.2.7	Radiated spurious emission test
☐	ANSI C63.10				6.4	Radiated emissions from unlicensed wireless devices below 30 MHz
☐	ANSI C63.10				6.5	Radiated emissions from unlicensed wireless devices in the frequency range of 30 MHz to 1000 MHz
☒	ANSI C63.10				6.6	Radiated emissions from unlicensed wireless devices above 1 GHz
		☐	ANSI C63.10		11.12.2.3	Quasi-peak measurement procedure
		☒	ANSI C63.10		11.12.2.4	Peak power measurement procedure
		☒	ANSI C63.10		11.12.2.5	Average power measurement procedures
			☐	ANSI C63.10	11.12.2.5.1	Trace averaging with continuous EUT transmission at full power
			☐	ANSI C63.10	11.12.2.5.2	Trace averaging across ON and OFF times of the EUT transmissions followed by duty cycle correction
			☒	ANSI C63.10	11.12.2.5.3	Reduced VBW averaging across ON and OFF times of the EUT transmissions with max hold

6.5. EUT test definition

Item	Radiated Emission Band Edge			
Device Category	☐	Fixed point-to-point		
	☐	Emit multiple directional beams, simultaneously or sequentially		
	☒	Other cases		
Test mode	Mode 1			
Test method	☒	Radiated		
		X Axis	Y Axis	Z Axis
				
		Worst Axis ☒	Worst Axis ☐	Worst Axis ☐
	☐	Conducted		
	☐	Chain 0		
				
	☐	Chain 0	Chain 1	
				
	☐	Chain 0	Chain 1	Chain 2

6.6. Duty Cycle

Test Mode	Tx On (ms)	Tx Off (ms)	Reduced VBW (kHz)	Tx On + Tx Off (ms)	Duty Cycle
BLE	0.394	0.230	2.7kHz	0.624	63.14%

BLE



6.7 Test Result

Engineer: Slark	
Site: AC5	Time: 2017/09/16 - 16:33
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Bluetooth Headset	Power: AC 120V/60Hz
Note: Mode 1:Transmit at 2402MHz by BLE	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		2390.000	39.176	3.494	-14.824	54.000	35.682	AV
2	*	2402.055	94.799	59.086	N/A	N/A	35.712	AV

Engineer: Slark	
Site: AC5	Time: 2017/09/16 - 16:39
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Bluetooth Headset	Power: AC 120V/60Hz
Note: Mode 1:Transmit at 2402MHz by BLE	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		2390.000	51.069	15.387	-22.931	74.000	35.682	PK
2	*	2402.198	95.668	59.955	N/A	N/A	35.714	PK

Engineer: Slark	
Site: AC5	Time: 2017/09/16 - 16:41
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Bluetooth Headset	Power: AC 120V/60Hz
Note: Mode 1:Transmit at 2402MHz by BLE	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		2390.000	39.149	3.467	-14.851	54.000	35.682	AV
2	*	2401.913	89.834	54.122	N/A	N/A	35.712	AV

Engineer: Slark	
Site: AC5	Time: 2017/09/16 - 16:42
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Bluetooth Headset	Power: AC 120V/60Hz
Note: Mode 1:Transmit at 2402MHz by BLE	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		2390.000	50.593	14.911	-23.407	74.000	35.682	PK
2	*	2401.960	90.716	55.003	N/A	N/A	35.712	PK

Engineer: Slark	
Site: AC5	Time: 2017/09/16 - 16:44
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Bluetooth Headset	Power: AC 120V/60Hz
Note: Mode 1:Transmit at 2440MHz by BLE	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		2390.000	39.100	3.418	-14.900	54.000	35.682	AV
2	*	2440.055	98.284	62.479	N/A	N/A	35.805	AV
3		2483.500	39.410	3.518	-14.590	54.000	35.891	AV

Engineer: Slark	
Site: AC5	Time: 2017/09/16 - 16:48
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Bluetooth Headset	Power: AC 120V/60Hz
Note: Mode 1:Transmit at 2440MHz by BLE	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		2390.000	50.020	14.338	-23.980	74.000	35.682	PK
2	*	2439.770	99.666	63.861	N/A	N/A	35.806	PK
3		2483.500	50.725	14.833	-23.275	74.000	35.891	PK

Engineer: Slark	
Site: AC5	Time: 2017/09/16 - 16:50
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Bluetooth Headset	Power: AC 120V/60Hz
Note: Mode 1:Transmit at 2440MHz by BLE	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		2390.000	39.180	3.498	-14.820	54.000	35.682	AV
2	*	2440.150	94.426	58.621	N/A	N/A	35.805	AV
3		2483.500	39.551	3.659	-14.449	54.000	35.891	AV

Engineer: Slark	
Site: AC5	Time: 2017/09/16 - 16:52
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Bluetooth Headset	Power: AC 120V/60Hz
Note: Mode 1:Transmit at 2440MHz by BLE	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		2390.000	50.387	14.705	-23.613	74.000	35.682	PK
2	*	2439.675	95.348	59.543	N/A	N/A	35.806	PK
3		2483.500	50.957	15.065	-23.043	74.000	35.891	PK

Engineer: Slark	
Site: AC5	Time: 2017/09/16 - 16:53
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Bluetooth Headset	Power: AC 120V/60Hz
Note: Mode 1:Transmit at 2480MHz by BLE	

No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	2480.057	96.036	60.169	N/A	N/A	35.867	AV
2		2483.500	43.114	7.222	-10.886	54.000	35.891	AV

Engineer: Slark	
Site: AC5	Time: 2017/09/16 - 16:57
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Bluetooth Headset	Power: AC 120V/60Hz
Note: Mode 1:Transmit at 2480MHz by BLE	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	2479.947	96.880	61.014	N/A	N/A	35.866	PK
2		2483.500	54.034	18.142	-19.966	74.000	35.891	PK

Engineer: Slark	
Site: AC5	Time: 2017/09/16 - 16:58
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Bluetooth Headset	Power: AC 120V/60Hz
Note: Mode 1:Transmit at 2480MHz by BLE	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	2480.057	85.925	50.058	N/A	N/A	35.867	AV
2		2483.500	39.898	4.006	-14.102	54.000	35.891	AV

Engineer: Slark	
Site: AC5	Time: 2017/09/16 - 17:00
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Bluetooth Headset	Power: AC 120V/60Hz
Note: Mode 1:Transmit at 2480MHz by BLE	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	2479.815	86.981	51.116	N/A	N/A	35.865	PK
2		2483.500	51.414	15.522	-22.586	74.000	35.891	PK

7. Occupied Bandwidth

7.1. Test Equipment

Occupied Bandwidth / TR-8					
Instrument	Manufacturer	Type No.	Serial No.	Cal. Date	Cal. Due Date
Spectrum Analyzer	Agilent	N9010A	MY48030494	2017.02.04	2018.02.03
EXA Spectrum Analyzer	Keysight	N9010A	MY55370495	2017.04.09	2018.04.08
MXA Signal Anlyzer	Keysight	N9020A	MY56060147	2017.04.09	2018.04.08
Temperature/Humidity Meter	zhichen	ZC1-2	TR8-TH	2017.04.10	2018.04.09
Note: All equipment are calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.					

7.2. Test Setup

Occupied Bandwidth test setup:



7.3. Limit

Occupied Bandwidth
Systems using digital modulation techniques operate in the2400-2483.5 MHz .The minimum 6 dB bandwidth shall be at least 500 kHz

7.4. Test Procedure

Test Method				
	Reference Rule		Chapter	Description
☒	ANSI C63.10		11.8	DTS bandwidth
	☐	ANSI C63.10	11.8.1	Option 1
	☒	ANSI C63.10	11.8.2	Option 2

7.5. EUT test definition

Item	Occupied Bandwidth			
Device Category	☐	Fixed point-to-point		
	☐	Emit multiple directional beams, simultaneously or sequentially		
	☒	Other cases		
Test mode	Mode 1			
Test method	☐	Radiated		
		X Axis	Y Axis	Z Axis
				
		Worst Axis ☐	Worst Axis ☐	Worst Axis ☐
	☒	Conducted		
	☒	Chain 0		
				
	☐	Chain 0	Chain 1	
				
	☐	Chain 0	Chain 1	Chain 2

7.6. Test Result

Product Name	:	Bluetooth Headset	Power	:	AC 120V/60Hz
Test Mode	:	Mode 1	Test Site	:	TR-8
Test Date	:	2017.09.15			

Mode	CH.	Test Freq. (MHz)	99% Occupied Bandwidth (kHz)	6dB Occupied Bandwidth (kHz)	Limit (kHz)	Result
1	00	2402	1066	704.2	>500	Pass
1	19	2440	1057.2	691.8	>500	Pass
1	39	2480	1057.8	700.5	>500	Pass

Note : The worst case of Occupied Bandwidth as below:

Mode 1 CH19 (2440MHz)



8. Fundamental emission output power

8.1. Test Equipment

Fundamental emission output power/ TR-8					
Instrument	Manufacturer	Type No.	Serial No.	Cal. Date	Cal. Due Date
Spectrum Analyzer	Agilent	E4446A	MY45300103	2017.01.04	2018.01.03
Spectrum Analyzer	Agilent	N9010A	MY48030494	2017.01.04	2018.01.03
Wideband Peak Power Meter	Anritsu	ML2495A	0905006	2016.10.14	2017.10.13
Power Sensor	Anritsu	MA2411B	0846014	2016.10.14	2017.10.13
Temperature/Humidity Meter	zhicheng	ZC1-2	TR8-TH	2017.04.10	2018.04.09
Note: All equipment are calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.					

8.2. Test Setup

Fundamental emission output power test setup



8.3. Limit

Fundamental emission output power Limit			
☒	G_{TX} ＜6dBi		P_{out}≤30dBm
☐	G_{TX} ＞6dBi		
	☐	Non-Fix point-point	P_{out}≤30-(G_{TX} -6)
	☐	Fix point-point	P_{out}≤30-[(G_{TX}-6)]/3
	☐	Point-to-multipoint	P_{out}≤30-(G_{TX}-6)
	☐	Overlap Beams	P_{out}≤30-[(G_{TX}-6)]/3
	☐	Aggregate power transmitted simultaneously on all beams	P_{out}≤30-[(G_{TX}-6)]/3
	☐	single directional beam	P_{out}≤30-[(G_{TX}-6)]/3+8dB
Note 1 : G_{TX} directional gain of transmitting antennas. Note 2 : P_{out} is maximum peak conducted output power .			

8.4. Test Procedure

Fundamental emission output power Test Method						
	References Rule				Chapter	Description
☒	ANSI C63.10				11.9	Fundamental emission output power
	☒	ANSI C63.10			11.9.1	Maximum peak conducted output power
		☐	ANSI C63.10		11.9.1.1	RBW ≥ DTS bandwidth
		☐	ANSI C63.10		11.9.1.2	Integrated band power method
		☒	ANSI C63.10		11.9.1.3	PKPM1 Peak power meter method
	☐	ANSI C63.10			11.9.2	Maximum conducted (average) output power
		☐	ANSI C63.10		11.9.2.2	Measurement using a spectrum analyzer (SA)
			☐	ANSI C63.10	11.9.2.2.2	Method AVGSA-1(Duty cycle≥98%)
			☐	ANSI C63.10	11.9.2.2.3	Method AVGSA-1A(Duty cycle≥98%)
			☐	ANSI C63.10	11.9.2.2.4	Method AVGSA-2(Duty cycle≤98%)
			☐	ANSI C63.10	11.9.2.2.5	Method AVGSA-2A(Duty cycle≤98%)
			☐	ANSI C63.10	11.9.2.2.4	Method AVGSA-3
			☐	ANSI C63.10	11.9.2.2.5	Method AVGSA-3A
		☐	ANSI C63.10		11.9.2.3	Measurement using a power meter (PM)
			☐	ANSI C63.10	11.9.2.3.1	Method AVGPM
			☐	ANSI C63.10	11.9.2.3.2	Method AVGPM-G

8.5. EUT test definition

Item	Fundamental emission output power			
Device Category	☐	Fixed point-to-point		
	☐	Emit multiple directional beams, simultaneously or sequentially		
	☒	Other cases		
Test mode	Mode 1			
Test method	☐	Radiated		
		X Axis	Y Axis	Z Axis
				
		Worst Axis ☐	Worst Axis ☐	Worst Axis ☐
	☒	Conducted		
	☒	Chain 0		
				
	☐	Chain 0	Chain 1	
				
	☐	Chain 0	Chain 1	Chain 2

8.6. Test Result

Product Name	:	Bluetooth Headset	Power	:	AC 120V/60Hz
Test Mode	:	Mode 1	Test Site	:	TR-8
Test Date	:	2017.09.15			

Mode	Channel	Test Frequency (MHz)	Measurement Power Output (dBm)	Limit (dBm)	Result
1	00	2402	7.99	30	Pass
1	19	2440	8.36	30	Pass
1	39	2480	8.19	30	Pass

9. Power Spectral Density

9.1. Test Equipment

Power Spectral Density / TR-8					
Instrument	Manufacturer	Type No.	Serial No.	Cal. Date	Cal. Due Date
Spectrum Analyzer	Agilent	N9010A	MY48030494	2017.02.04	2018.02.03
EXA Spectrum Analyzer	Keysight	N9010A	MY55370495	2017.04.09	2018.04.08
MXA Signal Anlyzer	Keysight	N9020A	MY56060147	2017.04.09	2018.04.08
Temperature/Humidity Meter	zhichen	ZC1-2	TR8-TH	2017.04.10	2018.04.09
Note: All equipment are calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.					

9.2. Test Setup

Power Spectral Density test setup



9.3. Limit

Power Spectral Density Limit
Power Spectral Density≤8dBm/3kHz

9.4. Test Procedure

Power Spectral Density Test Method				
	References Rule		Chapter	Description
☒	ANSI C63.10		11.10	Maximum power spectral density level in the fundamental emission
	☒	ANSI C63.10	11.10.2	Method PKPSD (peak PSD)
	☐	ANSI C63.10	11.10.3	Method AVGPSD-1(Duty cycle≥98%)
	☐	ANSI C63.10	11.10.4	Method AVGPSD-1A(Duty cycle≥98%)
	☐	ANSI C63.10	11.10.5	Method AVGPSD-2(Duty cycle＜98%)
	☐	ANSI C63.10	11.10.6	Method AVGPSD-2A(Duty cycle＜98%)
	☐	ANSI C63.10	11.10.7	Method AVGPSD-3
	☐	ANSI C63.10	11.10.8	Method AVGPSD-3A

9.5. EUT test definition

Item	Power Spectral Density Test Method			
Device Category	☐	Fixed point-to-point		
	☐	Emit multiple directional beams, simultaneously or sequentially		
	☒	Other cases		
Test mode	Mode 1			
Test method	☐	Radiated		
		X Axis	Y Axis	Z Axis
				
		Worst Axis ☐	Worst Axis ☐	Worst Axis ☐
	☒	Conducted		
	☒	Chain 0		
				
	☐	Chain 0	Chain 1	
				
	☐	Chain 0	Chain 1	Chain 2

9.6. Test Result

Product Name	:	Bluetooth Headset	Power	:	AC 120V/60Hz
Test Mode	:	Mode 1	Test Site	:	TR-8
Test Date	:	2017.09.15			

Mode	Channel	Test Frequency (MHz)	Measurement PSD (dBm/3kHz)	Total PSD (dBm/3kHz)	Limit (dBm/3kHz)	Result
1	00	2402	-7.209	-7.209	8	Pass
1	19	2440	-6.165	-6.165	8	Pass
1	39	2480	-6.540	-6.540	8	Pass

Note : The worst case of Power Spectral Density as below:

Mode 1 CH19(2440MHz)



10. Antenna Requirement

10.1. Limit

Antenna Requirement Limit
An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of §15.211, §15.213, §15.217, §15.219, or §15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with §15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

10.2. Antenna Connector Construction

Antenna Connector Construction	
☒	The use of a permanently attached antenna
☐	The antenna use of a unique coupling to the intentional radiator
☐	The use of a nonstandard antenna jack or electrical connector
Please refer to the attached document “Internal Photograph” to show the antenna connector.	

The End