FCC RF Test Report

APPLICANT	:	Weifang GoerTek Electronics Co.,Ltd.
EQUIPMENT	:	SRH-S1
BRAND NAME	:	SONY
MODEL NAME	:	SRH-S1
FCC ID	:	SZGSRHS1
STANDARD	:	FCC Part 15 Subpart C §15.247
CLASSIFICATION	:	(DTS) Digital Transmission System
TEST DATE(S)	:	Apr. 21, 2024 ~ Jun. 29, 2024

We, Sporton International Inc. (Kunshan), would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International Inc. (Kunshan), the test report shall not be reproduced except in full.

Jason Jia

Approved by: Jason Jia

ACCREDITED
Cert #5145.02

Sporton International Inc. (Kunshan)
No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300 People's Republic of China

TABLE OF CONTENTS

REVISION HISTORY **3**
SUMMARY OF TEST RESULT **4**
1 GENERAL DESCRIPTION **5**
1.1 Applicant 5
1.2 Manufacturer 5
1.3 Product Feature of Equipment Under Test 5
1.4 Product Specification of Equipment Under Test 6
1.5 Modification of EUT 6
1.6 Testing Location 6
1.7 Test Software 7
1.8 Applicable Standards 7
2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST **8**
2.1 Carrier Frequency Channel 8
2.2 Test Mode 9
2.3 Connection Diagram of Test System 10
2.4 Support Unit used in test configuration and system 11
2.5 EUT Operation Test Setup 11
2.6 Measurement Results Explanation Example 11
3 TEST RESULT **12**
3.1 6dB and 99% Bandwidth Measurement 12
3.2 Output Power Measurement 13
3.3 Power Spectral Density Measurement 14
3.4 Conducted Band Edges and Spurious Emission Measurement 15
3.5 Radiated Band Edges and Spurious Emission Measurement 16
3.6 AC Conducted Emission Measurement 20
3.7 Antenna Requirements 22
4 LIST OF MEASURING EQUIPMENT **23**
5 MEASUREMENT UNCERTAINTY **24**
APPENDIX A. CONDUCTED TEST RESULTS
APPENDIX B. AC CONDUCTED EMISSION TEST RESULT
APPENDIX C. RADIATED SPURIOUS EMISSION
APPENDIX D. DUTY CYCLE PLOTS

REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR420222B	Rev. 01	Initial issue of report	Jul. 15, 2024

SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	15.247(a)(2)	6dB Bandwidth	≥ 0.5MHz	Pass	-
3.1	-	99% Bandwidth	-	Report only	-
3.2	15.247(b)(3)	Peak Output Power	≤ 30dBm	Pass	-
3.3	15.247(e)	Power Spectral Density	≤ 8dBm/3kHz	Pass	-
3.4	15.247(d)	Conducted Band Edges and Spurious Emission	≤ 20dBc	Pass	-
3.5	15.247(d)	Radiated Band Edges and Spurious Emission	15.209(a) & 15.247(d)	Pass	Under limit 3.50 dB at 35.82 MHz
3.6	15.207	AC Conducted Emission	15.207(a)	Pass	Under limit 11.18 dB at 0.8990 MHz
3.7	15.203 & 15.247(b)	Antenna Requirement	15.203 & 15.247(b)	Pass	-

Conformity Assessment Condition:

1. The test results (PASS/FAIL) with all measurement uncertainty excluded are presented against the regulation limits or in accordance with the requirements stipulated by the applicant/manufacturer who shall bear all the risks of non-compliance that may potentially occur if measurement uncertainty is taken into account.
2. The measurement uncertainty please refer to each test result in the section “Measurement Uncertainty”

Disclaimer:

The product specifications of the EUT presented in the test report that may affect the test assessments are declared by the manufacturer who shall take full responsibility for the authenticity.

1 General Description

1.1 Applicant

Weifang GoerTek Electronics Co.,Ltd.
Gaoxin 2 Road,Free Trade Zone,Weifang,Shandong,261205,P.R.China

1.2 Manufacturer

Sony Corporation
1-7-1 Konan Minato-ku Tokyo, 108-0075 Japan

1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	SRH-S1
Brand Name	SONY
Model Name	SRH-S1
FCC ID	SZGSRHS1
SN	Conducted: TM722913CF000352 Conduction: VHZJD2DVT21008 Radiation: VHZJD2DVT21014
HW Version	R2
SW Version	V3
EUT Stage	Identical Prototype

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

1.4 Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx/Rx Frequency Range	2402 MHz ~ 2480 MHz
Number of Channels	40
Carrier Frequency of Each Channel	40 Channel (37 hopping + 3 advertising channel)
Maximum Output Power to Antenna	<ANT1> BLE 1Mbps: 3.49 dBm (0.0022 W) BLE 2Mbps: 3.53 dBm (0.0023 W) <ANT2> BLE 1Mbps: 3.99 dBm (0.0025 W) BLE 2Mbps: 3.76 dBm (0.0024 W)
99% Occupied Bandwidth	<ANT1> BLE 1Mbps: 1.027 MHz BLE 2Mbps: 2.038 MHz <ANT2> BLE 1Mbps: 1.027 MHz BLE 2Mbps: 2.038 MHz
Antenna Type / Gain	ANT.1 FPC Antenna with gain 4.91 dBi ANT.2 FPC Antenna with gain 4.03 dBi
Type of Modulation	Bluetooth LE : GFSK

Note:

1. The BLE Ant.1 & Ant.2 only support SISO mode, not support MIMO.
2. The BLE Ant.1 & Ant.2 are corresponding to Qualcomm chipset.

1.5 Modification of EUT

No modifications are made to the EUT during all test items.

1.6 Testing Location

Sporton International Inc. (Kunshan) is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.02.

Test Firm	Sporton International Inc. (Kunshan)		
Test Site Location	No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300 People's Republic of China TEL : +86-512-57900158		
Test Site No.	**Sporton Site No.**	**FCC Designation No.**	**FCC Test Firm Registration No.**
	CO01-KS 03CH08-KS TH01-KS	CN1257	314309

1.7 Test Software

Item	Site	Manufacturer	Name	Version
1.	TH01-KS	Tonscend	JS1120-3 test system China_210602	3.3.10
2.	03CH08-KS	AUDIX	E3	210616
3.	CO01-KS	AUDIX	E3	6.2009-8-24

1.8 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- 47 CFR Part 15 Subpart C §15.247
- FCC KDB 558074 D01 15.247 Meas Guidance v05r02
- ANSI C63.10-2013

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

2 Test Configuration of Equipment Under Test

2.1 Carrier Frequency Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
2400-2483.5 MHz	0	2402	21	2444
	1	2404	22	2446
	2	2406	23	2448
	3	2408	24	2450
	4	2410	25	2452
	5	2412	26	2454
	6	2414	27	2456
	7	2416	28	2458
	8	2418	29	2460
	9	2420	30	2462
	10	2422	31	2464
	11	2424	32	2466
	12	2426	33	2468
	13	2428	34	2470
	14	2430	35	2472
	15	2432	36	2474
	16	2434	37	2476
	17	2436	38	2478
	18	2438	39	2480
	19	2440	-	-
	20	2442	-	-

2.2 Test Mode

a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases (Y plane) were recorded in this report.

b. AC power line Conducted Emission was tested under maximum output power.

The following summary table is showing all test modes to demonstrate in compliance with the standard.

Summary table of Test Cases	
Test Item	**Data Rate / Modulation**
	Bluetooth – LE / GFSK
Conducted TCs	Mode 1: Bluetooth Tx CH00_2402 MHz_BLE 1Mbps Mode 2: Bluetooth Tx CH19_2440 MHz_BLE 1Mbps Mode 3: Bluetooth Tx CH39_2480 MHz_BLE 1Mbps Mode 4: Bluetooth Tx CH00_2402 MHz_BLE 2Mbps Mode 5: Bluetooth Tx CH19_2440 MHz_BLE 2Mbps Mode 6: Bluetooth Tx CH39_2480 MHz_BLE 2Mbps
Radiated TCs	Mode 1: Bluetooth Tx CH00_2402 MHz_BLE 1Mbps Mode 2: Bluetooth Tx CH19_2440 MHz_BLE 1Mbps Mode 3: Bluetooth Tx CH39_2480 MHz_BLE 1Mbps Mode 4: Bluetooth Tx CH00_2402 MHz_BLE 2Mbps Mode 5: Bluetooth Tx CH19_2440 MHz_BLE 2Mbps Mode 6: Bluetooth Tx CH39_2480 MHz_BLE 2Mbps
AC Conducted Emission	Mode 1: nRF Tx + Bluetooth Link + WLAN Link (2.4G) + USB Cable1 (Charging from Adapter)
Remark: For Radiated Test Cases, The tests were performance with Adapter and USB Cable1.	

RSE Co-location
BLE(2 Mbps) CH39_ANT 1_TX + BLE(2Mbps)_CH 39_ANT 3_TX

2.3 Connection Diagram of Test System

AC Conducted Emission:



Radiated Emission:



2.4 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	Bluetooth Earphone	Lenovo	thinkplus-BH3	N/A	N/A	N/A
2.	Notebook	Lenovo	G480	QDS-BRCM1050I	N/A	shielded cable DC O/P 1.8m , Unshielded AC I/P cable 1.8m
3.	Router	D-link	DIR-655	KA21R655B1	N/A	Unshielded,1.8m
4.	Adapter	tianyin	TPD-71B120250CU01	N/A	N/A	N/A

2.5 EUT Operation Test Setup

For BLE function, the engineering test program was provided and enabled to make EUT continuous transmit.

For AC power line conducted emissions, the EUT was set to connect with the WLAN AP under large package sizes transmission.

2.6 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example :

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 2.19 dB and 10dB attenuator.

Offset(dB) = RF cable loss(dB) + attenuator factor(dB).

= 2.19 + 10 = 12.19 (dB)

3 Test Result

3.1 6dB and 99% Bandwidth Measurement

3.1.1 Limit of 6dB and 99% Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.

3.1.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

3.1.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 11.8
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6 dB bandwidth must be greater than 500 kHz.
5. For 99% Bandwidth Measurement, the spectrum analyzer's resolution bandwidth (RBW) is set 1% to 5% of the 99% OBW and the VBW is set to 3 times of the RBW.
6. Measure and record the results in the test report.

3.1.4 Test Setup



3.1.5 Test Result of 6dB Bandwidth and 99% Occupied Bandwidth

Please refer to Appendix A.

3.2 Output Power Measurement

3.2.1 Limit of Output Power

For systems using digital modulation in the 2400-2483.5MHz, the limit for peak output power is 30dBm. If transmitting antenna of directional gain greater than 6dBi is used, the peak output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.

3.2.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

3.2.3 Test Procedures

1. The testing follows the Measurement Procedure of ANSI C63.10-2013 clause 11.9.1.3 PKPM1 Peak power meter or ANSI C63.10-2013 clause 11.9.2.3.1 Method AVGPM method.
2. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Measure the conducted output power and record the results in the test report.

3.2.4 Test Setup



3.2.5 Test Result of Peak Output Power

Please refer to Appendix A.

3.2.6 Test Result of Average Output Power (Reporting Only)

Please refer to Appendix A.

3.3 Power Spectral Density Measurement

3.3.1 Limit of Power Spectral Density

The peak power spectral density shall not be greater than 8dBm in any 3kHz band at any time interval of continuous transmission.

3.3.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

3.3.3 Test Procedures

1. The testing follows Measurement Procedure of ANSI C63.10-2013 clause 11.10.2 Method PKPSD.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 3 kHz. Video bandwidth VBW = 10 kHz In order to make an accurate measurement, set the span to 1.5 times DTS Channel Bandwidth. (6dB BW)
5. Detector = peak, Sweep time = auto couple, Trace mode = max hold, Allow trace to fully stabilize. Use the peak marker function to determine the maximum power level.
6. Measure and record the results in the test report.
7. The Measured power density (dBm)/ 100kHz is a reference level and used as 20dBc down limit line for Conducted Band Edges and Conducted Spurious Emission.

3.3.4 Test Setup



3.3.5 Test Result of Power Spectral Density

Please refer to Appendix A.

3.4 Conducted Band Edges and Spurious Emission Measurement

3.4.1 Limit of Conducted Band Edges and Spurious Emission

All harmonics/spurious must be at least 20 dB down from the highest emission level within the authorized band.

3.4.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

3.4.3 Test Procedure

1. The testing follows ANSI C63.10-2013 clause 11.13
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Set RBW = 100 kHz, VBW=300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

3.4.4 Test Setup



3.4.5 Test Result of Conducted Band Edges Plots

Please refer to Appendix A.

3.4.6 Test Result of Conducted Spurious Emission Plots

Please refer to Appendix A.

3.5 Radiated Band Edges and Spurious Emission Measurement

3.5.1 Limit of Radiated Band Edges and Spurious Emission

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. If the output power of this device was measured by spectrum analyzer, the attenuation under this paragraph shall be 30 dB instead of 20 dB. In addition, radiated emissions which fall in the restricted bands must also comply with the limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.5.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

3.5.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 11.11 & 11.12
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.
3. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
6. For testing below 1GHz, if the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then peak values of EUT will be reported, otherwise, the emissions will be repeated one by one using the CISPR quasi-peak method and reported.
7. For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than peak limit (that means the emission level in average mode also complies with the limit in average mode), then peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
8. Use the following spectrum analyzer settings:
   (1) Span shall wide enough to fully capture the emission being measured;
   (2) Set RBW=100 kHz for f < 1 GHz; VBW ≥ RBW; Sweep = auto; Detector function = peak; Trace = max hold;
   (3) Set RBW = 1 MHz, VBW= 3MHz for f ≥ 1 GHz for peak measurement.
   For average measurement:
   - VBW = 10 Hz, when duty cycle is no less than 98 percent.
   - VBW ≥ 1/T, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.

3.5.4 Test Setup

For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



3.5.5 Test Results of Radiated Spurious Emissions (9 kHz ~ 30 MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

There is a comparison data of both open-field test site and semi-Anechoic chamber, and the result came out very similar.

3.5.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix C.

3.5.7 Duty Cycle

Please refer to Appendix D.

3.5.8 Test Result of Radiated Spurious Emission (30MHz ~ 10th Harmonic or 40GHz, whichever is lower)

Please refer to Appendix C.

3.6 AC Conducted Emission Measurement

3.6.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dBμV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.

3.6.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

3.6.3 Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.

3.6.4 Test Setup



AMN = Artificial mains network (LISN)
AE = Associated equipment
EUT = Equipment under test
ISN = Impedance stabilization network

3.6.5 Test Result of AC Conducted Emission

Please refer to Appendix B.

3.7 Antenna Requirements

3.7.1 Standard Applicable

If directional gain of transmitting antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the rule.

3.7.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

3.7.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.

4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSV40	101040	10Hz~40GHz	Oct. 11, 2023	Apr. 21, 2024	Oct. 10, 2024	Conducted (TH01-KS)
Pulse Power Senor	Anritsu	MA2411B	0917070	300MHz~40GHz	Jan. 02, 2024	Apr. 21, 2024	Jan. 01, 2025	Conducted (TH01-KS)
Power Meter	Anritsu	ML2495A	1005002	50MHz Bandwidth	Jan. 02, 2024	Apr. 21, 2024	Jan. 01, 2025	Conducted (TH01-KS)
EMI Test Receiver	Keysight	N9038A	MY56400023	3Hz~8.5GHz;Max 30dBm	Jan. 04, 2024	Jun. 13, 2024	Jan. 03, 2025	Radiation (03CH08-KS)
Spectrum Analyzer	R&S	FSV40	101932	10kHz~40GHz; Max 30dBm	Oct. 10, 2023	Jun. 13, 2024	Oct. 09, 2024	Radiation (03CH08-KS)
Loop Antenna	R&S	HFH2-Z2E	101125	9kHz~30MHz	Oct. 10, 2023	Jun. 13, 2024	Oct. 09, 2024	Radiation (03CH08-KS)
Bilog Antenna	TESEQ& VGT	CBL 61110	59915	30MHz-1GHz	Aug. 12, 2023	Jun. 13, 2024	Aug. 11, 2024	Radiation (03CH08-KS)
Double Ridge Horn Antenna	ETS-Lindgren	3117	75959	1GHz~18GHz	Mar. 01, 2024	Jun. 13, 2024	Feb. 28, 2025	Radiation (03CH08-KS)
SHF-EHF Horn	Com-power	AH-840	101070	18GHz~40GHz	Jan. 05, 2024	Jun. 13, 2024	Jan. 04, 2025	Radiation (03CH08-KS)
Amplifier	SONOMA	310N	413741	9KHz-1GHz	Jan. 05, 2024	Jun. 13, 2024	Jan. 04, 2025	Radiation (03CH08-KS)
high gain Amplifier	EM	EM01G18GA	060845	1Ghz-18Ghz	Jan. 05, 2024	Jun. 13, 2024	Jan. 04, 2025	Radiation (03CH08-KS)
Amplifier	EM	EM01G18GA	060834	1Ghz-18Ghz	Oct. 10, 2023	Jun. 13, 2024	Oct. 09, 2024	Radiation (03CH08-KS)
Amplifier	MITEQ	EM18G40GGA	060728	18~40GHz	Jan. 04, 2024	Jun. 13, 2024	Jan. 03, 2025	Radiation (03CH08-KS)
AC Power Source	Chroma	61601	616010002473	N/A	NCR	Jun. 13, 2024	NCR	Radiation (03CH08-KS)
Turn Table	EM	EM 1000-T	N/A	0~360 degree	NCR	Jun. 13, 2024	NCR	Radiation (03CH08-KS)
Antenna Mast	EM	EM 1000-A	N/A	1 m~4 m	NCR	Jun. 13, 2024	NCR	Radiation (03CH08-KS)
EMI Receiver	R&S	ESCI7	100768	9kHz~7GHz;	Apr 18, 2024	Jun. 29, 2024	Apr 17, 2025	Conduction (CO01-KS)
AC LISN (for auxiliary equipment)	MessTec	AN3016	060103	9kHz~30MHz	Oct. 11, 2023	Jun. 29, 2024	Oct. 10, 2024	Conduction (CO01-KS)
AC LISN	MessTec	AN3016	060105	9kHz~30MHz	Apr 18, 2024	Jun. 29, 2024	Apr 17, 2025	Conduction (CO01-KS)
AC Power Source	Chroma	61602	ABP000000811	AC 0V~300V, 45Hz~1000Hz	Oct. 11, 2023	Jun. 29, 2024	Oct. 10, 2024	Conduction (CO01-KS)

NCR: No Calibration Required

5 Measurement Uncertainty

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI 63.10-2013. All the measurement uncertainty value were shown with a coverage K=2 to indicate 95% level of confidence. The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be compared directly to specified limit to determine compliance.

Uncertainty of Conducted Measurement

Conducted Spurious Emission & Bandedge	**±2.26 dB**
Occupied Channel Bandwidth	**±0.1%**
Conducted Power	**±0.46 dB**
Conducted Power Spectral Density	**±0.88 dB**
Frequency	**±0.4 Hz**

Uncertainty of AC Conducted Emission Measurement (0.15 MHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	**2.84 dB**

Uncertainty of Radiated Emission Measurement (9 KHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	**3.30 dB**

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	**6.04 dB**

Uncertainty of Radiated Emission Measurement (1 GHz ~ 18 GHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	**5.26 dB**

Uncertainty of Radiated Emission Measurement (18 GHz ~ 40 GHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	**5.04 dB**

---------- THE END ----------

Appendix A. Conducted Test Results

Ambient Condition: 25 ℃, 45 %RH	
Test Date: 2024.4.21	**Test Engineer:** Jiang Jun

<BLE_Ant.1/2>

DTS Bandwidth

Test Result

TestMode	Antenna	Freq(MHz)	DTS BW [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
BLE_1M	Ant1	2402	0.68	2401.66	2402.34	0.5	PASS
	Ant2	2402	0.68	2401.66	2402.34	0.5	PASS
	Ant1	2440	0.68	2439.66	2440.34	0.5	PASS
	Ant2	2440	0.68	2439.66	2440.34	0.5	PASS
	Ant1	2480	0.69	2479.66	2480.35	0.5	PASS
	Ant2	2480	0.68	2479.66	2480.35	0.5	PASS
BLE_2M	Ant1	2402	1.16	2401.43	2402.59	0.5	PASS
	Ant2	2402	1.16	2401.43	2402.59	0.5	PASS
	Ant1	2440	1.16	2439.44	2440.59	0.5	PASS
	Ant2	2440	1.16	2439.43	2440.59	0.5	PASS
	Ant1	2480	1.16	2479.43	2480.59	0.5	PASS
	Ant2	2480	1.15	2479.44	2480.59	0.5	PASS

Test Graphs

BLE_1M_Ant1_2402



BLE_1M_Ant2_2402



BLE_1M_Ant1_2440



BLE_1M_Ant2_2440



BLE_1M_Ant1_2480



BLE_1M_Ant2_2480



BLE_2M_Ant1_2402



BLE_2M_Ant2_2402



BLE_2M_Ant1_2440



BLE_2M_Ant2_2440



BLE_2M_Ant1_2480



Date: 21.APR.2024 10:10:47

BLE_2M_Ant2_2480



Date: 21.APR.2024 10:23:19

Occupied Channel Bandwidth

Test Result

TestMode	Antenna	Freq(MHz)	OCB [MHz]	FL[MHz]	FH[MHz]
BLE_1M	Ant1	2402	1.027	2401.5005	2402.5275
	Ant2	2402	1.023	2401.5005	2402.5235
	Ant1	2440	1.023	2439.5005	2440.5235
	Ant2	2440	1.027	2439.5005	2440.5275
	Ant1	2480	1.027	2479.5005	2480.5275
	Ant2	2480	1.027	2479.5005	2480.5275
BLE_2M	Ant1	2402	2.038	2401.0050	2403.0430
	Ant2	2402	2.038	2401.0050	2403.0430
	Ant1	2440	2.038	2439.0050	2441.0430
	Ant2	2440	2.038	2439.0050	2441.0430
	Ant1	2480	2.038	2479.0050	2481.0430
	Ant2	2480	2.038	2479.0050	2481.0430

Test Graphs

BLE_1M_Ant1_2402



BLE_1M_Ant2_2402



BLE_1M_Ant1_2440



BLE_1M_Ant2_2440



BLE_1M_Ant1_2480



BLE_1M_Ant2_2480



BLE_2M_Ant1_2402



BLE_2M_Ant2_2402



BLE_2M_Ant1_2440



BLE_2M_Ant2_2440



BLE_2M_Ant1_2480



BLE_2M_Ant2_2480



Maximum conducted output power

Test Result Peak

TestMode	Antenna	CH.	Peak Conducted Power (dBm)	Conducted Power Limit	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit	Pass/Fail
BLE1M	Ant1	0	3.01	30.00	4.91	7.92	36.00	Pass
		19	3.47	30.00	4.91	8.38	36.00	Pass
		39	3.49	30.00	4.91	8.40	36.00	Pass
BLE2M	Ant1	0	2.87	30.00	4.91	7.78	36.00	Pass
		19	3.49	30.00	4.91	8.40	36.00	Pass
		39	3.53	30.00	4.91	8.44	36.00	Pass
BLE1M	Ant2	0	3.99	30.00	4.03	8.02	36.00	Pass
		19	3.63	30.00	4.03	7.66	36.00	Pass
		39	3.15	30.00	4.03	7.18	36.00	Pass
BLE2M	Ant2	0	3.76	30.00	4.03	7.79	36.00	Pass
		19	3.41	30.00	4.03	7.44	36.00	Pass
		39	3.10	30.00	4.03	7.13	36.00	Pass

Test Result Average (Reference Only)

TestMode	Antenna	CH.	Duty Factor (dB)	Average Conducted Power (dBm)
BLE1M	Ant1	0	2.06	2.95
		19	2.06	3.39
		39	2.06	3.41
BLE2M	Ant1	0	4.74	2.75
		19	4.74	3.12
		39	4.74	3.28
BLE1M	Ant2	0	2.04	3.69
		19	2.04	3.29
		39	2.04	3.05
BLE2M	Ant2	0	4.77	3.51
		19	4.77	3.13
		39	4.77	3.05

Maximum power spectral density

Test Result

TestMode	Antenna	Freq(MHz)	Result[dBm/3kHz]	Limit[dBm/3kHz]	Verdict
BLE_1M	Ant1	2402	-12.26	≤8.00	PASS
	Ant2	2402	-11.67	≤8.00	PASS
	Ant1	2440	-11.70	≤8.00	PASS
	Ant2	2440	-12.11	≤8.00	PASS
	Ant1	2480	-11.66	≤8.00	PASS
	Ant2	2480	-12.24	≤8.00	PASS
BLE_2M	Ant1	2402	-14.46	≤8.00	PASS
	Ant2	2402	-13.87	≤8.00	PASS
	Ant1	2440	-13.81	≤8.00	PASS
	Ant2	2440	-14.26	≤8.00	PASS
	Ant1	2480	-13.82	≤8.00	PASS
	Ant2	2480	-14.43	≤8.00	PASS

Test Graphs

BLE_1M_Ant1_2402



BLE_1M_Ant2_2402



BLE_1M_Ant1_2440



BLE_1M_Ant2_2440



BLE_1M_Ant1_2480



BLE_1M_Ant2_2480



BLE_2M_Ant1_2402



BLE_2M_Ant2_2402



BLE_2M_Ant1_2440



BLE_2M_Ant2_2440



BLE_2M_Ant1_2480



BLE_2M_Ant2_2480



Reference level measurement

Test Result

TestMode	Antenna	Freq(MHz)	Max.Point[MHz]	Result[dBm/100KHz]
BLE_1M	Ant1	2402	2402.00	2.40
	Ant2	2402	2402.00	3.28
	Ant1	2440	2440.00	2.99
	Ant2	2440	2440.00	2.55
	Ant1	2480	2480.00	2.98
	Ant2	2480	2480.00	2.46
BLE_2M	Ant1	2402	2402.01	2.42
	Ant2	2402	2402.01	3.07
	Ant1	2440	2440.01	3.05
	Ant2	2440	2440.01	2.57
	Ant1	2480	2480.01	3.04
	Ant2	2480	2480.00	2.50

Test Graphs

BLE_1M_Ant1_2402



BLE_1M_Ant2_2402



BLE_1M_Ant1_2440



BLE_1M_Ant2_2440



BLE_1M_Ant1_2480



BLE_1M_Ant2_2480



BLE_2M_Ant1_2402



BLE_2M_Ant2_2402



BLE_2M_Ant1_2440



BLE_2M_Ant2_2440



BLE_2M_Ant1_2480



BLE_2M_Ant2_2480



Band edge measurements

Test Result

TestMode	Antenna	ChName	Freq(MHz)	RefLevel[dBm /100KHz]	Result[dBm /100KHz]	Limit[dBm /100KHz]	Verdict
BLE_1M	Ant1	Low	2402	2.40	-43.97	≤-17.6	PASS
	Ant2	Low	2402	3.28	-43.76	≤-16.72	PASS
	Ant1	High	2480	2.98	-43.37	≤-17.02	PASS
	Ant2	High	2480	2.46	-43.61	≤-17.54	PASS
BLE_2M	Ant1	Low	2402	2.42	-30.97	≤-17.58	PASS
	Ant2	Low	2402	3.07	-30.4	≤-16.93	PASS
	Ant1	High	2480	3.04	-42.56	≤-16.96	PASS
	Ant2	High	2480	2.50	-43.58	≤-17.5	PASS

Test Graphs

BLE_1M_Ant1_Low_2402



BLE_1M_Ant2_Low_2402



BLE_1M_Ant1_High_2480



BLE_1M_Ant2_High_2480



BLE_2M_Ant1_Low_2402



BLE_2M_Ant2_Low_2402



BLE_2M_Ant1_High_2480



BLE_2M_Ant2_High_2480



Conducted Spurious Emission

Test Result

TestMode	Antenna	Freq(MHz)	FreqRange [MHz]	RefLevel [dBm/100KHz]	Result [dBm/100KHz]	Limit [dBm/100KHz]	Verdict
BLE_1M	Ant1	2402	30~1000	2.40	-44.96	≤-17.6	PASS
			1000~26500	2.40	-37.18	≤-17.6	PASS
	Ant2	2402	30~1000	3.28	-45.62	≤-16.72	PASS
			1000~26500	3.28	-36.36	≤-16.72	PASS
	Ant1	2440	30~1000	2.99	-45.35	≤-17.01	PASS
			1000~26500	2.99	-36.03	≤-17.01	PASS
	Ant2	2440	30~1000	2.55	-45.6	≤-17.45	PASS
			1000~26500	2.55	-36.48	≤-17.45	PASS
	Ant1	2480	30~1000	2.98	-44.93	≤-17.02	PASS
			1000~26500	2.98	-36.31	≤-17.02	PASS
	Ant2	2480	30~1000	2.46	-45.16	≤-17.54	PASS
			1000~26500	2.46	-36.88	≤-17.54	PASS
BLE_2M	Ant1	2402	30~1000	2.42	-45.66	≤-17.58	PASS
			1000~26500	2.42	-36.52	≤-17.58	PASS
	Ant2	2402	30~1000	3.07	-45.52	≤-16.93	PASS
			1000~26500	3.07	-35.02	≤-16.93	PASS
	Ant1	2440	30~1000	3.05	-45.87	≤-16.95	PASS
			1000~26500	3.05	-36.85	≤-16.95	PASS
	Ant2	2440	30~1000	2.57	-45.83	≤-17.43	PASS
			1000~26500	2.57	-35.6	≤-17.43	PASS
	Ant1	2480	30~1000	3.04	-44.92	≤-16.96	PASS
			1000~26500	3.04	-36.38	≤-16.96	PASS
	Ant2	2480	30~1000	2.50	-44.93	≤-17.5	PASS
			1000~26500	2.50	-36.92	≤-17.5	PASS

Test Graphs

BLE_1M_Ant1_2402_30~1000



BLE_1M_Ant1_2402_1000~26500



BLE_1M_Ant2_2402_30~1000



BLE_1M_Ant2_2402_1000~26500



BLE_1M_Ant1_2440_30~1000



BLE_1M_Ant1_2440_1000~26500



BLE_1M_Ant2_2440_30~1000



BLE_1M_Ant2_2440_1000~26500



BLE_1M_Ant1_2480_30~1000



BLE_1M_Ant1_2480_1000~26500



BLE_1M_Ant2_2480_30~1000



BLE_1M_Ant2_2480_1000~26500



BLE_2M_Ant1_2402_30~1000



BLE_2M_Ant1_2402_1000~26500



BLE_2M_Ant2_2402_30~1000



BLE_2M_Ant2_2402_1000~26500



BLE_2M_Ant1_2440_30~1000



BLE_2M_Ant1_2440_1000~26500



BLE_2M_Ant2_2440_30~1000



BLE_2M_Ant2_2440_1000~26500



BLE_2M_Ant1_2480_30~1000



BLE_2M_Ant1_2480_1000~26500



BLE_2M_Ant2_2480_30~1000



BLE_2M_Ant2_2480_1000~26500



Appendix B. AC Conducted Emission Test Results

Test Engineer :	Amos	**Temperature :**	25.3~26.2℃
		Relative Humidity :	38~40%
Test Voltage :	120Vac / 60Hz	**Phase :**	Line
Remark :	All emissions not reported here are more than 10 dB below the prescribed limit.		



Site : CO01-KS
Condition : 15C RSS247-QP LISN-060105-L 2024 LINE

	Freq MHz	Level dBuV	Over Limit dB	Limit Line dBuV	Read Level dBuV	LISN Factor dB	Cable Loss dB	Remark
1	0.171	41.02	-23.88	64.90	30.50	0.10	10.42	QP
2	0.171	28.72	-26.18	54.90	18.20	0.10	10.42	Average
3	0.198	41.99	-21.72	63.71	31.50	0.08	10.41	QP
4	0.198	30.09	-23.62	53.71	19.60	0.08	10.41	Average
5	0.299	38.62	-21.66	60.28	28.20	0.09	10.33	QP
6	0.299	33.22	-17.06	50.28	22.80	0.09	10.33	Average
7	0.433	35.41	-21.79	57.20	25.20	-0.05	10.26	QP
8	0.433	29.11	-18.09	47.20	18.90	-0.05	10.26	Average
9	0.592	31.55	-24.45	56.00	21.50	-0.13	10.18	QP
10	0.592	24.25	-21.75	46.00	14.20	-0.13	10.18	Average
11	0.904	35.83	-20.17	56.00	25.90	-0.17	10.10	QP
12 *	0.904	33.03	-12.97	46.00	23.10	-0.17	10.10	Average

Test Engineer :	Amos	**Temperature :**	25.3~26.2℃
		Relative Humidity :	38~40%
Test Voltage :	120Vac / 60Hz	**Phase :**	Neutral
Remark :	All emissions not reported here are more than 10 dB below the prescribed limit.		



Site : CO01-KS
Condition : 15C RSS247-QP LISN-060105-N 2024 NEUTRAL

	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.191	42.84	-21.14	63.98	32.30	0.13	10.41	QP
2	0.191	32.14	-21.84	53.98	21.60	0.13	10.41	Average
3	0.248	37.16	-24.66	61.82	26.79	0.00	10.37	QP
4	0.248	27.56	-24.26	51.82	17.19	0.00	10.37	Average
5	0.433	33.62	-23.58	57.20	23.50	-0.14	10.26	QP
6	0.433	27.32	-19.88	47.20	17.20	-0.14	10.26	Average
7	0.654	30.60	-25.40	56.00	20.60	-0.16	10.16	QP
8	0.654	23.50	-22.50	46.00	13.50	-0.16	10.16	Average
9	0.899	37.12	-18.88	56.00	27.20	-0.18	10.10	QP
10 *	0.899	34.82	-11.18	46.00	24.90	-0.18	10.10	Average
11	1.503	36.50	-19.50	56.00	26.61	-0.19	10.08	QP
12	1.503	33.70	-12.30	46.00	23.81	-0.19	10.08	Average

Note:

1. Level(dBμV) = Read Level(dBμV) + LISN Factor(dB) + Cable Loss(dB)
2. Over Limit(dB) = Level(dBμV) – Limit Line(dBμV)

Appendix C. Radiated Spurious Emission Test Data

Test Engineer :	Koi Ji	Relative Humidity :	41~42%
		Temperature :	22 ~23℃

Radiated Spurious Emission Test Modes

Mode	Band (MHz)	Antenna	Modulation	Channel	Frequency	Data Rate	RU	Remark
Mode 7	2400-2483.5	1	Bluetooth-LE	00	2402	1Mbps	-	-
Mode 8	2400-2483.5	1	Bluetooth-LE	19	2440	1Mbps	-	-
Mode 9	2400-2483.5	1	Bluetooth-LE	39	2480	1Mbps	-	-
Mode 10	2400-2483.5	1	Bluetooth-LE	00	2402	2Mbps	-	-
Mode 11	2400-2483.5	1	Bluetooth-LE	19	2440	2Mbps	-	-
Mode 12	2400-2483.5	1	Bluetooth-LE	39	2480	2Mbps	-	-
Mode 13	2400-2483.5	2	Bluetooth-LE	00	2402	1Mbps	-	-
Mode 14	2400-2483.5	2	Bluetooth-LE	19	2440	1Mbps	-	-
Mode 15	2400-2483.5	2	Bluetooth-LE	39	2480	1Mbps	-	-
Mode 16	2400-2483.5	2	Bluetooth-LE	00	2402	2Mbps	-	-
Mode 17	2400-2483.5	2	Bluetooth-LE	19	2440	2Mbps	-	-
Mode 18	2400-2483.5	2	Bluetooth-LE	39	2480	2Mbps	-	-

Co-location Mode

Mode	Band (MHz)	Antenna	Modulation	Channel	Frequency	Data Rate	RU	Remark
48	2400-2483.5	1	Bluetooth-LE	39	2480	2Mbps	-	-
	2400-2483.5	3	Bluetooth-LE	39	2480	2Mbps	-	-

Summary of each worse mode

Mode	Modulation	Ch.	Freq. (MHz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Pol.	Peak Avg.	Result	Remark
7	Bluetooth-LE	00	2388.52	44.40	54.00	-9.60	V	AVERAGE	Pass	Band Edge
	Bluetooth-LE	00	4995.00	43.09	54.00	-10.91	V	AVERAGE	Pass	Harmonic
8	Bluetooth-LE	19	-	-	-	-	-	-	-	Band Edge
	Bluetooth-LE	19	4990.00	43.13	54.00	-10.87	V	AVERAGE	Pass	Harmonic
9	Bluetooth-LE	39	2493.64	44.51	54.00	-9.49	H	AVERAGE	Pass	Band Edge
	Bluetooth-LE	39	4996.00	43.07	54.00	-10.93	V	AVERAGE	Pass	Harmonic
10	Bluetooth-LE	00	2366.55	45.27	54.00	-8.73	H	AVERAGE	Pass	Band Edge
	Bluetooth-LE	00	4999.00	43.49	54.00	-10.51	V	AVERAGE	Pass	Harmonic
11	Bluetooth-LE	19	-	-	-	-	-	-	-	Band Edge
	Bluetooth-LE	19	4989.00	43.16	54.00	-10.84	V	AVERAGE	Pass	Harmonic
12	Bluetooth-LE	39	2483.50	46.19	54.00	-7.81	H	AVERAGE	Pass	Band Edge
	Bluetooth-LE	39	4996.00	43.68	54.00	-10.32	V	AVERAGE	Pass	Harmonic
13	Bluetooth-LE	00	2389.56	44.66	54.00	-9.34	V	AVERAGE	Pass	Band Edge
	Bluetooth-LE	00	4999.00	43.43	54.00	-10.57	V	AVERAGE	Pass	Harmonic
14	Bluetooth-LE	19	-	-	-	-	-	-	-	Band Edge
	Bluetooth-LE	19	4999.00	43.81	54.00	-10.19	V	AVERAGE	Pass	Harmonic
15	Bluetooth-LE	39	2486.26	44.53	54.00	-9.47	H	AVERAGE	Pass	Band Edge
	Bluetooth-LE	39	4993.00	43.37	54.00	-10.63	V	AVERAGE	Pass	Harmonic
16	Bluetooth-LE	00	2348.74	45.45	54.00	-8.55	V	AVERAGE	Pass	Band Edge
	Bluetooth-LE	00	4993.00	43.53	54.00	-10.47	V	AVERAGE	Pass	Harmonic
17	Bluetooth-LE	19	-	-	-	-	-	-	-	Band Edge
	Bluetooth-LE	19	4990.00	44.07	54.00	-9.93	V	AVERAGE	Pass	Harmonic
18	Bluetooth-LE	39	2494.12	45.32	54.00	-8.68	V	AVERAGE	Pass	Band Edge
	Bluetooth-LE	39	4996.00	43.39	54.00	-10.61	V	AVERAGE	Pass	Harmonic

Co-location Mode

Mode	Modulation	Ch.	Freq. (MHz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Pol.	Peak Avg.	Result	Remark
48	Bluetooth-LE	39	2483.56	46.34	54.00	-7.66	V	AVERAGE	Pass	Band Edge
48	Bluetooth-LE	39	4992.00	44.45	54.00	-9.55	H	AVERAGE	Pass	Harmonic
48	Bluetooth-LE	39	2483.50	45.27	54.00	-8.73	V	AVERAGE	Pass	Band Edge
48	Bluetooth-LE	39	4981.00	44.11	54.00	-9.89	H	AVERAGE	Pass	Harmonic

Mode	7	
	Band Edge	
	2400-2483.5_Bluetooth-LE _CH00_2402MHz	
ANT	1	
Pol.	Horizontal	Fundamental
Peak	 Limit Read Ant Cable Preamp Aux APos TPos Freq Level Line Margin Level Factor Loss Factor Factor Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2334.70 55.31 74.00 -18.69 39.47 32.18 8.60 30.94 6.00 299 116 PEAK	 Limit Read Ant Cable Preamp Aux APos TPos Freq Level Line Margin Level Factor Loss Factor Factor Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2402.00 98.84 ------ ------ 82.57 32.40 8.80 30.93 6.00 299 116 PEAK
Avg	 Limit Read Ant Cable Preamp Aux APos TPos Freq Level Line Margin Level Factor Loss Factor Factor Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2379.29 44.39 54.00 -9.61 28.21 32.36 8.75 30.93 6.00 299 116 AVERAGE	 Limit Read Ant Cable Preamp Aux APos TPos Freq Level Line Margin Level Factor Loss Factor Factor Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2402.00 98.06 ------ ------ 81.79 32.40 8.80 30.93 6.00 299 116 AVERAGE

Mode	7	
	Band Edge	
	2400-2483.5_Bluetooth-LE _CH00_2402MHz	
ANT	1	
Pol.	Vertical	Fundamental
Peak	 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2358.62 55.16 74.00 -18.84 39.08 32.32 8.70 30.94 6.00 120 229 PEAK	 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2402.00 99.29 ------ ------ 83.02 32.40 8.80 30.93 6.00 120 229 PEAK
Avg	 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2388.52 44.40 54.00 -9.60 28.18 32.38 8.77 30.93 6.00 120 229 AVERAGE	 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2402.00 98.15 ------ ------ 81.88 32.40 8.80 30.93 6.00 120 229 AVERAGE

Mode	7	
	Harmonic	
	2400-2483.5_Bluetooth-LE _CH00_2402MHz	
ANT	1	
Pol.	Horizontal	Vertical
Peak Avg	 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 4804.00 39.86 74.00 -34.14 58.72 34.29 12.54 65.69 0.00 -- -- PEAK 2 4989.00 52.28 74.00 -21.72 71.29 34.07 12.26 65.34 0.00 100 305 PEAK 3 4989.00 41.78 54.00 -12.22 60.79 34.07 12.26 65.34 0.00 100 305 AVERAGE	 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 4804.00 40.26 74.00 -33.74 59.12 34.29 12.54 65.69 0.00 -- -- PEAK 2 4995.00 53.90 74.00 -20.10 72.90 34.03 12.30 65.33 0.00 100 310 PEAK 3 4995.00 43.09 54.00 -10.91 62.09 34.03 12.30 65.33 0.00 100 310 AVERAGE

Mode	8	
	Harmonic	
	2400-2483.5_Bluetooth-LE _CH19_2440MHz	
ANT	1	
Pol.	Horizontal	Vertical
Peak Avg	 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 4880.00 39.63 74.00 -34.37 58.91 34.20 12.07 65.55 0.00 -- -- PEAK 2 4983.00 52.49 74.00 -21.51 71.53 34.10 12.22 65.36 0.00 100 300 PEAK 3 4983.00 41.67 54.00 -12.33 60.71 34.10 12.22 65.36 0.00 100 300 AVERAGE 4 7320.00 44.50 74.00 -29.50 58.57 35.80 14.98 64.85 0.00 -- -- PEAK	 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 4880.00 39.24 74.00 -34.76 58.52 34.20 12.07 65.55 0.00 -- -- PEAK 2 4990.00 53.57 74.00 -20.43 72.58 34.06 12.27 65.34 0.00 100 313 PEAK 3 4990.00 43.13 54.00 -10.87 62.14 34.06 12.27 65.34 0.00 100 313 AVERAGE 4 7320.00 42.46 74.00 -31.54 56.53 35.80 14.98 64.85 0.00 -- -- PEAK

Mode	9	
	Band Edge	
	2400-2483.5_Bluetooth-LE _CH39_2480MHz	
ANT	1	
Pol.	Horizontal	Fundamental
Peak	 Limit Read Ant Cable Preamp Aux APos TPos Freq Level Line Margin Level Factor Loss Factor Factor Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2492.38 55.05 74.00 -18.95 38.75 32.40 8.87 30.97 6.00 101 138 PEAK	 Limit Read Ant Cable Preamp Aux APos TPos Freq Level Line Margin Level Factor Loss Factor Factor Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2480.00 97.44 ------ ------ 81.13 32.40 8.88 30.97 6.00 101 138 PEAK
Avg	 Limit Read Ant Cable Preamp Aux APos TPos Freq Level Line Margin Level Factor Loss Factor Factor Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2493.64 44.51 54.00 -9.49 28.21 32.40 8.87 30.97 6.00 101 138 AVERAGE	 Limit Read Ant Cable Preamp Aux APos TPos Freq Level Line Margin Level Factor Loss Factor Factor Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2480.00 96.49 ------ ------ 80.18 32.40 8.88 30.97 6.00 101 138 AVERAGE

Mode	9	
	Band Edge	
	2400-2483.5_Bluetooth-LE _CH39_2480MHz	
ANT	1	
Pol.	Vertical	Fundamental
Peak	 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2494.60 55.36 74.00 -18.64 39.06 32.40 8.87 30.97 6.00 100 129 PEAK	 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2480.00 92.68 ------ ------ 76.37 32.40 8.88 30.97 6.00 100 129 PEAK
Avg	 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2496.10 44.45 54.00 -9.55 28.15 32.40 8.87 30.97 6.00 100 129 AVERAGE	 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2480.00 91.40 ------ ------ 75.09 32.40 8.88 30.97 6.00 100 129 AVERAGE

Mode	9	
	Harmonic	
	2400-2483.5_Bluetooth-LE _CH39_2480MHz	
ANT	1	
Pol.	Horizontal	Vertical
Peak Avg	 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 4960.00 41.00 74.00 -33.00 60.09 34.24 12.07 65.40 0.00 -- -- PEAK 2 4984.00 52.48 74.00 -21.52 71.50 34.10 12.23 65.35 0.00 100 301 PEAK 3 4984.00 41.64 54.00 -12.36 60.66 34.10 12.23 65.35 0.00 100 301 AVERAGE 4 7440.00 43.50 74.00 -30.50 57.68 35.80 15.21 65.19 0.00 -- -- PEAK	 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 4960.00 40.43 74.00 -33.57 59.52 34.24 12.07 65.40 0.00 -- -- PEAK 2 4996.00 53.87 74.00 -20.13 72.88 34.02 12.30 65.33 0.00 100 307 PEAK 3 4996.00 43.07 54.00 -10.93 62.08 34.02 12.30 65.33 0.00 100 307 AVERAGE 4 7440.00 42.80 74.00 -31.20 56.98 35.80 15.21 65.19 0.00 -- -- PEAK