



Prüfbericht-Nr.: <i>Test Report No.:</i>	50113475 001	Auftrags-Nr.: <i>Order No.:</i>	114071117	Seite 1 von 52 <i>Page 1 of 52</i>
Kunden-Referenz-Nr.: <i>Client Reference No.:</i>	N/A	Auftragsdatum: <i>Order date:</i>	9-Nov-2017	
Auftraggeber: <i>Client:</i>	Dexatek Technology, 15F.,NO.81,Sec.1,Sintai 5th Rd., Sijhih Dist., New Taipei City, Taiwan 221			
Prüfgegenstand: <i>Test item:</i>	Smart IP Cam			
Bezeichnung / Typ-Nr.: <i>Identification / Type No.:</i>	SA-7510			
Auftrags-Inhalt: <i>Order content:</i>	FCC Part 15C Test report (WiFi)			
Prüfgrundlage: <i>Test specification:</i>	FCC 47CFR Part 15: Subpart C Section 15.247 FCC 47CFR Part 2: Subpart J Section 2.1091			
Wareneingangsdatum: <i>Date of receipt:</i>	20-Nov-2017			
Prüfmuster-Nr.: <i>Test sample No.:</i>	A000657757-001 A000657757-002			
Prüfzeitraum: <i>Testing period:</i>	22-Nov-2017 - 30-Nov-2017			
Ort der Prüfung: <i>Place of testing:</i>	EMC Laboratory Taipei			
Prüflaboratorium: <i>Testing laboratory:</i>	TUV Rheinland Taiwan Ltd.			
Prüfergebnis*: <i>Test result*:</i>	Pass			
Report date / tested by:		kontrolliert von / reviewed by:		
2018-01-23 Sam C.J. Kuo/Engineer		2018-01-23 Arvin Ho/Vice General Manager		
Datum <i>Date</i>	Name / Stellung <i>Name / Position</i>	Unterschrift <i>Signature</i>	Datum <i>Date</i>	Name / Stellung <i>Name / Position</i>
				
Sonstiges / Other:				
Zustand des Prüfgegenstandes bei Anlieferung: <i>Condition of the test item at delivery:</i>		Prüfmuster vollständig und unbeschädigt <i>Test item complete and undamaged</i>		
* Legende: 1 = sehr gut 2 = gut 3 = befriedigend 4 = ausreichend 5 = mangelhaft P(ass) = entspricht o.g. Prüfgrundlage(n) F(ail) = entspricht nicht o.g. Prüfgrundlage(n) N/A = nicht anwendbar N/T = nicht getestet Legend: 1 = very good 2 = good 3 = satisfactory 4 = sufficient 5 = poor P(ass) = passed a.m. test specification(s) F(ail) = failed a.m. test specification(s) N/A = not applicable N/T = not tested				
Dieser Prüfbericht bezieht sich nur auf das o.g. Prüfmuster und darf ohne Genehmigung der Prüfstelle nicht auszugsweise vervielfältigt werden. Dieser Bericht berechtigt nicht zur Verwendung eines Prüfzeichens. <i>This test report only relates to the a. m. test sample. Without permission of the test center this test report is not permitted to be duplicated in extracts. This test report does not entitle to carry any test mark.</i>				

TEST SUMMARY

5.1.1 ANTENNA REQUIREMENT

RESULT: Passed

5.1.2 PEAK OUTPUT POWER

RESULT: Passed

5.1.3 6dB BANDWIDTH AND 99% BANDWIDTH

RESULT: Passed

5.1.4 POWER DENSITY

RESULT: Passed

5.1.5 CONDUCTED SPURIOUS EMISSIONS AND FREQUENCY BAND EDGE MEASURED IN 100kHz BANDWIDTH

RESULT: Passed

5.1.6 SPURIOUS EMISSION

RESULT: Passed

5.2.1 MAINS CONDUCTED EMISSIONS

RESULT: Passed

6.1.1 ELECTROMAGNETIC FIELDS

RESULT: Passed

Contents

1.	GENERAL REMARKS	5
1.1	COMPLEMENTARY MATERIALS.....	5
2.	TEST SITES	6
2.1	TEST LABORATORY	6
2.2	TEST FACILITIES	6
2.3	LIST OF TEST AND MEASUREMENT INSTRUMENTS.....	7
2.4	TRACEABILITY	8
2.5	CALIBRATION	8
2.6	MEASUREMENT UNCERTAINTY	8
3.	GENERAL PRODUCT INFORMATION.....	9
3.1	PRODUCT FUNCTION AND INTENDED USE	9
3.2	SYSTEM DETAILS AND RATINGS.....	9
3.3	INDEPENDENT OPERATION MODES.....	10
3.4	NOISE GENERATING AND NOISE SUPPRESSING PARTS	10
3.5	SUBMITTED DOCUMENTS.....	10
4.	TEST SET-UP AND OPERATION MODES.....	11
4.1	PRINCIPLE OF CONFIGURATION SELECTION	11
4.2	TEST OPERATION AND TEST SOFTWARE.....	11
4.3	ADDITIONAL ACCESSORIES AND AUXILIARY EQUIPMENT	12
4.4	COUNTERMEASURES TO ACHIEVE EMC COMPLIANCE.....	12
4.5	TEST SETUP DIAGRAM	12
5.	TEST RESULTS	14
5.1	TRANSMITTER REQUIREMENT & TEST SUITES.....	14
5.1.1	Antenna Requirement	14
5.1.2	Peak Output Power	15
5.1.3	6dB Bandwidth and 99% Bandwidth.....	17
5.1.4	Power Density	26
5.1.5	Conducted spurious emissions and Frequency Band Edge measured in 100kHz Bandwidth.....	34
5.1.6	Spurious Emission	45
5.2	MAINS EMISSIONS.....	46
5.2.1	Mains Conducted Emissions.....	46
6.	SAFETY HUMAN EXPOSURE	47

6.1	RADIO FREQUENCY EXPOSURE COMPLIANCE	47
6.1.1	<i>Electromagnetic Fields.....</i>	<i>47</i>
	PHOTOGRAPHS OF THE TEST SET-UP	48
7.	LIST OF TABLES	52
8.	LIST OF PHOTOGRAPHS.....	52

1. General Remarks

1.1 Complementary Materials

The following attachments are integral parts of this test report:

Appendix P: Photo Documentation

(File Name: 50113475APPENDIXP)

Appendix D: Test Result of Radiated Emissions

(File Name: 50113475APPENDIXD)

Test Specifications

The following standards were applied (in bold: product standards, otherwise: basic standards).

Table 1: Applied Standard and Test Levels

Radio
FCC 47 CFR Part 15: Subpart C Section 15.247 FCC 47 CFR Part 2: Subpart J Section 2.1091 ANSI C63.10:2013 KDB558074 D01 DTS Meas Guidance v03r05 KDB447498 D01 General RF Exposure Guidance v06

2. Test Sites

2.1 Test Laboratory

TUV Rheinland Taiwan Ltd.
Taichung Branch Office

No.9, Lane 36, Minsheng Rd., Sec. 3, Daya District,
Taichung City 428
Taiwan (R.O.C.)

2.2 Test Facilities

TUV Rheinland Taiwan Ltd.
Taipei Office

11F. No.758, Sec. 4, Bade Rd., Songshan Dist.
Taipei City 105
Taiwan (R.O.C.)

FCC RegistrationNo.: 340738
IC Canada Registration No.: 9465A-1
TAF Accredited NCC Test Lab. No.:0759
TAF ISO17025 Certification effective periods: 2016-Jul-1st to 2019-Jun-30th



Testing Laboratory
0759

2.3 List of Test and Measurement Instruments

Table 2: List of Test and Measurement Equipment

Kind of Equipment	Manu-facturer	Type	S/N	Last Calibration	Next Calibration
Test Software	Farad	EZ_EMC	Ver. TUV3A1	N/A	N/A
EMI Test Receiver	R&S	ESCI 7	100797	2016/12/30	2017/12/30
Spectrum Analyzer	R&S	FSV 40	100921	2017/05/02	2018/05/01
Spectrum Analyzer	Agilent	N9010A	MY53470241	2017/05/23	2018/05/22
Preamplifier (30MHz -1GHz)	HP	8447D	2944A06641	2016/12/28	2017/12/28
Preamplifier (18 GHz -40 GHz)	COM-POWER	PAM-840	461257	2016/12/01	2017/12/01
Pre-Amplifier (1GHz~18GHz)	EM Electronics	EM01G18G	60649	2017/07/28	2018/07/28
Bilog Antenna	TESEQ	CBL6111D	29804	2017/08/18	2018/08/18
Horn Antenna	ETS-Lindgren	3117	201918	2017/08/18	2018/08/18
Horn Antenna (18GHz~40GHz)	COM-POWER	AH-840	101031	2017/11/28	2018/11/28
Loop Antenna	Schwarzbeck	FMZB 1513	1513-076	2017/06/14	2018/06/14
EMI Test Receiver	R&S	ESCI7	100797	2016/12/30	2017/12/30
LISN (1 phase)	R&S	ENV216	101243	2017/06/18	2018/06/18
LISN	R&S	ENV216	101262	2017/06/22	2018/06/21

2.4 Traceability

All measurement equipment calibrations are traceable to NML(Taiwan)/NIST(USA) or where calibration is performed outside Taiwan, to equivalent nationally recognized standards organizations.

2.5 Calibration

Equipment requiring calibration is calibrated periodically by the manufacturer or according to manufacturer's specifications. Additionally all equipment is verified for proper performance on a regular basis using in house standards or comparisons.

2.6 Measurement Uncertainty

The estimated combined standard uncertainty for radiated emissions and conducted emissions measurements are $\pm 3\text{dB}$.

Table 3: Emission Measurement Uncertainty

Parameter	Uncertainty
RF power, conducted	$\pm 1.5 \text{ dB}$
Adjacent channel power	$\pm 3 \text{ dB}$
Radiated emission of transmitter, valid up to 26 GHz	$\pm 6 \text{ dB}$
Radiated emission of receiver, valid up to 26 GHz	$\pm 6 \text{ dB}$
Temperature	$\pm 2 \text{ }^{\circ}\text{C}$
Humidity	$\pm 10 \text{ \%}$

3. General Product Information

3.1 Product Function and Intended Use

The EUT is a WiFi Camera. It contains a WiFi/BT compatible module enabling the user to communicate data through a Wireless interface.
For details refer to the User Guide, Data Sheet and Circuit Diagram.

3.2 System Details and Ratings

Table 4: Basic Information of EUT

Item	EUT information
Kind of Equipment	Smart IP Cam
Type Designation	SA-7510
FCC ID	SZY-SA7510

Table 5: Technical Specification of EUT

Technical Specification	Value
Operating Frequencies	2412~2462 MHz
Channel Spacing	5 MHz
Channel number	802.11b/g/n: 11 (2412 MHz ~ 2462 MHz) ; 802.11n : 7 (2422~2452MHz)
Operation Voltage	5Vdc
Modulation	802.11b: DSSS 802.11g/n: OFDM with BPSK, QPSK, QAM
Antenna gain	1.5dBi

3.3 Independent Operation Modes

Basic operation modes are:

- A. Transmitting
 - 1. Low channel
 - 2. Middle channel
 - 3. High channel
- B. Receiving
- C. Standby
- D. Off

3.4 Noise Generating and Noise Suppressing Parts

Refer to the Circuit Diagram.

3.5 Submitted Documents

- | | |
|-------------------------|----------------------|
| - Block Diagram | - Circuit Diagram |
| - PCB Layout | - Instruction Manual |
| - Photo Document | - Rating Label |
| - Technical Description | |

4. Test Set-up and Operation Modes

4.1 Principle of Configuration Selection

The equipment under test (EUT) was configured to measure its maximum power level. The test modes were adapted accordingly in reference to the instructions for use.

4.2 Test Operation and Test Software

Setup for testing: Test samples are provided with a USB interface and can be controlled by terminal.

Terminal, we can order EUT run on the frequency which we want and set up the power at maximum value.

The samples were used as follows:

Conducted: A000657757-001

Radiation: A000657757-001

Full test was applied on all test modes, but only worst case was shown

IEEE 802.11b mode:

Channel Low (2412MHz), Channel Mid (2437MHz) and Channel High (2462MHz) with 1Mbps data rate were chosen for full testing.

IEEE 802.11g mode:

Channel Low (2412MHz), Channel Mid (2437MHz) and Channel High (2462MHz) with 6Mbps data rate were chosen for full testing.

IEEE 802.11n HT 20 mode:

Channel Low (2412MHz), Channel Mid (2437MHz) and Channel High (2462MHz) with 13Mbps data rate were chosen for full testing.

IEEE 802.11n HT 40 MHz mode:

Channel Low (2422MHz), Channel Mid (2442MHz) and Channel High (2452MHz) with 13Mbps data rate were chosen for full testing.

4.3 Accessories and Auxiliary Equipment

The product has been tested together with the following additional accessories:


Description	Manufacturer	Model No.	Serial No.
Notebook(EMC-06)	Lenovo	TP00048A	PB-0F8B2

4.4 Countermeasures to achieve EMC Compliance

The test sample which has been tested contained the noise suppression parts as described in the Constructional Data Form or the Technical Construction File. No additional measures were employed to achieve compliance.

4.5 Test Setup Diagram

Diagram of Measurement Configuration for Radiation Test



Note: Measurements above 1 GHz are done with a table height of 1.5m.

Diagram of Measurement Equipment Configuration for Mains Conduction Measurement (if applicable)





Diagram of Measurement Equipment Configuration for Conducted Transmitter Measurement



5. Test Results

5.1 Transmitter Requirement & Test Suites

5.1.1 Antenna Requirement

RESULT:**Passed**

Test standard	:	LP0002(2016): 3.10.1.3 FCC Part 15.247(b)(4), Part 15.203 and RSS- Gen 8.3
Limit	:	the use of antennas with directional gains that do not exceed 6 dBi

According to the manufacturer declaration, the EUT has an antenna with a directional gain of 1.5 dBi. The antenna is a Chip Antenna soldered to the PCB with no possibility of replacement with a non-approved antenna by the end-user. Therefore, the EUT is considered to comply with this provision.

Refer to EUT photo for details.

5.1.2 Peak Output Power

RESULT:

Passed

Test standard : LP0002(2016): 3.10.1.2
 FCC Part 15.247(b)(3), RSS-247 5.4(4)
 Basic standard : ANSI C63.10:2013, KDB558074
 Limit : 1 Watt
 Kind of test site : Shielded room

Test setup

Test Channel : Low/ Middle/ High
 Operation Mode : A

 Ambient temperature : 22-26 °C
 Relative humidity : 50-65 %
 Atmospheric pressure : 100-103 kPa

Table 6: Test result of Peak Output Power (802.11b)

Channel	Channel Frequency (MHz)	Output Power		Limit
		(dBm)	(W)	(W)
Low Channel	2412	14.63	0.02904	1
Middle Channel	2437	15.14	0.03266	1
High Channel	2462	15.73	0.03741	1

Table 7: Test result of Peak Output Power (802.11g)

Channel	Channel Frequency (MHz)	Output Power		Limit
		(dBm)	(W)	(W)
Low Channel	2412	19.81	0.09572	1
Middle Channel	2437	19.56	0.09036	1
High Channel	2462	18.97	0.07889	1

Table 8: Test result of Peak Output Power (802.11n HT20)

Channel	Channel Frequency (MHz)	Output Power		Limit
		(dBm)	(W)	(W)
Low Channel	2412	19.34	0.08590	1
Middle Channel	2437	19.40	0.08710	1
High Channel	2462	19.00	0.07943	1

Table 9: Test result of Peak Output Power (802.11n HT40)

Channel	Channel Frequency (MHz)	Output Power		Limit
		(dBm)	(W)	(W)
Low Channel	2422	20.35	0.10839	1
Middle Channel	2437	20.11	0.10257	1
High Channel	2452	19.63	0.09183	1

Max Value 108.3927 mW

5.1.3 6dB Bandwidth and 99% Bandwidth

RESULT:**Passed**

Test standard : LP0002(2016): 3.10.1.5
FCC Part 15.247(a)(2), RSS-247 5.2(1)
Basic standard : ANSI C63.10:2013, KDB558074
Kind of test site : Shielded room

Test setup

Test Channel : Low/ Middle/ High
Operation Mode : A

Ambient temperature : 22-26°C
Relative humidity : 50-65%
Atmospheric pressure : 100-103 kPa

Table 10: Test result of 6dB Bandwidth (802.11b)

Channel	Channel Frequency (MHz)	6dB Bandwidth (MHz)	Limit (MHz)	Result
Low Channel	2412	10.08	0.5	Pass
Mid Channel	2437	10.07	0.5	Pass
High Channel	2462	10.08	0.5	Pass

Table 11: Test result of 6dB Bandwidth (802.11g)

Channel	Channel Frequency (MHz)	6dB Bandwidth (MHz)	Limit (MHz)	Result
Low Channel	2412	16.36	0.5	Pass
Mid Channel	2437	16.38	0.5	Pass
High Channel	2462	16.38	0.5	Pass

Table 12: Test result of 6dB Bandwidth (802.11n HT20)

Channel	Channel Frequency (MHz)	6dB Bandwidth (MHz)	Limit (MHz)	Result
Low Channel	2412	17.35	0.5	Pass
Mid Channel	2437	17.57	0.5	Pass
High Channel	2462	17.43	0.5	Pass

Table 13: Test result of 6dB Bandwidth (802.11n HT40)

Channel	Channel Frequency (MHz)	6dB Bandwidth (MHz)	Limit (MHz)	Result
Low Channel	2422	35.19	0.5	Pass
Mid Channel	2437	35.35	0.5	Pass
High Channel	2452	35.35	0.5	Pass

Table 14: Test result of 99% Bandwidth (802.11b)

Channel	Channel Frequency (MHz)	99% Bandwidth (MHz)
Low Channel	2412	14.933
Mid Channel	2437	14.973
High Channel	2462	15.012

Table 15: Test result of 99% Bandwidth (802.11g)

Channel	Channel Frequency (MHz)	99% Bandwidth (MHz)
Low Channel	2412	16.452
Mid Channel	2437	16.457
High Channel	2462	16.555

Table 16: Test result of 99% Bandwidth (802.11n HT20)


Channel	Channel Frequency (MHz)	99% Bandwidth (MHz)
Low Channel	2412	17.62
Mid Channel	2437	17.639
High Channel	2462	17.632

Table 17: Test result of 99% Bandwidth (802.11n HT40)


Channel	Channel Frequency (MHz)	99% Bandwidth (MHz)
Low Channel	2422	35.748
Mid Channel	2437	35.829
High Channel	2452	35.85

Test Plot of 6dB Bandwidth (802.11b)


Low Channel



Middle Channel




High Channel




Test Plot of 6dB Bandwidth (802.11g)


Low Channel



Middle Channel




High Channel




Test Plot of 6dB Bandwidth (802.11n HT20)


Low Channel



Middle Channel




High Channel




Test Plot of 6dB Bandwidth (802.11n HT40)


Low Channel



Middle Channel



High Channel



5.1.4 Power Density

RESULT:
Passed

Test standard : LP0002(2016): 3.10.1.6 (2) (B)
 FCC Part 15.247(e) , RSS-247 5.2(2)
 Basic standard : ANSI C63.10:2013, KDB558074
 Kind of test site : Shielded room

Test setup

Test Channel : Low/ Middle/ High
 Operation Mode : A
 Ambient temperature : 22-26°C
 Relative humidity : 50-65%
 Atmospheric pressure : 100-103 kPa

Table 18: Test result of Power Density (802.11b)

Channel	Channel Frequency (MHz)	Power Density	Limit
		(dBm)	(dBm)
Low Channel	2412	3.35	8
Middle Channel	2437	4.02	8
High Channel	2462	4.79	8

Table 19: Test result of Power Density (802.11g)

Channel	Channel Frequency (MHz)	Power Density	Limit
		(dBm)	(dBm)
Low Channel	2412	-2.41	8
Middle Channel	2437	-1.85	8
High Channel	2462	-0.918	8

Table 20: Test result of Power Density (802.11n HT20)

Channel	Channel Frequency (MHz)	Power Density	Limit
		(dBm)	(dBm)
Low Channel	2412	-2.37	8
Middle Channel	2437	-1.92	8
High Channel	2462	-1	8

Table 21: Test result of Power Density (802.11n HT40)

Channel	Channel Frequency (MHz)	Power Density	Limit
		(dBm)	(dBm)
Low Channel	2422	-4.77	8
Middle Channel	2437	-4.63	8
High Channel	2452	-4.16	8

Test Plot of Power Density (802.11b)

Low Channel



Middle Channel




High Channel



Test Plot of Power Density (802.11g)

Low Channel



Middle Channel




High Channel




Test Plot of Power Density (802.11n HT20)


Low Channel



Middle Channel



High Channel



Test Plot of Power Density (802.11n HT40)

Low Channel



Middle Channel



High Channel



5.1.5 Conducted spurious emissions and Frequency Band Edge measured in 100kHz Bandwidth

RESULT:**Passed**

Test standard	:	LP0002(2016): 3.10.1.5 FCC part 15.247(d), RSS-247 5.5
Basic standard	:	ANSI C63.10:2013, KDB558074
Limit	:	20dB (below that in the 100kHz bandwidth within the band that contains the highest level of the desired power)
Kind of test site	:	Shielded room

Test setup

Test Channel	:	Low/ High
Operation mode	:	A
Ambient temperature	:	22-26°C
Relative humidity	:	50-65%
Atmospheric pressure	:	100-103 kPa

All emissions are more than 20dB below fundamental, details refer to following test plot, and compliance is achieved as well.

Due to the small size of the product and that there are no inductive components of significant size, 9kHz to 30MHz frequency range is not tested based on technical judgment.

Test Plot 100kHz Conducted Emissions (802.11b)

Low Channel



Middle Channel



High Channel



Test Plot 100kHz Conducted Emissions (802.11g)

Low Channel





Test Plot 100kHz Conducted Emissions (802.11n HT20)

Low Channel



Middle Channel



High Channel



Test Plot 100kHz Conducted Emissions (802.11n HT40)


Low Channel






Test Plot 100kHz RBW of Band Edge (802.11b)

Low Channel



High Channel



Test Plot 100kHz RBW of Band Edge (802.11g)

Low Channel




High Channel



Test Plot 100kHz RBW of Band Edge (802.11n HT20)

Low Channel




High Channel




Test Plot 100kHz RBW of Band Edge (802.11n HT40)

Low Channel



High Channel



5.1.6 Spurious Emission

RESULT:

Passed

Test standard	:	FCC part 15.247(d), FCC 15.205, FCC 15.209, RSS-210 2.2, RSS-247 5.5 and RSS-Gen 8.9 LP0002(2016): 3.10.1.5
Basic standard	:	ANSI C63.10:2013
Limits	:	Radiated emissions which fall in the restricted bands, as defined in FCC 15.205(a) and RSS-Gen i4, 8.9 (Table 6), must comply with the radiated emission limits specified in FCC 15.209(a) and RSS-Gen i4, 8.9 (Table 4 and 5). Radiated emissions which fall in the restricted bands, as defined in LP0002(2016): 2.7 , must comply with the radiated emission limits specified in LP0002(2016): 2.8 Emission radiated outside the specified frequency bands must comply with the radiated emission limits specified in FCC 15.209(a) and FCC 15.249(a), RSS-Gen i4, 8.9 (Table 4 and 5) and RSS-210 A2.9(a). Emission radiated outside the specified frequency bands must comply with the radiated emission limits specified in LP0002(2016): 2.8
Kind of test site	:	3m Semi-Anechoic Chamber

Test setup

Test Channel	:	Low/ Middle/ High
Operation mode	:	A, B

Remark: Testing was carried out within frequency range 30MHz to the tenth harmonic.

For details refer to Appendix D.

The Radiated Emissions testing was performed in the X, Y and Z axis orientation. The X Axis orientation is the worst-case and recorded in this test report. Due to the small size of the product and that there are no inductive components of significant size, 9kHz to 30MHz frequency range is not tested based on technical judgment.

5.2 Mains Emissions

5.2.1 Mains Conducted Emissions

RESULT:**Passed**

Test standard	:	FCC Part 15.207 FCC Part 15.107 RSS-Gen 8.8 LP0002(2016): 2.3
Limits	:	Mains Conducted emissions as defined in above standards
Kind of test site	:	Shielded Room

Test setup

Test Channel	:	Middle
Operation mode	:	A

Remark: For details refer to Appendix D.

6. Safety Human exposure

6.1 Radio Frequency Exposure Compliance

6.1.1 Electromagnetic Fields

RESULT:
Passed

Test standard : FCC KDB Publication 447498 D01 v06
 FCC 47 CFR Part 2: Subpart J Section 2.1091

Separation distance is more than 20 cm, thus mobile device exposure limits can be applied.

Maximum Exposure:

Power to Antenna (mW)	108.3927 mW
Power to Antenna (dBm)	20.4 dBm
Antenna Gain	2.01 dBi
Power+Ant Gain	172.2 mW
Distance	20 cm
S=	0.034 mW/cm ²

Limit FCC:

0.3-1.34 MHz (100) mW/cm²
 1.34-30 MHz (180/f²) mW/cm²
 30-300 MHz 0.2 mW/cm²
 300-1500 MHz f/1500 mW/cm²
1500-100,000 MHz 1.0 mW/cm²


---End---

Photographs of the Test Set-Up


Photograph 1: Set-up for Spurious Emissions (Front View)




Photograph 2: Set-up for Spurious Emissions (Back View 1)



Photograph 3: Set-up for Spurious Emissions (Back View 2)




Photograph 4: Set-up for Spurious Emissions (Back View 3)



Photograph 5: Set-up for Conducted testing



Photograph 6: Set-up for Mains Conducted testing (Back View)



Photograph 7: Set-up for Mains Conducted testing (Front View)



7. List of Tables

Table 1: Applied Standard and Test Levels	5
Table 2: List of Test and Measurement Equipment	7
Table 3: Emission Measurement Uncertainty.....	8
Table 4: Basic Information of EUT	9
Table 5: Technical Specification of EUT	9
Table 6: Test result of Peak Output Power (802.11b)	15
Table 7: Test result of Peak Output Power (802.11g)	15
Table 8: Test result of Peak Output Power (802.11n HT20)	16
Table 9: Test result of Peak Output Power (802.11n HT40)	16
Table 10: Test result of 6dB Bandwidth (802.11b)	18
Table 11: Test result of 6dB Bandwidth (802.11g)	18
Table 12: Test result of 6dB Bandwidth (802.11n HT20)	18
Table 13: Test result of 6dB Bandwidth (802.11n HT40)	18
Table 14: Test result of 99% Bandwidth (802.11b)	19
Table 15: Test result of 99% Bandwidth (802.11g)	19
Table 16: Test result of 99% Bandwidth (802.11n HT20)	19
Table 17: Test result of 99% Bandwidth (802.11n HT40)	19
Table 18: Test result of Power Density (802.11b)	26
Table 19: Test result of Power Density (802.11g)	26
Table 20: Test result of Power Density (802.11n HT20)	26
Table 21: Test result of Power Density (802.11n HT40)	27

8. List of Photographs

Photograph 1: Set-up for Spurious Emissions (Front View).....	48
Photograph 2: Set-up for Spurious Emissions (Back View 1)	48
Photograph 3: Set-up for Spurious Emissions (Back View 2)	49
Photograph 4: Set-up for Spurious Emissions (Back View 3)	49
Photograph 5: Set-up for Conducted testing	50
Photograph 6: Set-up for Mains Conducted testing (Back View)	50
Photograph 7: Set-up for Mains Conducted testing (Front View).....	51