

FCC 1.1307 (B) & §2.1091- MPE-BASED EXEMPTION

Applicable Standard

According to subpart 2.1091 systems operating under the provisions of this section shall be operated in a manner that ensures the public is not exposed to RF energy level in excess of the communication guidelines.

According to KDB 447498 D04 Interim General RF Exposure Guidance

MPE-Based Exemption:

General frequency and separation-distance dependent MPE-based effective radiated power (ERP) thresholds are in Table B.1 [Table 1 of § 1.1307(b)(1)(i)(C)] to support an exemption from further evaluation from 300 kHz through 100 GHz.

Table 1 to § 1.1307(b)(3)(i)(C) - Single RF Sources Subject to Routine Environmental Evaluation

RF Source frequency (MHz)	Threshold ERP (watts)
0.3-1.34	$1,920 R^2$.
1.34-30	$3,450 R^2/f^2$.
30-300	$3.83 R^2$.
300-1,500	$0.0128 R^2 f$.
1,500-100,000	$19.2 R^2$.

R is the minimum separation distance in meters

f = frequency in MHz

For multiple RF sources: Multiple RF sources are exempt if:

in the case of fixed RF sources operating in the same time-averaging period, or of multiple mobile or portable RF sources within a device operating in the same time averaging period, if the sum of the fractional contributions to the applicable thresholds is less than or equal to 1 as indicated in the following equation:

$$\sum_{i=1}^a \frac{P_i}{P_{th,i}} + \sum_{j=1}^b \frac{ERP_j}{ERP_{th,j}} + \sum_{k=1}^c \frac{Evaluated_k}{Exposure Limit_k} \leq 1$$

Result**For worst case:**

For Module YL43752:

Mode	Frequency (MHz)	Tune up conducted power [#]	Antenna Gain [#]		ERP		Evaluation Distance (m)	ERP Limit (mW)
		(dBm)	(dBi)	(dBd)	(dBm)	(mW)		
BT	2402-2480	8.5	3.08	0.93	9.43	8.77	0.2	768
BLE	2402-2480	8.0	3.08	0.93	8.93	7.82	0.2	768
2.4G Wi-Fi	2412-2462	18.5	3.08	0.93	19.43	87.70	0.2	768
5G Wi-Fi	5180-5240	12.0	4.17	2.02	14.02	25.23	0.2	768
	5260-5280	13.0	4.17	2.02	15.02	31.77	0.2	768
	5500-5700	12.0	4.17	2.02	14.02	25.23	0.2	768
	5745-5825	14.5	4.17	2.02	16.52	44.87	0.2	768

For Module YL43456:

Mode	Frequency (MHz)	Maximum power [#]	Antenna Gain [#]		ERP		Evaluation Distance (m)	ERP Limit (mW)
		(dBm)	(dBi)	(dBd)	(dBm)	(mW)		
2.4G Wi-Fi	2412-2462	20.71	3.22	1.07	21.78	150.66	0.2	768
5G Wi-Fi	5150-5850	16.28	4.17	2.02	18.30	67.61	0.2	768

Note 1: The tune-up power was refer the module report

Note 2: The antenna gain was declared by the applicant.

Note 3: 0dBd=2.15dBi.

Simultaneous transmitting consideration:

According to applicant, the BT can transmit at the same time with the Wi-Fi, the 2.4G Wi-Fi and 5G Wi-Fi cannot transmit at same time, the two Wi-Fi module cannot transmit as same time.

For worst case:

The ratio= $ERP_{BT}/limit + ERP_{Wi-Fi}/limit = 8.77/768 + 87.70/768 = 0.126 < 1.0$

To maintain compliance with the FCC's RF exposure guidelines, place the equipment at least 20cm from nearby persons.

Result: Compliant